

# Foundation of Cryptography, Lecture 6

## Interactive Proofs and Zero Knowledge

Iftach Haitner, Tel Aviv University

Tel Aviv University.

April 23, 2014

# Part I

## Interactive Proofs

# $\mathcal{NP}$ as a Non-interactive Proofs

## Definition 1 ( $\mathcal{NP}$ )

$\mathcal{L} \in \mathcal{NP}$  iff  $\exists$  and poly-time algorithm  $V$  such that:

- $\forall x \in \mathcal{L} \cap \{0, 1\}^n$  there exists  $w \in \{0, 1\}^*$  s.t.  $V(x, w) = 1$
- $V(x, w) = 0$  for every  $x \notin \mathcal{L}$  and  $w \in \{0, 1\}^*$

Only  $|x|$  counts for the running time of  $V$ .

# $\mathcal{NP}$ as a Non-interactive Proofs

## Definition 1 ( $\mathcal{NP}$ )

$\mathcal{L} \in \mathcal{NP}$  iff  $\exists$  and poly-time algorithm  $V$  such that:

- $\forall x \in \mathcal{L} \cap \{0, 1\}^n$  there exists  $w \in \{0, 1\}^*$  s.t.  $V(x, w) = 1$
- $V(x, w) = 0$  for every  $x \notin \mathcal{L}$  and  $w \in \{0, 1\}^*$

Only  $|x|$  counts for the running time of  $V$ .

A proof system

# $\mathcal{NP}$ as a Non-interactive Proofs

## Definition 1 ( $\mathcal{NP}$ )

$\mathcal{L} \in \mathcal{NP}$  iff  $\exists$  and poly-time algorithm  $V$  such that:

- $\forall x \in \mathcal{L} \cap \{0, 1\}^n$  there exists  $w \in \{0, 1\}^*$  s.t.  $V(x, w) = 1$
- $V(x, w) = 0$  for every  $x \notin \mathcal{L}$  and  $w \in \{0, 1\}^*$

Only  $|x|$  counts for the running time of  $V$ .

A proof system

- Efficient verifier, efficient prover (given the witness)

# $\mathcal{NP}$ as a Non-interactive Proofs

## Definition 1 ( $\mathcal{NP}$ )

$\mathcal{L} \in \mathcal{NP}$  iff  $\exists$  and poly-time algorithm  $V$  such that:

- $\forall x \in \mathcal{L} \cap \{0, 1\}^n$  there exists  $w \in \{0, 1\}^*$  s.t.  $V(x, w) = 1$
- $V(x, w) = 0$  for every  $x \notin \mathcal{L}$  and  $w \in \{0, 1\}^*$

Only  $|x|$  counts for the running time of  $V$ .

A proof system

- Efficient verifier, efficient prover (given the witness)
- Soundness holds unconditionally

## Interactive proofs

Protocols between **efficient** verifier and **unbounded** provers.

## Interactive proofs

Protocols between **efficient** verifier and **unbounded** provers.

### Definition 2 (Interactive proof)

A protocol  $(P, V)$  is an **interactive proof** for  $\mathcal{L}$ , if  $V$  is PPT and:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = 1] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and **any** algorithm  $P^*$   $\Pr[\langle (P^*, V)(x) \rangle = 1] \leq 1/3$

$\mathbf{IP}$  is the class of languages that have interactive proofs.



## Interactive proofs

Protocols between **efficient** verifier and **unbounded** provers.

### Definition 2 (Interactive proof)

A protocol  $(P, V)$  is an **interactive proof** for  $\mathcal{L}$ , if  $V$  is PPT and:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = 1] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and **any** algorithm  $P^*$   $\Pr[\langle (P^*, V)(x) \rangle = 1] \leq 1/3$

$\mathbf{IP}$  is the class of languages that have interactive proofs.

- $\mathbf{IP} = \mathbf{PSPACE}$ !

## Interactive proofs

Protocols between **efficient** verifier and **unbounded** provers.

### Definition 2 (Interactive proof)

A protocol  $(P, V)$  is an **interactive proof** for  $\mathcal{L}$ , if  $V$  is PPT and:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = 1] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and **any** algorithm  $P^*$   $\Pr[\langle (P^*, V)(x) \rangle = 1] \leq 1/3$

$\mathbf{IP}$  is the class of languages that have interactive proofs.

- $\mathbf{IP} = \mathbf{PSPACE}$ !
- We typically consider (and achieve) perfect completeness.

## Interactive proofs

Protocols between **efficient** verifier and **unbounded** provers.

### Definition 2 (Interactive proof)

A protocol  $(P, V)$  is an **interactive proof** for  $\mathcal{L}$ , if  $V$  is PPT and:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = 1] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and **any** algorithm  $P^*$   $\Pr[\langle (P^*, V)(x) \rangle = 1] \leq 1/3$

$\mathbf{IP}$  is the class of languages that have interactive proofs.

- $\mathbf{IP} = \mathbf{PSPACE}$ !
- We typically consider (and achieve) perfect completeness.
- Negligible “soundness error” achieved via repetition.

# Interactive proofs

Protocols between **efficient** verifier and **unbounded** provers.

## Definition 2 (Interactive proof)

A protocol  $(P, V)$  is an **interactive proof** for  $\mathcal{L}$ , if  $V$  is PPT and:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = 1] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and **any** algorithm  $P^* \Pr[\langle (P^*, V)(x) \rangle = 1] \leq 1/3$

$\mathbf{IP}$  is the class of languages that have interactive proofs.

- $\mathbf{IP} = \mathbf{PSPACE}$ !
- We typically consider (and achieve) perfect completeness.
- Negligible “soundness error” achieved via repetition.
- Sometime we have efficient provers via “auxiliary input”.

# Interactive proofs

Protocols between **efficient** verifier and **unbounded** provers.

## Definition 2 (Interactive proof)

A protocol  $(P, V)$  is an **interactive proof** for  $\mathcal{L}$ , if  $V$  is PPT and:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = 1] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and **any** algorithm  $P^*$   $\Pr[\langle (P^*, V)(x) \rangle = 1] \leq 1/3$

$\mathbf{IP}$  is the class of languages that have interactive proofs.

- $\mathbf{IP} = \mathbf{PSPACE}$ !
- We typically consider (and achieve) perfect completeness.
- Negligible “soundness error” achieved via repetition.
- Sometime we have efficient provers via “auxiliary input”.
- Relaxation: *Computationally sound proofs* [also known as, *interactive arguments*]: soundness only guaranteed against **efficient** (PPT) provers.

# Section 1

## **Interactive Proof for Graph Non-Isomorphism**

# Graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

## Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are **isomorphic**, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that  $(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

# Graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

## Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are **isomorphic**, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that  $(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

- We assume a reasonable mapping from graphs to strings



# Graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

## Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are **isomorphic**, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that  $(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

- We assume a reasonable mapping from graphs to strings
- graph isomorphism is an equivalence class.

# Graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

## Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are **isomorphic**, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that  $(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

- We assume a reasonable mapping from graphs to strings
- graph isomorphism is an equivalence class.
- $\mathcal{GI} = \{(G_0, G_1) : G_0 \equiv G_1\} \in \mathcal{NP}$

# Graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

## Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are **isomorphic**, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that  $(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

- We assume a reasonable mapping from graphs to strings
- graph isomorphism is an equivalence class.
- $\mathcal{GI} = \{(G_0, G_1) : G_0 \equiv G_1\} \in \mathcal{NP}$
- Does  $\mathcal{GINI} = \{(G_0, G_1) : G_0 \not\equiv G_1\} \in \mathcal{NP}$ ?

# Graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

## Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are **isomorphic**, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that  $(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

- We assume a reasonable mapping from graphs to strings
- graph isomorphism is an equivalence class.
- $\mathcal{GI} = \{(G_0, G_1) : G_0 \equiv G_1\} \in \mathcal{NP}$
- Does  $\mathcal{GINI} = \{(G_0, G_1) : G_0 \not\equiv G_1\} \in \mathcal{NP}$ ?
- We will show a simple interactive proof for  $\mathcal{GINI}$

# Graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

## Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are **isomorphic**, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that  $(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

- We assume a reasonable mapping from graphs to strings
- graph isomorphism is an equivalence class.
- $\mathcal{GI} = \{(G_0, G_1) : G_0 \equiv G_1\} \in \mathcal{NP}$
- Does  $\mathcal{GINI} = \{(G_0, G_1) : G_0 \not\equiv G_1\} \in \mathcal{NP}$ ?
- We will show a simple interactive proof for  $\mathcal{GINI}$

# Graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

## Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are **isomorphic**, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that  $(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

- We assume a reasonable mapping from graphs to strings
- graph isomorphism is an equivalence class.
- $\mathcal{GI} = \{(G_0, G_1) : G_0 \equiv G_1\} \in \mathcal{NP}$
- Does  $\mathcal{GINI} = \{(G_0, G_1) : G_0 \not\equiv G_1\} \in \mathcal{NP}$ ?
- We will show a simple interactive proof for  $\mathcal{GINI}$   
Idea: Beer tasting...

# Interactive proof for $\mathcal{GNI}$

## Protocol 4 ((P, V))

**Common input**  $G_0 = ([m], E_0), G_1 = ([m], E_1)$

- 1 V chooses  $b \leftarrow \{0, 1\}$  and  $\pi \leftarrow \Pi_m$ , and sends  $\pi(E_b)$  to P.<sup>a</sup>
- 2 P send  $b'$  to V (tries to set  $b' = b$ ).
- 3 V accepts iff  $b' = b$ .

---

<sup>a</sup> $\pi(E) = \{(\pi(u), \pi(v)) : (u, v) \in E\}$ .

# Interactive proof for $\mathcal{GNI}$

## Protocol 4 $((P, V))$

**Common input**  $G_0 = ([m], E_0), G_1 = ([m], E_1)$

- 1  $V$  chooses  $b \leftarrow \{0, 1\}$  and  $\pi \leftarrow \Pi_m$ , and sends  $\pi(E_b)$  to  $P$ .<sup>a</sup>
- 2  $P$  send  $b'$  to  $V$  (tries to set  $b' = b$ ).
- 3  $V$  accepts iff  $b' = b$ .

---

$$^a \pi(E) = \{(\pi(u), \pi(v)) : (u, v) \in E\}.$$

## Claim 5

The above protocol is  $\text{IP}$  for  $\mathcal{GNI}$ , with perfect completeness and soundness error  $\frac{1}{2}$ .



## Proving Claim 5

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)

## Proving Claim 5

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)

## Proving Claim 5

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)
- $([m], \pi(E_i))$  is a random element in  $[G_i]$  — the equivalence class of  $G_i$

## Proving Claim 5

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)
- $([m], \pi(E_i))$  is a random element in  $[G_i]$  — the equivalence class of  $G_i$

## Proving Claim 5

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)
- $([m], \pi(E_i))$  is a random element in  $[G_i]$  — the equivalence class of  $G_i$

Hence,

$$G_0 \equiv G_1: \Pr[b' = b] \leq \frac{1}{2}.$$

## Proving Claim 5

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)
- $([m], \pi(E_i))$  is a random element in  $[G_i]$  — the equivalence class of  $G_i$

Hence,

$$G_0 \equiv G_1: \Pr[b' = b] \leq \frac{1}{2}.$$

$$G_0 \not\equiv G_1: \Pr[b' = b] = 1 \text{ (i.e., } P \text{ can, possibly inefficiently, extracted from } \pi(E_i))$$

□

# Part II

## Zero knowledge Proofs

# Where is Waldo?





# Where is Waldo?



## Question 6

Can you prove you know where Waldo is **without** revealing his location?

# The concept of zero knowledge

- Proving w/o revealing any additional information.

# The concept of zero knowledge

- Proving w/o revealing any additional information.
- What does it mean?

# The concept of zero knowledge

- Proving w/o revealing any additional information.
- What does it mean?

Simulation paradigm.

# Zero knowledge Proof

## Definition 7 (zero-knowledge proofs)

An interactive proof  $(P, V)$  is **computational zero-knowledge proof** ( $\mathcal{CZK}$ ) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{L}} \approx_c \{S(x)\}_{x \in \mathcal{L}}$ .

# Zero knowledge Proof

## Definition 7 (zero-knowledge proofs)

An interactive proof  $(P, V)$  is **computational zero-knowledge proof** ( $\mathcal{CZK}$ ) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{L}} \approx_c \{S(x)\}_{x \in \mathcal{L}}$ .

**Perfect  $\mathcal{ZK}$**  ( $\mathcal{PZK}$ )/**statistical  $\mathcal{ZK}$**  ( $\mathcal{SZK}$ ) — the above distributions are identically/statistically close.

# Zero knowledge Proof

## Definition 7 (zero-knowledge proofs)

An interactive proof  $(P, V)$  is **computational zero-knowledge proof** ( $\mathcal{CZK}$ ) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{L}} \approx_c \{S(x)\}_{x \in \mathcal{L}}$ .

**Perfect  $\mathcal{ZK}$  ( $\mathcal{PZK}$ )/statistical  $\mathcal{ZK}$  ( $\mathcal{SZK}$ )** — the above distributions are identically/statistically close.

- 1  $\mathcal{ZK}$  is a property of the **prover**.

# Zero knowledge Proof

## Definition 7 (zero-knowledge proofs)

An interactive proof  $(P, V)$  is **computational zero-knowledge proof** ( $\mathcal{CZK}$ ) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}$ .

**Perfect  $\mathcal{ZK}$**  ( $\mathcal{PZK}$ )/**statistical  $\mathcal{ZK}$**  ( $\mathcal{SZK}$ ) — the above distributions are identically/statistically close.

- 1  $\mathcal{ZK}$  is a property of the **prover**.
- 2  $\mathcal{ZK}$  only required to hold with respect to true statements.



# Zero knowledge Proof

## Definition 7 (zero-knowledge proofs)

An interactive proof  $(P, V)$  is **computational zero-knowledge proof** ( $\mathcal{CZK}$ ) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{L}} \approx_c \{S(x)\}_{x \in \mathcal{L}}$ .

**Perfect  $\mathcal{ZK}$**  ( $\mathcal{PZK}$ )/**statistical  $\mathcal{ZK}$**  ( $\mathcal{SZK}$ ) — the above distributions are identically/statistically close.

- 1  $\mathcal{ZK}$  is a property of the **prover**.
- 2  $\mathcal{ZK}$  only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".

# Zero knowledge Proof

## Definition 7 (zero-knowledge proofs)

An interactive proof  $(P, V)$  is **computational zero-knowledge proof** ( $\mathcal{CZK}$ ) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{L}} \approx_c \{S(x)\}_{x \in \mathcal{L}}$ .

**Perfect  $\mathcal{ZK}$  ( $\mathcal{PZK}$ )/statistical  $\mathcal{ZK}$  ( $\mathcal{SZK}$ )** — the above distributions are identically/statistically close.

- 1  $\mathcal{ZK}$  is a property of the **prover**.
- 2  $\mathcal{ZK}$  only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".
- 4 Trivial to achieve for  $\mathcal{L} \in \mathcal{BPP}$

# Zero knowledge Proof

## Definition 7 (zero-knowledge proofs)

An interactive proof  $(P, V)$  is **computational zero-knowledge proof** ( $\mathcal{CZK}$ ) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}$ .

**Perfect ZK** ( $\mathcal{PZK}$ )/**statistical ZK** ( $\mathcal{SZK}$ ) — the above distributions are identically/statistically close.

- 1  $\mathcal{ZK}$  is a property of the **prover**.
- 2  $\mathcal{ZK}$  only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".
- 4 Trivial to achieve for  $\mathcal{L} \in \mathcal{BPP}$
- 5 Extension: auxiliary input

# Zero knowledge Proof

## Definition 7 (zero-knowledge proofs)

An interactive proof  $(P, V)$  is **computational zero-knowledge proof** ( $\mathcal{CZK}$ ) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}$ .

**Perfect ZK** ( $\mathcal{PZK}$ )/**statistical ZK** ( $\mathcal{SZK}$ ) — the above distributions are identically/statistically close.

- 1  $\mathcal{ZK}$  is a property of the **prover**.
- 2  $\mathcal{ZK}$  only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".
- 4 Trivial to achieve for  $\mathcal{L} \in \mathcal{BPP}$
- 5 Extension: auxiliary input
- 6 The "standard"  $\mathcal{NP}$  proof is typically not zero knowledge

# Zero knowledge Proof

## Definition 7 (zero-knowledge proofs)

An interactive proof  $(P, V)$  is **computational zero-knowledge proof** ( $\mathcal{CZK}$ ) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}$ .

**Perfect ZK** ( $\mathcal{PZK}$ )/**statistical ZK** ( $\mathcal{SZK}$ ) — the above distributions are identically/statistically close.

- 1  $\mathcal{ZK}$  is a property of the **prover**.
- 2  $\mathcal{ZK}$  only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".
- 4 Trivial to achieve for  $\mathcal{L} \in \mathcal{BPP}$
- 5 Extension: auxiliary input
- 6 The "standard"  $\mathcal{NP}$  proof is typically not zero knowledge
- 7 Next class —  $\mathcal{ZK}$  for all  $\mathcal{NP}$

## Section 2

# Zero-Knowledge Proof for Graph Isomorphism

# $\mathcal{ZK}$ Proof for Graph Isomorphism

Idea: route finding

## ZK Proof for Graph Isomorphism

Idea: route finding

### Protocol 8 ((P, V))

Common input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

P's input: a permutation  $\pi$  over  $[m]$  such that  $\pi(E_1) = E_0$ .

- 1 P chooses  $\pi' \leftarrow \Pi_m$  and sends  $E = \pi'(E_0)$  to V.
- 2 V sends  $b \leftarrow \{0, 1\}$  to P.
- 3 If  $b = 0$ , P sets  $\pi'' = \pi'$ , otherwise, it sends  $\pi'' = \pi' \circ \pi$  to V.
- 4 V accepts iff  $\pi''(E_b) = E$ .



# $\mathcal{ZK}$ Proof for Graph Isomorphism

Idea: route finding

## Protocol 8 ((P, V))

Common input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

P's input: a permutation  $\pi$  over  $[m]$  such that  $\pi(E_1) = E_0$ .

- 1 P chooses  $\pi' \leftarrow \Pi_m$  and sends  $E = \pi'(E_0)$  to V.
- 2 V sends  $b \leftarrow \{0, 1\}$  to P.
- 3 If  $b = 0$ , P sets  $\pi'' = \pi'$ , otherwise, it sends  $\pi'' = \pi' \circ \pi$  to V.
- 4 V accepts iff  $\pi''(E_b) = E$ .

## Claim 9

Protocol 8 is a  $\mathcal{SZK}$  for  $\mathcal{GI}$ , with perfect completeness and soundness  $\frac{1}{2}$ .

## Proving Claim 9

- Completeness: Clear

## Proving Claim 9

- Completeness: Clear
- Soundness: If exist  $j \in \{0, 1\}$  for which  $\nexists \pi' \in \Pi_m$  with  $\pi'(E_j) = E$ , then  $V$  rejects w.p. at least  $\frac{1}{2}$ .

Assuming  $V$  rejects w.p. less than  $\frac{1}{2}$  and let  $\pi_0$  and  $\pi_1$  be the values guaranteed by the above observation (i.e., mapping  $E_0$  and  $E_1$  to  $E$  respectively).

Then  $\pi_0^{-1}(\pi_1(E_1)) = \pi_0 \implies (G_0, G_1) \in \mathcal{GI}$ .

## Proving Claim 9

- Completeness: Clear
- Soundness: If exist  $j \in \{0, 1\}$  for which  $\nexists \pi' \in \Pi_m$  with  $\pi'(E_j) = E$ , then  $V$  rejects w.p. at least  $\frac{1}{2}$ .

Assuming  $V$  rejects w.p. less than  $\frac{1}{2}$  and let  $\pi_0$  and  $\pi_1$  be the values guaranteed by the above observation (i.e., mapping  $E_0$  and  $E_1$  to  $E$  respectively).

Then  $\pi_0^{-1}(\pi_1(E_1)) = \pi_0 \implies (G_0, G_1) \in \mathcal{GI}$ .

- $\mathcal{ZK}$ : Idea – for  $(G_0, G_1) \in \mathcal{GI}$ , it is easy to generate a random transcript for Steps 1-2, and to be able to open it with prob  $\frac{1}{2}$ .

## The simulator

For a start consider a deterministic cheating verifier  $V^*$  that never aborts.

## The simulator

For a start consider a deterministic cheating verifier  $V^*$  that never aborts.

### Algorithm 10 (S)

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

Do  $|x|$  times:

- 1 Choose  $b' \leftarrow \{0, 1\}$  and  $\pi \leftarrow \Pi_m$ , and “send”  $\pi(E_{b'})$  to  $V^*(x)$ .
- 2 Let  $b$  be  $V^*$ ’s answer. If  $b = b'$ , send  $\pi$  to  $V^*$ , output  $V^*$ ’s output and halt. Otherwise, **rewind**  $V^*$  to its initial step, and go to step 1.

Abort.

## The simulator

For a start consider a deterministic cheating verifier  $V^*$  that never aborts.

### Algorithm 10 (S)

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

Do  $|x|$  times:

- 1 Choose  $b' \leftarrow \{0, 1\}$  and  $\pi \leftarrow \Pi_m$ , and “send”  $\pi(E_{b'})$  to  $V^*(x)$ .
- 2 Let  $b$  be  $V^*$ ’s answer. If  $b = b'$ , send  $\pi$  to  $V^*$ , output  $V^*$ ’s output and halt. Otherwise, **rewind**  $V^*$  to its initial step, and go to step 1.

Abort.

### Claim 11

$$\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{GI}} \approx \{S(x)\}_{x \in \mathcal{GI}}$$

where  $\langle (P, V^*)(x) \rangle$  describes the parties’ join output in a random execution of  $(P, V^*)$  on input  $x$ .

## The simulator

For a start consider a deterministic cheating verifier  $V^*$  that never aborts.

### Algorithm 10 (S)

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

Do  $|x|$  times:

- 1 Choose  $b' \leftarrow \{0, 1\}$  and  $\pi \leftarrow \Pi_m$ , and “send”  $\pi(E_{b'})$  to  $V^*(x)$ .
- 2 Let  $b$  be  $V^*$ ’s answer. If  $b = b'$ , send  $\pi$  to  $V^*$ , output  $V^*$ ’s output and halt. Otherwise, **rewind**  $V^*$  to its initial step, and go to step 1.

Abort.

### Claim 11

$$\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{GI}} \approx \{S(x)\}_{x \in \mathcal{GI}}$$

where  $\langle (P, V^*)(x) \rangle$  describes the parties’ join output in a random execution of  $(P, V^*)$  on input  $x$ .

**Claim 11** implies that **Protocol 8** is zero knowledge. (?)



## Proving Claim 11

Consider the following inefficient simulator:

### Algorithm 12 ( $S'$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$ .

Do  $|x|$  times:

1 Choose  $\pi \leftarrow \Pi_m$  and send  $E = \pi(E_0)$  to  $V^*(x)$ .

2 Let  $b$  be  $V^*$ 's answer.

W.p.  $\frac{1}{2}$ ,

1 Find  $\pi'$  such that  $E = \pi'(E_b)$ , and send it to  $V^*$ .

2 Output  $V^*$ 's output and halt.

Otherwise, rewind  $V^*$  to its initial step, and go to step 1.

Abort.

## Proving Claim 11

Consider the following inefficient simulator:

### Algorithm 12 ( $S'$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$ .

Do  $|x|$  times:

1 Choose  $\pi \leftarrow \Pi_m$  and send  $E = \pi(E_0)$  to  $V^*(x)$ .

2 Let  $b$  be  $V^*$ 's answer.

W.p.  $\frac{1}{2}$ ,

1 Find  $\pi'$  such that  $E = \pi'(E_b)$ , and send it to  $V^*$ .

2 Output  $V^*$ 's output and halt.

Otherwise, rewind  $V^*$  to its initial step, and go to step 1.

Abort.

### Claim 13

$S(x) \equiv S'(x)$  for any  $x \in \mathcal{GI}$ .

## Proving Claim 11

Consider the following **inefficient** simulator:

### Algorithm 12 ( $S'$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$ .

Do  $|x|$  times:

1 Choose  $\pi \leftarrow \Pi_m$  and send  $E = \pi(E_0)$  to  $V^*(x)$ .

2 Let  $b$  be  $V^*$ 's answer.

W.p.  $\frac{1}{2}$ ,

1 Find  $\pi'$  such that  $E = \pi'(E_b)$ , and send it to  $V^*$ .

2 Output  $V^*$ 's output and halt.

Otherwise, **rewind**  $V^*$  to its initial step, and go to step 1.

Abort.

## Claim 13

$S(x) \equiv S'(x)$  for any  $x \in \mathcal{GI}$ .

Proof: ?

## Proving Claim 11 cont.

Consider a second inefficient simulator:

### Algorithm 14 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and send  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$  and send it to  $V^*$
- 3 Output  $V^*$ 's output and halt.

## Proving Claim 11 cont.

Consider a second inefficient simulator:

### Algorithm 14 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and send  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$  and send it to  $V^*$
- 3 Output  $V^*$ 's output and halt.

### Claim 15

$\forall x \in \mathcal{GI}$  it holds that

- 1  $\langle (P, V^*(x)) \rangle \equiv S''(x)$ .

## Proving Claim 11 cont.

Consider a second inefficient simulator:

### Algorithm 14 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and send  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$  and send it to  $V^*$
- 3 Output  $V^*$ 's output and halt.

### Claim 15

$\forall x \in \mathcal{GI}$  it holds that

- 1  $\langle (P, V^*(x)) \rangle \equiv S''(x)$ .
- 2  $SD(S''(x), S'(x)) \leq 2^{-|x|}$ .

## Proving Claim 11 cont.

Consider a second inefficient simulator:

### Algorithm 14 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and send  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$  and send it to  $V^*$
- 3 Output  $V^*$ 's output and halt.

### Claim 15

$\forall x \in \mathcal{GI}$  it holds that

- 1  $\langle (P, V^*(x)) \rangle \equiv S''(x)$ .
- 2  $SD(S''(x), S'(x)) \leq 2^{-|x|}$ .

## Proving Claim 11 cont.

Consider a second inefficient simulator:

### Algorithm 14 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and send  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$  and send it to  $V^*$
- 3 Output  $V^*$ 's output and halt.

### Claim 15

$\forall x \in \mathcal{GI}$  it holds that

- 1  $\langle (P, V^*(x)) \rangle \equiv S''(x)$ .
- 2  $SD(S''(x), S'(x)) \leq 2^{-|x|}$ .

Proof: ?



## Proving Claim 11 cont.

Consider a second inefficient simulator:

### Algorithm 14 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and send  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$  and send it to  $V^*$
- 3 Output  $V^*$ 's output and halt.

### Claim 15

$\forall x \in \mathcal{GI}$  it holds that

- 1  $\langle (P, V^*(x)) \rangle \equiv S''(x)$ .
- 2  $SD(S''(x), S'(x)) \leq 2^{-|x|}$ .

Proof: ? (1) is clear.

## Proving Claim 15(2)

Fix  $(E, \pi')$  and let  $\alpha = \Pr_{S''(x)}[(E, \pi')]$ .

## Proving Claim 15(2)

Fix  $(E, \pi')$  and let  $\alpha = \Pr_{S''(x)}[(E, \pi')]$ .

It holds that

$$\begin{aligned}\Pr_{S'(x)}[(E, \pi')] &= \alpha \cdot \sum_{i=1}^{|x|} \left(1 - \frac{1}{2}\right)^{i-1} \cdot \frac{1}{2} \\ &= (1 - 2^{-|x|}) \cdot \alpha\end{aligned}$$

## Proving Claim 15(2)

Fix  $(E, \pi')$  and let  $\alpha = \Pr_{S''(x)}[(E, \pi')]$ .

It holds that

$$\begin{aligned}\Pr_{S'(x)}[(E, \pi')] &= \alpha \cdot \sum_{i=1}^{|x|} \left(1 - \frac{1}{2}\right)^{i-1} \cdot \frac{1}{2} \\ &= (1 - 2^{-|x|}) \cdot \alpha\end{aligned}$$

Hence,  $SD(S''(x), S'(x)) \leq 2^{-|x|} \square$

- 1 Randomized verifiers

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers
- 3 Auxiliary input

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers
- 3 Auxiliary input
- 4 Negligible soundness error?



## Remarks

- ➊ Randomized verifiers
- ➋ Aborting verifiers
- ➌ Auxiliary input
- ➍ Negligible soundness error?

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers
- 3 Auxiliary input
- 4 Negligible soundness error?

Sequential repetition

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers
- 3 Auxiliary input
- 4 Negligible soundness error?

Sequential repetition

Parallel repetition

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers
- 3 Auxiliary input
- 4 Negligible soundness error?
  - Sequential repetition
  - Parallel repetition
- 5 Perfect  $\mathcal{ZK}$  for “expected time simulators”

## Remarks

- ➊ Randomized verifiers
- ➋ Aborting verifiers
- ➌ Auxiliary input
- ➍ Negligible soundness error?
  - Sequential repetition
  - Parallel repetition
- ➎ Perfect  $\mathcal{ZK}$  for “expected time simulators”
- ➏ “Black box” simulation

# **“Transcript simulation” might not suffice!**

## “Transcript simulation” might not suffice!

Let  $(G, E, D)$  be a public-key encryption scheme and let  $\mathcal{L} \in \mathcal{NP}$ .

## “Transcript simulation” might not suffice!

Let  $(G, E, D)$  be a public-key encryption scheme and let  $\mathcal{L} \in \mathcal{NP}$ .

### Protocol 16 $((P, V))$

Common input:  $x \in \{0, 1\}^*$

$P$ 's input:  $w \in R_{\mathcal{L}}(x)$

- 1  $V$  chooses  $(d, e) \leftarrow G(1^{|x|})$  and sends  $e$  to  $P$
- 2  $P$  sends  $c = E_e(w)$  to  $V$
- 3  $V$  accepts iff  $D_d(c) \in R_{\mathcal{L}}(x)$



## “Transcript simulation” might not suffice!

Let  $(G, E, D)$  be a public-key encryption scheme and let  $\mathcal{L} \in \mathcal{NP}$ .

### Protocol 16 $((P, V))$

Common input:  $x \in \{0, 1\}^*$

$P$ 's input:  $w \in R_{\mathcal{L}}(x)$

- 1  $V$  chooses  $(d, e) \leftarrow G(1^{|x|})$  and sends  $e$  to  $P$
- 2  $P$  sends  $c = E_e(w)$  to  $V$
- 3  $V$  accepts iff  $D_d(c) \in R_{\mathcal{L}}(x)$

- The above protocol has perfect completeness and soundness.

## “Transcript simulation” might not suffice!

Let  $(G, E, D)$  be a public-key encryption scheme and let  $\mathcal{L} \in \mathcal{NP}$ .

### Protocol 16 $((P, V))$

Common input:  $x \in \{0, 1\}^*$

$P$ 's input:  $w \in R_{\mathcal{L}}(x)$

- 1  $V$  chooses  $(d, e) \leftarrow G(1^{|x|})$  and sends  $e$  to  $P$
- 2  $P$  sends  $c = E_e(w)$  to  $V$
- 3  $V$  accepts iff  $D_d(c) \in R_{\mathcal{L}}(x)$

- The above protocol has perfect completeness and soundness.
- Is it zero-knowledge?

## “Transcript simulation” might not suffice!

Let  $(G, E, D)$  be a public-key encryption scheme and let  $\mathcal{L} \in \mathcal{NP}$ .

### Protocol 16 $((P, V))$

Common input:  $x \in \{0, 1\}^*$

$P$ 's input:  $w \in R_{\mathcal{L}}(x)$

- ➊  $V$  chooses  $(d, e) \leftarrow G(1^{|x|})$  and sends  $e$  to  $P$
- ➋  $P$  sends  $c = E_e(w)$  to  $V$
- ➌  $V$  accepts iff  $D_d(c) \in R_{\mathcal{L}}(x)$

- The above protocol has perfect completeness and soundness.
- Is it zero-knowledge?
- It has “transcript simulator” (at least for honest verifiers): exists PPT  $S$  such that  $\{((P(w \in R_{\mathcal{L}}(x)), V)(x))\}_{x \in \mathcal{L}} \approx_c \{S(x)\}_{x \in \mathcal{L}}$ ,  
where *trans* stands for the transcript of the protocol (i.e., the messages exchange through the execution).

## Section 3

# Black-box Zero Knowledge

# Black-box simulators

## Definition 17 (Black-box simulator)

$(P, V)$  is  $\mathcal{CZK}$  with **black-box simulation** for  $\mathcal{L}$ , if  $\exists$  oracle-aided PPT  $S$  s.t.

$$\{(P(w_x), V^*(z_x))(x)\}_{x \in \mathcal{L}} \approx_c \{S^{V^*(x, z_x)}(x)\}_{x \in \mathcal{L}}$$

for any deterministic polynomial-time<sup>a</sup>  $V^*$  and  $\{(w_x, z_x) \in R_{\mathcal{L}}(x) \times \{0, 1\}^*\}_{x \in \mathcal{L}}$ .

Prefect and statistical variants are defined analogously.

---

<sup>a</sup>Length of auxiliary input does not count for the running time.

# Black-box simulators

## Definition 17 (Black-box simulator)

$(P, V)$  is  $\mathcal{CZK}$  with **black-box simulation** for  $\mathcal{L}$ , if  $\exists$  oracle-aided PPT  $S$  s.t.

$$\{(P(w_x), V^*(z_x))(x)\}_{x \in \mathcal{L}} \approx_c \{S^{V^*(x, z_x)}(x)\}_{x \in \mathcal{L}}$$

for any deterministic polynomial-time<sup>a</sup>  $V^*$  and  $\{(w_x, z_x) \in R_{\mathcal{L}}(x) \times \{0, 1\}^*\}_{x \in \mathcal{L}}$ .

Prefect and statistical variants are defined analogously.

---

<sup>a</sup>Length of auxiliary input does not count for the running time.

❶ What about randomized verifier?

# Black-box simulators

## Definition 17 (Black-box simulator)

$(P, V)$  is  $\mathcal{CZK}$  with **black-box simulation** for  $\mathcal{L}$ , if  $\exists$  oracle-aided PPT  $S$  s.t.

$$\{(P(w_x), V^*(z_x))(x)\}_{x \in \mathcal{L}} \approx_c \{S^{V^*(x, z_x)}(x)\}_{x \in \mathcal{L}}$$

for any deterministic polynomial-time<sup>a</sup>  $V^*$  and  $\{(w_x, z_x) \in R_{\mathcal{L}}(x) \times \{0, 1\}^*\}_{x \in \mathcal{L}}$ .

Prefect and statistical variants are defined analogously.

---

<sup>a</sup>Length of auxiliary input does not count for the running time.

- 1 What about randomized verifier?
- 2 "Most simulators" are black box

# Black-box simulators

## Definition 17 (Black-box simulator)

$(P, V)$  is  $\mathcal{CZK}$  with **black-box simulation** for  $\mathcal{L}$ , if  $\exists$  oracle-aided PPT  $S$  s.t.

$$\{(P(w_x), V^*(z_x))(x)\}_{x \in \mathcal{L}} \approx_c \{S^{V^*(x, z_x)}(x)\}_{x \in \mathcal{L}}$$

for any deterministic polynomial-time<sup>a</sup>  $V^*$  and  $\{(w_x, z_x) \in R_{\mathcal{L}}(x) \times \{0, 1\}^*\}_{x \in \mathcal{L}}$ .

Prefect and statistical variants are defined analogously.

---

<sup>a</sup>Length of auxiliary input does not count for the running time.

- 1 What about randomized verifier?
- 2 "Most simulators" are black box



# Black-box simulators

## Definition 17 (Black-box simulator)

$(P, V)$  is  $\mathcal{CZK}$  with **black-box simulation** for  $\mathcal{L}$ , if  $\exists$  oracle-aided PPT  $S$  s.t.

$$\{(P(w_x), V^*(z_x))(x)\}_{x \in \mathcal{L}} \approx_c \{S^{V^*(x, z_x)}(x)\}_{x \in \mathcal{L}}$$

for any deterministic polynomial-time<sup>a</sup>  $V^*$  and  $\{(w_x, z_x) \in R_{\mathcal{L}}(x) \times \{0, 1\}^*\}_{x \in \mathcal{L}}$ .

Prefect and statistical variants are defined analogously.

---

<sup>a</sup>Length of auxiliary input does not count for the running time.

- 1 What about randomized verifier?
- 2 "Most simulators" are black box
- 3 Strictly **weaker** than general simulation!

## Section 4

# Zero Knowledge for all NP

- Assuming that OWFs exists, we give a (black-box)  $\mathcal{CZK}$  for 3COL .

## $\mathcal{CZK}$ for 3COL

- Assuming that OWFs exists, we give a (black-box)  $\mathcal{CZK}$  for 3COL .
- We show how to transform it for any  $\mathcal{L} \in \mathcal{NP}$  (using that 3COL  $\in \mathcal{NPC}$ ).

## $\mathcal{CZK}$ for 3COL

- Assuming that OWFs exists, we give a (black-box)  $\mathcal{CZK}$  for 3COL .
- We show how to transform it for any  $\mathcal{L} \in \mathcal{NP}$  (using that 3COL  $\in \mathcal{NPC}$ ).

- Assuming that OWFs exists, we give a (black-box)  $\mathcal{CZK}$  for 3COL .
- We show how to transform it for any  $\mathcal{L} \in \mathcal{NP}$  (using that  $3\text{COL} \in \mathcal{NPC}$ ).

### Definition 18 (3COL)

$G = (M, E) \in 3\text{COL}$ , if  $\exists \phi: M \mapsto [3]$  s.t.  $\phi(u) \neq \phi(v)$  for every  $(u, v) \in E$ .

- Assuming that OWFs exists, we give a (black-box)  $\mathcal{CZK}$  for 3COL .
- We show how to transform it for any  $\mathcal{L} \in \mathcal{NP}$  (using that  $3\text{COL} \in \mathcal{NPC}$ ).

### Definition 18 (3COL)

$G = (M, E) \in 3\text{COL}$ , if  $\exists \phi: M \mapsto [3]$  s.t.  $\phi(u) \neq \phi(v)$  for every  $(u, v) \in E$ .

We use [commitment schemes](#).

## The protocol

Let  $\pi_3$  be the set of all permutations over  $[3]$ .



## The protocol

Let  $\pi_3$  be the set of all permutations over  $[3]$ . We use perfectly binding commitment  $\text{Com} = (\text{Snd}, \text{Rcv})$ .

## The protocol

Let  $\pi_3$  be the set of all permutations over [3]. We use perfectly binding commitment  $\text{Com} = (\text{Snd}, \text{Rcv})$ .

### Protocol 19 ((P, V))

Common input: Graph  $G = (M, E)$  with  $n = |G|$

P's input: a (valid) coloring  $\phi$  of  $G$

- 1 P chooses  $\pi \leftarrow \Pi_3$  and sets  $\psi = \pi \circ \phi$
- 2  $\forall v \in M$ : P commits to  $\psi(v)$  using  $\text{Com}$  (with security parameter  $1^n$ ).  
Let  $c_v$  and  $d_v$  be the resulting commitment and decommitment.
- 3 V sends  $e = (u, v) \leftarrow E$  to P
- 4 P sends  $(d_u, \psi(u)), (d_v, \psi(v))$  to V
- 5 V verifies that
  - 1 Both decommitments are valid,
  - 2  $\psi(u), \psi(v) \in [3]$ , and
  - 3  $\psi(u) \neq \psi(v)$ .

## Claim 20

The above protocol is a  $\mathcal{CZK}$  for  $3\text{COL}$ , with perfect completeness and soundness  $1/|E|$ .

## Claim 20

The above protocol is a  $\mathcal{CZK}$  for  $3\text{COL}$ , with perfect completeness and soundness  $1/|E|$ .

- Completeness: Clear

## Claim 20

The above protocol is a  $\mathcal{CZK}$  for  $3\text{COL}$ , with perfect completeness and soundness  $1/|E|$ .

- Completeness: Clear
- Soundness: Let  $\{c_v\}_{v \in M}$  be the commitments resulting from an interaction of  $V$  with an arbitrary  $P^*$ .

Define  $\phi: M \mapsto [3]$  as follows:

$\forall v \in M$ : let  $\phi(v)$  be the (single) value that it is possible to decommit  $c_v$  into (if not in  $[3]$ , set  $\phi(v) = 1$ ).

## Claim 20

The above protocol is a  $\mathcal{CZK}$  for  $3\text{COL}$ , with perfect completeness and soundness  $1/|E|$ .

- Completeness: Clear
- Soundness: Let  $\{c_v\}_{v \in M}$  be the commitments resulting from an interaction of  $V$  with an arbitrary  $P^*$ .

Define  $\phi: M \mapsto [3]$  as follows:

$\forall v \in M$ : let  $\phi(v)$  be the (single) value that it is possible to decommit  $c_v$  into (if not in  $[3]$ , set  $\phi(v) = 1$ ).

## Claim 20

The above protocol is a  $\mathcal{CZK}$  for  $3\text{COL}$ , with perfect completeness and soundness  $1/|E|$ .

- Completeness: Clear
- Soundness: Let  $\{c_v\}_{v \in M}$  be the commitments resulting from an interaction of  $V$  with an arbitrary  $P^*$ .

Define  $\phi: M \mapsto [3]$  as follows:

$\forall v \in M$ : let  $\phi(v)$  be the (single) value that it is possible to decommit  $c_v$  into (if not in  $[3]$ , set  $\phi(v) = 1$ ).

If  $G \notin 3\text{COL}$ , then  $\exists (u, v) \in E$  s.t.  $\phi(u) \neq \phi(v)$ .

## Claim 20

The above protocol is a  $\mathcal{CZK}$  for  $3\text{COL}$ , with perfect completeness and soundness  $1/|E|$ .

- Completeness: Clear
- Soundness: Let  $\{c_v\}_{v \in M}$  be the commitments resulting from an interaction of  $V$  with an arbitrary  $P^*$ .

Define  $\phi: M \mapsto [3]$  as follows:

$\forall v \in M$ : let  $\phi(v)$  be the (single) value that it is possible to decommit  $c_v$  into (if not in  $[3]$ , set  $\phi(v) = 1$ ).

If  $G \notin 3\text{COL}$ , then  $\exists (u, v) \in E$  s.t.  $\phi(u) \neq \phi(v)$ .

Hence  $V$  rejects such  $x$  w.p. at least  $1/|E|$



## Proving $\mathcal{ZK}$

Fix a deterministic, non-aborting  $V^*$  that gets no auxiliary input.

## Proving $\mathcal{ZK}$

Fix a deterministic, non-aborting  $V^*$  that gets no auxiliary input.

### Algorithm 21 (S)

Input: A graph  $G = (M, E)$  with  $n = |G|$

Do  $n \cdot |E|$  times:

- 1 Choose  $e' = (u, v) \leftarrow E$ .
  - 1 Set  $\psi(u) \leftarrow [3]$ ,
  - 2 Set  $\psi(v) \leftarrow [3] \setminus \{\psi(u)\}$ , and
  - 3 Set  $\psi(w) = 1$  for  $w \in M \setminus \{u, v\}$ .
- 2  $\forall v \in M$ : commit to  $\psi(v)$  to  $V^*$  (resulting in  $c_v$  and  $d_v$ )
- 3 Let  $e$  be the edge sent by  $V^*$ .

If  $e = e'$ , send  $(d_u, \psi(u)), (d_v, \psi(v))$  to  $V^*$ , output  $V^*$ 's output and halt.

Otherwise, **rewind**  $V^*$  to its initial step, and go to step 1.

Abort.

## Proving $\mathcal{ZK}$ cont.

### Claim 22

$\{(P(w_x), V^*)(x)\}_{x \in 3\text{COL}} \approx_c \{S^{V^*(x)}(x)\}_{x \in 3\text{COL}}$ , for any  $\{w_x \in R_{3\text{COL}}(x)\}_{x \in 3\text{COL}}$ .

Consider the following (inefficient simulator)

### Algorithm 23 ( $S'$ )

Input:  $G = (V, E)$  with  $n = |G|$

Find (using brute force) a valid coloring  $\phi$  of  $G$

Do for  $n \cdot |E|$  times:

- 1 Act like the honest prover does given private input  $\phi$ .
- 2 Let  $e$  be the edge sent by  $V^*$ . W.p.  $1/|E|$ ,
  - 1 Send  $(\psi(u), d_u), (\psi(v), d_v)$  to  $V^*$ ,
  - 2 Output  $V^*$ 's output and halt.

Otherwise, **rewind**  $V^*$  to its initial step, and go to step 1.

Abort.

Consider the following (inefficient simulator)

### Algorithm 23 ( $S'$ )

Input:  $G = (V, E)$  with  $n = |G|$

Find (using brute force) a valid coloring  $\phi$  of  $G$

Do for  $n \cdot |E|$  times:

- 1 Act like the honest prover does given private input  $\phi$ .
- 2 Let  $e$  be the edge sent by  $V^*$ . W.p.  $1/|E|$ ,
  - 1 Send  $(\psi(u), d_u), (\psi(v), d_v)$  to  $V^*$ ,
  - 2 Output  $V^*$ 's output and halt.

Otherwise, **rewind**  $V^*$  to its initial step, and go to step 1.

Abort.

### Claim 24

$$\{S^{V^*}(x)\}_{x \in 3\text{COL}} \approx_c \{S'^{V^*}(x)\}_{x \in 3\text{COL}}$$

Consider the following (inefficient simulator)

### Algorithm 23 ( $S'$ )

Input:  $G = (V, E)$  with  $n = |G|$

Find (using brute force) a valid coloring  $\phi$  of  $G$

Do for  $n \cdot |E|$  times:

- 1 Act like the honest prover does given private input  $\phi$ .
- 2 Let  $e$  be the edge sent by  $V^*$ . W.p.  $1/|E|$ ,
  - 1 Send  $(\psi(u), d_u), (\psi(v), d_v)$  to  $V^*$ ,
  - 2 Output  $V^*$ 's output and halt.

Otherwise, **rewind**  $V^*$  to its initial step, and go to step 1.

Abort.

### Claim 24

$$\{S^{V^*}(x)\}_{x \in 3\text{COL}} \approx_c \{S'^{V^*}(x)\}_{x \in 3\text{COL}}$$

Proof: ?

## Proving Claim 24

Assume  $\exists$  PPT  $D$ ,  $p \in \text{poly}$  and an infinite set  $\mathcal{I} \subseteq 3\text{COL}$  s.t.

$$\left| \Pr[D(|x|, S^{V^*(x)}(x)) = 1] - \Pr[D(|x|, S'^{V^*(x)}(x)) = 1] \right| \geq 1/p(|x|)$$

for all  $x \in \mathcal{I}$ .

## Proving Claim 24

Assume  $\exists$  PPT  $D$ ,  $p \in \text{poly}$  and an infinite set  $\mathcal{I} \subseteq 3\text{COL}$  s.t.

$$\left| \Pr[D(|x|, S^{V^*(x)}(x)) = 1] - \Pr[D(|x|, S'^{V^*(x)}(x)) = 1] \right| \geq 1/p(|x|)$$

for all  $x \in \mathcal{I}$ .

Hence,  $\exists$  PPT  $R^*$  and  $b \in [3] \setminus 1$  such that

$$\{\text{View}_{R^*}(\text{Snd}(1), R^*(x))(1^{|x|})\}_{x \in \mathcal{I}} \not\approx_c \{\text{View}_{R^*}(\text{Snd}(b), R^*(x))(1^{|x|})\}_{x \in \mathcal{I}}$$



## Proving Claim 24

Assume  $\exists$  PPT  $D$ ,  $p \in \text{poly}$  and an infinite set  $\mathcal{I} \subseteq 3\text{COL}$  s.t.

$$\left| \Pr[D(|x|, S^{V^*}(x)) = 1] - \Pr[D(|x|, S'^{V^*}(x)) = 1] \right| \geq 1/p(|x|)$$

for all  $x \in \mathcal{I}$ .

Hence,  $\exists$  PPT  $R^*$  and  $b \in [3] \setminus 1$  such that

$$\{\text{View}_{R^*}(\text{Snd}(1), R^*(x))(1^{|x|})\}_{x \in \mathcal{I}} \not\approx_c \{\text{View}_{R^*}(\text{Snd}(b), R^*(x))(1^{|x|})\}_{x \in \mathcal{I}}$$

We critically used the non-uniform security of  $\text{Com}$ .

# $S'$ is a good simulator

## Claim 25

$\{(P(w_x), V^*)(x)\}_{x \in 3\text{COL}} \approx_c \{S'^{V^*(x)}(x)\}_{x \in 3\text{COL}}$ , for any  $\{w_x \in R_{GI}(x)\}_{x \in 3\text{COL}}$ .

# $S'$ is a good simulator

## Claim 25

$\{(P(w_x), V^*)(x)\}_{x \in 3\text{COL}} \approx_c \{S'^{V^*(x)}(x)\}_{x \in 3\text{COL}}$ , for any  $\{w_x \in R_{GI}(x)\}_{x \in 3\text{COL}}$ .

Proof: ?

## Remarks

- Aborting verifiers

## Remarks

- Aborting verifiers
- Auxiliary inputs

## Remarks

- Aborting verifiers
- Auxiliary inputs
- Soundness amplification

## Extending to all $\mathcal{NP}$

For  $\mathcal{L} \in \mathcal{NP}$  let  $\text{Map}_x$  and  $\text{Map}_w$  be two poly-time functions s.t.

- $x \in \mathcal{L} \iff \text{Map}_x(x) \in 3\text{COL},$

## Extending to all $\mathcal{NP}$

For  $\mathcal{L} \in \mathcal{NP}$  let  $\text{Map}_x$  and  $\text{Map}_w$  be two poly-time functions s.t.

- $x \in \mathcal{L} \iff \text{Map}_x(x) \in 3\text{COL}$ ,
- $\text{Map}_x$  is efficiently invertible.



## Extending to all $\mathcal{NP}$

For  $\mathcal{L} \in \mathcal{NP}$  let  $\text{Map}_x$  and  $\text{Map}_w$  be two poly-time functions s.t.

- $x \in \mathcal{L} \iff \text{Map}_x(x) \in 3\text{COL}$ ,
- $\text{Map}_x$  is efficiently invertible.
- $(x, w) \in R_{\mathcal{L}} \iff \text{Map}_w(x, w) \in R_{3\text{COL}}(\text{Map}_x(x))$

## Extending to all $\mathcal{NP}$

For  $\mathcal{L} \in \mathcal{NP}$  let  $\text{Map}_x$  and  $\text{Map}_w$  be two poly-time functions s.t.

- $x \in \mathcal{L} \iff \text{Map}_x(x) \in 3\text{COL}$ ,
- $\text{Map}_x$  is efficiently invertible.
- $(x, w) \in R_{\mathcal{L}} \iff \text{Map}_w(x, w) \in R_{3\text{COL}}(\text{Map}_x(x))$

## Extending to all $\mathcal{NP}$

For  $\mathcal{L} \in \mathcal{NP}$  let  $\text{Map}_x$  and  $\text{Map}_w$  be two poly-time functions s.t.

- $x \in \mathcal{L} \iff \text{Map}_x(x) \in 3\text{COL}$ ,
- $\text{Map}_x$  is efficiently invertible.
- $(x, w) \in R_{\mathcal{L}} \iff \text{Map}_w(x, w) \in R_{3\text{COL}}(\text{Map}_x(x))$

Let  $(P, V)$  be a  $\mathcal{CZK}$  for  $3\text{COL}$ .

## Extending to all $\mathcal{NP}$

For  $\mathcal{L} \in \mathcal{NP}$  let  $\text{Map}_x$  and  $\text{Map}_w$  be two poly-time functions s.t.

- $x \in \mathcal{L} \iff \text{Map}_x(x) \in 3\text{COL}$ ,
- $\text{Map}_x$  is efficiently invertible.
- $(x, w) \in R_{\mathcal{L}} \iff \text{Map}_w(x, w) \in R_{3\text{COL}}(\text{Map}_x(x))$

Let  $(P, V)$  be a  $\mathcal{CZK}$  for  $3\text{COL}$ .

### Protocol 26 $((P_{\mathcal{L}}, V_{\mathcal{L}}))$

Common input:  $x \in \{0, 1\}^*$ .

$P_{\mathcal{L}}$ 's input:  $w \in R_{\mathcal{L}}(x)$ .

- 1 The two parties interact in  $\langle (P(\text{Map}_w(x, w)), V)(\text{Map}_x(x)) \rangle$ , where  $P_{\mathcal{L}}$  and  $V_{\mathcal{L}}$  taking the role of  $P$  and  $V$  respectively.
- 2  $V_{\mathcal{L}}$  accepts iff  $V$  accepts in the above execution.

## Extending to all $\mathcal{L} \in \mathcal{NP}$ cont.

### Claim 27

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a  $\mathcal{CZK}$  for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

## Extending to all $\mathcal{L} \in \mathcal{NP}$ cont.

### Claim 27

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a  $\mathcal{CZK}$  for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

- Completeness and soundness: Clear.

## Extending to all $\mathcal{L} \in \mathcal{NP}$ cont.

### Claim 27

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a  $\mathcal{CZK}$  for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

- Completeness and soundness: Clear.
- Zero knowledge: Let  $S$  (an efficient)  $\mathcal{ZK}$  simulator for  $(P, V)$  (for 3COL). Define  $S_{\mathcal{L}}(x)$  to output  $S(\text{Map}_x(x))$ , while replacing the string  $\text{Map}_x(x)$  in the output of  $S$  with  $x$ .

## Extending to all $\mathcal{L} \in \mathcal{NP}$ cont.

### Claim 27

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a  $\mathcal{CZK}$  for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

- Completeness and soundness: Clear.
- Zero knowledge: Let  $S$  (an efficient)  $\mathcal{ZK}$  simulator for  $(P, V)$  (for 3COL). Define  $S_{\mathcal{L}}(x)$  to output  $S(\text{Map}_x(x))$ , while replacing the string  $\text{Map}_x(x)$  in the output of  $S$  with  $x$ .



## Extending to all $\mathcal{L} \in \mathcal{NP}$ cont.

### Claim 27

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a  $\mathcal{CZK}$  for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

- Completeness and soundness: Clear.
- Zero knowledge: Let  $S$  (an efficient)  $\mathcal{ZK}$  simulator for  $(P, V)$  (for 3COL). Define  $S_{\mathcal{L}}(x)$  to output  $S(\text{Map}_x(x))$ , while replacing the string  $\text{Map}_x(x)$  in the output of  $S$  with  $x$ .

### Claim 28

$\{(P_{\mathcal{L}}(w_x), V_{\mathcal{L}}^*)(x)\}_{x \in \mathcal{L}} \approx_c \{S_{\mathcal{L}}^{V_{\mathcal{L}}^*}(x)\}_{x \in \mathcal{L}}$  for any PPT  $V_{\mathcal{L}}^*$ .

## Extending to all $\mathcal{L} \in \mathcal{NP}$ cont.

### Claim 27

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a  $\mathcal{CZK}$  for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

- Completeness and soundness: Clear.
- Zero knowledge: Let  $S$  (an efficient)  $\mathcal{ZK}$  simulator for  $(P, V)$  (for 3COL). Define  $S_{\mathcal{L}}(x)$  to output  $S(\text{Map}_x(x))$ , while replacing the string  $\text{Map}_x(x)$  in the output of  $S$  with  $x$ .

### Claim 28

$\{(P_{\mathcal{L}}(w_x), V_{\mathcal{L}}^*)(x)\}_{x \in \mathcal{L}} \approx_c \{S_{\mathcal{L}}^{V_{\mathcal{L}}^*}(x)\}_{x \in \mathcal{L}}$  for any PPT  $V_{\mathcal{L}}^*$ .

## Extending to all $\mathcal{L} \in \mathcal{NP}$ cont.

### Claim 27

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a  $\mathcal{CZK}$  for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

- Completeness and soundness: Clear.
- Zero knowledge: Let  $S$  (an efficient)  $\mathcal{ZK}$  simulator for  $(P, V)$  (for 3COL). Define  $S_{\mathcal{L}}(x)$  to output  $S(\text{Map}_x(x))$ , while replacing the string  $\text{Map}_x(x)$  in the output of  $S$  with  $x$ .

### Claim 28

$\{(P_{\mathcal{L}}(w_x), V_{\mathcal{L}}^*)(x)\}_{x \in \mathcal{L}} \approx_c \{S_{\mathcal{L}}^{V_{\mathcal{L}}^*}(x)\}_{x \in \mathcal{L}}$  for any PPT  $V_{\mathcal{L}}^*$ .

Proof:

## Extending to all $\mathcal{L} \in \mathcal{NP}$ cont.

### Claim 27

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a  $\mathcal{CZK}$  for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for  $3\text{COL}$ .

- Completeness and soundness: Clear.
- Zero knowledge: Let  $S$  (an efficient)  $\mathcal{ZK}$  simulator for  $(P, V)$  (for  $3\text{COL}$ ). Define  $S_{\mathcal{L}}(x)$  to output  $S(\text{Map}_x(x))$ , while replacing the string  $\text{Map}_x(x)$  in the output of  $S$  with  $x$ .

### Claim 28

$\{(P_{\mathcal{L}}(w_x), V_{\mathcal{L}}^*)(x)\}_{x \in \mathcal{L}} \approx_c \{S_{\mathcal{L}}^{V_{\mathcal{L}}^*(x)}(x)\}_{x \in \mathcal{L}}$  for any PPT  $V_{\mathcal{L}}^*$ .

Proof: Assume  $\{(P_{\mathcal{L}}(w_x), V_{\mathcal{L}}^*)(x)\}_{x \in \mathcal{L}} \not\approx_c \{S_{\mathcal{L}}^{V_{\mathcal{L}}^*(x)}(x)\}_{x \in \mathcal{L}}$  for some  $V_{\mathcal{L}}^*$ .

## Extending to all $\mathcal{L} \in \mathcal{NP}$ cont.

### Claim 27

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a  $\mathcal{CZK}$  for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for  $3\text{COL}$ .

- Completeness and soundness: Clear.
- Zero knowledge: Let  $S$  (an efficient)  $\mathcal{ZK}$  simulator for  $(P, V)$  (for  $3\text{COL}$ ). Define  $S_{\mathcal{L}}(x)$  to output  $S(\text{Map}_x(x))$ , while replacing the string  $\text{Map}_x(x)$  in the output of  $S$  with  $x$ .

### Claim 28

$\{(P_{\mathcal{L}}(w_x), V_{\mathcal{L}}^*)(x))\}_{x \in \mathcal{L}} \approx_c \{S_{\mathcal{L}}^{V_{\mathcal{L}}^*}(x)\}_{x \in \mathcal{L}}$  for any PPT  $V_{\mathcal{L}}^*$ .

Proof: Assume  $\{(P_{\mathcal{L}}(w_x), V_{\mathcal{L}}^*)(x))\}_{x \in \mathcal{L}} \not\approx_c \{S_{\mathcal{L}}^{V_{\mathcal{L}}^*}(x)\}_{x \in \mathcal{L}}$  for some  $V_{\mathcal{L}}^*$ .

It follows that  $\{(P(\text{Map}_w(x, w_x)), V^*)(x))\}_{x \in 3\text{COL}} \not\approx_c \{S^{V^*}(x)\}_{x \in 3\text{COL}}$ .

$V^*(x)$ : act like  $V_{\mathcal{L}}^*(x')$  for  $x' = \text{Map}_x^{-1}(x)$ .