

**Foundation of Cryptography**  
**(0368-4162-01), Lecture 5**  
**Interactive Proofs and Zero Knowledge**

Iftach Haitner, Tel Aviv University

December 4, 2011

## Part I

# Interactive Proofs

## Interactive Vs. Interactive Proofs

### Definition 1 (NP)

$\mathcal{L} \in \text{NP}$  iff  $\exists \ell \in \text{poly}$  and poly-time algorithm  $V$  such that:

- $\forall x \in \mathcal{L} \cap \{0, 1\}^n$  there exists  $w \in \{0, 1\}^{\ell(n)}$  s.t.  $V(x, w) = 1$
- $V(x, \cdot) = 0$  for every  $x \notin \mathcal{L}$

## Interactive Vs. Interactive Proofs

### Definition 1 (NP)

$\mathcal{L} \in \text{NP}$  iff  $\exists \ell \in \text{poly}$  and poly-time algorithm  $V$  such that:

- $\forall x \in \mathcal{L} \cap \{0, 1\}^n$  there exists  $w \in \{0, 1\}^{\ell(n)}$  s.t.  $V(x, w) = 1$
- $V(x, \cdot) = 0$  for every  $x \notin \mathcal{L}$

- *Non-interactive proof*

## Interactive Vs. Interactive Proofs

### Definition 1 (NP)

$\mathcal{L} \in \text{NP}$  iff  $\exists \ell \in \text{poly}$  and poly-time algorithm  $V$  such that:

- $\forall x \in \mathcal{L} \cap \{0, 1\}^n$  there exists  $w \in \{0, 1\}^{\ell(n)}$  s.t.  $V(x, w) = 1$
- $V(x, \cdot) = 0$  for every  $x \notin \mathcal{L}$

- *Non-interactive* proof
- Interactive proofs?

## Interactive Vs. Interactive Proofs

### Definition 1 (NP)

$\mathcal{L} \in \text{NP}$  iff  $\exists \ell \in \text{poly}$  and poly-time algorithm  $V$  such that:

- $\forall x \in \mathcal{L} \cap \{0, 1\}^n$  there exists  $w \in \{0, 1\}^{\ell(n)}$  s.t.  $V(x, w) = 1$
- $V(x, \cdot) = 0$  for every  $x \notin \mathcal{L}$

- *Non-interactive* proof
- Interactive proofs?

## Interactive protocols

- Interactive algorithm

## Interactive protocols

- Interactive algorithm
- Protocol  $\pi = (A, B)$



## Interactive protocols

- Interactive algorithm
- Protocol  $\pi = (A, B)$
- RV describing the parties joint output  $\langle A(i_A), B(i_B) \rangle(i)$

## Interactive protocols

- Interactive algorithm
- Protocol  $\pi = (A, B)$
- RV describing the parties joint output  $\langle A(i_A), B(i_B) \rangle(i)$
- $m$ -round algorithm,  $m$ -round protocol

## Interactive Proofs

### Definition 2 (Interactive Proof (IP))

A protocol  $(P, V)$  is an interactive proof for  $\mathcal{L}$ , if  $V$  is PPT and the following hold:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = \text{Accept}] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and *any* algorithm  $P^*$   
 $\Pr[\langle (P^*, V)(x) \rangle = \text{Accept}] \leq 1/3$

## Interactive Proofs

### Definition 2 (Interactive Proof (IP))

A protocol  $(P, V)$  is an interactive proof for  $\mathcal{L}$ , if  $V$  is PPT and the following hold:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = \text{Accept}] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and *any* algorithm  $P^*$   
 $\Pr[\langle (P^*, V)(x) \rangle = \text{Accept}] \leq 1/3$

- $\text{IP} = \text{PSPACE}$

## Interactive Proofs

### Definition 2 (Interactive Proof (IP))

A protocol  $(P, V)$  is an interactive proof for  $\mathcal{L}$ , if  $V$  is PPT and the following hold:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = \text{Accept}] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and *any* algorithm  $P^*$   
 $\Pr[\langle (P^*, V)(x) \rangle = \text{Accept}] \leq 1/3$

- $\text{IP} = \text{PSPACE}$
- We typically consider (and achieve) perfect completeness

## Interactive Proofs

### Definition 2 (Interactive Proof (IP))

A protocol  $(P, V)$  is an interactive proof for  $\mathcal{L}$ , if  $V$  is PPT and the following hold:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = \text{Accept}] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and *any* algorithm  $P^*$   
 $\Pr[\langle (P^*, V)(x) \rangle = \text{Accept}] \leq 1/3$

- $\text{IP} = \text{PSPACE}$
- We typically consider (and achieve) perfect completeness
- Negligible “soundness error” achieved via repetition.

## Interactive Proofs

### Definition 2 (Interactive Proof (IP))

A protocol  $(P, V)$  is an interactive proof for  $\mathcal{L}$ , if  $V$  is PPT and the following hold:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = \text{Accept}] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and *any* algorithm  $P^*$   
 $\Pr[\langle (P^*, V)(x) \rangle = \text{Accept}] \leq 1/3$

- $IP = PSPACE$
- We typically consider (and achieve) perfect completeness
- Negligible “soundness error” achieved via repetition.
- soundness only against PPT: *computationally sound proofs/interactive arguments*.

## Interactive Proofs

### Definition 2 (Interactive Proof (IP))

A protocol  $(P, V)$  is an interactive proof for  $\mathcal{L}$ , if  $V$  is PPT and the following hold:

**Completeness**  $\forall x \in \mathcal{L}, \Pr[\langle (P, V)(x) \rangle = \text{Accept}] \geq 2/3$

**Soundness**  $\forall x \notin \mathcal{L}$ , and *any* algorithm  $P^*$   
 $\Pr[\langle (P^*, V)(x) \rangle = \text{Accept}] \leq 1/3$

- $\text{IP} = \text{PSPACE}$
- We typically consider (and achieve) perfect completeness
- Negligible “soundness error” achieved via repetition.
- soundness only against PPT: *computationally sound proofs/interactive arguments*.
- efficient provers via “auxiliary input”



## Section 1

# IP for GNI

## graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

### Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are *isomorphic*, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that

$(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

$GI = \{(G_0, G_1) : G_0 \equiv G_1\}$ .

## graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

### Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are *isomorphic*, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that

$(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

$GI = \{(G_0, G_1) : G_0 \equiv G_1\}$ .

- Assume reasonable mapping from graphs to strings

## graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

### Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are *isomorphic*, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that

$(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

$GI = \{(G_0, G_1) : G_0 \equiv G_1\}$ .

- Assume reasonable mapping from graphs to strings
- $GI \in NP$

## graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

### Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are *isomorphic*, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that

$(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

$GI = \{(G_0, G_1) : G_0 \equiv G_1\}$ .

- Assume reasonable mapping from graphs to strings
- $GI \in NP$
- Does  $GNI = \{(G_0, G_1) : G_0 \not\equiv G_1\} \in NP$ ?

## graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

### Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are *isomorphic*, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that

$(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

$GI = \{(G_0, G_1) : G_0 \equiv G_1\}$ .

- Assume reasonable mapping from graphs to strings
- $GI \in NP$
- Does  $GNI = \{(G_0, G_1) : G_0 \not\equiv G_1\} \in NP$ ?
- We will show a simple interactive proof for GNI

## graph isomorphism

$\Pi_m$  – the set of all permutations from  $[m]$  to  $[m]$

### Definition 3 (graph isomorphism)

Graphs  $G_0 = ([m], E_0)$  and  $G_1 = ([m], E_1)$  are *isomorphic*, denoted  $G_0 \equiv G_1$ , if  $\exists \pi \in \Pi_m$  such that

$(u, v) \in E_0$  iff  $(\pi(u), \pi(v)) \in E_1$ .

$GI = \{(G_0, G_1) : G_0 \equiv G_1\}$ .

- Assume reasonable mapping from graphs to strings
- $GI \in NP$
- Does  $GNI = \{(G_0, G_1) : G_0 \not\equiv G_1\} \in NP$ ?
- We will show a simple interactive proof for GNI Idea: Beer tasting...

## IP for GNI

**Protocol 4 ((P, V))**

**Common input**  $G_0 = ([m], E_0), G_1 = ([m], E_1)$

- 1 V chooses  $b \leftarrow \{0, 1\}$  and  $\pi \leftarrow \Pi_m$ , and sends  $\pi(E_b) = \{(\pi(u), \pi(v)) : (u, v) \in E_b\}$  to P
- 2 P send  $b'$  to V (tries to set  $b' = b$ )
- 3 V accepts iff  $b' = b$



## IP for GNI

**Protocol 4 ((P, V))****Common input**  $G_0 = ([m], E_0), G_1 = ([m], E_1)$ 

- 1 V chooses  $b \leftarrow \{0, 1\}$  and  $\pi \leftarrow \Pi_m$ , and sends  $\pi(E_b) = \{(\pi(u), \pi(v)) : (u, v) \in E_b\}$  to P
- 2 P send  $b'$  to V (tries to set  $b' = b$ )
- 3 V accepts iff  $b' = b$

**Claim 5**

The above protocol is IP for GNI, with perfect completeness and soundness error  $\frac{1}{2}$ .

## Proving Claim ??

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)

## Proving Claim ??

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)
- $([m], \pi(E_i))$  is a random element in  $[G_i]$  — the equivalence class of  $G_i$

## Proving Claim ??

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)
- $([m], \pi(E_i))$  is a random element in  $[G_i]$  — the equivalence class of  $G_i$

Hence,

$$G_0 \equiv G_1: \Pr[b' = b] \leq \frac{1}{2}.$$

## Proving Claim ??

- Graph isomorphism is an equivalence relation (separates the set of all graph pairs into separate subsets)
- $([m], \pi(E_i))$  is a random element in  $[G_i]$  — the equivalence class of  $G_i$

Hence,

$$G_0 \equiv G_1: \Pr[b' = b] \leq \frac{1}{2}.$$

$$G_0 \not\equiv G_1: \Pr[b' = b] = 1 \text{ (i.e., } i \text{ can, possibly inefficiently, extracted from } \pi(E_i))$$



## Part II

# Zero knowledge Proofs

## The concept of zero knowledge

- Proving w/o revealing any addition information.

## The concept of zero knowledge

- Proving w/o revealing any additional information.
- What does it mean?



## The concept of zero knowledge

- Proving w/o revealing any additional information.
- What does it mean?  
Simulation paradigm.

## Zero knowledge Proof

### Definition 6 (computational ZK)

An interactive proof  $(P, V)$  is computational zero-knowledge proof (CZKP) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that  $\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{L}} \approx_c \{S(x)\}_{x \in \mathcal{L}}$ .

## Zero knowledge Proof

### Definition 6 (computational ZK)

An interactive proof  $(P, V)$  is computational zero-knowledge proof (CZKP) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that

$$\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{L}} \approx_c \{S(x)\}_{x \in \mathcal{L}}.$$

Perfect ZK (PZKP)/statistical ZK (SZKP) – the above dist. are identically/statistically close, even for *unbounded*  $V^*$ .

## Zero knowledge Proof

### Definition 6 (computational ZK)

An interactive proof  $(P, V)$  is computational zero-knowledge proof (CZKP) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that

$$\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}.$$

Perfect ZK (PZKP)/statistical ZK (SZKP) – the above dist. are identically/statistically close, even for *unbounded*  $V^*$ .

- 1 ZK is a property of the prover.

## Zero knowledge Proof

### Definition 6 (computational ZK)

An interactive proof  $(P, V)$  is computational zero-knowledge proof (CZKP) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that

$$\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}.$$

Perfect ZK (PZKP)/statistical ZK (SZKP) – the above dist. are identically/statistically close, even for *unbounded*  $V^*$ .

- 1 ZK is a property of the prover.
- 2 ZK only required to hold with respect to true statements.

## Zero knowledge Proof

### Definition 6 (computational ZK)

An interactive proof  $(P, V)$  is computational zero-knowledge proof (CZKP) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that

$$\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}.$$

Perfect ZK (PZKP)/statistical ZK (SZKP) – the above dist. are identically/statistically close, even for *unbounded*  $V^*$ .

- 1 ZK is a property of the prover.
- 2 ZK only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".

## Zero knowledge Proof

### Definition 6 (computational ZK)

An interactive proof  $(P, V)$  is computational zero-knowledge proof (CZKP) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that

$$\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}.$$

Perfect ZK (PZKP)/statistical ZK (SZKP) – the above dist. are identically/statistically close, even for *unbounded*  $V^*$ .

- 1 ZK is a property of the prover.
- 2 ZK only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".
- 4 Trivial to achieve for  $\mathcal{L} \in \text{BPP}$

## Zero knowledge Proof

### Definition 6 (computational ZK)

An interactive proof  $(P, V)$  is computational zero-knowledge proof (CZKP) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that

$$\{\langle (P, V^*)(x) \rangle\}_{x \in \mathcal{L}} \approx_c \{S(x)\}_{x \in \mathcal{L}}.$$

Perfect ZK (PZKP)/statistical ZK (SZKP) – the above dist. are identically/statistically close, even for *unbounded*  $V^*$ .

- 1 ZK is a property of the prover.
- 2 ZK only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".
- 4 Trivial to achieve for  $\mathcal{L} \in \text{BPP}$
- 5 Extension: auxiliary input



## Zero knowledge Proof

### Definition 6 (computational ZK)

An interactive proof  $(P, V)$  is computational zero-knowledge proof (CZKP) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that

$$\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}.$$

Perfect ZK (PZKP)/statistical ZK (SZKP) – the above dist. are identically/statistically close, even for *unbounded*  $V^*$ .

- 1 ZK is a property of the prover.
- 2 ZK only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".
- 4 Trivial to achieve for  $\mathcal{L} \in \text{BPP}$
- 5 Extension: auxiliary input
- 6 The "standard" NP proof is typically not zero knowledge

## Zero knowledge Proof

### Definition 6 (computational ZK)

An interactive proof  $(P, V)$  is computational zero-knowledge proof (CZKP) for  $\mathcal{L}$ , if  $\forall$  PPT  $V^*$ ,  $\exists$  PPT  $S$  such that

$$\{ \langle (P, V^*)(x) \rangle \}_{x \in \mathcal{L}} \approx_c \{ S(x) \}_{x \in \mathcal{L}}.$$

Perfect ZK (PZKP)/statistical ZK (SZKP) – the above dist. are identically/statistically close, even for *unbounded*  $V^*$ .

- 1 ZK is a property of the prover.
- 2 ZK only required to hold with respect to true statements.
- 3 wlg.  $V^*$ 's outputs is its "view".
- 4 Trivial to achieve for  $\mathcal{L} \in \text{BPP}$
- 5 Extension: auxiliary input
- 6 The "standard" NP proof is typically not zero knowledge
- 7 Next class — ZK for all NP

## Section 2

# ZK Proof for GI

## ZK Proof for Graph Isomorphism

Idea: route finding

## ZK Proof for Graph Isomorphism

Idea: route finding

### Protocol 7 ((P, V))

**Common input**  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

**P's input** a permutation  $\pi$  such that  $\pi(E_1) = E_0$

- ➊ P chooses  $\pi' \leftarrow \Pi_m$  and sends  $E = \pi'(E_0)$  to V
- ➋ V sends  $b \leftarrow \{0, 1\}$  to P
- ➌ if  $b = 0$ , P sets  $\pi'' = \pi'$ , otherwise, it sends  $\pi'' = \pi' \circ \pi$  to V
- ➍ V accepts iff  $\pi''(E_b) = E$

## ZK Proof for Graph Isomorphism

Idea: route finding

### Protocol 7 ((P, V))

**Common input**  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

**P's input** a permutation  $\pi$  such that  $\pi(E_1) = E_0$

- ➊ P chooses  $\pi' \leftarrow \Pi_m$  and sends  $E = \pi'(E_0)$  to V
- ➋ V sends  $b \leftarrow \{0, 1\}$  to P
- ➌ if  $b = 0$ , P sets  $\pi'' = \pi'$ , otherwise, it sends  $\pi'' = \pi' \circ \pi$  to V
- ➍ V accepts iff  $\pi''(E_b) = E$

### Claim 8

The above protocol is SZKP for GI, with perfect completeness and soundness  $\frac{1}{2}$ .

## Proving Claim ??

**Completeness** Clear

## Proving Claim ??

**Completeness** Clear

**Soundness** If exist  $j \in \{0, 1\}$  for which  $\nexists \pi' \in \Pi_m$  with  $\pi'(E_j) = E$ , then  $V$  rejects w.p. at least  $\frac{1}{2}$ .



## Proving Claim ??

**Completeness** Clear

**Soundness** If exist  $j \in \{0, 1\}$  for which  $\nexists \pi' \in \Pi_m$  with  $\pi'(E_j) = E$ , then  $V$  rejects w.p. at least  $\frac{1}{2}$ .

Assuming  $V$  rejects w.p. less than  $\frac{1}{2}$  and lett  $\pi_0$  and  $\pi_1$  be the values guaranteed by the above observation (i.e., mapping  $E_0$  and  $E_1$  to  $E$  respectively).

## Proving Claim ??

**Completeness** Clear

**Soundness** If exist  $j \in \{0, 1\}$  for which  $\nexists \pi' \in \Pi_m$  with  $\pi'(E_j) = E$ , then  $V$  rejects w.p. at least  $\frac{1}{2}$ .

Assuming  $V$  rejects w.p. less than  $\frac{1}{2}$  and lett  $\pi_0$  and  $\pi_1$  be the values guaranteed by the above observation (i.e., mapping  $E_0$  and  $E_1$  to  $E$  respectively).

Then  $\pi_0^{-1}(\pi_1(E_1)) = \pi_0$

## Proving Claim ??

**Completeness** Clear

**Soundness** If exist  $j \in \{0, 1\}$  for which  $\nexists \pi' \in \Pi_m$  with  $\pi'(E_j) = E$ , then  $V$  rejects w.p. at least  $\frac{1}{2}$ .

Assuming  $V$  rejects w.p. less than  $\frac{1}{2}$  and lett  $\pi_0$  and  $\pi_1$  be the values guaranteed by the above observation (i.e., mapping  $E_0$  and  $E_1$  to  $E$  respectively).

Then  $\pi_0^{-1}(\pi_1(E_1)) = \pi_0 \implies (G_0, G_1) \in \text{GI}$ .

## Proving Claim ??

**Completeness** Clear

**Soundness** If exist  $j \in \{0, 1\}$  for which  $\nexists \pi' \in \Pi_m$  with  $\pi'(E_j) = E$ , then  $V$  rejects w.p. at least  $\frac{1}{2}$ .  
Assuming  $V$  rejects w.p. less than  $\frac{1}{2}$  and lett  $\pi_0$  and  $\pi_1$  be the values guaranteed by the above observation (i.e., mapping  $E_0$  and  $E_1$  to  $E$  respectively).

Then  $\pi_0^{-1}(\pi_1(E_1)) = \pi_0 \implies (G_0, G_1) \in \text{GI}$ .

**ZK** Idea: for  $(G_0, G_1) \in \text{GI}$ , it is easy to generate a random transcript for Steps 1-2, and to be able to open it with prob  $\frac{1}{2}$ .

## The simulator

For a start we consider a deterministic cheating verifier  $V^*$  that never aborts.

## The simulator

For a start we consider a deterministic cheating verifier  $V^*$  that never aborts.

### Algorithm 9 (S)

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

Do  $|x|$  times:

- ➊ Choose  $b' \leftarrow \{0, 1\}$  and  $\pi \leftarrow \Pi_m$ , and “send”  $\pi(E_{b'})$  to  $V^*(x)$ .
- ➋ Let  $b$  be  $V^*$ ’s answer. If  $b = b'$ , send  $\pi$  to  $V^*$ , output  $V^*$ ’s output and halt.  
Otherwise, rewind the simulation to its first step.

Abort

## The simulator

For a start we consider a deterministic cheating verifier  $V^*$  that never aborts.

### Algorithm 9 (S)

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

Do  $|x|$  times:

- 1 Choose  $b' \leftarrow \{0, 1\}$  and  $\pi \leftarrow \Pi_m$ , and “send”  $\pi(E_{b'})$  to  $V^*(x)$ .
- 2 Let  $b$  be  $V^*$ ’s answer. If  $b = b'$ , send  $\pi$  to  $V^*$ , output  $V^*$ ’s output and halt.  
Otherwise, rewind the simulation to its first step.

Abort

### Claim 10

$$\{\langle (P, V^*)(x) \rangle\}_{x \in \text{GI}} \approx \{S(x)\}_{x \in \text{GI}}$$

## Proving Claim ??

### Algorithm 11 (S')

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

Do  $|x|$  times:

- 1 Choose  $\pi \leftarrow \Pi_m$  and sends  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Let  $b$  be  $V^*$ 's answer.  
W.p.  $\frac{1}{2}$ , find  $\pi'$  such that  $E = \pi'(E_b)$  and send it to  $V^*$ ,  
output  $V^*$ 's output and halt.  
Otherwise, rewind the simulation to its first step.

Abort



## Proving Claim ??

### Algorithm 11 ( $S'$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

Do  $|x|$  times:

- 1 Choose  $\pi \leftarrow \Pi_m$  and sends  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Let  $b$  be  $V^*$ 's answer.  
W.p.  $\frac{1}{2}$ , find  $\pi'$  such that  $E = \pi'(E_b)$  and send it to  $V^*$ ,  
output  $V^*$ 's output and halt.  
Otherwise, rewind the simulation to its first step.

Abort

### Claim 12

$S(x) \equiv S'(x)$  for any  $x \in \text{GI}$ .

## Proving Claim ??

### Algorithm 11 ( $S'$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

Do  $|x|$  times:

- 1 Choose  $\pi \leftarrow \Pi_m$  and sends  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Let  $b$  be  $V^*$ 's answer.  
W.p.  $\frac{1}{2}$ , find  $\pi'$  such that  $E = \pi'(E_b)$  and send it to  $V^*$ ,  
output  $V^*$ 's output and halt.  
Otherwise, rewind the simulation to its first step.

Abort

### Claim 12

$S(x) \equiv S'(x)$  for any  $x \in \text{GI}$ .

Proof: ?

## Proving Claim ?? cont.

### Algorithm 13 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and sends  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$ , send it to  $V^*$ , output  $V^*$ 's output and halt.

## Proving Claim ?? cont.

### Algorithm 13 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and sends  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$ , send it to  $V^*$ , output  $V^*$ 's output and halt.

### Claim 14

$\forall x \in \text{GI}$  it holds that

- 1  $\langle (P, V^*(x)) \rangle \equiv S''(x)$ .

## Proving Claim ?? cont.

### Algorithm 13 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and sends  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$ , send it to  $V^*$ , output  $V^*$ 's output and halt.

### Claim 14

$\forall x \in \text{GI}$  it holds that

- 1  $\langle (P, V^*(x)) \rangle \equiv S''(x)$ .
- 2  $\text{SD}(S''(x), S'(x)) \leq 2^{-|x|}$ .

## Proving Claim ?? cont.

### Algorithm 13 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and sends  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$ , send it to  $V^*$ , output  $V^*$ 's output and halt.

### Claim 14

$\forall x \in \text{GI}$  it holds that

- 1  $\langle (P, V^*(x)) \rangle \equiv S''(x)$ .
- 2  $\text{SD}(S''(x), S'(x)) \leq 2^{-|x|}$ .

Proof: ?

## Proving Claim ?? cont.

### Algorithm 13 ( $S''$ )

Input:  $x = (G_0 = ([m], E_0), G_1 = ([m], E_1))$

- 1 Choose  $\pi \leftarrow \Pi_m$  and sends  $E = \pi(E_0)$  to  $V^*(x)$ .
- 2 Find  $\pi'$  such that  $E = \pi'(E_b)$ , send it to  $V^*$ , output  $V^*$ 's output and halt.

### Claim 14

$\forall x \in \text{GI}$  it holds that

- 1  $\langle (P, V^*(x)) \rangle \equiv S''(x)$ .
- 2  $\text{SD}(S''(x), S'(x)) \leq 2^{-|x|}$ .

Proof: ? (1) is clear.

## Proving Claim ??(2)

Fix  $(E, \pi')$  and let  $\alpha = \Pr_{S''}[(E, \pi')]$ .



## Proving Claim ??(2)

Fix  $(E, \pi')$  and let  $\alpha = \Pr_{S''}[(E, \pi')]$ .

It holds that

$$\begin{aligned}\Pr_{S'}[(E, \pi')] &= \alpha \cdot \sum_{i=1}^{|x|} \left(1 - \frac{1}{2}\right)^{i-1} \cdot \frac{1}{2} \\ &= (1 - 2^{-|x|}) \cdot \alpha\end{aligned}$$

## Proving Claim ??(2)

Fix  $(E, \pi')$  and let  $\alpha = \Pr_{S''}[(E, \pi')]$ .

It holds that

$$\begin{aligned}\Pr_{S'}[(E, \pi')] &= \alpha \cdot \sum_{i=1}^{|x|} \left(1 - \frac{1}{2}\right)^{i-1} \cdot \frac{1}{2} \\ &= (1 - 2^{-|x|}) \cdot \alpha\end{aligned}$$

Hence,  $\text{SD}(S''(x), S'(x)) \leq 2^{-|x|} \square$

## Remarks

- 1 Randomized verifiers

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers – Normalize aborting probability

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers – Normalize aborting probability
- 3 Auxiliary input

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers – Normalize aborting probability
- 3 Auxiliary input
- 4 Negligible soundness error?

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers – Normalize aborting probability
- 3 Auxiliary input
- 4 Negligible soundness error? Sequential/Parallel composition



## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers – Normalize aborting probability
- 3 Auxiliary input
- 4 Negligible soundness error? Sequential/Parallel composition
- 5 Perfect ZK for “expected time simulators”

## Remarks

- 1 Randomized verifiers
- 2 Aborting verifiers – Normalize aborting probability
- 3 Auxiliary input
- 4 Negligible soundness error? Sequential/Parallel composition
- 5 Perfect ZK for “expected time simulators”
- 6 “Black box” simulation

## Section 3

### **Black-box ZK**

## Black-box simulators

### Definition 15 (Black-box simulator)

$(P, V)$  is CZKP with black-box simulation for  $\mathcal{L}$ , if  $\exists$  oracle-aided PPT  $S$  s.t. for every deterministic polynomial-time<sup>a</sup>  $V^*$ :

$$\{(P(w_x), V^*(z))(x)\}_{x \in \mathcal{L}} \approx_c \{S^{V^*(x, z_x)}(x)\}_{x \in \mathcal{L}}$$

for any  $\{(w_x, z_x) \in R_{\mathcal{L}}(x) \times \{0, 1\}^*\}_{x \in \mathcal{L}}$ .

## Black-box simulators

### Definition 15 (Black-box simulator)

$(P, V)$  is CZKP with black-box simulation for  $\mathcal{L}$ , if  $\exists$  oracle-aided PPT  $S$  s.t. for every deterministic polynomial-time<sup>a</sup>  $V^*$ :

$$\{(P(w_x), V^*(z))(x)\}_{x \in \mathcal{L}} \approx_c \{S^{V^*(x, z_x)}(x)\}_{x \in \mathcal{L}}$$

for any  $\{(w_x, z_x) \in R_{\mathcal{L}}(x) \times \{0, 1\}^*\}_{x \in \mathcal{L}}$ .

Prefect and statistical variants are defined analogously.

---

<sup>a</sup>Length of auxiliary input does not count for the running time.

## Black-box simulators

### Definition 15 (Black-box simulator)

$(P, V)$  is CZKP with black-box simulation for  $\mathcal{L}$ , if  $\exists$  oracle-aided PPT  $S$  s.t. for every deterministic polynomial-time<sup>a</sup>  $V^*$ :

$$\{(P(w_x), V^*(z))(x)\}_{x \in \mathcal{L}} \approx_c \{S^{V^*(x, z_x)}(x)\}_{x \in \mathcal{L}}$$

for any  $\{(w_x, z_x) \in R_{\mathcal{L}}(x) \times \{0, 1\}^*\}_{x \in \mathcal{L}}$ .

Prefect and statistical variants are defined analogously.

---

<sup>a</sup>Length of auxiliary input does not count for the running time.

- 1 “Most simulators” are black box

## Black-box simulators

### Definition 15 (Black-box simulator)

$(P, V)$  is CZKP with black-box simulation for  $\mathcal{L}$ , if  $\exists$  oracle-aided PPT  $S$  s.t. for every deterministic polynomial-time<sup>a</sup>  $V^*$ :

$$\{(P(w_x), V^*(z))(x)\}_{x \in \mathcal{L}} \approx_c \{S^{V^*(x, z_x)}(x)\}_{x \in \mathcal{L}}$$

for any  $\{(w_x, z_x) \in R_{\mathcal{L}}(x) \times \{0, 1\}^*\}_{x \in \mathcal{L}}$ .

Prefect and statistical variants are defined analogously.

---

<sup>a</sup>Length of auxiliary input does not count for the running time.

- 1 “Most simulators” are black box
- 2 Strictly weaker than general simulation!

## Section 4

# Zero Knowledge for all NP



## CZKP for 3COL

- Assuming that OWFs exists, we give a CZKP for 3COL .
- We show how to transform it for any  $\mathcal{L} \in \text{NP}$  (using that  $3\text{COL} \in \text{NPC}$ ).

## CZKP for 3COL

- Assuming that OWFs exists, we give a CZKP for 3COL .
- We show how to transform it for any  $\mathcal{L} \in \text{NP}$  (using that  $3\text{COL} \in \text{NPC}$ ).

### Definition 16 (3COL)

$G = (M, E) \in 3\text{COL}$ , if  $\exists \phi: M \mapsto [3]$  s.t.  $\phi(u) \neq \phi(v)$  for every  $(u, v) \in E$ .

## CZKP for 3COL

- Assuming that OWFs exists, we give a CZKP for 3COL .
- We show how to transform it for any  $\mathcal{L} \in \text{NP}$  (using that  $3\text{COL} \in \text{NPC}$ ).

## Definition 16 (3COL)

$$G = (M, E) \in 3\text{COL}, \text{ if } \exists \phi: M \mapsto [3] \text{ s.t. } \phi(u) \neq \phi(v) \text{ for every } (u, v) \in E.$$

We use commitment schemes.

## The protocol

Let  $\pi_3$  be the set of all permutations over  $[3]$ .

## The protocol

Let  $\pi_3$  be the set of all permutations over  $[3]$ . We use perfectly binding commitment Com (statistically binding?).

## The protocol

Let  $\pi_3$  be the set of all permutations over  $[3]$ . We use perfectly binding commitment Com (statistically binding?).

### Protocol 17 ((P, V))

Common input: Graph  $G = (M, E)$  with  $n = |G|$

P's input: a (valid) coloring  $\phi$  of  $G$

- 1 P chooses  $\pi \leftarrow \Pi_3$  and sets  $\psi = \pi \circ \phi$
- 2  $\forall v \in M$ : P commits to  $\psi(v)$  using  $\text{Com}(1^n)$ .  
Let  $c_v$  and  $d_v$  be the resulting commitment and decommitment.
- 3 V sends  $e = (u, v) \leftarrow E$  to P
- 4 P sends  $(d_u, \psi(u)), (d_v, \psi(v))$  to V
- 5 V verifies that (1) both decommitments are valid, (2)  $\psi(u), \psi(v) \in [3]$  and (3)  $\psi(u) \neq \psi(v)$ .

**Claim 18**

The above protocol is a CZKP for 3COL, with perfect completeness and soundness  $1/|E|$ .

## Claim 18

The above protocol is a CZKP for 3COL, with perfect completeness and soundness  $1/|E|$ .

**Completeness:** Clear

**Soundness:** Let  $\{c_v\}_{v \in M}$  be the commitments resulting from an interaction of  $V$  with an arbitrary  $P^*$ .



## Claim 18

The above protocol is a CZKP for 3COL, with perfect completeness and soundness  $1/|E|$ .

**Completeness:** Clear

**Soundness:** Let  $\{c_v\}_{v \in M}$  be the commitments resulting from an interaction of  $V$  with an arbitrary  $P^*$ .

Define  $\phi: M \mapsto [3]$  as follows:

$\forall v \in M$ : let  $\phi(v)$  be the (single) value that it is possible to decommit  $c_v$  into (if not in  $[3]$ , set  $\phi(v) = 1$ ).

## Claim 18

The above protocol is a CZKP for 3COL, with perfect completeness and soundness  $1/|E|$ .

**Completeness:** Clear

**Soundness:** Let  $\{c_v\}_{v \in M}$  be the commitments resulting from an interaction of  $V$  with an arbitrary  $P^*$ .

Define  $\phi: M \mapsto [3]$  as follows:

$\forall v \in M$ : let  $\phi(v)$  be the (single) value that it is possible to decommit  $c_v$  into (if not in  $[3]$ , set  $\phi(v) = 1$ ).

If  $G \notin 3COL$ , then  $\exists (u, v) \in E$  s.t.  $\phi(u) \neq \phi(v)$ .

## Claim 18

The above protocol is a CZKP for 3COL, with perfect completeness and soundness  $1/|E|$ .

**Completeness:** Clear

**Soundness:** Let  $\{c_v\}_{v \in M}$  be the commitments resulting from an interaction of  $V$  with an arbitrary  $P^*$ .

Define  $\phi: M \mapsto [3]$  as follows:

$\forall v \in M$ : let  $\phi(v)$  be the (single) value that it is possible to decommit  $c_v$  into (if not in  $[3]$ , set  $\phi(v) = 1$ ).

If  $G \notin 3COL$ , then  $\exists (u, v) \in E$  s.t.  $\phi(u) \neq \phi(v)$ .

Hence  $V$  rejects such  $x$  w.p. at least  $1/|E|$

# Proving ZK

Fix a deterministic, non-aborting  $V^*$  that gets no auxiliary input.

# Proving ZK

Fix a deterministic, non-aborting  $V^*$  that gets no auxiliary input.

## Algorithm 19 (S)

Input: A graph  $G = (M, E)$  with  $n = |G|$

Do  $n \cdot |E|$  times:

- 1 Choose  $e' = (u, v) \leftarrow E$ . Set  $\psi(u) \leftarrow [3]$ ,  
 $\psi(v) \leftarrow [3] \setminus \{\psi(u)\}$ , and  $\psi(w) = 1$  for  $w \in M \setminus \{u, v\}$
- 2  $\forall v \in M$ : commit to  $\psi(v)$  to  $V^*$  (resulting in  $c_v$  and  $d_v$ )
- 3 Let  $e$  be the edge sent by  $V^*$ .  
If  $e = e'$ , send  $(d_u, \psi(u)), (d_v, \psi(v))$  to  $V^*$ , output  $V^*$ 's  
output and halt.  
Otherwise, rewind the simulation to its first step.

Abort

## Proving ZK cont.

### Claim 20

$\{(P(w_x), V^*)(x)\}_{x \in 3\text{COL}} \approx_c \{S^{V^*(x)}(x)\}_{x \in 3\text{COL}}$ , for any  $\{w_x \in R_{3\text{COL}}(x)\}_{x \in 3\text{COL}}$ .

Consider the following (inefficient simulator)

### Algorithm 21 ( $S'$ )

Input:  $G = (V, E)$  with  $n = |G|$

Find (using brute force) a valid coloring  $\phi$  of  $G$

Do  $n \cdot |E|$  times

① Act as the honest prover does given private input  $\phi$

② Let  $e$  be the edge sent by  $V^*$ .

W.p.  $1/|E|$ ,  $S'$  sends  $(\psi(u), d_u), (\psi(v), d_v)$  to  $V^*$ , output  $V^*$ 's output and halt.

Otherwise, rewind the simulation to its first step.

Abort

Consider the following (inefficient simulator)

### Algorithm 21 ( $S'$ )

Input:  $G = (V, E)$  with  $n = |G|$

Find (using brute force) a valid coloring  $\phi$  of  $G$

Do  $n \cdot |E|$  times

① Act as the honest prover does given private input  $\phi$

② Let  $e$  be the edge sent by  $V^*$ .

W.p.  $1/|E|$ ,  $S'$  sends  $(\psi(u), d_u), (\psi(v), d_v)$  to  $V^*$ , output  $V^*$ 's output and halt.

Otherwise, rewind the simulation to its first step.

Abort

### Claim 22

$$\{S^{V^*(x)}(x)\}_{x \in 3\text{COL}} \approx_c \{S'^{V^*(x)}(x)\}_{x \in 3\text{COL}}$$



Consider the following (inefficient simulator)

### Algorithm 21 ( $S'$ )

Input:  $G = (V, E)$  with  $n = |G|$

Find (using brute force) a valid coloring  $\phi$  of  $G$

Do  $n \cdot |E|$  times

① Act as the honest prover does given private input  $\phi$

② Let  $e$  be the edge sent by  $V^*$ .

W.p.  $1/|E|$ ,  $S'$  sends  $(\psi(u), d_u), (\psi(v), d_v)$  to  $V^*$ , output  $V^*$ 's output and halt.

Otherwise, rewind the simulation to its first step.

Abort

### Claim 22

$$\{S^{V^*(x)}(x)\}_{x \in 3\text{COL}} \approx_c \{S'^{V^*(x)}(x)\}_{x \in 3\text{COL}}$$

Proof: ?

## Proving Claim ??

Assume  $\exists$  PPT  $D$ ,  $p \in \text{poly}$  and an infinite set  $\mathcal{I} \subseteq 3\text{COL}$  s.t.

$$\left| \Pr[D(|x|, S^{V^*(x)}(x)) = 1] - \Pr[D(|x|, S'^{V^*(x)}(x)) = 1] \right| \geq 1/p(|x|)$$

for all  $x \in \mathcal{I}$ .

## Proving Claim ??

Assume  $\exists$  PPT  $D$ ,  $p \in \text{poly}$  and an infinite set  $\mathcal{I} \subseteq 3\text{COL}$  s.t.

$$\left| \Pr[D(|x|, S^{V^*}(x)) = 1] - \Pr[D(|x|, S'^{V^*}(x)) = 1] \right| \geq 1/p(|x|)$$

for all  $x \in \mathcal{I}$ .

Hence,  $\exists$  PPT  $R^*$  and  $b \neq b' \in [3]$  such that

$$\{\text{View}_{R^*}(S(b), R^*(x))(1^{|x|})\}_{x \in \mathcal{I}} \not\approx_c \{\text{View}_{R^*}(S(b'), R^*(x))(1^{|x|})\}_{x \in \mathcal{I}}$$

where  $S$  is the sender in Com.

## Proving Claim ??

Assume  $\exists$  PPT  $D$ ,  $p \in \text{poly}$  and an infinite set  $\mathcal{I} \subseteq 3\text{COL}$  s.t.

$$\left| \Pr[D(|x|, S^{V^*}(x)) = 1] - \Pr[D(|x|, S'^{V^*}(x)) = 1] \right| \geq 1/p(|x|)$$

for all  $x \in \mathcal{I}$ .

Hence,  $\exists$  PPT  $R^*$  and  $b \neq b' \in [3]$  such that

$$\{\text{View}_{R^*}(S(b), R^*(x))(1^{|x|})\}_{x \in \mathcal{I}} \not\approx_c \{\text{View}_{R^*}(S(b'), R^*(x))(1^{|x|})\}_{x \in \mathcal{I}}$$

where  $S$  is the sender in  $\text{Com}$ .

We critically used the non-uniform security of  $\text{Com}$

## $S'$ is a good simulator

### Claim 23

$\{(P(w_x), V^*)(x)\}_{x \in 3\text{COL}} \approx_c \{S'^{V^*}(x)\}_{x \in 3\text{COL}}$ , for any  $\{w_x \in R_{\text{GI}}(x)\}_{x \in 3\text{COL}}$ .

## $S'$ is a good simulator

### Claim 23

$\{(P(w_x), V^*)(x)\}_{x \in 3\text{COL}} \approx_c \{S'^{V^*(x)}(x)\}_{x \in 3\text{COL}}$ , for any  $\{w_x \in R_{\text{GI}}(x)\}_{x \in 3\text{COL}}$ .

Proof: ?

## Remarks

- Aborting verifiers
- Auxiliary inputs
- Soundness amplification

## Remarks

- Aborting verifiers
- Auxiliary inputs
- Soundness amplification
- Non-uniform hiding guarantee



## Extending to all $\mathcal{L} \in \text{NP}$

Let  $(P, V)$  be a CZKP for 3COL, and let  $\text{Map}_X$  and  $\text{Map}_W$  be two poly-time functions s.t.

- $\forall x \in \{0, 1\}^*: x \in \mathcal{L} \iff \text{Map}_X(x) \in \text{3COL},$
- $\forall x \in \mathcal{L} \text{ and } w \in R_L(x): \text{Map}_W(x, w) \in R_{\text{3COL}}(\text{Map}_X(x))$

## Extending to all $\mathcal{L} \in \text{NP}$

Let  $(P, V)$  be a CZKP for 3COL, and let  $\text{Map}_X$  and  $\text{Map}_W$  be two poly-time functions s.t.

- $\forall x \in \{0, 1\}^*: x \in \mathcal{L} \iff \text{Map}_X(x) \in 3\text{COL},$
- $\forall x \in \mathcal{L} \text{ and } w \in R_L(x): \text{Map}_W(x, w) \in R_{3\text{COL}}(\text{Map}_X(x))$

### Protocol 24 $((P_{\mathcal{L}}, V_{\mathcal{L}}))$

Common input:  $x \in \{0, 1\}^*$

$P_{\mathcal{L}}$ 's input:  $w \in R_L(x)$

- 1 The two parties interact in  $\langle (P(\text{Map}_W(x, w)), V(\text{Map}_X(x))) \rangle$ , where  $P_{\mathcal{L}}$  and  $V_{\mathcal{L}}$  taking the role of  $P$  and  $V$  respectively.
- 2  $V_{\mathcal{L}}$  accepts iff  $V$  accepts in the above execution.

Extending to NP

**Extending to all  $\mathcal{L} \in \text{NP}$  cont.****Claim 25**

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a CZKP for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

## Extending to all $\mathcal{L} \in \text{NP}$ cont.

### Claim 25

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a CZKP for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

- **Completeness and soundness:** Clear.

## Extending to all $\mathcal{L} \in \text{NP}$ cont.

### Claim 25

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a CZKP for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

- **Completeness and soundness:** Clear.
- **Zero knowledge:** Let  $S$  (an efficient) ZK simulator for  $(P, V)$  (for 3COL).  
Define  $S_{\mathcal{L}}(x)$  to output  $S(\text{Map}_X(x))$ , while replacing the string  $\text{Map}_X(x)$  in the output of  $S$  with  $x$ .

## Extending to all $\mathcal{L} \in \text{NP}$ cont.

### Claim 25

$(P_{\mathcal{L}}, V_{\mathcal{L}})$  is a CZKP for  $\mathcal{L}$  with the same completeness and soundness as  $(P, V)$  as for 3COL.

- **Completeness and soundness:** Clear.
- **Zero knowledge:** Let  $S$  (an efficient) ZK simulator for  $(P, V)$  (for 3COL).  
 Define  $S_{\mathcal{L}}(x)$  to output  $S(\text{Map}_X(x))$ , while replacing the string  $\text{Map}_X(x)$  in the output of  $S$  with  $x$ .  
 $\{(P(w_x), V^*)(x)\}_{x \in \mathcal{L}} \not\approx_c \{S_{\mathcal{L}}^{V^*(x)}(x)\}_{x \in \mathcal{L}}$  for some  $V_{\mathcal{L}}^*$ ,  
 implies  $\{(P(\text{Map}_W(x, w_x)), V^*)(x)\}_{x \in 3\text{COL}} \not\approx_c \{S^{V^*(x)}(x)\}_{x \in 3\text{COL}}$ ,
- $V^*(x)$ : find  $x^{-1} = \text{Map}_X^{-1}(x)$  and act like  $V_{\mathcal{L}}^*(x^{-1})$