

# Foundation of Cryptography, Lecture 11

## Black-Box Impossibility Results

Iftach Haitner, Tel Aviv University

Tel Aviv University.

June 10, 2014

## Motivating example: Basing Key-Agreement on OWFs

## Motivating example: Basing Key-Agreement on OWFs

- Key-Agreement protocols (KA) can be based on the existence of TDP, RSA or discrete log assumptions, and ...

## Motivating example: Basing Key-Agreement on OWFs

- Key-Agreement protocols (KA) can be based on the existence of TDP, RSA or discrete log assumptions, and ...
- We don't know how to base KA on the existence of OWFs/OWPs.

## Motivating example: Basing Key-Agreement on OWFs

- Key-Agreement protocols (KA) can be based on the existence of TDP, RSA or discrete log assumptions, and ...
- We don't know how to base KA on the existence of OWFs/OWPs.
- Can we base KA on OWFs/OWPs?

## Motivating example: Basing Key-Agreement on OWFs

- Key-Agreement protocols (KA) can be based on the existence of TDP, RSA or discrete log assumptions, and ...
- We don't know how to base KA on the existence of OWFs/OWPs.
- Can we base KA on OWFs/OWPs?
- Proving **unconditional** negative result seems beyond reach.

## Motivating example: Basing Key-Agreement on OWFs

- Key-Agreement protocols (KA) can be based on the existence of TDP, RSA or discrete log assumptions, and ...
- We don't know how to base KA on the existence of OWFs/OWPs.
- Can we base KA on OWFs/OWPs?
- Proving **unconditional** negative result seems beyond reach.  
Assume RSA assumption holds.

## Motivating example: Basing Key-Agreement on OWFs

- Key-Agreement protocols (KA) can be based on the existence of TDP, RSA or discrete log assumptions, and ...
- We don't know how to base KA on the existence of OWFs/OWPs.
- Can we base KA on OWFs/OWPs?
- Proving **unconditional** negative result seems beyond reach.

Assume RSA assumption holds.

⇒ key-agreement protocols exist.



## Motivating example: Basing Key-Agreement on OWFs

- Key-Agreement protocols (KA) can be based on the existence of TDP, RSA or discrete log assumptions, and ...
- We don't know how to base KA on the existence of OWFs/OWPs.
- Can we base KA on OWFs/OWPs?
- Proving **unconditional** negative result seems beyond reach.

Assume RSA assumption holds.

⇒ key-agreement protocols exist.

⇒ OWFs imply the existence of key-agreement protocols in a **trivial sense**.

# (Fully) Black-box constructions

## (Fully) Black-box constructions

### Definition 1 (A fully Black-box construction of $B$ from $A$ )


Black-box **construction**:

## (Fully) Black-box constructions

### Definition 1 (A fully Black-box construction of $B$ from $A$ )

Black-box **construction**:

A oracle-aided PPT  $I$  such that  $I^O$  implements  $B$  for any algorithm  $O$  implementing  $A$




## (Fully) Black-box constructions

### Definition 1 (A fully Black-box construction of $B$ from $A$ )

Black-box **construction**:

A oracle-aided PPT  $I$  such that  $I^O$  implements  $B$  for any algorithm  $O$  implementing  $A$




Black-box **proof of security**:

# (Fully) Black-box constructions

## Definition 1 (A fully Black-box construction of $B$ from $A$ )


Black-box **construction**:

A oracle-aided PPT  $I$  such that  $I^O$  implements  $B$  for any algorithm  $O$  implementing  $A$



Black-box **proof of security**:

A oracle-aided PPT  $R$  such that  $R^{O,D}$  breaks  $B$ , for any algorithms  $O$  implementing  $A$ , and  $D$  breaking  $B$ .




## (Fully) Black-box constructions

### Definition 1 (A fully Black-box construction of $B$ from $A$ )


Black-box **construction**:

A oracle-aided PPT  $I$  such that  $I^O$  implements  $B$  for any algorithm  $O$  implementing  $A$



Black-box **proof of security**:

A oracle-aided PPT  $R$  such that  $R^{O,D}$  breaks  $B$ , for any algorithms  $O$  implementing  $A$ , and  $D$  breaking  $B$ .




- Fully-black-box constructions relativize: hold relative to **any** oracle.

# (Fully) Black-box constructions

## Definition 1 (A fully Black-box construction of $B$ from $A$ )


Black-box **construction**:

A oracle-aided PPT  $I$  such that  $I^O$  implements  $B$  for any algorithm  $O$  implementing  $A$



Black-box **proof of security**:

A oracle-aided PPT  $R$  such that  $R^{O,D}$  breaks  $B$ , for any algorithms  $O$  implementing  $A$ , and  $D$  breaking  $B$ .



- Fully-black-box constructions relativize: hold relative to **any** oracle.
- Most constructions in cryptography are (fully) black-box, e.g., pseudorandom generator from OWF.




## (Fully) Black-box constructions

### Definition 1 (A fully Black-box construction of $B$ from $A$ )


Black-box **construction**:

A oracle-aided PPT  $I$  such that  $I^O$  implements  $B$  for any algorithm  $O$  implementing  $A$



Black-box **proof of security**:

A oracle-aided PPT  $R$  such that  $R^{O,D}$  breaks  $B$ , for any algorithms  $O$  implementing  $A$ , and  $D$  breaking  $B$ .



- Fully-black-box constructions relativize: hold relative to **any** oracle.
- Most constructions in cryptography are (fully) black-box, e.g., pseudorandom generator from OWF.
- Few “non black-box” techniques that apply in restricted settings (typically using ZK proofs)

# Approach for proving BB impossibility result

## Approach for proving BB impossibility result

Assume  $\exists$  fully-BB construction  $(I, R)$  of a KA from OWP.


## Approach for proving BB impossibility result

Assume  $\exists$  fully-BB construction  $(I, R)$  of a KA from OWP.




# Approach for proving BB impossibility result

Assume  $\exists$  fully-BB construction  $(I, R)$  of a KA from OWP.



# Approach for proving BB impossibility result


Assume  $\exists$  fully-BB construction  $(I, R)$  of a KA from OWP.



$I^\pi$  is an efficient KA protocol and  $R^{\pi,D}$  should invert  $\pi$  for any  $D$  breaking  $I^\pi$ .

# Approach for proving BB impossibility result

Assume  $\exists$  fully-BB construction  $(I, R)$  of a KA from OWP.




$I^\pi$  is an efficient KA protocol and  $R^{\pi, D}$  should invert  $\pi$  for any  $D$  breaking  $I^\pi$ .

Assume  $\exists$  (even inefficient) algorithm  $D$  that breaks **any** efficient KA with oracle access to  $\pi$ , but is **not useful** for inverting  $\pi$ .

# Approach for proving BB impossibility result

Assume  $\exists$  fully-BB construction  $(I, R)$  of a KA from OWP.



$I^\pi$  is an efficient KA protocol and  $R^{\pi, D}$  should invert  $\pi$  for any  $D$  breaking  $I^\pi$ .

Assume  $\exists$  (even inefficient) algorithm  $D$  that breaks **any** efficient KA with oracle access to  $\pi$ , but is **not useful** for inverting  $\pi$ .

This yields a contradiction, implying that  $(I, R)$  **does not exist**.



# Section 1

## **Random Permutations**

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .
- For integer  $b \geq a$ :  $a! \geq (\frac{a}{e})^a$  and  $\binom{b}{a} := \frac{b!}{(b-a)! \cdot a!} \leq (\frac{eb}{a})^a$

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .
- For integer  $b \geq a$ :  $a! \geq (\frac{a}{e})^a$  and  $\binom{b}{a} := \frac{b!}{(b-a)! \cdot a!} \leq (\frac{eb}{a})^a$
- For  $a = 2^{\alpha n}$ -size set  $\mathcal{S} \subseteq \{0, 1\}^n$ :



## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .
- For integer  $b \geq a$ :  $a! \geq (\frac{a}{e})^a$  and  $\binom{b}{a} := \frac{b!}{(b-a)! \cdot a!} \leq (\frac{eb}{a})^a$
- For  $a = 2^{\alpha n}$ -size set  $\mathcal{S} \subseteq \{0, 1\}^n$ :
  - ▶ It takes at most  $a \cdot ((1 - \alpha)n + O(1))$  bits to describe .

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .
- For integer  $b \geq a$ :  $a! \geq (\frac{a}{e})^a$  and  $\binom{b}{a} := \frac{b!}{(b-a)! \cdot a!} \leq (\frac{eb}{a})^a$
- For  $a = 2^{\alpha n}$ -size set  $\mathcal{S} \subseteq \{0, 1\}^n$ :
  - ▶ It takes at most  $a \cdot ((1 - \alpha)n + O(1))$  bits to describe .
  - ▶ It takes at least  $a(\alpha n - O(1))$  bits to describe a permutation over  $\mathcal{S}$ .

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .
- For integer  $b \geq a$ :  $a! \geq (\frac{a}{e})^a$  and  $\binom{b}{a} := \frac{b!}{(b-a)! \cdot a!} \leq (\frac{eb}{a})^a$
- For  $a = 2^{\alpha n}$ -size set  $\mathcal{S} \subseteq \{0, 1\}^n$ :
  - ▶ It takes at most  $a \cdot ((1 - \alpha)n + O(1))$  bits to describe .
  - ▶ It takes at least  $a(\alpha n - O(1))$  bits to describe a permutation over  $\mathcal{S}$ .
  - ▶ The latter is larger in for  $\alpha > \frac{1}{2}$ .

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .
- For integer  $b \geq a$ :  $a! \geq (\frac{a}{e})^a$  and  $\binom{b}{a} := \frac{b!}{(b-a)! \cdot a!} \leq (\frac{eb}{a})^a$
- For  $a = 2^{\alpha n}$ -size set  $\mathcal{S} \subseteq \{0, 1\}^n$ :
  - ▶ It takes at most  $a \cdot ((1 - \alpha)n + O(1))$  bits to describe .
  - ▶ It takes at least  $a(\alpha n - O(1))$  bits to describe a permutation over  $\mathcal{S}$ .
  - ▶ The latter is larger in for  $\alpha > \frac{1}{2}$ .
- We are in the number of  $M$ -size oracle-circuits .

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .
- For integer  $b \geq a$ :  $a! \geq (\frac{a}{e})^a$  and  $\binom{b}{a} := \frac{b!}{(b-a)! \cdot a!} \leq (\frac{eb}{a})^a$
- For  $a = 2^{\alpha n}$ -size set  $\mathcal{S} \subseteq \{0, 1\}^n$ :
  - ▶ It takes at most  $a \cdot ((1 - \alpha)n + O(1))$  bits to describe .
  - ▶ It takes at least  $a(\alpha n - O(1))$  bits to describe a permutation over  $\mathcal{S}$ .
  - ▶ The latter is larger in for  $\alpha > \frac{1}{2}$ .
- We are in the number of  $M$ -size oracle-circuits .

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .
- For integer  $b \geq a$ :  $a! \geq (\frac{a}{e})^a$  and  $\binom{b}{a} := \frac{b!}{(b-a)! \cdot a!} \leq (\frac{eb}{a})^a$
- For  $a = 2^{\alpha n}$ -size set  $\mathcal{S} \subseteq \{0, 1\}^n$ :
  - ▶ It takes at most  $a \cdot ((1 - \alpha)n + O(1))$  bits to describe .
  - ▶ It takes at least  $a(\alpha n - O(1))$  bits to describe a permutation over  $\mathcal{S}$ .
  - ▶ The latter is larger in for  $\alpha > \frac{1}{2}$ .
- We are in the number of  $M$ -size oracle-circuits .

### Claim 2

The number of  $M$ -size oracle-circuits mapping  $n$ -bit strings to  $n$ -bit strings, with oracle access to a function  $n$ -bit strings to  $n$ -bit strings, is at most  $2^{2M + (M+1)n(\log(Mn+n)+1)}$ .

## Before we begin

- Let  $\Pi_n$  — set of all permutations over  $\{0, 1\}^n$ , and let  $N = 2^n$ .
- $|\Pi_n| = N! \implies$  it takes  $\log(N!)$  bits to describe  $\pi \in \Pi_n$ .
- How many bits it takes to describe  $\mathcal{S} \subseteq \{0, 1\}^n$  of (known) size  $a$ ?  
There are  $\binom{N}{a}$  such sets, so it takes  $\log \binom{N}{a}$  bits to describe  $\mathcal{S}$ .
- For integer  $b \geq a$ :  $a! \geq (\frac{a}{e})^a$  and  $\binom{b}{a} := \frac{b!}{(b-a)! \cdot a!} \leq (\frac{eb}{a})^a$
- For  $a = 2^{\alpha n}$ -size set  $\mathcal{S} \subseteq \{0, 1\}^n$ :
  - ▶ It takes at most  $a \cdot ((1 - \alpha)n + O(1))$  bits to describe .
  - ▶ It takes at least  $a(\alpha n - O(1))$  bits to describe a permutation over  $\mathcal{S}$ .
  - ▶ The latter is larger in for  $\alpha > \frac{1}{2}$ .
- We are in the number of  $M$ -size oracle-circuits .

### Claim 2

The number of  $M$ -size oracle-circuits mapping  $n$ -bit strings to  $n$ -bit strings, with oracle access to a function  $n$ -bit strings to  $n$ -bit strings, is at most  $2^{2M + (M+1)n(\log(Mn+n)+1)}$ .

Proof: ?

# Random permutations are hard to invert

## Theorem 3 (Gennaro-Tevisan, '01 )

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}$ -query circuit  $D$ ,

$$\Pr_{\pi \leftarrow \Pi_n} \left[ \Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5} \right] \leq 2^{-2^{\frac{3}{5}n}/2}$$



# Random permutations are hard to invert

## Theorem 3 (Gennaro-Tevisan, '01 )

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}$ -query circuit  $D$ ,

$$\Pr_{\pi \leftarrow \Pi_n} \left[ \Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5} \right] \leq 2^{-2^{\frac{3}{5}n}/2}$$

- In words: Random permutations are (extremely) hard even for exponential-size circuits.

## Random permutations are hard to invert

### Theorem 3 (Gennaro-Tevisan, '01 )

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}$ -query circuit  $D$ ,

$$\Pr_{\pi \leftarrow \Pi_n} \left[ \Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5} \right] \leq 2^{-2^{\frac{3}{5}n}/2}$$

- In words: Random permutations are (extremely) hard even for exponential-size circuits.
- Constants are somewhat arbitrary and non tight.

# Random permutations are hard to invert

## Theorem 3 (Gennaro-Tevisan, '01 )

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}$ -query circuit  $D$ ,

$$\Pr_{\pi \leftarrow \Pi_n} \left[ \Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5} \right] \leq 2^{-2^{\frac{3}{5}n}/2}$$

- In words: Random permutations are (extremely) hard even for exponential-size circuits.
- Constants are somewhat arbitrary and non tight.
- By **Claim 2** the number of  $2^{n/5}$ -size circuits (of the right form) is bounded by  $2^{\tilde{O}(2^{n/5})}$ .

# Random permutations are hard to invert

## Theorem 3 (Gennaro-Tevisan, '01 )

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}$ -query circuit  $D$ ,

$$\Pr_{\pi \leftarrow \Pi_n} \left[ \Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5} \right] \leq 2^{-2^{\frac{3}{5}n}/2}$$

- In words: Random permutations are (extremely) hard even for exponential-size circuits.
- Constants are somewhat arbitrary and non tight.
- By **Claim 2** the number of  $2^{n/5}$ -size circuits (of the right form) is bounded by  $2^{\tilde{O}(2^{n/5})}$ .

# Random permutations are hard to invert

## Theorem 3 (Gennaro-Tevisan, '01 )

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}$ -query circuit  $D$ ,

$$\Pr_{\pi \leftarrow \Pi_n} \left[ \Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5} \right] \leq 2^{-2^{\frac{3}{5}n}/2}$$

- In words: Random permutations are (extremely) hard even for exponential-size circuits.
- Constants are somewhat arbitrary and non tight.
- By **Claim 2** the number of  $2^{n/5}$ -size circuits (of the right form) is bounded by  $2^{\tilde{O}(2^{n/5})}$ . Thus **Thm 3** yields that

$$\Pr_{\pi \leftarrow \Pi_n} \left[ \exists \text{ } 2^{n/5}\text{-size circuit } C \text{ with } \Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5} \right] \leq 2^{-2^{n/2}}$$

# Random permutations are hard to invert

## Theorem 3 (Gennaro-Tevisan, '01 )

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}$ -query circuit  $D$ ,

$$\Pr_{\pi \leftarrow \Pi_n} \left[ \Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5} \right] \leq 2^{-2^{3n/2}}$$

- In words: Random permutations are (extremely) hard even for exponential-size circuits.
- Constants are somewhat arbitrary and non tight.
- By Claim 2 the number of  $2^{n/5}$ -size circuits (of the right form) is bounded by  $2^{\tilde{O}(2^{n/5})}$ . Thus Thm 3 yields that

$$\Pr_{\pi \leftarrow \Pi_n} \left[ \exists 2^{n/5}\text{-size circuit } C \text{ with } \Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5} \right] \leq 2^{-2^{n/2}}$$

- In words: Random permutations are (extremely) hard **simultaneously**, for all exponential-size circuits.

## Proving GT theorem (Thm 3)

## Proving GT theorem (Thm 3)

### Lemma 4 (compression lemma)

For any  $q$ -query circuit  $D$  and  $\varepsilon > 0$ , exist algorithms  $\text{Enc}$  and  $\text{Dec}$  such that: Let  $\pi \in \Pi_n$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D^\pi(\pi(x)) = x] > \varepsilon$ , then

- $\text{Dec}(\text{Enc}(\pi)) = \pi$
- $|\text{Enc}(\pi)| \leq \log((2^n - a)!) + 2 \cdot \log \binom{N}{a}$ , for some  $a \geq \frac{\varepsilon N}{q+1}$ .



## Proving GT theorem (Thm 3)

### Lemma 4 (compression lemma)

For any  $q$ -query circuit  $D$  and  $\varepsilon > 0$ , exist algorithms  $\text{Enc}$  and  $\text{Dec}$  such that: Let  $\pi \in \Pi_n$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D^\pi(\pi(x)) = x] > \varepsilon$ , then

- $\text{Dec}(\text{Enc}(\pi)) = \pi$
- $|\text{Enc}(\pi)| \leq \log((2^n - a)!) + 2 \cdot \log \binom{N}{a}$ , for some  $a \geq \frac{\varepsilon N}{q+1}$ .
- The description of  $\pi$  using  $\text{Enc}(\pi)$  “saves”  $\log(a!) - \log \binom{N}{a}$  bits.

## Proving GT theorem (Thm 3)

### Lemma 4 (compression lemma)

For any  $q$ -query circuit  $D$  and  $\varepsilon > 0$ , exist algorithms  $\text{Enc}$  and  $\text{Dec}$  such that: Let  $\pi \in \Pi_n$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D^\pi(\pi(x)) = x] > \varepsilon$ , then

- $\text{Dec}(\text{Enc}(\pi)) = \pi$
  - $|\text{Enc}(\pi)| \leq \log((2^n - a)!) + 2 \cdot \log \binom{N}{a}$ , for some  $a \geq \frac{\varepsilon N}{q+1}$ .
- 
- The description of  $\pi$  using  $\text{Enc}(\pi)$  “saves”  $\log(a!) - \log \binom{N}{a}$  bits.
  - Let  $D$  be a  $2^{n/5}$ -query circuit.

## Proving GT theorem (Thm 3)

### Lemma 4 (compression lemma)

For any  $q$ -query circuit  $D$  and  $\varepsilon > 0$ , exist algorithms  $\text{Enc}$  and  $\text{Dec}$  such that: Let  $\pi \in \Pi_n$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D^\pi(\pi(x)) = x] > \varepsilon$ , then

- $\text{Dec}(\text{Enc}(\pi)) = \pi$
  - $|\text{Enc}(\pi)| \leq \log((2^n - a)!) + 2 \cdot \log \binom{N}{a}$ , for some  $a \geq \frac{\varepsilon N}{q+1}$ .
- 
- The description of  $\pi$  using  $\text{Enc}(\pi)$  “saves”  $\log(a!) - \log \binom{N}{a}$  bits.
  - Let  $D$  be a  $2^{n/5}$ -query circuit.

## Proving GT theorem (Thm 3)

### Lemma 4 (compression lemma)

For any  $q$ -query circuit  $D$  and  $\varepsilon > 0$ , exist algorithms  $\text{Enc}$  and  $\text{Dec}$  such that: Let  $\pi \in \Pi_n$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D^\pi(\pi(x)) = x] > \varepsilon$ , then

- $\text{Dec}(\text{Enc}(\pi)) = \pi$
- $|\text{Enc}(\pi)| \leq \log((2^n - a)!) + 2 \cdot \log \binom{N}{a}$ , for some  $a \geq \frac{\varepsilon N}{q+1}$ .

- The description of  $\pi$  using  $\text{Enc}(\pi)$  “saves”  $\log(a!) - \log \binom{N}{a}$  bits.
- Let  $D$  be a  $2^{n/5}$ -query circuit. Lemma 4 yields that the fraction of  $\pi \in \Pi_n$  with  $\Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5}$ , is (for large enough  $n$ ) at most

$$\frac{(N - 2^{\frac{3}{5}n})! \cdot \left(\frac{N}{2^{\frac{3}{5}n}}\right)^2}{N!} = \frac{\left(\frac{N}{2^{\frac{3}{5}n}}\right)}{2^{\frac{3}{5}n}!} \leq 2^{-2^{\frac{3}{5}n}/2},$$

## Proving GT theorem (Thm 3)

### Lemma 4 (compression lemma)

For any  $q$ -query circuit  $D$  and  $\varepsilon > 0$ , exist algorithms  $\text{Enc}$  and  $\text{Dec}$  such that: Let  $\pi \in \Pi_n$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D^\pi(\pi(x)) = x] > \varepsilon$ , then

- $\text{Dec}(\text{Enc}(\pi)) = \pi$
- $|\text{Enc}(\pi)| \leq \log((2^n - a)!) + 2 \cdot \log \binom{N}{a}$ , for some  $a \geq \frac{\varepsilon N}{q+1}$ .

- The description of  $\pi$  using  $\text{Enc}(\pi)$  “saves”  $\log(a!) - \log \binom{N}{a}$  bits.
- Let  $D$  be a  $2^{n/5}$ -query circuit. Lemma 4 yields that the fraction of  $\pi \in \Pi_n$  with  $\Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > 2^{-n/5}$ , is (for large enough  $n$ ) at most

$$\frac{(N - 2^{\frac{3}{5}n})! \cdot \left(\frac{N}{2^{\frac{3}{5}n}}\right)^2}{N!} = \frac{\left(\frac{N}{2^{\frac{3}{5}n}}\right)}{2^{\frac{3}{5}n}!} \leq 2^{-2^{\frac{3}{5}n}/2},$$

proving Thm 3.

## Proving Compression Lemma (Lemma 4)

Let  $D$  be  $q$ -query circuit, and let  $\pi$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > \varepsilon$ .

## Proving Compression Lemma (Lemma 4)

Let  $D$  be  $q$ -query circuit, and let  $\pi$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > \varepsilon$ .

### Construction 5 (Useful set $\mathcal{Y} \subseteq \{0,1\}^n$ )

- 1 Set  $\mathcal{Y} = \emptyset$  and  $\mathcal{I} = \{y \in \{0,1\}^n : D^\pi(\pi(x)) = \pi\}$ .
- 2 While  $\mathcal{I} \neq \emptyset$ , let  $y$  be the smallest lexicographic element in  $\mathcal{I}$ .
  - (a) Add  $y$  to  $\mathcal{Y}$ .
  - (b) Remove  $y$  and all  $\pi$ -queries  $D^\pi(y)$  makes, from  $\mathcal{I}$ .

## Proving Compression Lemma (Lemma 4)

Let  $D$  be  $q$ -query circuit, and let  $\pi$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > \varepsilon$ .

### Construction 5 (Useful set $\mathcal{Y} \subseteq \{0,1\}^n$ )

- 1 Set  $\mathcal{Y} = \emptyset$  and  $\mathcal{I} = \{y \in \{0,1\}^n : D^\pi(\pi(x)) = \pi\}$ .
- 2 While  $\mathcal{I} \neq \emptyset$ , let  $y$  be the smallest lexicographic element in  $\mathcal{I}$ .
  - (a) Add  $y$  to  $\mathcal{Y}$ .
  - (b) Remove  $y$  and all  $\pi$ -queries  $D^\pi(y)$  makes, from  $\mathcal{I}$ .

### Algorithm 6 ( $\text{Enc}(\pi)$ )

Output (description of)  $\mathcal{Y}$  and  $\mathcal{V} = \{(x, \pi(x)) : \pi(x) \notin \mathcal{Y}\}$ .



## Proving Compression Lemma (Lemma 4)

Let  $D$  be  $q$ -query circuit, and let  $\pi$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > \varepsilon$ .

### Construction 5 (Useful set $\mathcal{Y} \subseteq \{0,1\}^n$ )

- 1 Set  $\mathcal{Y} = \emptyset$  and  $\mathcal{I} = \{y \in \{0,1\}^n : D^\pi(\pi(x)) = \pi\}$ .
- 2 While  $\mathcal{I} \neq \emptyset$ , let  $y$  be the smallest lexicographic element in  $\mathcal{I}$ .
  - (a) Add  $y$  to  $\mathcal{Y}$ .
  - (b) Remove  $y$  and all  $\pi$ -queries  $D^\pi(y)$  makes, from  $\mathcal{I}$ .

### Algorithm 6 ( $\text{Enc}(\pi)$ )

Output (description of)  $\mathcal{Y}$  and  $\mathcal{V} = \{(x, \pi(x)) : \pi(x) \notin \mathcal{Y}\}$ .

(Under proper encoding)  $|\text{Enc}(\pi)| \leq \log((N - a)!) + 2 \cdot \log \binom{N}{a}$  for  $a = |\mathcal{Y}| \geq \frac{\varepsilon N}{q+1}$ .

## Proving Compression Lemma (Lemma 4)

Let  $D$  be  $q$ -query circuit, and let  $\pi$  be such that  $\Pr_{x \leftarrow \{0,1\}^n} [D(\pi(x)) = x] > \varepsilon$ .

### Construction 5 (Useful set $\mathcal{Y} \subseteq \{0,1\}^n$ )

- 1 Set  $\mathcal{Y} = \emptyset$  and  $\mathcal{I} = \{y \in \{0,1\}^n : D^\pi(\pi(x)) = \pi\}$ .
- 2 While  $\mathcal{I} \neq \emptyset$ , let  $y$  be the smallest lexicographic element in  $\mathcal{I}$ .
  - (a) Add  $y$  to  $\mathcal{Y}$ .
  - (b) Remove  $y$  and all  $\pi$ -queries  $D^\pi(y)$  makes, from  $\mathcal{I}$ .

### Algorithm 6 ( $\text{Enc}(\pi)$ )

Output (description of)  $\mathcal{Y}$  and  $\mathcal{V} = \{(x, \pi(x)) : \pi(x) \notin \mathcal{Y}\}$ .

(Under proper encoding)  $|\text{Enc}(\pi)| \leq \log((N - a)!) + 2 \cdot \log \binom{N}{a}$  for  $a = |\mathcal{Y}| \geq \frac{\varepsilon N}{q+1}$ .

### Algorithm 7 ( $\text{Dec}(\mathcal{Y}, \mathcal{V})$ )

For all  $y \in \mathcal{Y}$  in lex. order:

- 1 Emulate  $D^\pi(y)$ .
- 2 If  $D$  makes a  $\pi$ -query  $x$  that is undefined in  $\mathcal{V}$ , add  $(x, y)$  to  $\mathcal{V}$ .  
Otherwise, add  $(D^{\pi, \text{Sam}_r^\pi}(y), y)$  to  $\mathcal{V}$ .

Use  $\mathcal{V}$  to reconstruct  $\pi$ .

## Remarks

- The short description argument is an incredibly useful paradigm (see next).

## Remarks

- The short description argument is an incredibly useful paradigm (see next).
- Immediately yields same result for **algorithms** (replacing size with running time).

## Remarks

- The short description argument is an incredibly useful paradigm (see next).
- Immediately yields same result for **algorithms** (replacing size with running time).
- Alternative compression argument.

- The short description argument is an incredibly useful paradigm (see next).
- Immediately yields same result for **algorithms** (replacing size with running time).
- Alternative compression argument.
- Similar results can be proven for random variants of OWF, TDP, CRH.

## Section 2

# **BB Impossibility for Efficient OWF based PRG**

# BB Impossibility for OWF based PRG

## Definition 8 (pseudorandom generators (PRGs))

Poly-time  $G: \{0, 1\}^n \mapsto \{0, 1\}^{\ell(n)}$  is a **pseudorandom generator**, if

- $G$  is length extending (i.e.,  $\ell(n) > n$  for any  $n$ )
- $G(U_n)$  is pseudorandom (i.e.,  $\{G(U_n)\}_{n \in \mathbb{N}} \approx_c \{U_{\ell(n)}\}_{n \in \mathbb{N}}$ )



## BB Impossibility for OWF based PRG

### Definition 8 (pseudorandom generators (PRGs))

Poly-time  $G: \{0, 1\}^n \mapsto \{0, 1\}^{\ell(n)}$  is a **pseudorandom generator**, if

- $G$  is length extending (i.e.,  $\ell(n) > n$  for any  $n$ )
- $G(U_n)$  is pseudorandom (i.e.,  $\{G(U_n)\}_{n \in \mathbb{N}} \approx_c \{U_{\ell(n)}\}_{n \in \mathbb{N}}$ )

We focus on BB constructions of efficient length-doubling PRGs.

# BB Impossibility for OWF based PRG

## Definition 8 (pseudorandom generators (PRGs))

Poly-time  $G: \{0, 1\}^n \mapsto \{0, 1\}^{\ell(n)}$  is a **pseudorandom generator**, if

- $G$  is length extending (i.e.,  $\ell(n) > n$  for any  $n$ )
- $G(U_n)$  is pseudorandom (i.e.,  $\{G(U_n)\}_{n \in \mathbb{N}} \approx_c \{U_{\ell(n)}\}_{n \in \mathbb{N}}$ )

We focus on BB constructions of efficient length-doubling PRGs.

## Theorem 9

*In any fully-BB construction of length-doubling PRG over  $n$ -bits string from OWP over  $\{0, 1\}^n$ , the construction makes  $\Omega(n/\log n)$  oracle calls.*

# BB Impossibility for OWF based PRG

## Definition 8 (pseudorandom generators (PRGs))

Poly-time  $G: \{0, 1\}^n \mapsto \{0, 1\}^{\ell(n)}$  is a **pseudorandom generator**, if

- $G$  is length extending (i.e.,  $\ell(n) > n$  for any  $n$ )
- $G(U_n)$  is pseudorandom (i.e.,  $\{G(U_n)\}_{n \in \mathbb{N}} \approx_c \{U_{\ell(n)}\}_{n \in \mathbb{N}}$ )

We focus on BB constructions of efficient length-doubling PRGs.

## Theorem 9

*In any fully-BB construction of length-doubling PRG over  $n$ -bits string from OWP over  $\{0, 1\}^n$ , the construction makes  $\Omega(n/\log n)$  oracle calls.*

- Matches known upper bounds.

# BB Impossibility for OWF based PRG

## Definition 8 (pseudorandom generators (PRGs))

Poly-time  $G: \{0, 1\}^n \mapsto \{0, 1\}^{\ell(n)}$  is a **pseudorandom generator**, if

- $G$  is length extending (i.e.,  $\ell(n) > n$  for any  $n$ )
- $G(U_n)$  is pseudorandom (i.e.,  $\{G(U_n)\}_{n \in \mathbb{N}} \approx_c \{U_{\ell(n)}\}_{n \in \mathbb{N}}$ )

We focus on BB constructions of efficient length-doubling PRGs.

## Theorem 9

*In any fully-BB construction of length-doubling PRG over  $n$ -bits string from OWP over  $\{0, 1\}^n$ , the construction makes  $\Omega(n/\log n)$  oracle calls.*

- Matches known upper bounds.
- Without the restriction on the OWP input length, yields an optimal  $n^{\Omega(1)} / \log n$  bound.

# Proving Thm 9

## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

We assume wlg. that  $I$  makes distinct queries.(?)



## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

We assume wlg. that  $I$  makes distinct queries.(?)

- For  $t = t(n) = \lceil n/2q(n) \rceil$ , consider the following generator  
 $G: \{0, 1\}^{\frac{3}{2}n} \mapsto \{0, 1\}^{2n}$ :

## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

We assume wlg. that  $I$  makes distinct queries.(?)

- For  $t = t(n) = \lceil n/2q(n) \rceil$ , consider the following generator  
 $G: \{0, 1\}^{\frac{3}{2}n} \mapsto \{0, 1\}^{2n}$ :

### Algorithm 10 ( $G(x)$ )

## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

We assume wlg. that  $I$  makes distinct queries. (?)

- For  $t = t(n) = \lceil n/2q(n) \rceil$ , consider the following generator  
 $G: \{0, 1\}^{\frac{3}{2}n} \mapsto \{0, 1\}^{2n}$ :

### Algorithm 10 ( $G(x)$ )

- Emulate  $C^\pi(x_1, \dots, x_n)$ , while answering the  $i$ 'th query  $z$  of  $I$  to  $\pi$ , with  $x_{n+i \cdot t+1, \dots, n+(i+1) \cdot t} \circ z_{t+1, \dots, n}$ .

## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

We assume wlg. that  $I$  makes distinct queries.(?)

- For  $t = t(n) = \lceil n/2q(n) \rceil$ , consider the following generator  
 $G: \{0, 1\}^{\frac{3}{2}n} \mapsto \{0, 1\}^{2n}$ :

### Algorithm 10 ( $G(x)$ )

- Emulate  $C^\pi(x_1, \dots, x_n)$ , while answering the  $i$ 'th query  $z$  of  $I$  to  $\pi$ , with  $x_{n+i \cdot t+1}, \dots, x_{n+(i+1) \cdot t} \circ z_{t+1}, \dots, z_n$ .
- Output the same output that  $I$  does.

## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

We assume wlg. that  $I$  makes distinct queries.(?)

- For  $t = t(n) = \lceil n/2q(n) \rceil$ , consider the following generator  
 $G: \{0, 1\}^{\frac{3}{2}n} \mapsto \{0, 1\}^{2n}$ :

### Algorithm 10 ( $G(x)$ )

- Emulate  $C^\pi(x_1, \dots, x_n)$ , while answering the  $i$ 'th query  $z$  of  $I$  to  $\pi$ , with  $x_{n+i \cdot t+1, \dots, n+(i+1) \cdot t} \circ z_{t+1, \dots, n}$ .
  - Output the same output that  $I$  does.
- Let  $\Pi_{n,t}$  be the set of all permutations over  $\{0, 1\}^n$  that are **identity** over the last  $n - t$  bits (i.e.,  $\pi(x)_{n-t+1, \dots, n} = x_{n-t+1, \dots, n}$ ).

## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

We assume wlg. that  $I$  makes distinct queries.(?)

- For  $t = t(n) = \lceil n/2q(n) \rceil$ , consider the following generator  
 $G: \{0, 1\}^{\frac{3}{2}n} \mapsto \{0, 1\}^{2n}$ :

### Algorithm 10 ( $G(x)$ )

- Emulate  $C^\pi(x_1, \dots, n)$ , while answering the  $i$ 'th query  $z$  of  $I$  to  $\pi$ , with  $x_{n+i \cdot t+1, \dots, n+(i+1) \cdot t} \circ z_{t+1, \dots, n}$ .
  - Output the same output that  $I$  does.
- Let  $\Pi_{n,t}$  be the set of all permutations over  $\{0, 1\}^n$  that are **identity** over the last  $n - t$  bits (i.e.,  $\pi(x)_{n-t+1, \dots, n} = x_{n-t+1, \dots, n}$ ).

## Proving Thm 9

- Let  $(I, R)$  be a fully-BB reduction of a  $q(n) \in o(n/\log n)$ -query, length-doubling PRG over  $\{0, 1\}^n$ , to OWP over  $\{0, 1\}^n$ .

We assume wlg. that  $I$  makes distinct queries.(?)

- For  $t = t(n) = \lceil n/2q(n) \rceil$ , consider the following generator  
 $G: \{0, 1\}^{\frac{3}{2}n} \mapsto \{0, 1\}^{2n}$ :

### Algorithm 10 ( $G(x)$ )

- Emulate  $C^\pi(x_1, \dots, n)$ , while answering the  $i$ 'th query  $z$  of  $I$  to  $\pi$ , with  $x_{n+i \cdot t+1, \dots, n+(i+1) \cdot t} \circ z_{t+1, \dots, n}$ .
  - Output the same output that  $I$  does.
- Let  $\Pi_{n,t}$  be the set of all permutations over  $\{0, 1\}^n$  that are identity over the last  $n - t$  bits (i.e.,  $\pi(x)_{n-t+1, \dots, n} = x_{n-t+1, \dots, n}$ ).

### Claim 11

$$G(U_{3n/2}) \equiv (I^\pi(U_n))_{\pi \leftarrow \Pi_{n,t}}.$$

## Proving Thm 9, cont.



## Proving Thm 9, cont.

- $\exists$  algorithm  $D$  that distinguishes  $G(U_{3n/2})$  from  $U_{2n}$  with advantage  $1 - 2^{-n/4} > \frac{1}{2}$ . (?)

## Proving Thm 9, cont.

- $\exists$  algorithm  $D$  that distinguishes  $G(U_{3n/2})$  from  $U_{2n}$  with advantage  $1 - 2^{-n/4} > \frac{1}{2}$ . (?)

$$\implies \text{wlg. } \Pr_{\pi \leftarrow \Pi_{t,n}} [D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{2}$$

## Proving Thm 9, cont.

- $\exists$  algorithm  $D$  that distinguishes  $G(U_{3n/2})$  from  $U_{2n}$  with advantage  $1 - 2^{-n/4} > \frac{1}{2}$ . (?)

$$\implies \text{wlg. } \Pr_{\pi \leftarrow \Pi_{t,n}} [D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{2}$$

$$\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [\Pr[D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{4}] \geq \frac{1}{4}$$

## Proving Thm 9, cont.

- $\exists$  algorithm  $D$  that distinguishes  $G(U_{3n/2})$  from  $U_{2n}$  with advantage  $1 - 2^{-n/4} > \frac{1}{2}$ . (?)

$$\implies \text{wlg. } \Pr_{\pi \leftarrow \Pi_{t,n}} [D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{2}$$

$$\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [\Pr[D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{4}] \geq \frac{1}{4}$$

$$\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [R^{\pi,D} \text{ inverts } \pi \text{ with non-negligible prob.}] \geq \frac{1}{4}$$

## Proving Thm 9, cont.

- $\exists$  algorithm  $D$  that distinguishes  $G(U_{3n/2})$  from  $U_{2n}$  with advantage  $1 - 2^{-n/4} > \frac{1}{2}$ . (?)
  - $\implies$  wlg.  $\Pr_{\pi \leftarrow \Pi_{t,n}} [D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{2}$
  - $\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [\Pr[D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{4}] \geq \frac{1}{4}$
  - $\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [R^{\pi,D} \text{ inverts } \pi \text{ with non-negligible prob.}] \geq \frac{1}{4}$
- Let  $n' = t(n) \in \omega(\log n)$ .

## Proving Thm 9, cont.

- $\exists$  algorithm  $D$  that distinguishes  $G(U_{3n/2})$  from  $U_{2n}$  with advantage  $1 - 2^{-n/4} > \frac{1}{2}$ . (?)

$$\implies \text{wlg. } \Pr_{\pi \leftarrow \Pi_{t,n}} [D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{2}$$

$$\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [\Pr[D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{4}] \geq \frac{1}{4}$$

$$\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [R^{\pi,D} \text{ inverts } \pi \text{ with non-negligible prob.}] \geq \frac{1}{4}$$

- Let  $n' = t(n) \in \omega(\log n)$ .
- By the above, exists  $2^{o(n')}$ -query circuit  $R'$ , such that

$$\Pr_{\pi \leftarrow \Pi_{n'}} [R'^{\pi} \text{ inverts } \pi \text{ with non-negligible prob.}] \geq \frac{1}{4},$$

## Proving Thm 9, cont.

- $\exists$  algorithm  $D$  that distinguishes  $G(U_{3n/2})$  from  $U_{2n}$  with advantage  $1 - 2^{-n/4} > \frac{1}{2}$ . (?)

$$\implies \text{wlg. } \Pr_{\pi \leftarrow \Pi_{t,n}} [D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{2}$$

$$\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [\Pr[D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{4}] \geq \frac{1}{4}$$

$$\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [R^{\pi,D} \text{ inverts } \pi \text{ with non-negligible prob.}] \geq \frac{1}{4}$$

- Let  $n' = t(n) \in \omega(\log n)$ .
- By the above, exists  $2^{o(n')}$ -query circuit  $R'$ , such that

$$\Pr_{\pi \leftarrow \Pi_{n'}} [R'^{\pi} \text{ inverts } \pi \text{ with non-negligible prob.}] \geq \frac{1}{4},$$

## Proving Thm 9, cont.

- $\exists$  algorithm  $D$  that distinguishes  $G(U_{3n/2})$  from  $U_{2n}$  with advantage  $1 - 2^{-n/4} > \frac{1}{2}$ . (?)

$$\implies \text{wlg. } \Pr_{\pi \leftarrow \Pi_{t,n}} [D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{2}$$

$$\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [\Pr[D(I^\pi(U_n)) = 1] - \Pr[D(U_{2n}) = 1] > \frac{1}{4}] \geq \frac{1}{4}$$

$$\implies \Pr_{\pi \leftarrow \Pi_{t,n}} [R^{\pi,D} \text{ inverts } \pi \text{ with non-negligible prob.}] \geq \frac{1}{4}$$

- Let  $n' = t(n) \in \omega(\log n)$ .
- By the above, exists  $2^{o(n')}$ -query circuit  $R'$ , such that

$$\Pr_{\pi \leftarrow \Pi_{n'}} [R'^\pi \text{ inverts } \pi \text{ with non-negligible prob.}] \geq \frac{1}{4},$$

in contradiction to Thm 3.



## Remarks

- We showed a lower bound on the efficiency of fully-BB constructions of length-doubling PRG from OWPs.

## Remarks

- We showed a lower bound on the efficiency of fully-BB constructions of length-doubling PRG from OWPs.
- Actually we ruled out a **less restricted** type of BB-construction, called **weakly-BB construction**:  
If  $\mathcal{O}$  is a secure implementation of  $A$ , then  $I^{\mathcal{O}}$  is a secure implementation of  $B$  against adversaries with no access direct to  $\mathcal{O}$ .

## Remarks

- We showed a lower bound on the efficiency of fully-BB constructions of length-doubling PRG from OWPs.
- Actually we ruled out a **less restricted** type of BB-construction, called **weakly-BB construction**:  
If  $\mathcal{O}$  is a secure implementation of  $A$ , then  $I^{\mathcal{O}}$  is a secure implementation of  $B$  against adversaries with no access direct to  $\mathcal{O}$ .
- Results can be easily extended to OWFs/TDPs.

## Remarks

- We showed a lower bound on the efficiency of fully-BB constructions of length-doubling PRG from OWPs.
- Actually we ruled out a **less restricted** type of BB-construction, called **weakly-BB construction**:  
If  $\mathcal{O}$  is a secure implementation of  $A$ , then  $I^{\mathcal{O}}$  is a secure implementation of  $B$  against adversaries with no access direct to  $\mathcal{O}$ .
- Results can be easily extended to OWFs/TDPs.
- Using similar means, one can prove lower bound on fully-BB constructions of encryption schemes, signature schemes and universal-one-way-hash-functions (UOWHFs), from OWFs/OWPs/TDPs

## Section 3

# **BB Impossibility for Basing CRH on OWF**

## Basing CRH on OWF

### Definition 12 (collision resistant hash family (CRH))

A function family  $\mathcal{H} = \{\mathcal{H}_n: \{0, 1\}^* \mapsto \{0, 1\}^n\}$  is **collision resistant**, if

$$\Pr_{\substack{h \leftarrow \mathcal{H}_n \\ (x, x') \leftarrow A(1^n, h)}} [x \neq x' \in \{0, 1\}^* \wedge h(x) = h(x')] = \text{neg}(n)$$

for any PPT  $A$ .

## Basing CRH on OWF

### Definition 12 (collision resistant hash family (CRH))

A function family  $\mathcal{H} = \{\mathcal{H}_n: \{0, 1\}^* \mapsto \{0, 1\}^n\}$  is **collision resistant**, if

$$\Pr_{\substack{h \leftarrow \mathcal{H}_n \\ (x, x') \leftarrow A(1^n, h)}} [x \neq x' \in \{0, 1\}^* \wedge h(x) = h(x')] = \text{neg}(n)$$

for any PPT  $A$ .

- In a BB construction of CRH family, both the sampling and evaluation algorithms makes use of the oracle.

## Basing CRH on OWF

### Definition 12 (collision resistant hash family (CRH))

A function family  $\mathcal{H} = \{\mathcal{H}_n: \{0, 1\}^* \mapsto \{0, 1\}^n\}$  is **collision resistant**, if

$$\Pr_{\substack{h \leftarrow \mathcal{H}_n \\ (x, x') \leftarrow A(1^n, h)}} [x \neq x' \in \{0, 1\}^* \wedge h(x) = h(x')] = \text{neg}(n)$$

for any PPT  $A$ .

- In a BB construction of CRH family, both the sampling and evaluation algorithms makes use of the oracle.
- wlg. the sampling algorithm outputs a string  $h$ , **independent** of the oracle, and  $h \in \mathcal{H}_n$  is an oracle circuit.



## Basing CRH on OWF

### Definition 12 (collision resistant hash family (CRH))

A function family  $\mathcal{H} = \{\mathcal{H}_n: \{0, 1\}^* \mapsto \{0, 1\}^n\}$  is **collision resistant**, if

$$\Pr_{\substack{h \leftarrow \mathcal{H}_n \\ (x, x') \leftarrow A(1^n, h)}} [x \neq x' \in \{0, 1\}^* \wedge h(x) = h(x')] = \text{neg}(n)$$

for any PPT  $A$ .

- In a BB construction of CRH family, both the sampling and evaluation algorithms makes use of the oracle.
- wlg. the sampling algorithm outputs a string  $h$ , **independent** of the oracle, and  $h \in \mathcal{H}_n$  is an oracle circuit.
- For simplicity, assume that  $h \in \mathcal{H}_n$  only queries the oracle on inputs of length  $n$ .

## Basing CRH on OWF

### Definition 12 (collision resistant hash family (CRH))

A function family  $\mathcal{H} = \{\mathcal{H}_n: \{0, 1\}^* \mapsto \{0, 1\}^n\}$  is **collision resistant**, if

$$\Pr_{\substack{h \leftarrow \mathcal{H}_n \\ (x, x') \leftarrow A(1^n, h)}} [x \neq x' \in \{0, 1\}^* \wedge h(x) = h(x')] = \text{neg}(n)$$

for any PPT  $A$ .

- In a BB construction of CRH family, both the sampling and evaluation algorithms makes use of the oracle.
- wlg. the sampling algorithm outputs a string  $h$ , **independent** of the oracle, and  $h \in \mathcal{H}_n$  is an oracle circuit.
- For simplicity, assume that  $h \in \mathcal{H}_n$  only queries the oracle on inputs of length  $n$ .

## Basing CRH on OWF

### Definition 12 (collision resistant hash family (CRH))

A function family  $\mathcal{H} = \{\mathcal{H}_n: \{0, 1\}^* \mapsto \{0, 1\}^n\}$  is **collision resistant**, if

$$\Pr_{\substack{h \leftarrow \mathcal{H}_n \\ (x, x') \leftarrow A(1^n, h)}} [x \neq x' \in \{0, 1\}^* \wedge h(x) = h(x')] = \text{neg}(n)$$

for any PPT  $A$ .

- In a BB construction of CRH family, both the sampling and evaluation algorithms makes use of the oracle.
- wlg. the sampling algorithm outputs a string  $h$ , **independent** of the oracle, and  $h \in \mathcal{H}_n$  is an oracle circuit.
- For simplicity, assume that  $h \in \mathcal{H}_n$  only queries the oracle on inputs of length  $n$ .

### Theorem 13

*There exists no fully BB-construction of CRH from OWP.*

## Basing CRH on OWF

### Definition 12 (collision resistant hash family (CRH))

A function family  $\mathcal{H} = \{\mathcal{H}_n: \{0, 1\}^* \mapsto \{0, 1\}^n\}$  is **collision resistant**, if

$$\Pr_{\substack{h \leftarrow \mathcal{H}_n \\ (x, x') \leftarrow A(1^n, h)}} [x \neq x' \in \{0, 1\}^* \wedge h(x) = h(x')] = \text{neg}(n)$$

for any PPT  $A$ .

- In a BB construction of CRH family, both the sampling and evaluation algorithms makes use of the oracle.
- wlg. the sampling algorithm outputs a string  $h$ , **independent** of the oracle, and  $h \in \mathcal{H}_n$  is an oracle circuit.
- For simplicity, assume that  $h \in \mathcal{H}_n$  only queries the oracle on inputs of length  $n$ .

### Theorem 13

*There exists no fully BB-construction of CRH from OWF.*

- Seems harder to prove:

## Basing CRH on OWF

### Definition 12 (collision resistant hash family (CRH))

A function family  $\mathcal{H} = \{\mathcal{H}_n: \{0, 1\}^* \mapsto \{0, 1\}^n\}$  is **collision resistant**, if

$$\Pr_{\substack{h \leftarrow \mathcal{H}_n \\ (x, x') \leftarrow A(1^n, h)}} [x \neq x' \in \{0, 1\}^* \wedge h(x) = h(x')] = \text{neg}(n)$$

for any PPT  $A$ .

- In a BB construction of CRH family, both the sampling and evaluation algorithms makes use of the oracle.
- wlg. the sampling algorithm outputs a string  $h$ , **independent** of the oracle, and  $h \in \mathcal{H}_n$  is an oracle circuit.
- For simplicity, assume that  $h \in \mathcal{H}_n$  only queries the oracle on inputs of length  $n$ .

### Theorem 13

*There exists no fully BB-construction of CRH from OWF.*

- Seems harder to prove:

## Basing CRH on OWF

### Definition 12 (collision resistant hash family (CRH))

A function family  $\mathcal{H} = \{\mathcal{H}_n: \{0, 1\}^* \mapsto \{0, 1\}^n\}$  is **collision resistant**, if

$$\Pr_{\substack{h \leftarrow \mathcal{H}_n \\ (x, x') \leftarrow A(1^n, h)}} [x \neq x' \in \{0, 1\}^* \wedge h(x) = h(x')] = \text{neg}(n)$$

for any PPT **A**.

- In a BB construction of CRH family, both the sampling and evaluation algorithms makes use of the oracle.
- wlg. the sampling algorithm outputs a string  $h$ , **independent** of the oracle, and  $h \in \mathcal{H}_n$  is an oracle circuit.
- For simplicity, assume that  $h \in \mathcal{H}_n$  only queries the oracle on inputs of length  $n$ .

### Theorem 13

*There exists no fully BB-construction of CRH from OWF.*

- Seems harder to prove: CRH exists relative to random permutations!

# Proving Thm 13

## Proving Thm 13

Fix  $n \in \mathbb{N}$ .



## Proving Thm 13

Fix  $n \in \mathbb{N}$ .

We construct an (inefficient) algorithm Sam, that finds collision in any CRH, but non-useful for inverting random permutation.

## Proving Thm 13

Fix  $n \in \mathbb{N}$ .

We construct an (inefficient) algorithm **Sam**, that finds collision in **any** CRH, but **non-useful** for inverting random permutation.

### Algorithm 14 ( $\text{Sam}^\pi$ )

Input: An  $n$ -bit input circuit  $C$ .

Oracle:  $\pi \in \Pi_n$ .

- 1 Sample  $x \leftarrow \{0, 1\}^n$ .
- 2 Find the first (in a random order) random  $x' \in \{0, 1\}^n$  with  $C^\pi(x) = C^\pi(x')$ .
- 3 Return  $(x, x')$ .

## Proving Thm 13

Fix  $n \in \mathbb{N}$ .

We construct an (inefficient) algorithm **Sam**, that finds collision in **any** CRH, but **non-useful** for inverting random permutation.

### Algorithm 14 ( $\text{Sam}^\pi$ )

Input: An  $n$ -bit input circuit  $C$ .

Oracle:  $\pi \in \Pi_n$ .

- 1 Sample  $x \leftarrow \{0, 1\}^n$ .
- 2 Find the first (in a random order) random  $x' \in \{0, 1\}^n$  with  $C^\pi(x) = C^\pi(x')$ .
- 3 Return  $(x, x')$ .

- Let  $\text{Sam}_r$  be the variant of **Sam** whose coins are **fixed** to  $r$ .

## Proving Thm 13

Fix  $n \in \mathbb{N}$ .

We construct an (inefficient) algorithm **Sam**, that finds collision in **any** CRH, but **non-useful** for inverting random permutation.

### Algorithm 14 ( $\text{Sam}^\pi$ )

Input: An  $n$ -bit input circuit  $C$ .

Oracle:  $\pi \in \Pi_n$ .

- 1 Sample  $x \leftarrow \{0, 1\}^n$ .
- 2 Find the first (in a random order) random  $x' \in \{0, 1\}^n$  with  $C^\pi(x) = C^\pi(x')$ .
- 3 Return  $(x, x')$ .

- Let  $\text{Sam}_r$  be the variant of **Sam** whose coins are **fixed** to  $r$ .
- In the actual implementation **Sam** uses **independent** randomness per input query  $C$ .

## No CRH relative to Sam

## No CRH relative to Sam

Let  $\mathcal{H}_n$  be a length-decreasing oracle-aided circuit family.

## No CRH relative to Sam

Let  $\mathcal{H}_n$  be a length-decreasing oracle-aided circuit family.

### Claim 15

For any  $h \in \mathcal{H}_n$  and  $\pi \in \Pi_n$ :  $\Pr_{(x, x') \leftarrow \text{Sam}^\pi(h)} [x \neq x' \wedge h^\pi(x) = h^\pi(x')] \geq \frac{1}{4}$ .

## No CRH relative to Sam

Let  $\mathcal{H}_n$  be a length-decreasing oracle-aided circuit family.

### Claim 15

For any  $h \in \mathcal{H}_n$  and  $\pi \in \Pi_n$ :  $\Pr_{(x, x') \leftarrow \text{Sam}^\pi(h)} [x \neq x' \wedge h^\pi(x) = h^\pi(x')] \geq \frac{1}{4}$ .



## No CRH relative to Sam

Let  $\mathcal{H}_n$  be a length-decreasing oracle-aided circuit family.

### Claim 15

For any  $h \in \mathcal{H}_n$  and  $\pi \in \Pi_n$ :  $\Pr_{(x, x') \leftarrow \text{Sam}^\pi(h)} [x \neq x' \wedge h^\pi(x) = h^\pi(x')] \geq \frac{1}{4}$ .

Proof:

## No CRH relative to Sam

Let  $\mathcal{H}_n$  be a length-decreasing oracle-aided circuit family.

### Claim 15

For any  $h \in \mathcal{H}_n$  and  $\pi \in \Pi_n$ :  $\Pr_{(x,x') \leftarrow \text{Sam}^\pi(h)} [x \neq x' \wedge h^\pi(x) = h^\pi(x')] \geq \frac{1}{4}$ .

Proof: It suffices to prove that for any length decreasing function  $g$  over  $\{0, 1\}^n$ ,  $\Pr_{x \leftarrow \{0,1\}^n} [|g^{-1}(g(x))| = 1] \leq \frac{1}{2}$ .  $\square$

## No CRH relative to Sam

Let  $\mathcal{H}_n$  be a length-decreasing oracle-aided circuit family.

### Claim 15

For any  $h \in \mathcal{H}_n$  and  $\pi \in \Pi_n$ :  $\Pr_{(x, x') \leftarrow \text{Sam}^\pi(h)} [x \neq x' \wedge h^\pi(x) = h^\pi(x')] \geq \frac{1}{4}$ .

Proof: It suffices to prove that for any length decreasing function  $g$  over  $\{0, 1\}^n$ ,  $\Pr_{x \leftarrow \{0, 1\}^n} [|g^{-1}(g(x))| = 1] \leq \frac{1}{2}$ .  $\square$

The following algorithm breaks the collision resistance of any Black-box construction of a CRH from OWP.

## No CRH relative to Sam

Let  $\mathcal{H}_n$  be a length-decreasing oracle-aided circuit family.

### Claim 15

For any  $h \in \mathcal{H}_n$  and  $\pi \in \Pi_n$ :  $\Pr_{(x,x') \leftarrow \text{Sam}^\pi(h)} [x \neq x' \wedge h^\pi(x) = h^\pi(x')] \geq \frac{1}{4}$ .

Proof: It suffices to prove that for any length decreasing function  $g$  over  $\{0, 1\}^n$ ,  $\Pr_{x \leftarrow \{0,1\}^n} [|g^{-1}(g(x))| = 1] \leq \frac{1}{2}$ .  $\square$

The following algorithm breaks the collision resistance of any Black-box construction of a CRH from OWP.

### Algorithm 16 ( $D^{\text{Sam}^\pi}$ )

On input  $h \in \mathcal{H}_n$ , return  $\text{Sam}^\pi(h)$ .

## No CRH relative to Sam

Let  $\mathcal{H}_n$  be a length-decreasing oracle-aided circuit family.

### Claim 15

For any  $h \in \mathcal{H}_n$  and  $\pi \in \Pi_n$ :  $\Pr_{(x,x') \leftarrow \text{Sam}^\pi(h)} [x \neq x' \wedge h^\pi(x) = h^\pi(x')] \geq \frac{1}{4}$ .

Proof: It suffices to prove that for any length decreasing function  $g$  over  $\{0, 1\}^n$ ,  $\Pr_{x \leftarrow \{0,1\}^n} [|g^{-1}(g(x))| = 1] \leq \frac{1}{2}$ .  $\square$

The following algorithm breaks the collision resistance of any Black-box construction of a CRH from OWP.

### Algorithm 16 ( $D^{\text{Sam}^\pi}$ )

On input  $h \in \mathcal{H}_n$ , return  $\text{Sam}^\pi(h)$ .

# Random permutations are hard relative to Sam

# Random permutations are hard relative to Sam

Proof via the GT paradigm,

## Random permutations are hard relative to Sam

Proof via the GT paradigm, but  $D^{\pi, \text{Sam}_r^\pi}$ , via  $\text{Sam}_r^\pi$ , might make more than  $2^n$  queries...



## Random permutations are hard relative to $\text{Sam}$

Proof via the GT paradigm, but  $D^{\pi, \text{Sam}_r^\pi}$ , via  $\text{Sam}_r^\pi$ , might make more than  $2^n$  queries...

Idea: focus only on the “collision” queries made by  $\text{Sam}_r^\pi$ .

## Random permutations are hard relative to Sam

Proof via the GT paradigm, but  $D^{\pi, \text{Sam}_r^\pi}$ , via  $\text{Sam}_r^\pi$ , might make more than  $2^n$  queries...

Idea: focus only on the “collision” queries made by  $\text{Sam}_r^\pi$ .

### Definition 17

The **augmented number of queries** an oracle-aided circuit/algorithm with  $\text{Sam}$ -gate does, is the number of queries it makes **directly**, plus **twice** the number of queries the circuits it **passes** to  $\text{Sam}$  do.

## Random permutations are hard relative to Sam

Proof via the GT paradigm, but  $D^{\pi, \text{Sam}_r^\pi}$ , via  $\text{Sam}_r^\pi$ , might make more than  $2^n$  queries...

Idea: focus only on the “collision” queries made by  $\text{Sam}_r^\pi$ .

### Definition 17

The **augmented number of queries** an oracle-aided circuit/algorithm with  $\text{Sam}$ -gate does, is the number of queries it makes **directly**, plus **twice** the number of queries the circuits it **passes** to  $\text{Sam}$  do.

### Theorem 18

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}/2$ -augmented-query circuit  $D$ :

$$\Pr_{\pi \leftarrow \Pi_n; r \leftarrow \{0,1\}^*} \left[ \Pr_{x \leftarrow \{0,1\}^n} \left[ D^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x \right] > 2 \cdot 2^{-n/5} \right] \leq 2 \cdot 2^{-2^{\frac{3}{5}n}}$$

## Random permutations are hard relative to Sam

Proof via the GT paradigm, but  $D^{\pi, \text{Sam}_r^\pi}$ , via  $\text{Sam}_r^\pi$ , might make more than  $2^n$  queries...

Idea: focus only on the “collision” queries made by  $\text{Sam}_r^\pi$ .

### Definition 17

The **augmented number of queries** an oracle-aided circuit/algorithm with  $\text{Sam}$ -gate does, is the number of queries it makes **directly**, plus **twice** the number of queries the circuits it **passes** to  $\text{Sam}$  do.

### Theorem 18

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}/2$ -augmented-query circuit  $D$ :

$$\Pr_{\pi \leftarrow \Pi_n; r \leftarrow \{0,1\}^*} \left[ \Pr_{x \leftarrow \{0,1\}^n} \left[ D^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x \right] > 2 \cdot 2^{-n/5} \right] \leq 2 \cdot 2^{-2^{\frac{3}{5}n}}$$

- Almost the same result as in the non- $\text{Sam}$  case.

## Random permutations are hard relative to Sam

Proof via the GT paradigm, but  $D^{\pi, \text{Sam}_r^\pi}$ , via  $\text{Sam}_r^\pi$ , might make more than  $2^n$  queries...

Idea: focus only on the “collision” queries made by  $\text{Sam}_r^\pi$ .

### Definition 17

The **augmented number of queries** an oracle-aided circuit/algorithm with  $\text{Sam}$ -gate does, is the number of queries it makes **directly**, plus **twice** the number of queries the circuits it **passes** to  $\text{Sam}$  do.

### Theorem 18

For any large enough  $n \in \mathbb{N}$  and  $2^{n/5}/2$ -augmented-query circuit  $D$ :

$$\Pr_{\pi \leftarrow \Pi_n; r \leftarrow \{0,1\}^*} \left[ \Pr_{x \leftarrow \{0,1\}^n} \left[ D^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x \right] > 2 \cdot 2^{-n/5} \right] \leq 2 \cdot 2^{-2^{\frac{3}{5}n}}$$

- Almost the same result as in the non- $\text{Sam}$  case.
- Hence, random permutations are (extremely) hard for exponential-size circuits with oracle access to  $\text{Sam}$ .

# Proving Thm 18

## Proving Thm 18

Fix large enough  $n$ . The proof follows by the next two claims.

## Proving Thm 18

Fix large enough  $n$ . The proof follows by the next two claims.

### Definition 19

For circuit  $D$ ,  $\pi \in \Pi_n$ ,  $r \in \{0, 1\}^*$ , and  $y \in \{0, 1\}^n$ , let  $\text{hit}_{D;r}^\pi(y)$  be one, if  $D^{\pi, \text{Sam}_r^\pi}(y)$  makes a query  $(x, x') = \text{Sam}_r^\pi(C)$ , and either  $C^\pi(x)$  or  $C^\pi(x')$  query  $\pi$  on  $\pi^{-1}(y)$ .



## Proving Thm 18

Fix large enough  $n$ . The proof follows by the next two claims.

### Definition 19

For circuit  $D$ ,  $\pi \in \Pi_n$ ,  $r \in \{0, 1\}^*$ , and  $y \in \{0, 1\}^n$ , let  $\text{hit}_{D;r}^\pi(y)$  be one, if  $D^{\pi, \text{Sam}_r^\pi}(y)$  makes a query  $(x, x') = \text{Sam}_r^\pi(C)$ , and either  $C^\pi(x)$  or  $C^\pi(x')$  query  $\pi$  on  $\pi^{-1}(y)$ .

The following probabilities are over  $\pi \leftarrow \Pi_n$ ,  $r \leftarrow \{0, 1\}^*$  and  $x \leftarrow \{0, 1\}^n$ .

## Proving Thm 18

Fix large enough  $n$ . The proof follows by the next two claims.

### Definition 19

For circuit  $D$ ,  $\pi \in \Pi_n$ ,  $r \in \{0, 1\}^*$ , and  $y \in \{0, 1\}^n$ , let  $\text{hit}_{D;r}^\pi(y)$  be one, if  $D^{\pi, \text{Sam}_r^\pi}(y)$  makes a query  $(x, x') = \text{Sam}_r^\pi(C)$ , and either  $C^\pi(x)$  or  $C^\pi(x')$  query  $\pi$  on  $\pi^{-1}(y)$ .

The following probabilities are over  $\pi \leftarrow \Pi_n$ ,  $r \leftarrow \{0, 1\}^*$  and  $x \leftarrow \{0, 1\}^n$ .

### Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \text{hit}_{D;r}^\pi(\pi(x)) \right] > \varepsilon \right] \leq$$

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x \wedge \neg \text{hit}_{D;r}^\pi(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

## Proving Thm 18

Fix large enough  $n$ . The proof follows by the next two claims.

### Definition 19

For circuit  $D$ ,  $\pi \in \Pi_n$ ,  $r \in \{0, 1\}^*$ , and  $y \in \{0, 1\}^n$ , let  $\text{hit}_{D;r}^\pi(y)$  be one, if  $D^{\pi, \text{Sam}_r^\pi}(y)$  makes a query  $(x, x') = \text{Sam}_r^\pi(C)$ , and either  $C^\pi(x)$  or  $C^\pi(x')$  query  $\pi$  on  $\pi^{-1}(y)$ .

The following probabilities are over  $\pi \leftarrow \Pi_n$ ,  $r \leftarrow \{0, 1\}^*$  and  $x \leftarrow \{0, 1\}^n$ .

### Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \text{hit}_{D;r}^\pi(\pi(x)) \right] > \varepsilon \right] \leq \\ \Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^\pi(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

### Claim 21

For any  $2^{n/5}/2$ -augQuery circuit  $D$ :

$$\Pr_{\pi;r} \left[ \Pr_x \left[ D^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x \right] > 2^{-n/5} \wedge \neg \text{hit}_{D;r}^\pi \right] \leq 2^{-2^{3n/5}}.$$

## Proving Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \text{hit}_{D;r}^{\pi}(\pi(x)) \right] > \varepsilon \right] \leq$$

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^{\pi}(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

## Proving Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \text{hit}_{D;r}^{\pi}(\pi(x)) \right] > \varepsilon \right] \leq$$

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^{\pi}(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

Proof: We describe a **random** circuit  $\tilde{D}$ , and its deterministic variant follows by fixing the best coins.

## Proving Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \text{hit}_{D;r}^{\pi}(\pi(x)) \right] > \varepsilon \right] \leq$$

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^{\pi}(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

Proof: We describe a **random** circuit  $\tilde{D}$ , and its deterministic variant follows by fixing the best coins.

### Algorithm 22 ( $\tilde{D}^{\pi, \text{Sam}_r^{\pi}}(y)$ )

Emulate  $D^{\pi, \text{Sam}_r^{\pi}}(y)$ . Before any query of  $\text{Sam}_r^{\pi}(C)$ :

Evaluate  $C^{\pi}(z)$  for  $z \leftarrow \{0, 1\}^n$ . If  $C^{\pi}(z)$  makes a query  $\pi(x) = y$ , return  $x$  and halt.

## Proving Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:  
 $\Pr_{\pi;r} [\Pr_x [\text{hit}_{D;r}^{\pi}(\pi(x))] > \varepsilon] \leq$   
 $\Pr_{\pi;r} [\Pr_x [\tilde{D}^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^{\pi}(p(x))] > \varepsilon/2] \text{ for any } \varepsilon \geq 0.$

Proof: We describe a **random** circuit  $\tilde{D}$ , and its deterministic variant follows by fixing the best coins.

### Algorithm 22 ( $\tilde{D}^{\pi, \text{Sam}_r^{\pi}}(y)$ )

Emulate  $D^{\pi, \text{Sam}_r^{\pi}}(y)$ . Before any query of  $\text{Sam}_r^{\pi}(C)$ :

Evaluate  $C^{\pi}(z)$  for  $z \leftarrow \{0, 1\}^n$ . If  $C^{\pi}(z)$  makes a query  $\pi(x) = y$ , return  $x$  and halt.

- The augmented query complexity of  $\tilde{D}$  is at most twice that of  $D$ .

## Proving Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \text{hit}_{D;r}^{\pi}(\pi(x)) \right] > \varepsilon \right] \leq$$

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^{\pi}(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

Proof: We describe a **random** circuit  $\tilde{D}$ , and its deterministic variant follows by fixing the best coins.

### Algorithm 22 ( $\tilde{D}^{\pi, \text{Sam}_r^{\pi}}(y)$ )

Emulate  $D^{\pi, \text{Sam}_r^{\pi}}(y)$ . Before any query of  $\text{Sam}_r^{\pi}(C)$ :

Evaluate  $C^{\pi}(z)$  for  $z \leftarrow \{0, 1\}^n$ . If  $C^{\pi}(z)$  makes a query  $\pi(x) = y$ , return  $x$  and halt.

- The augmented query complexity of  $\tilde{D}$  is at most twice that of  $D$ .



## Proving Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \text{hit}_{D;r}^{\pi}(\pi(x)) \right] > \varepsilon \right] \leq$$

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^{\pi}(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

Proof: We describe a random circuit  $\tilde{D}$ , and its deterministic variant follows by fixing the best coins.

### Algorithm 22 ( $\tilde{D}^{\pi, \text{Sam}_r^{\pi}}(y)$ )

Emulate  $D^{\pi, \text{Sam}_r^{\pi}}(y)$ . Before any query of  $\text{Sam}_r^{\pi}(C)$ :

Evaluate  $C^{\pi}(z)$  for  $z \leftarrow \{0, 1\}^n$ . If  $C^{\pi}(z)$  makes a query  $\pi(x) = y$ , return  $x$  and halt.

- The augmented query complexity of  $\tilde{D}$  is at most twice that of  $D$ .
- Fix  $\pi$  and  $y$ , and let  $\delta_i = \Pr_r [D(y) \text{ makes first hit on } i\text{'th Sam query}]$ .

## Proving Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \text{hit}_{D;r}^{\pi}(\pi(x)) \right] > \varepsilon \right] \leq$$

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^{\pi}(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

Proof: We describe a random circuit  $\tilde{D}$ , and its deterministic variant follows by fixing the best coins.

### Algorithm 22 ( $\tilde{D}^{\pi, \text{Sam}_r^{\pi}}(y)$ )

Emulate  $D^{\pi, \text{Sam}_r^{\pi}}(y)$ . Before any query of  $\text{Sam}_r^{\pi}(C)$ :

Evaluate  $C^{\pi}(z)$  for  $z \leftarrow \{0, 1\}^n$ . If  $C^{\pi}(z)$  makes a query  $\pi(x) = y$ , return  $x$  and halt.

- The augmented query complexity of  $\tilde{D}$  is at most twice that of  $D$ .
- Fix  $\pi$  and  $y$ , and let  $\delta_i = \Pr_r [D(y) \text{ makes first hit on } i\text{'th Sam query}]$ .

## Proving Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \text{hit}_{D;r}^{\pi}(\pi(x)) \right] > \varepsilon \right] \leq$$

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^{\pi}(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

Proof: We describe a random circuit  $\tilde{D}$ , and its deterministic variant follows by fixing the best coins.

### Algorithm 22 ( $\tilde{D}^{\pi, \text{Sam}_r^{\pi}}(y)$ )

Emulate  $D^{\pi, \text{Sam}_r^{\pi}}(y)$ . Before any query of  $\text{Sam}_r^{\pi}(C)$ :

Evaluate  $C^{\pi}(z)$  for  $z \leftarrow \{0, 1\}^n$ . If  $C^{\pi}(z)$  makes a query  $\pi(x) = y$ , return  $x$  and halt.

- The augmented query complexity of  $\tilde{D}$  is at most twice that of  $D$ .
- Fix  $\pi$  and  $y$ , and let  $\delta_i = \Pr_r [D(y) \text{ makes first hit on } i\text{'th Sam query}]$ .  
 $\implies \Pr_r [D(y) \text{ makes first hit on the "x-part" of } i\text{'th Sam query}] \geq \delta_i/2$

## Proving Claim 20

For any  $t$ -augQuery circuit  $D$ ,  $\exists$   $2t$ -augQuery circuit  $\tilde{D}$  such that:

$$\Pr_{\pi;r} [\Pr_x [\text{hit}_{D;r}^{\pi}(\pi(x)) > \varepsilon] \leq$$

$$\Pr_{\pi;r} \left[ \Pr_x \left[ \tilde{D}^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = x \wedge \neg \text{hit}_{\tilde{D};r}^{\pi}(p(x)) \right] > \varepsilon/2 \right] \text{ for any } \varepsilon \geq 0.$$

Proof: We describe a random circuit  $\tilde{D}$ , and its deterministic variant follows by fixing the best coins.

### Algorithm 22 ( $\tilde{D}^{\pi, \text{Sam}_r^{\pi}}(y)$ )

Emulate  $D^{\pi, \text{Sam}_r^{\pi}}(y)$ . Before any query of  $\text{Sam}_r^{\pi}(C)$ :

Evaluate  $C^{\pi}(z)$  for  $z \leftarrow \{0, 1\}^n$ . If  $C^{\pi}(z)$  makes a query  $\pi(x) = y$ , return  $x$  and halt.

- The augmented query complexity of  $\tilde{D}$  is at most twice that of  $D$ .
- Fix  $\pi$  and  $y$ , and let  $\delta_i = \Pr_r [D(y)$  makes first hit on  $i$ 'th Sam query].  
 $\implies \Pr_r [D(y)$  makes first hit on the " $x$ -part" of  $i$ 'th Sam query]  $\geq \delta_i/2$   
 $\implies \Pr_r \left[ \tilde{D}(y) \text{ finds } \pi^{-1}(y) \text{ just before } i\text{'th Sam query, w/o hitting} \right] \geq \delta_i/2. \square$

## Proving Claim 21

For any  $2^{n/5}/2$ -augQuery circuit  $D$ :

$$\Pr_{\pi;r} [\Pr_x [D^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x] > 2^{-n/5} \wedge \neg \text{hit}_{D;r}^\pi] \leq 2^{-2^{3n/5}}.$$

## Proving Claim 21

For any  $2^{n/5}/2$ -augQuery circuit  $D$ :

$$\Pr_{\pi;r} [\Pr_x [D^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x] > 2^{-n/5} \wedge \neg \text{hit}_{D;r}^\pi] \leq 2^{-2^{3n/5}}.$$

The proof is similar to the non-Sam case.

## Proving Claim 21

**For any  $2^{n/5}/2$ -augQuery circuit  $D$ :**

$$\Pr_{\pi; r} [\Pr_x [D^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x] > 2^{-n/5} \wedge \neg \text{hit}_{D; r}^\pi] \leq 2^{-2^{3n/5}}.$$

The proof is similar to the non-Sam case.

### Lemma 23 (compression lemma, Sam variant)

For  $q$ -augQuery circuit  $D$ ,  $r \in \{0, 1\}^*$  and  $\varepsilon > 0$ , exist algorithms Enc and Dec such that: Let  $\pi \in \Pi_n$  be with

$\Pr_{x \leftarrow \{0, 1\}^n} [D^{\pi, \text{Sam}_r^\pi}(\pi(x)) = x \wedge \neg \text{hit}_{D; r}^\pi(p(x))] > \varepsilon$ , then

- $\text{Dec}(\text{Enc}(\pi)) = \pi$
- $|\text{Enc}(\pi)| \leq \log((N - a)!) + 2 \cdot \log \binom{N}{a}$ , for  $a \geq \frac{\varepsilon N}{q+1}$

## Proving Lemma 23



## Proving Lemma 23

### Definition 24

Assume  $D^{\pi, \text{Sam}_r^\pi}(\pi(x))(y)$  makes a query  $\text{Sam}_r^\pi(C)$  and get answer  $(x, x')$ , we call the  $\pi$ -queries done by  $C^\pi(x)$  and  $C^\pi(x')$ , **indirect queries** of  $D$ .

### Construction 25 (Useful set $\mathcal{Y} \subseteq \{0, 1\}^n$ )

- 1 Set  $\mathcal{Y} = \emptyset$  and  $\mathcal{I} = \{y \in \{0, 1\}^n : D^{\pi, \text{Sam}_r^\pi}(\pi(x)) = \pi \wedge \neg \text{hit}_{D,r}^\pi(y)\}$ .
- 2 While  $\mathcal{I} \neq \emptyset$ , let  $y$  be the smallest lex. element in  $\mathcal{I}$ .
  - 1 Add  $y$  to  $\mathcal{Y}$ .
  - 2 Remove  $y$  and all direct & indirect  $\pi$ -queries  $D(y)$  makes from  $\mathcal{I}$ .

## Proving Lemma 23

### Definition 24

Assume  $D^{\pi, \text{Sam}_r^{\pi}}(\pi(x))(y)$  makes a query  $\text{Sam}_r^{\pi}(C)$  and get answer  $(x, x')$ , we call the  $\pi$ -queries done by  $C^{\pi}(x)$  and  $C^{\pi}(x')$ , **indirect queries** of  $D$ .

### Construction 25 (Useful set $\mathcal{Y} \subseteq \{0, 1\}^n$ )

- ➊ Set  $\mathcal{Y} = \emptyset$  and  $\mathcal{I} = \{y \in \{0, 1\}^n : D^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = \pi \wedge \neg \text{hit}_{D,r}^{\pi}(y)\}$ .
- ➋ While  $\mathcal{I} \neq \emptyset$ , let  $y$  be the smallest lex. element in  $\mathcal{I}$ .
  - ➊ Add  $y$  to  $\mathcal{Y}$ .
  - ➋ Remove  $y$  and all direct & indirect  $\pi$ -queries  $D(y)$  makes from  $\mathcal{I}$ .

### Algorithm 26 ( $\text{Enc}(\pi)$ )

Output (description of)  $\mathcal{Y}$  and  $\mathcal{V} = \{(x, \pi(x)) : \pi(x) \notin \mathcal{Y}\}$ .

## Proving Lemma 23

### Definition 24

Assume  $D^{\pi, \text{Sam}_r^{\pi}}(\pi(x))(y)$  makes a query  $\text{Sam}_r^{\pi}(C)$  and get answer  $(x, x')$ , we call the  $\pi$ -queries done by  $C^{\pi}(x)$  and  $C^{\pi}(x')$ , **indirect queries** of  $D$ .

### Construction 25 (Useful set $\mathcal{Y} \subseteq \{0, 1\}^n$ )

- ➊ Set  $\mathcal{Y} = \emptyset$  and  $\mathcal{I} = \{y \in \{0, 1\}^n : D^{\pi, \text{Sam}_r^{\pi}}(\pi(x)) = \pi \wedge \neg \text{hit}_{D,r}^{\pi}(y)\}$ .
- ➋ While  $\mathcal{I} \neq \emptyset$ , let  $y$  be the smallest lex. element in  $\mathcal{I}$ .
  - ➊ Add  $y$  to  $\mathcal{Y}$ .
  - ➋ Remove  $y$  and all direct & indirect  $\pi$ -queries  $D(y)$  makes from  $\mathcal{I}$ .

### Algorithm 26 ( $\text{Enc}(\pi)$ )

Output (description of)  $\mathcal{Y}$  and  $\mathcal{V} = \{(x, \pi(x)) : \pi(x) \notin \mathcal{Y}\}$ .

Under proper encoding,  $|\text{Enc}(\pi)| \leq \log((N - a)!) + 2 \cdot \log \binom{N}{a}$  for  $a = |\mathcal{Y}| \geq \frac{\epsilon N}{q+1}$ .

## Proving **Lemma 23** cont.

## Proving Lemma 23 cont.

### Algorithm 27 ( $\text{Dec}(\mathcal{Y}, \mathcal{V})$ )

For all  $y \in \mathcal{Y}$  in lex. order:

- 1 Emulate  $D^{\pi, \text{Sam}_r^{\pi}}(y)$ .
  - 1 Answer  $\pi$ -query using  $\mathcal{V}$ .
  - 2 On  $\text{Sam}$ -query  $\text{Sam}_r^{\pi}(C)$ : choose  $x$  according to  $r$ , and let  $x'$  be the first element in  $\{0, 1\}^n$  for which the  $\pi$ -queries of  $C^{\pi}(x')$  are defined, and  $C^{\pi}(x') = C^{\pi}(x)$ .
- 2 If  $D$  makes a  $\pi$ -query  $x$  that is undefined in  $\mathcal{V}$ , add  $(x, y)$  to  $\mathcal{V}$ .  
Otherwise, add  $(D^{\pi, \text{Sam}_r^{\pi}}(y), y)$  to  $\mathcal{V}$ .

Use  $\mathcal{V}$  to reconstruct  $\pi$

## Proving Lemma 23 cont.

### Algorithm 27 ( $\text{Dec}(\mathcal{Y}, \mathcal{V})$ )

For all  $y \in \mathcal{Y}$  in lex. order:

- ① Emulate  $D^{\pi, \text{Sam}_r^{\pi}}(y)$ .
  - ① Answer  $\pi$ -query using  $\mathcal{V}$ .
  - ② On  $\text{Sam}$ -query  $\text{Sam}_r^{\pi}(C)$ : choose  $x$  according to  $r$ , and let  $x'$  be the first element in  $\{0, 1\}^n$  for which the  $\pi$ -queries of  $C^{\pi}(x')$  are defined, and  $C^{\pi}(x') = C^{\pi}(x)$ .
- ② If  $D$  makes a  $\pi$ -query  $x$  that is undefined in  $\mathcal{V}$ , add  $(x, y)$  to  $\mathcal{V}$ .  
Otherwise, add  $(D^{\pi, \text{Sam}_r^{\pi}}(y), y)$  to  $\mathcal{V}$ .

Use  $\mathcal{V}$  to reconstruct  $\pi$

Correctness holds since  $\text{hit}_{D,r}^{\pi}(y) = 0$  for all  $y \in \mathcal{Y}$ , and thus answer to all  $\text{Sam}$ -queries are defined.

## Remarks

- Results extends to OWFs and to TDPs.

## Remarks

- Results extends to OWFs and to TDPs.
- Making **Sam** use independent randomness per input query **C**?