

# Confidential Transactions Theory Justification

Iftach Haitner\*

July 23, 2025

## Abstract

[Iftach's Note: **TODO**]

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Preliminaries</b>	<b>2</b>
2.1	Notation . . . . .	2
<b>3</b>	<b>The Confidential Transaction Protocols</b>	<b>2</b>
3.1	The Ideal Functionality . . . . .	2
3.2	The Protocol . . . . .	3

---

\*Stellar Development Foundation. E-mail: [iftach.haitner@stellar.org](mailto:iftach.haitner@stellar.org).

# 1 Introduction

[Iftach's Note: TODO]

## 2 Preliminaries

### 2.1 Notation

We use calligraphic letters to denote sets, uppercase for random variables, and lowercase for integers and functions. Let  $\mathbb{N}$  denote the set of natural numbers. For  $n \in \mathbb{N}$ , let  $[n] := \{1, \dots, n\}$  and  $(n) := \{0, \dots, n\}$ . For a relation  $\mathcal{R}$ , let  $\mathcal{L}(\mathcal{R})$  denote its underlying language, i.e.,  $\mathcal{L}(\mathcal{R}) := \{x : \exists w : (x, w) \in \mathcal{R}\}$ .

## 3 The Confidential Transaction Protocols

### 3.1 The Ideal Functionality

**Functionality 3.1** ( $\mathcal{F}_{\text{ConfTrans}}$ : Confidential transactions).

Parties: Issuer  $I$ , Chain  $C$  and users  $U_1, \dots, U_n$ .

**Init.** Upon receiving init from all parties:

1. For each  $i \in [n]$ : set  $\text{balance}_i, \text{balance}_i^{\text{tmp}} \leftarrow 0$ .
2. Set  $\log \leftarrow \emptyset$ .

**Issue.** Upon receiving  $(\text{sid}, \text{issue}, x, d)$  from  $V$  and  $I$ :

1. Assert( $x \in \mathbb{N}$  and  $d \in [n]$ ).
2.  $\text{balance}_d^{\text{tmp}} += x$ .
3. Set  $\log += (\text{sid}, \text{issue}, x, d)$ .

**Transfer.** On call  $(\text{sid}, \text{transfer}, d)$ , by  $C$  and  $U_s$ , with  $U_s$  holding private input  $x$ .

1. Assert( $x \in \mathbb{N}$ ,  $\text{balance}_s \geq x$  and  $s, d \in [n]$ ).
2.  $\text{balance}_s -= x$ .
3.  $\text{balance}_d^{\text{tmp}} += x$ .
4. Set  $\log += (\text{sid}, \text{transfer}, s, d)$

**Update.** Upon receiving  $(\text{sid}, \text{update})$  from party  $P_i$  and  $C$ :

1. Set  $\text{balance}_i += \text{balance}_i^{\text{tmp}}$ .
2. Set  $\text{balance}_i^{\text{tmp}} \leftarrow 0$ .

3. Set  $\text{log} += (\text{sid}, \text{update}, i)$

**History.** Upon receiving  $(\text{sid}, \text{history})$  from party  $P_i$  and C: Send  $\text{log}$  to  $P_i$ .

[**Iftach's Note: TODO**

1. Should the receiver be part of the call in which it gets money.

2. Auditor?

]

### 3.2 The Protocol

**Protocol 3.2** ( $\Pi_{\text{ConfTrans}}$ : Confidential transactions).

Parties: Issuer I, Chain C and users  $U_1, \dots, U_n$ .

Parameters:  $1^{\kappa_c}$ .

Subprotocols: See below.

**Protocol 3.3** ( $\Pi_{\text{ConfTrans.Init}}$ ).

Participating parties. All parties.

Operation:

1.  $P_i$ , for all  $i \in [n]$ ,
  - (a) Set  $(pk_i, sk_i) \xleftarrow{R} \text{KeyGen}(1^{\kappa_c})$ .
  - (b) Store  $sk_i$ .
  - (c) Send  $pk_i$  to all parties.
2. All parties store  $\{pk_i\}_{i \in [n]}$ .
3. C:
  - (a) For all  $i \in [n]$ : Set  $B_i, B_i^{\text{tmp}} \xleftarrow{R} \text{Enc}_{pk_i}(0)$ .
  - (b) Set  $\text{log} \leftarrow \emptyset$ .

**Protocol 3.4** ( $\Pi_{\text{ConfTrans.Issue}}$ ).

Participating parties. I and C.

C's input.  $x \in \mathbb{N}$  and  $i \in [n]$ .

Operation:

1. I: Send  $(x, i)$  to C.
2. C: Set  $B_i^{\text{tmp}} += \text{Enc}_{pk_i}(x)$ .

3. C: Set  $\log \leftarrow (\text{sid}, \text{issue}, x, i)$ .

**Protocol 3.5** ( $\Pi_{\text{ConfTrans.Transfer}}$ ).

Participating parties.  $P_s$  and C.

Proof's systems:  $\Pi^{\text{pos}}, \Pi^{\text{lrg}}$

Common input.  $d \in [n]$ .

$P_s$ 's private input.  $x \in \mathbb{N}$ .

Operation:

1.  $P_s$ :

- (a)  $X \xleftarrow{R} \text{Enc}_{pk_d}(x; r)$  for  $r \xleftarrow{R} \{0, 1\}^{\kappa_c}$ .
- (b)  $\pi^{\text{pos}} \xleftarrow{R} \text{Plrg}((pk_d, X), (x, r))$ .
- (c)  $\pi^{\text{lrg}} \xleftarrow{R} \text{Plrg}((pk_s, pk_d, B_i, X), (sk_s, x, r))$ .
- (d) Send  $(X, \pi^{\text{pos}}, \pi^{\text{lrg}})$  to C.

2. C:

- (a)  $V^{\text{pos}}(pk_d, X)$ .
- (b)  $V^{\text{lrg}}(pk_s, pk_d, B_i, X)$ .
- (c) Set  $B_d^{\text{tmp}} \leftarrow X$ .
- (d) Set  $\log \leftarrow (\text{sid}, \text{transfer}, s, d)$ .

**Protocol 3.6** ( $\Pi_{\text{ConfTrans.Update}}$ ).

Participating parties.  $P_i$  and C.

Operation: C

- 1. Set  $B_i \leftarrow B_i^{\text{tmp}}$ .
- 2. Set  $B_i^{\text{tmp}} \xleftarrow{R} \text{Enc}_{pk_i}(0)$ .
- 3. Set  $\log \leftarrow (\text{sid}, \text{update}, i)$

**Protocol 3.7** ( $\Pi_{\text{ConfTrans.History}}$ ).

Participating parties.  $P_i$  and C.

Operation: C sends  $\log$  to  $P_i$ .