1


2013-AE-"14-26"

ai24btech11028 - Ronit Ranjan


- 1) The critical Mach number for a flat plate of zero thickness, at zero angle of attack, is ______
- 2) A damped single degree-of-freedom system is vibrating under a harmonic excitation with an amplitude ratio of 2.5 at resonance. The damping ratio of the system is _____
- 3) The cross-section of a long thin-walled member is as shown in the figure. When subjected to pure twist, point A




- a) does not move horizontally or axially, but moves vertically
- b) does not move axially, but moves both vertically and horizontally
- c) does not move horizontally, vertically or axially
- d) does not move vertically or axially, but moves horizontally
- 4) The channel section of uniform thickness 2mm shown in the figure is subjected to a torque of 10 Nm. If it is made of a material with shear modulus of 25 GPa, the twist per unit length in radians/m is




5) The stiffened cross-section of a long slender uniform structural member is idealized as shown in the figure below. The lumped areas at A, B, C and D have equal cross-sectional area of 3 cm². The webs AB, BC, CD and DA are each 5 mm thick. The structural member is subjected to a twisting moment of 10 kNm. The magnitudes of the shear flow in the webs, q_{AB} , q_{BC} , q_{CD} , and q_{DA} in kN/m are, respectively



- a) 20, 20, 20, 20
- b) 0, 0, 50, 50
- c) 40, 40, 0, 0
- d) 50, 50, 50, 50
- 6) Consider two engines P and Q. In P, the high pressure turbine blades are cooled with a bleed of 5% from the compressor after the compression process and in Q the turbine blades are not cooled. Comparing engine P with engine Q, which one of the following is NOT TRUE?
 - a) Turbine inlet temperature is higher for engine P
 - b) Specific thrust is higher for engine P
 - c) Compressor work is the same for both P and Q
 - d) Fuel flow rate is lower for engine P
- 7) The mass flow rate of air through an aircraft engine is 10 kg/s. The compressor outlet temperature is 400 K and the turbine inlet temperature is 1800 K. The heating value of the fuel is 42 MJ/kg and the specific heat at constant pressure is 1 kJ/kg-K. The mass flow rate of the fuel in kg/s is approximately
- 8) For a given inlet condition, if the turbine inlet temperature is fixed, what value of compressor efficiency given below leads to the lowest amount of fuel added in the combustor of a gas turbine engine?
 - a) 1
 - b) 0.95
 - c) 0.85
 - d) 0.8
- 9) A gas turbine engine is mounted on an aircraft which can attain a maximum altitude of 11 km from sea level. The combustor volume of this engine is decided based on conditions at
 - a) sea level
 - b) 8 km altitude
 - c) 5.5 km altitude
 - d) 11 km altitude
- 10) Consider the low earth orbit (LEO) and the geo synchronous orbit (GSO). Then
 - a) ΔV requirement for launch to LEO is greater than that for GSO, and altitude of LEO is lower than that of GSO
 - b) ΔV requirement for launch to LEO is lower than that for GSO, and altitude of LEO is lower than that of GSO
 - c) ΔV requirement for launch to LEO is greater than that for GSO, and altitude of LEO is greater than that of GSO
 - d) ΔV requirement for launch to LEO is lower than that for GSO, and altitude of LEO is greater than that of GSO
- 11) Which one of the following shows the CORRECT variation of stagnation temperature along the axis of an ideal ram jet engine?





- 12) A rocket motor has a chamber pressure of 100 bar and chamber temperature of 3000 K. The ambient pressure is 1 bar. Assume that the specific heat at constant pressure is 1 kJ/kg-K. Also assume that the flow in the nozzle is isentropic and optimally expanded. The exit static temperature in K is
 - a) 805
 - b) 845
 - c) 905
 - d) 945

Q.26 to Q.55 carry two marks each

13) $I = \iint_S (y^2\hat{i} + z^2\hat{j} + x^2\hat{k}) (\cdot(x\hat{i} + y\hat{j} + z\hat{k})) dS$, where S denotes the surface of the sphere of unit radius centered at the origin. Here \hat{i} , \hat{j} and \hat{k} denote three orthogonal unit vectors. The value of I is