



Middle East Technical University Northern Cyprus Campus
Computer Engineering Program

CNG491 Computer Engineering Design I

Markopy Documentation

Ata Hakçıl - 2243467
Osman Ömer Yıldıztuğay - 1921956
Celal Sahir Çetiner - 1755420
Yunus Emre Yılmaz - 2243723

Supervised by
Assoc. Prof. Dr. Okan Topçu

0.4.1 Documentation

1 Markov Passwords	3
1.1 About The Project	3
1.1.1 Built With	3
1.2 Getting Started	3
1.2.1 Prerequisites	4
1.2.2 Installing Dependencies	4
1.2.3 Installation	4
1.2.4 Building	4
1.3 Linux	4
1.4 Windows	5
1.5 Known Common issues	5
1.5.1 Linux	5
1.5.1.1 Markopy - Python.h - Not found	5
1.5.1.2 Markopy/MarkovPasswords - *.so not found, or other library related issues when building	5
1.5.2 Windows	5
1.5.2.1 Boost - Bootstrap.bat "ctype.h" not found	5
1.5.2.2 Cannot open file "*.lib"	5
1.5.2.3 Python.h not found	5
1.5.2.4 Simplified Theory	5
1.5.3 Contributing	6
1.5.4 Contact	6
2 Deprecated List	7
3 Namespace Index	9
3.1 Namespace List	9
4 Hierarchical Index	11
4.1 Class Hierarchy	11
5 Class Index	13
5.1 Class List	13
6 File Index	15
6.1 File List	15
7 Namespace Documentation	17
7.1 markopy_cli Namespace Reference	17
7.1.1 Detailed Description	17
7.1.2 Function Documentation	17
7.1.2.1 cli_generate()	17
7.1.2.2 cli_init()	18
7.1.2.3 cli_train()	18
7.1.3 Variable Documentation	19

7.1.3.1 action	19
7.1.3.2 args	19
7.1.3.3 bulk	19
7.1.3.4 corpus_list	19
7.1.3.5 default	19
7.1.3.6 help	19
7.1.3.7 model	19
7.1.3.8 model_base	19
7.1.3.9 model_extension	20
7.1.3.10 model_list	20
7.1.3.11 output	20
7.1.3.12 output_file_name	20
7.1.3.13 output_forced	20
7.1.3.14 parser	20
7.1.3.15 True	20
7.2 Markov Namespace Reference	20
7.2.1 Detailed Description	21
7.3 Markov::API Namespace Reference	21
7.3.1 Detailed Description	21
7.4 Markov::API::CLI Namespace Reference	21
7.4.1 Detailed Description	22
7.4.2 Typedef Documentation	22
7.4.2.1 ProgramOptions	22
7.4.3 Function Documentation	22
7.4.3.1 operator<<()	22
7.5 Markov::API::Concurrency Namespace Reference	22
7.5.1 Detailed Description	22
7.6 Markov::API::CUDA Namespace Reference	22
7.6.1 Detailed Description	23
7.6.2 Function Documentation	23
7.6.2.1 FastRandomWalkCUDAKernel()	23
7.6.2.2 strchr()	24
7.7 Markov::API::CUDA::Random Namespace Reference	24
7.7.1 Detailed Description	24
7.7.2 Function Documentation	24
7.7.2.1 devrandom()	24
7.8 Markov::GUI Namespace Reference	25
7.8.1 Detailed Description	25
7.9 Markov::Markopy Namespace Reference	25
7.9.1 Function Documentation	25
7.9.1.1 BOOST_PYTHON_MODULE()	25
7.10 Markov::Random Namespace Reference	26

7.10.1 Detailed Description	26
7.11 model_2gram Namespace Reference	26
7.11.1 Detailed Description	27
7.11.2 Variable Documentation	27
7.11.2.1 alphabet	27
7.11.2.2 f	27
7.12 random Namespace Reference	27
7.12.1 Detailed Description	27
7.13 random-model Namespace Reference	27
7.13.1 Variable Documentation	27
7.13.1.1 alphabet	27
7.13.1.2 f	28
7.14 Testing Namespace Reference	28
7.14.1 Detailed Description	28
7.15 Testing::MarkovModel Namespace Reference	28
7.15.1 Detailed Description	28
7.15.2 Function Documentation	28
7.15.2.1 TEST_CLASS() [1/3]	28
7.15.2.2 TEST_CLASS() [2/3]	29
7.15.2.3 TEST_CLASS() [3/3]	30
7.16 Testing::MarkovPasswords Namespace Reference	31
7.16.1 Detailed Description	31
7.17 Testing::MVP Namespace Reference	31
7.17.1 Detailed Description	32
7.18 Testing::MVP::MarkovModel Namespace Reference	32
7.18.1 Detailed Description	32
7.18.2 Function Documentation	32
7.18.2.1 TEST_CLASS() [1/3]	32
7.18.2.2 TEST_CLASS() [2/3]	33
7.18.2.3 TEST_CLASS() [3/3]	34
7.19 Testing::MVP::MarkovPasswords Namespace Reference	37
7.19.1 Detailed Description	37
7.19.2 Function Documentation	37
7.19.2.1 TEST_CLASS()	38
8 Class Documentation	41
8.1 Markov::API::CLI::_programOptions Struct Reference	41
8.1.1 Detailed Description	43
8.1.2 Member Data Documentation	43
8.1.2.1 bExport	43
8.1.2.2 bFailure	43
8.1.2.3 blmport	43

8.1.2.4 datasetname	44
8.1.2.5 exportname	44
8.1.2.6 generateN	44
8.1.2.7 importname	44
8.1.2.8 outputfilename	44
8.1.2.9 seperator	44
8.1.2.10 wordlistname	44
8.2 Markov::GUI::about Class Reference	45
8.2.1 Detailed Description	46
8.2.2 Constructor & Destructor Documentation	46
8.2.2.1 about()	46
8.2.3 Member Data Documentation	46
8.2.3.1 ui	46
8.3 Markov::API::CLI::Argparse Class Reference	46
8.3.1 Detailed Description	48
8.3.2 Constructor & Destructor Documentation	48
8.3.2.1 Argparse() [1/2]	48
8.3.2.2 Argparse() [2/2]	48
8.3.3 Member Function Documentation	50
8.3.3.1 getProgramOptions()	50
8.3.3.2 help()	50
8.3.3.3 parse()	51
8.3.3.4 setProgramOptions()	51
8.3.4 Member Data Documentation	52
8.3.4.1 po	52
8.4 Markov::GUI::CLI Class Reference	52
8.4.1 Detailed Description	53
8.4.2 Constructor & Destructor Documentation	53
8.4.2.1 CLI()	53
8.4.3 Member Function Documentation	53
8.4.3.1 about	54
8.4.3.2 start	54
8.4.3.3 statistics	54
8.4.4 Member Data Documentation	54
8.4.4.1 ui	54
8.5 Markov::API::CUDA::CUDADeviceController Class Reference	54
8.5.1 Detailed Description	56
8.5.2 Member Function Documentation	56
8.5.2.1 CudaCheckNotifyErr()	56
8.5.2.2 CudaMalloc2DToFlat()	56
8.5.2.3 CudaMemcpy2DToFlat()	57
8.5.2.4 CudaMigrate2DFlat()	58

8.5.2.5 ListCudaDevices()	59
8.6 Markov::API::CUDA::CUDAModelMatrix Class Reference	60
8.6.1 Detailed Description	64
8.6.2 Member Function Documentation	64
8.6.2.1 AdjustEdge()	64
8.6.2.2 AllocVRAMOutputBuffer()	65
8.6.2.3 ConstructMatrix()	65
8.6.2.4 CudaCheckNotifyErr()	67
8.6.2.5 CudaMalloc2DToFlat()	67
8.6.2.6 CudaMemcpy2DToFlat()	68
8.6.2.7 CudaMigrate2DFlat()	69
8.6.2.8 DeallocateMatrix()	70
8.6.2.9 DumpJSON()	71
8.6.2.10 Edges()	72
8.6.2.11 Export() [1/2]	72
8.6.2.12 Export() [2/2]	72
8.6.2.13 FastRandomWalk() [1/2]	73
8.6.2.14 FastRandomWalk() [2/2]	73
8.6.2.15 FastRandomWalkPartition()	74
8.6.2.16 FastRandomWalkThread()	76
8.6.2.17 FlattenMatrix()	77
8.6.2.18 Generate()	77
8.6.2.19 GenerateThread()	78
8.6.2.20 Import() [1/2]	79
8.6.2.21 Import() [2/2]	80
8.6.2.22 ListCudaDevices()	81
8.6.2.23 MigrateMatrix()	81
8.6.2.24 Nodes()	81
8.6.2.25 OpenDatasetFile()	82
8.6.2.26 RandomWalk()	82
8.6.2.27 Save()	83
8.6.2.28 StarterNode()	84
8.6.2.29 Train()	84
8.6.2.30 TrainThread()	85
8.6.3 Member Data Documentation	86
8.6.3.1 datasetFile	86
8.6.3.2 device_edgeMatrix	86
8.6.3.3 device_matrixIndex	86
8.6.3.4 device_outputBuffer	86
8.6.3.5 device_totalEdgeWeights	87
8.6.3.6 device_valueMatrix	87
8.6.3.7 edgeMatrix	87

8.6.3.8 edges	87
8.6.3.9 flatEdgeMatrix	87
8.6.3.10 flatValueMatrix	87
8.6.3.11 matrixIndex	87
8.6.3.12 matrixSize	87
8.6.3.13 modelSavefile	88
8.6.3.14 nodes	88
8.6.3.15 outputBuffer	88
8.6.3.16 outputFile	88
8.6.3.17 ready	88
8.6.3.18 starterNode	88
8.6.3.19 totalEdgeWeights	88
8.6.3.20 valueMatrix	89
8.7 Markov::Random::DefaultRandomEngine Class Reference	89
8.7.1 Detailed Description	90
8.7.2 Member Function Documentation	91
8.7.2.1 distribution()	91
8.7.2.2 generator()	91
8.7.2.3 random()	92
8.7.2.4 rd()	92
8.8 Markov::Edge< NodeStorageType > Class Template Reference	93
8.8.1 Detailed Description	95
8.8.2 Constructor & Destructor Documentation	95
8.8.2.1 Edge() [1/2]	95
8.8.2.2 Edge() [2/2]	95
8.8.3 Member Function Documentation	96
8.8.3.1 AdjustEdge()	96
8.8.3.2 EdgeWeight()	96
8.8.3.3 LeftNode()	96
8.8.3.4 RightNode()	97
8.8.3.5 SetLeftEdge()	97
8.8.3.6 SetRightEdge()	97
8.8.3.7 TraverseNode()	98
8.8.4 Member Data Documentation	98
8.8.4.1 _left	98
8.8.4.2 _right	98
8.8.4.3 _weight	98
8.9 Markov::API::MarkovPasswords Class Reference	98
8.9.1 Detailed Description	102
8.9.2 Constructor & Destructor Documentation	102
8.9.2.1 MarkovPasswords() [1/2]	102
8.9.2.2 MarkovPasswords() [2/2]	102

8.9.3 Member Function Documentation	102
8.9.3.1 AdjustEdge()	103
8.9.3.2 Edges()	103
8.9.3.3 Export() [1/2]	103
8.9.3.4 Export() [2/2]	104
8.9.3.5 Generate()	104
8.9.3.6 GenerateThread()	105
8.9.3.7 Import() [1/2]	106
8.9.3.8 Import() [2/2]	106
8.9.3.9 Nodes()	107
8.9.3.10 OpenDatasetFile()	108
8.9.3.11 RandomWalk()	108
8.9.3.12 Save()	109
8.9.3.13 StarterNode()	110
8.9.3.14 Train()	110
8.9.3.15 TrainThread()	111
8.9.4 Member Data Documentation	112
8.9.4.1 datasetFile	112
8.9.4.2 edges	112
8.9.4.3 modelSavefile	112
8.9.4.4 nodes	112
8.9.4.5 outputFile	112
8.9.4.6 starterNode	113
8.10 Markov::GUI::MarkovPasswordsGUI Class Reference	113
8.10.1 Detailed Description	114
8.10.2 Member Function Documentation	115
8.10.2.1 MarkovPasswordsGUI ::pass	115
8.10.2.2 MarkovPasswordsGUI::benchmarkSelected	115
8.10.2.3 MarkovPasswordsGUI::comparisonSelected	115
8.10.2.4 MarkovPasswordsGUI::home	115
8.10.2.5 MarkovPasswordsGUI::model	115
8.10.2.6 MarkovPasswordsGUI::modelvisSelected	115
8.10.2.7 MarkovPasswordsGUI::visualDebugSelected	115
8.10.3 Member Data Documentation	115
8.10.3.1 ui	115
8.11 Markov::API::CUDA::Random::Marsaglia Class Reference	115
8.11.1 Detailed Description	118
8.11.2 Member Function Documentation	118
8.11.2.1 CudaCheckNotifyErr()	118
8.11.2.2 CudaMalloc2DToFlat()	118
8.11.2.3 CudaMemcpy2DToFlat()	119
8.11.2.4 CudaMigrate2DFlat()	120

8.11.2.5 distribution()	121
8.11.2.6 generator()	122
8.11.2.7 ListCudaDevices()	122
8.11.2.8 MigrateToVRAM()	123
8.11.2.9 random()	123
8.11.2.10 rd()	124
8.11.3 Member Data Documentation	124
8.11.3.1 x	124
8.11.3.2 y	124
8.11.3.3 z	124
8.12 Markov::Random::Marsaglia Class Reference	125
8.12.1 Detailed Description	127
8.12.2 Constructor & Destructor Documentation	127
8.12.2.1 Marsaglia()	127
8.12.3 Member Function Documentation	127
8.12.3.1 distribution()	127
8.12.3.2 generator()	128
8.12.3.3 random()	128
8.12.3.4 rd()	129
8.12.4 Member Data Documentation	129
8.12.4.1 x	129
8.12.4.2 y	129
8.12.4.3 z	130
8.13 Markov::GUI::menu Class Reference	130
8.13.1 Detailed Description	131
8.13.2 Constructor & Destructor Documentation	131
8.13.2.1 menu()	131
8.13.3 Member Function Documentation	132
8.13.3.1 about	132
8.13.3.2 visualization	132
8.13.4 Member Data Documentation	132
8.13.4.1 ui	132
8.14 Markov::Random::Mersenne Class Reference	132
8.14.1 Detailed Description	134
8.14.2 Member Function Documentation	135
8.14.2.1 distribution()	135
8.14.2.2 generator()	135
8.14.2.3 random()	136
8.14.2.4 rd()	136
8.15 Markov::Model< NodeStorageType > Class Template Reference	137
8.15.1 Detailed Description	139
8.15.2 Constructor & Destructor Documentation	139

8.15.2.1 Model()	139
8.15.3 Member Function Documentation	139
8.15.3.1 AdjustEdge()	140
8.15.3.2 Edges()	140
8.15.3.3 Export() [1/2]	141
8.15.3.4 Export() [2/2]	141
8.15.3.5 Import() [1/2]	142
8.15.3.6 Import() [2/2]	142
8.15.3.7 Nodes()	144
8.15.3.8 RandomWalk()	144
8.15.3.9 StarterNode()	145
8.15.4 Member Data Documentation	145
8.15.4.1 edges	146
8.15.4.2 nodes	146
8.15.4.3 starterNode	146
8.16 Markov::API::ModelMatrix Class Reference	146
8.16.1 Detailed Description	150
8.16.2 Constructor & Destructor Documentation	150
8.16.2.1 ModelMatrix()	150
8.16.3 Member Function Documentation	150
8.16.3.1 AdjustEdge()	151
8.16.3.2 ConstructMatrix()	151
8.16.3.3 DeallocateMatrix()	153
8.16.3.4 DumpJSON()	153
8.16.3.5 Edges()	154
8.16.3.6 Export() [1/2]	155
8.16.3.7 Export() [2/2]	155
8.16.3.8 FastRandomWalk()	155
8.16.3.9 FastRandomWalkPartition()	157
8.16.3.10 FastRandomWalkThread()	159
8.16.3.11 Generate()	160
8.16.3.12 GenerateThread()	161
8.16.3.13 Import() [1/2]	162
8.16.3.14 Import() [2/2]	163
8.16.3.15 Nodes()	164
8.16.3.16 OpenDatasetFile()	164
8.16.3.17 RandomWalk()	165
8.16.3.18 Save()	166
8.16.3.19 StarterNode()	167
8.16.3.20 Train()	167
8.16.3.21 TrainThread()	168
8.16.4 Member Data Documentation	169

8.16.4.1 datasetFile	169
8.16.4.2 edgeMatrix	169
8.16.4.3 edges	169
8.16.4.4 matrixIndex	169
8.16.4.5 matrixSize	169
8.16.4.6 modelSavefile	169
8.16.4.7 nodes	170
8.16.4.8 outputFile	170
8.16.4.9 ready	170
8.16.4.10 starterNode	170
8.16.4.11 totalEdgeWeights	170
8.16.4.12 valueMatrix	170
8.17 Markov::Node< storageType > Class Template Reference	170
8.17.1 Detailed Description	173
8.17.2 Constructor & Destructor Documentation	173
8.17.2.1 Node() [1/2]	173
8.17.2.2 Node() [2/2]	174
8.17.3 Member Function Documentation	175
8.17.3.1 Edges()	175
8.17.3.2 FindEdge() [1/2]	175
8.17.3.3 FindEdge() [2/2]	175
8.17.3.4 Link() [1/2]	176
8.17.3.5 Link() [2/2]	176
8.17.3.6 NodeValue()	177
8.17.3.7 RandomNext()	177
8.17.3.8 TotalEdgeWeights()	178
8.17.3.9 UpdateEdges()	178
8.17.3.10 UpdateTotalVerticeWeight()	179
8.17.4 Member Data Documentation	179
8.17.4.1 _value	179
8.17.4.2 edges	179
8.17.4.3 edgesV	179
8.17.4.4 total_edge_weights	179
8.18 Markov::Random::RandomEngine Class Reference	180
8.18.1 Detailed Description	181
8.18.2 Member Function Documentation	181
8.18.2.1 random()	181
8.19 Markov::API::CLI::Terminal Class Reference	181
8.19.1 Detailed Description	183
8.19.2 Member Enumeration Documentation	183
8.19.2.1 color	183
8.19.3 Constructor & Destructor Documentation	183

8.19.3.1 Terminal()	183
8.19.4 Member Data Documentation	183
8.19.4.1 colormap	184
8.19.4.2 endl	184
8.20 Markov::API::Concurrency::ThreadSharedListHandler Class Reference	184
8.20.1 Detailed Description	186
8.20.2 Constructor & Destructor Documentation	186
8.20.2.1 ThreadSharedListHandler()	186
8.20.3 Member Function Documentation	187
8.20.3.1 next()	187
8.20.4 Member Data Documentation	187
8.20.4.1 listfile	187
8.20.4.2 mlock	187
8.21 Markov::GUI::Train Class Reference	188
8.21.1 Detailed Description	189
8.21.2 Constructor & Destructor Documentation	189
8.21.2.1 Train()	189
8.21.3 Member Function Documentation	189
8.21.3.1 home	189
8.21.3.2 train	189
8.21.4 Member Data Documentation	189
8.21.4.1 ui	189
9 File Documentation	191
9.1 about.h File Reference	191
9.2 about.h	191
9.3 argparse.cpp File Reference	192
9.4 argparse.cpp	192
9.5 argparse.h File Reference	192
9.5.1 Macro Definition Documentation	194
9.5.1.1 BOOST_ALL_DYN_LINK	194
9.6 argparse.h	194
9.7 CLI.h File Reference	197
9.8 CLI.h	198
9.9 cudaDeviceController.h File Reference	198
9.10 cudaDeviceController.h	199
9.11 cudaModelMatrix.h File Reference	201
9.12 cudaModelMatrix.h	202
9.13 cudarandom.h File Reference	203
9.14 cudarandom.h	204
9.15 dllmain.cpp File Reference	205
9.16 dllmain.cpp	205

9.17 edge.h File Reference	206
9.18 edge.h	207
9.19 framework.h File Reference	209
9.19.1 Macro Definition Documentation	209
9.19.1.1 WIN32_LEAN_AND_MEAN	209
9.20 framework.h	209
9.21 main.cpp File Reference	209
9.21.1 Function Documentation	210
9.21.1.1 main()	210
9.22 src/main.cpp	211
9.23 main.cpp File Reference	211
9.23.1 Function Documentation	212
9.23.1.1 main()	212
9.24 UI/src/main.cpp	213
9.25 markopy.cpp File Reference	213
9.25.1 Macro Definition Documentation	214
9.25.1.1 BOOST_PYTHON_STATIC_LIB	214
9.26 markopy.cpp	214
9.27 markopy_cli.py File Reference	214
9.28 markopy_cli.py	215
9.29 markovPasswords.cpp File Reference	217
9.29.1 Function Documentation	218
9.29.1.1 intHandler()	218
9.29.2 Variable Documentation	218
9.29.2.1 keepRunning	218
9.30 markovPasswords.cpp	219
9.31 markovPasswords.h File Reference	220
9.32 markovPasswords.h	221
9.33 MarkovPasswordsGUI.cpp File Reference	223
9.34 MarkovPasswordsGUI.cpp	223
9.35 MarkovPasswordsGUI.h File Reference	224
9.36 MarkovPasswordsGUI.h	225
9.37 menu.cpp File Reference	225
9.38 menu.cpp	225
9.39 menu.h File Reference	226
9.40 menu.h	227
9.41 model.h File Reference	227
9.42 model.h	228
9.43 model_2gram.py File Reference	232
9.44 model_2gram.py	233
9.45 modelMatrix.cpp File Reference	233
9.46 modelMatrix.cpp	233

9.47 modelMatrix.h File Reference	236
9.48 modelMatrix.h	237
9.49 node.h File Reference	239
9.50 node.h	240
9.51 pch.cpp File Reference	244
9.52 MarkovModel/src/pch.cpp	244
9.53 pch.cpp File Reference	244
9.54 UnitTests/pch.cpp	245
9.55 pch.h File Reference	245
9.56 MarkovModel/src/pch.h	245
9.57 pch.h File Reference	246
9.58 UnitTests/pch.h	246
9.59 random-model.py File Reference	246
9.60 random-model.py	246
9.61 random.h File Reference	247
9.62 random.h	248
9.63 README.md File Reference	250
9.64 term.cpp File Reference	250
9.64.1 Function Documentation	251
9.64.1.1 operator<<()	251
9.65 term.cpp	251
9.66 term.h File Reference	252
9.66.1 Macro Definition Documentation	253
9.66.1.1 TERM_FAIL	253
9.66.1.2 TERM_INFO	254
9.66.1.3 TERM_SUCC	254
9.66.1.4 TERM_WARN	254
9.67 term.h	254
9.68 threadSharedListHandler.cpp File Reference	255
9.69 threadSharedListHandler.cpp	255
9.70 threadSharedListHandler.h File Reference	255
9.71 threadSharedListHandler.h	256
9.72 Train.h File Reference	258
9.73 Train.h	258
9.74 UnitTests.cpp File Reference	258
9.75 UnitTests.cpp	260
Index	269

Chapter 1

Markov Passwords

Table of Contents

Markov Passwords

Generate wordlists with markov models.

[Wiki](#) · [Complete documentation](#) · [Report Bug](#) · [Add a Bug](#)

<details open="open">

1. [About The Project](#)
 - [Built With](#)
2. [Getting Started](#)
 - [Prerequisites](#)
 - [Installation](#)
3. [Contributing](#)
4. [Contact](#)

</details>

1.1 About The Project

This project aims to generate wordlists using markov models.

1.1.1 Built With

- CPP, with dependencies: boost, python3-dev, QT-5.

1.2 Getting Started

If you'd just like to use the project without contributing, check out the releases page. If you want to build, check out wiki for building the project.

1.2.1 Prerequisites

1.2.1.0.1 MarkovModel

- Make for linux, Visual Studio/MSBuild for Windows.

1.2.1.0.2 MarkovPasswords

- Boost.ProgramOptions (tested on 1.76.0)

1.2.1.0.3 Markopy

- Boost.Python (tested on 1.76.0)
- Python development package (tested on python 3.8)

1.2.1.0.4 MarkovPasswordsGUI

- QT development environment.

1.2.2 Installing Dependencies

1.2.2.0.1 Windows

- QT: Install [QT For Windows](#)
- Boost:
 - Download Boost from [its website](#)
 - Unzip the contents.
 - Launch "Visual Studio Developer Command Prompt"
 - Move to the boost installation directory. Run `bootstrap.bat`
 - Run `b2`.
- Python: You can use the windows app store to download python runtime and libraries.

1.2.2.0.2 Linux

- QT: Follow [this guide](#) to install QT on Linux.
- Boost: run `sudo apt-get install libboost-all-dev`
- Python: run `sudo apt-get install python3`

1.2.3 Installation

See the Wiki Page

1.2.4 Building

Building process can be fairly complicated depending on the environment.

1.3 Linux

If you've set up the dependencies, you can just build the project with make. List of directives is below.

```
.PHONY: all
all: model mp
model: $(INCLUDE) /$(MM_LIB)
mp: $(BIN) /$(MP_EXEC)
markopy: $(BIN) /$(MPY_SO)
.PHONY: clean
clean:
    $(RM) -r $(BIN) /*
```

1.4 Windows

Set up correct environment variables for BOOST_ROOT% (folder containing boost, libs, stage, tools) and PYTHON_PATH% (folder containing include, lib, libs, Tools, python.exe/python3.exe).

If you've set up the dependencies and environment variables correctly, you can open the solution with Visual Studio and build with that.

1.5 Known Common issues

1.5.1 Linux

1.5.1.1 Markopy - Python.h - Not found

Make sure you have the development version of python package, which includes the required header files. Check if header files exist: `/usr/include/python*`

If it doesn't, run `sudo apt-get install python3-dev`

1.5.1.2 Markopy/MarkovPasswords - *.so not found, or other library related issues when building

Run `ls /usr/lib/x86_64-linux-gnu/ | grep boost` and check the shared object filenames. A common issue is that libboost is required but filenames are formatted as libboost, or vice versa.

Do the same for python related library issues, run: `ls /usr/lib/x86_64-linux-gnu/ | grep python` to verify filename format is as required.

If not, you can modify the makefile, or create symlinks such as: `ln -s /usr/lib/x86_64-linux-gnu/libboostpython38.so /usr/lib/x86_64-linux-gnu/boost_python38.so`

1.5.2 Windows

1.5.2.1 Boost - Bootstrap.bat "ctype.h" not found

- Make sure you are working in the "Visual Studio Developer Command Prompt" terminal.
- Make sure you have Windows 10 SDK installed.
- From VS developer terminal, run `echo INCLUDE%`. If result does not have the windows sdk folders, run the following before running bootstrap (change your sdk version instead of 10.0.19041.0):

```
set INCLUDE=%INCLUDE%;C:\Program Files (x86)\Windows Kits\NETFXSDK\4.8\include\um;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\ucrt;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\shared;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\um;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\winrt;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\cppwinrt
set LIB=%LIB%;C:\Program Files (x86)\Windows Kits\10\lib\10.0.19041.0\ucrt\x64;C:\Program Files (x86)\Windows Kits\10\lib\10.0.19041.0\um\x64
```

1.5.2.2 Cannot open file "*.lib"

Make sure you have set the BOOST_ROOT environment variable correctly. Make sure you ran `b2` to build library files from boost sources.

1.5.2.3 Python.h not found

Make sure you have python installed, and make sure you set PYTHON_PATH environment variable.

1.5.2.4 Simplified Theory

What is a markov model Below, is the example [Markov](#) Model which can generate strings with the alphabet "a,b,c"

Iteration 1 Below is a demonstration of how training will be done. For this example, we are going to adjust the model with string "ab", and our occurrence will be "3" From MarkovPasswords, inside the train function, Model::adjust is called with "ab" and "3" parameters.

Now, `Model::adjust` will iteratively adjust the edge weights accordingly. It starts by adjusting weight between start and "a" node. This is done by calling `Edge::adjust` of the edge between the nodes. After adjustment, `ajust` function iterates to the next character, "b", and does the same thing. As this string is finished, it will adjust the final weight, `b->"end"`

Iteration 2 This time, same procedure will be applied for "bacb" string, with occurrence value of 12.

Iteration 38271 As the model is trained, hidden linguistical patterns start to appear, and our model looks like this. With our dataset, without doing any kind of linguistic analysis ourselves, our [Markov](#) Model has highlighted that strings are more likely to start with a, b tends to follow a, and a is likely to be repeated in the string.

1.5.3 Contributing

Feel free to contribute.

1.5.4 Contact

Twitter - [@ahakcil](#)

Chapter 2

Deprecated List

Member [Markov::API::MarkovPasswords::Generate](#) (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20)

See [Markov::API::MatrixModel::FastRandomWalk](#) for more information.

Chapter 3

Namespace Index

3.1 Namespace List

Here is a list of all namespaces with brief descriptions:

markopy_cli	17
Markov	
Namespace for the markov-model related classes. Contains Model , Node and Edge classes	20
Markov::API	
Namespace for the MarkovPasswords API	21
Markov::API::CLI	
Structure to hold parsed cli arguments	21
Markov::API::Concurrency	
Namespace for Concurrency related classes	22
Markov::API::CUDA	
Namespace for objects requiring CUDA libraries	22
Markov::API::CUDA::Random	
Namespace for Random engines operable under device space	24
Markov::GUI	
Namespace for MarkovPasswords API GUI wrapper	25
Markov::Markopy	25
Markov::Random	
Objects related to RNG	26
model_2gram	26
random	27
random-model	27
Testing	
Namespace for Microsoft Native Unit Testing Classes	28
Testing::MarkovModel	
Testing namespace for MarkovModel	28
Testing::MarkovPasswords	
Testing namespace for MarkovPasswords	31
Testing::MVP	
Testing Namespace for Minimal Viable Product	31
Testing::MVP::MarkovModel	
Testing Namespace for MVP MarkovModel	32
Testing::MVP::MarkovPasswords	
Testing namespace for MVP MarkovPasswords	37

Chapter 4

Hierarchical Index

4.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Markov::API::CLI::_programOptions	41
Markov::API::CLI::Argparse	46
Markov::API::CUDA::CUDADeviceController	54
Markov::API::CUDA::CUDAModelMatrix	60
Markov::API::CUDA::Random::Marsaglia	115
Markov::Edge< NodeStorageType >	93
Markov::Edge< char >	93
Markov::Edge< storageType >	93
Markov::Model< NodeStorageType >	137
Markov::Model< char >	137
Markov::API::MarkovPasswords	98
Markov::API::ModelMatrix	146
Markov::API::CUDA::CUDAModelMatrix	60
Markov::Node< storageType >	170
Markov::Node< char >	170
Markov::Node< NodeStorageType >	170
QMainWindow	
Markov::GUI::about	45
Markov::GUI::CLI	52
Markov::GUI::MarkovPasswordsGUI	113
Markov::GUI::menu	130
Markov::GUI::Train	188
Markov::Random::RandomEngine	180
Markov::Random::DefaultRandomEngine	89
Markov::Random::Marsaglia	125
Markov::API::CUDA::Random::Marsaglia	115
Markov::Random::Mersenne	132
Markov::API::CLI::Terminal	181
Markov::API::Concurrency::ThreadSharedListHandler	184

Chapter 5

Class Index

5.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Markov::API::CLI::_programOptions	
Structure to hold parsed cli arguments	41
Markov::GUI::about	
QT Class for about page	45
Markov::API::CLI::Argparse	
Parse command line arguments	46
Markov::GUI::CLI	
QT CLI Class	52
Markov::API::CUDA::CUDADeviceController	
Controller class for CUDA device	54
Markov::API::CUDA::CUDAModelMatrix	
Extension of Markov::API::ModelMatrix which is modified to run on GPU devices	60
Markov::Random::DefaultRandomEngine	
Implementation using Random.h default random engine	89
Markov::Edge< NodeStorageType >	
Edge class used to link nodes in the model together	93
Markov::API::MarkovPasswords	
Markov::Model with char represented nodes	98
Markov::GUI::MarkovPasswordsGUI	
Reporting UI	113
Markov::API::CUDA::Random::Marsaglia	
Extension of Markov::Random::Marsaglia which is capable of working on device space	115
Markov::Random::Marsaglia	
Implementation of Marsaglia Random Engine	125
Markov::GUI::menu	
QT Menu class	130
Markov::Random::Mersenne	
Implementation of Mersenne Twister Engine	132
Markov::Model< NodeStorageType >	
Class for the final Markov Model , constructed from nodes and edges	137
Markov::API::ModelMatrix	
Class to flatten and reduce Markov::Model to a Matrix	146
Markov::Node< storageType >	
A node class that for the vertices of model. Connected with eachother using Edge	170
Markov::Random::RandomEngine	
An abstract class for Random Engine	180
Markov::API::CLI::Terminal	
Pretty colors for Terminal . Windows Only	181
Markov::API::Concurrency::ThreadSharedListHandler	
Simple class for managing shared access to file	184

[Markov::GUI::Train](#)QT Training page class [188](#)

Chapter 6

File Index

6.1 File List

Here is a list of all files with brief descriptions:

about.h	191
argparse.cpp	192
argparse.h	192
CLI.h	197
cudaDeviceController.h	198
cudaModelMatrix.h	201
cudarandom.h	203
dllmain.cpp	205
edge.h	206
framework.h	209
src/main.cpp	209
UI/src/main.cpp	211
markopy.cpp	213
markopy_cli.py	214
markovPasswords.cpp	217
markovPasswords.h	220
MarkovPasswordsGUI.cpp	223
MarkovPasswordsGUI.h	224
menu.cpp	225
menu.h	226
model.h	227
model_2gram.py	232
modelMatrix.cpp	233
modelMatrix.h	236
node.h	239
MarkovModel/src/pch.cpp	244
UnitTests/pch.cpp	244
MarkovModel/src/pch.h	245
UnitTests/pch.h	246
random-model.py	246
random.h	247
term.cpp	250
term.h	252
threadSharedListHandler.cpp	255
threadSharedListHandler.h	255
Train.h	258
UnitTests.cpp	258

Chapter 7

Namespace Documentation

7.1 markopy_cli Namespace Reference

Functions

- def `cli_init` (input_model)
- def `cli_train` (model, dataset, separator, output, output_forced=False, bulk=False)
- def `cli_generate` (model, wordlist, bulk=False)

Variables

- `parser`
- `help`
- `default`
- `action`
- `args` = parser.parse_args()
- `corpus_list` = os.listdir(args.dataset)
- def `model` = `cli_init`(args.input)
- `output_file_name` = corpus
- string `model_extension` = ""
- `output_forced`
- `True`
- `bulk`
- `model_list` = os.listdir(args.input)
- `model_base` = input
- `output`

7.1.1 Detailed Description

```
@namespace Markov::Markopy::Python
```

7.1.2 Function Documentation

7.1.2.1 cli_generate()

```
def markopy_cli.cli_generate (  
    model,  
    wordlist,  
    bulk = False )
```

Definition at line 114 of file [markopy_cli.py](#).

```
00114 def cli_generate(model, wordlist, bulk=False):
00115     if not (wordlist or args.count):
00116         logging.pprint("Generation mode requires -w/--wordlist and -n/--count parameters. Exiting.")
00117         exit(2)
00118
00119     if (bulk and os.path.isfile(wordlist)):
00120         logging.pprint(f"{wordlist} exists and will be overwritten.", 1)
00121     model.Generate(int(args.count), wordlist, int(args.min), int(args.max), int(args.threads))
00122
00123
```

7.1.2.2 cli_init()

```
def markopy_cli.cli_init (
    input_model )
```

Definition at line 61 of file [markopy_cli.py](#).

```
00061 def cli_init(input_model):
00062     logging.VERBOSITY = 0
00063     if args.verbosity:
00064         logging.VERBOSITY = args.verbosity
00065         logging.pprint(f"Verbosity set to {args.verbosity}.", 2)
00066
00067     logging.pprint("Initializing model.", 1)
00068     model = markopy.ModelMatrix()
00069     logging.pprint("Model initialized.", 2)
00070
00071     logging.pprint("Importing model file.", 1)
00072
00073     if (not os.path.isfile(input_model)):
00074         logging.pprint(f"Model file at {input_model} not found. Check the file path, or working
00075         directory")
00076         exit(1)
00077
00078     model.Import(input_model)
00079     logging.pprint("Model imported successfully.", 2)
00080     return model
00081
```

7.1.2.3 cli_train()

```
def markopy_cli.cli_train (
    model,
    dataset,
    seperator,
    output,
    output_forced = False,
    bulk = False )
```

Definition at line 82 of file [markopy_cli.py](#).

```
00082 def cli_train(model, dataset, seperator, output, output_forced=False, bulk=False):
00083     if not (dataset and seperator and (output or not output_forced)):
00084         logging.pprint(
00085             f"Training mode requires -d/--dataset{' ', -o/--output' if output_forced else ''} and
00086             -s/--seperator parameters. Exiting.")
00087         exit(2)
00088
00089     if (not bulk and not os.path.isfile(dataset)):
00090         logging.pprint(f"{dataset} doesn't exists. Check the file path, or working directory")
00091         exit(3)
00092
00093     if (output and os.path.isfile(output)):
00094         logging.pprint(f"{output} exists and will be overwritten.", 1)
00095
00096     if (seperator == '\\t'):
00097         logging.pprint("Escaping seperator.", 3)
00098         seperator = '\\t'
00099
00100     if (len(seperator) != 1):
00101         logging.pprint(f'Delimiter must be a single character, and "{seperator}" is not accepted.')
00102         exit(4)
00103
00104     logging.pprint(f'Starting training.', 3)
00105     model.Train(dataset, seperator, int(args.threads))
00106     logging.pprint(f'Training completed.', 2)
```

```
00107         if (output):
00108             logging.pprint(f'Exporting model to {output}', 2)
00109             model.Export(output)
00110         else:
00111             logging.pprint(f'Model will not be exported.', 1)
00112
00113
```

7.1.3 Variable Documentation

7.1.3.1 action

markopy_cli.action

Definition at line 49 of file [markopy_cli.py](#).

7.1.3.2 args

markopy_cli.args = parser.parse_args()

Definition at line 58 of file [markopy_cli.py](#).

7.1.3.3 bulk

markopy_cli.bulk

Definition at line 139 of file [markopy_cli.py](#).

7.1.3.4 corpus_list

markopy_cli.corpus_list = os.listdir(args.dataset)

Definition at line 130 of file [markopy_cli.py](#).

7.1.3.5 default

markopy_cli.default

Definition at line 41 of file [markopy_cli.py](#).

7.1.3.6 help

markopy_cli.help

Definition at line 27 of file [markopy_cli.py](#).

7.1.3.7 model

def markopy_cli.model = cli_init(args.input)

Definition at line 132 of file [markopy_cli.py](#).

7.1.3.8 model_base

markopy_cli.model_base = input

Definition at line 153 of file [markopy_cli.py](#).

7.1.3.9 model_extension

```
markopy_cli.model_extension = ""
```

Definition at line 135 of file [markopy_cli.py](#).

7.1.3.10 model_list

```
markopy_cli.model_list = os.listdir(args.input)
```

Definition at line 147 of file [markopy_cli.py](#).

7.1.3.11 output

```
markopy_cli.output
```

Definition at line 167 of file [markopy_cli.py](#).

7.1.3.12 output_file_name

```
markopy_cli.output_file_name = corpus
```

Definition at line 134 of file [markopy_cli.py](#).

7.1.3.13 output_forced

```
markopy_cli.output_forced
```

Definition at line 139 of file [markopy_cli.py](#).

7.1.3.14 parser

```
markopy_cli.parser
```

Initial value:

```
00001 = argparse.ArgumentParser(description="Python wrapper for MarkovPasswords.",
00002                               epilog=f, formatter_class=argparse.RawTextHelpFormatter)
```

Definition at line 12 of file [markopy_cli.py](#).

7.1.3.15 True

```
markopy_cli.True
```

Definition at line 139 of file [markopy_cli.py](#).

7.2 Markov Namespace Reference

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

Namespaces

- [API](#)

Namespace for the [MarkovPasswords API](#).

- [GUI](#)

namespace for MarkovPasswords [API GUI](#) wrapper

- [Markopy](#)
- [Random](#)

Objects related to RNG.

Classes

- class [Edge](#)
Edge class used to link nodes in the model together.
- class [Model](#)
class for the final [Markov Model](#), constructed from nodes and edges.
- class [Node](#)
A node class that for the vertices of model. Connected with eachother using [Edge](#).

7.2.1 Detailed Description

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

7.3 Markov::API Namespace Reference

Namespace for the [MarkovPasswords API](#).

Namespaces

- [CLI](#)
Structure to hold parsed cli arguments.
- [Concurrency](#)
Namespace for [Concurrency](#) related classes.
- [CUDA](#)
Namespace for objects requiring [CUDA](#) libraries.

Classes

- class [MarkovPasswords](#)
[Markov::Model](#) with char represented nodes.
- class [ModelMatrix](#)
Class to flatten and reduce [Markov::Model](#) to a Matrix.

7.3.1 Detailed Description

Namespace for the [MarkovPasswords API](#).

7.4 Markov::API::CLI Namespace Reference

Structure to hold parsed cli arguments.

Classes

- struct [_programOptions](#)
Structure to hold parsed cli arguments.
- class [Argparse](#)
Parse command line arguments.
- class [Terminal](#)
pretty colors for [Terminal](#). Windows Only.

Typedefs

- typedef struct [Markov::API::CLI::_programOptions](#) ProgramOptions
Structure to hold parsed cli arguments.

Functions

- `std::ostream & operator<< (std::ostream &os, const Markov::API::CLI::Terminal::color &c)`

7.4.1 Detailed Description

Structure to hold parsed cli arguments.
Namespace for the [CLI](#) objects

7.4.2 Typedef Documentation

7.4.2.1 ProgramOptions

`typedef struct Markov::API::CLI::_programOptions Markov::API::CLI::ProgramOptions`
Structure to hold parsed cli arguments.

7.4.3 Function Documentation

7.4.3.1 operator<<()

```
std::ostream& Markov::API::CLI::operator<< (
    std::ostream & os,
    const Markov::API::CLI::Terminal::color & c )
```

overload for `std::cout`.

Definition at line 60 of file [term.cpp](#).

```
00060                                     {
00061     char buf[6];
00062     sprintf(buf, "%d", Terminal::colormap.find(c)->second);
00063     os << "\e[1;" << buf << "m";
00064     return os;
00065 }
```

References [Markov::API::CLI::Terminal::colormap](#).

7.5 Markov::API::Concurrency Namespace Reference

Namespace for [Concurrency](#) related classes.

Classes

- class [ThreadSharedListHandler](#)
Simple class for managing shared access to file.

7.5.1 Detailed Description

Namespace for [Concurrency](#) related classes.

7.6 Markov::API::CUDA Namespace Reference

Namespace for objects requiring [CUDA](#) libraries.

Namespaces

- [Random](#)
*Namespace for [Random](#) engines operable under **device** space.*

Classes

- class [CUDADeviceController](#)
Controller class for [CUDA](#) device.
- class [CUDAModelMatrix](#)
Extension of [Markov::API::ModelMatrix](#) which is modified to run on GPU devices.

Functions

- `__global__ void FastRandomWalkCUDAKernel` (unsigned long int n, int minLen, int maxLen, char *outputBuffer, char *matrixIndex, long int *totalEdgeWeights, long int *valueMatrix, char *edgeMatrix, int matrixSize, int memoryPerKernelGrid, unsigned long *seed)
[CUDA](#) kernel for the [FastRandomWalk](#) operation.
- `__device__ char * strchr` (char *p, char c, int s_len)
*[strchr](#) implementation on **device** space*

7.6.1 Detailed Description

Namespace for objects requiring [CUDA](#) libraries.

7.6.2 Function Documentation

7.6.2.1 FastRandomWalkCUDAKernel()

```
__global__ void Markov::API::CUDA::FastRandomWalkCUDAKernel (
    unsigned long int n,
    int minLen,
    int maxLen,
    char * outputBuffer,
    char * matrixIndex,
    long int * totalEdgeWeights,
    long int * valueMatrix,
    char * edgeMatrix,
    int matrixSize,
    int memoryPerKernelGrid,
    unsigned long * seed )
```

[CUDA](#) kernel for the [FastRandomWalk](#) operation.

Will be initiated by CPU and continued by GPU (**global** tag)

Parameters

<i>n</i>	- Number of passwords to generate.
<i>minlen</i>	- minimum string length for a single generation
<i>maxLen</i>	- maximum string length for a single generation
<i>outputBuffer</i>	- VRAM ptr to the output buffer
<i>matrixIndex</i>	- VRAM ptr to the matrix indices
<i>totalEdgeWeights</i>	- VRAM ptr to the totalEdgeWeights array
<i>valueMatrix</i>	- VRAM ptr to the edge weights array
<i>edgeMatrix</i>	- VRAM ptr to the edge representations array
<i>matrixSize</i>	- Size of the matrix dimensions
<i>memoryPerKernelGrid</i>	- Maximum memory usage per kernel grid
<i>seed</i>	- seed chunk to generate the random from (generated & used by Marsaglia)

7.6.2.2 strchr()

```
__device__ char* Markov::API::CUDA::strchr (
    char * p,
    char c,
    int s_len )
```

strchr implementation on **device** space
Find the first matching index of a string

Parameters

<i>p</i>	- string to check
<i>c</i>	- character to match
<i>s_len</i>	- maximum string length

Returns

pointer to the match

7.7 Markov::API::CUDA::Random Namespace Reference

Namespace for [Random](#) engines operable under **device** space.

Classes

- class [Marsaglia](#)

*Extension of [Markov::Random::Marsaglia](#) which is capable o working on **device** space.*

Functions

- `__device__ unsigned long` [devrandom](#) (unsigned long &x, unsigned long &y, unsigned long &z)
*[Marsaglia Random](#) Generation function operable in **device** space.*

7.7.1 Detailed Description

Namespace for [Random](#) engines operable under **device** space.

7.7.2 Function Documentation

7.7.2.1 devrandom()

```
__device__ unsigned long Markov::API::CUDA::Random::devrandom (
    unsigned long & x,
    unsigned long & y,
    unsigned long & z )
```

[Marsaglia Random](#) Generation function operable in **device** space.

Parameters

<i>x</i>	marsaglia internal x. Not constant, (ref)
<i>y</i>	marsaglia internal y. Not constant, (ref)
<i>z</i>	marsaglia internal z. Not constant, (ref)

Returns

returns `z`

Definition at line 43 of file [cudarandom.h](#).

```

00043
00044         unsigned long t;
00045         x ^= x << 16;
00046         x ^= x >> 5;
00047         x ^= x << 1;
00048
00049         t = x;
00050         x = y;
00051         y = z;
00052         z = t ^ x ^ y;
00053
00054         return z;
00055     }

```

7.8 Markov::GUI Namespace Reference

namespace for MarkovPasswords [API GUI](#) wrapper

Classes

- class [about](#)
QT Class for about page.
- class [CLI](#)
QT CLI Class.
- class [MarkovPasswordsGUI](#)
Reporting UI.
- class [menu](#)
QT Menu class.
- class [Train](#)
QT Training page class.

7.8.1 Detailed Description

namespace for MarkovPasswords [API GUI](#) wrapper

7.9 Markov::Markopy Namespace Reference

Functions

- [BOOST_PYTHON_MODULE](#) (markopy)

7.9.1 Function Documentation

7.9.1.1 BOOST_PYTHON_MODULE()

Markov::Markopy::BOOST_PYTHON_MODULE (
markopy)

Definition at line 12 of file [markopy.cpp](#).

```

00013     {
00014         bool (Markov::API::MarkovPasswords::*Import)(const char*) = &Markov::Model<char>::Import;
00015         bool (Markov::API::MarkovPasswords::*Export)(const char*) = &Markov::Model<char>::Export;
00016         class_<Markov::API::MarkovPasswords>("MarkovPasswords", init<>())
00017             .def(init<>())
00018             .def("Train", &Markov::API::MarkovPasswords::Train)
00019             .def("Generate", &Markov::API::MarkovPasswords::Generate)
00020             .def("Import", Import, "Import a model file.")
00021             .def("Export", Export, "Export a model to file.")

```


```

00022     ;
00023
00024     class_<Markov::API::ModelMatrix>("ModelMatrix", init<>())
00025
00026         .def(init<>())
00027         .def("Train", &Markov::API::ModelMatrix::Train)
00028         .def("Import", &Markov::API::ModelMatrix::Import, "Import a model file.")
00029         .def("Export", Export, "Export a model to file.")
00030         .def("ConstructMatrix", &Markov::API::ModelMatrix::ConstructMatrix)
00031         .def("DumpJSON", &Markov::API::ModelMatrix::DumpJSON)
00032         .def("FastRandomWalk", &Markov::API::ModelMatrix::FastRandomWalk)
00033     ;
00034 };

```

References [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), [Markov::Model< NodeStorageType>::Import\(\)](#), [Markov::API::ModelMatrix::FastRandomWalk\(\)](#), [Markov::API::MarkovPasswords::Generate\(\)](#), [Markov::API::ModelMatrix::Import\(\)](#), [Markov::Model< NodeStorageType>::Import\(\)](#), [Markov::API::MarkovPasswords::Train\(\)](#), and [Markov::API::ModelMatrix::Train\(\)](#).

Here is the call graph for this function:



7.10 Markov::Random Namespace Reference

Objects related to RNG.

Classes

- class [DefaultRandomEngine](#)
Implementation using [Random.h](#) default random engine.
- class [Marsaglia](#)
Implementation of [Marsaglia Random Engine](#).
- class [Mersenne](#)
Implementation of [Mersenne Twister Engine](#).
- class [RandomEngine](#)
An abstract class for [Random Engine](#).

7.10.1 Detailed Description

Objects related to RNG.

7.11 model_2gram Namespace Reference

Variables

- [alphabet](#) = string.printable
password alphabet

- `f = open('../models/2gram.mdl', 'wb')`
output file handle

7.11.1 Detailed Description

python script for generating a 2gram model

7.11.2 Variable Documentation

7.11.2.1 alphabet

`model_2gram.alphabet = string.printable`
password alphabet
Definition at line 10 of file [model_2gram.py](#).

7.11.2.2 f

`model_2gram.f = open('../models/2gram.mdl', 'wb')`
output file handle
Definition at line 16 of file [model_2gram.py](#).

7.12 random Namespace Reference

7.12.1 Detailed Description

-model

python script for generating a 2gram model

7.13 random-model Namespace Reference

Variables

- `alphabet = string.printable`
password alphabet
- `f = open('../models/random.mdl', 'wb')`
output file handle

7.13.1 Variable Documentation

7.13.1.1 alphabet

`random-model.alphabet = string.printable`
password alphabet
Definition at line 10 of file [random-model.py](#).

7.13.1.2 f

```
random-model.f = open('../models/random.mdl', "wb")
```

output file handle

Definition at line 16 of file [random-model.py](#).

7.14 Testing Namespace Reference

Namespace for Microsoft Native Unit [Testing](#) Classes.

Namespaces

- [MarkovModel](#)
Testing namespace for MarkovModel.
- [MarkovPasswords](#)
Testing namespace for MarkovPasswords.
- [MVP](#)
Testing Namespace for Minimal Viable Product.

7.14.1 Detailed Description

Namespace for Microsoft Native Unit [Testing](#) Classes.

7.15 Testing::MarkovModel Namespace Reference

[Testing](#) namespace for [MarkovModel](#).

Functions

- [TEST_CLASS](#) (Edge)
Test class for rest of Edge cases.
- [TEST_CLASS](#) (Node)
Test class for rest of Node cases.
- [TEST_CLASS](#) (Model)
Test class for rest of model cases.

7.15.1 Detailed Description

[Testing](#) namespace for [MarkovModel](#).

7.15.2 Function Documentation

7.15.2.1 TEST_CLASS() [1/3]

```
Testing::MarkovModel::TEST_CLASS (
    Edge )
```

Test class for rest of Edge cases.

send exception on integer underflow

test integer overflows

Definition at line 494 of file [UnitTests.cpp](#).

```
00495     {
00496     public:
00499         TEST_METHOD(except_integer_underflow) {
00500             auto _underflow_adjust = [] {
00501                 Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
```


```

00502         Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00503         Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
RightNode);
00504         e->AdjustEdge(15);
00505         e->AdjustEdge(-30);
00506         delete LeftNode;
00507         delete RightNode;
00508         delete e;
00509     };
00510     Assert::ExpectException<std::underflow_error>(_underflow_adjust);
00511 }
00512
00515 TEST_METHOD(except_integer_overflow) {
00516     auto _overflow_adjust = [] {
00517         Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00518         Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00519         Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
RightNode);
00520         e->AdjustEdge(~0ull);
00521         e->AdjustEdge(1);
00522         delete LeftNode;
00523         delete RightNode;
00524         delete e;
00525     };
00526     Assert::ExpectException<std::underflow_error>(_overflow_adjust);
00527 }
00528 };

```

References [TEST_CLASS\(\)](#).

Here is the call graph for this function:



7.15.2.2 TEST_CLASS() [2/3]

Testing::MarkovModel::TEST_CLASS (Model)

Test class for rest of model cases.

Definition at line 592 of file [UnitTests.cpp](#).

```

00593 {
00594     public:
00595         TEST_METHOD(functional_random_walk) {
00596             unsigned char* res2 = new unsigned char[12 + 5];
00597             Markov::Random::Marsaglia MarsagliaRandomEngine;
00598             Markov::Model<unsigned char> m;
00599             Markov::Node<unsigned char>* starter = m.StarterNode();
00600             Markov::Node<unsigned char>* a = new Markov::Node<unsigned char>('a');
00601             Markov::Node<unsigned char>* b = new Markov::Node<unsigned char>('b');
00602             Markov::Node<unsigned char>* c = new Markov::Node<unsigned char>('c');
00603             Markov::Node<unsigned char>* end = new Markov::Node<unsigned char>(0xff);
00604             starter->Link(a)->AdjustEdge(1);
00605             a->Link(b)->AdjustEdge(1);
00606             b->Link(c)->AdjustEdge(1);
00607             c->Link(end)->AdjustEdge(1);
00608
00609             char* res = (char*)m.RandomWalk(&MarsagliaRandomEngine,1,12,res2);
00610             Assert::IsFalse(strcmp(res, "abc"));
00611         }
00612         TEST_METHOD(functional_random_walk_without_any) {
00613             Markov::Model<unsigned char> m;
00614             Markov::Node<unsigned char>* starter = m.StarterNode();
00615             Markov::Node<unsigned char>* a = new Markov::Node<unsigned char>('a');
00616             Markov::Node<unsigned char>* b = new Markov::Node<unsigned char>('b');
00617             Markov::Node<unsigned char>* c = new Markov::Node<unsigned char>('c');
00618             Markov::Node<unsigned char>* end = new Markov::Node<unsigned char>(0xff);
00619             Markov::Edge<unsigned char>* res = NULL;

```

```


00620         starter->Link(a)->AdjustEdge(1);
00621         a->Link(b)->AdjustEdge(1);
00622         b->Link(c)->AdjustEdge(1);
00623         c->Link(end)->AdjustEdge(1);
00624
00625         res = starter->FindEdge('D');
00626         Assert::IsNull(res);
00627     }
00628 };
00629

```

References [TEST_CLASS\(\)](#).

Referenced by [TEST_CLASS\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



7.15.2.3 TEST_CLASS() [3/3]

```

Testing::MarkovModel::TEST_CLASS (
    Node )

```

Test class for rest of Node cases.

test RandomNext with 64 bit high values

test RandomNext with 64 bit high values

randomNext when no edges are present

Definition at line 532 of file [UnitTests.cpp](#).

```

00533     {
00534     public:
00535
00536     TEST_METHOD(rand_next_u64) {
00537         Markov::Random::Marsaglia MarsagliaRandomEngine;
00538         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00539         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00540         Markov::Edge<unsigned char>* e = src->Link(target1);
00541         e->AdjustEdge((unsigned long)(lull << 63));
00542         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00543         Assert::IsTrue(res == target1);
00544         delete src;
00545         delete target1;
00546         delete e;
00547     }
00548 }
00549
00550
00551

```


```

00554     TEST_METHOD(rand_next_u64_max) {
00555         Markov::Random::Marsaglia MarsagliaRandomEngine;
00556         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00557         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00558         Markov::Edge<unsigned char>* e = src->Link(target1);
00559         e->AdjustEdge((0xffffffff));
00560         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00561         Assert::IsTrue(res == target1);
00562         delete src;
00563         delete target1;
00564         delete e;
00565     }
00566 }
00567
00570     TEST_METHOD(uninitialized_rand_next) {
00571
00572         auto _invalid_next = [] {
00573             Markov::Random::Marsaglia MarsagliaRandomEngine;
00574             Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00575             Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00576             Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(src, target1);
00577             Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00578
00579             delete src;
00580             delete target1;
00581             delete e;
00582         };
00583
00584         Assert::ExpectException<std::logic_error>(_invalid_next);
00585     }
00586
00587 };
00588

```

References [TEST_CLASS\(\)](#).

Here is the call graph for this function:



7.16 Testing::MarkovPasswords Namespace Reference

[Testing](#) namespace for [MarkovPasswords](#).

7.16.1 Detailed Description

[Testing](#) namespace for [MarkovPasswords](#).

7.17 Testing::MVP Namespace Reference

[Testing](#) Namespace for Minimal Viable Product.

Namespaces

- [MarkovModel](#)
Testing Namespace for MVP MarkovModel.
- [MarkovPasswords](#)
Testing namespace for MVP MarkovPasswords.

7.17.1 Detailed Description

[Testing](#) Namespace for Minimal Viable Product.

7.18 Testing::MVP::MarkovModel Namespace Reference

[Testing](#) Namespace for [MVP MarkovModel](#).

Functions

- [TEST_CLASS](#) (Edge)
Test class for minimal viable Edge.
- [TEST_CLASS](#) (Node)
Test class for minimal viable Node.
- [TEST_CLASS](#) (Model)
Test class for minimal viable Model.

7.18.1 Detailed Description

[Testing](#) Namespace for [MVP MarkovModel](#).

7.18.2 Function Documentation

7.18.2.1 TEST_CLASS() [1/3]

Testing::MVP::MarkovModel::TEST_CLASS (
Edge)

Test class for minimal viable Edge.

test default constructor

test linked constructor with two nodes

test AdjustEdge function

test TraverseNode returning RightNode

test LeftNode/RightNode setter

test negative adjustments

Definition at line 21 of file [UnitTests.cpp](#).

```

00022     {
00023     public:
00024
00027         TEST_METHOD(default_constructor) {
00028             Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>;
00029             Assert::IsNull(e->LeftNode());
00030             Assert::IsNull(e->RightNode());
00031             delete e;
00032         }
00033
00036         TEST_METHOD(linked_constructor) {
00037             Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00038             Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00039             Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
RightNode);
00040             Assert::IsTrue(LeftNode == e->LeftNode());
00041             Assert::IsTrue(RightNode == e->RightNode());
00042             delete LeftNode;
00043             delete RightNode;
00044             delete e;
00045         }
00046
00049         TEST_METHOD(AdjustEdge) {
00050             Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00051             Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00052             Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
RightNode);
00053             e->AdjustEdge(15);
00054             Assert::AreEqual(15ull, e->EdgeWeight());
00055             e->AdjustEdge(15);

```


```

00056             Assert::AreEqual(30ull, e->EdgeWeight());
00057             delete LeftNode;
00058             delete RightNode;
00059             delete e;
00060         }
00061
00062     TEST_METHOD(TraverseNode) {
00063         Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00064         Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00065         Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00066             RightNode);
00067
00068         Assert::IsTrue(RightNode == e->TraverseNode());
00069         delete LeftNode;
00070         delete RightNode;
00071         delete e;
00072     }
00073
00074     TEST_METHOD(set_left_and_right) {
00075         Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00076         Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00077         Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(LeftNode,
00078             RightNode);
00079
00080         Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>;
00081         e2->SetLeftEdge(LeftNode);
00082         e2->SetRightEdge(RightNode);
00083
00084         Assert::IsTrue(e1->LeftNode() == e2->LeftNode());
00085         Assert::IsTrue(e1->RightNode() == e2->RightNode());
00086         delete LeftNode;
00087         delete RightNode;
00088         delete e1;
00089         delete e2;
00090     }
00091
00092     TEST_METHOD(negative_adjust) {
00093         Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00094         Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00095         Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00096             RightNode);
00097
00098         e->AdjustEdge(15);
00099         Assert::AreEqual(15ull, e->EdgeWeight());
00100         e->AdjustEdge(-15);
00101         Assert::AreEqual(0ull, e->EdgeWeight());
00102         delete LeftNode;
00103         delete RightNode;
00104         delete e;
00105     }
00106 };
00107

```

References [TEST_CLASS\(\)](#).

Here is the call graph for this function:



7.18.2.2 TEST_CLASS() [2/3]

```

Testing::MVP::MarkovModel::TEST_CLASS (
    Model )

```

Test class for minimal viable Model.

test model constructor for starter node

test import

test export

test random walk

Definition at line 347 of file [UnitTests.cpp](#).

```

00348 {

```

```


00349         public:
00352             TEST_METHOD(model_constructor) {
00353                 Markov::Model<unsigned char> m;
00354                 Assert::AreEqual((unsigned char)'0', m.StarterNode()->NodeValue());
00355             }
00356
00359             TEST_METHOD(import_filename) {
00360                 Markov::Model<unsigned char> m;
00361                 Assert::IsTrue(m.Import("../MarkovPasswords/Models/2gram.mdl"));
00362             }
00363
00366             TEST_METHOD(export_filename) {
00367                 Markov::Model<unsigned char> m;
00368                 Assert::IsTrue(m.Export("../MarkovPasswords/Models/testcase.mdl"));
00369             }
00370
00373             TEST_METHOD(random_walk) {
00374                 unsigned char* res = new unsigned char[12 + 5];
00375                 Markov::Random::Marsaglia MarsagliaRandomEngine;
00376                 Markov::Model<unsigned char> m;
00377                 Assert::IsTrue(m.Import("../Models/finished2.mdl"));
00378                 Assert::IsNotNull(m.RandomWalk(&MarsagliaRandomEngine, 1, 12, res));
00379             }
00380     };

```

References [TEST_CLASS\(\)](#).

Referenced by [TEST_CLASS\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



7.18.2.3 TEST_CLASS() [3/3]

```

Testing::MVP::MarkovModel::TEST_CLASS (
    Node )

```

Test class for minimal viable Node.

test default constructor

test custom constructor with unsigned char

test link function

test link function

test RandomNext with low values

test RandomNext with 32 bit high values

random next on a node with no follow-ups

Definition at line 111 of file UnitTests.cpp.

Markopy Documentation


```

00203         e1->AdjustEdge(1);
00204         e2->AdjustEdge((unsigned long)(1ull << 31));
00205         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00206         Assert::IsNull(res);
00207         Assert::IsTrue(res == target2);
00208         delete src;
00209         delete target1;
00210         delete e1;
00211         delete e2;
00212     }
00213
00216     TEST_METHOD(rand_next_choice_2) {
00217         Markov::Random::Marsaglia MarsagliaRandomEngine;
00218         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00219         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00220         Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00221         Markov::Edge<unsigned char>* e1 = src->Link(target1);
00222         Markov::Edge<unsigned char>* e2 = src->Link(target2);
00223         e2->AdjustEdge(1);
00224         e1->AdjustEdge((unsigned long)(1ull << 31));
00225         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00226         Assert::IsNull(res);
00227         Assert::IsTrue(res == target1);
00228         delete src;
00229         delete target1;
00230         delete e1;
00231         delete e2;
00232     }
00233
00234
00237     TEST_METHOD(update_edges_count) {
00238
00239         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00240         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00241         Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00242         Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00243         Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target2);
00244         e1->AdjustEdge(25);
00245         src->UpdateEdges(e1);
00246         e2->AdjustEdge(30);
00247         src->UpdateEdges(e2);
00248
00249         Assert::AreEqual((size_t)2, src->Edges()->size());
00250
00251         delete src;
00252         delete target1;
00253         delete e1;
00254         delete e2;
00255     }
00256
00257
00260     TEST_METHOD(update_edges_total) {
00261
00262         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00263         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00264         Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00265         Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target1);
00266         e1->AdjustEdge(25);
00267         src->UpdateEdges(e1);
00268         e2->AdjustEdge(30);
00269         src->UpdateEdges(e2);
00270
00271         //Assert::AreEqual(55ull, src->TotalEdgeWeights());
00272
00273         delete src;
00274         delete target1;
00275         delete e1;
00276         delete e2;
00277     }
00278
00279
00282     TEST_METHOD(find_vertice) {
00283
00284         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00285         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00286         Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00287         Markov::Edge<unsigned char>* res = NULL;
00288         src->Link(target1);
00289         src->Link(target2);
00290
00291
00292         res = src->FindEdge('b');
00293         Assert::IsNull(res);
00294         Assert::AreEqual((unsigned char)'b', res->TraverseNode()->NodeValue());
00295         res = src->FindEdge('c');
00296         Assert::IsNull(res);
00297         Assert::AreEqual((unsigned char)'c', res->TraverseNode()->NodeValue());

```


```

00298
00299         delete src;
00300         delete target1;
00301         delete target2;
00302
00303     }
00304
00305
00306
00309     TEST_METHOD(find_vertice_without_any) {
00310
00311         auto _invalid_next = [] {
00312             Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00313             Markov::Edge<unsigned char>* res = NULL;
00314
00315             res = src->FindEdge('b');
00316             Assert::IsNull(res);
00317
00318             delete src;
00319         };
00320
00321         //Assert::ExpectException<std::logic_error>(_invalid_next);
00322     }
00323
00326     TEST_METHOD(find_vertice_nonexistent) {
00327
00328         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00329         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00330         Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00331         Markov::Edge<unsigned char>* res = NULL;
00332         src->Link(target1);
00333         src->Link(target2);
00334
00335         res = src->FindEdge('D');
00336         Assert::IsNull(res);
00337
00338         delete src;
00339         delete target1;
00340         delete target2;
00341
00342     }
00343 };

```

References [TEST_CLASS\(\)](#).

Here is the call graph for this function:



7.19 Testing::MVP::MarkovPasswords Namespace Reference

[Testing](#) namespace for [MVP MarkovPasswords](#).

Functions

- [TEST_CLASS](#) (ArgParser)
Test Class for Argparse class.

7.19.1 Detailed Description

[Testing](#) namespace for [MVP MarkovPasswords](#).

7.19.2 Function Documentation

7.19.2.1 TEST_CLASS()

Testing::MVP::MarkovPasswords::TEST_CLASS (
 ArgParser)

Test Class for Argparse class.

test basic generate

test basic generate reordered params

test basic generate param longnames

test basic generate

test basic train

test basic generate

Definition at line 389 of file [UnitTests.cpp](#).

```

00390     {
00391     public:
00394         TEST_METHOD(generate_basic) {
00395             int argc = 8;
00396             char *argv[] = {"markov.exe", "generate", "-if", "model.mdl", "-of",
"passwords.txt", "-n", "100"};
00397
00398             /*ProgramOptions *p = Argparse::parse(argc, argv);
00399             Assert::IsNotNull(p);
00400
00401             Assert::AreEqual(p->bImport, true);
00402             Assert::AreEqual(p->bExport, false);
00403             Assert::AreEqual(p->importname, "model.mdl");
00404             Assert::AreEqual(p->outputfilename, "passwords.txt");
00405             Assert::AreEqual(p->generateN, 100); */
00406
00407         }
00408
00411         TEST_METHOD(generate_basic_reorder) {
00412             int argc = 8;
00413             char *argv[] = { "markov.exe", "generate", "-n", "100", "-if", "model.mdl", "-of",
"passwords.txt" };
00414
00415             /*ProgramOptions* p = Argparse::parse(argc, argv);
00416             Assert::IsNotNull(p);
00417
00418             Assert::AreEqual(p->bImport, true);
00419             Assert::AreEqual(p->bExport, false);
00420             Assert::AreEqual(p->importname, "model.mdl");
00421             Assert::AreEqual(p->outputfilename, "passwords.txt");
00422             Assert::AreEqual(p->generateN, 100); */
00423
00424         }
00427         TEST_METHOD(generate_basic_longname) {
00428             int argc = 8;
00429             char *argv[] = { "markov.exe", "generate", "-n", "100", "--inputfilename",
"model.mdl", "--outputfilename", "passwords.txt" };
00430
00431             /*ProgramOptions* p = Argparse::parse(argc, argv);
00432             Assert::IsNotNull(p);
00433
00434             Assert::AreEqual(p->bImport, true);
00435             Assert::AreEqual(p->bExport, false);
00436             Assert::AreEqual(p->importname, "model.mdl");
00437             Assert::AreEqual(p->outputfilename, "passwords.txt");
00438             Assert::AreEqual(p->generateN, 100); */
00439
00440         }
00443         TEST_METHOD(generate_fail_badmethod) {
00444             int argc = 8;
00445             char *argv[] = { "markov.exe", "junk", "-n", "100", "--inputfilename",
"model.mdl", "--outputfilename", "passwords.txt" };
00446
00447             /*ProgramOptions* p = Argparse::parse(argc, argv);
00448             Assert::IsNull(p); */
00449
00450         }
00453         TEST_METHOD(train_basic) {
00454             int argc = 4;
00455             char *argv[] = { "markov.exe", "train", "-ef", "model.mdl" };
00456
00457             /*ProgramOptions* p = Argparse::parse(argc, argv);
00458             Assert::IsNotNull(p);
00459
00460             Assert::AreEqual(p->bImport, false);
00461             Assert::AreEqual(p->bExport, true);
00462             Assert::AreEqual(p->exportname, "model.mdl"); */
00463
00464         }
00465


```

```
00468         TEST_METHOD(train_basic_longname) {
00469             int argc = 4;
00470             char *argv[] = { "markov.exe", "train", "--exportfilename", "model.mdl" };
00471
00472             /*ProgramOptions* p = Argparse::parse(argc, argv);
00473             Assert::IsNotNull(p);
00474
00475             Assert::AreEqual(p->bImport, false);
00476             Assert::AreEqual(p->bExport, true);
00477             Assert::AreEqual(p->exportname, "model.mdl"); */
00478         }
00479
00480
00481
00482     };
```


References [TEST_CLASS\(\)](#).

Referenced by [TEST_CLASS\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:




Chapter 8

Class Documentation

8.1 Markov::API::CLI::_programOptions Struct Reference

Structure to hold parsed cli arguments.
`#include <argparse.h>`

Collaboration diagram for Markov::API::CLI::_programOptions:



Public Attributes

- bool [blmport](#)
Import flag to validate import
- bool [bExport](#)
Export flag to validate export
- bool [bFailure](#)
Failure flag to validate succesfull running
- char [seperator](#)

Seperator character to use with training data. (character between occurence and value)"

- std::string [importname](#)
Import name of our model.
- std::string [exportname](#)
Import name of our given wordlist
- std::string [wordlistname](#)
Import name of our given wordlist
- std::string [outputfilename](#)
Output name of our generated password list
- std::string [datasetname](#)
The name of the given dataset
- int [generateN](#)
Number of passwords to be generated

8.1.1 Detailed Description

Structure to hold parsed cli arguements.
Definition at line 18 of file [argparse.h](#).

8.1.2 Member Data Documentation

8.1.2.1 bExport

bool Markov::API::CLI::_programOptions::bExport
Export flag to validate export

Definition at line 27 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

8.1.2.2 bFailure

bool Markov::API::CLI::_programOptions::bFailure
Failure flag to validate succesfull running

Definition at line 32 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

8.1.2.3 bImport

bool Markov::API::CLI::_programOptions::bImport
Import flag to validate import

Definition at line 22 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

8.1.2.4 datasetname

`std::string Markov::API::CLI::_programOptions::datasetname`
The name of the given dataset

Definition at line 62 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

8.1.2.5 exportname

`std::string Markov::API::CLI::_programOptions::exportname`
Import name of our given wordlist

Definition at line 47 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

8.1.2.6 generateN

`int Markov::API::CLI::_programOptions::generateN`
Number of passwords to be generated

Definition at line 67 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

8.1.2.7 importname

`std::string Markov::API::CLI::_programOptions::importname`
Import name of our model.

Definition at line 42 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

8.1.2.8 outputfilename

`std::string Markov::API::CLI::_programOptions::outputfilename`
Output name of our generated password list

Definition at line 57 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

8.1.2.9 seperator

`char Markov::API::CLI::_programOptions::seperator`
Seperator character to use with training data. (character between occurence and value)"

Definition at line 37 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

8.1.2.10 wordlistname

`std::string Markov::API::CLI::_programOptions::wordlistname`
Import name of our given wordlist

Definition at line 52 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#).

The documentation for this struct was generated from the following file:

- [argparse.h](#)

8.2 Markov::GUI::about Class Reference

QT Class for about page.

```
#include <about.h>
```

Inheritance diagram for Markov::GUI::about:



Collaboration diagram for Markov::GUI::about:



Public Member Functions

- [about](#) (QWidget *parent=Q_NULLPTR)

Private Attributes

- [Ui::main ui](#)

8.2.1 Detailed Description

QT Class for about page.

Definition at line 12 of file [about.h](#).

8.2.2 Constructor & Destructor Documentation

8.2.2.1 `about()`

```
Markov::GUI::about::about (
    QWidget * parent = Q_NULLPTR )
```

8.2.3 Member Data Documentation

8.2.3.1 `ui`

```
Ui:: main Markov::GUI::about::ui [private]
```

Definition at line 18 of file [about.h](#).

The documentation for this class was generated from the following file:


- [about.h](#)

8.3 Markov::API::CLI::Argparse Class Reference

Parse command line arguments.

```
#include <argparse.h>
```

Collaboration diagram for Markov::API::CLI::Argparse:



Public Member Functions

- [Argparse](#) ()
- [Argparse](#) (int argc, char **argv)
Parse command line arguments.
- [Markov::API::CLI::ProgramOptions getProgramOptions](#) (void)
Getter for command line options.

- void [setProgramOptions](#) (bool i, bool e, bool bf, char s, std::string iName, std::string exName, std::string oName, std::string dName, int n)

Initialize program options structure.

Static Public Member Functions

- static [Markov::API::CLI::ProgramOptions * parse](#) (int argc, char **argv)

parse cli commands and return

- static void [help](#) ()

Print help string.

Private Attributes

- [Markov::API::CLI::ProgramOptions po](#)

ProgramOptions structure object.

8.3.1 Detailed Description

Parse command line arguments.

Definition at line 74 of file [argparse.h](#).

8.3.2 Constructor & Destructor Documentation

8.3.2.1 Argparse() [1/2]

```
Markov::API::CLI::Argparse::Argparse ( )
```

8.3.2.2 Argparse() [2/2]

```
Markov::API::CLI::Argparse::Argparse (
    int argc,
    char ** argv ) [inline]
```

Parse command line arguments.

Parses command line arguments to populate ProgramOptions structure.

Parameters

<i>argc</i>	Number of command line arguments
<i>argv</i>	Array of command line parameters

Definition at line 86 of file [argparse.h](#).

```
00086                                     {
00087
00088         /*bool bImp;
00089         bool bExp;
00090         bool bFail;
00091         char sptr;
00092         std::string imports;
00093         std::string exports;
00094         std::string outputs;
00095         std::string datasets;
00096         int generateN;
00097         */
00098         opt::options_description desc("Options");
00099
00100
00101         desc.add_options()
00102             ("generate", "Generate strings with given parameters")
00103             ("train", "Train model with given parameters")
```

```

00104         ("combine", "Combine")
00105         ("import", opt::value<std::string>(), "Import model file")
00106         ("output", opt::value<std::string>(), "Output model file. This model will be exported
when done. Will be ignored for generation mode")
00107         ("dataset", opt::value<std::string>(), "Dataset file to read input from training. Will
be ignored for generation mode")
00108         ("separator", opt::value<char>(), "Separator character to use with training data.
(character between occurrence and value)")
00109         ("wordlist", opt::value<std::string>(), "Wordlist file path to export generation
results to. Will be ignored for training mode")
00110         ("count", opt::value<int>(), "Number of lines to generate. Ignored in training mode")
00111         ("verbosity", "Output verbosity")
00112         ("help", "Option definitions");
00113
00114     opt::variables_map vm;
00115
00116     opt::store(opt::parse_command_line(argc, argv, desc), vm);
00117
00118     opt::notify(vm);
00119
00120     //std::cout << desc << std::endl;
00121     if (vm.count("help")) {
00122         std::cout << desc << std::endl;
00123     }
00124
00125     if (vm.count("output") == 0) this->po.outputfilename = "NULL";
00126     else if (vm.count("output") == 1) {
00127         this->po.outputfilename = vm["output"].as<std::string>();
00128         this->po.bExport = true;
00129     }
00130     else {
00131         this->po.bFailure = true;
00132         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00133         std::cout << desc << std::endl;
00134     }
00135
00136     if (vm.count("dataset") == 0) this->po.datasetname = "NULL";
00137     else if (vm.count("dataset") == 1) {
00138         this->po.datasetname = vm["dataset"].as<std::string>();
00139     }
00140     else {
00141         this->po.bFailure = true;
00142         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00143         std::cout << desc << std::endl;
00144     }
00145
00146     if (vm.count("wordlist") == 0) this->po.wordlistname = "NULL";
00147     else if (vm.count("wordlist") == 1) {
00148         this->po.wordlistname = vm["wordlist"].as<std::string>();
00149     }
00150     else {
00151         this->po.bFailure = true;
00152         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00153         std::cout << desc << std::endl;
00154     }
00155
00156     if (vm.count("import") == 0) this->po.importname = "NULL";
00157     else if (vm.count("import") == 1) {
00158         this->po.importname = vm["import"].as<std::string>();
00159         this->po.bImport = true;
00160     }
00161     else {
00162         this->po.bFailure = true;
00163         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00164         std::cout << desc << std::endl;
00165     }
00166
00167     if (vm.count("count") == 0) this->po.generateN = 0;
00168     else if (vm.count("count") == 1) {
00169         this->po.generateN = vm["count"].as<int>();
00170     }
00171     else {
00172         this->po.bFailure = true;
00173         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00174         std::cout << desc << std::endl;
00175     }
00176
00177     /*std::cout << vm["output"].as<std::string>() << std::endl;
std::cout << vm["dataset"].as<std::string>() << std::endl;
std::cout << vm["wordlist"].as<std::string>() << std::endl;
std::cout << vm["output"].as<std::string>() << std::endl;
std::cout << vm["count"].as<int>() << std::endl;*/
00180
00181
00182
00183
00184
00185
00186


```

```
00187         //else if (vm.count("train")) std::cout << "train oldu" << std::endl;
00188     }
```

References [Markov::API::CLI::_programOptions::bExport](#), [Markov::API::CLI::_programOptions::bFailure](#), [Markov::API::CLI::_programOptions::datasetname](#), [Markov::API::CLI::_programOptions::generateN](#), [Markov::API::CLI::_programOptions::outputfilename](#), [po](#), and [Markov::API::CLI::_programOptions::wordlistname](#).

Referenced by [main\(\)](#).

Here is the caller graph for this function:



8.3.3 Member Function Documentation

8.3.3.1 getProgramOptions()

```
Markov::API::CLI::ProgramOptions Markov::API::CLI::Argparse::getProgramOptions (
    void ) [inline]
```

Getter for command line options.

Getter for ProgramOptions populated by the argument parser

Returns

ProgramOptions structure.

Definition at line 195 of file [argparse.h](#).

```
00195     {
00196         return this->po;
00197     }
```

References [po](#).

8.3.3.2 help()

```
void Markov::API::CLI::Argparse::help ( ) [static]
```

Print help string.

Definition at line 8 of file [argparse.cpp](#).

```
00008     {
00009         std::cout <<
00010         "Markov Passwords - Help\n"
00011         "Options:\n"
00012         "  \n"
00013         "  -of --outputfilename\n"
00014         "      Filename to output the generation results\n"
00015         "  -ef --exportfilename\n"
00016         "      filename to export built model to\n"
00017         "  -if --importfilename\n"
00018         "      filename to import model from\n"
00019         "  -n (generate count)\n"
00020         "      Number of lines to generate\n"
00021         "  \n"
00022         "Usage: \n"
00023         "  markov.exe -if empty_model.mdl -ef model.mdl\n"
00024         "      import empty_model.mdl and train it with data from stdin. When done, output the model to
00025         model.mdl\n"
00026         "  \n"
00027         "  markov.exe -if empty_model.mdl -n 15000 -of wordlist.txt\n"
00028         "      import empty_model.mdl and generate 15000 words to wordlist.txt\n"
```

```
00029         « std::endl;
00030 }
```

8.3.3.3 parse()

```
Markov::API::CLI::ProgramOptions * Markov::API::CLI::Argparse::parse (
    int argc,
    char ** argv ) [static]
parse cli commands and return
```

Parameters

<i>argc</i>	- Program argument count
<i>argv</i>	- Program argument values array

Returns

ProgramOptions structure.

Definition at line 4 of file [argparse.cpp](#).

```
00004 { return 0; }
```

8.3.3.4 setProgramOptions()

```
void Markov::API::CLI::Argparse::setProgramOptions (
    bool i,
    bool e,
    bool bf,
    char s,
    std::string iName,
    std::string exName,
    std::string oName,
    std::string dName,
    int n ) [inline]
Initialize program options structure.
```

Parameters

<i>i</i>	boolean, true if import operation is flagged
<i>e</i>	boolean, true if export operation is flagged
<i>bf</i>	boolean, true if there is something wrong with the command line parameters
<i>s</i>	separator character for the import function
<i>iName</i>	import filename
<i>exName</i>	export filename
<i>oName</i>	output filename
<i>dName</i>	corpus filename
<i>n</i>	number of passwords to be generated

Definition at line 212 of file [argparse.h](#).

```
00212
00213         this->po.bImport = i;
00214         this->po.bExport = e;
00215         this->po.seperator = s;
00216         this->po.bFailure = bf;
00217         this->po.generateN = n;
00218         this->po.importname = iName;
```



```

00219         this->po.exportname = exName;
00220         this->po.outputfilename = oName;
00221         this->po.datasetname = dName;
00222
00223         /*strcpy_s(this->po.importname,256,iName);
00224         strcpy_s(this->po.exportname,256,exName);
00225         strcpy_s(this->po.outputfilename,256,oName);
00226         strcpy_s(this->po.datasetname,256,dName);*/
00227
00228     }

```

References [Markov::API::CLI::_programOptions::bExport](#), [Markov::API::CLI::_programOptions::bFailure](#), [Markov::API::CLI::_programOptions::datasetname](#), [Markov::API::CLI::_programOptions::exportname](#), [Markov::API::CLI::_programOptions::importname](#), [Markov::API::CLI::_programOptions::outputfilename](#), [po](#), and [Markov::API::CLI::_programOptions::seperator](#).

8.3.4 Member Data Documentation

8.3.4.1 po

[Markov::API::CLI::ProgramOptions](#) [Markov::API::CLI::Argparse::po](#) [private]

ProgramOptions structure object.

Definition at line 247 of file [argparse.h](#).

Referenced by [Argparse\(\)](#), [getProgramOptions\(\)](#), and [setProgramOptions\(\)](#).

The documentation for this class was generated from the following files:


- [argparse.h](#)
- [argparse.cpp](#)

8.4 Markov::GUI::CLI Class Reference


QT [CLI](#) Class.

```
#include <CLI.h>
```

Inheritance diagram for [Markov::GUI::CLI](#):



Collaboration diagram for Markov::GUI::CLI:



Public Slots

- void [start](#) ()
- void [statistics](#) ()
- void [about](#) ()

Public Member Functions

- [CLI](#) (QWidget *parent=Q_NULLPTR)

Private Attributes

- Ui::CLI [ui](#)

8.4.1 Detailed Description

QT [CLI](#) Class.

Definition at line 8 of file [CLI.h](#).

8.4.2 Constructor & Destructor Documentation

8.4.2.1 CLI()

```

Markov::GUI::CLI::CLI (
    QWidget * parent = Q_NULLPTR )
  
```

8.4.3 Member Function Documentation

8.4.3.1 about


```
void Markov::GUI::CLI::about ( ) [slot]
```

8.4.3.2 start

```
void Markov::GUI::CLI::start ( ) [slot]
```

Referenced by [main\(\)](#).

Here is the caller graph for this function:



8.4.3.3 statistics

```
void Markov::GUI::CLI::statistics ( ) [slot]
```

8.4.4 Member Data Documentation

8.4.4.1 ui

```
Ui::CLI Markov::GUI::CLI::ui [private]
```

Definition at line 14 of file [CLI.h](#).

The documentation for this class was generated from the following file:


- [CLI.h](#)

8.5 Markov::API::CUDA::CUDADeviceController Class Reference


Controller class for [CUDA](#) device.

```
#include <cudaDeviceController.h>
```

Inheritance diagram for Markov::API::CUDA::CUDADeviceController:



Collaboration diagram for Markov::API::CUDA::CUDADeviceController:



Static Public Member Functions

- static `__host__ void ListCudaDevices ()`
List [CUDA](#) devices in the system.

Static Protected Member Functions

- static `__host__ int CudaCheckNotifyErr (cudaError_t _status, const char *msg, bool bExit=true)`
Check results of the last operation on GPU.
- template<typename T >
static `__host__ cudaError_t CudaMalloc2DToFlat (T **dst, int row, int col)`
Malloc a 2D array in device space.
- template<typename T >
static `__host__ cudaError_t CudaMemcpy2DToFlat (T *dst, T **src, int row, int col)`
Mempcy a 2D array in device space after flattening.
- template<typename T >
static `__host__ cudaError_t CudaMigrate2DFlat (T **dst, T **src, int row, int col)`
Both malloc and memcpy a 2D array into device VRAM.

8.5.1 Detailed Description

Controller class for [CUDA](#) device.

This implementation only supports Nvidia devices.

Definition at line 16 of file [cudaDeviceController.h](#).

8.5.2 Member Function Documentation

8.5.2.1 CudaCheckNotifyErr()

```
static __host__ int Markov::API::CUDA::CUDADeviceController::CudaCheckNotifyErr (
    cudaError_t _status,
    const char * msg,
    bool bExit = true ) [static], [protected]
```

Check results of the last operation on GPU.

Check the status returned from `cudaMalloc/cudaMemcpy` to find failures.

If a failure occurs, its assumed beyond redemption, and exited.

Parameters

<code>_status</code>	Cuda error status to check
<code>msg</code>	Message to print in case of a failure

Returns

0 if successful, 1 if failure. **Example output:**

```
char *da, a = "test";
cudaStatus = cudaMalloc((char **)&da, 5*sizeof(char*));
CudaCheckNotifyErr(cudaStatus, "Failed to allocate VRAM for *da.\n");
```

8.5.2.2 CudaMalloc2DToFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat (
    T ** dst,
```

```
int row,
int col ) [inline], [static], [protected]
```

Malloc a 2D array in device space.

This function will allocate enough space on VRAM for flattened 2D array.

Parameters

<i>dst</i>	destination pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:


```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
if(cudastatus!=cudaSuccess){
    CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
}
```

Definition at line 73 of file [cudaDeviceController.h](#).

```
00073
00074         cudaError_t cudastatus = cudaMalloc((T **)dst, row*col*sizeof(T));
00075         CudaCheckNotifyErr(cudastatus, "cudaMalloc Failed.", false);
00076         return cudastatus;
00077     }
```

References [CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



8.5.2.3 CudaMemcpy2DToFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat (
    T * dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected]
```

Memcpy a 2D array in device space after flattening.

Resulting buffer will not be true 2D array.

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:


```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
cudastatus = CudaMemcpy2DToFlat<char>(*dst,src,15,15);
CudaCheckNotifyErr(cudastatus, " CudaMemcpy2DToFlat Failed.", false);
```

Definition at line 101 of file [cudaDeviceController.h](#).

```
00101
00102         T* tempbuf = new T[row*col];
00103         for(int i=0;i<row;i++){
00104             memcpy(&(tempbuf[row*i]), src[i], col);
00105         }
00106         return cudaMemcpy(dst, tempbuf, row*col*sizeof(T), cudaMemcpyHostToDevice);
00107     }
00108 }
```

References [CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:

**8.5.2.4 CudaMigrate2DFlat()**

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat (
    T ** dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected]
```

Both malloc and memcpy a 2D array into device VRAM.

Resulting buffer will not be true 2D array.

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:

```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMigrate2DFlat<long int>(
    &dst, this->valueMatrix, this->matrixSize, this->matrixSize);
CudaCheckNotifyErr(cudastatus, " Cuda failed to initialize value matrix row.");
```

Definition at line 130 of file [cudaDeviceController.h](#).

```


00130                                     {
00131         cudaError_t cudastatus;
00132         cudastatus = CudaMalloc2DToFlat<T>(dst, row, col);
00133         if(cudastatus!=cudaSuccess){
00134             CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
00135             return cudastatus;
00136         }
00137         cudastatus = CudaMemcpy2DToFlat<T>(*dst,src,row,col);
00138         CudaCheckNotifyErr(cudastatus, " CudaMemcpy2DToFlat Failed.", false);
00139         return cudastatus;
00140     }

```


References [CudaMigrate2DFlat\(\)](#).

Referenced by [CudaMalloc2DToFlat\(\)](#), [CudaMemcpy2DToFlat\(\)](#), and [CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.5.2.5 ListCudaDevices()

```
static __host__ void Markov::API::CUDA::CUDADeviceController::ListCudaDevices ( ) [static]
```

List [CUDA](#) devices in the system.

This function will print details of every [CUDA](#) capable device in the system.

Example output:

```

Device Number: 0
Device name: GeForce RTX 2070
Memory Clock Rate (KHz): 7001000
Memory Bus Width (bits): 256
Peak Memory Bandwidth (GB/s): 448.064
Max Linear Threads: 1024

```

The documentation for this class was generated from the following file:


- [cudaDeviceController.h](#)

8.6 Markov::API::CUDA::CUDAModelMatrix Class Reference


Extension of [Markov::API::ModelMatrix](#) which is modified to run on GPU devices.

```
#include <cudaModelMatrix.h>
```

Inheritance diagram for Markov::API::CUDA::CUDAModelMatrix:



Collaboration diagram for Markov::API::CUDA::CUDAModelMatrix:



Public Member Functions

- __host__ void MigrateMatrix ()**
Migrate the class members to the VRAM.
- __host__ void FlattenMatrix ()**
Flatten migrated matrix from 2d to 1d.
- __host__ void FastRandomWalk** (unsigned long int n, const char *wordlistFileName, int minLen, int maxLen, bool bFileIO)

- *Random walk on the Matrix-reduced [Markov::Model](#).*
- bool [ConstructMatrix](#) ()
Construct the related Matrix data for the model.
- void [DumpJSON](#) ()
Debug function to dump the model to a JSON file.
- void [FastRandomWalk](#) (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20, bool bFileIO=true)
Random walk on the Matrix-reduced [Markov::Model](#).
- void [Import](#) (const char *filename)
Open a file to import with filename, and call bool [Model::Import](#) with std::ifstream.
- bool [Import](#) (std::ifstream *)
Import a file to construct the model.
- void [Train](#) (const char *datasetFileName, char delimiter, int threads)
Train the model with the dataset file.
- std::ifstream * [OpenDatasetFile](#) (const char *filename)
Open dataset file and return the ifstream pointer.
- std::ofstream * [Save](#) (const char *filename)
Export model to file.
- void [Generate](#) (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20)
Call [Markov::Model::RandomWalk](#) n times, and collect output.
- char * [RandomWalk](#) ([Markov::Random::RandomEngine](#) *randomEngine, int minSetting, int maxSetting, char *buffer)
Do a random walk on this model.
- void [AdjustEdge](#) (const char *payload, long int occurrence)
Adjust the model with a single string.
- bool [Export](#) (std::ofstream *)
Export a file of the model.
- bool [Export](#) (const char *filename)
Open a file to export with filename, and call bool [Model::Export](#) with std::ofstream.
- [Node](#)< char > * [StarterNode](#) ()
Return starter Node.
- std::vector< [Edge](#)< char > * > * [Edges](#) ()
Return a vector of all the edges in the model.
- std::map< char, [Node](#)< char > * > * [Nodes](#) ()
Return starter Node.

Static Public Member Functions

- static __host__ void [ListCudaDevices](#) ()
List [CUDA](#) devices in the system.

Protected Member Functions

- __host__ char * [AllocVRAMOutputBuffer](#) (long int n, long int singleGenMaxLen, long int CUDAKernelGridSize, long int sizePerGrid)
Allocate the output buffer for kernel operation.
- void [FastRandomWalkPartition](#) (std::mutex *mlock, std::ofstream *wordlist, unsigned long int n, int minLen, int maxLen, bool bFileIO, int threads)
A single partition of [FastRandomWalk](#) event.
- void [FastRandomWalkThread](#) (std::mutex *mlock, std::ofstream *wordlist, unsigned long int n, int minLen, int maxLen, int id, bool bFileIO)
A single thread of a single partition of [FastRandomWalk](#).
- bool [DeallocateMatrix](#) ()
Deallocate matrix and make it ready for re-construction.

Static Protected Member Functions

- static `__host__ int` [CudaCheckNotifyErr](#) (`cudaError_t _status`, `const char *msg`, `bool bExit=true`)
Check results of the last operation on GPU.
- `template<typename T >`
static `__host__ cudaError_t` [CudaMalloc2DToFlat](#) (`T **dst`, `int row`, `int col`)
Malloc a 2D array in device space.
- `template<typename T >`
static `__host__ cudaError_t` [CudaMemcpy2DToFlat](#) (`T *dst`, `T **src`, `int row`, `int col`)
Mempcy a 2D array in device space after flattening.
- `template<typename T >`
static `__host__ cudaError_t` [CudaMigrate2DFlat](#) (`T **dst`, `T **src`, `int row`, `int col`)
Both malloc and memcpy a 2D array into device VRAM.

Protected Attributes

- `char **` [edgeMatrix](#)
2-D Character array for the edge Matrix (The characters of Nodes)
- `long int **` [valueMatrix](#)
2-d Integer array for the value Matrix (For the weights of Edges)
- `int` [matrixSize](#)
to hold Matrix size
- `char *` [matrixIndex](#)
to hold the Matrix index (To hold the orders of 2-D arrays')
- `long int *` [totalEdgeWeights](#)
Array of the Total [Edge](#) Weights.
- `bool` [ready](#)
True when matrix is constructed. False if not.

Private Member Functions

- void [TrainThread](#) ([Markov::API::Concurrency::ThreadSharedListHandler](#) *listhandler, `char delimiter`)
A single thread invoked by the Train function.
- void [GenerateThread](#) (`std::mutex *outputLock`, `unsigned long int n`, `std::ofstream *wordlist`, `int minLen`, `int maxLen`)
A single thread invoked by the Generate function.

Private Attributes

- `char *` [device_edgeMatrix](#)
VRAM Address pointer of edge matrix (from [modelMatrix.h](#))
- `long int *` [device_valueMatrix](#)
VRAM Address pointer of value matrix (from [modelMatrix.h](#))
- `char *` [device_matrixIndex](#)
VRAM Address pointer of matrixIndex (from [modelMatrix.h](#))
- `long int *` [device_totalEdgeWeights](#)
VRAM Address pointer of total edge weights (from [modelMatrix.h](#))
- `char *` [device_outputBuffer](#)
RandomWalk results in device.
- `char *` [outputBuffer](#)
RandomWalk results in host.
- `char *` [flatEdgeMatrix](#)
Adding [Edge](#) matrix end-to-end and resize to 1-D array for better perfomance on traversing.

- long int * [flatValueMatrix](#)
Adding Value matrix end-to-end and resize to 1-D array for better performance on traversing.
- std::ifstream * [datasetFile](#)
- std::ofstream * [modelSavefile](#)
Dataset file input of our system
- std::ofstream * [outputFile](#)
File to save model of our system
- std::map< char, [Node](#)< char > * > [nodes](#)
Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
- [Node](#)< char > * [starterNode](#)
Starter Node of this model.
- std::vector< [Edge](#)< char > * > [edges](#)
A list of all edges in this model.

8.6.1 Detailed Description

Extension of [Markov::API::ModelMatrix](#) which is modified to run on GPU devices.
This implementation only supports Nvidia devices.
Definition at line 11 of file [cudaModelMatrix.h](#).

8.6.2 Member Function Documentation

8.6.2.1 AdjustEdge()

```
void Markov::Model< char >::AdjustEdge (
    const NodeStorageType * payload,
    long int occurrence ) [inherited]
```

Adjust the model with a single string.

Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from current node to the next, until NULL character is reached.

Then, update the edge EdgeWeight from current node, to the terminator node.

This function is used for training purposes, as it can be used for adjusting the model with each line of the corpus file.

Example Use: Create an empty model and train it with string: "testdata"

```
Markov::Model<char> model;
char test[] = "testdata";
model.AdjustEdge(test, 15);
```

Parameters

<i>string</i>	- String that is passed from the training, and will be used to AdjustEdge the model with
<i>occurrence</i>	- Occurrence of this string.

Definition at line 323 of file [model.h](#).

```
00323
00324     NodeStorageType p = payload[0];
00325     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00326     Markov::Edge<NodeStorageType>* e;
00327     int i = 0;
00328
00329     if (p == 0) return;
00330     while (p != 0) {
00331         e = curnode->FindEdge(p);
00332         if (e == NULL) return;
00333         e->AdjustEdge(occurrence);
00334         curnode = e->RightNode();
00335         p = payload[++i];
00336     }
```

```

00337
00338     e = curnode->FindEdge('\xff');
00339     e->AdjustEdge(occurrence);
00340     return;
00341 }

```

8.6.2.2 AllocVRAMOutputBuffer()

```

__host__ char* Markov::API::CUDA::CUDAModelMatrix::AllocVRAMOutputBuffer (
    long int n,
    long int singleGenMaxLen,
    long int CUDAKernelGridSize,
    long int sizePerGrid ) [protected]

```

Allocate the output buffer for kernel operation.

TODO

Parameters

<i>n</i>	- Number of passwords to generate.
<i>singleGenMaxLen</i>	- maximum string length for a single generation
<i>CUDAKernelGridSize</i>	- Total number of grid members in CUDA kernel
<i>sizePerGrid</i>	- Size to allocate per grid member

Returns

pointer to the allocation on VRAM

8.6.2.3 ConstructMatrix()

```
bool Markov::API::ModelMatrix::ConstructMatrix ( ) [inherited]
```

Construct the related Matrix data for the model.

This operation can be used after importing/training to allocate and populate the matrix content.

this will initialize: char** edgeMatrix -> a 2D array of mapping left and right connections of each edge. long int **valueMatrix -> a 2D array representing the edge weights. int matrixSize -> Size of the matrix, aka total number of nodes. char* matrixIndex -> order of nodes in the model long int *totalEdgeWeights -> total edge weights of each [Node](#).

Returns

True if constructed. False if already constructed.

Definition at line 22 of file [modelMatrix.cpp](#).

```

00022     {
00023         if(this->ready) return false;
00024         this->matrixSize = this->StarterNode()->edgesV.size() + 2;
00025
00026         this->matrixIndex = new char[this->matrixSize];
00027         this->totalEdgeWeights = new long int[this->matrixSize];
00028
00029         this->edgeMatrix = new char*[this->matrixSize];
00030         for(int i=0;i<this->matrixSize;i++){
00031             this->edgeMatrix[i] = new char[this->matrixSize];
00032         }
00033         this->valueMatrix = new long int*[this->matrixSize];
00034         for(int i=0;i<this->matrixSize;i++){
00035             this->valueMatrix[i] = new long int[this->matrixSize];
00036         }
00037         std::map< char, Node< char > * > *nodes;
00038         nodes = this->Nodes();
00039         int i=0;
00040         for (auto const& [repr, node] : *nodes){
00041             if(repr!=0) this->matrixIndex[i] = repr;
00042             else this->matrixIndex[i] = 199;
00043             this->totalEdgeWeights[i] = node->TotalEdgeWeights();
00044             for(int j=0;j<this->matrixSize;j++){
00045                 char val = node->NodeValue();

```


```

00046         if(val < 0){
00047             for(int k=0;k<this->matrixSize;k++){
00048                 this->valueMatrix[i][k] = 0;
00049                 this->edgeMatrix[i][k] = 255;
00050             }
00051             break;
00052         }
00053         else if(node->NodeValue() == 0 && j>(this->matrixSize-3)){
00054             this->valueMatrix[i][j] = 0;
00055             this->edgeMatrix[i][j] = 255;
00056         }else if(j==(this->matrixSize-1)) {
00057             this->valueMatrix[i][j] = 0;
00058             this->edgeMatrix[i][j] = 255;
00059         }else{
00060             this->valueMatrix[i][j] = node->edgesV[j]->EdgeWeight();
00061             this->edgeMatrix[i][j] = node->edgesV[j]->RightNode()->NodeValue();
00062         }
00063     }
00064 }
00065     i++;
00066 }
00067 this->ready = true;
00068 return true;
00069 //this->DumpJSON();
00070 }


```

References [Markov::API::ModelMatrix::edgeMatrix](#), [Markov::Edge< NodeStorageType >::EdgeWeight\(\)](#), [Markov::API::ModelMatrix::matrixSize](#), [Markov::Model< NodeStorageType >::Nodes\(\)](#), [Markov::Node< storageType >::NodeValue\(\)](#), [Markov::API::ModelMatrix::ready](#), [Markov::Edge< NodeStorageType >::RightNode\(\)](#), [Markov::Model< NodeStorageType >::StarterNode\(\)](#), [Markov::API::ModelMatrix::totalEdgeWeights](#), [Markov::Node< storageType >::TotalEdgeWeights\(\)](#), and [Markov::API::ModelMatrix::valueMatrix](#).
Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), [Markov::API::ModelMatrix::Import\(\)](#), and [Markov::API::ModelMatrix::Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.2.4 CudaCheckNotifyErr()

```
static __host__ int Markov::API::CUDA::CUDADeviceController::CudaCheckNotifyErr (
    cudaError_t _status,
    const char * msg,
    bool bExit = true ) [static], [protected], [inherited]
```

Check results of the last operation on GPU.

Check the status returned from cudaMalloc/cudaMemcpy to find failures.

If a failure occurs, its assumed beyond redemption, and exited.

Parameters

<i>_status</i>	Cuda error status to check
<i>msg</i>	Message to print in case of a failure

Returns

0 if successful, 1 if failure. **Example output:**

```
char *da, a = "test";
cudastatus = cudaMalloc((char **)&da, 5*sizeof(char));
CudaCheckNotifyErr(cudastatus, "Failed to allocate VRAM for *da.\n");
```

8.6.2.5 CudaMalloc2DToFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat (
    T ** dst,
    int row,
    int col ) [inline], [static], [protected], [inherited]
```

Malloc a 2D array in device space.

This function will allocate enough space on VRAM for flattened 2D array.

Parameters

<i>dst</i>	destination pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:


```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
if(cudastatus!=cudaSuccess){
    CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
}
```

Definition at line 73 of file [cudaDeviceController.h](#).

```
00073
00074         cudaError_t cudastatus = cudaMalloc((T **)dst, row*col*sizeof(T));
00075         CudaCheckNotifyErr(cudastatus, "cudaMalloc Failed.", false);
00076         return cudastatus;
00077     }
```

References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



8.6.2.6 CudaMemcpy2DToFlat()

```

template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat (
    T * dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected], [inherited]
  
```

Memcpy a 2D array in device space after flattening.

Resulting buffer will not be true 2D array.

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:

```

cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
cudastatus = CudaMemcpy2DToFlat<char>(&dst,src,15,15);
CudaCheckNotifyErr(cudastatus, " CudaMemcpy2DToFlat Failed.", false);
  
```


Definition at line 101 of file [cudaDeviceController.h](#).

```

00101
00102         T* tempbuf = new T[row*col];
00103         for(int i=0;i<row;i++){
00104             memcpy(&(tempbuf[row*i]), src[i], col);
00105         }
00106         return cudaMemcpy(dst, tempbuf, row*col*sizeof(T), cudaMemcpyHostToDevice);
00107     }
00108 }
  
```

References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



8.6.2.7 CudaMigrate2DFlat()

```

template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDAModelMatrix::CudaMigrate2DFlat (
    T ** dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected], [inherited]

```

Both malloc and memcpy a 2D array into device VRAM.
Resulting buffer will not be true 2D array.

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:

```

cudaError_t cudastatus;
char* dst;
cudastatus = CudaMigrate2DFlat<long int>(
    &dst, this->valueMatrix, this->matrixSize, this->matrixSize);
CudaCheckNotifyErr(cudastatus, "    Cuda failed to initialize value matrix row.");

```

Definition at line 130 of file [cudaDeviceController.h](#).

```


00130                                     {
00131     cudaError_t cudastatus;
00132     cudastatus = CudaMalloc2DToFlat<T>(dst, row, col);
00133     if(cudastatus!=cudaSuccess){
00134         CudaCheckNotifyErr(cudastatus, "    CudaMalloc2DToFlat Failed.", false);
00135         return cudastatus;
00136     }
00137     cudastatus = CudaMemcpy2DToFlat<T>(&dst, src, row, col);
00138     CudaCheckNotifyErr(cudastatus, "    CudaMemcpy2DToFlat Failed.", false);
00139     return cudastatus;
00140 }

```


References [Markov::API::CUDA::CUDAModelMatrix::CudaMigrate2DFlat\(\)](#).

Referenced by [Markov::API::CUDA::CUDAModelMatrix::CudaMalloc2DToFlat\(\)](#), [Markov::API::CUDA::CUDAModelMatrix::CudaMemcpy2DToFlat\(\)](#) and [Markov::API::CUDA::CUDAModelMatrix::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.2.8 DeallocateMatrix()

`bool Markov::API::ModelMatrix::DeallocateMatrix () [protected], [inherited]`
 Deallocate matrix and make it ready for re-construction.

Returns

True if deallocated. False if matrix was not initialized


Definition at line 72 of file [modelMatrix.cpp](#).

```

00072 {
00073     if(!this->ready) return false;
00074     delete[] this->matrixIndex;
00075     delete[] this->totalEdgeWeights;
00076
00077     for(int i=0;i<this->matrixSize;i++){
00078         delete[] this->edgeMatrix[i];
00079     }
00080     delete[] this->edgeMatrix;
00081
00082     for(int i=0;i<this->matrixSize;i++){
00083         delete[] this->valueMatrix[i];
00084     }
00085     delete[] this->valueMatrix;
00086
00087     this->matrixSize = -1;
00088     this->ready = false;
00089     return true;
00090 }
  
```

References [Markov::API::ModelMatrix::edgeMatrix](#), [Markov::API::ModelMatrix::matrixIndex](#), [Markov::API::ModelMatrix::matrixSize](#), [Markov::API::ModelMatrix::ready](#), [Markov::API::ModelMatrix::totalEdgeWeights](#), and [Markov::API::ModelMatrix::valueMatrix](#).

Referenced by [Markov::API::ModelMatrix::Import\(\)](#), and [Markov::API::ModelMatrix::Train\(\)](#).
Here is the caller graph for this function:



8.6.2.9 DumpJSON()

`void Markov::API::ModelMatrix::DumpJSON () [inherited]`

Debug function to dump the model to a JSON file.

Might not work 100%. Not meant for production use.

Definition at line 92 of file [modelMatrix.cpp](#).

```


00092     {
00093
00094         std::cout << "{\n    \"index\": \"\n";
00095         for(int i=0;i<this->matrixSize;i++){
00096             if(this->matrixIndex[i]=='') std::cout << "\\\"";
00097             else if(this->matrixIndex[i]=='\\') std::cout << "\\\"";
00098             else if(this->matrixIndex[i]==0) std::cout << "\\x00";
00099             else if(i==0) std::cout << "\\xff";
00100             else if(this->matrixIndex[i]=='\\n') std::cout << "\\n";
00101             else std::cout << this->matrixIndex[i];
00102         }
00103         std::cout <<
00104         "\",\n"
00105         "\"    \"edgemap\": {\n";
00106
00107         for(int i=0;i<this->matrixSize;i++){
00108             if(this->matrixIndex[i]=='') std::cout << "    \"\\\"\": [";
00109             else if(this->matrixIndex[i]=='\\') std::cout << "    \"\\\"\": [";
00110             else if(this->matrixIndex[i]==0) std::cout << "    \"\\x00\": [";
00111             else if(this->matrixIndex[i]<0) std::cout << "    \"\\xff\": [";
00112             else std::cout << "    \"    \" < this->matrixIndex[i] < \"\": [";
00113             for(int j=0;j<this->matrixSize;j++){
00114                 if(this->edgeMatrix[i][j]=='') std::cout << "    \"\\\"\": [";
00115                 else if(this->edgeMatrix[i][j]=='\\') std::cout << "    \"\\\"\": [";
00116                 else if(this->edgeMatrix[i][j]==0) std::cout << "    \"\\x00\": [";
00117                 else if(this->edgeMatrix[i][j]<0) std::cout << "    \"\\xff\": [";
00118                 else if(this->matrixIndex[i]=='\\n') std::cout << "    \"\\n\": [";
00119                 else std::cout << "    \"    \" < this->edgeMatrix[i][j] < \"\": [";
00120                 if(j!=this->matrixSize-1) std::cout << ", ";
00121             }
00122             std::cout << "],\n";
00123         }
00124         std::cout << "},\n";
00125
00126         std::cout << "\"    \" weightmap\": {\n";
00127         for(int i=0;i<this->matrixSize;i++){
00128             if(this->matrixIndex[i]=='') std::cout << "    \"\\\"\": [";
00129             else if(this->matrixIndex[i]=='\\') std::cout << "    \"\\\"\": [";
00130             else if(this->matrixIndex[i]==0) std::cout << "    \"\\x00\": [";
00131             else if(this->matrixIndex[i]<0) std::cout << "    \"\\xff\": [";
00132             else std::cout << "    \"    \" < this->matrixIndex[i] < \"\": [";
00133             for(int j=0;j<this->matrixSize;j++){
00134                 std::cout << this->valueMatrix[i][j];
00135                 if(j!=this->matrixSize-1) std::cout << ", ";
00136             }
00137             std::cout << "],\n";
00138         }
00139         std::cout << "    }\n\n";
00140     }
00141 }

```

References [Markov::API::ModelMatrix::edgeMatrix](#), [Markov::API::ModelMatrix::matrixIndex](#), [Markov::API::ModelMatrix::matrixSize](#), and [Markov::API::ModelMatrix::valueMatrix](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the caller graph for this function:



8.6.2.10 Edges()

```
std::vector<Edge<char >*> Markov::Model< char >::Edges ( ) [inline], [inherited]
```

Return a vector of all the edges in the model.

Returns

vector of edges

Definition at line 172 of file [model.h](#).

```
00172 { return &edges; }
```

8.6.2.11 Export() [1/2]

```
bool Markov::Model< char >::Export (
    const char * filename ) [inherited]
```

Open a file to export with filename, and call bool [Model::Export](#) with std::ofstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Export file to filename

```
Markov::Model<char> model;
model.Export("test.mdl");
```

Definition at line 286 of file [model.h](#).

```
00286
00287     std::ofstream exportfile;
00288     exportfile.open(filename);
00289     return this->Export(&exportfile);
00290 }
```

8.6.2.12 Export() [2/2]

```
bool Markov::Model< char >::Export (
    std::ofstream * f ) [inherited]
```

Export a file of the model.

File contains a list of edges. Format is: Left_repr;EdgeWeight;right_repr. For more information on the format, check out the project wiki or github readme.

Iterate over this vertices, and their edges, and write them to file.

Returns

True if successful, False for incomplete models.

Example Use: Export file to ofstream

```
Markov::Model<char> model;
std::ofstream file("test.mdl");
model.Export(&file);
```

Definition at line 274 of file [model.h](#).

```
00274
{
```

```

00275     Markov::Edge<NodeStorageType>* e;
00276     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00277         e = this->edges[i];
00278         //std::cout << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," <<
00279         e->RightNode()->NodeValue() << "\n";
00279         *f << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," << e->RightNode()->NodeValue() <<
00280         "\n";
00280     }
00281
00282     return true;
00283 }

```

8.6.2.13 FastRandomWalk() [1/2]

```

__host__ void Markov::API::CUDA::CUDAModelMatrix::FastRandomWalk (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen,
    int maxLen,
    bool bFileIO )

```

Random walk on the Matrix-reduced [Markov::Model](#).

TODO

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

```

Markov::API::ModelMatrix mp;
mp.Import("models/finished.mdl");
mp.FastRandomWalk(50000000,"./wordlist.txt",6,12,25, true);

```

8.6.2.14 FastRandomWalk() [2/2]

```

void Markov::API::ModelMatrix::FastRandomWalk (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20,
    bool bFileIO = true ) [inherited]

```

Random walk on the Matrix-reduced [Markov::Model](#).

This has an O(N) Memory complexity. To limit the maximum usage, requests with $n > 50M$ are partitioned using [Markov::API::ModelMatrix::FastRandomWalkPartition](#).

If $n > 50M$, threads are going to be synced, files are going to be flushed, and buffers will be reallocated every 50M generations. This comes at a minor performance penalty.

While it has the same functionality, this operation reduces [Markov::API::MarkovPasswords::Generate](#) runtime by %96.5

This function has deprecated [Markov::API::MarkovPasswords::Generate](#), and will eventually replace it.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate

Parameters

<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

Markov::API::ModelMatrix mp;
 mp.Import("models/finished.mdl");
 mp.FastRandomWalk(50000000, ".wordlist.txt", 6, 12, 25, true);

Definition at line 195 of file modelMatrix.cpp.

```

00195
                                {
00196
00197
00198     std::ofstream wordlist;
00199     if(bFileIO)
00200         wordlist.open(wordlistFileName);
00201
00202     std::mutex mlock;
00203     if(n<=500000000ull) return this->FastRandomWalkPartition(&mlock, &wordlist, n, minLen, maxLen,
bFileIO, threads);
00204     else{
00205         int numberOfPartitions = n/500000000ull;
00206         for(int i=0;i<numberOfPartitions;i++)
00207             this->FastRandomWalkPartition(&mlock, &wordlist, 50000000ull, minLen, maxLen, bFileIO,
threads);
00208     }
00209
00210
00211 }
```


References [Markov::API::ModelMatrix::FastRandomWalkPartition\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.2.15 FastRandomWalkPartition()

```

void Markov::API::ModelMatrix::FastRandomWalkPartition (
    std::mutex * mlock,
    std::ofstream * wordlist,
    unsigned long int n,
    int minLen,
    int maxLen,
    bool bFileIO,
    int threads ) [protected], [inherited]
```

A single partition of FastRandomWalk event.

Since FastRandomWalk has to allocate its output buffer before operation starts and writes data in chunks, large n parameters would lead to huge memory allocations. **Without Partitioning:**

- 50M results 12 characters max -> 550 Mb Memory allocation
- 5B results 12 characters max -> 55 Gb Memory allocation
- 50B results 12 characters max -> 550GB Memory allocation

Instead, FastRandomWalk is partitioned per 50M generations to limit the top memory need.

Parameters

<i>mlock</i>	- mutex lock to distribute to child threads
<i>wordlist</i>	- Reference to the wordlist file to write to
<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

Definition at line 214 of file [modelMatrix.cpp](#).

```


00214
00215
00216         int iterationsPerThread = n/threads;
00217         int iterationsPerThreadCarryOver = n%threads;
00218
00219         std::vector<std::thread*> threadsV;
00220
00221         int id = 0;
00222         for(int i=0;i<threads;i++){
00223             threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this,
00224 mlock, wordlist, iterationsPerThread, minLen, maxLen, id, bFileIO));
00225             id++;
00226         }
00227         threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this, mlock,
00228 wordlist, iterationsPerThreadCarryOver, minLen, maxLen, id, bFileIO));
00229         for(int i=0;i<threads;i++){
00230             threadsV[i]->join();
00231         }
00232     }

```


References [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

Referenced by [Markov::API::ModelMatrix::FastRandomWalk\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.2.16 FastRandomWalkThread()

```
void Markov::API::ModelMatrix::FastRandomWalkThread (
    std::mutex * mlock,
    std::ofstream * wordlist,
    unsigned long int n,
    int minLen,
    int maxLen,
    int id,
    bool bFileIO ) [protected], [inherited]
```

A single thread of a single partition of FastRandomWalk.

A FastRandomWalkPartition will initiate as many of this function as requested.

This function contains the bulk of the generation algorithm.

Parameters

<i>mlock</i>	- mutex lock to distribute to child threads
<i>wordlist</i>	- Reference to the wordlist file to write to
<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>id</i>	- DEPRECATED Thread id - No longer used
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

Definition at line 144 of file [modelMatrix.cpp](#).


```
00144
00145         if(n==0) return;
00146
00147         Markov::Random::Marsaglia MarsagliaRandomEngine;
00148         char* e;
00149         char *res = new char[maxLen*n];
00150         int index = 0;
00151         char next;
00152         int len=0;
00153         long int selection;
00154         char cur;
00155         long int bufferctr = 0;
00156         for (int i = 0; i < n; i++) {
00157             cur=199;
00158             len=0;
00159             while (true) {
00160                 e = strchr(this->matrixIndex, cur);
00161                 index = e - this->matrixIndex;
00162                 selection = MarsagliaRandomEngine.random() % this->totalEdgeWeights[index];
00163                 for(int j=0;j<this->matrixSize;j++){
00164                     selection -= this->valueMatrix[index][j];
00165                     if (selection < 0){
00166                         next = this->edgeMatrix[index][j];
00167                         break;
00168                     }
00169                 }
00170
00171                 if (len >= maxLen) break;
00172                 else if ((next < 0) && (len < minLen)) continue;
00173                 else if (next < 0) break;
00174                 cur = next;
00175                 res[bufferctr + len++] = cur;
00176             }
00177             res[bufferctr + len++] = '\n';
00178             bufferctr+=len;
00179         }
00180         if(bFileIO){
00181             mlock->lock();
00182             *wordlist << res;
00183             mlock->unlock();
00184         }else{
00185             mlock->lock();
00186             std::cout << res;
00187             mlock->unlock();
00188         }
00189     }
```

```
00190     delete res;
00191
00192 }
```

References [Markov::API::ModelMatrix::edgeMatrix](#), [Markov::API::ModelMatrix::matrixIndex](#), [Markov::API::ModelMatrix::matrixSize](#), [Markov::Random::Marsaglia::random\(\)](#), [Markov::API::ModelMatrix::totalEdgeWeights](#), and [Markov::API::ModelMatrix::valueMatrix](#).

Referenced by [Markov::API::ModelMatrix::FastRandomWalkPartition\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.2.17 FlattenMatrix()

```
__host__ void Markov::API::CUDA::CUDAModelMatrix::FlattenMatrix ( )
```

Flatten migrated matrix from 2d to 1d.

8.6.2.18 Generate()

```
void Markov::API::MarkovPasswords::Generate (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20 ) [inherited]
```

Call [Markov::Model::RandomWalk](#) n times, and collect output.

Generate from model and write results to a file. a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Deprecated See [Markov::API::MatrixModel::FastRandomWalk](#) for more information.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn

Definition at line 110 of file [markovPasswords.cpp](#).

```
00110
{
00111     char* res;
```

```


00112     char print[100];
00113     std::ofstream wordlist;
00114     wordlist.open(wordlistFileName);
00115     std::mutex mlock;
00116     int iterationsPerThread = n/threads;
00117     int iterationsCarryOver = n%threads;
00118     std::vector<std::thread*> threadsV;
00119     for(int i=0;i<threads;i++){
00120         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::GenerateThread, this,
&mlock, iterationsPerThread, &wordlist, minLen, maxLen));
00121     }
00122
00123     for(int i=0;i<threads;i++){
00124         threadsV[i]->join();
00125         delete threadsV[i];
00126     }
00127
00128     this->GenerateThread(&mlock, iterationsCarryOver, &wordlist, minLen, maxLen);
00129
00130 }

```


References [Markov::API::MarkovPasswords::GenerateThread\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.2.19 GenerateThread()

```

void Markov::API::MarkovPasswords::GenerateThread (
    std::mutex * outputLock,
    unsigned long int n,
    std::ofstream * wordlist,
    int minLen,
    int maxLen ) [private], [inherited]

```

A single thread invoked by the Generate function.

DEPRECATED: See [Markov::API::MatrixModel::FastRandomWalkThread](#) for more information. This has been replaced with a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Parameters

<i>outputLock</i>	- shared mutex lock to lock during output operation. Prevents race condition on write.
<i>n</i>	number of lines to be generated by this thread
<i>wordlist</i>	wordlistfile
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate

Definition at line 132 of file [markovPasswords.cpp](#).

```

00132
00133     char* res = new char[maxLen+5];
00134     if (n==0) return;
00135
00136     Markov::Random::Marsaglia MarsagliaRandomEngine;
00137     for (int i = 0; i < n; i++) {
00138         this->RandomWalk(&MarsagliaRandomEngine, minLen, maxLen, res);
00139         outputLock->lock();
00140         *wordlist « res « "\n";
00141         outputLock->unlock();
00142     }
00143 }
```


References [Markov::Model< NodeStorageType >::RandomWalk\(\)](#).

Referenced by [Markov::API::MarkovPasswords::Generate\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.2.20 Import() [1/2]

```

void Markov::API::ModelMatrix::Import (
    const char * filename ) [inherited]
```

Open a file to import with filename, and call bool [Model::Import](#) with std::ifstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file with filename

```

Markov::Model<char> model;
model.Import("test.mdl");
```

Construct the matrix when done.

Definition at line 10 of file [modelMatrix.cpp](#).


```

00010     {
00011         this->DeallocateMatrix();
00012         this->Markov::API::MarkovPasswords::Import(filename);
00013         this->ConstructMatrix();
00014     }
```


References [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), and [Markov::Model< NodeStorageType >::Import\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.2.21 Import() [2/2]

```
bool Markov::Model< char >::Import (
    std::ifstream * f ) [inherited]
```

Import a file to construct the model.

File contains a list of edges. For more info on the file format, check out the wiki and github readme pages. Format is: Left_repr;EdgeWeight;right_repr

Iterate over this list, and construct nodes and edges accordingly.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file from ifstream

```
Markov::Model<char> model;
std::ifstream file("test.mdl");
model.Import(&file);
```

Definition at line 207 of file [model.h](#).

```
00207                                     {
00208     std::string cell;
00209
00210     char src;
00211     char target;
00212     long int oc;
00213
00214     while (std::getline(*f, cell)) {
00215         //std::cout << "cell: " << cell << std::endl;
00216         src = cell[0];
00217         target = cell[cell.length() - 1];
00218         char* j;
00219         oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(), &j, 10);
00220         //std::cout << oc << "\n";
00221         Markov::Node<NodeStorageType>* srcN;
```

```

00222         Markov::Node<NodeStorageType>* targetN;
00223         Markov::Edge<NodeStorageType>* e;
00224         if (this->nodes.find(src) == this->nodes.end()) {
00225             srcN = new Markov::Node<NodeStorageType>(src);
00226             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(src, srcN));
00227             //std::cout << "Creating new node at start.\n";
00228         }
00229         else {
00230             srcN = this->nodes.find(src)->second;
00231         }
00232
00233         if (this->nodes.find(target) == this->nodes.end()) {
00234             targetN = new Markov::Node<NodeStorageType>(target);
00235             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(target, targetN));
00236             //std::cout << "Creating new node at end.\n";
00237         }
00238         else {
00239             targetN = this->nodes.find(target)->second;
00240         }
00241         e = srcN->Link(targetN);
00242         e->AdjustEdge(oc);
00243         this->edges.push_back(e);
00244
00245         //std::cout << int(srcN->NodeValue()) << " --" << e->EdgeWeight() << "--> " <<
int(targetN->NodeValue()) << "\n";
00246
00247     }
00248
00249     for (std::pair<unsigned char, Markov::Node<NodeStorageType>*> const& x : this->nodes) {
00250         //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
00251         std::sort (x.second->edgesV.begin(), x.second->edgesV.end(), [] (Edge<NodeStorageType> *lhs,
00252             Edge<NodeStorageType> *rhs)->bool{
00253             return lhs->EdgeWeight() > rhs->EdgeWeight();
00254         });
00255         //for(int i=0;i<x.second->edgesV.size();i++)
00256         // std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00257         //std::cout << "\n";
00258     }
00259     //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00260     //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00261
00262     return true;
00263 }

```

8.6.2.22 ListCudaDevices()

```
static __host__ void Markov::API::CUDA::CUDADeviceController::ListCudaDevices ( ) [static],
[inherited]
```

List [CUDA](#) devices in the system.

This function will print details of every [CUDA](#) capable device in the system.

Example output:

```

Device Number: 0
Device name: GeForce RTX 2070
Memory Clock Rate (KHz): 7001000
Memory Bus Width (bits): 256
Peak Memory Bandwidth (GB/s): 448.064
Max Linear Threads: 1024

```

8.6.2.23 MigrateMatrix()

```
__host__ void Markov::API::CUDA::CUDAModelMatrix::MigrateMatrix ( )
```

Migrate the class members to the VRAM.

Cannot be used without calling [Markov::API::ModelMatrix::ConstructMatrix](#) at least once. This function will manage the memory allocation and data transfer from CPU RAM to GPU VRAM.

Newly allocated VRAM pointers are set in the class member variables.

8.6.2.24 Nodes()

```
std::map<char , Node<char >*>* Markov::Model< char >::Nodes ( ) [inline], [inherited]
```

Return starter [Node](#).

Returns

starter node with 00 NodeValue

Definition at line 177 of file [model.h](#).

```
00177 { return &nodes; }
```

8.6.2.25 OpenDatasetFile()

```
std::ifstream * Markov::API::MarkovPasswords::OpenDatasetFile (
    const char * filename ) [inherited]
```

Open dataset file and return the ifstream pointer.

Parameters

<i>filename</i>	- Filename to open
-----------------	--------------------

Returns


ifstream* to the the dataset file

Definition at line 43 of file [markovPasswords.cpp](#).

```
00043 {
00044
00045     std::ifstream* datasetFile;
00046
00047     std::ifstream newFile(filename);
00048
00049     datasetFile = &newFile;
00050
00051     this->Import(datasetFile);
00052     return datasetFile;
00053 }
```

References [Markov::Model< NodeStorageType >::Import\(\)](#).

Here is the call graph for this function:

**8.6.2.26 RandomWalk()**

```
char * Markov::Model< char >::RandomWalk (
    Markov::Random::RandomEngine * randomEngine,
    int minSetting,
    int maxSetting,
    NodeStorageType * buffer ) [inherited]
```

Do a random walk on this model.

Start from the starter node, on each node, invoke RandomNext using the random engine on current node, until terminator node is reached. If terminator node is reached before minimum length criateria is reached, ignore the last selection and re-invoke randomNext

If maximum length criteria is reached but final node is not, cut off the generation and proceed to the final node. This function takes [Markov::Random::RandomEngine](#) as a parameter to generate pseudo random numbers from This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne output is higher in entropy, most use cases don't really need super high entropy output, so [Markov::Random::Marsaglia](#) is preferable for better performance.

This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening via maximum length criteria.

Example Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use Marsaglia

```
Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}
```

Parameters

<i>randomEngine</i>	Random Engine to use for the random walks. For examples, see Markov::Random::Mersenne and Markov::Random::Marsaglia
<i>minSetting</i>	Minimum number of characters to generate
<i>maxSetting</i>	Maximum number of character to generate
<i>buffer</i>	buffer to write the result to

Returns

Null terminated string that was generated.

Definition at line 293 of file [model.h](#).

```
00293
00294     {
00295         Markov::Node<NodeStorageType>* n = this->starterNode;
00296         int len = 0;
00297         Markov::Node<NodeStorageType>* temp_node;
00298         while (true) {
00299             temp_node = n->RandomNext(randomEngine);
00300             if (len >= maxSetting) {
00301                 break;
00302             }
00303             else if ((temp_node == NULL) && (len < minSetting)) {
00304                 continue;
00305             }
00306             else if (temp_node == NULL) {
00307                 break;
00308             }
00309             n = temp_node;
00310             buffer[len++] = n->NodeValue();
00311         }
00312         //null terminate the string
00313         buffer[len] = 0x00;
00314         //do something with the generated string
00315         return buffer; //for now
00316     }
00317 }
```

8.6.2.27 Save()

```
std::ofstream * Markov::API::MarkovPasswords::Save (
    const char * filename ) [inherited]
```

Export model to file.

Parameters

<i>filename</i>	- Export filename.
-----------------	--------------------

Returns


std::ofstream* of the exported file.

Definition at line 98 of file [markovPasswords.cpp](#).

```
00098                                     {
00099     std::ofstream* exportFile;
00100
00101     std::ofstream newFile(filename);
00102
00103     exportFile = &newFile;
00104
00105     this->Export(exportFile);
00106     return exportFile;
00107 }
```

References [Markov::Model< NodeStorageType >::Export\(\)](#).

Here is the call graph for this function:

**8.6.2.28 StarterNode()**

[Node<char >*](#) [Markov::Model< char >::StarterNode \(\)](#) [inline], [inherited]

Return starter [Node](#).

Returns

starter node with 00 NodeValue

Definition at line 167 of file [model.h](#).

```
00167 { return starterNode; }
```

8.6.2.29 Train()

```
void Markov::API::ModelMatrix::Train (
    const char * datasetFileName,
    char delimiter,
    int threads ) [inherited]
```

Train the model with the dataset file.

Parameters

<i>datasetFileName</i>	- ifstream* to the dataset. If null, use class member
<i>delimiter</i>	- a character, same as the delimiter in dataset content
<i>threads</i>	- number of OS threads to spawn

```
Markov::API::MarkovPasswords mp;
mp.Import ("models/2gram.mdl");
mp.Train("password.corpus");
```

Construct the matrix when done.

Definition at line 16 of file [modelMatrix.cpp](#).


```
00016                                     {
00017     this->DeallocateMatrix();
00018     this->Markov::API::MarkovPasswords::Train(datasetFileName, delimiter, threads);
00019     this->ConstructMatrix();
00020 }
```

References [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), and


[Markov::API::MarkovPasswords::Train\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.2.30 TrainThread()

```
void Markov::API::MarkovPasswords::TrainThread (
    Markov::API::Concurrency::ThreadSharedListHandler * listhandler,
    char delimiter ) [private], [inherited]
```

A single thread invoked by the Train function.

Parameters

<i>listhandler</i>	- Listhandler class to read corpus from
<i>delimiter</i>	- a character, same as the delimiter in dataset content

Definition at line 77 of file [markovPasswords.cpp](#).

```
00077 {
00078     char format_str[] = "%ld,%s";
00079     format_str[3]=delimiter;
00080     std::string line;
00081     while (listhandler->next(&line) && keepRunning) {
00082         long int oc;
00083         if (line.size() > 100) {
00084             line = line.substr(0, 100);
00085         }
00086         char* linebuf = new char[line.length()+5];
00087 #ifdef _WIN32
00088         sscanf_s(line.c_str(), "%ld,%s", &oc, linebuf, line.length()+5); //<== changed format_str to->
```

```


    "%ld,%s"
00089 #else
00090     sscanf(line.c_str(), format_str, &oc, linebuf);
00091 #endif
00092     this->AdjustEdge((const char*)linebuf, oc);
00093     delete linebuf;
00094 }
00095 }

```


References [Markov::Model< NodeStorageType >::AdjustEdge\(\)](#), [keepRunning](#), and [Markov::API::Concurrency::ThreadSharedListHa](#)

Referenced by [Markov::API::MarkovPasswords::Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.6.3 Member Data Documentation

8.6.3.1 datasetFile

`std::ifstream* Markov::API::MarkovPasswords::datasetFile` [private], [inherited]
 Definition at line 106 of file [markovPasswords.h](#).

8.6.3.2 device_edgeMatrix

`char* Markov::API::CUDA::CUDAModelMatrix::device_edgeMatrix` [private]
 VRAM Address pointer of edge matrix (from [modelMatrix.h](#))
 Definition at line 73 of file [cudaModelMatrix.h](#).

8.6.3.3 device_matrixIndex

`char* Markov::API::CUDA::CUDAModelMatrix::device_matrixIndex` [private]
 VRAM Address pointer of matrixIndex (from [modelMatrix.h](#))
 Definition at line 83 of file [cudaModelMatrix.h](#).

8.6.3.4 device_outputBuffer

`char* Markov::API::CUDA::CUDAModelMatrix::device_outputBuffer` [private]
 RandomWalk results in device.
 Definition at line 94 of file [cudaModelMatrix.h](#).

8.6.3.5 device_totalEdgeWeights

```
long int* Markov::API::CUDA::CUDAModelMatrix::device_totalEdgeWeights [private]
```

VRAM Address pointer of total edge weights (from [modelMatrix.h](#))

Definition at line 88 of file [cudaModelMatrix.h](#).

8.6.3.6 device_valueMatrix

```
long int* Markov::API::CUDA::CUDAModelMatrix::device_valueMatrix [private]
```

VRAM Address pointer of value matrix (from [modelMatrix.h](#))

Definition at line 78 of file [cudaModelMatrix.h](#).

8.6.3.7 edgeMatrix

```
char** Markov::API::ModelMatrix::edgeMatrix [protected], [inherited]
```

2-D Character array for the edge Matrix (The characters of Nodes)

Definition at line 136 of file [modelMatrix.h](#).

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), and [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

8.6.3.8 edges

```
std::vector<Edge<char >> Markov::Model< char >::edges [private], [inherited]
```

A list of all edges in this model.

Definition at line 195 of file [model.h](#).

8.6.3.9 flatEdgeMatrix

```
char* Markov::API::CUDA::CUDAModelMatrix::flatEdgeMatrix [private]
```

Adding [Edge](#) matrix end-to-end and resize to 1-D array for better performance on traversing.

Definition at line 104 of file [cudaModelMatrix.h](#).

8.6.3.10 flatValueMatrix

```
long int* Markov::API::CUDA::CUDAModelMatrix::flatValueMatrix [private]
```

Adding Value matrix end-to-end and resize to 1-D array for better performance on traversing.

Definition at line 109 of file [cudaModelMatrix.h](#).

8.6.3.11 matrixIndex

```
char* Markov::API::ModelMatrix::matrixIndex [protected], [inherited]
```

to hold the Matrix index (To hold the orders of 2-D arrays')

Definition at line 151 of file [modelMatrix.h](#).

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), and [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

8.6.3.12 matrixSize

```
int Markov::API::ModelMatrix::matrixSize [protected], [inherited]
```

to hold Matrix size

Definition at line 146 of file [modelMatrix.h](#).

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), and [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

8.6.3.13 modelSavefile

`std::ofstream* Markov::API::MarkovPasswords::modelSavefile [private], [inherited]`
 Dataset file input of our system

Definition at line 107 of file [markovPasswords.h](#).

8.6.3.14 nodes

`std::map<char , Node<char >*> Markov::Model< char >::nodes [private], [inherited]`
 Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
 Definition at line 184 of file [model.h](#).

8.6.3.15 outputBuffer

`char* Markov::API::CUDA::CUDAModelMatrix::outputBuffer [private]`
 RandomWalk results in host.
 Definition at line 99 of file [cudaModelMatrix.h](#).

8.6.3.16 outputFile

`std::ofstream* Markov::API::MarkovPasswords::outputFile [private], [inherited]`
 File to save model of our system

Definition at line 108 of file [markovPasswords.h](#).

8.6.3.17 ready

`bool Markov::API::ModelMatrix::ready [protected], [inherited]`
 True when matrix is constructed. False if not.
 Definition at line 161 of file [modelMatrix.h](#).
 Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), and [Markov::API::ModelMatrix::ModelMatrix\(\)](#).

8.6.3.18 starterNode

`Node<char >* Markov::Model< char >::starterNode [private], [inherited]`
 Starter [Node](#) of this model.
 Definition at line 189 of file [model.h](#).

8.6.3.19 totalEdgeWeights

`long int* Markov::API::ModelMatrix::totalEdgeWeights [protected], [inherited]`
 Array of the Total [Edge](#) Weights.
 Definition at line 156 of file [modelMatrix.h](#).
 Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), and [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

8.6.3.20 valueMatrix

```
long int** Markov::API::ModelMatrix::valueMatrix [protected], [inherited]
```

2-d Integer array for the value Matrix (For the weights of Edges)

Definition at line 141 of file [modelMatrix.h](#).

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), and [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

The documentation for this class was generated from the following file:


- [cudaModelMatrix.h](#)

8.7 Markov::Random::DefaultRandomEngine Class Reference


Implementation using [Random.h](#) default random engine.

```
#include <random.h>
```

Inheritance diagram for Markov::Random::DefaultRandomEngine:



Collaboration diagram for Markov::Random::DefaultRandomEngine:



Public Member Functions

- unsigned long `random ()`
Generate *Random* Number.

Protected Member Functions

- `std::random_device & rd ()`
Default random device for seeding.
- `std::default_random_engine & generator ()`
Default random engine for seeding.
- `std::uniform_int_distribution< long long unsigned > & distribution ()`
Distribution schema for seeding.

8.7.1 Detailed Description

Implementation using [Random.h](#) default random engine.

This engine is also used by other engines for seeding.

Example Use: Using Default Engine with RandomWalk

```

Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::DefaultRandomEngine randomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&randomEngine, 5, 10, res);
    std::cout << res << "\n";
}
  
```

Example Use: Generating a random number with [Marsaglia](#) Engine

```

Markov::Random::DefaultRandomEngine de;
std::cout << de.random();
  
```

Definition at line [52](#) of file [random.h](#).

8.7.2 Member Function Documentation

8.7.2.1 distribution()

```
std::uniform_int_distribution<long long unsigned>& Markov::Random::DefaultRandomEngine::distribution
( ) [inline], [protected]
```


Distribution schema for seeding.

Definition at line 81 of file [random.h](#).

```
00081                                     {
00082         static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00083         return _distribution;
00084     }
```

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [random\(\)](#).

Here is the caller graph for this function:



8.7.2.2 generator()

```
std::default_random_engine& Markov::Random::DefaultRandomEngine::generator ( ) [inline],
[protected]
```

Default random engine for seeding.

Definition at line 73 of file [random.h](#).

```
00073                                     {
00074         static std::default_random_engine _generator(rd());
00075         return _generator;
00076     }
```


References [rd\(\)](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [random\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.7.2.3 random()

unsigned long Markov::Random::DefaultRandomEngine::random () [inline], [virtual]

Generate [Random](#) Number.

Returns

random number in long range.

Implements [Markov::Random::RandomEngine](#).

Reimplemented in [Markov::Random::Marsaglia](#).


Definition at line 57 of file [random.h](#).

```

00057         {
00058             return this->distribution() (this->generator());
00059         }
  
```

References [distribution\(\)](#), and [generator\(\)](#).

Here is the call graph for this function:



8.7.2.4 rd()

std::random_device& Markov::Random::DefaultRandomEngine::rd () [inline], [protected]

Default random device for seeding.


Definition at line 65 of file [random.h](#).

```

00065         {
00066             static std::random_device _rd;
00067             return _rd;
00068         }
  
```

Referenced by [generator\(\)](#).

Here is the caller graph for this function:



The documentation for this class was generated from the following file:


- [random.h](#)

8.8 Markov::Edge< NodeStorageType > Class Template Reference


[Edge](#) class used to link nodes in the model together.

```
#include <model.h>
```

Inheritance diagram for Markov::Edge< NodeStorageType >:



Collaboration diagram for `Markov::Edge< NodeStorageType >`:



Public Member Functions

- `Edge ()`
Default constructor.
- `Edge (Node< NodeStorageType > *_left, Node< NodeStorageType > *_right)`
Constructor. Initialize edge with given RightNode and LeftNode.
- `void AdjustEdge (long int offset)`
Adjust the edge EdgeWeight with offset. Adds the offset parameter to the edge EdgeWeight.
- `Node< NodeStorageType > * TraverseNode ()`
Traverse this edge to RightNode.
- `void SetLeftEdge (Node< NodeStorageType > *)`
Set LeftNode of this edge.
- `void SetRightEdge (Node< NodeStorageType > *)`
Set RightNode of this edge.
- `uint64_t EdgeWeight ()`
return edge's EdgeWeight.
- `Node< NodeStorageType > * LeftNode ()`
return edge's LeftNode
- `Node< NodeStorageType > * RightNode ()`
return edge's RightNode

Private Attributes

- [Node](#)< NodeStorageType > * [_left](#)
source node
- [Node](#)< NodeStorageType > * [_right](#)
target node
- long int [_weight](#)
Edge Edge Weight.

8.8.1 Detailed Description

```
template<typename NodeStorageType>
class Markov::Edge< NodeStorageType >
```

[Edge](#) class used to link nodes in the model together.

Has LeftNode, RightNode, and EdgeWeight of the edge. Edges are *UNIDIRECTIONAL* in this model. They can only be traversed LeftNode to RightNode.

Definition at line 26 of file [model.h](#).

8.8.2 Constructor & Destructor Documentation

8.8.2.1 Edge() [1/2]

```
template<typename NodeStorageType >
Markov::Edge< NodeStorageType >::Edge
```

Default constructor.

Definition at line 116 of file [edge.h](#).

```
00116 {
00117     this->_left = NULL;
00118     this->_right = NULL;
00119     this->_weight = 0;
00120 }
```

8.8.2.2 Edge() [2/2]

```
template<typename NodeStorageType >
Markov::Edge< NodeStorageType >::Edge (
    Markov::Node< NodeStorageType > * _left,
    Markov::Node< NodeStorageType > * _right )
```

Constructor. Initialize edge with given RightNode and LeftNode.

Parameters

_left	- Left node of this edge.
_right	- Right node of this edge.

Example Use: Construct edge

```
Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
```

Definition at line 123 of file [edge.h](#).

```
00123 {
00124     this->_left = _left;
00125     this->_right = _right;
00126     this->_weight = 0;
00127 }
```

8.8.3 Member Function Documentation

8.8.3.1 AdjustEdge()

```
template<typename NodeStorageType >
void Markov::Edge< NodeStorageType >::AdjustEdge (
    long int offset )
```

Adjust the edge EdgeWeight with offset. Adds the offset parameter to the edge EdgeWeight.

Parameters

<i>offset</i>	- NodeValue to be added to the EdgeWeight
---------------	---

Example Use: Construct edge

```
Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
e1->AdjustEdge(25);
```

Definition at line 130 of file [edge.h](#).

```
00130                                     {
00131     this->_weight += offset;
00132     this->LeftNode()->UpdateTotalVerticeWeight(offset);
00133 }
```

8.8.3.2 EdgeWeight()

```
template<typename NodeStorageType >
uint64_t Markov::Edge< NodeStorageType >::EdgeWeight [inline]
return edge's EdgeWeight.
```

Returns


edge's EdgeWeight.

Definition at line 153 of file [edge.h](#).

```
00153                                     {
00154     return this->_weight;
00155 }
```

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:



8.8.3.3 LeftNode()

```
template<typename NodeStorageType >
Markov::Node< NodeStorageType > * Markov::Edge< NodeStorageType >::LeftNode
return edge's LeftNode
```

Returns

edge's LeftNode.

Definition at line 158 of file [edge.h](#).

```
00158                                     {
00159     return this->_left;
00160 }
```

8.8.3.4 RightNode()

```
template<typename NodeStorageType >
```

```
Markov::Node< NodeStorageType > * Markov::Edge< NodeStorageType >::RightNode [inline]
```

return edge's RightNode

Returns


edge's RightNode.

Definition at line 163 of file [edge.h](#).

```
00163                                     {
00164     return this->_right;
00165 }
```

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:

**8.8.3.5 SetLeftEdge()**

```
template<typename NodeStorageType >
```

```
void Markov::Edge< NodeStorageType >::SetLeftEdge (
    Markov::Node< NodeStorageType > * n )
```

Set LeftNode of this edge.

Parameters

<i>node</i>	- Node to be linked with.
-------------	---

Definition at line 143 of file [edge.h](#).

```
00143                                     {
00144     this->_left = n;
00145 }
```

8.8.3.6 SetRightEdge()

```
template<typename NodeStorageType >
```

```
void Markov::Edge< NodeStorageType >::SetRightEdge (
    Markov::Node< NodeStorageType > * n )
```

Set RightNode of this edge.

Parameters

<i>node</i>	- Node to be linked with.
-------------	---

Definition at line 148 of file [edge.h](#).

```
00148
00149     this->_right = n;
00150 }
```

8.8.3.7 TraverseNode()

```
template<typename NodeStorageType >
```

```
Markov::Node< NodeStorageType > * Markov::Edge< NodeStorageType >::TraverseNode [inline]
```

Traverse this edge to RightNode.

Returns

Right node. If this is a terminator node, return NULL

Example Use: Traverse a node

```
Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
e1->AdjustEdge(25);
Markov::Edge<unsigned char>* e2 = e1->traverseNode();
```

Definition at line 136 of file [edge.h](#).

```
00136
00137     if (this->RightNode()->NodeValue() == 0xff) //terminator node
00138         return NULL;
00139     return _right;
00140 }
```

8.8.4 Member Data Documentation

8.8.4.1 _left

```
template<typename NodeStorageType >
```

```
Node<NodeStorageType>* Markov::Edge< NodeStorageType >::_left [private]
```

source node

Definition at line 98 of file [edge.h](#).

8.8.4.2 _right

```
template<typename NodeStorageType >
```

```
Node<NodeStorageType>* Markov::Edge< NodeStorageType >::_right [private]
```

target node

Definition at line 103 of file [edge.h](#).

Referenced by [Markov::Edge< char >::TraverseNode\(\)](#).

8.8.4.3 _weight

```
template<typename NodeStorageType >
```

```
long int Markov::Edge< NodeStorageType >::_weight [private]
```

Edge Edge Weight.

Definition at line 108 of file [edge.h](#).

The documentation for this class was generated from the following files:


- [model.h](#)
- [edge.h](#)

8.9 Markov::API::MarkovPasswords Class Reference


[Markov::Model](#) with char represented nodes.

```
#include <markovPasswords.h>
```

Inheritance diagram for Markov::API::MarkovPasswords:



Collaboration diagram for Markov::API::MarkovPasswords:



Public Member Functions

- [MarkovPasswords](#) ()
Initialize the markov model from `MarkovModel::Markov::Model`.
- [MarkovPasswords](#) (const char *filename)
Initialize the markov model from `MarkovModel::Markov::Model`, with an import file.
- `std::ifstream` * [OpenDatasetFile](#) (const char *filename)
Open dataset file and return the ifstream pointer.

- void [Train](#) (const char *datasetFileName, char delimiter, int threads)
Train the model with the dataset file.
- std::ofstream * [Save](#) (const char *filename)
Export model to file.
- void [Generate](#) (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20)
Call [Markov::Model::RandomWalk](#) n times, and collect output.
- char * [RandomWalk](#) ([Markov::Random::RandomEngine](#) *randomEngine, int minSetting, int maxSetting, char *buffer)
Do a random walk on this model.
- void [AdjustEdge](#) (const char *payload, long int occurrence)
Adjust the model with a single string.
- bool [Import](#) (std::ifstream *)
Import a file to construct the model.
- bool [Import](#) (const char *filename)
Open a file to import with filename, and call bool [Model::Import](#) with std::ifstream.
- bool [Export](#) (std::ofstream *)
Export a file of the model.
- bool [Export](#) (const char *filename)
Open a file to export with filename, and call bool [Model::Export](#) with std::ofstream.
- [Node](#)< char > * [StarterNode](#) ()
Return starter Node.
- std::vector< [Edge](#)< char > * > * [Edges](#) ()
Return a vector of all the edges in the model.
- std::map< char, [Node](#)< char > * > * [Nodes](#) ()
Return starter Node.

Private Member Functions

- void [TrainThread](#) ([Markov::API::Concurrency::ThreadSharedListHandler](#) *listhandler, char delimiter)
A single thread invoked by the [Train](#) function.
- void [GenerateThread](#) (std::mutex *outputLock, unsigned long int n, std::ofstream *wordlist, int minLen, int maxLen)
A single thread invoked by the [Generate](#) function.

Private Attributes

- std::ifstream * [datasetFile](#)
- std::ofstream * [modelSavefile](#)
Dataset file input of our system
- std::ofstream * [outputFile](#)
File to save model of our system
- std::map< char, [Node](#)< char > * > * [nodes](#)
Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
- [Node](#)< char > * [starterNode](#)
Starter Node of this model.
- std::vector< [Edge](#)< char > * > * [edges](#)
A list of all edges in this model.

8.9.1 Detailed Description

[Markov::Model](#) with char represented nodes.

Includes wrappers for [Markov::Model](#) and additional helper functions to handle file I/O

This class is an extension of [Markov::Model<char>](#), with higher level abstractions such as train and generate.

Definition at line 17 of file [markovPasswords.h](#).

8.9.2 Constructor & Destructor Documentation

8.9.2.1 MarkovPasswords() [1/2]

`Markov::API::MarkovPasswords::MarkovPasswords ()`

Initialize the markov model from `MarkovModel::Markov::Model`.

Parent constructor. Has no extra functionality.

Definition at line 26 of file [markovPasswords.cpp](#).

```
00026                                     : Markov::Model<char>() {
00027
00028
00029 }
```

8.9.2.2 MarkovPasswords() [2/2]

`Markov::API::MarkovPasswords::MarkovPasswords (`
 `const char * filename)`

Initialize the markov model from `MarkovModel::Markov::Model`, with an import file.

This function calls the [Markov::Model::Import](#) on the filename to construct the model. Same thing as creating and empty model, and calling [MarkovPasswords::Import](#) on the filename.

Parameters

<i>filename</i>	- Filename to import
-----------------	----------------------

Example Use: Construction via filename


```
MarkovPasswords mp("test.mdl");
```

Definition at line 31 of file [markovPasswords.cpp](#).

```
00031                                     {
00032
00033     std::ifstream* importFile;
00034
00035     this->Import(filename);
00036
00037     //std::ifstream* newFile(filename);
00038
00039     //importFile = newFile;
00040
00041 }
```

References [Markov::Model< NodeStorageType >::Import\(\)](#).

Here is the call graph for this function:



8.9.3 Member Function Documentation

8.9.3.1 AdjustEdge()

```
void Markov::Model< char >::AdjustEdge (
    const char * payload,
    long int occurrence ) [inherited]
```

Adjust the model with a single string.

Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from current node to the next, until NULL character is reached.

Then, update the edge EdgeWeight from current node, to the terminator node.

This function is used for training purposes, as it can be used for adjusting the model with each line of the corpus file.

Example Use: Create an empty model and train it with string: "testdata"

```
Markov::Model<char> model;
char test[] = "testdata";
model.AdjustEdge(test, 15);
```

Parameters

<i>string</i>	- String that is passed from the training, and will be used to AdjustEdge the model with
<i>occurrence</i>	- Occurrence of this string.

Definition at line 323 of file [model.h](#).

```
00323
00324     NodeStorageType p = payload[0];
00325     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00326     Markov::Edge<NodeStorageType>* e;
00327     int i = 0;
00328
00329     if (p == 0) return;
00330     while (p != 0) {
00331         e = curnode->FindEdge(p);
00332         if (e == NULL) return;
00333         e->AdjustEdge(occurrence);
00334         curnode = e->RightNode();
00335         p = payload[++i];
00336     }
00337
00338     e = curnode->FindEdge('\xff');
00339     e->AdjustEdge(occurrence);
00340     return;
00341 }
```

8.9.3.2 Edges()

```
std::vector<Edge<char >*> Markov::Model< char >::Edges [inline], [inherited]
```

Return a vector of all the edges in the model.

Returns

vector of edges

Definition at line 172 of file [model.h](#).

```
00172 { return &edges; }
```

8.9.3.3 Export() [1/2]

```
bool Markov::Model< char >::Export (
    const char * filename ) [inherited]
```

Open a file to export with filename, and call bool [Model::Export](#) with std::ofstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Export file to filename

```
Markov::Model<char> model;
model.Export("test.mdl");
```

Definition at line 286 of file [model.h](#).

```
00286                                     {
00287     std::ofstream exportfile;
00288     exportfile.open(filename);
00289     return this->Export(&exportfile);
00290 }
```

8.9.3.4 Export() [2/2]

```
bool Markov::Model< char >::Export (
    std::ofstream * f ) [inherited]
```

Export a file of the model.

File contains a list of edges. Format is: Left_repr;EdgeWeight;right_repr. For more information on the format, check out the project wiki or github readme.

Iterate over this vertices, and their edges, and write them to file.

Returns

True if successful, False for incomplete models.

Example Use: Export file to ofstream

```
Markov::Model<char> model;
std::ofstream file("test.mdl");
model.Export(&file);
```

Definition at line 274 of file [model.h](#).

```
00274                                     {
00275     Markov::Edge<NodeStorageType>* e;
00276     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00277         e = this->edges[i];
00278         //std::cout << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," <<
00279         e->RightNode()->NodeValue() << "\n";
00279         *f << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," << e->RightNode()->NodeValue() <<
00280         "\n";
00280     }
00281     return true;
00282 }
00283 }
```

8.9.3.5 Generate()

```
void Markov::API::MarkovPasswords::Generate (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20 )
```

Call [Markov::Model::RandomWalk](#) n times, and collect output.

Generate from model and write results to a file. a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Deprecated See [Markov::API::MatrixModel::FastRandomWalk](#) for more information.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn

Definition at line 110 of file [markovPasswords.cpp](#).

```
00110                                     {
00111     char* res;
```

```


00112     char print[100];
00113     std::ofstream wordlist;
00114     wordlist.open(wordlistFileName);
00115     std::mutex mlock;
00116     int iterationsPerThread = n/threads;
00117     int iterationsCarryOver = n%threads;
00118     std::vector<std::thread*> threadsV;
00119     for(int i=0;i<threads;i++){
00120         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::GenerateThread, this,
&mlock, iterationsPerThread, &wordlist, minLen, maxLen));
00121     }
00122
00123     for(int i=0;i<threads;i++){
00124         threadsV[i]->join();
00125         delete threadsV[i];
00126     }
00127
00128     this->GenerateThread(&mlock, iterationsCarryOver, &wordlist, minLen, maxLen);
00129
00130 }

```


References [GenerateThread\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.9.3.6 GenerateThread()

```

void Markov::API::MarkovPasswords::GenerateThread (
    std::mutex * outputLock,
    unsigned long int n,
    std::ofstream * wordlist,
    int minLen,
    int maxLen ) [private]

```

A single thread invoked by the Generate function.

DEPRECATED: See [Markov::API::MatrixModel::FastRandomWalkThread](#) for more information. This has been replaced with a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Parameters

<i>outputLock</i>	- shared mutex lock to lock during output operation. Prevents race condition on write.
<i>n</i>	number of lines to be generated by this thread
<i>wordlist</i>	wordlistfile
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate

Definition at line 132 of file `markovPasswords.cpp`.

```


00132
00133     char* res = new char[maxLen+5];
00134     if (n==0) return;
00135
00136     Markov::Random::Marsaglia MarsagliaRandomEngine;
00137     for (int i = 0; i < n; i++) {
00138         this->RandomWalk(&MarsagliaRandomEngine, minLen, maxLen, res);
00139         outputLock->lock();
00140         *wordlist « res « "\n";
00141         outputLock->unlock();
00142     }
00143 }

```


References `Markov::Model< NodeStorageType >::RandomWalk()`.

Referenced by `Generate()`.

Here is the call graph for this function:



Here is the caller graph for this function:



8.9.3.7 Import() [1/2]

```

bool Markov::Model< char >::Import (
    const char * filename ) [inherited]

```

Open a file to import with filename, and call bool `Model::Import` with `std::ifstream`.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file with filename

```

Markov::Model<char> model;
model.Import("test.mdl");

```

Definition at line 266 of file `model.h`.

```

00266
00267     std::ifstream importfile;
00268     importfile.open(filename);
00269     return this->Import(&importfile);
00270
00271 }

```

8.9.3.8 Import() [2/2]

```

bool Markov::Model< char >::Import (
    std::ifstream * f ) [inherited]

```

Import a file to construct the model.

File contains a list of edges. For more info on the file format, check out the wiki and github readme pages. Format is: `Left_repr;EdgeWeight;right_repr`

Iterate over this list, and construct nodes and edges accordingly.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file from ifstream

```
Markov::Model<char> model;
std::ifstream file("test.mdl");
model.Import(&file);
```

Definition at line 207 of file [model.h](#).

```
00207     {
00208         std::string cell;
00209
00210         char src;
00211         char target;
00212         long int oc;
00213
00214         while (std::getline(*f, cell)) {
00215             //std::cout << "cell: " << cell << std::endl;
00216             src = cell[0];
00217             target = cell[cell.length() - 1];
00218             char* j;
00219             oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(), &j, 10);
00220             //std::cout << oc << "\n";
00221             Markov::Node<NodeStorageType>* srcN;
00222             Markov::Node<NodeStorageType>* targetN;
00223             Markov::Edge<NodeStorageType>* e;
00224             if (this->nodes.find(src) == this->nodes.end()) {
00225                 srcN = new Markov::Node<NodeStorageType>(src);
00226                 this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(src, srcN));
00227                 //std::cout << "Creating new node at start.\n";
00228             }
00229             else {
00230                 srcN = this->nodes.find(src)->second;
00231             }
00232
00233             if (this->nodes.find(target) == this->nodes.end()) {
00234                 targetN = new Markov::Node<NodeStorageType>(target);
00235                 this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(target, targetN));
00236                 //std::cout << "Creating new node at end.\n";
00237             }
00238             else {
00239                 targetN = this->nodes.find(target)->second;
00240             }
00241             e = srcN->Link(targetN);
00242             e->AdjustEdge(oc);
00243             this->edges.push_back(e);
00244
00245             //std::cout << int(srcN->NodeValue()) << " --" << e->EdgeWeight() << "--> " <<
00246             int(targetN->NodeValue()) << "\n";
00247
00248         }
00249
00250         for (std::pair<unsigned char, Markov::Node<NodeStorageType>*> const& x : this->nodes) {
00251             //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
00252             std::sort (x.second->edgesV.begin(), x.second->edgesV.end(), [] (Edge<NodeStorageType> *lhs,
00253             Edge<NodeStorageType> *rhs)->bool{
00254                 return lhs->EdgeWeight() > rhs->EdgeWeight();
00255             });
00256             //for(int i=0;i<x.second->edgesV.size();i++)
00257             // std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00258             //std::cout << "\n";
00259         }
00260         //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00261         //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00262         return true;
00263     }
```

8.9.3.9 Nodes()

```
std::map<char , Node<char >*>* Markov::Model< char >::Nodes [inline], [inherited]
```

Return starter [Node](#).

Returns

starter node with 00 NodeValue

Definition at line 177 of file [model.h](#).

```
00177 { return &nodes; }
```


8.9.3.10 OpenDatasetFile()

```
std::ifstream * Markov::API::MarkovPasswords::OpenDatasetFile (
    const char * filename )
```

Open dataset file and return the ifstream pointer.

Parameters

<i>filename</i>	- Filename to open
-----------------	--------------------

Returns


ifstream* to the the dataset file

Definition at line 43 of file [markovPasswords.cpp](#).

```
00043
00044
00045     std::ifstream* datasetFile;
00046
00047     std::ifstream newFile(filename);
00048
00049     datasetFile = &newFile;
00050
00051     this->Import(datasetFile);
00052     return datasetFile;
00053 }
```

References [Markov::Model< NodeStorageType >::Import\(\)](#).

Here is the call graph for this function:



8.9.3.11 RandomWalk()

```
char * Markov::Model< char >::RandomWalk (
    Markov::Random::RandomEngine * randomEngine,
    int minSetting,
    int maxSetting,
    char * buffer ) [inherited]
```

Do a random walk on this model.

Start from the starter node, on each node, invoke RandomNext using the random engine on current node, until terminator node is reached. If terminator node is reached before minimum length criateria is reached, ignore the last selection and re-invoke randomNext

If maximum length criteria is reached but final node is not, cut off the generation and proceed to the final node. This function takes [Markov::Random::RandomEngine](#) as a parameter to generate pseudo random numbers from

This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne output is higher in entropy, most use cases don't really need super high entropy output, so [Markov::Random::Marsaglia](#) is preferable for better performance.

This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening via maximum length criteria.

Example Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use Marsaglia

```
Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
```

```

    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}

```

Parameters

<i>randomEngine</i>	Random Engine to use for the random walks. For examples, see Markov::Random::Mersenne and Markov::Random::Marsaglia
<i>minSetting</i>	Minimum number of characters to generate
<i>maxSetting</i>	Maximum number of character to generate
<i>buffer</i>	buffer to write the result to

Returns

Null terminated string that was generated.

Definition at line 293 of file [model.h](#).

```

00293
00294     Markov::Node<NodeStorageType>* n = this->starterNode;
00295     int len = 0;
00296     Markov::Node<NodeStorageType>* temp_node;
00297     while (true) {
00298         temp_node = n->RandomNext(randomEngine);
00299         if (len >= maxSetting) {
00300             break;
00301         }
00302         else if ((temp_node == NULL) && (len < minSetting)) {
00303             continue;
00304         }
00305         else if (temp_node == NULL) {
00306             break;
00307         }
00308     }
00309     n = temp_node;
00310     buffer[len++] = n->NodeValue();
00311 }
00312
00313 //null terminate the string
00314 buffer[len] = 0x00;
00315
00316 //do something with the generated string
00317 return buffer; //for now
00318
00319 }
00320

```

8.9.3.12 Save()

```

std::ofstream * Markov::API::MarkovPasswords::Save (
    const char * filename )

```

Export model to file.

Parameters

<i>filename</i>	- Export filename.
-----------------	--------------------

Returns

std::ofstream* of the exported file.

Definition at line 98 of file [markovPasswords.cpp](#).

```


00098
00099     std::ofstream* exportFile;
00100
00101     std::ofstream newFile(filename);
00102
00103     exportFile = &newFile;
00104
00105     this->Export(exportFile);

```

```
00106     return exportFile;
00107 }
```

References [Markov::Model< NodeStorageType >::Export\(\)](#).

Here is the call graph for this function:



8.9.3.13 StarterNode()

[Node](#)<char >* [Markov::Model](#)< char >::StarterNode [inline], [inherited]

Return starter [Node](#).

Returns

starter node with 00 NodeValue

Definition at line 167 of file [model.h](#).

```
00167 { return starterNode; }
```

8.9.3.14 Train()

```
void Markov::API::MarkovPasswords::Train (
    const char * datasetFileName,
    char delimiter,
    int threads )
```

Train the model with the dataset file.

Parameters

<i>datasetFileName</i>	- ifstream* to the dataset. If null, use class member
<i>delimiter</i>	- a character, same as the delimiter in dataset content
<i>threads</i>	- number of OS threads to spawn

```
Markov::API::MarkovPasswords mp;
```

```
mp.Import ("models/2gram.mdl");
```

```
mp.Train("password.corpus");
```

Definition at line 57 of file [markovPasswords.cpp](#).


```
00057                                     {
00058     signal(SIGINT, intHandler);
00059     Markov::API::Concurrency::ThreadSharedListHandler listhandler(datasetFileName);
00060     auto start = std::chrono::high_resolution_clock::now();
00061
00062     std::vector<std::thread*> threadsV;
00063     for(int i=0;i<threads;i++){
00064         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::TrainThread, this,
00065         &listhandler, delimiter));
00066     }
00067     for(int i=0;i<threads;i++){
00068         threadsV[i]->join();
00069         delete threadsV[i];
00070     }
00071     auto finish = std::chrono::high_resolution_clock::now();
00072     std::chrono::duration<double> elapsed = finish - start;
00073     std::cout << "Elapsed time: " << elapsed.count() << " s\n";
00074
00075 }
```

References [intHandler\(\)](#), [Markov::API::Concurrency::ThreadSharedListHandler::ThreadSharedListHandler\(\)](#), and


[TrainThread\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [Markov::API::ModelMatrix::Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.9.3.15 TrainThread()

```
void Markov::API::MarkovPasswords::TrainThread (
    Markov::API::Concurrency::ThreadSharedListHandler * listhandler,
    char delimiter ) [private]
```

A single thread invoked by the Train function.

Parameters

<i>listhandler</i>	- Listhandler class to read corpus from
<i>delimiter</i>	- a character, same as the delimiter in dataset content


Definition at line 77 of file [markovPasswords.cpp](#).

```
00077
{
00078     char format_str[] = "%ld,%s";
00079     format_str[3]=delimiter;
00080     std::string line;
00081     while (listhandler->next(&line) && keepRunning) {
00082         long int oc;
00083         if (line.size() > 100) {
00084             line = line.substr(0, 100);
00085         }
00086         char* linebuf = new char[line.length()+5];
00087 #ifdef _WIN32
00088         sscanf_s(line.c_str(), "%ld,%s", &oc, linebuf, line.length()+5); //<== changed format_str to->
00089         "%ld,%s"
00089 #else
00090         sscanf(line.c_str(), format_str, &oc, linebuf);
00091 #endif
00092         this->AdjustEdge((const char*)linebuf, oc);
00093         delete linebuf;
00094     }
00095 }
```


References [Markov::Model< NodeStorageType >::AdjustEdge\(\)](#), [keepRunning](#), and [Markov::API::Concurrency::ThreadSharedListHa](#)

Referenced by [Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.9.4 Member Data Documentation

8.9.4.1 datasetFile

`std::ifstream* Markov::API::MarkovPasswords::datasetFile [private]`

Definition at line 106 of file [markovPasswords.h](#).

8.9.4.2 edges

`std::vector<Edge<char >*> Markov::Model< char >::edges [private], [inherited]`

A list of all edges in this model.

Definition at line 195 of file [model.h](#).

8.9.4.3 modelSavefile

`std::ofstream* Markov::API::MarkovPasswords::modelSavefile [private]`

Dataset file input of our system

Definition at line 107 of file [markovPasswords.h](#).

8.9.4.4 nodes

`std::map<char , Node<char >*> Markov::Model< char >::nodes [private], [inherited]`

Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.

Definition at line 184 of file [model.h](#).

8.9.4.5 outputFile

`std::ofstream* Markov::API::MarkovPasswords::outputFile [private]`

File to save model of our system

Definition at line 108 of file [markovPasswords.h](#).

8.9.4.6 starterNode

`Node<char > * Markov::Model< char >::starterNode [private], [inherited]`

Starter [Node](#) of this model.

Definition at line 189 of file [model.h](#).

The documentation for this class was generated from the following files:


- [markovPasswords.h](#)
- [markovPasswords.cpp](#)

8.10 Markov::GUI::MarkovPasswordsGUI Class Reference


Reporting UI.

```
#include <MarkovPasswordsGUI.h>
```

Inheritance diagram for Markov::GUI::MarkovPasswordsGUI:



Collaboration diagram for Markov::GUI::MarkovPasswordsGUI:



Public Slots

- void [MarkovPasswordsGUI::benchmarkSelected](#) ()
- void [MarkovPasswordsGUI::modelvisSelected](#) ()
- void [MarkovPasswordsGUI::visualDebugSelected](#) ()
- void [MarkovPasswordsGUI::comparisonSelected](#) ()
- void [MarkovPasswordsGUI::home](#) ()
- void [MarkovPasswordsGUI::pass](#) ()
- void [MarkovPasswordsGUI::model](#) ()

Private Attributes

- `Ui::MarkovPasswordsGUIClass` [ui](#)

8.10.1 Detailed Description

Reporting UI.

UI for reporting and debugging tools for MarkovPassword

Definition at line 13 of file [MarkovPasswordsGUI.h](#).

8.10.2 Member Function Documentation

8.10.2.1 MarkovPasswordsGUI::pass

```
void Markov::GUI::MarkovPasswordsGUI::MarkovPasswordsGUI::pass ( ) [slot]
```

8.10.2.2 MarkovPasswordsGUI::benchmarkSelected

```
void Markov::GUI::MarkovPasswordsGUI::MarkovPasswordsGUI::benchmarkSelected ( ) [slot]
```

8.10.2.3 MarkovPasswordsGUI::comparisonSelected

```
void Markov::GUI::MarkovPasswordsGUI::MarkovPasswordsGUI::comparisonSelected ( ) [slot]
```

8.10.2.4 MarkovPasswordsGUI::home

```
void Markov::GUI::MarkovPasswordsGUI::MarkovPasswordsGUI::home ( ) [slot]
```

8.10.2.5 MarkovPasswordsGUI::model

```
void Markov::GUI::MarkovPasswordsGUI::MarkovPasswordsGUI::model ( ) [slot]
```

8.10.2.6 MarkovPasswordsGUI::modelvisSelected

```
void Markov::GUI::MarkovPasswordsGUI::MarkovPasswordsGUI::modelvisSelected ( ) [slot]
```

8.10.2.7 MarkovPasswordsGUI::visualDebugSelected

```
void Markov::GUI::MarkovPasswordsGUI::MarkovPasswordsGUI::visualDebugSelected ( ) [slot]
```

8.10.3 Member Data Documentation

8.10.3.1 ui

```
Ui::MarkovPasswordsGUIClass Markov::GUI::MarkovPasswordsGUI::ui [private]
```

Definition at line 17 of file [MarkovPasswordsGUI.h](#).

The documentation for this class was generated from the following file:


- [MarkovPasswordsGUI.h](#)

8.11 Markov::API::CUDA::Random::Marsaglia Class Reference


Extension of [Markov::Random::Marsaglia](#) which is capable o working on **device** space.

```
#include <cularandom.h>
```


Inheritance diagram for Markov::API::CUDA::Random::Marsaglia:



Collaboration diagram for Markov::API::CUDA::Random::Marsaglia:



Public Member Functions

- unsigned long [random](#) ()
Generate [Random](#) Number.

Static Public Member Functions

- static unsigned long * [MigrateToVRAM](#) (Markov::API::CUDA::Random::Marsaglia *MEarr, long int gridSize)
Migrate a [Marsaglia](#) to VRAM as seedChunk.
- static __host__ void [ListCudaDevices](#) ()
List [CUDA](#) devices in the system.

Public Attributes

- unsigned long [x](#)
- unsigned long [y](#)
- unsigned long [z](#)

Protected Member Functions

- `std::random_device & rd ()`
Default random device for seeding.
- `std::default_random_engine & generator ()`
Default random engine for seeding.
- `std::uniform_int_distribution< long long unsigned > & distribution ()`
Distribution schema for seeding.

Static Protected Member Functions

- `static __host__ int CudaCheckNotifyErr (cudaError_t _status, const char *msg, bool bExit=true)`
Check results of the last operation on GPU.
- `template<typename T >`
`static __host__ cudaError_t CudaMalloc2DToFlat (T **dst, int row, int col)`
Malloc a 2D array in device space.
- `template<typename T >`
`static __host__ cudaError_t CudaMemcpy2DToFlat (T *dst, T **src, int row, int col)`
Mempcy a 2D array in device space after flattening.
- `template<typename T >`
`static __host__ cudaError_t CudaMigrate2DFlat (T **dst, T **src, int row, int col)`
Both malloc and memcpy a 2D array into device VRAM.

8.11.1 Detailed Description

Extension of [Markov::Random::Marsaglia](#) which is capable o working on **device** space.
Definition at line 11 of file [cudarandom.h](#).

8.11.2 Member Function Documentation

8.11.2.1 CudaCheckNotifyErr()

```
static __host__ int Markov::API::CUDA::CUDADeviceController::CudaCheckNotifyErr (
    cudaError_t _status,
    const char * msg,
    bool bExit = true ) [static], [protected], [inherited]
```

Check results of the last operation on GPU.

Check the status returned from `cudaMalloc/cudaMemcpy` to find failures.

If a failure occurs, its assumed beyond redemption, and exited.

Parameters

<code>_status</code>	Cuda error status to check
<code>msg</code>	Message to print in case of a failure

Returns

0 if successful, 1 if failure. **Example output:**

```
char *da, a = "test";
cudastatus = cudaMalloc((char **)&da, 5*sizeof(char));
CudaCheckNotifyErr(cudastatus, "Failed to allocate VRAM for *da.\n");
```

8.11.2.2 CudaMalloc2DToFlat()

```
template<typename T >
```

```
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat (
    T ** dst,
    int row,
    int col ) [inline], [static], [protected], [inherited]
```

Malloc a 2D array in device space.

This function will allocate enough space on VRAM for flattened 2D array.

Parameters

<i>dst</i>	destination pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:


```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
if (cudastatus!=cudaSuccess){
    CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
}
```

Definition at line 73 of file [cudaDeviceController.h](#).

```
00073
00074         cudaError_t cudastatus = cudaMalloc((T **)dst, row*col*sizeof(T));
00075         CudaCheckNotifyErr(cudastatus, "cudaMalloc Failed.", false);
00076         return cudastatus;
00077     }
```

References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



8.11.2.3 CudaMemcpy2DToFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat (
    T * dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected], [inherited]
```

Memcpy a 2D array in device space after flattening.

Resulting buffer will not be true 2D array.

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer

Parameters

<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:


```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
cudastatus = CudaMemcpy2DToFlat<char>(*dst, src, 15, 15);
CudaCheckNotifyErr(cudastatus, " CudaMemcpy2DToFlat Failed.", false);
```

Definition at line 101 of file [cudaDeviceController.h](#).

```
00101                                     {
00102         T* tempbuf = new T[row*col];
00103         for(int i=0;i<row;i++){
00104             memcpy(&(tempbuf[row*i]), src[i], col);
00105         }
00106         return cudaMemcpy(dst, tempbuf, row*col*sizeof(T), cudaMemcpyHostToDevice);
00107     }
00108 }
```

References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



8.11.2.4 CudaMigrate2DFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat (
    T ** dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected], [inherited]
```

Both malloc and memcpy a 2D array into device VRAM.

Resulting buffer will not be true 2D array.

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:

```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMigrate2DFlat<long int>(
    &dst, this->valueMatrix, this->matrixSize, this->matrixSize);
CudaCheckNotifyErr(cudastatus, "    Cuda failed to initialize value matrix row.");
```


Definition at line 130 of file [cudaDeviceController.h](#).

```
00130                                     {
00131         cudaError_t cudastatus;
00132         cudastatus = CudaMalloc2DToFlat<T>(dst, row, col);
00133         if(cudastatus!=cudaSuccess){
00134             CudaCheckNotifyErr(cudastatus, "    CudaMalloc2DToFlat Failed.", false);
00135             return cudastatus;
00136         }
00137         cudastatus = CudaMemcpy2DToFlat<T>(*dst,src,row,col);
00138         CudaCheckNotifyErr(cudastatus, "    CudaMemcpy2DToFlat Failed.", false);
00139         return cudastatus;
00140     }
```


References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Referenced by [Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat\(\)](#), [Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat\(\)](#) and [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:

**8.11.2.5 distribution()**

```
std::uniform_int_distribution<long long unsigned>& Markov::Random::DefaultRandomEngine::distribution
( ) [inline], [protected], [inherited]
```


Distribution schema for seeding.

Definition at line 81 of file [random.h](#).

```
00081                                     {
00082         static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00083         return _distribution;
00084     }
```

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the caller graph for this function:



8.11.2.6 generator()

```
std::default_random_engine& Markov::Random::DefaultRandomEngine::generator ( ) [inline],
[protected], [inherited]
```

Default random engine for seeding.


Definition at line 73 of file [random.h](#).

```
00073                                     {
00074         static std::default_random_engine _generator(rd() ());
00075         return _generator;
00076     }
```


References [Markov::Random::DefaultRandomEngine::rd\(\)](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.11.2.7 ListCudaDevices()

```
static __host__ void Markov::API::CUDA::CUDADeviceController::ListCudaDevices ( ) [static],
```

[inherited]

List [CUDA](#) devices in the system.

This function will print details of every [CUDA](#) capable device in the system.

Example output:

```
Device Number: 0
Device name: GeForce RTX 2070
Memory Clock Rate (KHz): 7001000
Memory Bus Width (bits): 256
Peak Memory Bandwidth (GB/s): 448.064
Max Linear Threads: 1024
```

8.11.2.8 MigrateToVRAM()

```
static unsigned long* Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM (
    Markov::API::CUDA::Random::Marsaglia * MEarr,
    long int gridSize ) [inline], [static]
```

Migrate a [Marsaglia](#)[] to VRAM as seedChunk.

Parameters

<i>MEarr</i>	Array of Marsaglia Engines
<i>gridSize</i>	GridSize of the CUDA Kernel, aka size of array

Returns

pointer to the resulting seed chunk in device VRAM.

Definition at line 19 of file [cudarandom.h](#).

```
00019                                     {
00020         cudaError_t cudastatus;
00021         unsigned long* seedChunk;
00022         cudastatus = cudaMalloc((unsigned long**)&seedChunk, gridSize*3*sizeof(unsigned long));
00023         CudaCheckNotifyErr(cudastatus, "Failed to allocate seed buffer");
00024         unsigned long *temp = new unsigned long[gridSize*3];
00025         for(int i=0;i<gridSize;i++){
00026             temp[i*3] = MEarr[i].x;
00027             temp[i*3+1] = MEarr[i].y;
00028             temp[i*3+2] = MEarr[i].z;
00029         }
00030         //for(int i=0;i<gridSize*3;i++) std::cout << temp[i] << "\n";
00031         cudaMemcpy(seedChunk, temp, gridSize*3*sizeof(unsigned long), cudaMemcpyHostToDevice);
00032         CudaCheckNotifyErr(cudastatus, "Failed to memcpy seed buffer.");
00033         return seedChunk;
00034     }
```

References [Markov::Random::Marsaglia::x](#), [Markov::Random::Marsaglia::y](#), and [Markov::Random::Marsaglia::z](#).

8.11.2.9 random()

```
unsigned long Markov::Random::Marsaglia::random ( ) [inline], [virtual], [inherited]
```

Generate [Random](#) Number.

Returns

random number in long range.

Reimplemented from [Markov::Random::DefaultRandomEngine](#).

Definition at line 131 of file [random.h](#).

```
00131                                     {
00132         unsigned long t;
00133         x ^= x << 16;
00134         x ^= x >> 5;
00135         x ^= x << 1;
00136
00137         t = x;
00138         x = y;
00139         y = z;
00140         z = t ^ x ^ y;
00141
00142         return z;
00143     }
```




```
00143     }
```

References [Markov::Random::Marsaglia::x](#), [Markov::Random::Marsaglia::y](#), and [Markov::Random::Marsaglia::z](#).

Referenced by [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

Here is the caller graph for this function:



8.11.2.10 rd()

```
std::random_device& Markov::Random::DefaultRandomEngine::rd ( ) [inline], [protected], [inherited]
```

Default random device for seeding.


Definition at line 65 of file [random.h](#).

```

00065     {
00066         static std::random_device _rd;
00067         return _rd;
00068     }
```

Referenced by [Markov::Random::DefaultRandomEngine::generator\(\)](#).

Here is the caller graph for this function:



8.11.3 Member Data Documentation

8.11.3.1 x

```
unsigned long Markov::Random::Marsaglia::x [inherited]
```

Definition at line 146 of file [random.h](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), [MigrateToVRAM\(\)](#), and [Markov::Random::Marsaglia::random\(\)](#).

8.11.3.2 y

```
unsigned long Markov::Random::Marsaglia::y [inherited]
```

Definition at line 147 of file [random.h](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), [MigrateToVRAM\(\)](#), and [Markov::Random::Marsaglia::random\(\)](#).

8.11.3.3 z

```
unsigned long Markov::Random::Marsaglia::z [inherited]
```

Definition at line 148 of file [random.h](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), [MigrateToVRAM\(\)](#), and [Markov::Random::Marsaglia::random\(\)](#).

The documentation for this class was generated from the following file:


- [cudarandom.h](#)

8.12 Markov::Random::Marsaglia Class Reference


Implementation of [Marsaglia Random](#) Engine.

```
#include <random.h>
```

Inheritance diagram for Markov::Random::Marsaglia:



Collaboration diagram for Markov::Random::Marsaglia:



Public Member Functions

- [Marsaglia](#) ()
Construct [Marsaglia](#) Engine.
- unsigned long [random](#) ()
Generate [Random](#) Number.

Public Attributes

- unsigned long [x](#)
- unsigned long [y](#)
- unsigned long [z](#)

Protected Member Functions

- `std::random_device & rd ()`
Default random device for seeding.

- `std::default_random_engine & generator ()`
Default random engine for seeding.
- `std::uniform_int_distribution< long long unsigned > & distribution ()`
Distribution schema for seeding.

8.12.1 Detailed Description

Implementation of [Marsaglia Random](#) Engine.

This is an implementation of [Marsaglia Random](#) engine, which for most use cases is a better fit than other solutions. Very simple mathematical formula to generate pseudorandom integer, so its crazy fast.

This implementation of the [Marsaglia](#) Engine is seeded by [random.h](#) default random engine. [RandomEngine](#) is only seeded once so its not a performance issue.

Example Use: Using [Marsaglia](#) Engine with RandomWalk

```
Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}
```

Example Use: Generating a random number with [Marsaglia](#) Engine

```
Markov::Random::Marsaglia me;
std::cout << me.random();
```

Definition at line 116 of file [random.h](#).

8.12.2 Constructor & Destructor Documentation

8.12.2.1 Marsaglia()

Markov::Random::Marsaglia::Marsaglia () [inline]

Construct [Marsaglia](#) Engine.


Initialize x,y and z using the default random engine.

Definition at line 123 of file [random.h](#).

```
00123     {
00124         this->x = this->distribution() (this->generator());
00125         this->y = this->distribution() (this->generator());
00126         this->z = this->distribution() (this->generator());
00127         //std::cout << "x: " << x << ", y: " << y << ", z: " << z << "\n";
00128     }
```

References [Markov::Random::DefaultRandomEngine::distribution\(\)](#), [Markov::Random::DefaultRandomEngine::generator\(\)](#), [x](#), [y](#), and [z](#).

Here is the call graph for this function:



8.12.3 Member Function Documentation

8.12.3.1 distribution()

`std::uniform_int_distribution<long long unsigned>& Markov::Random::DefaultRandomEngine::distribution () [inline], [protected], [inherited]`


Distribution schema for seeding.

Definition at line 81 of file [random.h](#).

```
00081                                     {
00082         static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00083         return _distribution;
00084     }
```

Referenced by [Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the caller graph for this function:



8.12.3.2 generator()

```
std::default_random_engine& Markov::Random::DefaultRandomEngine::generator ( ) [inline],
[protected], [inherited]
```

Default random engine for seeding.

Definition at line 73 of file [random.h](#).

```
00073                                     {
00074         static std::default_random_engine _generator(rd() ());
00075         return _generator;
00076     }
```


References [Markov::Random::DefaultRandomEngine::rd\(\)](#).

Referenced by [Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.12.3.3 random()

```
unsigned long Markov::Random::Marsaglia::random ( ) [inline], [virtual]
```

Generate [Random](#) Number.

Returns

random number in long range.

Reimplemented from [Markov::Random::DefaultRandomEngine](#).

Definition at line 131 of file [random.h](#).

```
00131     {
00132         unsigned long t;
00133         x ^= x << 16;
00134         x ^= x >> 5;
00135         x ^= x << 1;
00136
00137         t = x;
00138         x = y;
00139         y = z;
00140         z = t ^ x ^ y;
00141
00142         return z;
00143     }
```

References [x](#), [y](#), and [z](#).

Referenced by [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

Here is the caller graph for this function:



8.12.3.4 rd()

`std::random_device& Markov::Random::DefaultRandomEngine::rd ()` [inline], [protected], [inherited]


Default random device for seeding.

Definition at line 65 of file [random.h](#).

```
00065     {
00066         static std::random_device _rd;
00067         return _rd;
00068     }
```

Referenced by [Markov::Random::DefaultRandomEngine::generator\(\)](#).

Here is the caller graph for this function:



8.12.4 Member Data Documentation

8.12.4.1 x

`unsigned long Markov::Random::Marsaglia::x`

Definition at line 146 of file [random.h](#).

Referenced by [Marsaglia\(\)](#), [Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM\(\)](#), and [random\(\)](#).

8.12.4.2 y

`unsigned long Markov::Random::Marsaglia::y`

Definition at line 147 of file [random.h](#).

Referenced by [Marsaglia\(\)](#), [Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM\(\)](#), and [random\(\)](#).

8.12.4.3 z

```
unsigned long Markov::Random::Marsaglia::z
```

Definition at line 148 of file [random.h](#).

Referenced by [Marsaglia\(\)](#), [Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM\(\)](#), and [random\(\)](#).

The documentation for this class was generated from the following file:


- [random.h](#)

8.13 Markov::GUI::menu Class Reference


QT Menu class.

```
#include <menu.h>
```

Inheritance diagram for Markov::GUI::menu:



Collaboration diagram for Markov::GUI::menu:



Public Slots

- void [about](#) ()
- void [visualization](#) ()

Public Member Functions

- [menu](#) (QWidget *parent=Q_NULLPTR)

Private Attributes

- [Ui::main ui](#)

8.13.1 Detailed Description

QT Menu class.

Definition at line 9 of file [menu.h](#).

8.13.2 Constructor & Destructor Documentation

8.13.2.1 menu()

```

menu::menu (
    QWidget * parent = Q_NULLPTR )
  
```

Definition at line 8 of file [menu.cpp](#).

```

00009      : QMainWindow(parent)
00010  {
00011      ui.setupUi(this);
00012
00013
00014      //QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {about(); });
00015      QObject::connect(ui.visu, &QPushButton::clicked, this, [this] {visualization(); });
00016  }
  
```


8.13.3 Member Function Documentation

8.13.3.1 about

```
void menu::about ( ) [slot]
Definition at line 17 of file menu.cpp.
00017         {
00018
00019
00020 }
```

8.13.3.2 visualization

```
void menu::visualization ( ) [slot]
Definition at line 21 of file menu.cpp.
00021         {
00022     MarkovPasswordsGUI* w = new MarkovPasswordsGUI;
00023     w->show();
00024     this->close();
00025 }
```

8.13.4 Member Data Documentation

8.13.4.1 ui

`Ui::main` Markov::GUI::menu::ui [private]
Definition at line 15 of file menu.h.

The documentation for this class was generated from the following files:


- [menu.h](#)
- [menu.cpp](#)

8.14 Markov::Random::Mersenne Class Reference


Implementation of [Mersenne](#) Twister Engine.

```
#include <random.h>
```

Inheritance diagram for Markov::Random::Mersenne:



Collaboration diagram for Markov::Random::Mersenne:



Public Member Functions

- unsigned long [random](#) ()
Generate [Random](#) Number.

Protected Member Functions

- std::random_device & [rd](#) ()
Default random device for seeding.
- std::default_random_engine & [generator](#) ()
Default random engine for seeding.
- std::uniform_int_distribution< long long unsigned > & [distribution](#) ()
Distribution schema for seeding.

8.14.1 Detailed Description

Implementation of [Mersenne](#) Twister Engine.

This is an implementation of [Mersenne](#) Twister Engine, which is slow but is a good implementation for high entropy pseudorandom.

Example Use: Using [Mersenne](#) Engine with RandomWalk

```

Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Mersenne MersenneTwisterEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MersenneTwisterEngine, 5, 10, res);
    std::cout << res << "\n";
}

```

Example Use: Generating a random number with [Marsaglia Engine](#)

```

Markov::Random::Mersenne me;
std::cout << me.random();

```

Definition at line 176 of file [random.h](#).

8.14.2 Member Function Documentation

8.14.2.1 distribution()

```

std::uniform_int_distribution<long long unsigned>& Markov::Random::DefaultRandomEngine::distribution
( ) [inline], [protected], [inherited]

```

Distribution schema for seeding.

Definition at line 81 of file [random.h](#).


```

00081                                     {
00082         static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00083         return _distribution;
00084     }

```

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the caller graph for this function:



8.14.2.2 generator()

```

std::default_random_engine& Markov::Random::DefaultRandomEngine::generator ( ) [inline],
[protected], [inherited]

```

Default random engine for seeding.

Definition at line 73 of file [random.h](#).

```


00073                                     {
00074         static std::default_random_engine _generator(rd() {});
00075         return _generator;
00076     }

```


References [Markov::Random::DefaultRandomEngine::rd\(\)](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.14.2.3 random()

unsigned long Markov::Random::DefaultRandomEngine::random () [inline], [virtual], [inherited]
Generate [Random](#) Number.

Returns

random number in long range.

Implements [Markov::Random::RandomEngine](#).

Reimplemented in [Markov::Random::Marsaglia](#).


Definition at line 57 of file [random.h](#).

```

00057         {
00058             return this->distribution() (this->generator());
00059         }
  
```

References [Markov::Random::DefaultRandomEngine::distribution\(\)](#), and [Markov::Random::DefaultRandomEngine::generator\(\)](#).

Here is the call graph for this function:



8.14.2.4 rd()

std::random_device& Markov::Random::DefaultRandomEngine::rd () [inline], [protected], [inherited]
Default random device for seeding.


Definition at line 65 of file [random.h](#).

```

00065         {
00066             static std::random_device _rd;
00067             return _rd;
00068         }
  
```

Referenced by [Markov::Random::DefaultRandomEngine::generator\(\)](#).

Here is the caller graph for this function:



The documentation for this class was generated from the following file:


- [random.h](#)

8.15 Markov::Model< NodeStorageType > Class Template Reference

class for the final [Markov Model](#), constructed from nodes and edges.

```
#include <model.h>
```

Inheritance diagram for Markov::Model< NodeStorageType >:



- Import a file to construct the model.*
- bool [Import](#) (const char *filename)
Open a file to import with filename, and call bool [Model::Import](#) with std::ifstream.
- bool [Export](#) (std::ofstream *)
Export a file of the model.
- bool [Export](#) (const char *filename)
Open a file to export with filename, and call bool [Model::Export](#) with std::ofstream.
- [Node](#)< NodeStorageType > * [StarterNode](#) ()
Return starter [Node](#).
- std::vector< [Edge](#)< NodeStorageType > * > * [Edges](#) ()
Return a vector of all the edges in the model.
- std::map< NodeStorageType, [Node](#)< NodeStorageType > * > * [Nodes](#) ()
Return starter [Node](#).

Private Attributes

- std::map< NodeStorageType, [Node](#)< NodeStorageType > * > [nodes](#)
Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
- [Node](#)< NodeStorageType > * [starterNode](#)
Starter [Node](#) of this model.
- std::vector< [Edge](#)< NodeStorageType > * > [edges](#)
A list of all edges in this model.

8.15.1 Detailed Description

```
template<typename NodeStorageType>
class Markov::Model< NodeStorageType >
```

class for the final [Markov Model](#), constructed from nodes and edges.

Each atomic piece of the generation result is stored in a node, while edges contain the relation weights. *Extending:* To extend the class, implement the template and inherit from it, as "class MyModel : public Markov::Model<char>". For a complete demonstration of how to extend the class, see [MarkovPasswords](#).

Whole model can be defined as a list of the edges, as dangling nodes are pointless. This approach is used for the import/export operations. For more information on importing/exporting model, check out the [github readme](#) and [wiki page](#).

Definition at line 41 of file [model.h](#).

8.15.2 Constructor & Destructor Documentation

8.15.2.1 Model()

```
template<typename NodeStorageType >
Markov::Model< NodeStorageType >::Model
```

Initialize a model with only start and end nodes.

Initialize an empty model with only a starterNode Starter node is a special kind of node that has constant 0x00 value, and will be used to initiate the generation execution from.

Definition at line 201 of file [model.h](#).

```
00201         {
00202     this->starterNode = new Markov::Node<NodeStorageType>(0);
00203     this->nodes.insert({ 0, this->starterNode });
00204 }
```

8.15.3 Member Function Documentation

8.15.3.1 AdjustEdge()

```
template<typename NodeStorageType >
void Markov::Model< NodeStorageType >::AdjustEdge (
    const NodeStorageType * payload,
    long int occurrence )
```

Adjust the model with a single string.

Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from current node to the next, until NULL character is reached.

Then, update the edge EdgeWeight from current node, to the terminator node.

This function is used for training purposes, as it can be used for adjusting the model with each line of the corpus file.

Example Use: Create an empty model and train it with string: "testdata"

```
Markov::Model<char> model;
char test[] = "testdata";
model.AdjustEdge(test, 15);
```

Parameters

<i>string</i>	- String that is passed from the training, and will be used to AdjustEdge the model with
<i>occurrence</i>	- Occurrence of this string.

Definition at line 323 of file [model.h](#).

```
00323                                     {
00324     NodeStorageType p = payload[0];
00325     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00326     Markov::Edge<NodeStorageType>* e;
00327     int i = 0;
00328
00329     if (p == 0) return;
00330     while (p != 0) {
00331         e = curnode->FindEdge(p);
00332         if (e == NULL) return;
00333         e->AdjustEdge(occurrence);
00334         curnode = e->RightNode();
00335         p = payload[++i];
00336     }
00337
00338     e = curnode->FindEdge('\xff');
00339     e->AdjustEdge(occurrence);
00340     return;
00341 }
```

Referenced by [Markov::API::MarkovPasswords::TrainThread\(\)](#).

Here is the caller graph for this function:



8.15.3.2 Edges()

```
template<typename NodeStorageType >
std::vector<Edge<NodeStorageType>*>* Markov::Model< NodeStorageType >::Edges ( ) [inline]
Return a vector of all the edges in the model.
```

Returns

vector of edges

Definition at line 172 of file [model.h](#).

```
00172 { return &edges; }
```

8.15.3.3 Export() [1/2]

```
template<typename NodeStorageType >
bool Markov::Model< NodeStorageType >::Export (
    const char * filename )
```

Open a file to export with filename, and call bool [Model::Export](#) with `std::ofstream`.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Export file to filename


```
Markov::Model<char> model;
model.Export("test.mdl");
```

Definition at line 286 of file [model.h](#).

```
00286
00287     std::ofstream exportfile;
00288     exportfile.open(filename);
00289     return this->Export(&exportfile);
00290 }
```

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

Here is the caller graph for this function:



8.15.3.4 Export() [2/2]

```
template<typename NodeStorageType >
bool Markov::Model< NodeStorageType >::Export (
    std::ofstream * f )
```

Export a file of the model.

File contains a list of edges. Format is: Left_repr;EdgeWeight;right_repr. For more information on the format, check out the project wiki or github readme.

Iterate over this vertices, and their edges, and write them to file.

Returns

True if successful, False for incomplete models.


Example Use: Export file to ofstream

```
Markov::Model<char> model;
std::ofstream file("test.mdl");
model.Export(&file);
```

Definition at line 274 of file [model.h](#).

```
00274
00275     Markov::Edge<NodeStorageType>* e;
00276     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00277         e = this->edges[i];
00278         //std::cout << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," <<
00279         e->RightNode()->NodeValue() << "\n";
00280         *f << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," << e->RightNode()->NodeValue() <<
00281         "\n";
00282     }
00283     return true;
```

Referenced by [Markov::API::MarkovPasswords::Save\(\)](#).
Here is the caller graph for this function:



8.15.3.5 Import() [1/2]

```

template<typename NodeStorageType >
bool Markov::Model< NodeStorageType >::Import (
    const char * filename )
  
```

Open a file to import with filename, and call bool [Model::Import](#) with std::ifstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file with filename

```

Markov::Model<char> model;
model.Import("test.mdl");
  
```


Definition at line 266 of file [model.h](#).

```

00266                                     {
00267     std::ifstream importfile;
00268     importfile.open(filename);
00269     return this->Import(&importfile);
00270
00271 }
  
```

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), [Markov::API::ModelMatrix::Import\(\)](#), and [Markov::API::MarkovPasswords::MarkovPasswords\(\)](#).

Here is the caller graph for this function:



8.15.3.6 Import() [2/2]

```

template<typename NodeStorageType >
bool Markov::Model< NodeStorageType >::Import (
    std::ifstream * f )
  
```

Import a file to construct the model.

File contains a list of edges. For more info on the file format, check out the wiki and github readme pages. Format is: Left_repr;EdgeWeight;right_repr

Iterate over this list, and construct nodes and edges accordingly.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file from ifstream


```
Markov::Model<char> model;
std::ifstream file("test.mdl");
model.Import(&file);
```

Definition at line 207 of file [model.h](#).

```
00207                                     {
00208     std::string cell;
00209
00210     char src;
00211     char target;
00212     long int oc;
00213
00214     while (std::getline(*f, cell)) {
00215         //std::cout << "cell: " << cell << std::endl;
00216         src = cell[0];
00217         target = cell[cell.length() - 1];
00218         char* j;
00219         oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(), &j, 10);
00220         //std::cout << oc << "\n";
00221         Markov::Node<NodeStorageType>* srcN;
00222         Markov::Node<NodeStorageType>* targetN;
00223         Markov::Edge<NodeStorageType>* e;
00224         if (this->nodes.find(src) == this->nodes.end()) {
00225             srcN = new Markov::Node<NodeStorageType>(src);
00226             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(src, srcN));
00227             //std::cout << "Creating new node at start.\n";
00228         }
00229         else {
00230             srcN = this->nodes.find(src)->second;
00231         }
00232
00233         if (this->nodes.find(target) == this->nodes.end()) {
00234             targetN = new Markov::Node<NodeStorageType>(target);
00235             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(target, targetN));
00236             //std::cout << "Creating new node at end.\n";
00237         }
00238         else {
00239             targetN = this->nodes.find(target)->second;
00240         }
00241         e = srcN->Link(targetN);
00242         e->AdjustEdge(oc);
00243         this->edges.push_back(e);
00244
00245         //std::cout << int(srcN->NodeValue()) << " --" << e->EdgeWeight() << "--> " <<
00246         int(targetN->NodeValue()) << "\n";
00247     }
00248
00249     for (std::pair<unsigned char, Markov::Node<NodeStorageType>*> const& x : this->nodes) {
00250         //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
00251         std::sort(x.second->edgesV.begin(), x.second->edgesV.end(), [](Edge<NodeStorageType> *lhs,
00252             Edge<NodeStorageType> *rhs)->bool{
00253             return lhs->EdgeWeight() > rhs->EdgeWeight();
00254         });
00255         //for(int i=0; i<x.second->edgesV.size(); i++)
00256         //    std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00257         //std::cout << "\n";
00258     }
00259     //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00260     //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00261
00262     return true;
00263 }
```

Referenced by [Markov::API::MarkovPasswords::OpenDatasetFile\(\)](#).

Here is the caller graph for this function:



8.15.3.7 Nodes()

```
template<typename NodeStorageType >
std::map<NodeStorageType, Node<NodeStorageType>*>* Markov::Model< NodeStorageType >::Nodes (
) [inline]
```

Return starter [Node](#).

Returns


starter node with 00 NodeValue

Definition at line 177 of file [model.h](#).

```
00177 { return &nodes; }
```

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:



8.15.3.8 RandomWalk()

```
template<typename NodeStorageType >
NodeStorageType * Markov::Model< NodeStorageType >::RandomWalk (
    Markov::Random::RandomEngine * randomEngine,
    int minSetting,
    int maxSetting,
    NodeStorageType * buffer )
```

Do a random walk on this model.

Start from the starter node, on each node, invoke RandomNext using the random engine on current node, until terminator node is reached. If terminator node is reached before minimum length criateria is reached, ignore the last selection and re-invoke randomNext

If maximum length criteria is reached but final node is not, cut off the generation and proceed to the final node. This function takes [Markov::Random::RandomEngine](#) as a parameter to generate pseudo random numbers from

This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne output is higher in entropy, most use cases don't really need super high entropy output, so [Markov::Random::Marsaglia](#) is preferable for better performance.

This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening via maximum length criteria.

Example Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use Marsaglia

```
Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}
```

Parameters

<i>randomEngine</i>	Random Engine to use for the random walks. For examples, see Markov::Random::Mersenne and Markov::Random::Marsaglia
<i>minSetting</i>	Minimum number of characters to generate
<i>maxSetting</i>	Maximum number of character to generate
<i>buffer</i>	buffer to write the result to

Returns

Null terminated string that was generated.

Definition at line 293 of file [model.h](#).

```

00293
00294     {
00295         Markov::Node<NodeStorageType>* n = this->starterNode;
00296         int len = 0;
00297         Markov::Node<NodeStorageType>* temp_node;
00298         while (true) {
00299             temp_node = n->RandomNext(randomEngine);
00300             if (len >= maxSetting) {
00301                 break;
00302             }
00303             else if ((temp_node == NULL) && (len < minSetting)) {
00304                 continue;
00305             }
00306             else if (temp_node == NULL) {
00307                 break;
00308             }
00309             n = temp_node;
00310             buffer[len++] = n->NodeValue();
00311         }
00312         //null terminate the string
00313         buffer[len] = 0x00;
00314         //do something with the generated string
00315         return buffer; //for now
00316     }
00317
00318
00319
00320

```

Referenced by [Markov::API::MarkovPasswords::GenerateThread\(\)](#).

Here is the caller graph for this function:

**8.15.3.9 StarterNode()**

```

template<typename NodeStorageType >
Node<NodeStorageType>* Markov::Model< NodeStorageType >::StarterNode ( ) [inline]
Return starter Node.

```

Returns


starter node with 00 NodeValue

Definition at line 167 of file [model.h](#).

```
00167 { return starterNode; }
```

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:

**8.15.4 Member Data Documentation**

8.15.4.1 edges

```
template<typename NodeStorageType >
std::vector<Edge<NodeStorageType>*> Markov::Model< NodeStorageType >::edges [private]
```

A list of all edges in this model.

Definition at line 195 of file [model.h](#).

Referenced by [Markov::Model< char >::Edges\(\)](#).

8.15.4.2 nodes

```
template<typename NodeStorageType >
std::map<NodeStorageType, Node<NodeStorageType>*> Markov::Model< NodeStorageType >::nodes
[private]
```

Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.

Definition at line 184 of file [model.h](#).

Referenced by [Markov::Model< char >::Nodes\(\)](#).

8.15.4.3 starterNode

```
template<typename NodeStorageType >
Node<NodeStorageType>* Markov::Model< NodeStorageType >::starterNode [private]
```

Starter [Node](#) of this model.

Definition at line 189 of file [model.h](#).

Referenced by [Markov::Model< char >::StarterNode\(\)](#).

The documentation for this class was generated from the following file:


- [model.h](#)

8.16 Markov::API::ModelMatrix Class Reference


Class to flatten and reduce [Markov::Model](#) to a Matrix.

```
#include <modelMatrix.h>
```

Inheritance diagram for Markov::API::ModelMatrix:



Collaboration diagram for Markov::API::ModelMatrix:



Public Member Functions

- [ModelMatrix](#) ()
- [ConstructMatrix](#) ()
- [DumpJSON](#) ()

Construct the related Matrix data for the model.

Debug function to dump the model to a JSON file.

- void [FastRandomWalk](#) (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20, bool bFileIO=true)
Random walk on the Matrix-reduced [Markov::Model](#).
- void [Import](#) (const char *filename)
Open a file to import with filename, and call bool [Model::Import](#) with std::ifstream.
- void [Train](#) (const char *datasetFileName, char delimiter, int threads)
Train the model with the dataset file.
- std::ifstream * [OpenDatasetFile](#) (const char *filename)
Open dataset file and return the ifstream pointer.
- std::ofstream * [Save](#) (const char *filename)
Export model to file.
- void [Generate](#) (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20)
Call [Markov::Model::RandomWalk](#) n times, and collect output.
- char * [RandomWalk](#) ([Markov::Random::RandomEngine](#) *randomEngine, int minSetting, int maxSetting, char *buffer)
Do a random walk on this model.
- void [AdjustEdge](#) (const char *payload, long int occurrence)
Adjust the model with a single string.
- bool [Import](#) (std::ifstream *)
Import a file to construct the model.
- bool [Export](#) (std::ofstream *)
Export a file of the model.
- bool [Export](#) (const char *filename)
Open a file to export with filename, and call bool [Model::Export](#) with std::ofstream.
- [Node](#)< char > * [StarterNode](#) ()
Return starter Node.
- std::vector< [Edge](#)< char > * > * [Edges](#) ()
Return a vector of all the edges in the model.
- std::map< char, [Node](#)< char > * > * [Nodes](#) ()
Return starter Node.

Protected Member Functions

- void [FastRandomWalkPartition](#) (std::mutex *mlock, std::ofstream *wordlist, unsigned long int n, int minLen, int maxLen, bool bFileIO, int threads)
A single partition of FastRandomWalk event.
- void [FastRandomWalkThread](#) (std::mutex *mlock, std::ofstream *wordlist, unsigned long int n, int minLen, int maxLen, int id, bool bFileIO)
A single thread of a single partition of FastRandomWalk.
- bool [DeallocateMatrix](#) ()
Deallocate matrix and make it ready for re-construction.

Protected Attributes

- char ** [edgeMatrix](#)
2-D Character array for the edge Matrix (The characters of Nodes)
- long int ** [valueMatrix](#)
2-d Integer array for the value Matrix (For the weights of Edges)
- int [matrixSize](#)
to hold Matrix size
- char * [matrixIndex](#)

to hold the Matrix index (To hold the orders of 2-D arrays')

- long int * [totalEdgeWeights](#)

Array of the Total [Edge](#) Weights.

- bool [ready](#)

True when matrix is constructed. False if not.

Private Member Functions

- void [TrainThread](#) ([Markov::API::Concurrency::ThreadSharedListHandler](#) *listhandler, char delimiter)

A single thread invoked by the Train function.

- void [GenerateThread](#) (std::mutex *outputLock, unsigned long int n, std::ofstream *wordlist, int minLen, int maxLen)

A single thread invoked by the Generate function.

Private Attributes

- std::ifstream * [datasetFile](#)

- std::ofstream * [modelSavefile](#)

Dataset file input of our system

- std::ofstream * [outputFile](#)

File to save model of our system

- std::map< char, [Node](#)< char > * > [nodes](#)

Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.

- [Node](#)< char > * [starterNode](#)

Starter Node of this model.

- std::vector< [Edge](#)< char > * > [edges](#)

A list of all edges in this model.

8.16.1 Detailed Description

Class to flatten and reduce [Markov::Model](#) to a Matrix.

Matrix level operations can be used for Generation events, with a significant performance optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)

To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for allocation.

Threads are synchronized and files are flushed every 50M operations.

Definition at line 13 of file [modelMatrix.h](#).

8.16.2 Constructor & Destructor Documentation

8.16.2.1 ModelMatrix()

[Markov::API::ModelMatrix::ModelMatrix](#) ()

Definition at line 6 of file [modelMatrix.cpp](#).

```
00006         {
00007             this->ready = false;
00008         }
```

References [ready](#).

8.16.3 Member Function Documentation

8.16.3.1 AdjustEdge()

```
void Markov::Model< char >::AdjustEdge (
    const NodeStorageType * payload,
    long int occurrence ) [inherited]
```

Adjust the model with a single string.

Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from current node to the next, until NULL character is reached.

Then, update the edge EdgeWeight from current node, to the terminator node.

This function is used for training purposes, as it can be used for adjusting the model with each line of the corpus file.

Example Use: Create an empty model and train it with string: "testdata"

```
Markov::Model<char> model;
char test[] = "testdata";
model.AdjustEdge(test, 15);
```

Parameters

<i>string</i>	- String that is passed from the training, and will be used to AdjustEdge the model with
<i>occurrence</i>	- Occurrence of this string.

Definition at line 323 of file [model.h](#).

```
00323                                     {
00324     NodeStorageType p = payload[0];
00325     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00326     Markov::Edge<NodeStorageType>* e;
00327     int i = 0;
00328
00329     if (p == 0) return;
00330     while (p != 0) {
00331         e = curnode->FindEdge(p);
00332         if (e == NULL) return;
00333         e->AdjustEdge(occurrence);
00334         curnode = e->RightNode();
00335         p = payload[++i];
00336     }
00337
00338     e = curnode->FindEdge('\xff');
00339     e->AdjustEdge(occurrence);
00340     return;
00341 }
```

8.16.3.2 ConstructMatrix()

```
bool Markov::API::ModelMatrix::ConstructMatrix ( )
```

Construct the related Matrix data for the model.

This operation can be used after importing/training to allocate and populate the matrix content.

this will initialize: char** edgeMatrix -> a 2D array of mapping left and right connections of each edge. long int **valueMatrix -> a 2D array representing the edge weights. int matrixSize -> Size of the matrix, aka total number of nodes. char* matrixIndex -> order of nodes in the model long int *totalEdgeWeights -> total edge weights of each [Node](#).

Returns

True if constructed. False if already constructed.

Definition at line 22 of file [modelMatrix.cpp](#).

```
00022                                     {
00023     if(this->ready) return false;
00024     this->matrixSize = this->StarterNode()->edgesV.size() + 2;
00025
00026     this->matrixIndex = new char[this->matrixSize];
00027     this->totalEdgeWeights = new long int[this->matrixSize];
00028
00029     this->edgeMatrix = new char*[this->matrixSize];
00030     for(int i=0;i<this->matrixSize;i++){
00031         this->edgeMatrix[i] = new char[this->matrixSize];
00032     }
00033     this->valueMatrix = new long int*[this->matrixSize];
00034     for(int i=0;i<this->matrixSize;i++){
00035         this->valueMatrix[i] = new long int[this->matrixSize];
```

```


00036     }
00037     std::map< char, Node< char > * > *nodes;
00038     nodes = this->Nodes();
00039     int i=0;
00040     for (auto const& [repr, node] : *nodes){
00041         if(repr!=0) this->matrixIndex[i] = repr;
00042         else this->matrixIndex[i] = 199;
00043         this->totalEdgeWeights[i] = node->TotalEdgeWeights();
00044         for(int j=0;j<this->matrixSize;j++){
00045             char val = node->NodeValue();
00046             if(val < 0){
00047                 for(int k=0;k<this->matrixSize;k++){
00048                     this->valueMatrix[i][k] = 0;
00049                     this->edgeMatrix[i][k] = 255;
00050                 }
00051                 break;
00052             }
00053             else if(node->NodeValue() == 0 && j>(this->matrixSize-3)){
00054                 this->valueMatrix[i][j] = 0;
00055                 this->edgeMatrix[i][j] = 255;
00056             }else if(j==(this->matrixSize-1)) {
00057                 this->valueMatrix[i][j] = 0;
00058                 this->edgeMatrix[i][j] = 255;
00059             }else{
00060                 this->valueMatrix[i][j] = node->edgesV[j]->EdgeWeight();
00061                 this->edgeMatrix[i][j] = node->edgesV[j]->RightNode()->NodeValue();
00062             }
00063         }
00064     }
00065     i++;
00066 }
00067 this->ready = true;
00068 return true;
00069 //this->DumpJSON();
00070 }

```


References [edgeMatrix](#), [Markov::Edge< NodeStorageType >::EdgeWeight\(\)](#), [matrixIndex](#), [matrixSize](#), [Markov::Model< NodeStorageType >::Nodes](#), [Markov::Node< storageType >::NodeValue\(\)](#), [ready](#), [Markov::Edge< NodeStorageType >::RightNode\(\)](#), [Markov::Model< NodeStorageType >::StarterNode](#), [totalEdgeWeights](#), [Markov::Node< storageType >::TotalEdgeWeights\(\)](#), and [valueMatrix](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), [Import\(\)](#), and [Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.16.3.3 DeallocateMatrix()

```
bool Markov::API::ModelMatrix::DeallocateMatrix ( ) [protected]
```

Deallocate matrix and make it ready for re-construction.

Returns

True if deallocated. False if matrix was not initialized

Definition at line 72 of file [modelMatrix.cpp](#).


```

00072 {
00073     if(!this->ready) return false;
00074     delete[] this->matrixIndex;
00075     delete[] this->totalEdgeWeights;
00076
00077     for(int i=0;i<this->matrixSize;i++){
00078         delete[] this->edgeMatrix[i];
00079     }
00080     delete[] this->edgeMatrix;
00081
00082     for(int i=0;i<this->matrixSize;i++){
00083         delete[] this->valueMatrix[i];
00084     }
00085     delete[] this->valueMatrix;
00086
00087     this->matrixSize = -1;
00088     this->ready = false;
00089     return true;
00090 }
```

References [edgeMatrix](#), [matrixIndex](#), [matrixSize](#), [ready](#), [totalEdgeWeights](#), and [valueMatrix](#).

Referenced by [Import\(\)](#), and [Train\(\)](#).

Here is the caller graph for this function:



8.16.3.4 DumpJSON()

```
void Markov::API::ModelMatrix::DumpJSON ( )
```

Debug function to dump the model to a JSON file.

Might not work 100%. Not meant for production use.

Definition at line 92 of file [modelMatrix.cpp](#).

```

00092 {
00093
```


8.16.3.6 Export() [1/2]

```
bool Markov::Model< char >::Export (
    const char * filename ) [inherited]
```

Open a file to export with filename, and call bool [Model::Export](#) with std::ofstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Export file to filename

```
Markov::Model<char> model;
model.Export("test.mdl");
```

Definition at line 286 of file [model.h](#).

```
00286                                     {
00287     std::ofstream exportfile;
00288     exportfile.open(filename);
00289     return this->Export(&exportfile);
00290 }
```

8.16.3.7 Export() [2/2]

```
bool Markov::Model< char >::Export (
    std::ofstream * f ) [inherited]
```

Export a file of the model.

File contains a list of edges. Format is: Left_repr;EdgeWeight;right_repr. For more information on the format, check out the project wiki or github readme.

Iterate over this vertices, and their edges, and write them to file.

Returns

True if successful, False for incomplete models.

Example Use: Export file to ofstream

```
Markov::Model<char> model;
std::ofstream file("test.mdl");
model.Export(&file);
```

Definition at line 274 of file [model.h](#).

```
00274                                     {
00275     Markov::Edge<NodeStorageType>* e;
00276     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00277         e = this->edges[i];
00278         //std::cout << e->LeftNode()->NodeValue() << ", " << e->EdgeWeight() << ", " <<
00279         e->RightNode()->NodeValue() << "\n";
00279         *f << e->LeftNode()->NodeValue() << ", " << e->EdgeWeight() << ", " << e->RightNode()->NodeValue() <<
00280         "\n";
00280     }
00281     return true;
00282 }
00283 }
```

8.16.3.8 FastRandomWalk()

```
void Markov::API::ModelMatrix::FastRandomWalk (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20,
    bool bFileIO = true )
```

Random walk on the Matrix-reduced [Markov::Model](#).

This has an O(N) Memory complexity. To limit the maximum usage, requests with n>50M are partitioned using [Markov::API::ModelMatrix::FastRandomWalkPartition](#).

If n>50M, threads are going to be synced, files are going to be flushed, and buffers will be reallocated every 50M generations. This comes at a minor performance penalty.

While it has the same functionality, this operation reduces [Markov::API::MarkovPasswords::Generate](#) runtime by %96.5

This function has deprecated [Markov::API::MarkovPasswords::Generate](#), and will eventually replace it.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

```
Markov::API::ModelMatrix mp;
mp.Import("models/finished.mdl");
mp.FastRandomWalk(50000000, "./wordlist.txt", 6, 12, 25, true);
```

Definition at line 195 of file [modelMatrix.cpp](#).

```
00195
{
00196
00197
00198     std::ofstream wordlist;
00199     if(bFileIO)
00200         wordlist.open(wordlistFileName);
00201
00202     std::mutex mlock;
00203     if(n<=50000000u) return this->FastRandomWalkPartition(&mlock, &wordlist, n, minLen, maxLen,
bFileIO, threads);
00204     else{
00205         int numberOfPartitions = n/50000000u;
00206         for(int i=0;i<numberOfPartitions;i++)
00207             this->FastRandomWalkPartition(&mlock, &wordlist, 50000000u, minLen, maxLen, bFileIO,
threads);
00208     }
00209
00210
00211 }
```


References [FastRandomWalkPartition\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.16.3.9 FastRandomWalkPartition()

```
void Markov::API::ModelMatrix::FastRandomWalkPartition (
    std::mutex * mlock,
    std::ofstream * wordlist,
    unsigned long int n,
    int minLen,
    int maxLen,
```

```
bool bFileIO,
int threads ) [protected]
```

A single partition of FastRandomWalk event.

Since FastRandomWalk has to allocate its output buffer before operation starts and writes data in chunks, large n parameters would lead to huge memory allocations. **Without Partitioning:**

- 50M results 12 characters max -> 550 Mb Memory allocation
- 5B results 12 characters max -> 55 Gb Memory allocation
- 50B results 12 characters max -> 550GB Memory allocation

Instead, FastRandomWalk is partitioned per 50M generations to limit the top memory need.

Parameters

<i>mlock</i>	- mutex lock to distribute to child threads
<i>wordlist</i>	- Reference to the wordlist file to write to
<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.


Definition at line 214 of file [modelMatrix.cpp](#).

```
00214
{
00215
00216     int iterationsPerThread = n/threads;
00217     int iterationsPerThreadCarryOver = n%threads;
00218
00219     std::vector<std::thread*> threadsV;
00220
00221     int id = 0;
00222     for(int i=0;i<threads;i++){
00223         threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this,
mlock, wordlist, iterationsPerThread, minLen, maxLen, id, bFileIO));
00224         id++;
00225     }
00226
00227     threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this, mlock,
wordlist, iterationsPerThreadCarryOver, minLen, maxLen, id, bFileIO));
00228
00229     for(int i=0;i<threads;i++){
00230         threadsV[i]->join();
00231     }
00232 }
```


References [FastRandomWalkThread\(\)](#).

Referenced by [FastRandomWalk\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.16.3.10 FastRandomWalkThread()

```

void Markov::API::ModelMatrix::FastRandomWalkThread (
    std::mutex * mlock,
    std::ofstream * wordlist,
    unsigned long int n,
    int minLen,
    int maxLen,
    int id,
    bool bFileIO ) [protected]
  
```

A single thread of a single partition of FastRandomWalk.

A FastRandomWalkPartition will initiate as many of this function as requested.

This function contains the bulk of the generation algorithm.

Parameters

<i>mlock</i>	- mutex lock to distribute to child threads
<i>wordlist</i>	- Reference to the wordlist file to write to
<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>id</i>	- DEPRECATED Thread id - No longer used
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

Definition at line 144 of file [modelMatrix.cpp](#).

```

00144
00145         if (n==0) return;
00146
00147         Markov::Random::Marsaglia MarsagliaRandomEngine;
00148         char* e;
00149         char *res = new char[maxLen*n];
00150         int index = 0;
00151         char next;
00152         int len=0;
00153         long int selection;
00154         char cur;
00155         long int bufferctr = 0;
00156         for (int i = 0; i < n; i++) {
00157             cur=199;
00158             len=0;
00159             while (true) {
00160                 e = strchr(this->matrixIndex, cur);
00161                 index = e - this->matrixIndex;
00162                 selection = MarsagliaRandomEngine.random() % this->totalEdgeWeights[index];
00163                 for(int j=0;j<this->matrixSize;j++){
00164                     selection -= this->valueMatrix[index][j];
00165                     if (selection < 0){
00166                         next = this->edgeMatrix[index][j];
00167                         break;
00168                     }
00169                 }
00170             }
00171             if (len >= maxLen) break;
00172             else if ((next < 0) && (len < minLen)) continue;
  
```

```


00173         else if (next < 0) break;
00174         cur = next;
00175         res[bufferctr + len++] = cur;
00176     }
00177     res[bufferctr + len++] = '\n';
00178     bufferctr+=len;
00179 }
00180 }
00181 if(bFileIO){
00182     mlock->lock();
00183     *wordlist « res;
00184     mlock->unlock();
00185 }else{
00186     mlock->lock();
00187     std::cout « res;
00188     mlock->unlock();
00189 }
00190 delete res;
00191
00192 }

```

References [edgeMatrix](#), [matrixIndex](#), [matrixSize](#), [Markov::Random::Marsaglia::random\(\)](#), [totalEdgeWeights](#), and [valueMatrix](#).

Referenced by [FastRandomWalkPartition\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.16.3.11 Generate()

```

void Markov::API::MarkovPasswords::Generate (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20 ) [inherited]

```

Call [Markov::Model::RandomWalk](#) n times, and collect output.

Generate from model and write results to a file. a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Deprecated See [Markov::API::MatrixModel::FastRandomWalk](#) for more information.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn

Definition at line 110 of file [markovPasswords.cpp](#).


```

00110
00111     {
00112         char* res;
00113         char print[100];
00114         std::ofstream wordlist;
00115         wordlist.open(wordlistFileName);
00116         std::mutex mlock;
00117         int iterationsPerThread = n/threads;
00118         int iterationsCarryOver = n%threads;
00119         std::vector<std::thread*> threadsV;
00120         for(int i=0;i<threads;i++){
00121             threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::GenerateThread, this,
00122                 &mlock, iterationsPerThread, &wordlist, minLen, maxLen));
00123         }
00124         for(int i=0;i<threads;i++){
00125             threadsV[i]->join();
00126             delete threadsV[i];
00127         }
00128         this->GenerateThread(&mlock, iterationsCarryOver, &wordlist, minLen, maxLen);
00129     }
00130 }
```


References [Markov::API::MarkovPasswords::GenerateThread\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.16.3.12 GenerateThread()

```

void Markov::API::MarkovPasswords::GenerateThread (
    std::mutex * outputLock,
    unsigned long int n,
    std::ofstream * wordlist,
    int minLen,
    int maxLen ) [private], [inherited]
```

A single thread invoked by the Generate function.

DEPRECATED: See [Markov::API::MatrixModel::FastRandomWalkThread](#) for more information. This has been replaced with a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Parameters

<i>outputLock</i>	- shared mutex lock to lock during output operation. Prevents race condition on write.
<i>n</i>	number of lines to be generated by this thread
<i>wordlist</i>	wordlistfile
<i>minLen</i>	- Minimum password length to generate

Parameters

<i>maxLen</i>	- Maximum password length to generate
---------------	---------------------------------------

Definition at line 132 of file [markovPasswords.cpp](#).

```

00132
00133     char* res = new char[maxLen+5];
00134     if (n==0) return;
00135
00136     Markov::Random::Marsaglia MarsagliaRandomEngine;
00137     for (int i = 0; i < n; i++) {
00138         this->RandomWalk(&MarsagliaRandomEngine, minLen, maxLen, res);
00139         outputLock->lock();
00140         *wordlist « res « "\n";
00141         outputLock->unlock();
00142     }
00143 }

```


References [Markov::Model< NodeStorageType >::RandomWalk\(\)](#).

Referenced by [Markov::API::MarkovPasswords::Generate\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.16.3.13 Import() [1/2]

```

void Markov::API::ModelMatrix::Import (
    const char * filename )

```

Open a file to import with filename, and call bool [Model::Import](#) with `std::ifstream`.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file with filename

```

Markov::Model<char> model;
model.Import("test.mdl");

```

Construct the matrix when done.

Definition at line 10 of file [modelMatrix.cpp](#).

```


00010     {
00011         this->DeallocateMatrix();
00012         this->Markov::API::MarkovPasswords::Import(filename);
00013         this->ConstructMatrix();
00014     }

```


References [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), and [Markov::Model< NodeStorageType >::Import\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.16.3.14 Import() [2/2]

```
bool Markov::Model< char >::Import (
    std::ifstream * f ) [inherited]
```

Import a file to construct the model.

File contains a list of edges. For more info on the file format, check out the wiki and github readme pages. Format is: Left_repr;EdgeWeight;right_repr

Iterate over this list, and construct nodes and edges accordingly.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file from ifstream

```
Markov::Model<char> model;
std::ifstream file("test.mdl");
model.Import(&file);
```

Definition at line 207 of file [model.h](#).

```
00207                                     {
00208     std::string cell;
00209
00210     char src;
00211     char target;
00212     long int oc;
00213
00214     while (std::getline(*f, cell)) {
00215         //std::cout << "cell: " << cell << std::endl;
00216         src = cell[0];
00217         target = cell[cell.length() - 1];
00218         char* j;
00219         oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(), &j, 10);
00220         //std::cout << oc << "\n";
00221         Markov::Node<NodeStorageType>* srcN;
```



```

00222     Markov::Node<NodeStorageType>* targetN;
00223     Markov::Edge<NodeStorageType>* e;
00224     if (this->nodes.find(src) == this->nodes.end()) {
00225         srcN = new Markov::Node<NodeStorageType>(src);
00226         this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(src, srcN));
00227         //std::cout << "Creating new node at start.\n";
00228     }
00229     else {
00230         srcN = this->nodes.find(src)->second;
00231     }
00232
00233     if (this->nodes.find(target) == this->nodes.end()) {
00234         targetN = new Markov::Node<NodeStorageType>(target);
00235         this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(target, targetN));
00236         //std::cout << "Creating new node at end.\n";
00237     }
00238     else {
00239         targetN = this->nodes.find(target)->second;
00240     }
00241     e = srcN->Link(targetN);
00242     e->AdjustEdge(oc);
00243     this->edges.push_back(e);
00244
00245     //std::cout << int(srcN->NodeValue()) << " --" << e->EdgeWeight() << "--> " <<
    int(targetN->NodeValue()) << "\n";
00246
00247
00248     }
00249
00250     for (std::pair<unsigned char, Markov::Node<NodeStorageType>*> const& x : this->nodes) {
00251         //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
00252         std::sort (x.second->edgesV.begin(), x.second->edgesV.end(), [] (Edge<NodeStorageType> *lhs,
    Edge<NodeStorageType> *rhs)->bool{
00253             return lhs->EdgeWeight() > rhs->EdgeWeight();
00254         });
00255         //for(int i=0;i<x.second->edgesV.size();i++)
00256         // std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00257         //std::cout << "\n";
00258     }
00259     //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00260     //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00261
00262     return true;
00263 }

```

8.16.3.15 Nodes()

std::map<char , Node<char >*>* Markov::Model< char >::Nodes () [inline], [inherited]
Return starter Node.

Returns

starter node with 00 NodeValue

Definition at line 177 of file [model.h](#).

```
00177 { return &nodes; }
```

8.16.3.16 OpenDatasetFile()

```
std::ifstream * Markov::API::MarkovPasswords::OpenDatasetFile (
    const char * filename ) [inherited]
```

Open dataset file and return the ifstream pointer.

Parameters

<i>filename</i>	- Filename to open
-----------------	--------------------

Returns

ifstream* to the the dataset file

Definition at line 43 of file [markovPasswords.cpp](#).

```
00043
```

```
{
```


```

00044
00045     std::ifstream* datasetFile;
00046
00047     std::ifstream newFile(filename);
00048
00049     datasetFile = &newFile;
00050
00051     this->Import(datasetFile);
00052     return datasetFile;
00053 }

```

References [Markov::Model< NodeStorageType >::Import\(\)](#).

Here is the call graph for this function:



8.16.3.17 RandomWalk()

```

char * Markov::Model< char >::RandomWalk (
    Markov::Random::RandomEngine * randomEngine,
    int minSetting,
    int maxSetting,
    NodeStorageType * buffer ) [inherited]

```

Do a random walk on this model.

Start from the starter node, on each node, invoke RandomNext using the random engine on current node, until terminator node is reached. If terminator node is reached before minimum length criateria is reached, ignore the last selection and re-invoke randomNext

If maximum length criteria is reached but final node is not, cut off the generation and proceed to the final node. This function takes [Markov::Random::RandomEngine](#) as a parameter to generate pseudo random numbers from This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne output is higher in entropy, most use cases don't really need super high entropy output, so [Markov::Random::Marsaglia](#) is preferable for better performance.

This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening via maximum length criteria.

Example Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use Marsaglia

```

Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}

```

Parameters

<i>randomEngine</i>	Random Engine to use for the random walks. For examples, see Markov::Random::Mersenne and Markov::Random::Marsaglia
<i>minSetting</i>	Minimum number of characters to generate
<i>maxSetting</i>	Maximum number of character to generate
<i>buffer</i>	buffer to write the result to

Returns

Null terminated string that was generated.

Definition at line 293 of file [model.h](#).

```

00293
00294     Markov::Node<NodeStorageType>* n = this->starterNode;
00295     int len = 0;
00296     Markov::Node<NodeStorageType>* temp_node;
00297     while (true) {
00298         temp_node = n->RandomNext(randomEngine);
00299         if (len >= maxSetting) {
00300             break;
00301         }
00302         else if ((temp_node == NULL) && (len < minSetting)) {
00303             continue;
00304         }
00305
00306         else if (temp_node == NULL){
00307             break;
00308         }
00309
00310         n = temp_node;
00311
00312         buffer[len++] = n->NodeValue();
00313     }
00314
00315     //null terminate the string
00316     buffer[len] = 0x00;
00317
00318     //do something with the generated string
00319     return buffer; //for now
00320 }
```

8.16.3.18 Save()

```
std::ofstream * Markov::API::MarkovPasswords::Save (
    const char * filename ) [inherited]
```

Export model to file.

Parameters

<i>filename</i>	- Export filename.
-----------------	--------------------

Returns

std::ofstream* of the exported file.


Definition at line 98 of file [markovPasswords.cpp](#).

```

00098
00099     std::ofstream* exportFile;
00100
00101     std::ofstream newFile(filename);
00102
00103     exportFile = &newFile;
00104
00105     this->Export(exportFile);
00106     return exportFile;
00107 }
```

References [Markov::Model< NodeStorageType >::Export\(\)](#).

Here is the call graph for this function:



8.16.3.19 StarterNode()

`Node<char > * Markov::Model< char >::StarterNode () [inline], [inherited]`

Return starter [Node](#).

Returns

starter node with 00 NodeValue

Definition at line 167 of file [model.h](#).

```
00167 { return starterNode; }
```

8.16.3.20 Train()

```
void Markov::API::ModelMatrix::Train (
    const char * datasetFileName,
    char delimiter,
    int threads )
```

Train the model with the dataset file.

Parameters

<i>datasetFileName</i>	- ifstream* to the dataset. If null, use class member
<i>delimiter</i>	- a character, same as the delimiter in dataset content
<i>threads</i>	- number of OS threads to spawn

```
Markov::API::MarkovPasswords mp;
mp.Import ("models/2gram.mdl");
mp.Train ("password.corpus");
```

Construct the matrix when done.


Definition at line 16 of file [modelMatrix.cpp](#).

```
00016 {
00017     this->DeallocateMatrix();
00018     this->Markov::API::MarkovPasswords::Train(datasetFileName, delimiter, threads);
00019     this->ConstructMatrix();
00020 }
```


References [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), and [Markov::API::MarkovPasswords::Train\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.16.3.21 TrainThread()

```
void Markov::API::MarkovPasswords::TrainThread (
    Markov::API::Concurrency::ThreadSharedListHandler * listhandler,
    char delimiter ) [private], [inherited]
```

A single thread invoked by the Train function.

Parameters

<i>listhandler</i>	- Listhandler class to read corpus from
<i>delimiter</i>	- a character, same as the delimiter in dataset content


Definition at line 77 of file [markovPasswords.cpp](#).

```
00077
{
00078     char format_str[] = "%ld,%s";
00079     format_str[3]=delimiter;
00080     std::string line;
00081     while (listhandler->next(&line) && keepRunning) {
00082         long int oc;
00083         if (line.size() > 100) {
00084             line = line.substr(0, 100);
00085         }
00086         char* linebuf = new char[line.length()+5];
00087 #ifdef _WIN32
00088         sscanf_s(line.c_str(), "%ld,%s", &oc, linebuf, line.length()+5); //<== changed format_str to->
00089         "%ld,%s"
00089     #else
00090         sscanf(line.c_str(), format_str, &oc, linebuf);
00091     #endif
00092     this->AdjustEdge((const char*)linebuf, oc);
00093     delete linebuf;
00094     }
00095 }
```


References [Markov::Model< NodeStorageType >::AdjustEdge\(\)](#), [keepRunning](#), and [Markov::API::Concurrency::ThreadSharedListHandler](#).

Referenced by [Markov::API::MarkovPasswords::Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.16.4 Member Data Documentation

8.16.4.1 datasetFile

`std::ifstream* Markov::API::MarkovPasswords::datasetFile` [private], [inherited]
 Definition at line 106 of file [markovPasswords.h](#).

8.16.4.2 edgeMatrix

`char** Markov::API::ModelMatrix::edgeMatrix` [protected]
 2-D Character array for the edge Matrix (The characters of Nodes)
 Definition at line 136 of file [modelMatrix.h](#).
 Referenced by [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), [DumpJSON\(\)](#), and [FastRandomWalkThread\(\)](#).

8.16.4.3 edges

`std::vector<Edge<char >*> Markov::Model< char >::edges` [private], [inherited]
 A list of all edges in this model.
 Definition at line 195 of file [model.h](#).

8.16.4.4 matrixIndex

`char* Markov::API::ModelMatrix::matrixIndex` [protected]
 to hold the Matrix index (To hold the orders of 2-D arrays')
 Definition at line 151 of file [modelMatrix.h](#).
 Referenced by [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), [DumpJSON\(\)](#), and [FastRandomWalkThread\(\)](#).

8.16.4.5 matrixSize

`int Markov::API::ModelMatrix::matrixSize` [protected]
 to hold Matrix size
 Definition at line 146 of file [modelMatrix.h](#).
 Referenced by [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), [DumpJSON\(\)](#), and [FastRandomWalkThread\(\)](#).

8.16.4.6 modelSavefile

`std::ofstream* Markov::API::MarkovPasswords::modelSavefile` [private], [inherited]
 Dataset file input of our system
 Definition at line 107 of file [markovPasswords.h](#).

8.16.4.7 nodes

```
std::map<char , Node<char >*> Markov::Model< char >::nodes [private], [inherited]
```

Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.

Definition at line 184 of file [model.h](#).

8.16.4.8 outputFile

```
std::ofstream* Markov::API::MarkovPasswords::outputFile [private], [inherited]
```

File to save model of our system

Definition at line 108 of file [markovPasswords.h](#).

8.16.4.9 ready

```
bool Markov::API::ModelMatrix::ready [protected]
```

True when matrix is constructed. False if not.

Definition at line 161 of file [modelMatrix.h](#).

Referenced by [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), and [ModelMatrix\(\)](#).

8.16.4.10 starterNode

```
Node<char >* Markov::Model< char >::starterNode [private], [inherited]
```

Starter Node of this model.

Definition at line 189 of file [model.h](#).

8.16.4.11 totalEdgeWeights

```
long int* Markov::API::ModelMatrix::totalEdgeWeights [protected]
```

Array of the Total Edge Weights.

Definition at line 156 of file [modelMatrix.h](#).

Referenced by [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), and [FastRandomWalkThread\(\)](#).

8.16.4.12 valueMatrix

```
long int** Markov::API::ModelMatrix::valueMatrix [protected]
```

2-d Integer array for the value Matrix (For the weights of Edges)

Definition at line 141 of file [modelMatrix.h](#).

Referenced by [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), [DumpJSON\(\)](#), and [FastRandomWalkThread\(\)](#).

The documentation for this class was generated from the following files:


- [modelMatrix.h](#)
- [modelMatrix.cpp](#)

8.17 Markov::Node< storageType > Class Template Reference


A node class that for the vertices of model. Connected with eachother using [Edge](#).

```
#include <model.h>
```

Inheritance diagram for Markov::Node< storageType >:



Collaboration diagram for `Markov::Node< storageType >`:



Public Member Functions

- `Node()`
Default constructor. Creates an empty `Node`.
- `Node(storageType _value)`
Constructor. Creates a `Node` with no edges and with given `NodeValue`.
- `Edge< storageType > * Link(Node< storageType > *)`
Link this node with another, with this node as its source.
- `Edge< storageType > * Link(Edge< storageType > *)`
Link this node with another, with this node as its source.
- `Node< storageType > * RandomNext(Markov::Random::RandomEngine *randomEngine)`
Chose a random node from the list of edges, with regards to its `EdgeWeight`, and `TraverseNode` to that.
- `bool UpdateEdges(Edge< storageType > *)`
Insert a new edge to the this.edges.

- [Edge< storageType > * FindEdge](#) (storageType repr)
Find an edge with its character representation.
- [Edge< storageType > * FindEdge](#) ([Node< storageType > *target](#))
Find an edge with its pointer. Avoid unless neccessary because comptutational cost of find by character is cheaper (because of std::map)
- unsigned char [NodeValue](#) ()
Return character representation of this node.
- void [UpdateTotalVerticeWeight](#) (long int offset)
Change total weights with offset.
- std::map< storageType, [Edge< storageType > * > * Edges](#) ()
return edges
- long int [TotalEdgeWeights](#) ()
return total edge weights

Public Attributes

- std::vector< [Edge< storageType > * > edgesV](#)

Private Attributes

- storageType [_value](#)
Character representation of this node. 0 for starter, 0xff for terminator.
- long int [total_edge_weights](#)
Total weights of the vertices, required by RandomNext.
- std::map< storageType, [Edge< storageType > * > edges](#)
A map of all edges connected to this node, where this node is at the LeftNode. Map is indexed by unsigned char, which is the character representation of the node.

8.17.1 Detailed Description

```
template<typename storageType>
class Markov::Node< storageType >
```

A node class that for the vertices of model. Connected with eachother using [Edge](#).
This class will later be templated to accept other data types than char*.
Definition at line 23 of file [model.h](#).

8.17.2 Constructor & Destructor Documentation

8.17.2.1 Node() [1/2]

```
template<typename storageType >
Markov::Node< storageType >::Node()
Default constructor. Creates an empty Node.
Definition at line 201 of file node.h.
00201         {
00202     this->_value = 0;
00203     this->total_edge_weights = 0L;
00204 };
```

8.17.2.2 Node() [2/2]

```
template<typename storageType >  
Markov::Node< storageType >::Node (  
    storageType _value )
```

Constructor. Creates a [Node](#) with no edges and with given NodeValue.

Parameters

<code>_value</code>	- Nodes character representation.
---------------------	-----------------------------------

Example Use: Construct nodes

```
Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
```

Definition at line 195 of file [node.h](#).

```
00195                                     {
00196     this->_value = _value;
00197     this->total_edge_weights = 0L;
00198 };
```

8.17.3 Member Function Documentation

8.17.3.1 Edges()

```
template<typename storageType >
std::map< storageType, Markov::Edge< storageType > * > * Markov::Node< storageType >::Edges
[inline]
return edges
```

Definition at line 264 of file [node.h](#).

```
00264                                     {
00265     return &(this->edges);
00266 }
```

8.17.3.2 FindEdge() [1/2]

```
template<typename storageType >
Edge<storageType>* Markov::Node< storageType >::FindEdge (
    Node< storageType > * target )
```

Find an edge with its pointer. Avoid unless necessary because computational cost of find by character is cheaper (because of std::map)

Parameters

<i>target</i>	- target node.
---------------	----------------

Returns

[Edge](#) that is connected between this node, and the target node.

8.17.3.3 FindEdge() [2/2]

```
template<typename storageType >
Markov::Edge< storageType > * Markov::Node< storageType >::FindEdge (
    storageType repr )
```

Find an edge with its character representation.

Parameters

<i>repr</i>	- character NodeValue of the target node.
-------------	---

Returns

[Edge](#) that is connected between this node, and the target node.

Example Use: Construct and update edges

```
Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
Markov::Edge<unsigned char>* res = NULL;
src->Link(target1);
src->Link(target2);
res = src->FindEdge('b');
```

Definition at line 252 of file [node.h](#).

```
00252 {
00253     auto e = this->edges.find(repr);
00254     if (e == this->edges.end()) return NULL;
00255     return e->second;
00256 };
```

8.17.3.4 Link() [1/2]

```
template<typename storageType >
Markov::Edge< storageType > * Markov::Node< storageType >::Link (
    Markov::Edge< storageType > * v )
```

Link this node with another, with this node as its source.

DOES NOT create a new [Edge](#).

Parameters

Edge	- Edge that will accept this node as its LeftNode.
----------------------	--

Returns

the same edge as parameter target.

Example Use: Construct and link nodes

```
Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
LeftNode->Link(e);
```

Definition at line 219 of file [node.h](#).

```
00219 {
00220     v->SetLeftEdge(this);
00221     this->UpdateEdges(v);
00222     return v;
00223 }
```

8.17.3.5 Link() [2/2]

```
template<typename storageType >
Markov::Edge< storageType > * Markov::Node< storageType >::Link (
    Markov::Node< storageType > * n )
```

Link this node with another, with this node as its source.

Creates a new [Edge](#).

Parameters

<i>target</i>	- Target node which will be the RightNode() of new edge.
---------------	--

Returns

A new node with LeftNode as this, and RightNode as parameter target.

Example Use: Construct nodes

```
Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
```

```
Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
```

Definition at line 212 of file [node.h](#).

```
00212
00213     Markov::Edge<storageType>* v = new Markov::Edge<storageType>(this, n);
00214     this->UpdateEdges(v);
00215     return v;
00216 }
```

8.17.3.6 NodeValue()

```
template<typename storageType >
```

```
unsigned char Markov::Node< storageType >::NodeValue [inline]
```

Return character representation of this node.

Returns


character representation at `_value`.

Definition at line 207 of file [node.h](#).

```
00207
00208     return _value;
00209 }
```

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:



8.17.3.7 RandomNext()

```
template<typename storageType >
```

```
Markov::Node< storageType > * Markov::Node< storageType >::RandomNext (
    Markov::Random::RandomEngine * randomEngine )
```

Chose a random node from the list of edges, with regards to its `EdgeWeight`, and `TraverseNode` to that.

This operation is done by generating a random number in range of `0-this.total_edge_weights`, and then iterating over the list of edges. At each step, `EdgeWeight` of the edge is subtracted from the random number, and once it is 0, next node is selected.

Returns

[Node](#) that was chosen at `EdgeWeight` biased random.

Example Use: Use `randomNext` to do a random walk on the model

```
char* buffer[64];
Markov::Model<char> model;
model.Import("model.mdl");
Markov::Node<char>* n = model.starterNode;
int len = 0;
Markov::Node<char>* temp_node;
while (true) {
    temp_node = n->RandomNext(randomEngine);
    if (len >= maxSetting) {
        break;
    }
    else if ((temp_node == NULL) && (len < minSetting)) {
        continue;
    }
    else if (temp_node == NULL) {
        break;
    }
}
```

```

    n = temp_node;
    buffer[len++] = n->NodeValue();
}

```

Definition at line 226 of file `node.h`.

```

00226
00227
00228     //get a random NodeValue in range of total_vertice_weight
00229     long int selection = randomEngine->random() %
this->total_edge_weights; //distribution() (generator()); // distribution(generator);
00230     //make absolute, no negative modulus values wanted
00231     //selection = (selection >= 0) ? selection : (selection + this->total_edge_weights);
00232     for(int i=0; i<this->edgesV.size(); i++){
00233         selection -= this->edgesV[i]->EdgeWeight();
00234         if (selection < 0) return this->edgesV[i]->TraverseNode();
00235     }
00236
00237     //if this assertion is reached, it means there is an implementation error above
00238     std::cout << "This should never be reached (node failed to walk to next)\n"; //cant assert from
child thread
00239     assert(true && "This should never be reached (node failed to walk to next)");
00240     return NULL;
00241 }

```

8.17.3.8 TotalEdgeWeights()

```

template<typename storageType >
long int Markov::Node< storageType >::TotalEdgeWeights [inline]
return total edge weights

```

Definition at line 269 of file `node.h`.


```

00269
00270     return this->total_edge_weights;
00271 }

```

Referenced by `Markov::API::ModelMatrix::ConstructMatrix()`.

Here is the caller graph for this function:



8.17.3.9 UpdateEdges()

```

template<typename storageType >
bool Markov::Node< storageType >::UpdateEdges (
    Markov::Edge< storageType > * v )

```

Insert a new edge to the this.edges.

Parameters

<i>edge</i>	- New edge that will be inserted.
-------------	-----------------------------------

Returns

true if insertion was successful, false if it fails.

Example Use: Construct and update edges

```

Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target2);
e1->AdjustEdge(25);
src->UpdateEdges(e1);

```

```
e2->AdjustEdge(30);
src->UpdateEdges(e2);
```

Definition at line 244 of file [node.h](#).

```
00244
00245     this->edges.insert({ v->RightNode()->NodeValue(), v });
00246     this->edgesV.push_back(v);
00247     //this->total_edge_weights += v->EdgeWeight();
00248     return v->TraverseNode();
00249 }
```

8.17.3.10 UpdateTotalVerticeWeight()

```
template<typename storageType >
void Markov::Node< storageType >::UpdateTotalVerticeWeight (
    long int offset )
```

Change total weights with offset.

Parameters

<i>offset</i>	to adjust the vertice weight with
---------------	-----------------------------------

Definition at line 259 of file [node.h](#).

```
00259
00260     this->total_edge_weights += offset;
00261 }
```

8.17.4 Member Data Documentation

8.17.4.1 _value

```
template<typename storageType >
storageType Markov::Node< storageType >::_value [private]
```

Character representation of this node. 0 for starter, 0xff for terminator.

Definition at line 171 of file [node.h](#).

Referenced by [Markov::Node< NodeStorageType >::NodeValue\(\)](#).

8.17.4.2 edges

```
template<typename storageType >
std::map<storageType, Edge<storageType>*> Markov::Node< storageType >::edges [private]
```

A map of all edges connected to this node, where this node is at the LeftNode. Map is indexed by unsigned char, which is the character representation of the node.

Definition at line 182 of file [node.h](#).

8.17.4.3 edgesV

```
template<typename storageType >
std::vector<Edge<storageType>*> Markov::Node< storageType >::edgesV
```

Definition at line 165 of file [node.h](#).

8.17.4.4 total_edge_weights

```
template<typename storageType >
long int Markov::Node< storageType >::total_edge_weights [private]
```

Total weights of the vertices, required by RandomNext.

Definition at line 176 of file [node.h](#).

The documentation for this class was generated from the following files:


- [model.h](#)
- [node.h](#)

8.18 Markov::Random::RandomEngine Class Reference


An abstract class for [Random](#) Engine.

```
#include <random.h>
```

Inheritance diagram for Markov::Random::RandomEngine:



Collaboration diagram for Markov::Random::RandomEngine:



Public Member Functions

- virtual unsigned long [random](#) ()=0

8.18.1 Detailed Description

An abstract class for [Random](#) Engine.

This class is used for generating random numbers, which are used for random walking on the graph.

Main reason behind allowing different random engines is that some use cases may favor performance, while some favor good random.

[Mersenne](#) can be used for truer random, while [Marsaglia](#) can be used for deterministic but fast random.

Definition at line [21](#) of file [random.h](#).

8.18.2 Member Function Documentation


8.18.2.1 random()

```
virtual unsigned long Markov::Random::RandomEngine::random ( ) [inline], [pure virtual]
```

Implemented in [Markov::Random::Marsaglia](#), and [Markov::Random::DefaultRandomEngine](#).

Referenced by [Markov::Node< NodeStorageType >::RandomNext\(\)](#).

Here is the caller graph for this function:



The documentation for this class was generated from the following file:


- [random.h](#)

8.19 Markov::API::CLI::Terminal Class Reference

pretty colors for [Terminal](#). Windows Only.

```
#include <term.h>
```

Collaboration diagram for Markov::API::CLI::Terminal:



Public Types

- enum `color` {
`RESET`, `BLACK`, `RED`, `GREEN`,
`YELLOW`, `BLUE`, `MAGENTA`, `CYAN`,
`WHITE`, `LIGHTGRAY`, `DARKGRAY`, `BROWN` }

Public Member Functions

- [Terminal](#) ()

Static Public Attributes

- static std::map< [Markov::API::CLI::Terminal::color](#), int > [colormap](#)
- static std::ostream [endl](#)

8.19.1 Detailed Description

pretty colors for [Terminal](#). Windows Only.
Definition at line 18 of file [term.h](#).

8.19.2 Member Enumeration Documentation

8.19.2.1 color

```
enum Markov::API::CLI::Terminal::color
```

Enumerator

RESET	
BLACK	
RED	
GREEN	
YELLOW	
BLUE	
MAGENTA	
CYAN	
WHITE	
LIGHTGRAY	
DARKGRAY	
BROWN	

Definition at line 26 of file [term.h](#).

```
00026 { RESET, BLACK, RED, GREEN, YELLOW, BLUE, MAGENTA, CYAN, WHITE, LIGHTGRAY, DARKGRAY, BROWN };
```

8.19.3 Constructor & Destructor Documentation

8.19.3.1 Terminal()

```
Terminal::Terminal ( )
```

Default constructor. Get references to stdout and stderr handles.

Definition at line 56 of file [term.cpp](#).

```
00056 {  
00057     /*this->*/  
00058 }
```

8.19.4 Member Data Documentation

8.19.4.1 colormap

```
std::map< Terminal::color, int > Terminal::colormap [static]
```

Initial value:

```
= {  
    {Terminal::color::BLACK, 30},  
    {Terminal::color::BLUE, 34},  
    {Terminal::color::GREEN, 32},  
    {Terminal::color::CYAN, 36},  
    {Terminal::color::RED, 31},  
    {Terminal::color::MAGENTA, 35},  
    {Terminal::color::BROWN, 0},  
    {Terminal::color::LIGHTGRAY, 0},  
    {Terminal::color::DARKGRAY, 0},  
    {Terminal::color::YELLOW, 33},  
    {Terminal::color::WHITE, 37},  
    {Terminal::color::RESET, 0},  
}
```

Definition at line 32 of file [term.h](#).

Referenced by [operator<<\(\)](#).

8.19.4.2 endl

```
std::ostream Markov::API::CLI::Terminal::endl [static]
```

Definition at line 37 of file [term.h](#).

The documentation for this class was generated from the following files:


- [term.h](#)
- [term.cpp](#)

8.20 Markov::API::Concurrency::ThreadSharedListHandler Class Reference

Simple class for managing shared access to file.

```
#include <threadSharedListHandler.h>
```

Collaboration diagram for Markov::API::Concurrency::ThreadSharedListHandler:



Public Member Functions

- [ThreadSharedListHandler](#) (const char *filename)

Construct the Thread Handler with a filename.

- bool [next](#) (std::string *line)

Read the next line from the file.

Private Attributes

- `std::ifstream` [listfile](#)
- `std::mutex` [mlock](#)

8.20.1 Detailed Description

Simple class for managing shared access to file.

This class maintains the handover of each line from a file to multiple threads.

When two different threads try to read from the same file while reading a line isn't completed, it can have unexpected results. Line might be split, or might be read twice. This class locks the read action on the list until a line is completed, and then proceeds with the handover.

Definition at line 18 of file [threadSharedListHandler.h](#).

8.20.2 Constructor & Destructor Documentation

8.20.2.1 ThreadSharedListHandler()

```
Markov::API::Concurrency::ThreadSharedListHandler::ThreadSharedListHandler (
    const char * filename )
```

Construct the Thread Handler with a filename.

Simply open the file, and initialize the locks.

Example Use: Simple file read

```
ThreadSharedListHandler listhandler("test.txt");
std::string line;
std::cout << listhandler->next(&line) << "\n";
```

Example Use: Example use case from [MarkovPasswords](#) showing multithreaded access

```
void MarkovPasswords::Train(const char* datasetFileName, char delimiter, int threads) {
    ThreadSharedListHandler listhandler(datasetFileName);
    auto start = std::chrono::high_resolution_clock::now();
    std::vector<std::thread*> threadsV;
    for(int i=0;i<threads;i++){
        threadsV.push_back(new std::thread(&MarkovPasswords::TrainThread, this, &listhandler,
            datasetFileName, delimiter));
    }
    for(int i=0;i<threads;i++){
        threadsV[i]->join();
        delete threadsV[i];
    }
    auto finish = std::chrono::high_resolution_clock::now();
    std::chrono::duration<double> elapsed = finish - start;
    std::cout << "Elapsed time: " << elapsed.count() << " s\n";
}

void MarkovPasswords::TrainThread(ThreadSharedListHandler *listhandler, const char* datasetFileName, char
    delimiter){
    char format_str[] = "%ld,%s";
    format_str[2]=delimiter;
    std::string line;
    while (listhandler->next(&line)) {
        long int oc;
        if (line.size() > 100) {
            line = line.substr(0, 100);
        }
        char* linebuf = new char[line.length()+5];
        sscanf_s(line.c_str(), format_str, &oc, linebuf, line.length()+5);
        this->AdjustEdge((const char*)linebuf, oc);
        delete linebuf;
    }
}
```

Parameters

<i>filename</i>	Filename for the file to manage.
-----------------	----------------------------------


Definition at line 4 of file [threadSharedListHandler.cpp](#).

```
00004
00005     this->listfile;
00006     this->listfile.open(filename, std::ios_base::binary);
00007 }
```

References [listfile](#).

Referenced by [Markov::API::MarkovPasswords::Train\(\)](#).

Here is the caller graph for this function:



8.20.3 Member Function Documentation

8.20.3.1 next()

```
bool Markov::API::Concurrency::ThreadSharedListHandler::next (
    std::string * line )
```

Read the next line from the file.

This action will be blocked until another thread (if any) completes the read operation on the file.

Example Use: Simple file read

```
ThreadSharedListHandler listhandler("test.txt");
std::string line;
std::cout << listhandler->next(&line) << "\n";
```

Definition at line 10 of file [threadSharedListHandler.cpp](#).

```
00010
00011     bool res = false;
00012     this->mlock.lock();
00013     res = (std::getline(this->listfile, *line, '\n')) ? true : false;
00014     this->mlock.unlock();
00015
00016     return res;
00017 }
```

References [listfile](#), and [mlock](#).

Referenced by [Markov::API::MarkovPasswords::TrainThread\(\)](#).

Here is the caller graph for this function:



8.20.4 Member Data Documentation

8.20.4.1 listfile

```
std::ifstream Markov::API::Concurrency::ThreadSharedListHandler::listfile [private]
```

Definition at line 88 of file [threadSharedListHandler.h](#).

Referenced by [next\(\)](#), and [ThreadSharedListHandler\(\)](#).

8.20.4.2 mlock

```
std::mutex Markov::API::Concurrency::ThreadSharedListHandler::mlock [private]
```

Definition at line 89 of file [threadSharedListHandler.h](#).

Referenced by [next\(\)](#).

The documentation for this class was generated from the following files:


- [threadSharedListHandler.h](#)
- [threadSharedListHandler.cpp](#)

8.21 Markov::GUI::Train Class Reference


QT Training page class.

```
#include <Train.h>
```

Inheritance diagram for Markov::GUI::Train:



Collaboration diagram for Markov::GUI::Train:



Public Slots

- void [home](#) ()
- void [train](#) ()

Public Member Functions

- [Train](#) (QWidget *parent=Q_NULLPTR)

Private Attributes

- Ui::Train [ui](#)

8.21.1 Detailed Description

QT Training page class.

Definition at line 9 of file [Train.h](#).

8.21.2 Constructor & Destructor Documentation

8.21.2.1 Train()

```
Markov::GUI::Train::Train (  
    QWidget * parent = Q_NULLPTR )
```

8.21.3 Member Function Documentation

8.21.3.1 home

```
void Markov::GUI::Train::home ( ) [slot]
```

8.21.3.2 train

```
void Markov::GUI::Train::train ( ) [slot]
```

8.21.4 Member Data Documentation

8.21.4.1 ui

```
Ui::Train Markov::GUI::Train::ui [private]
```

Definition at line 15 of file [Train.h](#).

The documentation for this class was generated from the following file:

- [Train.h](#)


Chapter 9

File Documentation

9.1 about.h File Reference

```
#include <QtWidgets/QMainWindow>
#include "ui_about.h"
#include <ui_menu.h>
```

Include dependency graph for about.h:



Classes

- class [Markov::GUI::about](#)
QT Class for about page.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::GUI](#)
namespace for MarkovPasswords [API GUI](#) wrapper

9.2 about.h

```
00001 #pragma once
00002 #include <QtWidgets/QMainWindow>
00003 #include "ui_about.h"
00004 #include <ui_menu.h>
00005
00006 /** @brief namespace for MarkovPasswords API GUI wrapper
00007 */
00008 namespace Markov::GUI{
00009
00010     /** @brief QT Class for about page
00011     */
00012     class about :public QMainWindow {
```

```

00013     Q_OBJECT
00014     public:
00015         about(QWidget* parent = Q_NULLPTR);
00016
00017     private:
00018         Ui:: main ui;
00019
00020
00021     };
00022 };

```


9.3 argparse.cpp File Reference

```

#include "argparse.h"
#include "color/term.h"

```

Include dependency graph for argparse.cpp:



9.4 argparse.cpp

```

00001 #include "argparse.h"
00002 #include "color/term.h"
00003
00004 Markov::API::CLI::ProgramOptions* Markov::API::CLI::Argparse::parse(int argc, char** argv) { return 0;
00005 }
00006
00007
00008 void Markov::API::CLI::Argparse::help() {
00009     std::cout <<
00010     "Markov Passwords - Help\n"
00011     "Options:\n"
00012     "  \n"
00013     "  -of --outputfilename\n"
00014     "      Filename to output the generation results\n"
00015     "  -ef --exportfilename\n"
00016     "      filename to export built model to\n"
00017     "  -if --importfilename\n"
00018     "      filename to import model from\n"
00019     "  -n (generate count)\n"
00020     "      Number of lines to generate\n"
00021     "  \n"
00022     "Usage: \n"
00023     "  markov.exe -if empty_model.mdl -ef model.mdl\n"
00024     "      import empty_model.mdl and train it with data from stdin. When done, output the model to
00025     model.mdl\n"
00026     "  \n"
00027     "  markov.exe -if empty_model.mdl -n 15000 -of wordlist.txt\n"
00028     "      import empty_model.mdl and generate 15000 words to wordlist.txt\n"
00029     << std::endl;
00030 }

```

9.5 argparse.h File Reference


```

#include <string>


```

```
#include <iostream>
#include <boost/program_options.hpp>
```

Include dependency graph for argparse.h:



This graph shows which files directly or indirectly include this file:



Classes

- struct [Markov::API::CLI::_programOptions](#)
Structure to hold parsed cli arguments.
- class [Markov::API::CLI::Argparse](#)
Parse command line arguments.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords](#) API.
- [Markov::API::CLI](#)
Structure to hold parsed cli arguments.

Macros

- #define [BOOST_ALL_DYN_LINK](#) 1

Typedefs

- typedef struct [Markov::API::CLI::_programOptions](#) [Markov::API::CLI::ProgramOptions](#)

Structure to hold parsed cli arguments.

9.5.1 Macro Definition Documentation

9.5.1.1 BOOST_ALL_DYN_LINK

```
#define BOOST_ALL_DYN_LINK 1
```

Definition at line 4 of file [argparse.h](#).

9.6 argparse.h

```
00001 #include<string>
00002 #include<iostream>
00003
00004 #define BOOST_ALL_DYN_LINK 1
00005
00006 #include <boost/program_options.hpp>
00007
00008 /** @brief Structure to hold parsed cli arguments.
00009 */
00010 namespace opt = boost::program_options;
00011
00012 /**
00013     @brief Namespace for the CLI objects
00014 */
00015 namespace Markov::API::CLI{
00016
00017     /** @brief Structure to hold parsed cli arguments. */
00018     typedef struct _programOptions {
00019         /**
00020             @brief Import flag to validate import
00021         */
00022         bool bImport;
00023
00024         /**
00025             @brief Export flag to validate export
00026         */
00027         bool bExport;
00028
00029         /**
00030             @brief Failure flag to validate succesfull running
00031         */
00032         bool bFailure;
00033
00034         /**
00035             @brief Seperator character to use with training data. (character between occurence and
00036             value)"
00037         */
00038         char seperator;
00039
00040         /**
00041             @brief Import name of our model
00042         */
00043         std::string importname;
00044
00045         /**
00046             @brief Import name of our given wordlist
00047         */
00048         std::string exportname;
00049
00050         /**
00051             @brief Import name of our given wordlist
00052         */
00053         std::string wordlistname;
00054
00055         /**
00056             @brief Output name of our generated password list
00057         */
00058         std::string outputfilename;
00059
00060         /**
00061             @brief The name of the given dataset
00062         */
00063         std::string datasetname;
```

```

00063
00064     /**
00065      * @brief Number of passwords to be generated
00066      */
00067     int generateN;
00068
00069 } ProgramOptions;
00070
00071
00072 /** @brief Parse command line arguments
00073 */
00074 class Argparse {
00075 public:
00076
00077     Argparse();
00078
00079     /** @brief Parse command line arguments.
00080      *
00081      * Parses command line arguments to populate ProgramOptions structure.
00082      *
00083      * @param argc Number of command line arguments
00084      * @param argv Array of command line parameters
00085      */
00086     Argparse(int argc, char** argv) {
00087
00088         /*bool bImp;
00089         bool bExp;
00090         bool bFail;
00091         char sptr;
00092         std::string imports;
00093         std::string exports;
00094         std::string outputs;
00095         std::string datasets;
00096         int generateN;
00097         */
00098         opt::options_description desc("Options");
00099
00100
00101         desc.add_options()
00102             ("generate", "Generate strings with given parameters")
00103             ("train", "Train model with given parameters")
00104             ("combine", "Combine")
00105             ("import", opt::value<std::string>(), "Import model file")
00106             ("output", opt::value<std::string>(), "Output model file. This model will be exported
when done. Will be ignored for generation mode")
00107             ("dataset", opt::value<std::string>(), "Dataset file to read input from training. Will
be ignored for generation mode")
00108             ("separator", opt::value<char>(), "Separator character to use with training data.
(character between occurrence and value)")
00109             ("wordlist", opt::value<std::string>(), "Wordlist file path to export generation
results to. Will be ignored for training mode")
00110             ("count", opt::value<int>(), "Number of lines to generate. Ignored in training mode")
00111             ("verbosity", "Output verbosity")
00112             ("help", "Option definitions");
00113
00114         opt::variables_map vm;
00115
00116         opt::store(opt::parse_command_line(argc, argv, desc), vm);
00117
00118         opt::notify(vm);
00119
00120         //std::cout << desc << std::endl;
00121         if (vm.count("help")) {
00122             std::cout << desc << std::endl;
00123         }
00124
00125         if (vm.count("output") == 0) this->po.outputfilename = "NULL";
00126         else if (vm.count("output") == 1) {
00127             this->po.outputfilename = vm["output"].as<std::string>();
00128             this->po.bExport = true;
00129         }
00130         else {
00131             this->po.bFailure = true;
00132             std::cout << "UNIDENTIFIED INPUT" << std::endl;
00133             std::cout << desc << std::endl;
00134         }
00135
00136         if (vm.count("dataset") == 0) this->po.datasetname = "NULL";
00137         else if (vm.count("dataset") == 1) {
00138             this->po.datasetname = vm["dataset"].as<std::string>();
00139         }
00140         else {
00141             this->po.bFailure = true;
00142             std::cout << "UNIDENTIFIED INPUT" << std::endl;
00143             std::cout << desc << std::endl;
00144         }
00145     }

```



```

00146
00147
00148         if (vm.count("wordlist") == 0) this->po.wordlistname = "NULL";
00149     else if (vm.count("wordlist") == 1) {
00150         this->po.wordlistname = vm["wordlist"].as<std::string>();
00151     }
00152     else {
00153         this->po.bFailure = true;
00154         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00155         std::cout << desc << std::endl;
00156     }
00157
00158     if (vm.count("import") == 0) this->po.importname = "NULL";
00159     else if (vm.count("import") == 1) {
00160         this->po.importname = vm["import"].as<std::string>();
00161         this->po.bImport = true;
00162     }
00163     else {
00164         this->po.bFailure = true;
00165         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00166         std::cout << desc << std::endl;
00167     }
00168
00169
00170     if (vm.count("count") == 0) this->po.generateN = 0;
00171     else if (vm.count("count") == 1) {
00172         this->po.generateN = vm["count"].as<int>();
00173     }
00174     else {
00175         this->po.bFailure = true;
00176         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00177         std::cout << desc << std::endl;
00178     }
00179
00180     /*std::cout << vm["output"].as<std::string>() << std::endl;
00181     std::cout << vm["dataset"].as<std::string>() << std::endl;
00182     std::cout << vm["wordlist"].as<std::string>() << std::endl;
00183     std::cout << vm["output"].as<std::string>() << std::endl;
00184     std::cout << vm["count"].as<int>() << std::endl;*/
00185
00186
00187     //else if (vm.count("train")) std::cout << "train oldu" << std::endl;
00188 }
00189
00190 /** @brief Getter for command line options
00191  *
00192  * Getter for ProgramOptions populated by the argument parser
00193  * @returns ProgramOptions structure.
00194  */
00195 Markov::API::CLI::ProgramOptions getProgramOptions(void) {
00196     return this->po;
00197 }
00198
00199 /** @brief Initialize program options structure.
00200  *
00201  * @param i boolean, true if import operation is flagged
00202  * @param e boolean, true if export operation is flagged
00203  * @param bf boolean, true if there is something wrong with the command line parameters
00204  * @param s separator character for the import function
00205  * @param iName import filename
00206  * @param exName export filename
00207  * @param oName output filename
00208  * @param dName corpus filename
00209  * @param n number of passwords to be generated
00210  *
00211  */
00212 void setProgramOptions(bool i, bool e, bool bf, char s, std::string iName, std::string exName,
00213     std::string oName, std::string dName, int n) {
00214     this->po.bImport = i;
00215     this->po.bExport = e;
00216     this->po.separator = s;
00217     this->po.bFailure = bf;
00218     this->po.generateN = n;
00219     this->po.importname = iName;
00220     this->po.exportname = exName;
00221     this->po.outputfilename = oName;
00222     this->po.datasetname = dName;
00223
00224     /*strcpy_s(this->po.importname,256,iName);
00225     strcpy_s(this->po.exportname,256,exName);
00226     strcpy_s(this->po.outputfilename,256,oName);
00227     strcpy_s(this->po.datasetname,256,dName);*/
00228 }
00229
00230 /** @brief parse cli commands and return
00231  * @param argc - Program argument count

```

```

00232      * @param argv - Program argument values array
00233      * @return ProgramOptions structure.
00234      */
00235      static Markov::API::CLI::ProgramOptions* parse(int argc, char** argv);
00236
00237
00238      /** @brief Print help string.
00239      */
00240      static void help();
00241
00242  private:
00243      /**
00244       * @brief ProgramOptions structure object
00245       */
00246
00247      Markov::API::CLI::ProgramOptions po;
00248  };
00249
00250  };

```


9.7 CLI.h File Reference

```


#include <QtWidgets/QMainWindow>
#include "ui_CLI.h"

```

Include dependency graph for CLI.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::GUI::CLI](#)
QT CLI Class.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::GUI](#)

namespace for MarkovPasswords [API GUI](#) wrapper

9.8 CLI.h

```

00001 #pragma once
00002 #include <QtWidgets/QMainWindow>
00003 #include "ui_CLI.h"
00004
00005 namespace Markov::GUI{
00006     /** @brief QT CLI Class
00007     */
00008     class CLI :public QMainWindow {
00009         Q_OBJECT
00010     public:
00011         CLI(QWidget* parent = Q_NULLPTR);
00012
00013     private:
00014         Ui::CLI ui;
00015
00016     public slots:
00017         void start();
00018         void statistics();
00019         void about();
00020     };
00021 };

```


9.9 cudaDeviceController.h File Reference

```


#include <iostream>
#include <curand_kernel.h>
#include <cuda.h>
#include <cuda_runtime.h>
#include <device_launch_parameters.h>

```

Include dependency graph for cudaDeviceController.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::CUDA::CUDADeviceController](#)
Controller class for [CUDA](#) device.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords API](#).
- [Markov::API::CUDA](#)
Namespace for objects requiring [CUDA](#) libraries.

9.10 cudaDeviceController.h

```

00001
00002 #pragma once
00003 #include <iostream>
00004 #include <curand_kernel.h>
00005 #include <cuda.h>
00006 #include <cuda_runtime.h>
00007 #include <device_launch_parameters.h>
00008
00009 /** @brief Namespace for objects requiring CUDA libraries.
00010 */
00011 namespace Markov::API::CUDA{
00012     /** @brief Controller class for CUDA device
00013      *
00014      * This implementation only supports Nvidia devices.
00015      */
00016     class CUDADeviceController{
00017     public:
00018         /** @brief List CUDA devices in the system.
00019          *
00020          * This function will print details of every CUDA capable device in the system.
00021          *
00022          * @b Example @b output:
00023          * @code{.txt}
00024          * Device Number: 0
00025          * Device name: GeForce RTX 2070
00026          * Memory Clock Rate (KHz): 7001000
00027          * Memory Bus Width (bits): 256
00028          * Peak Memory Bandwidth (GB/s): 448.064
00029          * Max Linear Threads: 1024
00030          * @endcode
00031          */
00032         __host__ static void ListCudaDevices();
00033
00034     protected:
00035         /** @brief Check results of the last operation on GPU.

```

```

00036      *
00037      * Check the status returned from cudaMalloc/cudaMemcpy to find failures.
00038      *
00039      * If a failure occurs, its assumed beyond redemption, and exited.
00040      * @param _status Cuda error status to check
00041      * @param msg Message to print in case of a failure
00042      * @return 0 if successful, 1 if failure.
00043      * @b Example @b output:
00044      * @code{.cpp}
00045      * char *da, a = "test";
00046      * cudastatus = cudaMalloc((char **)&da, 5*sizeof(char*));
00047      * CudaCheckNotifyErr(cudastatus, "Failed to allocate VRAM for *da.\n");
00048      * @endcode
00049      */
00050      __host__ static int CudaCheckNotifyErr(cudaError_t _status, const char* msg, bool bExit=true);
00051
00052
00053      /** @brief Malloc a 2D array in device space
00054      *
00055      * This function will allocate enough space on VRAM for flattened 2D array.
00056      *
00057      * @param dst destination pointer
00058      * @param row row size of the 2d array
00059      * @param col column size of the 2d array
00060      * @return cudaError_t status of the cudaMalloc operation
00061      *
00062      * @b Example @b output:
00063      * @code{.cpp}
00064      * cudaError_t cudastatus;
00065      * char* dst;
00066      * cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
00067      * if(cudastatus!=cudaSuccess){
00068      *     CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
00069      * }
00070      * @endcode
00071      */
00072      template <typename T>
00073      __host__ static cudaError_t CudaMalloc2DToFlat(T** dst, int row, int col){
00074          cudaError_t cudastatus = cudaMalloc((T **)&dst, row*col*sizeof(T));
00075          CudaCheckNotifyErr(cudastatus, "cudaMalloc Failed.", false);
00076          return cudastatus;
00077      }
00078
00079
00080      /** @brief Malloc a 2D array in device space after flattening
00081      *
00082      * Resulting buffer will not be true 2D array.
00083      *
00084      * @param dst destination pointer
00085      * @param rc source pointer
00086      * @param row row size of the 2d array
00087      * @param col column size of the 2d array
00088      * @return cudaError_t status of the cudaMalloc operation
00089      *
00090      * @b Example @b output:
00091      * @code{.cpp}
00092      * cudaError_t cudastatus;
00093      * char* dst;
00094      * cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
00095      * CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
00096      * cudastatus = CudaMemcpy2DToFlat<char>(*dst,src,15,15);
00097      * CudaCheckNotifyErr(cudastatus, " CudaMemcpy2DToFlat Failed.", false);
00098      * @endcode
00099      */
00100      template <typename T>
00101      __host__ static cudaError_t CudaMemcpy2DToFlat(T* dst, T** src, int row, int col){
00102          T* tempbuf = new T[row*col];
00103          for(int i=0;i<row;i++){
00104              memcpy(&(tempbuf[row*i]), src[i], col);
00105          }
00106          return cudaMemcpy(dst, tempbuf, row*col*sizeof(T), cudaMemcpyHostToDevice);
00107      }
00108
00109
00110      /** @brief Both malloc and memcpy a 2D array into device VRAM.
00111      *
00112      * Resulting buffer will not be true 2D array.
00113      *
00114      * @param dst destination pointer
00115      * @param rc source pointer
00116      * @param row row size of the 2d array
00117      * @param col column size of the 2d array
00118      * @return cudaError_t status of the cudaMalloc operation
00119      *
00120      * @b Example @b output:
00121      * @code{.cpp}
00122      * cudaError_t cudastatus;

```

```

00123     *   char* dst;
00124     *   cudastatus = CudaMigrate2DFlat<long int>(
00125     *       &dst, this->valueMatrix, this->matrixSize);
00126     *   CudaCheckNotifyErr(cudastatus, "   Cuda failed to initialize value matrix row.");
00127     * @endcode
00128     */
00129     template <typename T>
00130     __host__ static cudaError_t CudaMigrate2DFlat(T** dst, T** src, int row, int col){
00131         cudaError_t cudastatus;
00132         cudastatus = CudaMalloc2DToFlat<T>(dst, row, col);
00133         if(cudastatus!=cudaSuccess){
00134             CudaCheckNotifyErr(cudastatus, "   CudaMalloc2DToFlat Failed.", false);
00135             return cudastatus;
00136         }
00137         cudastatus = CudaMemcpy2DToFlat<T>(*dst,src,row,col);
00138         CudaCheckNotifyErr(cudastatus, "   CudaMemcpy2DToFlat Failed.", false);
00139         return cudastatus;
00140     }
00141
00142     private:
00143     };
00144
00145 };


```

9.11 cudaModelMatrix.h File Reference

```
#include "MarkovPasswords/src/modelMatrix.h"
```

```
#include "cudaDeviceController.h"
```

Include dependency graph for cudaModelMatrix.h:



Classes

- class [Markov::API::CUDA::CUDAModelMatrix](#)
Extension of [Markov::API::ModelMatrix](#) which is modified to run on GPU devices.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords API](#).
- [Markov::API::CUDA](#)
Namespace for objects requiring [CUDA](#) libraries.

Functions

- __global__ void [Markov::API::CUDA::FastRandomWalkCUDAKernel](#) (unsigned long int n, int minLen, int maxLen, char *outputBuffer, char *matrixIndex, long int *totalEdgeWeights, long int *valueMatrix, char *edgeMatrix, int matrixSize, int memoryPerKernelGrid, unsigned long *seed)
[CUDA](#) kernel for the [FastRandomWalk](#) operation.

- `__device__ char * Markov::API::CUDA::strchr (char *p, char c, int s_len)`
strchr implementation on device space

9.12 cudaModelMatrix.h

```

00001 #include "MarkovPasswords/src/modelMatrix.h"
00002 #include "cudaDeviceController.h"
00003
00004 /** @brief Namespace for objects requiring CUDA libraries.
00005 */
00006 namespace Markov::API::CUDA{
00007     /** @brief Extension of Markov::API::ModelMatrix which is modified to run on GPU devices.
00008     *
00009     * This implementation only supports Nvidia devices.
00010     */
00011     class CUDAModelMatrix : public ModelMatrix, public CUDADeviceController{
00012     public:
00013
00014         /** @brief Migrate the class members to the VRAM
00015         *
00016         * Cannot be used without calling Markov::API::ModelMatrix::ConstructMatrix at least once.
00017         * This function will manage the memory allocation and data transfer from CPU RAM to GPU VRAM.
00018         *
00019         * Newly allocated VRAM pointers are set in the class member variables.
00020         */
00021         __host__ void MigrateMatrix();
00022
00023
00024         /** @brief Flatten migrated matrix from 2d to 1d
00025         *
00026         */
00027         __host__ void FlattenMatrix();
00028
00029
00030         /** @brief Random walk on the Matrix-reduced Markov::Model
00031         *
00032         * TODO
00033         *
00034         * @param n - Number of passwords to generate.
00035         * @param wordlistFileName - Filename to write to
00036         * @param minLen - Minimum password length to generate
00037         * @param maxLen - Maximum password length to generate
00038         * @param threads - number of OS threads to spawn
00039         * @param bFileIO - If false, filename will be ignored and will output to stdout.
00040         */
00041         __host__ void FastRandomWalk(unsigned long int n, const char* wordlistFileName, int minLen,
00042                                     int maxLen, bool bFileIO);
00043
00044     protected:
00045
00046         /** @brief Allocate the output buffer for kernel operation
00047         *
00048         * TODO
00049         *
00050         * @param n - Number of passwords to generate.
00051         * @param singleGenMaxLen - maximum string length for a single generation
00052         * @param CUDAKernelGridSize - Total number of grid members in CUDA kernel
00053         * @param sizePerGrid - Size to allocate per grid member
00054         * @return pointer to the allocation on VRAM
00055         */
00056         __host__ char* AllocVRAMOutputBuffer(long int n, long int singleGenMaxLen, long int
00057                                             CUDAKernelGridSize, long int sizePerGrid);
00058     private:
00059
00060         /**
00061         * @brief VRAM Address pointer of edge matrix (from modelMatrix.h)
00062         */
00063         char* device_edgeMatrix;
00064
00065         /**
00066         * @brief VRAM Address pointer of value matrix (from modelMatrix.h)
00067         */

```

```

00078     long int *device_valueMatrix;
00079
00080     /**
00081      * @brief VRAM Address pointer of matrixIndex (from modelMatrix.h)
00082      */
00083     char *device_matrixIndex;
00084
00085     /**
00086      * @brief VRAM Address pointer of total edge weights (from modelMatrix.h)
00087      */
00088     long int *device_totalEdgeWeights;
00089
00090
00091     /**
00092      * @brief RandomWalk results in device
00093      */
00094     char* device_outputBuffer;
00095
00096     /**
00097      * @brief RandomWalk results in host
00098      */
00099     char* outputBuffer;
00100
00101     /**
00102      * @brief Adding Edge matrix end-to-end and resize to 1-D array for better performance on
traversing
00103      */
00104     char* flatEdgeMatrix;
00105
00106     /**
00107      * @brief Adding Value matrix end-to-end and resize to 1-D array for better performance on
traversing
00108      */
00109     long int* flatValueMatrix;
00110
00111 };
00112
00113 /** @brief CUDA kernel for the FastRandomWalk operation
00114  *
00115  * Will be initiated by CPU and continued by GPU (__global__ tag)
00116  *
00117  *
00118  * @param n - Number of passwords to generate.
00119  * @param minlen - minimum string length for a single generation
00120  * @param maxlen - maximum string length for a single generation
00121  * @param outputBuffer - VRAM ptr to the output buffer
00122  * @param matrixIndex - VRAM ptr to the matrix indices
00123  * @param totalEdgeWeights - VRAM ptr to the totalEdgeWeights array
00124  * @param valueMatrix - VRAM ptr to the edge weights array
00125  * @param edgeMatrix - VRAM ptr to the edge representations array
00126  * @param matrixSize - Size of the matrix dimensions
00127  * @param memoryPerKernelGrid - Maximum memory usage per kernel grid
00128  * @param seed - seed chunk to generate the random from (generated & used by Marsaglia)
00129  *
00130  *
00131  */
00132 __global__ void FastRandomWalkCUKADKernel(unsigned long int n, int minLen, int maxLen, char*
outputBuffer,
00133     char* matrixIndex, long int* totalEdgeWeights, long int* valueMatrix, char *edgeMatrix,
00134     int matrixSize, int memoryPerKernelGrid, unsigned long *seed); //, unsigned long mex, unsigned
long mey, unsigned long mez);
00136
00137
00138 /** @brief srtchr implementation on __device__ space
00139  *
00140  * Find the first matching index of a string
00141  *
00142  *
00143  * @param p - string to check
00144  * @param c - character to match
00145  * @param s_len - maximum string length
00146  * @returns pointer to the match
00147  */
00148 __device__ char* srtchr(char* p, char c, int s_len);
00149
00150 };

```


9.13 cudarandom.h File Reference

```

#include "MarkovModel/src/random.h"
#include "CudaMarkovPasswords/src/cudaDeviceController.h"

```


Include dependency graph for `cularandom.h`:



Classes

- class [Markov::API::CUDA::Random::Marsaglia](#)

Extension of [Markov::Random::Marsaglia](#) which is capable o working on **device** space.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::API](#)

Namespace for the [MarkovPasswords API](#).

- [Markov::API::CUDA](#)

Namespace for objects requiring [CUDA](#) libraries.

- [Markov::API::CUDA::Random](#)

Namespace for [Random](#) engines operable under **device** space.

Functions

- `__device__ unsigned long Markov::API::CUDA::Random::devrandom (unsigned long &x, unsigned long &y, unsigned long &z)`

[Marsaglia Random](#) Generation function operable in **device** space.

9.14 cularandom.h

```

00001 #pragma once
00002 #include "MarkovModel/src/random.h"
00003 #include "CudaMarkovPasswords/src/cudaDeviceController.h"
00004
00005 /** @brief Namespace for Random engines operable under __device__ space.
00006 */
00007 namespace Markov::API::CUDA::Random{
00008
00009     /** @brief Extension of Markov::Random::Marsaglia which is capable o working on __device__ space.
00010     */
00011     class Marsaglia : public Markov::Random::Marsaglia, public CUDADeviceController{
00012     public:
00013
00014         /** @brief Migrate a Marsaglia[] to VRAM as seedChunk
00015         * @param MEarr Array of Marsaglia Engines
00016         * @param gridSize GridSize of the CUDA Kernel, aka size of array
00017         * @returns pointer to the resulting seed chunk in device VRAM.
00018         */
00019         static unsigned long* MigrateToVRAM(Markov::API::CUDA::Random::Marsaglia *MEarr, long int
gridSize){
00020             cudaError_t cudastatus;
00021             unsigned long* seedChunk;
00022             cudastatus = cudaMalloc((unsigned long*)&seedChunk, gridSize*3*sizeof(unsigned long));
00023             CudaCheckNotifyErr(cudastatus, "Failed to allocate seed buffer");
00024             unsigned long *temp = new unsigned long[gridSize*3];
00025             for(int i=0;i<gridSize;i++){
00026                 temp[i*3] = MEarr[i].x;
00027                 temp[i*3+1] = MEarr[i].y;
00028                 temp[i*3+2] = MEarr[i].z;

```

```

00029         }
00030         //for(int i=0;i<gridSize*3;i++) std::cout << temp[i] << "\n";
00031         cudaMemcpy(seedChunk, temp, gridSize*3*sizeof(unsigned long), cudaMemcpyHostToDevice);
00032         CudaCheckNotifyErr(cudastatus, "Failed to memcpy seed buffer.");
00033         return seedChunk;
00034     }
00035 };
00036
00037 /** @brief Marsaglia Random Generation function operable in __device__ space
00038  * @param x marsaglia internal x. Not constant, (ref)
00039  * @param y marsaglia internal y. Not constant, (ref)
00040  * @param z marsaglia internal z. Not constant, (ref)
00041  * @returns returns z
00042  */
00043 __device__ unsigned long devrandom(unsigned long &x, unsigned long &y, unsigned long &z){
00044     unsigned long t;
00045     x ^= x << 16;
00046     x ^= x >> 5;
00047     x ^= x << 1;
00048
00049     t = x;
00050     x = y;
00051     y = z;
00052     z = t ^ x ^ y;
00053
00054     return z;
00055 }
00056 };

```


9.15 dllmain.cpp File Reference

```

#include "pch.h"
#include "model.h"
#include <iostream>

```

Include dependency graph for dllmain.cpp:



9.16 dllmain.cpp

```

00001 #include "pch.h"
00002 #include "model.h"
00003 #include <iostream>
00004
00005
00006 #ifdef _WIN32
00007 __declspec(dllexport) void dll_loadtest() {
00008     std::cout << "External function called.\n";
00009     //cudaTestEntry();
00010 }
00011
00012 BOOL APIENTRY DllMain(HMODULE hModule, DWORD ul_reason_for_call, LPVOID lpReserved)
00013 {
00014     switch (ul_reason_for_call)
00015     {
00016     case DLL_PROCESS_ATTACH:
00017     case DLL_THREAD_ATTACH:
00018     case DLL_THREAD_DETACH:
00019     case DLL_PROCESS_DETACH:
00020         break;
00021     }

```


Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

9.18 edge.h

```

00001 #pragma once
00002 #include <cstdint>
00003 #include <cstddef>
00004
00005 namespace Markov {
00006
00007     template <typename NodeStorageType>
00008     class Node;
00009
00010     /** @brief Edge class used to link nodes in the model together.
00011     *
00012     * Has LeftNode, RightNode, and EdgeWeight of the edge.
00013     * Edges are *UNIDIRECTIONAL* in this model. They can only be traversed LeftNode to RightNode.
00014     */
00015     template <typename NodeStorageType>
00016     class Edge {
00017     public:
00018
00019         /** @brief Default constructor.
00020         */
00021         Edge<NodeStorageType>();
00022
00023         /** @brief Constructor. Initialize edge with given RightNode and LeftNode
00024         * @param _left - Left node of this edge.
00025         * @param _right - Right node of this edge.
00026         *
00027         * @b Example @b Use: Construct edge
00028         * @code{.cpp}
00029         * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00030         * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00031         * Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00032         * @endcode
00033         */
00034         Edge<NodeStorageType>(Node<NodeStorageType>* _left, Node<NodeStorageType>* _right);
00035
00036         /** @brief Adjust the edge EdgeWeight with offset.
00037         * Adds the offset parameter to the edge EdgeWeight.
00038         * @param offset - NodeValue to be added to the EdgeWeight
00039         *
00040         * @b Example @b Use: Construct edge
00041         * @code{.cpp}
00042         * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00043         * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00044         * Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00045         *
00046         * e1->AdjustEdge(25);
00047         *
00048         * @endcode
00049         */
00050         void AdjustEdge(long int offset);
00051
00052         /** @brief Traverse this edge to RightNode.
00053         * @return Right node. If this is a terminator node, return NULL
00054         *
00055         * @b Example @b Use: Traverse a node
00056         * @code{.cpp}
00057         * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00058         * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00059         * Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00060         *
00061         * e1->AdjustEdge(25);
00062         * Markov::Edge<unsigned char>* e2 = e1->traverseNode();
00063         * @endcode
00064         */
00065         inline Node<NodeStorageType>* TraverseNode();
00066
00067         /** @brief Set LeftNode of this edge.
00068         * @param node - Node to be linked with.
00069         */
00070         void SetLeftEdge (Node<NodeStorageType>*>);
00071
00072         /** @brief Set RightNode of this edge.
00073         * @param node - Node to be linked with.
00074         */
00075         void SetRightEdge (Node<NodeStorageType>*>);
00076
00077         /** @brief return edge's EdgeWeight.
00078         * @return edge's EdgeWeight.
00079         */
00080         inline Node<NodeStorageType>* EdgeWeight();
00081     };

```


```

00082         inline uint64_t EdgeWeight();
00083
00084         /** @brief return edge's LeftNode
00085         * @return edge's LeftNode.
00086         */
00087         Node<NodeStorageType>* LeftNode();
00088
00089         /** @brief return edge's RightNode
00090         * @return edge's RightNode.
00091         */
00092         inline Node<NodeStorageType>* RightNode();
00093
00094     private:
00095         /**
00096          * @brief source node
00097          */
00098         Node<NodeStorageType>* _left;
00099
00100         /**
00101          * @brief target node
00102          */
00103         Node<NodeStorageType>* _right;
00104
00105         /** @brief
00106          * Edge Edge Weight
00107          */
00108         long int _weight;
00109     };
00110
00111
00112 };
00113
00114 //default constructor of edge
00115 template <typename NodeStorageType>
00116 Markov::Edge<NodeStorageType>::Edge() {
00117     this->_left = NULL;
00118     this->_right = NULL;
00119     this->_weight = 0;
00120 }
00121 //constructor of edge
00122 template <typename NodeStorageType>
00123 Markov::Edge<NodeStorageType>::Edge(Markov::Node<NodeStorageType>* _left,
00124     Markov::Node<NodeStorageType>* _right) {
00125     this->_left = _left;
00126     this->_right = _right;
00127     this->_weight = 0;
00128 }
00129 //to AdjustEdge the edges by the edge with its offset
00130 template <typename NodeStorageType>
00131 void Markov::Edge<NodeStorageType>::AdjustEdge(long int offset) {
00132     this->_weight += offset;
00133     this->LeftNode()->UpdateTotalVerticeWeight(offset);
00134 }
00135 //to TraverseNode the node
00136 template <typename NodeStorageType>
00137 inline Markov::Node<NodeStorageType>* Markov::Edge<NodeStorageType>::TraverseNode() {
00138     if (this->RightNode()->NodeValue() == 0xff) //terminator node
00139         return NULL;
00140     return _right;
00141 }
00142 //to set the LeftNode of the node
00143 template <typename NodeStorageType>
00144 void Markov::Edge<NodeStorageType>::SetLeftEdge(Markov::Node<NodeStorageType>* n) {
00145     this->_left = n;
00146 }
00147 //to set the RightNode of the node
00148 template <typename NodeStorageType>
00149 void Markov::Edge<NodeStorageType>::SetRightEdge(Markov::Node<NodeStorageType>* n) {
00150     this->_right = n;
00151 }
00152 //to get the EdgeWeight of the node
00153 template <typename NodeStorageType>
00154 inline uint64_t Markov::Edge<NodeStorageType>::EdgeWeight() {
00155     return this->_weight;
00156 }
00157 //to get the LeftNode of the node
00158 template <typename NodeStorageType>
00159 Markov::Node<NodeStorageType>* Markov::Edge<NodeStorageType>::LeftNode() {
00160     return this->_left;
00161 }
00162 //to get the RightNode of the node
00163 template <typename NodeStorageType>
00164 inline Markov::Node<NodeStorageType>* Markov::Edge<NodeStorageType>::RightNode() {
00165     return this->_right;
00166 }

```

9.19 framework.h File Reference

This graph shows which files directly or indirectly include this file:



Macros

- `#define WIN32_LEAN_AND_MEAN`

9.19.1 Macro Definition Documentation

9.19.1.1 WIN32_LEAN_AND_MEAN

```
#define WIN32_LEAN_AND_MEAN
```

Definition at line 3 of file [framework.h](#).

9.20 framework.h


```
00001 #pragma once
00002
00003 #define WIN32_LEAN_AND_MEAN           // Exclude rarely-used stuff from Windows headers
00004 // Windows Header Files
00005
00006 #ifdef _WIN32
00007 #include <windows.h>
00008 #endif
```

9.21 main.cpp File Reference

```
#include <iostream>
#include "color/term.h"
#include "argparse.h"
#include <string>
#include <cstring>
#include <sstream>
#include "markovPasswords.h"
#include "modelMatrix.h"
```

```
#include <chrono>
```

Include dependency graph for src/main.cpp:



Functions

- `int main (int argc, char **argv)`

Launch CLI tool.

9.21.1 Function Documentation

9.21.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

Launch CLI tool.


Definition at line 14 of file `src/main.cpp`.

```

00014         {
00015
00016             Markov::API::CLI::Terminal t;
00017             /*
00018             ProgramOptions* p = Argparse::parse(argc, argv);
00019
00020             if (p==0 || p->bFailure) {
00021                 std::cout << TERM_FAIL << "Arguments Failed to Parse" << std::endl;
00022                 Argparse::help();
00023             }*/
00024             Markov::API::CLI::Argparse a(argc,argv);
00025
00026             Markov::API::ModelMatrix mp;
00027
00028             mp.Import("Markopy/src/CLI/sample_models/2gram.mdl");
00029             mp.Train("datasets/graduation.corpus", '\t', 1);
00030             mp.Export("test.mdl");
00031             return 0; /*
00032             std::cerr << "Importing model.\n";
00033             markovPass.Import("models/finished.mdl");
00034             std::cerr << "Import done. \n";
00035             markovPass.ConstructMatrix();
00036             std::chrono::steady_clock::time_point begin = std::chrono::steady_clock::now();
00037             //markovPass.FastRandomWalk(50000000,"/media/ignis/Stuff/wordlist.txt",6,12,25, true);
00038             markovPass.FastRandomWalk(500000000,"/media/ignis/Stuff/wordlist2.txt",6,12,25, true);
00039             std::chrono::steady_clock::time_point end = std::chrono::steady_clock::now();
00040
00041             std::cerr << "Finished in:" << std::chrono::duration_cast<std::chrono::milliseconds> (end -
begin).count() << " milliseconds" << std::endl;*/
00042             return 0;
00043         }
```

References `Markov::API::CLI::Argparse::Argparse()`, `Markov::Model< NodeStorageType >::Export()`, `Markov::API::ModelMatrix::Import()` and `Markov::API::ModelMatrix::Train()`.

Here is the call graph for this function:



9.22 src/main.cpp

```

00001 #pragma once
00002 #include <iostream>
00003 #include "color/term.h"
00004 #include "argparse.h"
00005 #include <string>
00006 #include <cstring>
00007 #include <sstream>
00008 #include "markovPasswords.h"
00009 #include "modelMatrix.h"
00010 #include <chrono>
00011
00012 /** @brief Launch CLI tool.
00013 */
00014 int main(int argc, char** argv) {
00015     Markov::API::CLI::Terminal t;
00016     /*
00017     ProgramOptions* p = Argparse::parse(argc, argv);
00018
00019     if (p==0 || p->bFailure) {
00020         std::cout << TERM_FAIL << "Arguments Failed to Parse" << std::endl;
00021         Argparse::help();
00022     }*/
00023     Markov::API::CLI::Argparse a(argc,argv);
00024
00025     Markov::API::ModelMatrix mp;
00026
00027     mp.Import("Markopy/src/CLI/sample_models/2gram.mdl");
00028     mp.Train("datasets/graduation.corpus", '\t', 1);
00029     mp.Export("test.mdl");
00030     return 0; /*
00031     std::cerr << "Importing model.\n";
00032     markovPass.Import("models/finished.mdl");
00033     std::cerr << "Import done. \n";
00034     markovPass.ConstructMatrix();
00035     std::chrono::steady_clock::time_point begin = std::chrono::steady_clock::now();
00036     //markovPass.FastRandomWalk(50000000,"/media/ignis/Stuff/wordlist.txt",6,12,25, true);
00037     markovPass.FastRandomWalk(50000000,"/media/ignis/Stuff/wordlist2.txt",6,12,25, true);
00038     std::chrono::steady_clock::time_point end = std::chrono::steady_clock::now();
00039
00040     std::cerr << "Finished in:" << std::chrono::duration_cast<std::chrono::milliseconds>(end -
00041     begin).count() << " milliseconds" << std::endl;*/
00042     return 0;
00043 }

```


9.23 main.cpp File Reference

```

#include "menu.h"
#include <QtWidgets/QApplication>
#include <QSplashScreen>
#include <QDateTime>
#include "CLI.h"

```


Include dependency graph for UI/src/main.cpp:



Functions

- int [main](#) (int argc, char *argv[])
Launch UI.

9.23.1 Function Documentation

9.23.1.1 main()

```
int main (
    int argc,
    char * argv[ ] )
```

Launch UI.


Definition at line 12 of file [UI/src/main.cpp](#).

```

00013 {
00014
00015
00016
00017     QApplication a(argc, argv);
00018
00019     QPixmap loadingPix("views/startup.jpg");
00020     QSplashScreen splash(loadingPix);
00021     splash.show();
00022     QDateTime time = QDateTime::currentDateTime();
00023     QDateTime currentTime = QDateTime::currentDateTime(); //Record current time
00024     while (time.secsTo(currentTime) <= 5) //5 is the number of seconds to delay
00025     {
00026         currentTime = QDateTime::currentDateTime();
00027         a.processEvents();
00028     };
00029
00030
00031     CLI w;
00032     w.show();
00033     splash.finish(&w);
00034     return a.exec();
00035 }
```

References [Markov::GUI::CLI::start\(\)](#).

Here is the call graph for this function:



9.24 UI/src/main.cpp

```

00001 //include "MarkovPasswordsGUI.h"
00002 #include "menu.h"
00003 #include <QtWidgets/QApplication>
00004 #include <QSplashScreen>
00005 #include < QDateTime >
00006 #include "CLI.h"
00007
00008 using namespace Markov::GUI;
00009
00010 /** @brief Launch UI.
00011 */
00012 int main(int argc, char *argv[])
00013 {
00014
00015
00016
00017     QApplication a(argc, argv);
00018
00019     QPixmap loadingPix("views/startup.jpg");
00020     QSplashScreen splash(loadingPix);
00021     splash.show();
00022     QDateTime time = QDateTime::currentDateTime();
00023     QDateTime currentTime = QDateTime::currentDateTime();    //Record current time
00024     while (time.secsTo(currentTime) <= 5)                    //5 is the number of seconds to delay
00025     {
00026         currentTime = QDateTime::currentDateTime();
00027         a.processEvents();
00028     };
00029
00030
00031     CLI w;
00032     w.show();
00033     splash.finish(&w);
00034     return a.exec();
00035 }

```


9.25 markopy.cpp File Reference

```

#include "../.../MarkovPasswords/src/markovPasswords.h"
#include <Python.h>
#include <boost/python.hpp>
#include <MarkovPasswords/src/modelMatrix.h>

```

Include dependency graph for markopy.cpp:



Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::Markopy](#)

Macros

- `#define BOOST_PYTHON_STATIC_LIB`

Functions

- `Markov::Markopy::BOOST_PYTHON_MODULE` (markopy)

9.25.1 Macro Definition Documentation

9.25.1.1 BOOST_PYTHON_STATIC_LIB

`#define BOOST_PYTHON_STATIC_LIB`

Definition at line 4 of file [markopy.cpp](#).

9.26 markopy.cpp

```

00001 #pragma once
00002 #include ".././../MarkovPasswords/src/markovPasswords.h"
00003
00004 #define BOOST_PYTHON_STATIC_LIB
00005 #include <Python.h>
00006 #include <boost/python.hpp>
00007 #include <MarkovPasswords/src/modelMatrix.h>
00008
00009 using namespace boost::python;
00010
00011 namespace Markov::Markopy{
00012     BOOST_PYTHON_MODULE(markopy)
00013     {
00014         bool (Markov::API::MarkovPasswords::Import)(const char*) = &Markov::Model<char>::Import;
00015         bool (Markov::API::MarkovPasswords::Export)(const char*) = &Markov::Model<char>::Export;
00016         class_<Markov::API::MarkovPasswords>("MarkovPasswords", init<>())
00017             .def(init<>())
00018             .def("Train", &Markov::API::MarkovPasswords::Train)
00019             .def("Generate", &Markov::API::MarkovPasswords::Generate)
00020             .def("Import", Import, "Import a model file.")
00021             .def("Export", Export, "Export a model to file.")
00022         ;
00023
00024         class_<Markov::API::ModelMatrix>("ModelMatrix", init<>())
00025
00026             .def(init<>())
00027             .def("Train", &Markov::API::ModelMatrix::Train)
00028             .def("Import", &Markov::API::ModelMatrix::Import, "Import a model file.")
00029             .def("Export", Export, "Export a model to file.")
00030             .def("ConstructMatrix", &Markov::API::ModelMatrix::ConstructMatrix)
00031             .def("DumpJSON", &Markov::API::ModelMatrix::DumpJSON)
00032             .def("FastRandomWalk", &Markov::API::ModelMatrix::FastRandomWalk)
00033         ;
00034     };
00035 };

```

9.27 markopy_cli.py File Reference

Namespaces

- [markopy_cli](#)

Functions

- def [markopy_cli.cli_init](#) (input_model)
- def [markopy_cli.cli_train](#) (model, dataset, seperator, output, output_forced=False, bulk=False)
- def [markopy_cli.cli_generate](#) (model, wordlist, bulk=False)

Variables

- `markopy_cli.parser`
- `markopy_cli.help`
- `markopy_cli.default`
- `markopy_cli.action`
- `markopy_cli.args = parser.parse_args()`
- `markopy_cli.corpus_list = os.listdir(args.dataset)`
- `def markopy_cli.model = cli_init(args.input)`
- `markopy_cli.output_file_name = corpus`
- `string markopy_cli.model_extension = ""`
- `markopy_cli.output_forced`
- `markopy_cli.True`
- `markopy_cli.bulk`
- `markopy_cli.model_list = os.listdir(args.input)`
- `markopy_cli.model_base = input`
- `markopy_cli.output`

9.28 markopy_cli.py

```

00001 #!/usr/bin/python3
00002 """
00003     @namespace Markov::Markopy::Python
00004     """
00005
00006 import markopy
00007 import argparse
00008 import allocate as logging
00009 import re
00010 import os
00011
00012 parser = argparse.ArgumentParser(description="Python wrapper for MarkovPasswords.",
00013                                 epilog=f"""Sample runs:
00014 {__file__} train untrained.mdl -d dataset.dat -s "\\t" -o trained.mdl
00015     Import untrained.mdl, train it with dataset.dat which has tab delimited data, output resulting
00016     model to trained.mdl\n
00017 {__file__} generate trained.mdl -n 500 -w output.txt
00018     Import trained.mdl, and generate 500 lines to output.txt
00019
00020 {__file__} combine untrained.mdl -d dataset.dat -s "\\t" -n 500 -w output.txt
00021     Train and immediately generate 500 lines to output.txt. Do not export trained model.
00022
00023 {__file__} combine untrained.mdl -d dataset.dat -s "\\t" -n 500 -w output.txt -o trained.mdl
00024     Train and immediately generate 500 lines to output.txt. Export trained model.
00025 """, formatter_class=argparse.RawTextHelpFormatter)
00026
00027 parser.add_argument("mode", help="Operation mode, supported modes: \"generate\", \"train\" and
00028                                \"combine\".")
00029 parser.add_argument("input", help="Input model file. This model will be imported before starting
00030                                operation.\n"
00031                                + "For more information on the file structure for input, check out
00032                                the wiki page.")
00033 parser.add_argument("-o", "--output",
00034                    help="Output model filename. This model will be exported when done. Will be
00035                    ignored for generation mode.")
00036 parser.add_argument("-d", "--dataset",
00037                    help="Dataset filename to read input from for training. Will be ignored for
00038                    generation mode.\n"
00039                    + "Dataset is occurrence of a string and the string value seperated by a
00040                    seperator. For more info "
00041                    + "on the dataset file structure, check out the github wiki page.")
00042 parser.add_argument("-s", "--seperator",
00043                    help="Seperator character to use with training data. (character between occurrence
00044                    and value)\n"
00045                    + "For more information on dataset/corpus file structure, check out the github
00046                    wiki.")
00047 parser.add_argument("-w", "--wordlist",
00048                    help="Wordlist filename path to export generation results to. Will be ignored for
00049                    training mode")
00050 parser.add_argument("--min", default=6, help="Minimum length that is allowed during generation.\n"
00051                    + "Any string shorter than this parameter will retry to continue instead of
00052                    proceeding to "
00053                    + "finishing node")
00054 parser.add_argument("--max", default=12, help="Maximum length that is allowed during generation.\n")

```

```

00045         + "Any string that does reaches this length are cut off irregardless to their
           position on the model.")
00046 parser.add_argument("-n", "--count", help="Number of lines to generate. Ignored in training mode.")
00047 parser.add_argument("-t", "--threads", default=10, help="Number of threads to use with
           training/generation.\n")
00048         + "This many OS threads will be created for training/generation functions")
00049 parser.add_argument("-v", "--verbosity", action="count", help="Output verbosity.\n")
00050         + "Set verbosity to 1: -v\n"
00051         + "Set verbosity to 3: -vvv\n"
00052         + "Print pretty much everything, including caller functions: -vvvvvvvvvvvvvvv")
00053 parser.add_argument("-b", "--bulk", action="store_true",
00054         help="Bulk generate or bulk train every corpus/model in the folder.\n"
00055         + "If working on this mode, output/input/dataset parameters should be a folder.\n"
00056         + "Selected operation (generate/train) will be applied to each file in the folder,
           and "
00057         + "output to the output directory.")
00058 args = parser.parse_args()
00059
00060
00061 def cli_init(input_model):
00062     logging.VERBOSITY = 0
00063     if args.verbosity:
00064         logging.VERBOSITY = args.verbosity
00065         logging.pprint(f"Verbosity set to {args.verbosity}.", 2)
00066
00067     logging.pprint("Initializing model.", 1)
00068     model = markopy.ModelMatrix()
00069     logging.pprint("Model initialized.", 2)
00070
00071     logging.pprint("Importing model file.", 1)
00072
00073     if (not os.path.isfile(input_model)):
00074         logging.pprint(f"Model file at {input_model} not found. Check the file path, or working
           directory")
00075         exit(1)
00076
00077     model.Import(input_model)
00078     logging.pprint("Model imported successfully.", 2)
00079     return model
00080
00081
00082 def cli_train(model, dataset, seperator, output, output_forced=False, bulk=False):
00083     if not (dataset and seperator and (output or not output_forced)):
00084         logging.pprint(
00085             f"Training mode requires -d/--dataset{' ', -o/--output' if output_forced else ''} and
           -s/--seperator parameters. Exiting.")
00086         exit(2)
00087
00088     if (not bulk and not os.path.isfile(dataset)):
00089         logging.pprint(f"{dataset} doesn't exists. Check the file path, or working directory")
00090         exit(3)
00091
00092     if (output and os.path.isfile(output)):
00093         logging.pprint(f"{output} exists and will be overwritten.", 1)
00094
00095     if (seperator == '\\t'):
00096         logging.pprint("Escaping seperator.", 3)
00097         seperator = '\t'
00098
00099     if (len(seperator) != 1):
00100         logging.pprint(f'Delimiter must be a single character, and "{seperator}" is not accepted.')
00101         exit(4)
00102
00103     logging.pprint(f'Starting training.', 3)
00104     model.Train(dataset, seperator, int(args.threads))
00105     logging.pprint(f'Training completed.', 2)
00106
00107     if (output):
00108         logging.pprint(f'Exporting model to {output}', 2)
00109         model.Export(output)
00110     else:
00111         logging.pprint(f'Model will not be exported.', 1)
00112
00113
00114 def cli_generate(model, wordlist, bulk=False):
00115     if not (wordlist or args.count):
00116         logging.pprint("Generation mode requires -w/--wordlist and -n/--count parameters. Exiting.")
00117         exit(2)
00118
00119     if (bulk and os.path.isfile(wordlist)):
00120         logging.pprint(f"{wordlist} exists and will be overwritten.", 1)
00121     model.Generate(int(args.count), wordlist, int(args.min), int(args.max), int(args.threads))
00122
00123     if (args.bulk):
00124         logging.pprint(f"Bulk mode operation chosen.", 4)
00125
00126

```

```

00127     if (args.mode.lower() == "train"):
00128         if (os.path.isdir(args.output) and not os.path.isfile(args.output)) and (
00129             os.path.isdir(args.dataset) and not os.path.isfile(args.dataset)):
00130             corpus_list = os.listdir(args.dataset)
00131             for corpus in corpus_list:
00132                 model = cli_init(args.input)
00133                 logging.pprint(f"Training {args.input} with {corpus}", 2)
00134                 output_file_name = corpus
00135                 model_extension = ""
00136                 if "." in args.input:
00137                     model_extension = args.input.split(".")[1]
00138                 cli_train(model, f"{args.dataset}/{corpus}", args.seperator,
00139                     f"{args.output}/{corpus}.{model_extension}", output_forced=True, bulk=True)
00140             else:
00141                 logging.pprint("In bulk training, output and dataset should be a directory.")
00142                 exit(1)
00143
00144     elif (args.mode.lower() == "generate"):
00145         if (os.path.isdir(args.wordlist) and not os.path.isfile(args.wordlist)) and (
00146             os.path.isdir(args.input) and not os.path.isfile(args.input)):
00147             model_list = os.listdir(args.input)
00148             print(model_list)
00149             for input in model_list:
00150                 logging.pprint(f"Generating from {args.input}/{input} to {args.wordlist}/{input}.txt",
00151                     2)
00152                 model = cli_init(f"{args.input}/{input}")
00153                 model_base = input
00154                 if "." in args.input:
00155                     model_base = input.split(".")[1]
00156                 cli_generate(model, f"{args.wordlist}/{model_base}.txt", bulk=True)
00157             else:
00158                 logging.pprint("In bulk generation, input and wordlist should be directory.")
00159
00160     else:
00161         model = cli_init(args.input)
00162         if (args.mode.lower() == "generate"):
00163             cli_generate(model, args.wordlist)
00164
00165     elif (args.mode.lower() == "train"):
00166         cli_train(model, args.dataset, args.seperator, args.output, output_forced=True)
00167
00168     elif (args.mode.lower() == "combine"):
00169         cli_train(model, args.dataset, args.seperator, args.output)
00170         cli_generate(model, args.wordlist)
00171
00172     else:
00173         logging.pprint("Invalid mode arguement given.")
00174         logging.pprint("Accepted modes: 'Generate', 'Train', 'Combine'")
00175         exit(5)

```


9.29 markovPasswords.cpp File Reference

```

#include "markovPasswords.h"
#include <string.h>
#include <chrono>
#include <thread>
#include <vector>
#include <mutex>
#include <string>
#include <signal.h>
#include <unistd.h>

```

Include dependency graph for markovPasswords.cpp:



Functions

- void [intHandler](#) (int dummy)

Variables

- static volatile int [keepRunning](#) = 1

9.29.1 Function Documentation

9.29.1.1 intHandler()

```
void intHandler (
    int dummy )
```


Definition at line 18 of file [markovPasswords.cpp](#).

```
00018 {
00019     std::cout << "You wanted this man by presing CTRL-C ! Ok bye.";
00020     //Sleep(5000);
00021     keepRunning = 0;
00022     exit(0);
00023 }
```

References [keepRunning](#).

Referenced by [Markov::API::MarkovPasswords::Train\(\)](#).

Here is the caller graph for this function:



9.29.2 Variable Documentation

9.29.2.1 keepRunning

```
volatile int keepRunning = 1 [static]
```

Definition at line 16 of file [markovPasswords.cpp](#).

Referenced by [intHandler\(\)](#), and [Markov::API::MarkovPasswords::TrainThread\(\)](#).

9.30 markovPasswords.cpp

```

00001 #pragma once
00002 #include "markovPasswords.h"
00003 #include <string.h>
00004 #include <chrono>
00005 #include <thread>
00006 #include <vector>
00007 #include <mutex>
00008 #include <string>
00009 #include <signal.h>
00010 #ifdef _WIN32
00011 #include <Windows.h>
00012 #else
00013 #include <unistd.h>
00014 #endif
00015
00016 static volatile int keepRunning = 1;
00017
00018 void intHandler(int dummy) {
00019     std::cout << "You wanted this man by presing CTRL-C ! Ok bye.";
00020     //Sleep(5000);
00021     keepRunning = 0;
00022     exit(0);
00023 }
00024
00025
00026 Markov::API::MarkovPasswords::MarkovPasswords() : Markov::Model<char>() {
00027
00028
00029 }
00030
00031 Markov::API::MarkovPasswords::MarkovPasswords(const char* filename) {
00032
00033     std::ifstream* importFile;
00034
00035     this->Import(filename);
00036
00037     //std::ifstream* newFile(filename);
00038
00039     //importFile = newFile;
00040
00041 }
00042
00043 std::ifstream* Markov::API::MarkovPasswords::OpenDatasetFile(const char* filename){
00044
00045     std::ifstream* datasetFile;
00046
00047     std::ifstream newFile(filename);
00048
00049     datasetFile = &newFile;
00050
00051     this->Import(datasetFile);
00052     return datasetFile;
00053 }
00054
00055
00056
00057 void Markov::API::MarkovPasswords::Train(const char* datasetFileName, char delimiter, int threads) {
00058     signal(SIGINT, intHandler);
00059     Markov::API::Concurrency::ThreadSharedListHandler listhandler(datasetFileName);
00060     auto start = std::chrono::high_resolution_clock::now();
00061
00062     std::vector<std::thread*> threadsV;
00063     for(int i=0;i<threads;i++){
00064         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::TrainThread, this,
00065             &listhandler, delimiter));
00066     }
00067
00068     for(int i=0;i<threads;i++){
00069         threadsV[i]->join();
00070         delete threadsV[i];
00071     }
00072     auto finish = std::chrono::high_resolution_clock::now();
00073     std::chrono::duration<double> elapsed = finish - start;
00074     std::cout << "Elapsed time: " << elapsed.count() << " s\n";
00075 }
00076
00077 void Markov::API::MarkovPasswords::TrainThread(Markov::API::Concurrency::ThreadSharedListHandler
00078     *listhandler, char delimiter){
00079     char format_str[] = "%ld,%s";
00080     format_str[3]=delimiter;
00081     std::string line;
00082     while (listhandler->next(&line) && keepRunning) {
00083         long int oc;
00084         if (line.size() > 100) {

```



```

00084         line = line.substr(0, 100);
00085     }
00086     char* linebuf = new char[line.length()+5];
00087 #ifdef _WIN32
00088     sscanf_s(line.c_str(), "%ld,%s", &oc, linebuf, line.length()+5); //<== changed format_str to->
00089     "%ld,%s"
00089 #else
00090     sscanf(line.c_str(), format_str, &oc, linebuf);
00091 #endif
00092     this->AdjustEdge((const char*)linebuf, oc);
00093     delete linebuf;
00094 }
00095 }
00096
00097
00098 std::ofstream* Markov::API::MarkovPasswords::Save(const char* filename) {
00099     std::ofstream* exportFile;
00100
00101     std::ofstream newFile(filename);
00102
00103     exportFile = &newFile;
00104
00105     this->Export(exportFile);
00106     return exportFile;
00107 }
00108
00109
00110 void Markov::API::MarkovPasswords::Generate(unsigned long int n, const char* wordlistFileName, int
minLen, int maxLen, int threads) {
00111     char* res;
00112     char print[100];
00113     std::ofstream wordlist;
00114     wordlist.open(wordlistFileName);
00115     std::mutex mlock;
00116     int iterationsPerThread = n/threads;
00117     int iterationsCarryOver = n%threads;
00118     std::vector<std::thread*> threadsV;
00119     for(int i=0;i<threads;i++){
00120         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::GenerateThread, this,
&mlock, iterationsPerThread, &wordlist, minLen, maxLen));
00121     }
00122
00123     for(int i=0;i<threads;i++){
00124         threadsV[i]->join();
00125         delete threadsV[i];
00126     }
00127
00128     this->GenerateThread(&mlock, iterationsCarryOver, &wordlist, minLen, maxLen);
00129
00130 }
00131
00132 void Markov::API::MarkovPasswords::GenerateThread(std::mutex *outputLock, unsigned long int n,
std::ofstream *wordlist, int minLen, int maxLen) {
00133     char* res = new char[maxLen+5];
00134     if(n==0) return;
00135
00136     Markov::Random::Marsaglia MarsagliaRandomEngine;
00137     for (int i = 0; i < n; i++) {
00138         this->RandomWalk(&MarsagliaRandomEngine, minLen, maxLen, res);
00139         outputLock->lock();
00140         *wordlist << res << "\n";
00141         outputLock->unlock();
00142     }
00143 }

```


9.31 markovPasswords.h File Reference

```


#include "threadSharedListHandler.h"
#include "MarkovModel/src/model.h"

```

Include dependency graph for markovPasswords.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::MarkovPasswords](#)
Markov::Model with char represented nodes.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords API](#).

9.32 markovPasswords.h

```

00001 #pragma once
00002 #include "threadSharedListHandler.h"
00003 #include "MarkovModel/src/model.h"
00004
00005
00006 /** @brief Namespace for the MarkovPasswords API
00007 */
00008 namespace Markov::API{
00009
00010     /** @brief Markov::Model with char represented nodes.
00011     *
00012     * Includes wrappers for Markov::Model and additional helper functions to handle file I/O
00013     *

```

```

00014     * This class is an extension of Markov::Model<char>, with higher level abstractions such as train
and generate.
00015     *
00016     */
00017     class MarkovPasswords : public Markov::Model<char>{
00018     public:
00019
00020         /** @brief Initialize the markov model from MarkovModel::Markov::Model.
00021         *
00022         * Parent constructor. Has no extra functionality.
00023         */
00024         MarkovPasswords();
00025
00026         /** @brief Initialize the markov model from MarkovModel::Markov::Model, with an import file.
00027         *
00028         * This function calls the Markov::Model::Import on the filename to construct the model.
00029         * Same thing as creating an empty model, and calling MarkovPasswords::Import on the
filename.
00030         *
00031         * @param filename - Filename to import
00032         *
00033         *
00034         * @b Example @b Use: Construction via filename
00035         * @code{.cpp}
00036         * MarkovPasswords mp("test.mdl");
00037         * @endcode
00038         */
00039         MarkovPasswords(const char* filename);
00040
00041         /** @brief Open dataset file and return the ifstream pointer
00042         * @param filename - Filename to open
00043         * @return ifstream* to the the dataset file
00044         */
00045         std::ifstream* OpenDatasetFile(const char* filename);
00046
00047
00048         /** @brief Train the model with the dataset file.
00049         * @param datasetFileName - Ifstream* to the dataset. If null, use class member
00050         * @param delimiter - a character, same as the delimiter in dataset content
00051         * @param threads - number of OS threads to spawn
00052         *
00053         * @code{.cpp}
00054         * Markov::API::MarkovPasswords mp;
00055         * mp.Import("models/2gram.mdl");
00056         * mp.Train("password.corpus");
00057         * @endcode
00058         */
00059         void Train(const char* datasetFileName, char delimiter, int threads);
00060
00061
00062
00063         /** @brief Export model to file.
00064         * @param filename - Export filename.
00065         * @return std::ofstream* of the exported file.
00066         */
00067         std::ofstream* Save(const char* filename);
00068
00069         /** @brief Call Markov::Model::RandomWalk n times, and collect output.
00070         *
00071         * Generate from model and write results to a file.
00072         * a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5
on average.
00073         *
00074         * @deprecated See Markov::API::MatrixModel::FastRandomWalk for more information.
00075         * @param n - Number of passwords to generate.
00076         * @param wordlistFileName - Filename to write to
00077         * @param minLen - Minimum password length to generate
00078         * @param maxLen - Maximum password length to generate
00079         * @param threads - number of OS threads to spawn
00080         */
00081         void Generate(unsigned long int n, const char* wordlistFileName, int minLen=6, int maxLen=12,
int threads=20);
00082
00083
00084     private:
00085
00086         /** @brief A single thread invoked by the Train function.
00087         * @param listhandler - Listhandler class to read corpus from
00088         * @param delimiter - a character, same as the delimiter in dataset content
00089         *
00090         */
00091         void TrainThread(Markov::API::Concurrency::ThreadSharedListHandler *listhandler, char
delimiter);
00092
00093         /** @brief A single thread invoked by the Generate function.
00094         *
00095         * @b DEPRECATED: See Markov::API::MatrixModel::FastRandomWalkThread for more information.

```

```

00096     This has been replaced with
00097     * a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5
00098     on average.
00099     *
00098     * @param outputLock - shared mutex lock to lock during output operation. Prevents race
00099     condition on write.
00099     * @param n number of lines to be generated by this thread
00100     * @param wordlist wordlistfile
00101     * @param minLen - Minimum password length to generate
00102     * @param maxLen - Maximum password length to generate
00103     *
00104     */
00105 void GenerateThread(std::mutex *outputLock, unsigned long int n, std::ofstream *wordlist, int
minLen, int maxLen);
00106 std::ifstream* datasetFile; /** @brief Dataset file input of our system */
00107 std::ofstream* modelSavefile; /** @brief File to save model of our system */
00108 std::ofstream* outputFile; /** @brief Generated output file of our system */
00109 };
00110
00111
00112
00113 };

```


9.33 MarkovPasswordsGUI.cpp File Reference

```

#include "MarkovPasswordsGUI.h"
#include <fstream>
#include <qwebengineview.h>
#include <Windows.h>
#include "CLI.h"

```

Include dependency graph for MarkovPasswordsGUI.cpp:



9.34 MarkovPasswordsGUI.cpp

```

00001 #include "MarkovPasswordsGUI.h"
00002 #include <fstream>
00003 #include <qwebengineview.h>
00004 #include <Windows.h>
00005 #include "CLI.h"
00006
00007 using namespace Markov::GUI;
00008
00009 MarkovPasswordsGUI::MarkovPasswordsGUI(QWidget *parent)
00010     : QMainWindow(parent)
00011 {
00012     ui.setupUi(this);
00013
00014
00015     QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {home(); });
00016     QObject::connect(ui.pushButton_2, &QPushButton::clicked, this, [this] {model(); });
00017     QObject::connect(ui.pushButton_3, &QPushButton::clicked, this, [this] {pass(); });
00018 }
00019
00020
00021 void MarkovPasswordsGUI::home() {
00022     CLI* w = new CLI;
00023     w->show();
00024     this->close();
00025 }
00026 void MarkovPasswordsGUI::pass() {
00027     QWebEngineView* webkit = ui.centralWidget->findChild<QWebEngineView*>("chartArea");

```

```

00028
00029 //get working directory
00030 char path[255];
00031 GetCurrentDirectoryA(255, path);
00032
00033 //get absolute path to the layout html
00034 std::string layout = "file:/// " + std::string(path) + "\\views\\bar.html";
00035 std::replace(layout.begin(), layout.end(), '\\', '/');
00036 webkit->setUrl(QUrl(layout.c_str()));
00037 }
00038
00039 void MarkovPasswordsGUI::model() {
00040     QWebEngineView* webkit = ui.centralWidget->findChild<QWebEngineView*>("chartArea");
00041
00042     //get working directory
00043     char path[255];
00044     GetCurrentDirectoryA(255, path);
00045
00046     //get absolute path to the layout html
00047     std::string layout = "file:/// " + std::string(path) + "\\views\\index.html";
00048     std::replace(layout.begin(), layout.end(), '\\', '/');
00049     webkit->setUrl(QUrl(layout.c_str()));
00050 }

```


9.35 MarkovPasswordsGUI.h File Reference

```


#include <QtWidgets/QMainWindow>
#include "ui_MarkovPasswordsGUI.h"

```

Include dependency graph for MarkovPasswordsGUI.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::GUI::MarkovPasswordsGUI](#)

Reporting UI.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::GUI](#)
namespace for MarkovPasswords [API GUI](#) wrapper

9.36 MarkovPasswordsGUI.h

```

00001 #pragma once
00002
00003 #include <QtWidgets/QMainWindow>
00004 #include "ui_MarkovPasswordsGUI.h"
00005
00006
00007
00008 namespace Markov::GUI{
00009     /** @brief Reporting UI.
00010      *
00011      * UI for reporting and debugging tools for MarkovPassword
00012      */
00013     class MarkovPasswordsGUI : public QMainWindow {
00014         Q_OBJECT
00015
00016     private:
00017         Ui::MarkovPasswordsGUIClass ui;
00018
00019
00020         //Slots for buttons in GUI.
00021     public slots:
00022
00023         void MarkovPasswordsGUI::benchmarkSelected();
00024         void MarkovPasswordsGUI::modelvisSelected();
00025         void MarkovPasswordsGUI::visualDebugSelected();
00026         void MarkovPasswordsGUI::comparisonSelected();
00027
00028
00029     public slots:
00030
00031         void MarkovPasswordsGUI::home();
00032         void MarkovPasswordsGUI :: pass();
00033         void MarkovPasswordsGUI::model();
00034     };
00035 };

```


9.37 menu.cpp File Reference

```

#include "menu.h"
#include <fstream>
#include "MarkovPasswordsGUI.h"
#include <QtWidgets/QApplication>

```

Include dependency graph for menu.cpp:



9.38 menu.cpp

```

00001 #include "menu.h"

```

```

00002 #include <fstream>
00003 #include "MarkovPasswordsGUI.h"
00004 #include <QtWidgets/QApplication>
00005
00006 using namespace Markov::GUI;
00007
00008 menu::menu(QWidget* parent)
00009     : QMainWindow(parent)
00010 {
00011     ui.setupUi(this);
00012
00013     //QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {about(); });
00014     QObject::connect(ui.visu, &QPushButton::clicked, this, [this] {visualization(); });
00015 }
00016
00017 void menu::about() {
00018
00019
00020 }
00021 void menu::visualization() {
00022     MarkovPasswordsGUI* w = new MarkovPasswordsGUI;
00023     w->show();
00024     this->close();
00025 }

```


9.39 menu.h File Reference

```


#include <QtWidgets/QMainWindow>
#include "ui_menu.h"

```

Include dependency graph for menu.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::GUI::menu](#)

QT Menu class.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::GUI](#)

namespace for MarkovPasswords [API GUI](#) wrapper

9.40 menu.h

```

00001 #pragma once
00002 #include <QtWidgets/QMainWindow>
00003 #include "ui_menu.h"
00004
00005
00006 namespace Markov::GUI{
00007     /** @brief QT Menu class
00008     */
00009     class menu:public QMainWindow {
00010     Q_OBJECT
00011     public:
00012         menu(QWidget* parent = Q_NULLPTR);
00013
00014     private:
00015         Ui::main ui;
00016
00017     public slots:
00018         void about();
00019         void visualization();
00020     };
00021 };

```


9.41 model.h File Reference

```


#include <map>
#include <vector>
#include <fstream>
#include <assert.h>
#include <string>
#include <algorithm>
#include "node.h"
#include "edge.h"

```

Include dependency graph for model.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::Node< storageType >](#)
A node class that for the vertices of model. Connected with eachother using [Edge](#).
- class [Markov::Edge< NodeStorageType >](#)
[Edge](#) class used to link nodes in the model together.
- class [Markov::Model< NodeStorageType >](#)
class for the final [Markov Model](#), constructed from nodes and edges.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

9.42 model.h

```

00001 /** @dir Model.h
00002  *
00003  */
00004
00005
00006 #pragma once
00007 #include <map>
00008 #include <vector>
00009 #include <fstream>
00010 #include <assert.h>
00011 #include <string>
00012 #include <algorithm>
00013 #include "node.h"
00014 #include "edge.h"
00015
00016 /**
00017  @brief Namespace for the markov-model related classes.
00018  Contains Model, Node and Edge classes
00019  */
00020 namespace Markov {
00021
00022     template <typename NodeStorageType>
00023     class Node;
00024
00025     template <typename NodeStorageType>
00026     class Edge;
00027
00028     template <typename NodeStorageType>
00029
00030     /** @brief class for the final Markov Model, constructed from nodes and edges.
00031      *
00032      * Each atomic piece of the generation result is stored in a node, while edges contain the
00033      * relation weights.
00034      * *Extending:*
00035      * To extend the class, implement the template and inherit from it, as "class MyModel : public
00036      Markov::Model<char>".
  
```

```

00035     * For a complete demonstration of how to extend the class, see MarkovPasswords.
00036     *
00037     * Whole model can be defined as a list of the edges, as dangling nodes are pointless. This
approach is used for the import/export operations.
00038     * For more information on importing/exporting model, check out the github readme and wiki page.
00039     *
00040     */
00041     class Model {
00042     public:
00043
00044         /** @brief Initialize a model with only start and end nodes.
00045         *
00046         * Initialize an empty model with only a starterNode
00047         * Starter node is a special kind of node that has constant 0x00 value, and will be used to
initiate the generation execution from.
00048         */
00049         Model<NodeStorageType>();
00050
00051         /** @brief Do a random walk on this model.
00052         *
00053         * Start from the starter node, on each node, invoke RandomNext using the random engine on
current node, until terminator node is reached.
00054         * If terminator node is reached before minimum length criateria is reached, ignore the last
selection and re-invoke randomNext
00055         *
00056         * If maximum length criteria is reached but final node is not, cut off the generation and
proceed to the final node.
00057         * This function takes Markov::Random::RandomEngine as a parameter to generate pseudo random
numbers from
00058         *
00059         * This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne
output is higher in entropy, most use cases
00060         * don't really need super high entropy output, so Markov::Random::Marsaglia is preferable for
better performance.
00061         *
00062         * This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening
via maximum length criteria.
00063         *
00064         * @b Example @b Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use
Marsaglia
00065         * @code{.cpp}
00066         * Markov::Model<char> model;
00067         * Model.import("model.mdl");
00068         * char* res = new char[11];
00069         * Markov::Random::Marsaglia MarsagliaRandomEngine;
00070         * for (int i = 0; i < 10; i++) {
00071         *     this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
00072         *     std::cout << res << "\n";
00073         * }
00074         * @endcode
00075         *
00076         * @param randomEngine Random Engine to use for the random walks. For examples, see
Markov::Random::Mersenne and Markov::Random::Marsaglia
00077         * @param minSetting Minimum number of characters to generate
00078         * @param maxSetting Maximum number of character to generate
00079         * @param buffer buffer to write the result to
00080         * @return Null terminated string that was generated.
00081         */
00082         NodeStorageType* RandomWalk(Markov::Random::RandomEngine* randomEngine, int minSetting, int
maxSetting, NodeStorageType* buffer);
00083
00084         /** @brief Adjust the model with a single string.
00085         *
00086         * Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from
current node to the next, until NULL character is reached.
00087         *
00088         * Then, update the edge EdgeWeight from current node, to the terminator node.
00089         *
00090         * This function is used for training purposes, as it can be used for adjusting the model with
each line of the corpus file.
00091         *
00092         * @b Example @b Use: Create an empty model and train it with string: "testdata"
00093         * @code{.cpp}
00094         * Markov::Model<char> model;
00095         * char test[] = "testdata";
00096         * model.AdjustEdge(test, 15);
00097         * @endcode
00098         *
00099         *
00100         * @param string - String that is passed from the training, and will be used to AdjustEdge the
model with
00101         * @param occurrence - Occurrence of this string.
00102         *
00103         *
00104         */
00105         void AdjustEdge(const NodeStorageType* payload, long int occurrence);
00106

```

```

00107     /** @brief Import a file to construct the model.
00108     *
00109     * File contains a list of edges. For more info on the file format, check out the wiki and
github readme pages.
00110     * Format is: Left_repr;EdgeWeight;right_repr
00111     *
00112     * Iterate over this list, and construct nodes and edges accordingly.
00113     * @return True if successful, False for incomplete models or corrupt file formats
00114     *
00115     * @b Example @b Use: Import a file from ifstream
00116     * @code{.cpp}
00117     * Markov::Model<char> model;
00118     * std::ifstream file("test.mdl");
00119     * model.Import(&file);
00120     * @endcode
00121     */
00122     bool Import(std::ifstream*);
00123
00124     /** @brief Open a file to import with filename, and call bool Model::Import with std::ifstream
00125     * @return True if successful, False for incomplete models or corrupt file formats
00126     *
00127     * @b Example @b Use: Import a file with filename
00128     * @code{.cpp}
00129     * Markov::Model<char> model;
00130     * model.Import("test.mdl");
00131     * @endcode
00132     */
00133     bool Import(const char* filename);
00134
00135     /** @brief Export a file of the model.
00136     *
00137     * File contains a list of edges.
00138     * Format is: Left_repr;EdgeWeight;right_repr.
00139     * For more information on the format, check out the project wiki or github readme.
00140     *
00141     * Iterate over this vertices, and their edges, and write them to file.
00142     * @return True if successful, False for incomplete models.
00143     *
00144     * @b Example @b Use: Export file to ofstream
00145     * @code{.cpp}
00146     * Markov::Model<char> model;
00147     * std::ofstream file("test.mdl");
00148     * model.Export(&file);
00149     * @endcode
00150     */
00151     bool Export(std::ofstream*);
00152
00153     /** @brief Open a file to export with filename, and call bool Model::Export with std::ofstream
00154     * @return True if successful, False for incomplete models or corrupt file formats
00155     *
00156     * @b Example @b Use: Export file to filename
00157     * @code{.cpp}
00158     * Markov::Model<char> model;
00159     * model.Export("test.mdl");
00160     * @endcode
00161     */
00162     bool Export(const char* filename);
00163
00164     /** @brief Return starter Node
00165     * @return starter node with 00 NodeValue
00166     */
00167     Node<NodeStorageType>* StarterNode() { return starterNode; }
00168
00169     /** @brief Return a vector of all the edges in the model
00170     * @return vector of edges
00171     */
00172     std::vector<Edge<NodeStorageType>*>* Edges() { return &edges; }
00173
00174     /** @brief Return starter Node
00175     * @return starter node with 00 NodeValue
00176     */
00177     std::map<NodeStorageType, Node<NodeStorageType>*>* Nodes() { return &nodes; }
00178
00179 private:
00180     /**
00181     * @brief Map LeftNode is the Nodes NodeValue
00182     * Map RightNode is the node pointer
00183     */
00184     std::map<NodeStorageType, Node<NodeStorageType>*> nodes;
00185
00186     /**
00187     * @brief Starter Node of this model.
00188     */
00189     Node<NodeStorageType>* starterNode;
00190
00191
00192     /**

```

```

00193         @brief A list of all edges in this model.
00194     */
00195     std::vector<Edge<NodeStorageType>*> edges;
00196 };
00197
00198 };
00199
00200 template <typename NodeStorageType>
00201 Markov::Model<NodeStorageType>::Model() {
00202     this->starterNode = new Markov::Node<NodeStorageType>(0);
00203     this->nodes.insert({ 0, this->starterNode });
00204 }
00205
00206 template <typename NodeStorageType>
00207 bool Markov::Model<NodeStorageType>::Import(std::ifstream* f) {
00208     std::string cell;
00209
00210     char src;
00211     char target;
00212     long int oc;
00213
00214     while (std::getline(*f, cell)) {
00215         //std::cout << "cell: " << cell << std::endl;
00216         src = cell[0];
00217         target = cell[cell.length() - 1];
00218         char* j;
00219         oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(), &j, 10);
00220         //std::cout << oc << "\n";
00221         Markov::Node<NodeStorageType>* srcN;
00222         Markov::Node<NodeStorageType>* targetN;
00223         Markov::Edge<NodeStorageType>* e;
00224         if (this->nodes.find(src) == this->nodes.end()) {
00225             srcN = new Markov::Node<NodeStorageType>(src);
00226             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(src, srcN));
00227             //std::cout << "Creating new node at start.\n";
00228         }
00229         else {
00230             srcN = this->nodes.find(src)->second;
00231         }
00232
00233         if (this->nodes.find(target) == this->nodes.end()) {
00234             targetN = new Markov::Node<NodeStorageType>(target);
00235             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>*>(target, targetN));
00236             //std::cout << "Creating new node at end.\n";
00237         }
00238         else {
00239             targetN = this->nodes.find(target)->second;
00240         }
00241         e = srcN->Link(targetN);
00242         e->AdjustEdge(oc);
00243         this->edges.push_back(e);
00244
00245         //std::cout << int(srcN->NodeValue()) << " --" << e->EdgeWeight() << "--> " <<
int(targetN->NodeValue()) << "\n";
00246
00247     }
00248 }
00249
00250 for (std::pair<unsigned char, Markov::Node<NodeStorageType>*> const& x : this->nodes) {
00251     //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
00252     std::sort(x.second->edgesV.begin(), x.second->edgesV.end(), [](Edge<NodeStorageType>* lhs,
Edge<NodeStorageType>* rhs)->bool{
00253         return lhs->EdgeWeight() > rhs->EdgeWeight();
00254     });
00255     //for(int i=0; i<x.second->edgesV.size(); i++)
00256     // std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00257     //std::cout << "\n";
00258 }
00259 //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00260 //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00261
00262 return true;
00263 }
00264
00265 template <typename NodeStorageType>
00266 bool Markov::Model<NodeStorageType>::Import(const char* filename) {
00267     std::ifstream importfile;
00268     importfile.open(filename);
00269     return this->Import(&importfile);
00270 }
00271
00272
00273 template <typename NodeStorageType>
00274 bool Markov::Model<NodeStorageType>::Export(std::ofstream* f) {
00275     Markov::Edge<NodeStorageType>* e;
00276     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00277         e = this->edges[i];

```

```

00278         //std::cout << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," <<
e->RightNode()->NodeValue() << "\n";
00279         *f << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," << e->RightNode()->NodeValue() <<
"\n";
00280     }
00281
00282     return true;
00283 }
00284
00285 template <typename NodeStorageType>
00286 bool Markov::Model<NodeStorageType>::Export(const char* filename) {
00287     std::ofstream exportfile;
00288     exportfile.open(filename);
00289     return this->Export(&exportfile);
00290 }
00291
00292 template <typename NodeStorageType>
00293 NodeStorageType* Markov::Model<NodeStorageType>::RandomWalk(Markov::Random::RandomEngine*
randomEngine, int minSetting, int maxSetting, NodeStorageType* buffer) {
00294     Markov::Node<NodeStorageType>* n = this->starterNode;
00295     int len = 0;
00296     Markov::Node<NodeStorageType>* temp_node;
00297     while (true) {
00298         temp_node = n->RandomNext(randomEngine);
00299         if (len >= maxSetting) {
00300             break;
00301         }
00302         else if ((temp_node == NULL) && (len < minSetting)) {
00303             continue;
00304         }
00305
00306         else if (temp_node == NULL) {
00307             break;
00308         }
00309
00310         n = temp_node;
00311
00312         buffer[len++] = n->NodeValue();
00313     }
00314
00315     //null terminate the string
00316     buffer[len] = 0x00;
00317
00318     //do something with the generated string
00319     return buffer; //for now
00320 }
00321
00322 template <typename NodeStorageType>
00323 void Markov::Model<NodeStorageType>::AdjustEdge(const NodeStorageType* payload, long int occurrence) {
00324     NodeStorageType p = payload[0];
00325     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00326     Markov::Edge<NodeStorageType>* e;
00327     int i = 0;
00328
00329     if (p == 0) return;
00330     while (p != 0) {
00331         e = curnode->FindEdge(p);
00332         if (e == NULL) return;
00333         e->AdjustEdge(occurrence);
00334         curnode = e->RightNode();
00335         p = payload[++i];
00336     }
00337
00338     e = curnode->FindEdge('\xff');
00339     e->AdjustEdge(occurrence);
00340     return;
00341 }

```

9.43 model_2gram.py File Reference

Namespaces

- [model_2gram](#)

Variables

- [model_2gram.alphabet](#) = string.printable
password alphabet
- [model_2gram.f](#) = open('../models/2gram.mdl', "wb")

output file handle

9.44 model_2gram.py

```

00001 #!/usr/bin/python3
00002 """
00003     python script for generating a 2gram model
00004 """
00005
00006 import string
00007 import re
00008
00009
00010 alphabet = string.printable
00011 alphabet = re.sub('\s', "", alphabet)
00012 print(f"alphabet={alphabet}")
00013 #exit()
00014
00015
00016 f = open('../models/2gram.mdl', "wb")
00017 #tie start nodes
00018 for sym in alphabet:
00019     f.write(b"\x00,1," + bytes(sym, encoding='ascii') + b"\n")
00020
00021 #tie terminator nodes
00022 for sym in alphabet:
00023     f.write(bytes(sym, encoding='ascii') + b",1,\xff\n")
00024
00025 #tie internals
00026 for src in alphabet:
00027     for target in alphabet:
00028         f.write(bytes(src, encoding='ascii') + b",1," + bytes(target, encoding='ascii') + b"\n")

```


9.45 modelMatrix.cpp File Reference

```

#include "modelMatrix.h"
#include <map>
#include <cstring>
#include <thread>

```

Include dependency graph for modelMatrix.cpp:



9.46 modelMatrix.cpp

```

00001 #include "modelMatrix.h"
00002 #include <map>
00003 #include <cstring>
00004 #include <thread>
00005
00006 Markov::API::ModelMatrix::ModelMatrix() {
00007     this->ready = false;
00008 }
00009

```

```

00010 void Markov::API::ModelMatrix::Import(const char *filename){
00011     this->DeallocateMatrix();
00012     this->Markov::API::MarkovPasswords::Import(filename);
00013     this->ConstructMatrix();
00014 }
00015
00016 void Markov::API::ModelMatrix::Train(const char *datasetFileName, char delimiter, int threads){
00017     this->DeallocateMatrix();
00018     this->Markov::API::MarkovPasswords::Train(datasetFileName,delimiter,threads);
00019     this->ConstructMatrix();
00020 }
00021
00022 bool Markov::API::ModelMatrix::ConstructMatrix(){
00023     if(this->ready) return false;
00024     this->matrixSize = this->StarterNode()->edgesV.size() + 2;
00025
00026     this->matrixIndex = new char[this->matrixSize];
00027     this->totalEdgeWeights = new long int[this->matrixSize];
00028
00029     this->edgeMatrix = new char*[this->matrixSize];
00030     for(int i=0;i<this->matrixSize;i++){
00031         this->edgeMatrix[i] = new char[this->matrixSize];
00032     }
00033     this->valueMatrix = new long int*[this->matrixSize];
00034     for(int i=0;i<this->matrixSize;i++){
00035         this->valueMatrix[i] = new long int[this->matrixSize];
00036     }
00037     std::map< char, Node< char > * > *nodes;
00038     nodes = this->Nodes();
00039     int i=0;
00040     for (auto const& [repr, node] : *nodes){
00041         if(repr!=0) this->matrixIndex[i] = repr;
00042         else this->matrixIndex[i] = 199;
00043         this->totalEdgeWeights[i] = node->TotalEdgeWeights();
00044         for(int j=0;j<this->matrixSize;j++){
00045             char val = node->NodeValue();
00046             if(val < 0){
00047                 for(int k=0;k<this->matrixSize;k++){
00048                     this->valueMatrix[i][k] = 0;
00049                     this->edgeMatrix[i][k] = 255;
00050                 }
00051                 break;
00052             }
00053             else if(node->NodeValue() == 0 && j>(this->matrixSize-3)){
00054                 this->valueMatrix[i][j] = 0;
00055                 this->edgeMatrix[i][j] = 255;
00056             }else if(j==(this->matrixSize-1)) {
00057                 this->valueMatrix[i][j] = 0;
00058                 this->edgeMatrix[i][j] = 255;
00059             }else{
00060                 this->valueMatrix[i][j] = node->edgesV[j]->EdgeWeight();
00061                 this->edgeMatrix[i][j] = node->edgesV[j]->RightNode()->NodeValue();
00062             }
00063         }
00064         i++;
00065     }
00066     this->ready = true;
00067     return true;
00068     //this->DumpJSON();
00069 }
00070
00071
00072 bool Markov::API::ModelMatrix::DeallocateMatrix(){
00073     if(!this->ready) return false;
00074     delete[] this->matrixIndex;
00075     delete[] this->totalEdgeWeights;
00076
00077     for(int i=0;i<this->matrixSize;i++){
00078         delete[] this->edgeMatrix[i];
00079     }
00080     delete[] this->edgeMatrix;
00081
00082     for(int i=0;i<this->matrixSize;i++){
00083         delete[] this->valueMatrix[i];
00084     }
00085     delete[] this->valueMatrix;
00086
00087     this->matrixSize = -1;
00088     this->ready = false;
00089     return true;
00090 }
00091
00092 void Markov::API::ModelMatrix::DumpJSON(){
00093
00094     std::cout << "{\n  \"index\": \"\";\n";
00095     for(int i=0;i<this->matrixSize;i++){
00096         if(this->matrixIndex[i]!='') std::cout << "\\\"";

```

```

00097         else if(this->matrixIndex[i]=='\\') std::cout << "\\\\";
00098         else if(this->matrixIndex[i]==0) std::cout << "\\x00";
00099         else if(i==0) std::cout << "\\xff";
00100         else if(this->matrixIndex[i]=='\n') std::cout << "\\n";
00101         else std::cout << this->matrixIndex[i];
00102     }
00103     std::cout <<
00104     "\\n"
00105     "\\edgemap\\": {\n";
00106
00107     for(int i=0;i<this->matrixSize;i++){
00108         if(this->matrixIndex[i]=='') std::cout << "    "\\\"": [";
00109         else if(this->matrixIndex[i]=='\\') std::cout << "    "\\\"": [";
00110         else if(this->matrixIndex[i]==0) std::cout << "    "\\x00\"": [";
00111         else if(this->matrixIndex[i]<0) std::cout << "    "\\xff\"": [";
00112         else std::cout << "    \" < this->matrixIndex[i] < \"\": [";
00113         for(int j=0;j<this->matrixSize;j++){
00114             if(this->edgeMatrix[i][j]=='') std::cout << "\\\"";
00115             else if(this->edgeMatrix[i][j]=='\\') std::cout << "\\\"";
00116             else if(this->edgeMatrix[i][j]==0) std::cout << "\\x00\"";
00117             else if(this->edgeMatrix[i][j]<0) std::cout << "\\xff\"";
00118             else if(this->matrixIndex[i]=='\n') std::cout << "\\n\"";
00119             else std::cout << "\" < this->edgeMatrix[i][j] < \"\"";
00120             if(j!=this->matrixSize-1) std::cout << ", ";
00121         }
00122         std::cout << "],\n";
00123     }
00124     std::cout << "],\n";
00125
00126     std::cout << "\\    weightmap\\": {\n";
00127     for(int i=0;i<this->matrixSize;i++){
00128         if(this->matrixIndex[i]=='') std::cout << "    "\\\"": [";
00129         else if(this->matrixIndex[i]=='\\') std::cout << "    "\\\"": [";
00130         else if(this->matrixIndex[i]==0) std::cout << "    "\\x00\"": [";
00131         else if(this->matrixIndex[i]<0) std::cout << "    "\\xff\"": [";
00132         else std::cout << "    \" < this->matrixIndex[i] < \"\": [";
00133
00134         for(int j=0;j<this->matrixSize;j++){
00135             std::cout << this->valueMatrix[i][j];
00136             if(j!=this->matrixSize-1) std::cout << ", ";
00137         }
00138         std::cout << "],\n";
00139     }
00140     std::cout << "    }\n\n";
00141 }
00142
00143
00144 void Markov::API::ModelMatrix::FastRandomWalkThread(std::mutex *mlock, std::ofstream *wordlist,
00145 unsigned long int n, int minLen, int maxLen, int id, bool bFileIO){
00146     if(n==0) return;
00147
00148     Markov::Random::Marsaglia MarsagliaRandomEngine;
00149     char* e;
00150     char *res = new char[maxLen*n];
00151     int index = 0;
00152     char next;
00153     int len=0;
00154     long int selection;
00155     char cur;
00156     long int bufferctr = 0;
00157     for (int i = 0; i < n; i++) {
00158         cur=199;
00159         len=0;
00160         while (true) {
00161             e = strchr(this->matrixIndex, cur);
00162             index = e - this->matrixIndex;
00163             selection = MarsagliaRandomEngine.random() % this->totalEdgeWeights[index];
00164             for(int j=0;j<this->matrixSize;j++){
00165                 selection -= this->valueMatrix[index][j];
00166                 if (selection < 0){
00167                     next = this->edgeMatrix[index][j];
00168                     break;
00169                 }
00170             }
00171             if (len >= maxLen) break;
00172             else if ((next < 0) && (len < minLen)) continue;
00173             else if (next < 0) break;
00174             cur = next;
00175             res[bufferctr + len++] = cur;
00176         }
00177         res[bufferctr + len++] = '\n';
00178         bufferctr+=len;
00179     }
00180 }
00181 if(bFileIO){
00182     mlock->lock();

```



```

00183         *wordlist « res;
00184         mlock->unlock();
00185     }else{
00186         mlock->lock();
00187         std::cout « res;
00188         mlock->unlock();
00189     }
00190     delete res;
00191
00192 }
00193
00194
00195 void Markov::API::ModelMatrix::FastRandomWalk(unsigned long int n, const char* wordlistFileName, int
minLen, int maxLen, int threads, bool bFileIO){
00196
00197     std::ofstream wordlist;
00198     if(bFileIO)
00199         wordlist.open(wordlistFileName);
00200
00201     std::mutex mlock;
00202     if(n<=50000000ull) return this->FastRandomWalkPartition(&mlock, &wordlist, n, minLen, maxLen,
bFileIO, threads);
00203
00204     else{
00205         int numberOfPartitions = n/50000000ull;
00206         for(int i=0;i<numberOfPartitions;i++){
00207             this->FastRandomWalkPartition(&mlock, &wordlist, 50000000ull, minLen, maxLen, bFileIO,
threads);
00208         }
00209
00210     }
00211 }
00212
00213
00214 void Markov::API::ModelMatrix::FastRandomWalkPartition(std::mutex *mlock, std::ofstream *wordlist,
unsigned long int n, int minLen, int maxLen, bool bFileIO, int threads){
00215
00216     int iterationsPerThread = n/threads;
00217     int iterationsPerThreadCarryOver = n%threads;
00218
00219     std::vector<std::thread*> threadsV;
00220
00221     int id = 0;
00222     for(int i=0;i<threads;i++){
00223         threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this,
mlock, wordlist, iterationsPerThread, minLen, maxLen, id, bFileIO));
00224         id++;
00225     }
00226
00227     threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this, mlock,
wordlist, iterationsPerThreadCarryOver, minLen, maxLen, id, bFileIO));
00228
00229     for(int i=0;i<threads;i++){
00230         threadsV[i]->join();
00231     }
00232 }

```


9.47 modelMatrix.h File Reference

```


#include "markovPasswords.h"
#include <mutex>

```

Include dependency graph for modelMatrix.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::ModelMatrix](#)
Class to flatten and reduce [Markov::Model](#) to a Matrix.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords](#) API.

9.48 modelMatrix.h

```

00001 #include "markovPasswords.h"
00002 #include <mutex>
00003
00004 namespace Markov::API{
00005
00006     /** @brief Class to flatten and reduce Markov::Model to a Matrix
00007      *
00008      * Matrix level operations can be used for Generation events, with a significant performance
00009      * optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)
00010      *
00011      * To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for
00012      * allocation. Threads are synchronized and files are flushed every 50M operations.
00013      */
00014     class ModelMatrix : public Markov::API::MarkovPasswords{
00015     public:
00016         ModelMatrix();
  
```

```

00016
00017     /** @brief Construct the related Matrix data for the model.
00018     *
00019     * This operation can be used after importing/training to allocate and populate the matrix
content.
00020     *
00021     * this will initialize:
00022     * char** edgeMatrix -> a 2D array of mapping left and right connections of each edge.
00023     * long int **valueMatrix -> a 2D array representing the edge weights.
00024     * int matrixSize -> Size of the matrix, aka total number of nodes.
00025     * char* matrixIndex -> order of nodes in the model
00026     * long int *totalEdgeWeights -> total edge weights of each Node.
00027     *
00028     * @returns True if constructed. False if already constructed.
00029     */
00030     bool ConstructMatrix();
00031
00032
00033     /** @brief Debug function to dump the model to a JSON file.
00034     *
00035     * Might not work 100%. Not meant for production use.
00036     */
00037     void DumpJSON();
00038
00039
00040     /** @brief Random walk on the Matrix-reduced Markov::Model
00041     *
00042     * This has an O(N) Memory complexity. To limit the maximum usage, requests with n>50M are
partitioned using Markov::API::ModelMatrix::FastRandomWalkPartition.
00043     *
00044     * If n>50M, threads are going to be synced, files are going to be flushed, and buffers will
be reallocated every 50M generations.
00045     * This comes at a minor performance penalty.
00046     *
00047     * While it has the same functionality, this operation reduces
Markov::API::MarkovPasswords::Generate runtime by %96.5
00048     *
00049     * This function has deprecated Markov::API::MarkovPasswords::Generate, and will eventually
replace it.
00050     *
00051     * @param n - Number of passwords to generate.
00052     * @param wordlistFileName - Filename to write to
00053     * @param minLen - Minimum password length to generate
00054     * @param maxLen - Maximum password length to generate
00055     * @param threads - number of OS threads to spawn
00056     * @param bFileIO - If false, filename will be ignored and will output to stdout.
00057     *
00058     *
00059     * @code{.cpp}
00060     * Markov::API::ModelMatrix mp;
00061     * mp.Import("models/finished.mdl");
00062     * mp.FastRandomWalk(50000000, "./wordlist.txt", 6, 12, 25, true);
00063     * @endcode
00064     *
00065     */
00066     void FastRandomWalk(unsigned long int n, const char* wordlistFileName, int minLen=6, int
maxLen=12, int threads=20, bool bFileIO=true);
00067
00068     /** @copydoc Markov::Model::Import(const char *filename)
00069     * Construct the matrix when done.
00070     *
00071     */
00072     void Import(const char *filename);
00073
00074     /** @copydoc Markov::API::MarkovPasswords::Train(const char *datasetFileName, char delimiter,
int threads)
00075     * Construct the matrix when done.
00076     *
00077     */
00078     void Train(const char *datasetFileName, char delimiter, int threads);
00079
00080     protected:
00081
00082     /** @brief A single partition of FastRandomWalk event
00083     *
00084     * Since FastRandomWalk has to allocate its output buffer before operation starts and writes
data in chunks,
00085     * large n parameters would lead to huge memory allocations.
00086     * @b Without @b Partitioning:
00087     * - 50M results 12 characters max -> 550 Mb Memory allocation
00088     *
00089     * - 5B results 12 characters max -> 55 Gb Memory allocation
00090     *
00091     * - 50B results 12 characters max -> 550GB Memory allocation
00092     *
00093     * Instead, FastRandomWalk is partitioned per 50M generations to limit the top memory need.
00094     *

```

```

00095      * @param mlock - mutex lock to distribute to child threads
00096      * @param wordlist - Reference to the wordlist file to write to
00097      * @param n - Number of passwords to generate.
00098      * @param wordlistFileName - Filename to write to
00099      * @param minLen - Minimum password length to generate
00100      * @param maxLen - Maximum password length to generate
00101      * @param threads - number of OS threads to spawn
00102      * @param bFileIO - If false, filename will be ignored and will output to stdout.
00103      *
00104      */
00105      void FastRandomWalkPartition(std::mutex *mlock, std::ofstream *wordlist, unsigned long int n,
00106      int minLen, int maxLen, bool bFileIO, int threads);
00107
00108      /** @brief A single thread of a single partition of FastRandomWalk
00109      *
00110      * A FastRandomWalkPartition will initiate as many of this function as requested.
00111      *
00112      * This function contains the bulk of the generation algorithm.
00113      *
00114      * @param mlock - mutex lock to distribute to child threads
00115      * @param wordlist - Reference to the wordlist file to write to
00116      * @param n - Number of passwords to generate.
00117      * @param wordlistFileName - Filename to write to
00118      * @param minLen - Minimum password length to generate
00119      * @param maxLen - Maximum password length to generate
00120      * @param id - @b DEPRECATED Thread id - No longer used
00121      * @param bFileIO - If false, filename will be ignored and will output to stdout.
00122      *
00123      */
00124      void FastRandomWalkThread(std::mutex *mlock, std::ofstream *wordlist, unsigned long int n, int
00125      minLen, int maxLen, int id, bool bFileIO);
00126
00127      /** @brief Deallocate matrix and make it ready for re-construction
00128      *
00129      * @returns True if deallocated. False if matrix was not initialized
00130      */
00131      bool DeallocateMatrix();
00132
00133      /**
00134      @brief 2-D Character array for the edge Matrix (The characters of Nodes)
00135      */
00136      char** edgeMatrix;
00137
00138      /**
00139      @brief 2-d Integer array for the value Matrix (For the weights of Edges)
00140      */
00141      long int **valueMatrix;
00142
00143      /**
00144      @brief to hold Matrix size
00145      */
00146      int matrixSize;
00147
00148      /**
00149      @brief to hold the Matrix index (To hold the orders of 2-D arrays')
00150      */
00151      char* matrixIndex;
00152
00153      /**
00154      @brief Array of the Total Edge Weights
00155      */
00156      long int *totalEdgeWeights;
00157
00158      /**
00159      @brief True when matrix is constructed. False if not.
00160      */
00161      bool ready;
00162      };
00163
00164
00165
00166 };

```


9.49 node.h File Reference

```


#include <vector>
#include <map>
#include <assert.h>
#include <iostream>
#include <stdexcept>

```

```
#include "edge.h"
#include "random.h"
Include dependency graph for node.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::Node< storageType >](#)

A node class that for the vertices of model. Connected with eachother using [Edge](#).

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

9.50 node.h

```
00001 #pragma once
00002 #include <vector>
00003 #include <map>
00004 #include <assert.h>
00005 #include <iostream>
00006 #include <stdexcept> // To use runtime_error
00007 #include "edge.h"
00008 #include "random.h"
00009 namespace Markov {
00010
00011     /** @brief A node class that for the vertices of model. Connected with eachother using Edge
00012     *
00013     * This class will later be templated to accept other data types than char*.
00014     */
00015     template <typename storageType>
```

```

00016     class Node {
00017     public:
00018
00019         /** @brief Default constructor. Creates an empty Node.
00020         */
00021         Node<storageType>();
00022
00023         /** @brief Constructor. Creates a Node with no edges and with given NodeValue.
00024         * @param _value - Nodes character representation.
00025         *
00026         * @b Example @b Use: Construct nodes
00027         * @code{.cpp}
00028         * Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00029         * Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00030         * @endcode
00031         */
00032         Node<storageType>(storageType _value);
00033
00034         /** @brief Link this node with another, with this node as its source.
00035         *
00036         * Creates a new Edge.
00037         * @param target - Target node which will be the RightNode() of new edge.
00038         * @return A new node with LeftNode as this, and RightNode as parameter target.
00039         *
00040         * @b Example @b Use: Construct nodes
00041         * @code{.cpp}
00042         * Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00043         * Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00044         * Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
00045         * @endcode
00046         */
00047         Edge<storageType>* Link(Node<storageType>*);
00048
00049         /** @brief Link this node with another, with this node as its source.
00050         *
00051         * *DOES NOT* create a new Edge.
00052         * @param Edge - Edge that will accept this node as its LeftNode.
00053         * @return the same edge as parameter target.
00054         *
00055         * @b Example @b Use: Construct and link nodes
00056         * @code{.cpp}
00057         * Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00058         * Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00059         * Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
00060         * LeftNode->Link(e);
00061         * @endcode
00062         */
00063         Edge<storageType>* Link(Edge<storageType>*);
00064
00065         /** @brief Chose a random node from the list of edges, with regards to its EdgeWeight, and
00066         TraverseNode to that.
00067         *
00068         * This operation is done by generating a random number in range of 0-this.total_edge_weights,
00069         and then iterating over the list of edges.
00070         * At each step, EdgeWeight of the edge is subtracted from the random number, and once it is
00071         0, next node is selected.
00072         * @return Node that was chosen at EdgeWeight biased random.
00073         *
00074         * @b Example @b Use: Use randomNext to do a random walk on the model
00075         * @code{.cpp}
00076         * char* buffer[64];
00077         * Markov::Model<char> model;
00078         * model.Import("model.mdl");
00079         * Markov::Node<char>* n = model.starterNode;
00080         * int len = 0;
00081         * Markov::Node<char>* temp_node;
00082         * while (true) {
00083             temp_node = n->RandomNext(randomEngine);
00084             if (len >= maxSetting) {
00085                 break;
00086             }
00087             else if ((temp_node == NULL) && (len < minSetting)) {
00088                 continue;
00089             }
00090             else if (temp_node == NULL) {
00091                 break;
00092             }
00093             n = temp_node;
00094             buffer[len++] = n->NodeValue();
00095         }
00096         * @endcode
00097         */
00098         Node<storageType>* RandomNext(Markov::Random::RandomEngine* randomEngine);
00099

```

```

00100     /** @brief Insert a new edge to the this.edges.
00101     * @param edge - New edge that will be inserted.
00102     * @return true if insertion was successful, false if it fails.
00103     *
00104     * @b Example @b Use: Construct and update edges
00105     *
00106     * @code{.cpp}
00107     * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00108     * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00109     * Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00110     * Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00111     * Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target2);
00112     * e1->AdjustEdge(25);
00113     * src->UpdateEdges(e1);
00114     * e2->AdjustEdge(30);
00115     * src->UpdateEdges(e2);
00116     * @endcode
00117     */
00118     bool UpdateEdges(Edge<storageType>*);
00119
00120     /** @brief Find an edge with its character representation.
00121     * @param repr - character NodeValue of the target node.
00122     * @return Edge that is connected between this node, and the target node.
00123     *
00124     * @b Example @b Use: Construct and update edges
00125     *
00126     * @code{.cpp}
00127     * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00128     * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00129     * Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00130     * Markov::Edge<unsigned char>* res = NULL;
00131     * src->Link(target1);
00132     * src->Link(target2);
00133     * res = src->FindEdge('b');
00134     *
00135     * @endcode
00136     *
00137     */
00138     Edge<storageType>* FindEdge(storageType repr);
00139
00140     /** @brief Find an edge with its pointer. Avoid unless necessary because computational cost
of find by character is cheaper (because of std::map)
00141     * @param target - target node.
00142     * @return Edge that is connected between this node, and the target node.
00143     */
00144     Edge<storageType>* FindEdge(Node<storageType>* target);
00145
00146     /** @brief Return character representation of this node.
00147     * @return character representation at _value.
00148     */
00149     inline unsigned char NodeValue();
00150
00151     /** @brief Change total weights with offset
00152     * @param offset to adjust the vertice weight with
00153     */
00154     void UpdateTotalVerticeWeight(long int offset);
00155
00156     /** @brief return edges
00157     */
00158     inline std::map<storageType, Edge<storageType>*>* Edges();
00159
00160     /** @brief return total edge weights
00161     */
00162     inline long int TotalEdgeWeights();
00163
00164
00165     std::vector<Edge<storageType>*> edgesV;
00166 private:
00167
00168     /**
00169     * @brief Character representation of this node. 0 for starter, 0xff for terminator.
00170     */
00171     storageType _value;
00172
00173     /**
00174     * @brief Total weights of the vertices, required by RandomNext
00175     */
00176     long int total_edge_weights;
00177
00178     /**
00179     * @brief A map of all edges connected to this node, where this node is at the LeftNode.
00180     * Map is indexed by unsigned char, which is the character representation of the node.
00181     */
00182     std::map<storageType, Edge<storageType>*> edges;
00183 };
00184 };
00185

```

```

00186
00187
00188
00189
00190
00191
00192
00193
00194 template <typename storageType>
00195 Markov::Node<storageType>::Node(storageType _value) {
00196     this->_value = _value;
00197     this->total_edge_weights = 0L;
00198 };
00199
00200 template <typename storageType>
00201 Markov::Node<storageType>::Node() {
00202     this->_value = 0;
00203     this->total_edge_weights = 0L;
00204 };
00205
00206 template <typename storageType>
00207 inline unsigned char Markov::Node<storageType>::NodeValue() {
00208     return _value;
00209 }
00210
00211 template <typename storageType>
00212 Markov::Edge<storageType>* Markov::Node<storageType>::Link(Markov::Node<storageType>* n) {
00213     Markov::Edge<storageType>* v = new Markov::Edge<storageType>(this, n);
00214     this->UpdateEdges(v);
00215     return v;
00216 }
00217
00218 template <typename storageType>
00219 Markov::Edge<storageType>* Markov::Node<storageType>::Link(Markov::Edge<storageType>* v) {
00220     v->SetLeftEdge(this);
00221     this->UpdateEdges(v);
00222     return v;
00223 }
00224
00225 template <typename storageType>
00226 Markov::Node<storageType>* Markov::Node<storageType>::RandomNext(Markov::Random::RandomEngine*
    randomEngine) {
00227
00228     //get a random NodeValue in range of total_vertice_weight
00229     long int selection = randomEngine->random() %
    this->total_edge_weights; //distribution(generator()); // distribution(generator);
00230     //make absolute, no negative modulus values wanted
00231     //selection = (selection >= 0) ? selection : (selection + this->total_edge_weights);
00232     for(int i=0; i<this->edgesV.size(); i++){
00233         selection -= this->edgesV[i]->EdgeWeight();
00234         if (selection < 0) return this->edgesV[i]->TraverseNode();
00235     }
00236
00237     //if this assertion is reached, it means there is an implementation error above
00238     std::cout << "This should never be reached (node failed to walk to next)\n"; //cant assert from
    child thread
00239     assert(true && "This should never be reached (node failed to walk to next)");
00240     return NULL;
00241 }
00242
00243 template <typename storageType>
00244 bool Markov::Node<storageType>::UpdateEdges(Markov::Edge<storageType>* v) {
00245     this->edges.insert({ v->RightNode()->NodeValue(), v });
00246     this->edgesV.push_back(v);
00247     //this->total_edge_weights += v->EdgeWeight();
00248     return v->TraverseNode();
00249 }
00250
00251 template <typename storageType>
00252 Markov::Edge<storageType>* Markov::Node<storageType>::FindEdge(storageType repr) {
00253     auto e = this->edges.find(repr);
00254     if (e == this->edges.end()) return NULL;
00255     return e->second;
00256 };
00257
00258 template <typename storageType>
00259 void Markov::Node<storageType>::UpdateTotalVerticeWeight(long int offset) {
00260     this->total_edge_weights += offset;
00261 }
00262
00263 template <typename storageType>
00264 inline std::map<storageType, Markov::Edge<storageType>*>* Markov::Node<storageType>::Edges() {
00265     return &(this->edges);
00266 }
00267
00268 template <typename storageType>
00269 inline long int Markov::Node<storageType>::TotalEdgeWeights() {

```




```
00270     return this->total_edge_weights;
00271 }
```

9.51 pch.cpp File Reference

```
#include "pch.h"
```

Include dependency graph for MarkovModel/src/pch.cpp:




9.52 MarkovModel/src/pch.cpp

```
00001 // pch.cpp: source file corresponding to the pre-compiled header
00002
00003 #include "pch.h"
00004
00005 // When you are using pre-compiled headers, this source file is necessary for compilation to succeed.
```

9.53 pch.cpp File Reference

```
#include "pch.h"
```

Include dependency graph for UnitTests/pch.cpp:



9.54 UnitTests/pch.cpp

```


00001 // pch.cpp: source file corresponding to the pre-compiled header
00002
00003 #include "pch.h"
00004
00005 // When you are using pre-compiled headers, this source file is necessary for compilation to succeed.

```


9.55 pch.h File Reference

```
#include "framework.h"
```

Include dependency graph for MarkovModel/src/pch.h:



This graph shows which files directly or indirectly include this file:



9.56 MarkovModel/src/pch.h


```

00001 // pch.h: This is a precompiled header file.
00002 // Files listed below are compiled only once, improving build performance for future builds.
00003 // This also affects IntelliSense performance, including code completion and many code browsing
00004 // features.
00005 // However, files listed here are ALL re-compiled if any one of them is updated between builds.
00006 // Do not add files here that you will be updating frequently as this negates the performance
00007 // advantage.
00008
00009 #ifndef PCH_H
00010 #define PCH_H
00011
00012 // add headers that you want to pre-compile here
00013 #include "framework.h"
00014
00015 #endif //PCH_H

```

9.57 pch.h File Reference

This graph shows which files directly or indirectly include this file:



9.58 UnitTests/pch.h

```

00001 // pch.h: This is a precompiled header file.
00002 // Files listed below are compiled only once, improving build performance for future builds.
00003 // This also affects IntelliSense performance, including code completion and many code browsing
00004 // features.
00004 // However, files listed here are ALL re-compiled if any one of them is updated between builds.
00005 // Do not add files here that you will be updating frequently as this negates the performance
00005 // advantage.
00006
00007 #ifndef PCH_H
00008 #define PCH_H
00009
00010 // add headers that you want to pre-compile here
00011
00012 #endif //PCH_H
  
```

9.59 random-model.py File Reference

Namespaces

- [random-model](#)
- [random](#)

Variables

- [random-model.alphabet](#) = `string.printable`
password alphabet
- [random-model.f](#) = `open("../models/random.mdl", "wb")`
output file handle

9.60 random-model.py

```

00001 #!/usr/bin/python3
00002 """
00003     python script for generating a 2gram model
00004 """
00005
00006 import string
00007 import re
00008
00009
00010 alphabet = string.printable
00011 alphabet = re.sub('\s', "", alphabet)
00012 print(f"alphabet={alphabet}")
  
```

```

00013 #exit()
00014
00015
00016 f = open('../models/random.mdl', "wb")
00017 #tie start nodes
00018 for sym in alphabet:
00019     f.write(b"\x00,1," + bytes(sym, encoding='ascii') + b"\n")
00020
00021 #tie terminator nodes
00022 for sym in alphabet:
00023     f.write(bytes(sym, encoding='ascii') + b",1,\xff\n")
00024
00025 #tie internals
00026 for src in alphabet:
00027     for target in alphabet:
00028         f.write(bytes(src, encoding='ascii') + b",1," + bytes(target, encoding='ascii') + b"\n")

```


9.61 random.h File Reference

```


#include <random>
#include <iostream>

```

Include dependency graph for random.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::Random::RandomEngine](#)
An abstract class for [Random Engine](#).
- class [Markov::Random::DefaultRandomEngine](#)
Implementation using [Random.h](#) default random engine.
- class [Markov::Random::Marsaglia](#)
Implementation of [Marsaglia Random Engine](#).
- class [Markov::Random::Mersenne](#)
Implementation of [Mersenne Twister Engine](#).

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::Random](#)
Objects related to RNG.

9.62 random.h

```

00001
00002 #pragma once
00003 #include <random>
00004 #include <iostream>
00005
00006 /**
00007  @brief Objects related to RNG
00008  */
00009 namespace Markov::Random{
00010
00011     /** @brief An abstract class for Random Engine
00012      *
00013      * This class is used for generating random numbers, which are used for random walking on the
00014      graph.
00015      * Main reason behind allowing different random engines is that some use cases may favor
00016      performance,
00017      * while some favor good random.
00018      * Mersenne can be used for truer random, while Marsaglia can be used for deterministic but fast
00019      random.
00020      */
00021     class RandomEngine{
00022     public:
00023         virtual inline unsigned long random() = 0;
00024     };
00025
00026
00027
00028     /** @brief Implementation using Random.h default random engine
00029      *
00030      * This engine is also used by other engines for seeding.
00031      *
00032      * @b Example @b Use: Using Default Engine with RandomWalk
00033      * @code{.cpp}
00034      * Markov::Model<char> model;
00035      * Model.import("model.mdl");
00036      * char* res = new char[11];
00037      * Markov::Random::DefaultRandomEngine randomEngine;
00038      * for (int i = 0; i < 10; i++) {
00039      *     this->RandomWalk(&randomEngine, 5, 10, res);
00040      *     std::cout << res << "\n";
00041      * }
00042      * @endcode
00043      *
00044      * @b Example @b Use: Generating a random number with Marsaglia Engine
00045      * @code{.cpp}
00046      * Markov::Random::DefaultRandomEngine de;
00047      * std::cout << de.random();
00048      * @endcode
00049      *
00050      */
00051     class DefaultRandomEngine : public RandomEngine{
00052

```

```

00053     public:
00054         /** @brief Generate Random Number
00055          * @return random number in long range.
00056          */
00057         inline unsigned long random() {
00058             return this->distribution() (this->generator());
00059         }
00060     protected:
00061
00062         /** @brief Default random device for seeding
00063          *
00064          */
00065         inline std::random_device& rd() {
00066             static std::random_device _rd;
00067             return _rd;
00068         }
00069
00070         /** @brief Default random engine for seeding
00071          *
00072          */
00073         inline std::default_random_engine& generator() {
00074             static std::default_random_engine _generator(rd() ());
00075             return _generator;
00076         }
00077
00078         /** @brief Distribution schema for seeding.
00079          *
00080          */
00081         inline std::uniform_int_distribution<long long unsigned>& distribution() {
00082             static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00083             return _distribution;
00084         }
00085     };
00086
00087
00088     /** @brief Implementation of Marsaglia Random Engine
00089     *
00090     * This is an implementation of Marsaglia Random engine, which for most use cases is a better fit
00091     than other solutions.
00092     * Very simple mathematical formula to generate pseudorandom integer, so its crazy fast.
00093     *
00094     * This implementation of the Marsaglia Engine is seeded by random.h default random engine.
00095     * RandomEngine is only seeded once so its not a performance issue.
00096     *
00097     * @b Example @b Use: Using Marsaglia Engine with RandomWalk
00098     * @code{.cpp}
00099     * Markov::Model<char> model;
00100     * Model.import("model.mdl");
00101     * char* res = new char[11];
00102     * Markov::Random::Marsaglia MarsagliaRandomEngine;
00103     * for (int i = 0; i < 10; i++) {
00104     *     this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
00105     *     std::cout << res << "\n";
00106     * }
00107     * @endcode
00108     *
00109     * @b Example @b Use: Generating a random number with Marsaglia Engine
00110     * @code{.cpp}
00111     * Markov::Random::Marsaglia me;
00112     * std::cout << me.random();
00113     * @endcode
00114     *
00115     */
00116     class Marsaglia : public DefaultRandomEngine{
00117     public:
00118
00119         /** @brief Construct Marsaglia Engine
00120          *
00121          * Initialize x,y and z using the default random engine.
00122          */
00123         Marsaglia() {
00124             this->x = this->distribution() (this->generator());
00125             this->y = this->distribution() (this->generator());
00126             this->z = this->distribution() (this->generator());
00127             //std::cout << "x: " << x << ", y: " << y << ", z: " << z << "\n";
00128         }
00129
00130
00131         inline unsigned long random() {
00132             unsigned long t;
00133             x ^= x << 16;
00134             x ^= x >> 5;
00135             x ^= x << 1;
00136
00137             t = x;
00138             x = y;

```

```

00139         y = z;
00140         z = t ^ x ^ y;
00141
00142         return z;
00143     }
00144
00145     unsigned long x;
00146     unsigned long y;
00147     unsigned long z;
00148 };
00149
00150
00151
00152     /** @brief Implementation of Mersenne Twister Engine
00153     *
00154     * This is an implementation of Mersenne Twister Engine, which is slow but is a good
00155     * implementation for high entropy pseudorandom.
00156     *
00157     * @b Example @b Use: Using Mersenne Engine with RandomWalk
00158     * @code{.cpp}
00159     * Markov::Model<char> model;
00160     * Model.import("model.mdl");
00161     * char* res = new char[11];
00162     * Markov::Random::Mersenne MersenneTwisterEngine;
00163     * for (int i = 0; i < 10; i++) {
00164     *     this->RandomWalk(&MersenneTwisterEngine, 5, 10, res);
00165     *     std::cout << res << "\n";
00166     * }
00167     * @endcode
00168     *
00169     * @b Example @b Use: Generating a random number with Marsaglia Engine
00170     * @code{.cpp}
00171     * Markov::Random::Mersenne me;
00172     * std::cout << me.random();
00173     * @endcode
00174     *
00175     */
00176     class Mersenne : public DefaultRandomEngine{
00177     };
00178 };
00179
00180
00181 };

```

9.63 README.md File Reference


9.64 term.cpp File Reference

```

#include "term.h"
#include <string>

```

Include dependency graph for term.cpp:



Functions

- `std::ostream & operator<< (std::ostream &os, const Terminal::color &c)`

9.64.1 Function Documentation

9.64.1.1 operator<<()

```
std::ostream& operator<< (
    std::ostream & os,
    const Markov::API::CLI::Terminal::color & c )
```

overload for `std::cout`.

Definition at line 60 of file [term.cpp](#).

```
00060                                     {
00061     char buf[6];
00062     sprintf(buf, "%d", Terminal::colormap.find\(c\)->second);
00063     os << "\e[1;" << buf << "m";
00064     return os;
00065 }
```

References [Markov::API::CLI::Terminal::colormap](#).

9.65 term.cpp

```
00001 #pragma once
00002 #include "term.h"
00003 #include <string>
00004
00005 using namespace Markov::API::CLI;
00006
00007 //Windows text processing is different from unix systems, so use windows header and text attributes
00008 #ifdef _WIN32
00009
00010 HANDLE Terminal::\_stdout;
00011 HANDLE Terminal::\_stderr;
00012
00013 std::map<Terminal::color, DWORD> Terminal::colormap = {
00014     {Terminal::color::BLACK, 0},
00015     {Terminal::color::BLUE, 1},
00016     {Terminal::color::GREEN, 2},
00017     {Terminal::color::CYAN, 3},
00018     {Terminal::color::RED, 4},
00019     {Terminal::color::MAGENTA, 5},
```



```

00020     {Terminal::color::BROWN, 6},
00021     {Terminal::color::LIGHTGRAY, 7},
00022     {Terminal::color::DARKGRAY, 8},
00023     {Terminal::color::YELLOW, 14},
00024     {Terminal::color::WHITE, 15},
00025     {Terminal::color::RESET, 15},
00026 };
00027
00028
00029 Terminal::Terminal() {
00030     Terminal::_stdout = GetStdHandle(STD_OUTPUT_HANDLE);
00031     Terminal::_stderr = GetStdHandle(STD_ERROR_HANDLE);
00032 }
00033
00034 std::ostream& operator<<(std::ostream& os, const Terminal::color& c) {
00035     SetConsoleTextAttribute(Terminal::_stdout, Terminal::colormap.find(c)->second);
00036     return os;
00037 }
00038
00039 #else
00040
00041 std::map<Terminal::color, int> Terminal::colormap = {
00042     {Terminal::color::BLACK, 30},
00043     {Terminal::color::BLUE, 34},
00044     {Terminal::color::GREEN, 32},
00045     {Terminal::color::CYAN, 36},
00046     {Terminal::color::RED, 31},
00047     {Terminal::color::MAGENTA, 35},
00048     {Terminal::color::BROWN, 0},
00049     {Terminal::color::LIGHTGRAY, 0},
00050     {Terminal::color::DARKGRAY, 0},
00051     {Terminal::color::YELLOW, 33},
00052     {Terminal::color::WHITE, 37},
00053     {Terminal::color::RESET, 0},
00054 };
00055
00056 Terminal::Terminal() {
00057     /*this->*/
00058 }
00059
00060 std::ostream& operator<<(std::ostream& os, const Terminal::color& c) {
00061     char buf[6];
00062     sprintf(buf, "%d", Terminal::colormap.find(c)->second);
00063     os << "\e[" << buf << "m";
00064     return os;
00065 }
00066
00067
00068
00069
00070 #endif


```

9.66 term.h File Reference


```
#include <iostream>
```

```
#include <map>
```

Include dependency graph for term.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::CLI::Terminal](#)
pretty colors for [Terminal](#). Windows Only.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords API](#).
- [Markov::API::CLI](#)
Structure to hold parsed cli arguments.

Macros

- `#define TERM_FAIL "[" << Markov::API::CLI::Terminal::color::RED << "+" << Markov::API::CLI::Terminal::color::RESET << "]" "`
- `#define TERM_INFO "[" << Markov::API::CLI::Terminal::color::BLUE << "+" << Markov::API::CLI::Terminal::color::RESET << "]" "`
- `#define TERM_WARN "[" << Markov::API::CLI::Terminal::color::YELLOW << "+" << Markov::API::CLI::Terminal::color::RESET << "]" "`
- `#define TERM_SUCC "[" << Markov::API::CLI::Terminal::color::GREEN << "+" << Markov::API::CLI::Terminal::color::RESET << "]" "`

Functions

- `std::ostream & Markov::API::CLI::operator<< (std::ostream &os, const Markov::API::CLI::Terminal::color &c)`

9.66.1 Macro Definition Documentation

9.66.1.1 TERM_FAIL

```
#define TERM_FAIL "[" << Markov::API::CLI::Terminal::color::RED << "+" << Markov::API::CLI::Terminal::color::RESET << "]" "
```

Definition at line 10 of file [term.h](#).

9.66.1.2 TERM_INFO

```
#define TERM_INFO "[" << Markov::API::CLI::Terminal::color::BLUE << "+" << Markov::API::CLI::Terminal::color::RESET << "]" "
```

Definition at line 11 of file [term.h](#).

9.66.1.3 TERM_SUCC

```
#define TERM_SUCC "[" << Markov::API::CLI::Terminal::color::GREEN << "+" << Markov::API::CLI::Terminal::color::RESET << "]" "
```

Definition at line 13 of file [term.h](#).

9.66.1.4 TERM_WARN

```
#define TERM_WARN "[" << Markov::API::CLI::Terminal::color::YELLOW << "+" << Markov::API::CLI::Terminal::color::RESET << "]" "
```

Definition at line 12 of file [term.h](#).


9.67 term.h

```
00001 #pragma once
00002
00003 #ifdef _WIN32
00004 #include <Windows.h>
00005 #endif
00006
00007 #include <iostream>
00008 #include <map>
00009
00010 #define TERM_FAIL "[" << Markov::API::CLI::Terminal::color::RED << "+" <<
00011 Markov::API::CLI::Terminal::color::RESET << "]" "
00012 #define TERM_INFO "[" << Markov::API::CLI::Terminal::color::BLUE << "+" <<
00013 Markov::API::CLI::Terminal::color::RESET << "]" "
00014 #define TERM_WARN "[" << Markov::API::CLI::Terminal::color::YELLOW << "+" <<
00015 Markov::API::CLI::Terminal::color::RESET << "]" "
00016 #define TERM_SUCC "[" << Markov::API::CLI::Terminal::color::GREEN << "+" <<
00017 Markov::API::CLI::Terminal::color::RESET << "]" "
00018
00019 namespace Markov::API::CLI{
00020     /** @brief pretty colors for Terminal. Windows Only.
00021     */
00022     class Terminal {
00023     public:
00024
00025         /** Default constructor.
00026         * Get references to stdout and stderr handles.
00027         */
00028         Terminal();
00029
00030         enum color { RESET, BLACK, RED, GREEN, YELLOW, BLUE, MAGENTA, CYAN, WHITE, LIGHTGRAY,
00031 DARKGRAY, BROWN };
00032
00033         #ifdef _WIN32
00034             static HANDLE _stdout;
00035             static HANDLE _stderr;
00036             static std::map<Markov::API::CLI::Terminal::color, DWORD> colormap;
00037         #else
00038             static std::map<Markov::API::CLI::Terminal::color, int> colormap;
00039         #endif
00040
00041         static std::ostream endl;
00042
00043     };
00044
00045     /** overload for std::cout.
00046     */
00047     std::ostream& operator<<(std::ostream& os, const Markov::API::CLI::Terminal::color& c);
00048
00049 }
```

9.68 threadSharedListHandler.cpp File Reference

```
#include "threadSharedListHandler.h"
```

Include dependency graph for threadSharedListHandler.cpp:



9.69 threadSharedListHandler.cpp

```


00001 #include "threadSharedListHandler.h"
00002
00003
00004 Markov::API::Concurrency::ThreadSharedListHandler::ThreadSharedListHandler(const char* filename){
00005     this->listfile;
00006     this->listfile.open(filename, std::ios_base::binary);
00007 }
00008
00009
00010 bool Markov::API::Concurrency::ThreadSharedListHandler::next(std::string* line){
00011     bool res = false;
00012     this->mlock.lock();
00013     res = (std::getline(this->listfile, *line, '\n')) ? true : false;
00014     this->mlock.unlock();
00015
00016     return res;
00017 }
  
```

9.70 threadSharedListHandler.h File Reference


```

#include <string>
#include <fstream>
#include <mutex>
  
```

Include dependency graph for threadSharedListHandler.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::Concurrency::ThreadSharedListHandler](#)

Simple class for managing shared access to file.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords](#) API.
- [Markov::API::Concurrency](#)
Namespace for [Concurrency](#) related classes.

9.71 threadSharedListHandler.h

```

00001 #include <string>
00002 #include <fstream>
00003 #include <mutex>
00004
00005 /** @brief Namespace for Concurrency related classes
00006 */
00007 namespace Markov::API::Concurrency{
00008
00009 /** @brief Simple class for managing shared access to file

```

```

00010  *
00011  * This class maintains the handover of each line from a file to multiple threads.
00012  *
00013  * When two different threads try to read from the same file while reading a line isn't completed, it
00014  * can have unexpected results.
00015  * Line might be split, or might be read twice.
00016  * This class locks the read action on the list until a line is completed, and then proceeds with the
00017  * handover.
00018  *
00019  */
00020  class ThreadSharedListHandler{
00021  public:
00022     /** @brief Construct the Thread Handler with a filename
00023     *
00024     * Simply open the file, and initialize the locks.
00025     *
00026     * @b Example @b Use: Simple file read
00027     * @code{.cpp}
00028     * ThreadSharedListHandler listhandler("test.txt");
00029     * std::string line;
00030     * std::cout << listhandler->next(&line) << "\n";
00031     * @endcode
00032     *
00033     * @b Example @b Use: Example use case from MarkovPasswords showing multithreaded access
00034     * @code{.cpp}
00035     * void MarkovPasswords::Train(const char* datasetFileName, char delimiter, int threads) {
00036     *     ThreadSharedListHandler listhandler(datasetFileName);
00037     *     auto start = std::chrono::high_resolution_clock::now();
00038     *     std::vector<std::thread*> threadsV;
00039     *     for(int i=0;i<threads;i++){
00040     *         threadsV.push_back(new std::thread(&MarkovPasswords::TrainThread, this, &listhandler,
00041     * datasetFileName, delimiter));
00042     *     }
00043     *     for(int i=0;i<threads;i++){
00044     *         threadsV[i]->join();
00045     *         delete threadsV[i];
00046     *     }
00047     *     auto finish = std::chrono::high_resolution_clock::now();
00048     *     std::chrono::duration<double> elapsed = finish - start;
00049     *     std::cout << "Elapsed time: " << elapsed.count() << " s\n";
00050     * }
00051     *
00052     * void MarkovPasswords::TrainThread(ThreadSharedListHandler *listhandler, const char*
00053     * datasetFileName, char delimiter){
00054     *     char format_str[] = "%ld,%s";
00055     *     format_str[2]=delimiter;
00056     *     std::string line;
00057     *     while (listhandler->next(&line)) {
00058     *         long int oc;
00059     *         if (line.size() > 100) {
00060     *             line = line.substr(0, 100);
00061     *         }
00062     *         char* linebuf = new char[line.length()+5];
00063     *         sscanf_s(line.c_str(), format_str, &oc, linebuf, line.length()+5);
00064     *         this->AdjustEdge((const char*)linebuf, oc);
00065     *         delete linebuf;
00066     *     }
00067     * }
00068     * @endcode
00069     *
00070     * @param filename Filename for the file to manage.
00071     */
00072     ThreadSharedListHandler(const char* filename);
00073     /** @brief Read the next line from the file.
00074     *
00075     * This action will be blocked until another thread (if any) completes the read operation on the
00076     * file.
00077     *
00078     * @b Example @b Use: Simple file read
00079     * @code{.cpp}
00080     * ThreadSharedListHandler listhandler("test.txt");
00081     * std::string line;
00082     * std::cout << listhandler->next(&line) << "\n";
00083     * @endcode
00084     */
00085     bool next(std::string* line);
00086 private:
00087     std::ifstream listfile;
00088     std::mutex mlock;
00089 };
00090
00091

```


```
00092 };
```

9.72 Train.h File Reference

```
#include <QtWidgets/QMainWindow>
```

```
#include "ui_Train.h"
```

Include dependency graph for Train.h:



Classes

- class [Markov::GUI::Train](#)

QT Training page class.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::GUI](#)

namespace for MarkovPasswords [API GUI](#) wrapper

9.73 Train.h


```

00001 #pragma once
00002 #include <QtWidgets/QMainWindow>
00003 #include "ui_Train.h"
00004
00005 namespace Markov::GUI{
00006
00007     /** @brief QT Training page class
00008     */
00009     class Train :public QMainWindow {
00010     Q_OBJECT
00011     public:
00012         Train(QWidget* parent = Q_NULLPTR);
00013
00014     private:
00015         Ui::Train ui;
00016
00017     public slots:
00018         void home();
00019         void train();
00020     };
00021 };
```

9.74 UnitTests.cpp File Reference

```
#include "pch.h"
```

```
#include "CppUnitTest.h"
#include "MarkovModel/src/model.h"
Include dependency graph for UnitTests.cpp:
```



Namespaces

- [Testing](#)
Namespace for Microsoft Native Unit [Testing](#) Classes.
- [Testing::MVP](#)
[Testing](#) Namespace for Minimal Viable Product.
- [Testing::MVP::MarkovModel](#)
[Testing](#) Namespace for [MVP MarkovModel](#).
- [Testing::MVP::MarkovPasswords](#)
[Testing](#) namespace for [MVP MarkovPasswords](#).
- [Testing::MarkovModel](#)
[Testing](#) namespace for [MarkovModel](#).
- [Testing::MarkovPasswords](#)
[Testing](#) namespace for [MarkovPasswords](#).

Functions

- [Testing::MVP::MarkovModel::TEST_CLASS](#) (Edge)
Test class for minimal viable Edge.
- [Testing::MVP::MarkovModel::TEST_CLASS](#) (Node)
Test class for minimal viable Node.
- [Testing::MVP::MarkovModel::TEST_CLASS](#) (Model)
Test class for minimal viable Model.
- [Testing::MVP::MarkovPasswords::TEST_CLASS](#) (ArgParser)
Test Class for Argparse class.
- [Testing::MarkovModel::TEST_CLASS](#) (Edge)
Test class for rest of Edge cases.
- [Testing::MarkovModel::TEST_CLASS](#) (Node)
Test class for rest of Node cases.
- [Testing::MarkovModel::TEST_CLASS](#) (Model)
Test class for rest of model cases.

9.75 UnitTests.cpp

```

00001 #include "pch.h"
00002 #include "CppUnitTest.h"
00003 #include "MarkovModel/src/model.h"
00004
00005 using namespace Microsoft::VisualStudio::CppUnitTestFramework;
00006
00007
00008 /** @brief Namespace for Microsoft Native Unit Testing Classes
00009 */
00010 namespace Testing {
00011
00012     /** @brief Testing Namespace for Minimal Viable Product
00013     */
00014     namespace MVP {
00015         /** @brief Testing Namespace for MVP MarkovModel
00016         */
00017         namespace MarkovModel
00018         {
00019             /** @brief Test class for minimal viable Edge
00020             */
00021             TEST_CLASS(Edge)
00022             {
00023             public:
00024
00025                 /** @brief test default constructor
00026                 */
00027                 TEST_METHOD(default_constructor) {
00028                     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>;
00029                     Assert::IsNull(e->LeftNode());
00030                     Assert::IsNull(e->RightNode());
00031                     delete e;
00032                 }
00033
00034                 /** @brief test linked constructor with two nodes
00035                 */
00036                 TEST_METHOD(linked_constructor) {
00037                     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00038                     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00039                     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00040 RightNode);
00041                     Assert::IsTrue(LeftNode == e->LeftNode());
00042                     Assert::IsTrue(RightNode == e->RightNode());
00043                     delete LeftNode;
00044                     delete RightNode;
00045                     delete e;
00046                 }
00047
00048                 /** @brief test AdjustEdge function
00049                 */
00050                 TEST_METHOD(AdjustEdge) {
00051                     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00052                     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00053                     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00054 RightNode);
00055                     e->AdjustEdge(15);
00056                     Assert::AreEqual(15ull, e->EdgeWeight());
00057                     e->AdjustEdge(15);
00058                     Assert::AreEqual(30ull, e->EdgeWeight());
00059                     delete LeftNode;
00060                     delete RightNode;
00061                     delete e;
00062                 }
00063
00064                 /** @brief test TraverseNode returning RightNode
00065                 */
00066                 TEST_METHOD(TraverseNode) {
00067                     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00068                     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00069                     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00070 RightNode);
00071                     Assert::IsTrue(RightNode == e->TraverseNode());
00072                     delete LeftNode;
00073                     delete RightNode;
00074                     delete e;
00075                 }
00076
00077                 /** @brief test LeftNode/RightNode setter
00078                 */
00079                 TEST_METHOD(set_left_and_right) {
00080                     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00081                     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00082                     Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(LeftNode,
00083 RightNode);
00084                     Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>;

```

```

00082         e2->SetLeftEdge(LeftNode);
00083         e2->SetRightEdge(RightNode);
00084
00085         Assert::IsTrue(e1->LeftNode() == e2->LeftNode());
00086         Assert::IsTrue(e1->RightNode() == e2->RightNode());
00087         delete LeftNode;
00088         delete RightNode;
00089         delete e1;
00090         delete e2;
00091     }
00092
00093     /** @brief test negative adjustments
00094     */
00095     TEST_METHOD(negative_adjust) {
00096         Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00097         Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00098         Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
RightNode);
00099         e->AdjustEdge(15);
00100         Assert::AreEqual(15ull, e->EdgeWeight());
00101         e->AdjustEdge(-15);
00102         Assert::AreEqual(0ull, e->EdgeWeight());
00103         delete LeftNode;
00104         delete RightNode;
00105         delete e;
00106     }
00107 };
00108
00109     /** @brief Test class for minimal viable Node
00110     */
00111     TEST_CLASS(Node)
00112     {
00113     public:
00114
00115         /** @brief test default constructor
00116         */
00117         TEST_METHOD(default_constructor) {
00118             Markov::Node<unsigned char>* n = new Markov::Node<unsigned char>();
00119             Assert::AreEqual((unsigned char)0, n->NodeValue());
00120             delete n;
00121         }
00122
00123         /** @brief test custom constructor with unsigned char
00124         */
00125         TEST_METHOD(uchar_constructor) {
00126             Markov::Node<unsigned char>* n = NULL;
00127             unsigned char test_cases[] = { 'c', 0x00, 0xff, -32 };
00128             for (unsigned char tcase : test_cases) {
00129                 n = new Markov::Node<unsigned char>(tcase);
00130                 Assert::AreEqual(tcase, n->NodeValue());
00131                 delete n;
00132             }
00133         }
00134
00135         /** @brief test link function
00136         */
00137         TEST_METHOD(link_left) {
00138             Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00139             Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00140
00141             Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
00142             delete LeftNode;
00143             delete RightNode;
00144             delete e;
00145         }
00146
00147         /** @brief test link function
00148         */
00149         TEST_METHOD(link_right) {
00150             Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00151             Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00152
00153             Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(NULL, RightNode);
00154             LeftNode->Link(e);
00155             Assert::IsTrue(LeftNode == e->LeftNode());
00156             Assert::IsTrue(RightNode == e->RightNode());
00157             delete LeftNode;
00158             delete RightNode;
00159             delete e;
00160         }
00161
00162         /** @brief test RandomNext with low values
00163         */
00164         TEST_METHOD(rand_next_low) {
00165             Markov::Random::Marsaglia MarsagliaRandomEngine;
00166             Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00167             Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');

```

```

00168         Markov::Edge<unsigned char>* e = src->Link(target1);
00169         e->AdjustEdge(15);
00170         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00171         Assert::IsTrue(res == target1);
00172         delete src;
00173         delete target1;
00174         delete e;
00175     }
00176 }
00177
00178 /** @brief test RandomNext with 32 bit high values
00179 */
00180 TEST_METHOD(rand_next_u32) {
00181     Markov::Random::Marsaglia MarsagliaRandomEngine;
00182     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00183     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00184     Markov::Edge<unsigned char>* e = src->Link(target1);
00185     e->AdjustEdge(1 << 31);
00186     Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00187     Assert::IsTrue(res == target1);
00188     delete src;
00189     delete target1;
00190     delete e;
00191 }
00192
00193
00194 /** @brief random next on a node with no follow-ups
00195 */
00196 TEST_METHOD(rand_next_choice_1) {
00197     Markov::Random::Marsaglia MarsagliaRandomEngine;
00198     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00199     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00200     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00201     Markov::Edge<unsigned char>* e1 = src->Link(target1);
00202     Markov::Edge<unsigned char>* e2 = src->Link(target2);
00203     e1->AdjustEdge(1);
00204     e2->AdjustEdge((unsigned long)(1ull << 31));
00205     Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00206     Assert::IsNotNull(res);
00207     Assert::IsTrue(res == target2);
00208     delete src;
00209     delete target1;
00210     delete e1;
00211     delete e2;
00212 }
00213
00214 /** @brief random next on a node with no follow-ups
00215 */
00216 TEST_METHOD(rand_next_choice_2) {
00217     Markov::Random::Marsaglia MarsagliaRandomEngine;
00218     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00219     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00220     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00221     Markov::Edge<unsigned char>* e1 = src->Link(target1);
00222     Markov::Edge<unsigned char>* e2 = src->Link(target2);
00223     e2->AdjustEdge(1);
00224     e1->AdjustEdge((unsigned long)(1ull << 31));
00225     Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00226     Assert::IsNotNull(res);
00227     Assert::IsTrue(res == target1);
00228     delete src;
00229     delete target1;
00230     delete e1;
00231     delete e2;
00232 }
00233
00234
00235 /** @brief test updateEdges
00236 */
00237 TEST_METHOD(update_edges_count) {
00238
00239     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00240     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00241     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00242     Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00243     Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target2);
00244     e1->AdjustEdge(25);
00245     src->UpdateEdges(e1);
00246     e2->AdjustEdge(30);
00247     src->UpdateEdges(e2);
00248
00249     Assert::AreEqual((size_t)2, src->Edges()->size());
00250
00251     delete src;
00252     delete target1;
00253     delete e1;
00254     delete e2;

```

```

00255
00256     }
00257
00258     /** @brief test updateEdges
00259     */
00260     TEST_METHOD(update_edges_total) {
00261
00262         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00263         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00264         Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00265         Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target1);
00266         e1->AdjustEdge(25);
00267         src->UpdateEdges(e1);
00268         e2->AdjustEdge(30);
00269         src->UpdateEdges(e2);
00270
00271         //Assert::AreEqual(55ull, src->TotalEdgeWeights());
00272
00273         delete src;
00274         delete target1;
00275         delete e1;
00276         delete e2;
00277     }
00278
00279
00280     /** @brief test FindVertice
00281     */
00282     TEST_METHOD(find_vertice) {
00283
00284         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00285         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00286         Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00287         Markov::Edge<unsigned char>* res = NULL;
00288         src->Link(target1);
00289         src->Link(target2);
00290
00291
00292         res = src->FindEdge('b');
00293         Assert::IsNotNull(res);
00294         Assert::AreEqual((unsigned char)'b', res->TraverseNode()->NodeValue());
00295         res = src->FindEdge('c');
00296         Assert::IsNotNull(res);
00297         Assert::AreEqual((unsigned char)'c', res->TraverseNode()->NodeValue());
00298
00299         delete src;
00300         delete target1;
00301         delete target2;
00302
00303     }
00304
00305
00306
00307     /** @brief test FindVertice
00308     */
00309     TEST_METHOD(find_vertice_without_any) {
00310
00311         auto _invalid_next = [] {
00312             Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00313             Markov::Edge<unsigned char>* res = NULL;
00314
00315             res = src->FindEdge('b');
00316             Assert::IsNull(res);
00317
00318             delete src;
00319         };
00320
00321         //Assert::ExpectException<std::logic_error>(_invalid_next);
00322     }
00323
00324     /** @brief test FindVertice
00325     */
00326     TEST_METHOD(find_vertice_nonexistent) {
00327
00328         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00329         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00330         Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00331         Markov::Edge<unsigned char>* res = NULL;
00332         src->Link(target1);
00333         src->Link(target2);
00334
00335         res = src->FindEdge('D');
00336         Assert::IsNull(res);
00337
00338         delete src;
00339         delete target1;
00340         delete target2;
00341

```

```

00342     }
00343 };
00344
00345 /** @brief Test class for minimal viable Model
00346 */
00347 TEST_CLASS(Model)
00348 {
00349 public:
00350     /** @brief test model constructor for starter node
00351     */
00352     TEST_METHOD(model_constructor) {
00353         Markov::Model<unsigned char> m;
00354         Assert::AreEqual((unsigned char)'0', m.StarterNode()->NodeValue());
00355     }
00356
00357     /** @brief test import
00358     */
00359     TEST_METHOD(import_filename) {
00360         Markov::Model<unsigned char> m;
00361         Assert::IsTrue(m.Import("../MarkovPasswords/Models/2gram.mdl"));
00362     }
00363
00364     /** @brief test export
00365     */
00366     TEST_METHOD(export_filename) {
00367         Markov::Model<unsigned char> m;
00368         Assert::IsTrue(m.Export("../MarkovPasswords/Models/testcase.mdl"));
00369     }
00370
00371     /** @brief test random walk
00372     */
00373     TEST_METHOD(random_walk) {
00374         unsigned char* res = new unsigned char[12 + 5];
00375         Markov::Random::Marsaglia MarsagliaRandomEngine;
00376         Markov::Model<unsigned char> m;
00377         Assert::IsTrue(m.Import("../Models/finished2.mdl"));
00378         Assert::IsNotNull(m.RandomWalk(&MarsagliaRandomEngine, 1, 12, res));
00379     }
00380 };
00381
00382 /** @brief Testing namespace for MVP MarkovPasswords
00383 */
00384 namespace MarkovPasswords
00385 {
00386     /** @brief Test Class for Argparse class
00387     */
00388     TEST_CLASS(ArgParser)
00389     {
00390     public:
00391         /** @brief test basic generate
00392         */
00393         TEST_METHOD(generate_basic) {
00394             int argc = 8;
00395             char *argv[] = {"markov.exe", "generate", "-if", "model.mdl", "-of",
00396 "passwords.txt", "-n", "100"};
00397
00398             /*ProgramOptions *p = Argparse::parse(argc, argv);
00399             Assert::IsNotNull(p);
00400
00401             Assert::AreEqual(p->bImport, true);
00402             Assert::AreEqual(p->bExport, false);
00403             Assert::AreEqual(p->importname, "model.mdl");
00404             Assert::AreEqual(p->outputfilename, "passwords.txt");
00405             Assert::AreEqual(p->generateN, 100); */
00406
00407         }
00408
00409         /** @brief test basic generate reordered params
00410         */
00411         TEST_METHOD(generate_basic_reorder) {
00412             int argc = 8;
00413             char *argv[] = { "markov.exe", "generate", "-n", "100", "-if", "model.mdl", "-of",
"passwords.txt" };
00414
00415             /*ProgramOptions* p = Argparse::parse(argc, argv);
00416             Assert::IsNotNull(p);
00417
00418             Assert::AreEqual(p->bImport, true);
00419             Assert::AreEqual(p->bExport, false);
00420             Assert::AreEqual(p->importname, "model.mdl");
00421             Assert::AreEqual(p->outputfilename, "passwords.txt");
00422             Assert::AreEqual(p->generateN, 100);*/
00423
00424         }
00425
00426         /** @brief test basic generate param longnames
00427         */

```

```

00427         TEST_METHOD(generate_basic_longname) {
00428             int argc = 8;
00429             char *argv[] = { "markov.exe", "generate", "-n", "100", "--inputfilename",
"model.mdl", "--outputfilename", "passwords.txt" };
00430
00431             /*ProgramOptions* p = Argparse::parse(argc, argv);
00432             Assert::IsNotNull(p);
00433
00434             Assert::AreEqual(p->bImport, true);
00435             Assert::AreEqual(p->bExport, false);
00436             Assert::AreEqual(p->importname, "model.mdl");
00437             Assert::AreEqual(p->outputfilename, "passwords.txt");
00438             Assert::AreEqual(p->generateN, 100); */
00439         }
00440
00441         /** @brief test basic generate
00442         */
00443         TEST_METHOD(generate_fail_badmethod) {
00444             int argc = 8;
00445             char *argv[] = { "markov.exe", "junk", "-n", "100", "--inputfilename",
"model.mdl", "--outputfilename", "passwords.txt" };
00446
00447             /*ProgramOptions* p = Argparse::parse(argc, argv);
00448             Assert::IsNull(p); */
00449         }
00450
00451         /** @brief test basic train
00452         */
00453         TEST_METHOD(train_basic) {
00454             int argc = 4;
00455             char *argv[] = { "markov.exe", "train", "-ef", "model.mdl" };
00456
00457             /*ProgramOptions* p = Argparse::parse(argc, argv);
00458             Assert::IsNotNull(p);
00459
00460             Assert::AreEqual(p->bImport, false);
00461             Assert::AreEqual(p->bExport, true);
00462             Assert::AreEqual(p->exportname, "model.mdl"); */
00463         }
00464
00465         /** @brief test basic generate
00466         */
00467         TEST_METHOD(train_basic_longname) {
00468             int argc = 4;
00469             char *argv[] = { "markov.exe", "train", "--exportfilename", "model.mdl" };
00470
00471             /*ProgramOptions* p = Argparse::parse(argc, argv);
00472             Assert::IsNotNull(p);
00473
00474             Assert::AreEqual(p->bImport, false);
00475             Assert::AreEqual(p->bExport, true);
00476             Assert::AreEqual(p->exportname, "model.mdl"); */
00477         }
00478     };
00479
00480
00481
00482     };
00483
00484 }
00485
00486
00487
00488 /** @brief Testing namespace for MarkovModel
00489 */
00490 namespace MarkovModel {
00491
00492     /** @brief Test class for rest of Edge cases
00493     */
00494     TEST_CLASS(Edge)
00495     {
00496     public:
00497         /** @brief send exception on integer underflow
00498         */
00499         TEST_METHOD(except_integer_underflow) {
00500             auto _underflow_adjust = [] {
00501                 Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00502                 Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00503                 Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
RightNode);
00504                 e->AdjustEdge(15);
00505                 e->AdjustEdge(-30);
00506                 delete LeftNode;
00507                 delete RightNode;
00508                 delete e;
00509             };
00510             Assert::ExpectException<std::underflow_error>(_underflow_adjust);

```

```

00511     }
00512
00513     /** @brief test integer overflows
00514     */
00515     TEST_METHOD(except_integer_overflow) {
00516         auto _overflow_adjust = [] {
00517             Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00518             Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00519             Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
RightNode);
00520             e->AdjustEdge(~0ull);
00521             e->AdjustEdge(1);
00522             delete LeftNode;
00523             delete RightNode;
00524             delete e;
00525         };
00526         Assert::ExpectException<std::underflow_error>(_overflow_adjust);
00527     }
00528 };
00529
00530 /** @brief Test class for rest of Node cases
00531 */
00532 TEST_CLASS(Node)
00533 {
00534 public:
00535
00536     /** @brief test RandomNext with 64 bit high values
00537     */
00538     TEST_METHOD(rand_next_u64) {
00539         Markov::Random::Marsaglia MarsagliaRandomEngine;
00540         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00541         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00542         Markov::Edge<unsigned char>* e = src->Link(target1);
00543         e->AdjustEdge((unsigned long)(1ull << 63));
00544         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00545         Assert::IsTrue(res == target1);
00546         delete src;
00547         delete target1;
00548         delete e;
00549     }
00550
00551
00552     /** @brief test RandomNext with 64 bit high values
00553     */
00554     TEST_METHOD(rand_next_u64_max) {
00555         Markov::Random::Marsaglia MarsagliaRandomEngine;
00556         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00557         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00558         Markov::Edge<unsigned char>* e = src->Link(target1);
00559         e->AdjustEdge((0xffffffff));
00560         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00561         Assert::IsTrue(res == target1);
00562         delete src;
00563         delete target1;
00564         delete e;
00565     }
00566
00567
00568     /** @brief randomNext when no edges are present
00569     */
00570     TEST_METHOD(uninitialized_rand_next) {
00571
00572         auto _invalid_next = [] {
00573             Markov::Random::Marsaglia MarsagliaRandomEngine;
00574             Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00575             Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00576             Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(src, target1);
00577             Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00578
00579             delete src;
00580             delete target1;
00581             delete e;
00582         };
00583
00584         Assert::ExpectException<std::logic_error>(_invalid_next);
00585     }
00586
00587 };
00588
00589
00590 /** @brief Test class for rest of model cases
00591 */
00592 TEST_CLASS(Model)
00593 {
00594 public:
00595     TEST_METHOD(functional_random_walk) {
00596         unsigned char* res2 = new unsigned char[12 + 5];

```

```

00597         Markov::Random::Marsaglia MarsagliaRandomEngine;
00598         Markov::Model<unsigned char> m;
00599         Markov::Node<unsigned char>* starter = m.StarterNode();
00600         Markov::Node<unsigned char>* a = new Markov::Node<unsigned char>('a');
00601         Markov::Node<unsigned char>* b = new Markov::Node<unsigned char>('b');
00602         Markov::Node<unsigned char>* c = new Markov::Node<unsigned char>('c');
00603         Markov::Node<unsigned char>* end = new Markov::Node<unsigned char>(0xff);
00604         starter->Link(a)->AdjustEdge(1);
00605         a->Link(b)->AdjustEdge(1);
00606         b->Link(c)->AdjustEdge(1);
00607         c->Link(end)->AdjustEdge(1);
00608
00609         char* res = (char*)m.RandomWalk(&MarsagliaRandomEngine,1,12,res2);
00610         Assert::IsFalse(strcmp(res, "abc"));
00611     }
00612     TEST_METHOD(functional_random_walk_without_any) {
00613         Markov::Model<unsigned char> m;
00614         Markov::Node<unsigned char>* starter = m.StarterNode();
00615         Markov::Node<unsigned char>* a = new Markov::Node<unsigned char>('a');
00616         Markov::Node<unsigned char>* b = new Markov::Node<unsigned char>('b');
00617         Markov::Node<unsigned char>* c = new Markov::Node<unsigned char>('c');
00618         Markov::Node<unsigned char>* end = new Markov::Node<unsigned char>(0xff);
00619         Markov::Edge<unsigned char>* res = NULL;
00620         starter->Link(a)->AdjustEdge(1);
00621         a->Link(b)->AdjustEdge(1);
00622         b->Link(c)->AdjustEdge(1);
00623         c->Link(end)->AdjustEdge(1);
00624
00625         res = starter->FindEdge('D');
00626         Assert::IsNull(res);
00627     }
00628 }
00629 };
00630
00631 }
00632
00633 /** @brief Testing namespace for MarkovPasswords
00634 */
00635 namespace MarkovPasswords {
00636
00637 };
00638
00639 }

```


Index

- [_left](#)
 - [Markov::Edge< NodeStorageType >, 98](#)
 - [_right](#)
 - [Markov::Edge< NodeStorageType >, 98](#)
 - [_value](#)
 - [Markov::Node< storageType >, 179](#)
 - [_weight](#)
 - [Markov::Edge< NodeStorageType >, 98](#)
- [about](#)
 - [Markov::GUI::about, 46](#)
 - [Markov::GUI::CLI, 53](#)
 - [Markov::GUI::menu, 132](#)
- [about.h, 191](#)
- [action](#)
 - [markopy_cli, 19](#)
- [AdjustEdge](#)
 - [Markov::API::CUDA::CUDAModelMatrix, 64](#)
 - [Markov::API::MarkovPasswords, 102](#)
 - [Markov::API::ModelMatrix, 150](#)
 - [Markov::Edge< NodeStorageType >, 96](#)
 - [Markov::Model< NodeStorageType >, 139](#)
- [AllocVRAMOutputBuffer](#)
 - [Markov::API::CUDA::CUDAModelMatrix, 65](#)
- [alphabet](#)
 - [model_2gram, 27](#)
 - [random-model, 27](#)
- [Argparse](#)
 - [Markov::API::CLI::Argparse, 48](#)
- [argparse.cpp, 192](#)
- [argparse.h, 192, 194](#)
 - [BOOST_ALL_DYN_LINK, 194](#)
- [args](#)
 - [markopy_cli, 19](#)
- [bExport](#)
 - [Markov::API::CLI::_programOptions, 43](#)
- [bFailure](#)
 - [Markov::API::CLI::_programOptions, 43](#)
- [blImport](#)
 - [Markov::API::CLI::_programOptions, 43](#)
- [BLACK](#)
 - [Markov::API::CLI::Terminal, 183](#)
- [BLUE](#)
 - [Markov::API::CLI::Terminal, 183](#)
- [BOOST_ALL_DYN_LINK](#)
 - [argparse.h, 194](#)
- [BOOST_PYTHON_MODULE](#)
 - [Markov::Markopy, 25](#)
- [BOOST_PYTHON_STATIC_LIB](#)
 - [markopy.cpp, 214](#)
- [BROWN](#)
 - [Markov::API::CLI::Terminal, 183](#)
- [bulk](#)
 - [markopy_cli, 19](#)
- [CLI](#)
 - [Markov::GUI::CLI, 53](#)
- [CLI.h, 197, 198](#)
- [cli_generate](#)
 - [markopy_cli, 17](#)
- [cli_init](#)
 - [markopy_cli, 18](#)
- [cli_train](#)
 - [markopy_cli, 18](#)
- [color](#)
 - [Markov::API::CLI::Terminal, 183](#)
- [colormap](#)
 - [Markov::API::CLI::Terminal, 183](#)
- [ConstructMatrix](#)
 - [Markov::API::CUDA::CUDAModelMatrix, 65](#)
 - [Markov::API::ModelMatrix, 151](#)
- [corpus_list](#)
 - [markopy_cli, 19](#)
- [CudaCheckNotifyErr](#)
 - [Markov::API::CUDA::CUDADeviceController, 56](#)
 - [Markov::API::CUDA::CUDAModelMatrix, 66](#)
 - [Markov::API::CUDA::Random::Marsaglia, 118](#)
- [cudaDeviceController.h, 198, 199](#)
- [CudaMalloc2DToFlat](#)
 - [Markov::API::CUDA::CUDADeviceController, 56](#)
 - [Markov::API::CUDA::CUDAModelMatrix, 67](#)
 - [Markov::API::CUDA::Random::Marsaglia, 118](#)
- [CudaMemcpy2DToFlat](#)
 - [Markov::API::CUDA::CUDADeviceController, 57](#)
 - [Markov::API::CUDA::CUDAModelMatrix, 68](#)
 - [Markov::API::CUDA::Random::Marsaglia, 119](#)
- [CudaMigrate2DFlat](#)
 - [Markov::API::CUDA::CUDADeviceController, 58](#)
 - [Markov::API::CUDA::CUDAModelMatrix, 69](#)
 - [Markov::API::CUDA::Random::Marsaglia, 120](#)
- [cudaModelMatrix.h, 201, 202](#)
- [cudarandom.h, 203, 204](#)
- [CYAN](#)
 - [Markov::API::CLI::Terminal, 183](#)
- [DARKGRAY](#)
 - [Markov::API::CLI::Terminal, 183](#)
- [datasetFile](#)
 - [Markov::API::CUDA::CUDAModelMatrix, 86](#)

- Markov::API::MarkovPasswords, 112
- Markov::API::ModelMatrix, 169
- datasetname
 - Markov::API::CLI::_programOptions, 43
- DeallocateMatrix
 - Markov::API::CUDA::CUDAModelMatrix, 70
 - Markov::API::ModelMatrix, 153
- default
 - markopy_cli, 19
- device_edgeMatrix
 - Markov::API::CUDA::CUDAModelMatrix, 86
- device_matrixIndex
 - Markov::API::CUDA::CUDAModelMatrix, 86
- device_outputBuffer
 - Markov::API::CUDA::CUDAModelMatrix, 86
- device_totalEdgeWeights
 - Markov::API::CUDA::CUDAModelMatrix, 86
- device_valueMatrix
 - Markov::API::CUDA::CUDAModelMatrix, 87
- devrandom
 - Markov::API::CUDA::Random, 24
- distribution
 - Markov::API::CUDA::Random::Marsaglia, 121
 - Markov::Random::DefaultRandomEngine, 91
 - Markov::Random::Marsaglia, 127
 - Markov::Random::Mersenne, 135
- dllmain.cpp, 205
- DumpJSON
 - Markov::API::CUDA::CUDAModelMatrix, 71
 - Markov::API::ModelMatrix, 153
- Edge
 - Markov::Edge< NodeStorageType >, 95
- edge.h, 206, 207
- edgeMatrix
 - Markov::API::CUDA::CUDAModelMatrix, 87
 - Markov::API::ModelMatrix, 169
- Edges
 - Markov::API::CUDA::CUDAModelMatrix, 72
 - Markov::API::MarkovPasswords, 103
 - Markov::API::ModelMatrix, 154
 - Markov::Model< NodeStorageType >, 140
 - Markov::Node< storageType >, 175
- edges
 - Markov::API::CUDA::CUDAModelMatrix, 87
 - Markov::API::MarkovPasswords, 112
 - Markov::API::ModelMatrix, 169
 - Markov::Model< NodeStorageType >, 145
 - Markov::Node< storageType >, 179
- edgesV
 - Markov::Node< storageType >, 179
- EdgeWeight
 - Markov::Edge< NodeStorageType >, 96
- endl
 - Markov::API::CLI::Terminal, 184
- Export
 - Markov::API::CUDA::CUDAModelMatrix, 72
 - Markov::API::MarkovPasswords, 103, 104
 - Markov::API::ModelMatrix, 154, 155
- Markov::Model< NodeStorageType >, 140, 141
- exportname
 - Markov::API::CLI::_programOptions, 44
- f
 - model_2gram, 27
 - random-model, 27
- FastRandomWalk
 - Markov::API::CUDA::CUDAModelMatrix, 73
 - Markov::API::ModelMatrix, 155
- FastRandomWalkCUDAKernel
 - Markov::API::CUDA, 23
- FastRandomWalkPartition
 - Markov::API::CUDA::CUDAModelMatrix, 74
 - Markov::API::ModelMatrix, 157
- FastRandomWalkThread
 - Markov::API::CUDA::CUDAModelMatrix, 75
 - Markov::API::ModelMatrix, 159
- FindEdge
 - Markov::Node< storageType >, 175
- flatEdgeMatrix
 - Markov::API::CUDA::CUDAModelMatrix, 87
- FlattenMatrix
 - Markov::API::CUDA::CUDAModelMatrix, 77
- flatValueMatrix
 - Markov::API::CUDA::CUDAModelMatrix, 87
- framework.h, 209
- WIN32_LEAN_AND_MEAN, 209
- Generate
 - Markov::API::CUDA::CUDAModelMatrix, 77
 - Markov::API::MarkovPasswords, 104
 - Markov::API::ModelMatrix, 160
- generateN
 - Markov::API::CLI::_programOptions, 44
- GenerateThread
 - Markov::API::CUDA::CUDAModelMatrix, 78
 - Markov::API::MarkovPasswords, 105
 - Markov::API::ModelMatrix, 161
- generator
 - Markov::API::CUDA::Random::Marsaglia, 122
 - Markov::Random::DefaultRandomEngine, 91
 - Markov::Random::Marsaglia, 128
 - Markov::Random::Mersenne, 135
- getProgramOptions
 - Markov::API::CLI::Argparse, 50
- GREEN
 - Markov::API::CLI::Terminal, 183
- help
 - markopy_cli, 19
 - Markov::API::CLI::Argparse, 50
- home
 - Markov::GUI::Train, 189
- Import
 - Markov::API::CUDA::CUDAModelMatrix, 79, 80
 - Markov::API::MarkovPasswords, 106
 - Markov::API::ModelMatrix, 162, 163

- Markov::Model< NodeStorageType >, 142
- importname
 - Markov::API::CLI::_programOptions, 44
- intHandler
 - markovPasswords.cpp, 218
- keepRunning
 - markovPasswords.cpp, 218
- LeftNode
 - Markov::Edge< NodeStorageType >, 96
- LIGHTGRAY
 - Markov::API::CLI::Terminal, 183
- Link
 - Markov::Node< storageType >, 176
- ListCudaDevices
 - Markov::API::CUDA::CUDADeviceController, 59
 - Markov::API::CUDA::CUDAModelMatrix, 81
 - Markov::API::CUDA::Random::Marsaglia, 122
- listfile
 - Markov::API::Concurrency::ThreadSharedListHandler, 187
- MAGENTA
 - Markov::API::CLI::Terminal, 183
- main
 - src/main.cpp, 210
 - UI/src/main.cpp, 212
- main.cpp, 209, 211, 213
- markopy.cpp, 213, 214
 - BOOST_PYTHON_STATIC_LIB, 214
- markopy_cli, 17
 - action, 19
 - args, 19
 - bulk, 19
 - cli_generate, 17
 - cli_init, 18
 - cli_train, 18
 - corpus_list, 19
 - default, 19
 - help, 19
 - model, 19
 - model_base, 19
 - model_extension, 19
 - model_list, 20
 - output, 20
 - output_file_name, 20
 - output_forced, 20
 - parser, 20
 - True, 20
- markopy_cli.py, 214, 215
- Markov, 20
- Markov::API, 21
- Markov::API::CLI, 21
 - operator<, 22
 - ProgramOptions, 22
- Markov::API::CLI::_programOptions, 41
 - bExport, 43
 - bFailure, 43
 - blImport, 43
 - datasetname, 43
 - exportname, 44
 - generateN, 44
 - importname, 44
 - outputfilename, 44
 - seperator, 44
 - wordlistname, 44
- Markov::API::CLI::Argparse, 46
 - Argparse, 48
 - getProgramOptions, 50
 - help, 50
 - parse, 51
 - po, 52
 - setProgramOptions, 51
- Markov::API::CLI::Terminal, 181
 - BLACK, 183
 - BLUE, 183
 - BROWN, 183
 - color, 183
 - colormap, 183
 - CYAN, 183
 - DARKGRAY, 183
 - endl, 184
 - GREEN, 183
 - LIGHTGRAY, 183
 - MAGENTA, 183
 - RED, 183
 - RESET, 183
 - Terminal, 183
 - WHITE, 183
 - YELLOW, 183
- Markov::API::Concurrency, 22
- Markov::API::Concurrency::ThreadSharedListHandler, 184
 - listfile, 187
 - mlock, 187
 - next, 187
 - ThreadSharedListHandler, 186
- Markov::API::CUDA, 22
 - FastRandomWalkCUDAKernel, 23
 - strchr, 24
- Markov::API::CUDA::CUDADeviceController, 54
 - CudaCheckNotifyErr, 56
 - CudaMalloc2DToFlat, 56
 - CudaMemcpy2DToFlat, 57
 - CudaMigrate2DFlat, 58
 - ListCudaDevices, 59
- Markov::API::CUDA::CUDAModelMatrix, 60
 - AdjustEdge, 64
 - AllocVRAMOutputBuffer, 65
 - ConstructMatrix, 65
 - CudaCheckNotifyErr, 66
 - CudaMalloc2DToFlat, 67
 - CudaMemcpy2DToFlat, 68
 - CudaMigrate2DFlat, 69
 - datasetFile, 86
 - DeallocateMatrix, 70

- device_edgeMatrix, [86](#)
- device_matrixIndex, [86](#)
- device_outputBuffer, [86](#)
- device_totalEdgeWeights, [86](#)
- device_valueMatrix, [87](#)
- DumpJSON, [71](#)
- edgeMatrix, [87](#)
- Edges, [72](#)
- edges, [87](#)
- Export, [72](#)
- FastRandomWalk, [73](#)
- FastRandomWalkPartition, [74](#)
- FastRandomWalkThread, [75](#)
- flatEdgeMatrix, [87](#)
- FlattenMatrix, [77](#)
- flatValueMatrix, [87](#)
- Generate, [77](#)
- GenerateThread, [78](#)
- Import, [79](#), [80](#)
- ListCudaDevices, [81](#)
- matrixIndex, [87](#)
- matrixSize, [87](#)
- MigrateMatrix, [81](#)
- modelSavefile, [88](#)
- Nodes, [81](#)
- nodes, [88](#)
- OpenDatasetFile, [82](#)
- outputBuffer, [88](#)
- outputFile, [88](#)
- RandomWalk, [82](#)
- ready, [88](#)
- Save, [83](#)
- StarterNode, [84](#)
- starterNode, [88](#)
- totalEdgeWeights, [88](#)
- Train, [84](#)
- TrainThread, [85](#)
- valueMatrix, [88](#)
- Markov::API::CUDA::Random, [24](#)
 - devrandom, [24](#)
- Markov::API::CUDA::Random::Marsaglia, [115](#)
 - CudaCheckNotifyErr, [118](#)
 - CudaMalloc2DToFlat, [118](#)
 - CudaMemcpy2DToFlat, [119](#)
 - CudaMigrate2DFlat, [120](#)
 - distribution, [121](#)
 - generator, [122](#)
 - ListCudaDevices, [122](#)
 - MigrateToVRAM, [123](#)
 - random, [123](#)
 - rd, [124](#)
 - x, [124](#)
 - y, [124](#)
 - z, [124](#)
- Markov::API::MarkovPasswords, [98](#)
 - AdjustEdge, [102](#)
 - datasetFile, [112](#)
 - Edges, [103](#)
 - edges, [112](#)
 - Export, [103](#), [104](#)
 - Generate, [104](#)
 - GenerateThread, [105](#)
 - Import, [106](#)
 - MarkovPasswords, [102](#)
 - modelSavefile, [112](#)
 - Nodes, [107](#)
 - nodes, [112](#)
 - OpenDatasetFile, [107](#)
 - outputFile, [112](#)
 - RandomWalk, [108](#)
 - Save, [109](#)
 - StarterNode, [110](#)
 - starterNode, [113](#)
 - Train, [110](#)
 - TrainThread, [111](#)
- Markov::API::ModelMatrix, [146](#)
 - AdjustEdge, [150](#)
 - ConstructMatrix, [151](#)
 - datasetFile, [169](#)
 - DeallocateMatrix, [153](#)
 - DumpJSON, [153](#)
 - edgeMatrix, [169](#)
 - Edges, [154](#)
 - edges, [169](#)
 - Export, [154](#), [155](#)
 - FastRandomWalk, [155](#)
 - FastRandomWalkPartition, [157](#)
 - FastRandomWalkThread, [159](#)
 - Generate, [160](#)
 - GenerateThread, [161](#)
 - Import, [162](#), [163](#)
 - matrixIndex, [169](#)
 - matrixSize, [169](#)
 - ModelMatrix, [150](#)
 - modelSavefile, [169](#)
 - Nodes, [164](#)
 - nodes, [169](#)
 - OpenDatasetFile, [164](#)
 - outputFile, [170](#)
 - RandomWalk, [165](#)
 - ready, [170](#)
 - Save, [166](#)
 - StarterNode, [167](#)
 - starterNode, [170](#)
 - totalEdgeWeights, [170](#)
 - Train, [167](#)
 - TrainThread, [168](#)
 - valueMatrix, [170](#)
- Markov::Edge< NodeStorageType >, [93](#)
 - _left, [98](#)
 - _right, [98](#)
 - _weight, [98](#)
 - AdjustEdge, [96](#)
 - Edge, [95](#)
 - EdgeWeight, [96](#)
 - LeftNode, [96](#)

- RightNode, [97](#)
- SetLeftEdge, [97](#)
- SetRightEdge, [97](#)
- TraverseNode, [98](#)
- Markov::GUI, [25](#)
- Markov::GUI::about, [45](#)
 - about, [46](#)
 - ui, [46](#)
- Markov::GUI::CLI, [52](#)
 - about, [53](#)
 - CLI, [53](#)
 - start, [54](#)
 - statistics, [54](#)
 - ui, [54](#)
- Markov::GUI::MarkovPasswordsGUI, [113](#)
 - MarkovPasswordsGUI::pass, [115](#)
 - MarkovPasswordsGUI::benchmarkSelected, [115](#)
 - MarkovPasswordsGUI::comparisonSelected, [115](#)
 - MarkovPasswordsGUI::home, [115](#)
 - MarkovPasswordsGUI::model, [115](#)
 - MarkovPasswordsGUI::modelvisSelected, [115](#)
 - MarkovPasswordsGUI::visualDebugSelected, [115](#)
 - ui, [115](#)
- Markov::GUI::menu, [130](#)
 - about, [132](#)
 - menu, [131](#)
 - ui, [132](#)
 - visualization, [132](#)
- Markov::GUI::Train, [188](#)
 - home, [189](#)
 - Train, [189](#)
 - train, [189](#)
 - ui, [189](#)
- Markov::Markopy, [25](#)
 - BOOST_PYTHON_MODULE, [25](#)
- Markov::Model< NodeStorageType >, [137](#)
 - AdjustEdge, [139](#)
 - Edges, [140](#)
 - edges, [145](#)
 - Export, [140](#), [141](#)
 - Import, [142](#)
 - Model, [139](#)
 - Nodes, [144](#)
 - nodes, [146](#)
 - RandomWalk, [144](#)
 - StarterNode, [145](#)
 - starterNode, [146](#)
- Markov::Node< storageType >, [170](#)
 - _value, [179](#)
 - Edges, [175](#)
 - edges, [179](#)
 - edgesV, [179](#)
 - FindEdge, [175](#)
 - Link, [176](#)
 - Node, [173](#)
 - NodeValue, [177](#)
 - RandomNext, [177](#)
 - total_edge_weights, [179](#)
 - TotalEdgeWeights, [178](#)
 - UpdateEdges, [178](#)
 - UpdateTotalVerticeWeight, [179](#)
- Markov::Random, [26](#)
- Markov::Random::DefaultRandomEngine, [89](#)
 - distribution, [91](#)
 - generator, [91](#)
 - random, [92](#)
 - rd, [92](#)
- Markov::Random::Marsaglia, [125](#)
 - distribution, [127](#)
 - generator, [128](#)
 - Marsaglia, [127](#)
 - random, [128](#)
 - rd, [129](#)
 - x, [129](#)
 - y, [129](#)
 - z, [130](#)
- Markov::Random::Mersenne, [132](#)
 - distribution, [135](#)
 - generator, [135](#)
 - random, [136](#)
 - rd, [136](#)
- Markov::Random::RandomEngine, [180](#)
 - random, [181](#)
- MarkovPasswords
 - Markov::API::MarkovPasswords, [102](#)
- markovPasswords.cpp, [217](#), [219](#)
 - intHandler, [218](#)
 - keepRunning, [218](#)
- markovPasswords.h, [220](#), [221](#)
- MarkovPasswordsGUI::pass
 - Markov::GUI::MarkovPasswordsGUI, [115](#)
- MarkovPasswordsGUI.cpp, [223](#)
- MarkovPasswordsGUI.h, [224](#), [225](#)
- MarkovPasswordsGUI::benchmarkSelected
 - Markov::GUI::MarkovPasswordsGUI, [115](#)
- MarkovPasswordsGUI::comparisonSelected
 - Markov::GUI::MarkovPasswordsGUI, [115](#)
- MarkovPasswordsGUI::home
 - Markov::GUI::MarkovPasswordsGUI, [115](#)
- MarkovPasswordsGUI::model
 - Markov::GUI::MarkovPasswordsGUI, [115](#)
- MarkovPasswordsGUI::modelvisSelected
 - Markov::GUI::MarkovPasswordsGUI, [115](#)
- MarkovPasswordsGUI::visualDebugSelected
 - Markov::GUI::MarkovPasswordsGUI, [115](#)
- Marsaglia
 - Markov::Random::Marsaglia, [127](#)
- matrixIndex
 - Markov::API::CUDA::CUDAModelMatrix, [87](#)
 - Markov::API::ModelMatrix, [169](#)
- matrixSize
 - Markov::API::CUDA::CUDAModelMatrix, [87](#)
 - Markov::API::ModelMatrix, [169](#)
- menu
 - Markov::GUI::menu, [131](#)
- menu.cpp, [225](#)

- menu.h, [226](#), [227](#)
- MigrateMatrix
 - Markov::API::CUDA::CUDAModelMatrix, [81](#)
- MigrateToVRAM
 - Markov::API::CUDA::Random::Marsaglia, [123](#)
- mlock
 - Markov::API::Concurrency::ThreadSharedListHandler, [187](#)
- Model
 - Markov::Model< NodeStorageType >, [139](#)
- model
 - markopy_cli, [19](#)
- model.h, [227](#), [228](#)
- model_2gram, [26](#)
 - alphabet, [27](#)
 - f, [27](#)
- model_2gram.py, [232](#), [233](#)
- model_base
 - markopy_cli, [19](#)
- model_extension
 - markopy_cli, [19](#)
- model_list
 - markopy_cli, [20](#)
- ModelMatrix
 - Markov::API::ModelMatrix, [150](#)
- modelMatrix.cpp, [233](#)
- modelMatrix.h, [236](#), [237](#)
- modelSavefile
 - Markov::API::CUDA::CUDAModelMatrix, [88](#)
 - Markov::API::MarkovPasswords, [112](#)
 - Markov::API::ModelMatrix, [169](#)
- next
 - Markov::API::Concurrency::ThreadSharedListHandler, [187](#)
- Node
 - Markov::Node< storageType >, [173](#)
- node.h, [239](#), [240](#)
- Nodes
 - Markov::API::CUDA::CUDAModelMatrix, [81](#)
 - Markov::API::MarkovPasswords, [107](#)
 - Markov::API::ModelMatrix, [164](#)
 - Markov::Model< NodeStorageType >, [144](#)
- nodes
 - Markov::API::CUDA::CUDAModelMatrix, [88](#)
 - Markov::API::MarkovPasswords, [112](#)
 - Markov::API::ModelMatrix, [169](#)
 - Markov::Model< NodeStorageType >, [146](#)
- NodeValue
 - Markov::Node< storageType >, [177](#)
- OpenDatasetFile
 - Markov::API::CUDA::CUDAModelMatrix, [82](#)
 - Markov::API::MarkovPasswords, [107](#)
 - Markov::API::ModelMatrix, [164](#)
- operator<<
 - Markov::API::CLI, [22](#)
 - term.cpp, [251](#)
- output
 - markopy_cli, [20](#)
 - output_file_name
 - markopy_cli, [20](#)
 - output_forced
 - markopy_cli, [20](#)
 - outputBuffer
 - Markov::API::CUDA::CUDAModelMatrix, [88](#)
 - outputFile
 - Markov::API::CUDA::CUDAModelMatrix, [88](#)
 - Markov::API::MarkovPasswords, [112](#)
 - Markov::API::ModelMatrix, [170](#)
 - outputfilename
 - Markov::API::CLI::_programOptions, [44](#)
- parse
 - Markov::API::CLI::Argparse, [51](#)
- parser
 - markopy_cli, [20](#)
- pch.cpp, [244](#), [245](#)
- pch.h, [245](#), [246](#)
- po
 - Markov::API::CLI::Argparse, [52](#)
- ProgramOptions
 - Markov::API::CLI, [22](#)
- random, [27](#)
 - Markov::API::CUDA::Random::Marsaglia, [123](#)
 - Markov::Random::DefaultRandomEngine, [92](#)
 - Markov::Random::Marsaglia, [128](#)
 - Markov::Random::Mersenne, [136](#)
 - Markov::Random::RandomEngine, [181](#)
- random-model, [27](#)
 - alphabet, [27](#)
 - f, [27](#)
- random-model.py, [246](#)
- random.h, [247](#), [248](#)
- RandomNext
 - Markov::Node< storageType >, [177](#)
- RandomWalk
 - Markov::API::CUDA::CUDAModelMatrix, [82](#)
 - Markov::API::MarkovPasswords, [108](#)
 - Markov::API::ModelMatrix, [165](#)
 - Markov::Model< NodeStorageType >, [144](#)
- rd
 - Markov::API::CUDA::Random::Marsaglia, [124](#)
 - Markov::Random::DefaultRandomEngine, [92](#)
 - Markov::Random::Marsaglia, [129](#)
 - Markov::Random::Mersenne, [136](#)
- README.md, [250](#)
- ready
 - Markov::API::CUDA::CUDAModelMatrix, [88](#)
 - Markov::API::ModelMatrix, [170](#)
- RED
 - Markov::API::CLI::Terminal, [183](#)
- RESET
 - Markov::API::CLI::Terminal, [183](#)
- RightNode
 - Markov::Edge< NodeStorageType >, [97](#)

- Save
 - Markov::API::CUDA::CUDAModelMatrix, [83](#)
 - Markov::API::MarkovPasswords, [109](#)
 - Markov::API::ModelMatrix, [166](#)
- separator
 - Markov::API::CLI::_programOptions, [44](#)
- SetLeftEdge
 - Markov::Edge< NodeStorageType >, [97](#)
- setProgramOptions
 - Markov::API::CLI::Argparse, [51](#)
- SetRightEdge
 - Markov::Edge< NodeStorageType >, [97](#)
- src/main.cpp
 - main, [210](#)
- start
 - Markov::GUI::CLI, [54](#)
- StarterNode
 - Markov::API::CUDA::CUDAModelMatrix, [84](#)
 - Markov::API::MarkovPasswords, [110](#)
 - Markov::API::ModelMatrix, [167](#)
 - Markov::Model< NodeStorageType >, [145](#)
- starterNode
 - Markov::API::CUDA::CUDAModelMatrix, [88](#)
 - Markov::API::MarkovPasswords, [113](#)
 - Markov::API::ModelMatrix, [170](#)
 - Markov::Model< NodeStorageType >, [146](#)
- statistics
 - Markov::GUI::CLI, [54](#)
- strchr
 - Markov::API::CUDA, [24](#)
- term.cpp, [250](#), [251](#)
 - operator<<, [251](#)
- term.h, [252](#), [254](#)
 - TERM_FAIL, [253](#)
 - TERM_INFO, [253](#)
 - TERM_SUCC, [254](#)
 - TERM_WARN, [254](#)
- TERM_FAIL
 - term.h, [253](#)
- TERM_INFO
 - term.h, [253](#)
- TERM_SUCC
 - term.h, [254](#)
- TERM_WARN
 - term.h, [254](#)
- Terminal
 - Markov::API::CLI::Terminal, [183](#)
- TEST_CLASS
 - Testing::MarkovModel, [28–30](#)
 - Testing::MVP::MarkovModel, [32–34](#)
 - Testing::MVP::MarkovPasswords, [37](#)
- Testing, [28](#)
- Testing::MarkovModel, [28](#)
 - TEST_CLASS, [28–30](#)
- Testing::MarkovPasswords, [31](#)
- Testing::MVP, [31](#)
- Testing::MVP::MarkovModel, [32](#)
 - TEST_CLASS, [32–34](#)
- Testing::MVP::MarkovPasswords, [37](#)
 - TEST_CLASS, [37](#)
- ThreadSharedListHandler
 - Markov::API::Concurrency::ThreadSharedListHandler, [186](#)
- threadSharedListHandler.cpp, [255](#)
- threadSharedListHandler.h, [255](#), [256](#)
- total_edge_weights
 - Markov::Node< storageType >, [179](#)
- TotalEdgeWeights
 - Markov::Node< storageType >, [178](#)
- totalEdgeWeights
 - Markov::API::CUDA::CUDAModelMatrix, [88](#)
 - Markov::API::ModelMatrix, [170](#)
- Train
 - Markov::API::CUDA::CUDAModelMatrix, [84](#)
 - Markov::API::MarkovPasswords, [110](#)
 - Markov::API::ModelMatrix, [167](#)
 - Markov::GUI::Train, [189](#)
- train
 - Markov::GUI::Train, [189](#)
- Train.h, [258](#)
- TrainThread
 - Markov::API::CUDA::CUDAModelMatrix, [85](#)
 - Markov::API::MarkovPasswords, [111](#)
 - Markov::API::ModelMatrix, [168](#)
- TraverseNode
 - Markov::Edge< NodeStorageType >, [98](#)
- True
 - markopy_cli, [20](#)
- ui
 - Markov::GUI::about, [46](#)
 - Markov::GUI::CLI, [54](#)
 - Markov::GUI::MarkovPasswordsGUI, [115](#)
 - Markov::GUI::menu, [132](#)
 - Markov::GUI::Train, [189](#)
- UI/src/main.cpp
 - main, [212](#)
- UnitTests.cpp, [258](#), [260](#)
- UpdateEdges
 - Markov::Node< storageType >, [178](#)
- UpdateTotalVerticeWeight
 - Markov::Node< storageType >, [179](#)
- valueMatrix
 - Markov::API::CUDA::CUDAModelMatrix, [88](#)
 - Markov::API::ModelMatrix, [170](#)
- visualization
 - Markov::GUI::menu, [132](#)
- WHITE
 - Markov::API::CLI::Terminal, [183](#)
- WIN32_LEAN_AND_MEAN
 - framework.h, [209](#)
- wordlistname
 - Markov::API::CLI::_programOptions, [44](#)
- x

Markov::API::CUDA::Random::Marsaglia, [124](#)
Markov::Random::Marsaglia, [129](#)

y

Markov::API::CUDA::Random::Marsaglia, [124](#)
Markov::Random::Marsaglia, [129](#)

YELLOW

Markov::API::CLI::Terminal, [183](#)

z

Markov::API::CUDA::Random::Marsaglia, [124](#)
Markov::Random::Marsaglia, [130](#)