



Middle East Technical University Northern Cyprus Campus
Computer Engineering Program

CNG491 Computer Engineering Design I

Markopy Documentation

Ata Hakçıl - 2243467
Osman Ömer Yıldıztugay - 1921956
Celal Sahir Çetiner - 1755420
Yunus Emre Yılmaz - 2243723

Supervised by
Assoc. Prof. Dr. Okan Topçu

0.6.0 Documentation

1 Markopy	3
1.1 About The Project	4
1.1.1 Possible Use Cases	4
1.1.2 Getting Started	4
1.1.3 Releases	4
1.2 Building	5
1.3 Prerequisites	5
1.3.1 General prequisites	5
1.3.1.1 Linux	5
1.3.1.2 Windows	5
1.3.2 MarkovModel	5
1.3.3 MarkovAPI	5
1.3.4 MarkovAPICLI	5
1.3.5 Markopy	5
1.3.6 CudaMarkovAPI	6
1.3.7 CudaMarkopy	6
1.3.8 MarkovPasswordsGUI	6
1.3.9 CMake Configuration	6
1.3.9.1 Build everything	6
1.3.9.2 Build libraries only	6
1.3.9.3 Build CUDA-accelerated libraries	6
1.3.9.4 Build python module & libraries	6
1.3.9.5 Build CUDA accelerated python module	6
1.3.9.6 Build CUDA accelerated python module and the GUI	6
1.3.10 Installing Dependencies	7
1.4 Known Common issues	7
1.4.1 Linux	7
1.4.1.1 Markopy - Python.h - Not found	7
1.4.1.2 Markopy/MarkovAPI - *.so not found, or other library related issues when building	7
1.4.2 Windows	8
1.4.2.1 Boost - Bootstrap.bat "ctype.h" not found	8
1.4.2.2 Cannot open file "*.lib"	8
1.4.2.3 Python.h not found	8
1.5 Contributing	8
1.6 Contact	8
2 NVSight Report	9
2.0.1 Overview	9
2.0.2 Session	14
2.0.3 PTX	16
3 Deprecated List	19

4 Namespace Index	21
4.1 Namespace List	21
5 Hierarchical Index	23
5.1 Class Hierarchy	23
6 Class Index	25
6.1 Class List	25
7 File Index	27
7.1 File List	27
8 Namespace Documentation	29
8.1 markopy Namespace Reference	29
8.1.1 Detailed Description	29
8.1.2 Function Documentation	29
8.1.2.1 cli_generate()	29
8.1.2.2 cli_init()	30
8.1.2.3 cli_train()	31
8.1.3 Variable Documentation	32
8.1.3.1 action	32
8.1.3.2 args	32
8.1.3.3 default	32
8.1.3.4 help	32
8.1.3.5 parser	33
8.2 Markov Namespace Reference	33
8.2.1 Detailed Description	33
8.3 Markov::API Namespace Reference	33
8.3.1 Detailed Description	34
8.4 Markov::API::CLI Namespace Reference	34
8.4.1 Detailed Description	34
8.4.2 Typedef Documentation	34
8.4.2.1 ProgramOptions	34
8.4.3 Function Documentation	34
8.4.3.1 operator<<()	34
8.5 Markov::API::Concurrency Namespace Reference	35
8.5.1 Detailed Description	35
8.6 Markov::API::CUDA Namespace Reference	35
8.6.1 Detailed Description	35
8.6.2 Function Documentation	35
8.6.2.1 FastRandomWalkCUDAKernel()	35
8.6.2.2 strchr()	37
8.7 Markov::API::CUDA::Random Namespace Reference	37
8.7.1 Detailed Description	37

8.7.2 Function Documentation	37
8.7.2.1 devrandom()	38
8.8 Markov::GUI Namespace Reference	38
8.8.1 Detailed Description	38
8.9 Markov::Markopy Namespace Reference	38
8.9.1 Function Documentation	39
8.9.1.1 BOOST_PYTHON_MODULE()	39
8.10 Markov::Random Namespace Reference	39
8.10.1 Detailed Description	40
8.11 model_2gram Namespace Reference	40
8.11.1 Detailed Description	40
8.11.2 Variable Documentation	40
8.11.2.1 alphabet	40
8.11.2.2 f	40
8.12 random Namespace Reference	40
8.12.1 Detailed Description	40
8.13 random-model Namespace Reference	40
8.13.1 Variable Documentation	41
8.13.1.1 alphabet	41
8.13.1.2 f	41
8.14 Testing Namespace Reference	41
8.14.1 Detailed Description	41
8.15 Testing::MarkovModel Namespace Reference	41
8.15.1 Detailed Description	41
8.15.2 Function Documentation	41
8.15.2.1 TEST_CLASS() [1/3]	42
8.15.2.2 TEST_CLASS() [2/3]	42
8.15.2.3 TEST_CLASS() [3/3]	43
8.16 Testing::MarkovPasswords Namespace Reference	44
8.16.1 Detailed Description	44
8.17 Testing::MVP Namespace Reference	45
8.17.1 Detailed Description	45
8.18 Testing::MVP::MarkovModel Namespace Reference	45
8.18.1 Detailed Description	45
8.18.2 Function Documentation	45
8.18.2.1 TEST_CLASS() [1/3]	45
8.18.2.2 TEST_CLASS() [2/3]	47
8.18.2.3 TEST_CLASS() [3/3]	47
8.19 Testing::MVP::MarkovPasswords Namespace Reference	50
8.19.1 Detailed Description	51
8.19.2 Function Documentation	51
8.19.2.1 TEST_CLASS()	51

9 Class Documentation	53
9.1 Markov::API::CLI::__programOptions Struct Reference	53
9.1.1 Detailed Description	54
9.1.2 Member Data Documentation	54
9.1.2.1 bExport	54
9.1.2.2 bFailure	54
9.1.2.3 bImport	54
9.1.2.4 datasetname	54
9.1.2.5 exportname	55
9.1.2.6 generateN	55
9.1.2.7 importname	55
9.1.2.8 outputfilename	55
9.1.2.9 seperator	55
9.1.2.10 wordlistname	55
9.2 Markov::GUI::about Class Reference	56
9.2.1 Detailed Description	57
9.2.2 Constructor & Destructor Documentation	57
9.2.2.1 about()	57
9.2.3 Member Data Documentation	57
9.2.3.1 ui	57
9.3 Markov::API::CLI::Argparse Class Reference	57
9.3.1 Detailed Description	59
9.3.2 Constructor & Destructor Documentation	59
9.3.2.1 Argparse() [1/2]	59
9.3.2.2 Argparse() [2/2]	59
9.3.3 Member Function Documentation	61
9.3.3.1 getProgramOptions()	61
9.3.3.2 help()	61
9.3.3.3 parse()	62
9.3.3.4 setProgramOptions()	62
9.3.4 Member Data Documentation	63
9.3.4.1 po	63
9.4 Markov::GUI::CLI Class Reference	63
9.4.1 Detailed Description	64
9.4.2 Constructor & Destructor Documentation	64
9.4.2.1 CLI()	64
9.4.3 Member Function Documentation	65
9.4.3.1 about	65
9.4.3.2 start	65
9.4.3.3 statistics	66
9.4.4 Member Data Documentation	66
9.4.4.1 ui	66

9.5 Markov::API::CUDA::CUDADeviceController Class Reference	66
9.5.1 Detailed Description	68
9.5.2 Member Function Documentation	68
9.5.2.1 CudaCheckNotifyErr()	68
9.5.2.2 CudaMalloc2DToFlat()	69
9.5.2.3 CudaMemcpy2DToFlat()	70
9.5.2.4 CudaMigrate2DFlat()	71
9.5.2.5 ListCudaDevices()	72
9.6 Markov::API::CUDA::CUDAModelMatrix Class Reference	73
9.6.1 Detailed Description	77
9.6.2 Member Function Documentation	77
9.6.2.1 AdjustEdge()	78
9.6.2.2 AllocVRAMOutputBuffer()	78
9.6.2.3 Buff()	79
9.6.2.4 ConstructMatrix()	80
9.6.2.5 CudaCheckNotifyErr()	81
9.6.2.6 CudaMalloc2DToFlat()	82
9.6.2.7 CudaMemcpy2DToFlat()	83
9.6.2.8 CudaMigrate2DFlat()	84
9.6.2.9 DeallocateMatrix()	85
9.6.2.10 DumpJSON()	86
9.6.2.11 Edges()	87
9.6.2.12 Export() [1/2]	87
9.6.2.13 Export() [2/2]	87
9.6.2.14 FastRandomWalk() [1/3]	88
9.6.2.15 FastRandomWalk() [2/3]	89
9.6.2.16 FastRandomWalk() [3/3]	90
9.6.2.17 FastRandomWalkPartition()	91
9.6.2.18 FastRandomWalkThread()	92
9.6.2.19 FlattenMatrix()	94
9.6.2.20 GatherAsyncKernelOutput()	94
9.6.2.21 Generate()	94
9.6.2.22 GenerateThread()	96
9.6.2.23 Import() [1/2]	97
9.6.2.24 Import() [2/2]	98
9.6.2.25 LaunchAsyncKernel()	99
9.6.2.26 ListCudaDevices()	99
9.6.2.27 MigrateMatrix()	99
9.6.2.28 Nodes()	100
9.6.2.29 OpenDatasetFile()	100
9.6.2.30 OptimizeEdgeOrder()	101
9.6.2.31 prepKernelMemoryChannel()	101

9.6.2.32 RandomWalk()	102
9.6.2.33 Save()	103
9.6.2.34 StarterNode()	103
9.6.2.35 Train()	104
9.6.2.36 TrainThread()	105
9.6.3 Member Data Documentation	106
9.6.3.1 alternatingKernels	106
9.6.3.2 cudaBlocks	106
9.6.3.3 cudaGridSize	106
9.6.3.4 cudaMemPerGrid	106
9.6.3.5 cudaPerKernelAllocationSize	106
9.6.3.6 cudastreams	106
9.6.3.7 cudaThreads	107
9.6.3.8 datasetFile	107
9.6.3.9 device_edgeMatrix	107
9.6.3.10 device_matrixIndex	107
9.6.3.11 device_outputBuffer	107
9.6.3.12 device_seeds	107
9.6.3.13 device_totalEdgeWeights	107
9.6.3.14 device_valueMatrix	107
9.6.3.15 edgeMatrix	107
9.6.3.16 edges	108
9.6.3.17 flatEdgeMatrix	108
9.6.3.18 flatValueMatrix	108
9.6.3.19 iterationsPerKernelThread	108
9.6.3.20 matrixIndex	108
9.6.3.21 matrixSize	108
9.6.3.22 modelSavefile	108
9.6.3.23 nodes	109
9.6.3.24 numberOfPartitions	109
9.6.3.25 outputBuffer	109
9.6.3.26 outputFile	109
9.6.3.27 ready	109
9.6.3.28 starterNode	109
9.6.3.29 totalEdgeWeights	109
9.6.3.30 totalOutputPerKernel	109
9.6.3.31 totalOutputPerSync	110
9.6.3.32 valueMatrix	110
9.7 Markov::Random::DefaultRandomEngine Class Reference	110
9.7.1 Detailed Description	112
9.7.2 Member Function Documentation	113
9.7.2.1 distribution()	113

9.7.2.2 generator()	113
9.7.2.3 random()	114
9.7.2.4 rd()	114
9.8 Markov::Edge< NodeStorageType > Class Template Reference	115
9.8.1 Detailed Description	116
9.8.2 Constructor & Destructor Documentation	116
9.8.2.1 Edge() [1/2]	116
9.8.2.2 Edge() [2/2]	116
9.8.3 Member Function Documentation	117
9.8.3.1 AdjustEdge()	117
9.8.3.2 EdgeWeight()	117
9.8.3.3 LeftNode()	118
9.8.3.4 RightNode()	118
9.8.3.5 SetLeftEdge()	119
9.8.3.6 SetRightEdge()	119
9.8.3.7 TraverseNode()	119
9.8.4 Member Data Documentation	119
9.8.4.1 _left	119
9.8.4.2 _right	120
9.8.4.3 _weight	120
9.9 Markov::GUI::Generate Class Reference	120
9.9.1 Detailed Description	121
9.9.2 Constructor & Destructor Documentation	121
9.9.2.1 Generate()	121
9.9.3 Member Function Documentation	122
9.9.3.1 generation	122
9.9.3.2 home	123
9.9.3.3 train	123
9.9.3.4 vis	123
9.9.4 Member Data Documentation	124
9.9.4.1 ui	124
9.10 Markov::API::MarkovPasswords Class Reference	124
9.10.1 Detailed Description	127
9.10.2 Constructor & Destructor Documentation	128
9.10.2.1 MarkovPasswords() [1/2]	128
9.10.2.2 MarkovPasswords() [2/2]	128
9.10.3 Member Function Documentation	128
9.10.3.1 AdjustEdge()	128
9.10.3.2 Buff()	129
9.10.3.3 Edges()	130
9.10.3.4 Export() [1/2]	131
9.10.3.5 Export() [2/2]	131

9.10.3.6 Generate()	131
9.10.3.7 GenerateThread()	132
9.10.3.8 Import() [1/2]	133
9.10.3.9 Import() [2/2]	134
9.10.3.10 Nodes()	135
9.10.3.11 OpenDatasetFile()	135
9.10.3.12 OptimizeEdgeOrder()	135
9.10.3.13 RandomWalk()	136
9.10.3.14 Save()	137
9.10.3.15 StarterNode()	137
9.10.3.16 Train()	138
9.10.3.17 TrainThread()	139
9.10.4 Member Data Documentation	140
9.10.4.1 datasetFile	140
9.10.4.2 edges	140
9.10.4.3 modelSavefile	140
9.10.4.4 nodes	140
9.10.4.5 outputFile	140
9.10.4.6 starterNode	140
9.11 Markov::GUI::MarkovPasswordsGUI Class Reference	141
9.11.1 Detailed Description	142
9.11.2 Constructor & Destructor Documentation	142
9.11.2.1 MarkovPasswordsGUI()	142
9.11.3 Member Function Documentation	143
9.11.3.1 benchmarkSelected	143
9.11.3.2 home	143
9.11.3.3 model	143
9.11.3.4 pass	143
9.11.4 Member Data Documentation	143
9.11.4.1 ui	144
9.12 Markov::Random::Marsaglia Class Reference	144
9.12.1 Detailed Description	147
9.12.2 Constructor & Destructor Documentation	147
9.12.2.1 Marsaglia()	147
9.12.3 Member Function Documentation	147
9.12.3.1 distribution()	147
9.12.3.2 generator()	148
9.12.3.3 random()	148
9.12.3.4 rd()	149
9.12.4 Member Data Documentation	149
9.12.4.1 x	149
9.12.4.2 y	149

9.12.4.3 z	150
9.13 Markov::API::CUDA::Random::Marsaglia Class Reference	150
9.13.1 Detailed Description	152
9.13.2 Member Function Documentation	152
9.13.2.1 CudaCheckNotifyErr()	152
9.13.2.2 CudaMalloc2DToFlat()	153
9.13.2.3 CudaMemcpy2DToFlat()	154
9.13.2.4 CudaMigrate2DFlat()	155
9.13.2.5 distribution()	156
9.13.2.6 generator()	157
9.13.2.7 ListCudaDevices()	157
9.13.2.8 MigrateToVRAM()	158
9.13.2.9 random()	158
9.13.2.10 rd()	159
9.13.3 Member Data Documentation	159
9.13.3.1 x	159
9.13.3.2 y	159
9.13.3.3 z	159
9.14 Markov::GUI::menu Class Reference	160
9.14.1 Detailed Description	161
9.14.2 Constructor & Destructor Documentation	161
9.14.2.1 menu()	161
9.14.3 Member Function Documentation	161
9.14.3.1 about	161
9.14.3.2 visualization	162
9.14.4 Member Data Documentation	162
9.14.4.1 ui	162
9.15 Markov::Random::Mersenne Class Reference	162
9.15.1 Detailed Description	164
9.15.2 Member Function Documentation	165
9.15.2.1 distribution()	165
9.15.2.2 generator()	165
9.15.2.3 random()	166
9.15.2.4 rd()	166
9.16 Markov::Model< NodeStorageType > Class Template Reference	167
9.16.1 Detailed Description	168
9.16.2 Constructor & Destructor Documentation	168
9.16.2.1 Model()	168
9.16.3 Member Function Documentation	168
9.16.3.1 AdjustEdge()	169
9.16.3.2 Edges()	169
9.16.3.3 Export() [1/2]	170

9.16.3.4 Export() [2/2]	170
9.16.3.5 Import() [1/2]	171
9.16.3.6 Import() [2/2]	171
9.16.3.7 Nodes()	172
9.16.3.8 OptimizeEdgeOrder()	173
9.16.3.9 RandomWalk()	173
9.16.3.10 StarterNode()	175
9.16.4 Member Data Documentation	175
9.16.4.1 edges	175
9.16.4.2 nodes	175
9.16.4.3 starterNode	175
9.17 Markov::API::ModelMatrix Class Reference	175
9.17.1 Detailed Description	179
9.17.2 Constructor & Destructor Documentation	179
9.17.2.1 ModelMatrix()	179
9.17.3 Member Function Documentation	179
9.17.3.1 AdjustEdge()	179
9.17.3.2 Buff()	180
9.17.3.3 ConstructMatrix()	181
9.17.3.4 DeallocateMatrix()	183
9.17.3.5 DumpJSON()	184
9.17.3.6 Edges()	185
9.17.3.7 Export() [1/2]	185
9.17.3.8 Export() [2/2]	185
9.17.3.9 FastRandomWalk() [1/2]	186
9.17.3.10 FastRandomWalk() [2/2]	187
9.17.3.11 FastRandomWalkPartition()	188
9.17.3.12 FastRandomWalkThread()	189
9.17.3.13 Generate()	190
9.17.3.14 GenerateThread()	192
9.17.3.15 Import() [1/2]	193
9.17.3.16 Import() [2/2]	194
9.17.3.17 Nodes()	195
9.17.3.18 OpenDatasetFile()	195
9.17.3.19 OptimizeEdgeOrder()	195
9.17.3.20 RandomWalk()	196
9.17.3.21 Save()	197
9.17.3.22 StarterNode()	197
9.17.3.23 Train()	198
9.17.3.24 TrainThread()	199
9.17.4 Member Data Documentation	199
9.17.4.1 datasetFile	200

9.17.4.2 edgeMatrix	200
9.17.4.3 edges	200
9.17.4.4 matrixIndex	200
9.17.4.5 matrixSize	200
9.17.4.6 modelSavefile	200
9.17.4.7 nodes	200
9.17.4.8 outputFile	200
9.17.4.9 ready	201
9.17.4.10 starterNode	201
9.17.4.11 totalEdgeWeights	201
9.17.4.12 valueMatrix	201
9.18 Markov::Node< storageType > Class Template Reference	201
9.18.1 Detailed Description	203
9.18.2 Constructor & Destructor Documentation	203
9.18.2.1 Node() [1/2]	203
9.18.2.2 Node() [2/2]	203
9.18.3 Member Function Documentation	204
9.18.3.1 Edges()	204
9.18.3.2 FindEdge() [1/2]	204
9.18.3.3 FindEdge() [2/2]	204
9.18.3.4 Link() [1/2]	205
9.18.3.5 Link() [2/2]	205
9.18.3.6 NodeValue()	206
9.18.3.7 RandomNext()	206
9.18.3.8 TotalEdgeWeights()	207
9.18.3.9 UpdateEdges()	207
9.18.3.10 UpdateTotalVerticeWeight()	208
9.18.4 Member Data Documentation	208
9.18.4.1 _value	208
9.18.4.2 edges	208
9.18.4.3 edgesV	208
9.18.4.4 total_edge_weights	208
9.19 QMainWindow Class Reference	209
9.20 Markov::Random::RandomEngine Class Reference	209
9.20.1 Detailed Description	211
9.20.2 Member Function Documentation	211
9.20.2.1 random()	211
9.21 Markov::API::CLI::Terminal Class Reference	211
9.21.1 Detailed Description	213
9.21.2 Member Enumeration Documentation	213
9.21.2.1 color	213
9.21.3 Constructor & Destructor Documentation	213

9.21.3.1 Terminal()	213
9.21.4 Member Data Documentation	213
9.21.4.1 colormap	214
9.21.4.2 endl	214
9.22 Markov::API::Concurrency::ThreadSharedListHandler Class Reference	214
9.22.1 Detailed Description	216
9.22.2 Constructor & Destructor Documentation	216
9.22.2.1 ThreadSharedListHandler()	216
9.22.3 Member Function Documentation	217
9.22.3.1 next()	217
9.22.4 Member Data Documentation	217
9.22.4.1 listfile	217
9.22.4.2 mlock	217
9.23 Markov::GUI::Train Class Reference	218
9.23.1 Detailed Description	219
9.23.2 Constructor & Destructor Documentation	219
9.23.2.1 Train()	219
9.23.3 Member Function Documentation	220
9.23.3.1 home	220
9.23.3.2 train	220
9.23.4 Member Data Documentation	221
9.23.4.1 ui	221
10 File Documentation	223
10.1 about.cpp File Reference	223
10.1.1 Detailed Description	223
10.2 about.cpp	223
10.3 about.h File Reference	223
10.3.1 Detailed Description	224
10.4 about.h	225
10.5 argparse.cpp File Reference	225
10.5.1 Detailed Description	225
10.6 argparse.cpp	225
10.7 argparse.h File Reference	226
10.7.1 Detailed Description	227
10.7.2 Macro Definition Documentation	227
10.7.2.1 BOOST_ALL_STATIC_LIB	228
10.7.2.2 BOOST_PROGRAM_OPTIONS_STATIC_LIB	228
10.8 argparse.h	228
10.9 CLI.cpp File Reference	231
10.9.1 Detailed Description	231
10.10 CLI.cpp	231

10.11 CLI.h File Reference	232
10.11.1 Detailed Description	233
10.12 CLI.h	233
10.13 cudaDeviceController.cu File Reference	233
10.13.1 Detailed Description	234
10.14 cudaDeviceController.cu	234
10.15 cudaDeviceController.h File Reference	235
10.15.1 Detailed Description	236
10.16 cudaDeviceController.h	236
10.17 cudaModelMatrix.cu File Reference	238
10.17.1 Detailed Description	239
10.18 cudaModelMatrix.cu	239
10.19 cudaModelMatrix.h File Reference	242
10.19.1 Detailed Description	244
10.20 cudaModelMatrix.h	244
10.21 cudarandom.h File Reference	246
10.21.1 Detailed Description	247
10.22 cudarandom.h	248
10.23 dllmain.cpp File Reference	248
10.23.1 Detailed Description	249
10.24 dllmain.cpp	249
10.25 edge.h File Reference	250
10.25.1 Detailed Description	251
10.26 edge.h	251
10.27 framework.h File Reference	253
10.27.1 Detailed Description	253
10.27.2 Macro Definition Documentation	253
10.27.2.1 WIN32_LEAN_AND_MEAN	254
10.28 framework.h	254
10.29 Generate.cpp File Reference	254
10.29.1 Detailed Description	254
10.30 Generate.cpp	254
10.31 Generate.h File Reference	256
10.31.1 Detailed Description	257
10.32 Generate.h	257
10.33 main.cpp File Reference	258
10.33.1 Detailed Description	258
10.33.2 Function Documentation	258
10.33.2.1 main()	259
10.34 MarkovAPICLI/src/main.cpp	259
10.35 main.cpp File Reference	260
10.35.1 Detailed Description	261

10.35.2 Function Documentation	261
10.35.2.1 main()	261
10.36 MarkovPasswordsGUI/src/main.cpp	261
10.37 main.cu File Reference	262
10.37.1 Detailed Description	262
10.37.2 Function Documentation	262
10.37.2.1 main()	262
10.38 main.cu	263
10.39 markopy.cpp File Reference	263
10.39.1 Detailed Description	264
10.39.2 Macro Definition Documentation	265
10.39.2.1 BOOST_ALL_STATIC_LIB	265
10.39.2.2 BOOST_PYTHON_STATIC_LIB	265
10.40 markopy.cpp	265
10.41 markopy.py File Reference	266
10.42 markopy.py	266
10.43 markovPasswords.cpp File Reference	268
10.43.1 Detailed Description	269
10.43.2 Function Documentation	269
10.43.2.1 intHandler()	269
10.43.3 Variable Documentation	270
10.43.3.1 keepRunning	270
10.44 markovPasswords.cpp	270
10.45 markovPasswords.h File Reference	272
10.45.1 Detailed Description	273
10.46 markovPasswords.h	273
10.47 MarkovPasswordsGUI.cpp File Reference	275
10.47.1 Detailed Description	275
10.48 MarkovPasswordsGUI.cpp	275
10.49 MarkovPasswordsGUI.h File Reference	276
10.49.1 Detailed Description	277
10.50 MarkovPasswordsGUI.h	277
10.51 menu.cpp File Reference	278
10.51.1 Detailed Description	278
10.52 menu.cpp	278
10.53 menu.h File Reference	279
10.53.1 Detailed Description	280
10.54 menu.h	280
10.55 model.h File Reference	280
10.55.1 Detailed Description	281
10.56 model.h	281
10.57 model_2gram.py File Reference	286

10.58 model_2gram.py	286
10.59 modelMatrix.cpp File Reference	286
10.59.1 Detailed Description	287
10.60 modelMatrix.cpp	287
10.61 modelMatrix.h File Reference	290
10.61.1 Detailed Description	291
10.62 modelMatrix.h	291
10.63 node.h File Reference	294
10.63.1 Detailed Description	295
10.64 node.h	295
10.65 pch.cpp File Reference	299
10.65.1 Detailed Description	299
10.66 MarkovModel/src/pch.cpp	299
10.67 pch.cpp File Reference	299
10.67.1 Detailed Description	300
10.68 UnitTests/pch.cpp	300
10.69 pch.h File Reference	300
10.69.1 Detailed Description	301
10.70 MarkovModel/src/pch.h	301
10.71 pch.h File Reference	301
10.71.1 Detailed Description	302
10.72 UnitTests/pch.h	302
10.73 random-model.py File Reference	302
10.74 random-model.py	303
10.75 random.h File Reference	303
10.75.1 Detailed Description	304
10.76 random.h	305
10.77 README.md File Reference	307
10.78 report.md File Reference	307
10.79 term.cpp File Reference	307
10.79.1 Detailed Description	308
10.79.2 Function Documentation	308
10.79.2.1 operator<<()	308
10.80 term.cpp	308
10.81 term.h File Reference	309
10.81.1 Detailed Description	311
10.81.2 Macro Definition Documentation	311
10.81.2.1 TERM_FAIL	311
10.81.2.2 TERM_INFO	311
10.81.2.3 TERM_SUCC	311
10.81.2.4 TERM_WARN	311
10.82 term.h	311

10.83 threadSharedListHandler.cpp File Reference	312
10.83.1 Detailed Description	312
10.84 threadSharedListHandler.cpp	313
10.85 threadSharedListHandler.h File Reference	313
10.85.1 Detailed Description	314
10.86 threadSharedListHandler.h	314
10.87 Train.cpp File Reference	316
10.87.1 Detailed Description	316
10.88 Train.cpp	316
10.89 Train.h File Reference	317
10.89.1 Detailed Description	318
10.90 Train.h	319
10.91 UnitTests.cpp File Reference	319
10.91.1 Detailed Description	320
10.92 UnitTests.cpp	320
Index	329

CHAPTER1

Markopy

Markopy

Generate wordlists with markov models.

[HTML documentation](#) · [PDF documentation](#) · [Github Page](#) · [Report Bug](#) · [Add a Bug](#)

Table of Contents

1. [About The Project](#)
 - [Possible Use Cases](#)
 - [Getting Started](#)
 - [Releases](#)
 2. [Building](#)
 - [CMake configuration](#)
 - [Build everything](#)
 - [Build libraries only](#)
 - [Build CUDA-accelerated libraries](#)
 - [Build python module & libraries](#)
 - [Build CUDA accelerated python module](#)
 - [Build CUDA accelerated python module and the GUI](#)
 - [Prerequisites](#)
 - [General Prerequisites](#)
 - * [Linux](#)
 - * [Windows](#)
 - [MarkovModel](#)
 - [MarkovAPI](#)
 - [MarkovAPICLI](#)
 - [Markopy](#)
 - [CudaMarkovAPI](#)
 - [CudaMarkopy](#)
 - [MarkovPasswordsGUI](#)
 - [Installing Dependencies](#)
 - [Windows](#)
 - [Linux](#)
 3. [Known Common Issues](#)
 4. [Contributing](#)
 5. [Contact](#)
-

1.1 About The Project

This projects primary goal is to create a comfortable development environment for working with [Markov](#) Models, as well as creating an end product which can be used for generating password wordlists using [Markov](#) Models. This project contains following sub-projects:

- MarkovModel
 - A versatile header-only template library for basic [Markov](#) Model structure.
- MarkovAPI
 - A static/dynamic library built on MarkovModel, specialized to generate single-word lines.
- MarkovAPICLI
 - A command line interface built on top of MarkovAPI
- Markopy
 - A CPython extension wrapper for MarkovAPI, along with its own command line interface.
- MarkovPasswordsGUI
 - A graphical user interface for MarkovAPI
- CudaMarkovAPI
 - GPU-accelerated wrapper for MarkovAPI
- CudaMarkopy
 - GPU-accelereted wrapper for CudaMarkovAPI

1.1.1 Possible Use Cases

While main focus of the development has been towards random walk performance and password generation, underlying libraries could be used for other applications such as specific use cases of hidden markov models in bioinformatics and gene research.

1.1.2 Getting Started

If you'd just like to use the project without contributing, check out the releases page. Latest minor release (0.8.x, 0.9.x) is even with main branch, and latest patch release (0.8.1, 0.8.2) is even with development branch.

1.1.3 Releases

Releases are maintained automatically via github actions. Each push to the main branch will trigger a minor version release, while each accepted pull request into the development branch will trigger a patch version release.

Pull requests to the development branch will also trigger a draft release only visible to the maintainers.

Release files contain:

- libmarkov-{version}-{platform}.zip
 - Depending on the platform, contains the libmarkov.so or markov.lib from that version.
- libcudamarkov-{version}-{platform}.zip
 - Depending on the platform, contains the libcudamarkov.so or cudamarkov.lib from that version.
- markopy-{version}-{platform}-py{ver}.{extension}.zip
 - Depending on the paltform, contains markopy.so or markopy.pyd. CPython extensions are compiled for specific versions. If your python version is not supported by the releases, you can create an issue, or build it yourself using the python3.x-dev package.

- cudamarkopy-{version}-{platform}-py{ver}.{extension}.zip
 - Depending on the platform, contains cudamarkopy.so or cudamarkopy.pyd. CPython extensions are compiled for specific versions. If your python version is not supported by the releases, you can create an issue, or build it yourself using the python3.x-dev package.
 - models-{version}.zip
 - Contains the latest models with the release version. Contains base models (untrained), trained models, and language-specific models.
-

1.2 Building

You can build the project using cmake with g++ & nvcc on linux, and msbuild & nvcc on windows.

1.3 Prerequisites

You can find a list of the dependencies below. If you have any missing, check out the [setting up prerequisites](#) part.

1.3.1 General prerequisites

To build the simple core of this project, you'll need:

1.3.1.1 Linux

- CMake, preferably one of the latest versions.
- CXX compiler, preferably g++ or clang++ (LLVM 3.9+).

1.3.1.2 Windows

- CMake, preferably one of the latest versions.
- CXX compiler, preferably msbuild(cl.exe) or clang++ (LLVM 3.9+). Please note that mingw is not recommended as it is not officially supported by the nvcc.exe, and might not be linkable if you are building the CUDA components too.

1.3.2 MarkovModel

This project does not have any extra dependencies, and it can be compiled with general dependencies without anything extra.

1.3.3 MarkovAPI

This project does not have any extra dependencies, and it can be compiled with general dependencies without anything extra.

1.3.4 MarkovAPICLI

- Boost.program_options (tested on 1.71.0-1.76.0)

1.3.5 Markopy

- Boost.Python (tested on 1.71.0-1.76.0)
 - Python development package (tested on python 36-39)
-

1.3.6 CudaMarkovAPI

- CUDA toolkit (11.0+, c++17 support required)

1.3.7 CudaMarkopy

- CUDA toolkit (11.0+, c++17 support required)
- Boost.Python (tested on 1.71.0-1.76.0)
- Python development package (tested on python 36-39)

1.3.8 MarkovPasswordsGUI

- QT5 development environment. (qt5-qmake on ubuntu apt-get)
- QTWebEngine5 plugin. (qtwebengine5-dev on ubuntu apt-get)

1.3.9 CMake Configuration

You can build this project with cmake.

If you don't have prerequisites for some of the projects set up, you can use the partial set up configuration to ignore those projects when setting the project up.

If you do not meet the prerequisites, you'll have to partially set up the CMake file (you can't use -target to build some of the targets, because configuration phase will fail too).

Some examples for partially setting up and building the project are below.

1.3.9.1 Build everything

```
$ cmake . -DPYTHON_VER=38 && cmake --build .
```

This will build all the libraries and executables. Requires python-dev, CUDA, QT5, QT5-Webview

1.3.9.2 Build libraries only

```
$ cmake . -DPARTIAL=1 -DB_LIBS=1 && cmake --build .
```

Only build basic libraries. Requires only CXX compiler.

1.3.9.3 Build CUDA-accelerated libraries

```
$ cmake . -DPARTIAL=1 -DB_CUDA=1 && cmake --build .
```

Build libraries along with cuda accelerated ones.

1.3.9.4 Build python module & libraries

```
$ cmake . -DPARTIAL=1 -DPYTHON_VER=39 && cmake --build .
```

Will build basic libraries and python modules.

1.3.9.5 Build CUDA accelerated python module

```
$ cmake . -DPARTIAL=1 -DPYTHON_VER=39 -DB_CUDA=1 && cmake --build .
```

Will build cudamarkopy.

1.3.9.6 Build CUDA accelerated python module and the GUI

```
$ cmake . -DPARTIAL=1 -DPYTHON_VER=39 -DB_CUDA=1 -DB_GUI && cmake --build .
```

Combine methods

1.3.10 Installing Dependencies

1.3.10.0.1 Windows

- QT: Install [QT For Windows](#)
- Boost (program_options and python):
 - Download Boost from [its website](#). Prefer one of the tested versions, 1.71.0 to 1.76.0
 - Unzip the contents.
 - Launch "Visual Studio Developer Command Prompt" (If you don't have this, properly set up the PATH% variable for cl.exe)
 - Move to the boost installation directory. Bootstrap libraries with your python version:
`.\bootstrap.bat --with-python=$(which python3.6) --with-python-version=3.6;`
 - Run b2 to build the libraries.
`.\b2.exe --layout=system address-model=64 variant=release link=static runtime-link=shared threading=multi --with-program_options --with-python stage;`
- Python: You can use the windows app store to download python runtime and libraries.

1.3.10.0.2 Linux

- QT: Follow [this guide](#) to install QT on Linux. Alternatively, on ubuntu you can `sudo apt-get install qt5-qmake qtwebengine5-dev`
- Boost (program options and python):
 - Download Boost from [its website](#). Prefer one of the tested versions, 1.71.0 to 1.76.0
 - Unzip the contents.
 - Move to the boost installation directory. Bootstrap libraries with your python version:
`./bootstrap.sh --with-python=$(which python3.6) --with-python-version=3.6;`
 - Run b2 to build the libraries.
`./b2 variant=release link=static threading=multi --with-program_options install;`
`./b2 --with-python --buildid=3.6 install;`
- Boost (alternative)
 - Use a package manager to install boost
`sudo apt-get install libboost-all-dev`
- Python:
`sudo apt-get install python3-dev`

1.4 Known Common issues

1.4.1 Linux

1.4.1.1 Markopy - Python.h - Not found

Make sure you have the development version of python package, which includes the required header files. Check if header files exist: `/usr/include/python*` or `locate Python.h`. If it doesn't, run `sudo apt-get install python3-dev`

1.4.1.2 Markopy/MarkovAPI - *.so not found, or other library related issues when building

Run:

```
ls /usr/lib/x86_64-linux-gnu/ | grep boost
```

and check the shared object filenames. A common issue is that lboost is required but filenames are formatted as libboost, or vice versa.

Do the same for python related library issues, run:

```
ls /usr/lib/x86_64-linux-gnu/ | grep python
```

to verify filename format is as required.

If not, you can modify the makefile, or create symlinks such as:

```
ln -s /usr/lib/x86_64-linux-gnu/libboost_python38.so /usr/lib/x86_64-linux-gnu/boost_python38.so
```

1.4.2 Windows

1.4.2.1 Boost - Bootstrap.bat "ctype.h" not found

- Make sure you are working in the "Visual Studio Developer Command Prompt" terminal.
- Make sure you have Windows 10 SDK installed.
- From VS developer terminal, run echo INCLUDE%. If result does not have the windows sdk folders, run the following before running bootstrap (change your sdk version instead of 10.0.19041.0):

```
set INCLUDE=%INCLUDE%;C:\Program Files (x86)\Windows Kits\NETFXSDK\4.8\include\um;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\ucrt;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\shared;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\um;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\winrt;C:\Program Files (x86)\Windows Kits\10\include\10.0.19041.0\cppwinrt  
set LIB=%LIB%;C:\Program Files (x86)\Windows Kits\10\lib\10.0.19041.0\ucrt\x64;C:\Program Files (x86)\Windows Kits\10\lib\10.0.19041.0\um\x64
```

1.4.2.2 Cannot open file "*.lib"

Make sure you have set the BOOST_ROOT environment variable correctly. Make sure you ran b2 to build library files from boost sources.

1.4.2.3 Python.h not found

Make sure you have python installed, and make sure you set PYTHON_PATH environment variable.

1.5 Contributing

Feel free to contribute. We welcome all the issues and pull requests.

1.6 Contact

Twitter - [@ahakcil](#)

CHAPTER2

NVInsight Report

2.0.1 Overview




Figure 2.1 SOL SM Breakdown




Figure 2.2 Arithmetic Intensity




Figure 2.3 Pipe utilization




Figure 2.4 Memory Workload Analysis

Shared Memory												
	Instructions	Requests	Wavefronts	% Peak	Bank Conflicts							
Shared Load	0	0	0	0	0							
Shared Load Matrix	0	0	0	0	0							
Shared Store	0	0	0	0	0							
Shared Atomic	0	0	0	0	0							
Other	-	-	8.192	0.00	0							
Total	0	0	8.192	0.00	0							
L1/TEX Cache												
	Instructions	Requests	Wavefronts	% Peak	Sectors	Sectors/Req	Hit Rate	Bytes	Sector Misses to L2	% Peak to L2	Returns to SM	% Peak to SM
Local Load	0	0	0	0	0	0	0	0	192.724.146	2.90	2.101.570.675	31.65
Global Load	1.223.036.801	1.223.036.801	1.747.696.951	26.32	2.987.208.909	2.44	93.85	95.590.685.088				
Surface Load	0	0	0	0	0	0	0	0	0	0	0	0
Texture Load	0	0	0	0	0	0	0	0	0	0	0	0
Global Store	46.586.822	46.586.822	163.741.228	2.47	920.981.177	19.77	74.23	29.471.397.664	772.161.127	11.63	-	-
Local Store	0	0	0	0	0	0	0	0	0	0	-	-
Surface Store	0	0	0	0	0	0	0	0	0	0	-	-
Global Reduction	0	0	0	0	0	0	0	0	0	0	-	-
Surface Reduction	0	0	0	0	0	0	0	0	0	0	-	-
Global Atomic ALU	0	0	0	0	0	0	0	0	0	0	-	-
Global Atomic CAS	0	0	0	0	0	0	0	0	0	0	see above	see above
Surface Atomic ALU	0	0	0	0	0	0	0	0	0	0	see above	see above
Surface Atomic CAS	0	0	0	0	0	0	0	0	0	0	see above	see above
Loads	1.223.036.801	1.223.036.801	1.747.696.951	26.32	2.987.208.909	2.44	93.85	95.590.685.088	192.724.146	2.90	2.101.570.675	31.65
Stores	46.586.822	46.586.822	163.741.228	2.47	920.981.177	19.77	74.23	29.471.397.664	772.161.127	11.63	-	-
Total	1.269.623.623	1.269.623.623	1.911.438.179	28.78	3.908.190.086	3.08	89.23	125.062.082.752	964.885.273	14.53	2.101.570.675	31.65
L2 Cache												
	Requests	Sectors	Sectors/Req	% Peak	Hit Rate	Bytes	Throughput	Sector Misses to Device	Sector Misses to System	Sector Misses to Peer		
L1/TEX Load	63.680.170	193.047.854	3.03	3.45	99.46	6.177.531.328	40.817.641.959.44	1.028.090	0	0	0	0
L1/TEX Store	405.095.227	772.063.559	1.91	13.79	100	24.706.033.888	163.243.534.016.14	0	0	0	0	0
L1/TEX Atomic ALU	0	0	0	0	0	0	0	0	0	0	0	0
L1/TEX Atomic CAS	0	0	0	0	0	0	0	0	0	0	0	0
L1/TEX Reduction	0	0	0	0	0	0	0	0	0	0	0	0
L1/TEX Total	468.490.666	963.888.704	2.06	17.22	99.89	30.844.438.528	203.802.648.894.60	1.013.223	0	0	0	0
GPU Total	472.620.531	972.615.552	2.06	17.37	99.07	31.123.697.664	205.647.835.721.17	9.036.807	180	0	0	0
Device Memory												
	Sectors	% Peak	Bytes	Throughput								
Load	9.094.353	0.44	291.019.296	1.922.891.329.35								
Store	439.786.885	21.36	14.073.180.320	92.987.636.166.04								
Total	448.881.238	21.80	14.364.199.616	94.910.527.495.39								

Figure 2.5 Shared memory and L1/L2 cache

L1/TEX Cache (Deprecated)												
	Instructions	L1/TEX Requests	% Peak	Hit Rate	L2 Requests	% Peak	L2 Returns	% Peak	L1/TEX Returns	% Peak		
Global Load Cached	1.223.036.801	1.223.036.801	18.42	93.85	-	-	192.724.146	2.90	2.101.570.675	31.65		
Global Load Uncached	-	-	-	-	-	-	-	-	-	-		
Local Load Cached	0	0	0	0	-	-	-	-	-	-		
Local Load Uncached	-	-	-	-	-	-	-	-	-	-		
Surface Load	0	0	0	0	-	-	0	0	0	0		
Texture Load	0	0	0	0	-	-	0	0	0	0		
Global Store	46.586.822	46.586.822	0.70	74.23	772.161.127	11.63	-	-	-	-		
Local Store	0	0	0	0	772.161.127	-	-	-	-	-		
Surface Store	0	0	0	0	0	0	-	-	-	-		
Global Reduction	0	0	0	0	0	0	-	-	-	-		
Surface Reduction	0	0	0	0	0	0	-	-	-	-		
Global Atomic	0	0	0	0	0	0	-	-	-	-		
Global Atomic CAS	0	0	0	0	0	0	0	0	see above	see above		
Surface Atomic	0	0	0	0	0	0	0	0	see above	see above		
Surface Atomic CAS	0	0	0	0	0	0	0	0	see above	see above		
Loads	1.223.036.801	1.223.036.801	18.42	93.85	-	-	192.724.146	2.90	2.101.570.675	31.65		
Stores	46.586.822	46.586.822	0.70	74.23	772.161.127	11.63	-	-	-	-		
Total	1.269.623.623	1.269.623.623	19.12	89.23	772.161.127	11.63	192.724.146	2.90	2.101.570.675	31.65		
L2 Cache (Deprecated)												
	L2 Requests	% Peak	L2 Returns	% Peak	Total Bytes	Total Throughput						
Global Load Cached	-	-	-	-	6.167.172.672	40.749.197.804.43						
Global Load Uncached	-	-	192.724.146	2.90	-	-						
Local Load Cached	-	-	-	-	-	-						
Local Load Uncached	-	-	-	-	-	-						
Surface Load	-	-	0	0	0	0						
Texture Load	-	-	0	0	0	0						
Global Store	772.161.127	11.63	-	-	24.709.156.064	163.264.163.593.77						
Local Store	-	-	-	-	-	-						
Surface Store	0	0	-	-	0	0						
Global Reduction	0	0	-	-	0	0						
Surface Reduction	0	0	-	-	0	0						
Global Atomic	0	0	0	0	0	0						
Global Atomic CAS	0	0	0	0	0	0						
Surface Atomic	0	0	0	0	0	0						
Surface Atomic CAS	0	0	0	0	0	0						
Loads	-	-	192.724.146	2.90	6.167.172.672	40.749.197.804.43						
Stores	772.161.127	11.63	-	-	24.709.156.064	163.264.163.593.77						
Total	772.161.127	11.63	192.724.146	2.90	30.876.328.736	204.013.361.398.20						

Figure 2.6 L1/L2 Cache




Figure 2.7 Warp Scheduler




Figure 2.8 Instruction statistics




Figure 2.9 Instruction statistics continued

Launch Statistics	
Summary of the configuration used to launch the kernel. The launch configuration defines the size of the kernel grid, the division of the grid into blocks, and the GPU resources needed to execute the kernel. Choosing an efficient launch configuration maximizes device utilization.	
Grid Size	1,024 Registers Per Thread [register/thread]
Block Size	1,056 Static Shared Memory Per Block [byte/block]
Threads [thread]	262,144 Dynamic Shared Memory Per Block [byte/block]
Waves Per SM	7,11 Driver Shared Memory Per Block [byte/block]
Function Cache Configuration	cudaFuncCacheNone Shared Memory Configuration Size [kbyte] 32,77
Occupancy	
Occupancy is the ratio of the number of active warps per multiprocessor to the maximum number of possible active warps. Another way to view occupancy is the percentage of the hardware's ability to process warps that is actively in use. Higher occupancy does not always result in higher performance, however, low occupancy always reduces the ability to hide latencies, resulting in overall performance degradation. Large discrepancies between the theoretical and the achieved occupancy during execution typically indicates highly imbalanced workloads.	
Theoretical Occupancy [%]	100 Block Limit Registers [block] 31
Theoretical Active Warps per SM [warp]	32 Block Limit Shared Mem [block] 0
Achieved Occupancy [%]	95,67 Block Limit Warps [block] 0
Achieved Active Warps Per SM [warp]	30,62 Block Limit SM [block] 16

Figure 2.10 Launch statistics and occupancy




Figure 2.11 Warp occupancy analysis

Recommendations	
Occupancy	This kernel's theoretical occupancy is not impacted by any block limit.
Source Counters ▲	
Source metrics, including branch efficiency and sampled warp stall reasons. Sampling Data metrics are periodically sampled over the kernel runtime. They indicate when warps were stalled and couldn't be scheduled. See the documentation for a description of all stall reasons. Only focus on stalls if the schedulers fail to issue every cycle.	Most Instructions Executed
Branch Instructions (inst)	2,503,193,367 Branch Efficiency (%) 88,83
Branch Instructions Ratio (%)	0,17 Avg. Divergent Branches 1,707,456,31
Most Instructions Executed	
Location	Value
0x7f3856f66d40 in FastRandomWalkCUDAKernel	876,282,222
0x7f3856f66e20 in FastRandomWalkCUDAKernel	876,282,222
0x7f3856f66e10 in FastRandomWalkCUDAKernel	876,282,222
0x7f3856f66e00 in FastRandomWalkCUDAKernel	876,282,222
0x7f3856f66d00 in FastRandomWalkCUDAKernel	876,282,222
Recommendations	
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 495729524 sectors, got 1129463138 (2.28x) at PC 0x7f3856f972e0
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 10706038 sectors, got 235929600 (22.04x) at PC 0x7f3856f97500
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 73523408 sectors, got 219526454 (2.99x) at PC 0x7f3856f96e50
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 73523408 sectors, got 219526454 (2.99x) at PC 0x7f3856f96e00
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 73523408 sectors, got 219524734 (2.99x) at PC 0x7f3856f96e60
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 73523408 sectors, got 219524734 (2.99x) at PC 0x7f3856f96e00
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 73523408 sectors, got 219523845 (2.99x) at PC 0x7f3856f96e70
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 73523408 sectors, got 219523845 (2.99x) at PC 0x7f3856f96e00
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 112931494 sectors, got 242418510 (2.15x) at PC 0x7f3856f913e0
Uncoalesced Global Accesses	[Warning] Uncoalesced global access, expected 819200 sectors, got 26214400 (32.00x) at PC 0x7f3856f97500

Figure 2.12 Instructional statistics

2.0.2 Session




Figure 2.13 Session overview

Device Attributes	
Filter:	
Attribute	GeForce RTX 2070 (0)
architecture	352
async_engine_count	3
can_flush_remote_writes	0
can_map_host_memory	1
can_tex2d_gather	1
can_use_64_bit_stream_mem_ops	0
can_use_host_pointer_for_registered_mem	1
can_use_stream_mem_ops	0
can_use_stream_wait_value_nor	0
chip	358
clock_rate	1440000
compute_capability_major	7
compute_capability_minor	5
compute_mode	0
compute_preemption_supported	1
concurrent_kernels	1
concurrent_managed_access	1
cooperative_launch	1
cooperative_multi_device_launch	1
device_index	0
direct_managed_mem_access_from_host	0
display_name	GeForce RTX 2070
ecc_enabled	0
fb_bus_width	256
flop_count	4
generic_compression_supported	0
global_l1_cache_supported	1
global_memory_bus_width	256
gpu_direct_rdma_with_cuda_vmm_supported	0
gpu_overlap	1
gpu_pci_device_id	521146590
gpu_pci_ext_device_id	7952
gpu_pci_ext_downstream_link_rate	8000
gpu_pci_ext_downstream_link_width	16
gpu_pci_ext_gen	2
gpu_pci_ext_gpu_gen	2
gpu_pci_ext_gpu_link_rate	8000

Figure 2.14 Device details

gpu_pci_ext_gpu_link_width	16
gpu_pci_revision_id	161
gpu_pci_sub_system_id	274537733
handle_type_posix_file_descriptor_supported	1
handle_type_win32_handle_supported	0
handle_type_win32_kmt_handle_supported	0
host_native_atomic_supported	0
host_register_supported	1
implementation	358
integrated	0
kernel_exec_timeout	0
l2_cache_size	4194304
l2s_count	32
limits_max_cta_per_sm	16
local_l1t_cache_supported	1
managed_memory	1
max_access_policy_window_size	0
max_block_dim_x	1024
max_block_dim_y	1024
max_block_dim_z	64
max_blocks_per_multiprocessor	16
max_gpu_frequency_khz	1440000
max_grid_dim_x	2147483647
max_grid_dim_y	65535
max_grid_dim_z	65535
max_ipc_per_multiprocessor	4
max_ipc_per_scheduler	1
max_mem_frequency_khz	7001000
max_persisting_l2_cache_size	0
max_pitch	2147483647
max_registers_per_block	65536
max_registers_per_multiprocessor	65536
max_registers_per_thread	255
max_shared_memory_per_block	49152
max_shared_memory_per_block_optin	65536
max_shared_memory_per_multiprocessor	65536
max_threads_per_block	1024
max_threads_per_multiprocessor	1024
max_warp_per_multiprocessor	32
max_warp_per_scheduler	8
maximum_surface_id_layered_layers	2048

Figure 2.15 Device details cont

maximum_surface_id_layered_width	32768
maximum_surface_id_width	32768
maximum_surface_id_height	65536
maximum_surface_id_layered_height	32768
maximum_surface_id_layered_layers	2048
maximum_surface_id_layered_width	32768
maximum_surface_id_width	131072
maximum_surface_id_depth	16384
maximum_surface_id_height	16384
maximum_surface_id_width	16384
maximum_surfacecubemap_layered_layers	2046
maximum_surfacecubemap_layered_width	32768
maximum_surfacecubemap_width	32768
maximum_texture_id_layered_layers	2048
maximum_texture_id_layered_width	32768
maximum_texture_id_linear_width	268435456
maximum_texture_id_mipmapped_width	32768
maximum_texture_id_width	131072
maximum_texture2d_gather_height	32768
maximum_texture2d_gather_width	32768
maximum_texture2d_height	65536
maximum_texture2d_layered_height	32768
maximum_texture2d_layered_layers	2048
maximum_texture2d_layered_width	32768
maximum_texture2d_linear_height	65000
maximum_texture2d_linear_pitch	2097120
maximum_texture2d_linear_width	131072
maximum_texture2d_mipmapped_height	32768
maximum_texture2d_mipmapped_width	32768
maximum_texture2d_width	131072
maximum_texture3d_depth	16384
maximum_texture3d_depth_alternate	32768
maximum_texture3d_height	16384
maximum_texture3d_height_alternate	8192
maximum_texture3d_width	16384
maximum_texture3d_width_alternate	8192
maximum_texturecubemap_layered_layers	2046
maximum_texturecubemap_layered_width	32768
maximum_texturecubemap_width	32768
memory_clock_rate	7001000
multi_gpu_board	0

Figure 2.16 Device details cont

```
multi.gpu.board.group_id          0
multiprocessor_count              36
num_12s_per_fbp                  8
num_schedulers_per_multiprocessor 4
num_tx_per_multiprocessor        1
pageable_memory_access           0
pageable_memory_access_uses_host_page_tables 0
pci.bus_id                       1
pci.device_id                     0
pci.domain_id                     0
ram_location                      1
ram_type                          17
reserved.shared_memory_per_block   0
sass_level                        7
single_to_double_precision_ratio  32
stream_priorities_supported      1
surface_alignment                 512
ttc_driver                        0
texture_alignment                 512
texture_pitch_alignment           32
total_constant_memory             65536
total_memory                       8370061312
unified_addressing                1
virtual_address.management_supported 1
warp_size                          32
```

Figure 2.17 Device details cont

2.0.3 PTX

#	Address	Source	Live Registers	Sampling Data (All)	Sampling Data (Not issued)	Instructions Executed	sted-On Thread Executed	Avg Thread Executed	Divergent Branches	Address Space	Access Operation	Access Size
33	00007f38_56f96d00	PRMT R18, R13, 0x9910, RZ	17	687	82	11.684.464	287.649.750	24				
34	00007f38_56f96d10	PRMT R13, R15, 0x9910, RZ	17	20,31,1	12.991	11.684.464	287.649.750	24				
35	00007f38_56f96d20	ISETP_NE.AND PO, PT, R13, R18, PT	17	1,328	385	11.684.464	287.649.750	24				
36	00007f38_56f96d30	IMAD_MOV.U32 R13, RZ, RZ, [0x0]{0x178}	17	171	0	11.684.464	287.649.750	24				
37	00007f38_56f96d40	@PB BRA 0x7f3856f96e40	17	2,254	778	11.684.464	0	0	0			
38	00007f38_56f96d50	IMAD_U32 R16, RZ, RZ, UR4	17	1,086	372	11.684.464	287.649.750	24				
39	00007f38_56f96d60	IMAD_U32 R17, RZ, RZ, UR5	18	434	70	11.684.464	287.649.750	24				
40	00007f38_56f96d70	IMAD_MOV.U32 R19, RZ, RZ, c[0x0]{0x178}	19	457	65	11.684.464	287.649.750	24				
41	00007f38_56f96d80	PRMT R13, R15, 0x9910, RZ	20	99,140	36,576	876.282,222	5,995,224,188	18				
42	00007f38_56f96d90	ISETP_NE.AND PO, PT, R13, RZ, PT	20	109,188	29,140	876.282,222	5,995,224,188	18				
43	00007f38_56f96da0	IMAD_MOV.U32 R13, RZ, RZ, RZ	20	14,340	0	876.282,222	5,995,224,188	18				
44	00007f38_56f96db0	@PB BRA 0x7f3856f96e40	20	17,459	54,075	876.282,222	0	0	0			
45	00007f38_56f96dc0	LDG_E,U8SYS R15, [R16]	20	356,113	213,113	876.282,222	5,995,224,188	18				
46	00007f38_56f96dd0	IADD R19, R19, 0x1, RZ	20	14,661	0	876.282,222	5,995,224,188	18				
47	00007f38_56f96de0	IADD R16, R1, R16, 0x1, RZ	20	84,787	109,807	876.282,222	5,995,224,188	18				
48	00007f38_56f96df0	IMAD_X R17, RZ, RZ, R17, P1	20	92,920	25,942	876.282,222	5,995,224,188	18				
49	00007f38_56f96e00	PRMT R13, R15, 0x9910, RZ	20	506,019	233,027	876.282,222	5,995,224,188	18				
50	00007f38_56f96e10	ISETP_NE.AND PO, PT, R13, R18, PT	20	104,47	26,136	876.282,222	5,995,224,188	18				
51	00007f38_56f96e20	@PO BRA 0x7f3856f96e40	20	18,644	63,081	876.282,222	5,707,574,438	17	130,300,867			
52	00007f38_56f96e30	IMAD_MOV.U32 R13, RZ, RZ, R19	16	66,2,3	17,746	141,490,440	287.649.750	24				
53	00007f38_56f96e40	BSYNC B1	15	21,174	6,043	141,490,440	287.649.750	24				
54	00007f38_56f96e50	LDG_E,U4SYS R16, [R2]	17	29,214	12,084	11.684.464	287.649.750	24				
55	00007f38_56f96e60	LDG_E,U4SYS R20, [R2+0x8]	19	3,706	9,995	11.684.464	287.649.750	24				
56	00007f38_56f96e70	LDG_E,U4SYS R22, [R2+0x10]	21	4,206	2,322	11.684.464	287.649.750	24				
57	00007f38_56f96e80	IADD R28, R13, -c[0x10]{0x178}, RZ	22	205	0	11.684.464	287.649.750	24				
58	00007f38_56f96e90	LEA R18, R0, R28, c[0x0]{0x180}, 0x3	23	1,678	368	11.684.464	287.649.750	24				
59	00007f38_56f96ea0	IMAD_U32 R15, R16, 0x10000, RZ	24	126,820	56,945	11.684.464	287.649.750	24				
60	00007f38_56f96eb0	SHF_L,U64_HI R19, R16, 0x18, R17	25	214	0	11.684.464	287.649.750	24				
61	00007f38_56f96ec0	STG_E,U4SYS [R2], R20	25	10,863	6,815	11.684.464	287.649.750	24				
62	00007f38_56f96ed0	LOP3_LUT R16, R15, R16, RZ, 0x3c, IPT	25	787	202	11.684.464	287.649.750	24				
63	00007f38_56f96ee0	LOP3_LUT R17, R19, R17, RZ, 0x3c, IPT	24	437	108	11.684.464	287.649.750	24				
64	00007f38_56f96ef0	STG_E,U4SYS [R2+0x8], R22	23	7,406	4,422	11.684.464	287.649.750	24				
65	00007f38_56f96f00	SFH_R,S32_HI R15, RZ, 0x1f, R28	24	196	0	11.684.464	287.649.750	24				

# Address	Source	Live Registers	Sampling Data (All)	Sampling Data (Not Issued)	Instructions Executed	at-on Thread	Avg Thread Executed	Divergent Branches	Address Space	Access Operation	Access Size
66 00007f38 56f96f10	SHF.R.U64 R25, R16, 0x5, R17	29	1.483	557	11.684.464	287.649.750	24				
67 00007f38 56f96f20	SHF.R.U32.HI R26, R2, 0x3, R17	26	485	153	11.684.464	287.649.750	24				
68 00007f38 56f96f30	IOP3.LUT R25, R25, R16, R2, 0x3c, IPT	26	471	120	11.684.464	287.649.750	24				
69 00007f38 56f96f40	IOP3.LUT R26, R26, R17, R2, 0x3c, IPT	25	461	134	11.684.464	287.649.750	24				
70 00007f38 56f96f50	IOP3.LUT R16, R20, R2, RZ, 0x3c, IPT	25	477	156	11.684.464	287.649.750	24				
71 00007f38 56f96f60	IMAD.SHL.U32 R19, R25, 0x2, RZ	24	202	0	11.684.464	287.649.750	24				
72 00007f38 56f96f70	LOP3.LUT R17, R21, R23, RZ, 0x3c, IPT	25	201	0	11.684.464	287.649.750	24				
73 00007f38 56f96f80	SHF.L.U64.HI R24, R25, 0x1, R26	24	1.889	481	11.684.464	287.649.750	24				
74 00007f38 56f96f90	LOP3.LUT R16, R16, R19, R25, 0x06, IPT	24	427	121	11.684.464	287.649.750	24				
75 00007f38 56f96fb0	LEA.H.IX R19, R28, C[0x0][0x184], R15, 0x3, P0	21	445	142	11.684.464	287.649.750	24				
77 00007f38 56f96fc0	STG.E.64.SYS [R2+0x10], R16	19	10.643	6.778	11.684.464	287.649.750	24				64
78 00007f38 56f96fd0	LDC.E.64.SYS R18, [R18]	19	5.739	3.464	11.684.464	287.649.750	24				64
79 00007f38 56f96fe0	BMOV.32.CLEAR RZ, B1	19	201	0	11.684.464	287.649.750	24				
80 00007f38 56f96ff0	BSSY B1, 0x7f3856f97190	19	233	1	11.684.464	287.649.750	24				
81 00007f38 56f97000	LOP3.LUT R15, R17, R19, R2, 0x0c, IPT	20	21.874	11.248	11.684.464	287.649.750	24				
82 00007f38 56f97010	LOP3.LUT R17, R17, R24, R6, 0x06, IPT	19	1.267	375	11.684.464	287.649.750	24				
83 00007f38 56f97020	@P0 BRA 0x7f3856f97060	18	2.539	1.016	11.684.464	6	0	6			
84 00007f38 56f97030	MOV R20, 0x550	18	1.118	404	11.684.464	287.649.744	24				
85 00007f38 56f97040	CALL.REL.NOIND 0x7f3856f97610	17	1.763	702	11.684.464	287.649.744	24				
86 00007f38 56f97050	BRA 0x7f3856f97180	17	2.548	1.016	11.684.464	287.649.744	24				
87 00007f38 56f97060	I2F.U32.RP R15, R18	18	767	218	6	6	1				
88 00007f38 56f97070	IMAD.MOV R17, RZ, RZ, -R18	19	0	0	6	6	1				
89 00007f38 56f97080	ISETP.NE.U32.AND P1, PT, R18, RZ, PT	19	0	0	6	6	1				
90 00007f38 56f97090	MUFU.RCP R15, R15	19	0	0	6	6	1				
91 00007f38 56f97090	IADD3 R20, R15, 0xfffffe, RZ	20	0	0	6	6	1				
92 00007f38 56f97080	F2I.FTZ.U32.TRUNC.NTZ R21, R20	20	0	0	6	6	1				
93 00007f38 56f97080	IMAD.MOV.U32 R20, RZ, RZ, RZ	20	0	0	6	6	1				
94 00007f38 56f97060	IMAD R17, R17, R21, R2	20	0	0	6	6	1				
95 00007f38 56f970e0	IMAD.HI.U32 R21, R21, R17, R20	20	0	0	6	6	1				
96 00007f38 56f970f0	IMAD.MOV.U32 R17, RZ, RZ	19	0	0	6	6	1				
97 00007f38 56f97100	IMAD.HI.U32 R21, R21, R16, R2	19	0	0	6	6	1				
98 00007f38 56f97110	IMAD.MOV R21, RZ, RZ, -R21	19	0	0	6	6	1				

# Address	Source	Live Registers	Sampling Data (All)	Sampling Data (Not Issued)	Instructions Executed	at-on Thread	Avg Thread Executed	Divergent Branches	Address Space	Access Operation	Access Size
99 00007f38 56f97120	IMAD.R16, R18, R21, R16	19	0	0	6	6	1				
100 00007f38 56f97130	ISETP.GE.U32.AND P0, PT, R16, R18, PT	18	0	0	6	6	1				
101 00007f38 56f97140	@P0 IMAD.IADD R16, R16, 0x1, -R18	18	0	0	6	0	0				
102 00007f38 56f97150	ISETP.GE.P0, PT, R16, R18, PT	18	0	0	6	6	1				
103 00007f38 56f97160	@P0 IMAD.IADD R16, R16, 0x1, -R18	18	0	0	6	0	0				
104 00007f38 56f97170	@P1 IOP3.LUT R16, R2, R18, RZ, 0x33, IPT	18	0	0	6	0	0				
105 00007f38 56f97180	BSYNC B1	17	2.039	892	11.684.470	287.649.750	24				
106 00007f38 56f97190	ISETP.GE.AND P0, PT, R0, PT, R0, 0x1, PT	17	2.707	1.008	11.684.464	287.649.750	24				
107 00007f38 56f971a0	@P0 BRA 0x7f3856f97400	17	2.528	922	11.684.464	0	0	0			
108 00007f38 56f971b0	IADD3 R15, R13, -c[0x0][0x178], RZ	18	1.068	355	11.684.464	287.649.750	24				
109 00007f38 56f971c0	IMAD.MOV.U32 R20, R18, RZ, C[0x0][0x190]	18	184	0	11.684.464	287.649.750	24				
110 00007f38 56f971d0	BMOV.32.CLEAR RZ, B1	18	195	0	11.684.464	287.649.750	24				
111 00007f38 56f971e0	IMAD.MOV.U32 R21, RZ, 0xfffffe, RZ	19	167	0	11.684.464	287.649.750	24				
112 00007f38 56f971f0	SHF.R.S32.HI R22, RZ, 0x1f, R15	20	194	0	11.684.464	287.649.750	24				
113 00007f38 56f97200	IMAD.MOV.U32 R19, R19, RZ, 0x8	21	175	2	11.684.464	287.649.750	24				
114 00007f38 56f97210	BSSY B1, 0x7f3856f97400	21	159	0	11.684.464	287.649.750	24				
115 00007f38 56f97220	IMAD.R18, R15, c[0x0][0x198], RZ	22	192	1	11.684.464	287.649.750	24				
116 00007f38 56f97230	IMAD.R19, R8, R15, R15, R15	23	507	33	11.684.464	287.649.750	24				
117 00007f38 56f97240	IMAD.WIDE.U32 R20, R15, c[0x0][0x198], R20	23	400	41	11.684.464	287.649.750	24				
118 00007f38 56f97250	IMAD.WIDE.R18, R19, R19, c[0x0][0x188]	22	1.434	192	11.684.464	287.649.750	24				
119 00007f38 56f97260	IMAD.R13, R22, c[0x0][0x198], R13	22	1.471	239	11.684.464	287.649.750	24				
120 00007f38 56f97270	IMAD.MOV.U32 R15, RZ, RZ, R20	22	735	75	11.684.464	287.649.750	24				
121 00007f38 56f97280	IMAD.IADD R24, R24, 0x1, R13	22	481	49	11.684.464	287.649.750	24				
122 00007f38 56f97290	IMAD.MOV.U32 R13, R13, RZ, R18	21	433	58	11.684.464	287.649.750	24				
123 00007f38 56f972a0	IMAD.MOV.U32 R18, R18, R18, R18	21	480	81	11.684.464	287.649.750	24				
124 00007f38 56f972b0	IMAD.MOV.U32 R20, RZ, RZ, RZ	21	474	66	11.684.464	287.649.750	24				
125 00007f38 56f972c0	IMAD.MOV.U32 R18, RZ, R2, R13	22	18.654	6.950	17.2403.954	1.902.672.000	11				
126 00007f38 56f972d0	IMAD.MOV.U32 R19, RZ, RZ, R22	23	6.550	1.097	17.2403.954	1.902.672.000	11				
127 00007f38 56f972e0	LDC.E.64.SYS R18, [R18]	23	114.75	68.549	17.2403.954	1.902.672.000	11				
128 00007f38 56f972f0	IADD3 R16, P0, -R18, R18, R16	23	311.537	152.671	17.2403.954	1.902.672.000	11				
129 00007f38 56f97300	IMAD.X R17, R17, 0x1, -R19, P0	22	17.804	5.596	17.2403.954	1.902.672.000	11				
130 00007f38 56f97310	ISETP.GE.U32.AND P0, PT, R16, RZ, PT	21	2.876	0	17.2403.954	1.902.672.000	11				
131 00007f38 56f97320	ISETP.GE.AND P0, PT, R17, RZ, PT, P0	21	22.174	5.962	17.2403.954	1.902.672.000	11				

# Address	Source	Live Registers	Data (All)	Sampling Data (Not Issued)	Instructions Executed	at-on Thread	Avg Thread Executed	Divergent Branches	Address Space	Access Operation	Access Size
132 00007f38 56f97330	@P0 BRA 0x7f3856f973c0	21	36.388	15.144	172.403.640	287.649.750	24	104.391.323			
133 00007f38 56f97340	IADD3 R20, R20, 0x1, RZ	21	24.534	9.068	160.719.550	1.615.022.310	10				
134 00007f38 56f97350	IADD3 R15, P1, R15, 0x1, RZ	21	6.096	1.530	160.719.550	1.615.022.310	10				
135 00007f38 56f97360	ISETP.GE.AN P0, PT, R20, R9, PT	21	6.332	1.587	160.719.550	1.615.022.310	10				
136 00007f38 56f97370	IADD3 R13, P2, R13, 0x8, RZ	21	6.376	1.805	160.719.550	1.615.022.310	10				
137 00007f38 56f97380	IMAD.X R24, R2, RZ, R24, P1	21	2.671	30	160.719.550	1.615.022.310	10				
138 00007f38 56f97390	IMAD.X R22, R22, RZ, R2, R22, P2	21	14.497	2.222	160.719.550	1.615.022.310	10				
139 00007f38 56f973a0	@P0 BRA 0x7f3856f972c0	21	16.604	4.259	160.719.550	1.615.022.310	10				
140 00007f38 56f973d0	IMAD.MOV.U32 R16, RZ, RZ, R15	14	10.624	2.949	0	0	0	0			
141 00007f38 56f973e0	IMAD.MOV.U32 R16, R1, PT, R16, R15	16	12.297	5.673	112.931.450	287.649.750	24				
142 00007f38 56f973f0	IMAD.MOV.U32 R17, RZ, R24, R24	16	4.465	883	112.931.450	287.649.750	24				
143 00007f38 56f973g0	LDC.E.US.B.SYS R11, [R16]	16	13.527	44.12	112.931.450	287.649.750					

# Address	Source	Live Registers	Sampling Data (All)	Sampling Data (Not Issued)	Instructions Executed	at-On Thread	Avg Thread Executed	Divergent Branches	Address Space	Access Operation	Access Size
165 00007f38 56f97540	B SYNC_B0	13	1.160	332	2,747,966	26,214,400	9				
166 00007f38 56f97550	IMAD.MOV.U32 R4, RZ, RZ, 0xa	14	1.079	455	819,200	26,214,400	32				
167 00007f38 56f97560	IADD R10, R10, 0x1, RZ	14	14	0	819,200	26,214,400	32				
168 00007f38 56f97570	IADD R5, R5, 0x1, RZ	14	31	6	819,200	26,214,400	32				
169 00007f38 56f97580	ISETP.GE.U32.AND P0, PT, R10, c[0x0][0x1601], PT	14	33	9	819,200	26,214,400	32				
170 00007f38 56f97590	SHF.R.S32.NI R0, RZ, 0x1f, R10	15	29	8	819,200	26,214,400	32				
171 00007f38 56f975a0	STG.E.UB.SYS [R16], R4	15	330	212	819,200	26,214,400	32			Global	Store
172 00007f38 56f975b0	IADD R14, P1, R5, R14, RZ	14	14	0	819,200	26,214,400	32				
173 00007f38 56f975c0	ISETP.GE.U32.AND EX P0, PT, R0, c[0x0][0x164], PT	14	157	36	819,200	26,214,400	32				
174 00007f38 56f975d0	LEA.HI,X.SX32 R12, R5, R12, 0x1, P1	13	35	8	819,200	26,214,400	32				
175 00007f38 56f975e0	EIP# BRA 0x7f3856f96c50	12	190	82	819,200	25,952,256	31	0			
176 00007f38 56f975f0	STG.E.UB.SYS [R16+0x1], RZ	5	52	14	8,192	262,144	32			Global	Store
177 00007f38 56f97600	EXTT	1	1	0	8,192	262,144	32				
178 00007f38 56f97610	I2F.U64.RP R15, R18	1	1,641	767	11,684,464	287,649,744	24				
179 00007f38 56f97620	MVFU.RCP R15, R16	1	8,356	3,739	11,684,464	287,649,744	24				
180 00007f38 56f97630	IADD R22, R15, 0x1fffffe, RZ	4	3,209	1,254	11,684,464	287,649,744	24				
181 00007f38 56f97640	F2I.U64.TRUNC R12, R22	4	1,386	431	11,684,464	287,649,744	24				
182 00007f38 56f97650	IMAD.WIDE.U32 R24, R22, R18, RZ	4	8,611	3,881	11,684,464	287,649,744	24				
183 00007f38 56f97660	IMAD.R21, R22, R19, R25	5	1,956	606	11,684,464	287,649,744	24				
184 00007f38 56f97670	IADD R27, P0, RZ, -R24, RZ	5	181	0	11,684,464	287,649,744	24				
185 00007f38 56f97680	IMAD.MOV.U32 R25, RZ, RZ, R22	5	203	0	11,684,464	287,649,744	24				
186 00007f38 56f97690	IMAD.R21, R23, R18, R21	5	504	61	11,684,464	287,649,744	24				
187 00007f38 56f976a0	IMAD.HI.U32 R24, R22, R27, RZ	6	480	63	11,684,464	287,649,744	24				
188 00007f38 56f976b0	IMAD.X R21, R2, R21, P0	6	1,468	237	11,684,464	287,649,744	24				
189 00007f38 56f976c0	IMAD.WIDE.U32 R24, P0, R22, R21, R24	6	4,408	218	11,684,464	287,649,744	24				
190 00007f38 56f976d0	IMAD.HI.U32 R22, R23, R21, RZ	6	1,327	231	11,684,464	287,649,744	24				
191 00007f38 56f976e0	IMAD.HI.U32 R24, P1, R23, R27, R24	6	1,697	244	11,684,464	287,649,744	24				
192 00007f38 56f976f0	IMAD.R27, R23, R21, RZ	5	1,524	225	11,684,464	287,649,744	24				
193 00007f38 56f97700	IMAD.X R22, R23, R1x, R23, P0	4	771	61	11,684,464	287,649,744	24				
194 00007f38 56f97710	IMAD.MOV.U32 R23, RZ, RZ, RZ	4	479	69	11,684,464	287,649,744	24				
195 00007f38 56f97720	IADD R27, P2, R27, R24, RZ	4	198	0	11,684,464	287,649,744	24				
196 00007f38 56f97730	IADD.X R15, RZ, RZ, R22, P2, P1	4	1,833	381	11,684,464	287,649,744	24				
197 00007f38 56f97740	IMAD.WIDE.U32 R24, R27, R18, RZ	5	181	0	11,684,464	287,649,744	24				

# Address	Source	Live Registers	Sampling Data (All)	Sampling Data (Not Issued)	Instructions Executed	at-On Thread	Avg Thread Executed	Divergent Branches	Address Space	Access Operation	Access Size
198 00007f38 56f97750	IMAD.R21, R27, R19, R25	6	2,029	536	11,684,464	287,649,744	24				
199 00007f38 56f97760	IADD R25, P0, RZ, -R24, RZ	6	217	0	11,684,464	287,649,744	24				
200 00007f38 56f97770	IMAD.R11, R15, R18, R21	5	975	159	11,684,464	287,649,744	24				
201 00007f38 56f97780	IMAD.HI.U32 R26, R27, R25, RZ	6	540	58	11,684,464	287,649,744	24				
202 00007f38 56f97790	IMAD.X R22, R2, RZ, -R21, P0	7	1,444	222	11,684,464	287,649,744	24				
203 00007f38 56f977a0	IMAD.WIDE.U32 R26, P0, R27, R22, R26	6	1,383	241	11,684,464	287,649,744	24				
204 00007f38 56f977b0	IMAD.R24, R15, R22, RZ	7	1,388	230	11,684,464	287,649,744	24				
205 00007f38 56f977c0	IMAD.HI.U32 R21, P1, R15, R16, R26	8	1,483	213	11,684,464	287,649,744	24				
206 00007f38 56f977d0	IADD R21, P2, R24, R21, RZ	8	2,784	807	11,684,464	287,649,744	24				
207 00007f38 56f977e0	IMAD.HI.U32 R24, R22, R2, RZ	8	206	0	11,684,464	287,649,744	24				
208 00007f38 56f977f0	IMAD.HI.U32 R22, R21, R16, RZ	8	1,296	213	11,684,464	287,649,744	24				
209 00007f38 56f97800	IMAD.X R15, R24, R1x, R15, P0	8	1,577	243	11,684,464	287,649,744	24				
210 00007f38 56f97810	IMAD.WIDE.U32 R22, R21, R17, R22	8	1,313	250	11,684,464	287,649,744	24				
211 00007f38 56f97820	IADD.X R15, RZ, R2, R15, P2, P1	7	209	0	11,684,464	287,649,744	24				
212 00007f38 56f97830	IMAD.HI.U32 R0, P0, R15, R16, R12	8	2,156	659	11,684,464	287,649,744	24				
213 00007f38 56f97840	IMAD.R22, R15, R17, RZ	7	1,294	247	11,684,464	287,649,744	24				
214 00007f38 56f97850	IMAD.HI.U32 R15, R15, R17, RZ	7	727	82	11,684,464	287,649,744	24				
215 00007f38 56f97860	IADD.R21, P1, R22, R21, RZ	7	1,749	317	11,684,464	287,649,744	24				
216 00007f38 56f97870	IMAD.X R15, RZ, R2, R15, P0	6	1,179	280	11,684,464	287,649,744	24				
217 00007f38 56f97880	IMAD.WIDE.U32 R22, R21, R18, RZ	8	644	60	11,684,464	287,649,744	24				
218 00007f38 56f97890	IMAD.R21, R21, R19, R23	8	205	0	11,684,464	287,649,744	24				
219 00007f38 56f978a0	IMAD.R21, R21, R19, R23	8	729	57	11,684,464	287,649,744	24				
220 00007f38 56f978b0	IADD.R23, P1, R22, R16, RZ	8	205	0	11,684,464	287,649,744	24				
221 00007f38 56f978c0	IMAD.R15, R15, R18, R21	8	934	139	11,684,464	287,649,744	24				
222 00007f38 56f978d0	ISETP.GE.U32.AND P0, PT, R23, R18, PT	7	216	0	11,684,464	287,649,744	24				
223 00007f38 56f978e0	IMAD.X R17, R17, 0x1, -R15, P1	8	922	149	11,684,464	287,649,744	24				
224 00007f38 56f978f0	IADD.R15, P1, R17, 0x1, -R15, P1	8	284	0	11,684,464	287,649,744	24				
225 00007f38 56f97900	ISETP.GE.U32.AND EX P0, PT, R17, R19, PT, P0	9	1,874	449	11,684,464	287,649,744	24				
226 00007f38 56f97910	IMAD.X R21, R17, 0x1, -R19, P1	9	197	0	11,684,464	287,649,744	24				
227 00007f38 56f97920	ISETP.NE.U32.AND P0, PT, R17, R19, PT, P0	9	217	0	11,684,464	287,649,744	24				
228 00007f38 56f97930	SEL.R15, R15, R13, P0	9	528	95	11,684,464	287,649,744	24				
229 00007f38 56f97940	SEL.R21, R21, R17, P0	9	479	135	11,684,464	287,649,744	24				
230 00007f38 56f97950	IADD.R16, P2, -R18, R15, RZ	9	508	136	11,684,464	287,649,744	24				
231 00007f38 56f97960	ISETP.GE.U32.AND EX P0, PT, R15, R18, PT	9	472	145	11,684,464	287,649,744	24				
232 00007f38 56f97970	ISETP.NE.AND EX P1, PT, R19, RZ, PT, P1	9	1,790	467	11,684,464	287,649,744	24				
233 00007f38 56f97980	IMAD.X R17, R21, 0x1, -R19, P2	10	199	0	11,684,464	287,649,744	24				
234 00007f38 56f97990	ISETP.GE.U32.AND EX P0, PT, R21, R19, PT, P0	10	185	0	11,684,464	287,649,744	24				
235 00007f38 56f979a0	SEL.R17, R17, R21, P0	10	1,358	367	11,684,464	287,649,744	24				
236 00007f38 56f979b0	IMAD.MOV.U32 R21, R2, RZ, 0x0	10	192	0	11,684,464	287,649,744	24				
237 00007f38 56f979c0	SEL.R16, R16, R15, P0	10	201	0	11,684,464	287,649,744	24				
238 00007f38 56f979d0	SEL.R17, R17, 0xffffffff, P1	9	484	115	11,684,464	287,649,744	24				
239 00007f38 56f979e0	SEL.R16, R16, 0xffffffff, P1	9	422	123	11,684,464	287,649,744	24				
240 00007f38 56f979f0	RET.REL.NODEC R20 0x7f3856f96b00	9	192	0	11,684,464	287,649,744	24	0			
241 00007f38 56f97a00	BRA 0x7f3856f97a00	0	7,516	3,626							
242 00007f38 56f97a10	NOP		0	0	0	0	0				
243 00007f38 56f97a20	NOP		0	0	0	0	0				
244 00007f38 56f97a30	NOP		0	0	0	0	0				
245 00007											

CHAPTER3

Deprecated List

Member **Markov::API::MarkovPasswords::Generate** (`unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20`)

See `Markov::API::MatrixModel::FastRandomWalk` for more information.

CHAPTER4

Namespace Index

4.1 Namespace List

Here is a list of all namespaces with brief descriptions:

markopy	29
Markov	
Namespace for the markov-model related classes. Contains Model , Node and Edge classes	33
Markov::API	
Namespace for the MarkovPasswords API	33
Markov::API::CLI	
Structure to hold parsed cli arguements	34
Markov::API::Concurrency	
Namespace for Concurrency related classes	35
Markov::API::CUDA	
Namespace for objects requiring CUDA libraries	35
Markov::API::CUDA::Random	
Namespace for Random engines operable under device space	37
Markov::GUI	
Namespace for MarkovPasswords API GUI wrapper	38
Markov::Markopy	38
Markov::Random	
Objects related to RNG	39
model_2gram	40
random	40
random-model	40
Testing	
Namespace for Microsoft Native Unit Testing Classes	41
Testing::MarkovModel	
Testing namespace for MarkovModel	41
Testing::MarkovPasswords	
Testing namespace for MarkovPasswords	44
Testing::MVP	
Testing Namespace for Minimal Viable Product	45
Testing::MVP::MarkovModel	
Testing Namespace for MVP MarkovModel	45
Testing::MVP::MarkovPasswords	
Testing namespace for MVP MarkovPasswords	50

CHAPTER5

Hierarchical Index

5.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Markov::API::CLI::_programOptions	53
Markov::API::CLI::Argparse	57
Markov::API::CUDA::CUDADeviceController	66
Markov::API::CUDA::CUDAModelMatrix	73
Markov::API::CUDA::Random::Marsaglia	150
Markov::Edge< NodeStorageType >	115
Markov::Edge< char >	115
Markov::Edge< storageType >	115
Markov::Model< NodeStorageType >	167
Markov::Model< char >	167
Markov::API::MarkovPasswords	124
Markov::API::ModelMatrix	175
Markov::API::CUDA::CUDAModelMatrix	73
Markov::Node< storageType >	201
Markov::Node< char >	201
Markov::Node< NodeStorageType >	201
QMainWindow	209
Markov::GUI::about	56
Markov::GUI::CLI	63
Markov::GUI::Generate	120
Markov::GUI::MarkovPasswordsGUI	141
Markov::GUI::menu	160
Markov::GUI::Train	218
Markov::Random::RandomEngine	209
Markov::Random::DefaultRandomEngine	110
Markov::Random::Marsaglia	144
Markov::API::CUDA::Random::Marsaglia	150
Markov::Random::Mersenne	162
Markov::API::CLI::Terminal	211
Markov::API::Concurrency::ThreadSharedListHandler	214
char	??
long int	??

CHAPTER6

Class Index

6.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Markov::API::CLI::_programOptions	Structure to hold parsed cli arguements	53
Markov::GUI::about	QT Class for about page	56
Markov::API::CLI::Argparse	Parse command line arguements	57
Markov::GUI::CLI	QT CLI Class	63
Markov::API::CUDA::CUDADeviceController	Controller class for CUDA device	66
Markov::API::CUDA::CUDAModelMatrix	Extension of Markov::API::ModelMatrix which is modified to run on GPU devices	73
Markov::Random::DefaultRandomEngine	Implementation using Random.h default random engine	110
Markov::Edge< NodeStorageType >	Edge class used to link nodes in the model together	115
Markov::GUI::Generate	QT Generation page class	120
Markov::API::MarkovPasswords	Markov::Model with char represented nodes	124
Markov::GUI::MarkovPasswordsGUI	Reporting UI	141
Markov::Random::Marsaglia	Implementation of Marsaglia Random Engine	144
Markov::API::CUDA::Random::Marsaglia	Extension of Markov::Random::Marsaglia which is capable o working on device space	150
Markov::GUI::menu	QT Menu class	160
Markov::Random::Mersenne	Implementation of Mersenne Twister Engine	162
Markov::Model< NodeStorageType >	Class for the final Markov Model, constructed from nodes and edges	167
Markov::API::ModelMatrix	Class to flatten and reduce Markov::Model to a Matrix	175
Markov::Node< storageType >	A node class that for the vertices of model. Connected with eachother using Edge	201
QMainWindow		209
Markov::Random::RandomEngine	An abstract class for Random Engine	209
Markov::API::CLI::Terminal	Pretty colors for Terminal. Windows Only	211
Markov::API::Concurrency::ThreadSharedListHandler	Simple class for managing shared access to file	214
Markov::GUI::Train	QT Training page class	218

CHAPTER7

File Index

7.1 File List

Here is a list of all files with brief descriptions:

about.cpp	About page	223
about.h	About page	223
argparse.cpp	Arguement handler class for native CPP cli	225
argparse.h	Arguement handler class for native CPP cli	226
CLI.cpp	CLI page	231
CLI.h	CLI page	232
cudaDeviceController.cu	Simple static class for basic CUDA device controls	233
cudaDeviceController.h	Simple static class for basic CUDA device controls	235
cudaModelMatrix.cu	CUDA accelerated extension of Markov::API::ModelMatrix	238
cudaModelMatrix.h	CUDA accelerated extension of Markov::API::ModelMatrix	242
cudarandom.h	Extension of Markov::Random::Marsaglia for CUDA	246
dllmain.cpp	DLLMain for dynamic windows library	248
edge.h	Edge class template	250
framework.h	For windows dynamic library	253
Generate.cpp	Generation Page	254
Generate.h	Generation Page	256
MarkovAPICLI/src/main.cpp	Test cases for Markov::API::ModelMatrix	258
MarkovPasswordsGUI/src/main.cpp	Entry point for GUI	260
main.cu	Simple test file to check libcudamarkov	262
markopy.cpp	CPython wrapper for libmarkov utils	263
markopy.py		266
markovPasswords.cpp	Wrapper for Markov::Model to use with char represented models	268
markovPasswords.h	Wrapper for Markov::Model to use with char represented models	272
MarkovPasswordsGUI.cpp	Main activity page for GUI	275

MarkovPasswordsGUI.h	
Main activity page for GUI	276
menu.cpp	
Menu page	278
menu.h	
Menu page	279
model.h	
Model class template	280
model_2gram.py	286
modelMatrix.cpp	
An extension of Markov::API::MarkovPasswords	286
modelMatrix.h	
An extension of Markov::API::MarkovPasswords	290
node.h	
Node class template	294
MarkovModel/src/pch.cpp	
For windows dynamic library	299
UnitTests/pch.cpp	
For windows dynamic library	299
MarkovModel/src/pch.h	
For windows dynamic library	300
UnitTests/pch.h	
For windows dynamic library	301
random-model.py	302
random.h	
Random engine implementations for Markov	303
term.cpp	
Terminal handler for pretty stuff like colors	307
term.h	
Terminal handler for pretty stuff like colors	309
threadSharedListHandler.cpp	
Thread-safe wrapper for std::ifstream	312
threadSharedListHandler.h	
Thread-safe wrapper for std::ifstream	313
Train.cpp	
Training page for GUI	316
Train.h	
Training page for GUI	317
UnitTests.cpp	
Unit tests with Microsoft::VisualStudio::CppUnitTestFramework	319

CHAPTER8

Namespace Documentation

8.1 markopy Namespace Reference

Functions

- def `cli_init` (str input_model)
- def `cli_train` (markopy.ModelMatrix model, str dataset, str seperator, str output, bool output_forced=False, bool bulk=False)
- def `cli_generate` (markopy.ModelMatrix model, str wordlist, bool bulk=False)

Variables

- `parser`
- `help`
- `default`
- `action`
- `args = parser.parse_args()`

8.1.1 Detailed Description

```
@package markopy
@file markopy.py
@namespace Python::Markopy
@brief Command line
@authors Ata Hakçıl
```

8.1.2 Function Documentation

8.1.2.1 `cli_generate()`

```
def markopy.cli_generate (
    markopy.ModelMatrix model,
    str wordlist,
    bool bulk = False )

Generate strings from the model
@param model: model instance
@param wordlist: wordlist filename
@param bulk: marks bulk operation with directories
```

Definition at line 106 of file `markopy.py`.

```
00106 def cli_generate(model : markopy.ModelMatrix, wordlist : str, bulk : bool=False):
00107     """ Generate strings from the model
00108     @param model: model instance
00109     @param wordlist: wordlist filename
00110     @param bulk: marks bulk operation with directories
00111     """
00112     if not (wordlist or args.count):
00113         logging pprint("Generation mode requires -w/--wordlist and -n/--count parameters. Exiting.")
00114         exit(2)
00115
00116     if(bulk and os.path.isfile(wordlist)):
00117         logging pprint(f"{wordlist} exists and will be overwritten.", 1)
00118     model.Generate(int(args.count), wordlist, int(args.min), int(args.max), int(args.threads))
00119
00120 if(args.bulk):
00121     logging pprint(f"\"Bulk mode operation chosen.\", 4)
```


```

00123     if (args.mode.lower() == "train"):
00124         if (os.path.isdir(args.output) and not os.path.isfile(args.output)) and
00125             (os.path.isdir(args.dataset) and not os.path.isfile(args.dataset)):
00126             corpus_list = os.listdir(args.dataset)
00127             for corpus in corpus_list:
00128                 model = cli_init(args.input)
00129                 logging pprint(f"Training {args.input} with {corpus}", 2)
00130                 output_file_name = corpus
00131                 model_extension = ""
00132                 if "." in args.input:
00133                     model_extension = args.input.split(".")[-1]
00134                     cli_train(model, f"{args.dataset}/{corpus}", args.separator,
00135                             f"{args.output}/{corpus}.{model_extension}", output_forced=True, bulk=True)
00136             else:
00137                 logging pprint("In bulk training, output and dataset should be a directory.")
00138                 exit(1)
00139         elif (args.mode.lower() == "generate"):
00140             if (os.path.isdir(args.wordlist) and not os.path.isfile(args.wordlist)) and
00141                 (os.path.isdir(args.input) and not os.path.isfile(args.input)):
00142                 model_list = os.listdir(args.input)
00143                 print(model_list)
00144                 for input in model_list:
00145                     logging pprint(f"Generating from {args.input}/{input} to {args.wordlist}/{input}.txt",
00146                             2)
00147
00148                 model = cli_init(f"{args.input}/{input}")
00149                 model_base = input
00150                 if "." in args.input:
00151                     model_base = input.split(".")[1]
00152                     cli_generate(model, f"{args.wordlist}/{model_base}.txt", bulk=True)
00153             else:
00154                 logging pprint("In bulk generation, input and wordlist should be directory.")
00155         else:
00156             model = cli_init(args.input)
00157             if (args.mode.lower() == "generate"):
00158                 cli_generate(model, args.wordlist)
00159
00160             elif (args.mode.lower() == "train"):
00161                 cli_train(model, args.dataset, args.separator, args.output, output_forced=True)
00162
00163             elif (args.mode.lower() == "combine"):
00164                 cli_train(model, args.dataset, args.separator, args.output)
00165                 cli_generate(model, args.wordlist)
00166
00167             else:
00168                 logging pprint("Invalid mode argument given.")
00169                 logging pprint("Accepted modes: 'Generate', 'Train', 'Combine'")
00170                 exit(5)

```

References [cli_init\(\)](#), and [cli_train\(\)](#).

Here is the call graph for this function:



8.1.2.2 cli_init()

```

def markopy.cli_init (
    str input_model )

```

```
Initialize the model for CLI interation
@param input_model Model filename
```

Definition at line 45 of file [markopy.py](#).

```
00045 def cli_init(input_model : str):
00046     """ Initialize the model for CLI interation
00047     @param input_model Model filename
00048     """
00049     logging.VERBOSITY = 0
00050     if args.verbosity:
00051         logging.VERBOSITY = args.verbosity
00052         logging pprint(f"Verbosity set to {args.verbosity}.", 2)
00053
00054     logging pprint("Initializing model.", 1)
00055     model = markopy.ModelMatrix()
00056     logging pprint("Model initialized.", 2)
00057
00058     logging pprint("Importing model file.", 1)
00059
00060     if(not os.path.isfile(input_model)):
00061         logging pprint(f"Model file at {input_model} not found. Check the file path, or working
00062         directory")
00063         exit(1)
00064
00065     model.Import(input_model)
00066     logging pprint("Model imported successfully.", 2)
00067
00068 return model
```

Referenced by [cli_generate\(\)](#).

Here is the caller graph for this function:



8.1.2.3 cli_train()

```
def markopy.cli_train (
    markopy.ModelMatrix model,
    str dataset,
    str seperator,
    str output,
    bool output_forced = False,
    bool bulk = False )

Train a model via CLI parameters
@param model Model instance
@param dataset filename for the dataset
@param seperator separator used with the dataset
@param output output filename
@param output_forced force overwrite
@param bulk marks bulk operation with directories
```

Definition at line 68 of file [markopy.py](#).

```
00068 def cli_train(model : markopy.ModelMatrix, dataset : str, seperator : str, output : str, output_forced
    : bool=False, bulk : bool=False):
00069     """ Train a model via CLI parameters
00070     @param model Model instance
00071     @param dataset filename for the dataset
00072     @param seperator separator used with the dataset
00073     @param output output filename
00074     @param output_forced force overwrite
00075     @param bulk marks bulk operation with directories
00076     """
```

```

00077     if not (dataset and separator and (output or not output_forced)):
00078         logging pprint(f"Training mode requires -d/--dataset{', -o/--output' if output_forced else''}
00079         and -s/--separator parameters. Exiting.")
00080         exit(2)
00081
00082     if(not bulk and not os.path.isfile(dataset)):
00083         logging pprint(f"{dataset} doesn't exists. Check the file path, or working directory")
00084         exit(3)
00085
00086     if(output and os.path.isfile(output)):
00087         logging pprint(f"{output} exists and will be overwritten.", 1 )
00088
00089     if(seperator == '\\t'):
00090         logging pprint("Escaping seperator.", 3)
00091         seperator = '\t'
00092
00093     if(len(seperator)!=1):
00094         logging pprint(f'Delimiter must be a single character, and "{seperator}" is not accepted.')
00095         exit(4)
00096
00097     logging pprint(f'Starting training.', 3)
00098     model.Train(dataset,seperator, int(args.threads))
00099     logging pprint(f'Training completed.', 2)
00100
00101     if(output):
00102         logging pprint(f'Exporting model to {output}', 2)
00103         model.Export(output)
00104     else:
00105         logging pprint(f'Model will not be exported.', 1)

```

Referenced by [cli_generate\(\)](#).

Here is the caller graph for this function:



8.1.3 Variable Documentation

8.1.3.1 action

`markopy.action`

Definition at line 38 of file [markopy.py](#).

8.1.3.2 args

`markopy.args = parser.parse_args()`

Definition at line 40 of file [markopy.py](#).

8.1.3.3 default

`markopy.default`

Definition at line 34 of file [markopy.py](#).

8.1.3.4 help

`markopy.help`

Definition at line 28 of file [markopy.py](#).

8.1.3.5 parser

```
markopy.parser
Initial value:
00001 = argparse.ArgumentParser(description="Python wrapper for MarkovPasswords.",
00002 epilog=f, formatter_class=argparse.RawTextHelpFormatter)
Definition at line 14 of file markopy.py.
```

8.2 Markov Namespace Reference

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

Namespaces

- [API](#)
Namespace for the [MarkovPasswords API](#).
- [GUI](#)
namespace for [MarkovPasswords API GUI](#) wrapper
- [Markopy](#)
- [Random](#)
Objects related to RNG.

Classes

- class [Edge](#)
[Edge](#) class used to link nodes in the model together.
- class [Model](#)
class for the final [Markov Model](#), constructed from nodes and edges.
- class [Node](#)
A node class that for the vertices of model. Connected with eachother using [Edge](#).

8.2.1 Detailed Description

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

8.3 Markov::API Namespace Reference

Namespace for the [MarkovPasswords API](#).

Namespaces

- [CLI](#)
Structure to hold parsed cli arguements.
- [Concurrency](#)
Namespace for [Concurrency](#) related classes.
- [CUDA](#)
Namespace for objects requiring [CUDA](#) libraries.

Classes

- class [MarkovPasswords](#)
[Markov::Model](#) with char represented nodes.
- class [ModelMatrix](#)
Class to flatten and reduce [Markov::Model](#) to a Matrix.

8.3.1 Detailed Description

Namespace for the [MarkovPasswords API](#).

8.4 Markov::API::CLI Namespace Reference

Structure to hold parsed cli arguements.

Classes

- struct [_programOptions](#)
Structure to hold parsed cli arguements.
- class [Argparse](#)
Parse command line arguements.
- class [Terminal](#)
pretty colors for [Terminal](#). Windows Only.

Typedefs

- typedef struct [Markov::API::CLI::_programOptions](#) [ProgramOptions](#)
Structure to hold parsed cli arguements.

Functions

- std::ostream & [operator<<](#) (std::ostream &os, const [Markov::API::CLI::Terminal::color](#) &c)

8.4.1 Detailed Description

Structure to hold parsed cli arguements.

Namespace for the [CLI](#) objects

8.4.2 Typedef Documentation

8.4.2.1 ProgramOptions

```
typedef struct Markov::API::CLI::\_programOptions Markov::API::CLI::ProgramOptions
Structure to hold parsed cli arguements.
```

8.4.3 Function Documentation

8.4.3.1 operator<<()

```
std::ostream& Markov::API::CLI::operator<< (
    std::ostream & os,
    const Markov::API::CLI::Terminal::color & c )
overload for std::cout.  

Definition at line 66 of file term.cpp.
00066
00067     char buf[6];
00068     sprintf(buf, "%d", Terminal::colormap.find(c)->second);
00069     os << "\e[1;" << buf << "m";
00070     return os;
00071 }
```

References [Markov::API::CLI::Terminal::colormap](#).

8.5 Markov::API::Concurrency Namespace Reference

Namespace for [Concurrency](#) related classes.

Classes

- class [ThreadSharedListHandler](#)
Simple class for managing shared access to file.

8.5.1 Detailed Description

Namespace for [Concurrency](#) related classes.

8.6 Markov::API::CUDA Namespace Reference

Namespace for objects requiring [CUDA](#) libraries.

Namespaces

- [Random](#)
Namespace for [Random](#) engines operable under [device](#) space.

Classes

- class [CUDADeviceController](#)
Controller class for [CUDA](#) device.
- class [CUDAModelMatrix](#)
Extension of [Markov::API::ModelMatrix](#) which is modified to run on GPU devices.

Functions

- `__global__ void FastRandomWalkCUDAKernel (unsigned long int n, int minLen, int maxLen, char *outputBuffer, char *matrixIndex, long int *totalEdgeWeights, long int *valueMatrix, char *edgeMatrix, int matrixSize, int memoryPerKernelGrid, unsigned long *seed)`
CUDA kernel for the FastRandomWalk operation.
- `__device__ char * strchr (char *p, char c, int s_len)`
strchr implementation on [device](#) space

8.6.1 Detailed Description

Namespace for objects requiring [CUDA](#) libraries.

8.6.2 Function Documentation

8.6.2.1 FastRandomWalkCUDAKernel()

```
__global__ void Markov::API::CUDA::FastRandomWalkCUDAKernel (
    unsigned long int n,
    int minLen,
    int maxLen,
    char * outputBuffer,
    char * matrixIndex,
    long int * totalEdgeWeights,
    long int * valueMatrix,
```

```

    char * edgeMatrix,
    int matrixSize,
    int memoryPerKernelGrid,
    unsigned long * seed )

```

CUDA kernel for the FastRandomWalk operation.

Will be initiated by CPU and continued by GPU (**global** tag)

Parameters

<i>n</i>	- Number of passwords to generate.
<i>minlen</i>	- minimum string length for a single generation
<i>maxLen</i>	- maximum string length for a single generation
<i>outputBuffer</i>	- VRAM ptr to the output buffer
<i>matrixIndex</i>	- VRAM ptr to the matrix indices
<i>totalEdgeWeights</i>	- VRAM ptr to the totalEdgeWeights array
<i>valueMatrix</i>	- VRAM ptr to the edge weights array
<i>edgeMatrix</i>	- VRAM ptr to the edge representations array
<i>matrixSize</i>	- Size of the matrix dimensions
<i>memoryPerKernelGrid</i>	- Maximum memory usage per kernel grid
<i>seed</i>	- seed chunk to generate the random from (generated & used by Marsaglia)

Definition at line 194 of file [cudaModelMatrix.cu](#).

```

00195
00196
00197     int kernelWorkerIndex = threadIdx.x + blockIdx.x * blockDim.x;
00198
00199     if(n==0) return;
00200
00201     char* e;
00202     int index = 0;
00203     char next;
00204     int len=0;
00205     long int selection;
00206     char cur;
00207     long int bufferctr = 0;
00208     unsigned long int *x,*y,*z,t;
00209     char* res = &outputBuffer[kernelWorkerIndex*memoryPerKernelGrid];
00210     x=&seed[kernelWorkerIndex*3];
00211     y=&seed[kernelWorkerIndex*3+1];
00212     z=&seed[kernelWorkerIndex*3+2];
00213     for (int i = 0; i < n; i++) {
00214         cur=199;
00215         len=0;
00216         while (true) {
00217             e = strchr(matrixIndex, cur, matrixSize);
00218             index = e - matrixIndex;
00219             /*selection = Markov::API::CUDA::Random::devrandom(
00220                 seed[kernelWorkerIndex*3],
00221                 seed[kernelWorkerIndex*3+1],
00222                 seed[kernelWorkerIndex*3+2]) % totalEdgeWeights[index];*/
00223             *x ^= *x << 16;
00224             *x ^= *x >> 5;
00225             *x ^= *x << 1;
00226
00227             t = *x;
00228             *x = *y;
00229             *y = *z;
00230             *z = t ^ *x ^ *y;
00231             selection = *z % totalEdgeWeights[index];
00232             for(int j=0;j<matrixSize-1;j++){
00233                 selection -= valueMatrix[index*matrixSize + j];
00234                 if (selection < 0){
00235                     next = edgeMatrix[index*sizeof(char)*matrixSize + j];
00236                     break;
00237                 }
00238             }
00239             if (len >= maxLen) break;
00240             else if ((next < 0) && (len < minLen)) continue;
00241             else if (next < 0) break;
00242             cur = next;
00243             res[bufferctr + len++] = cur;

```

```

00245         }
00246         res[bufferctr + len++] = '\n';
00247         bufferctr+=len;
00248     }
00249     res[bufferctr] = '\0';
00250 }
```

8.6.2.2 strchr()

```
__device__ char * Markov::API::CUDA::strchr (
    char * p,
    char c,
    int s_len )
```

srtchr implementation on **device** space
Find the first matching index of a string

Parameters

<i>p</i>	- string to check
<i>c</i>	- character to match
<i>s_len</i>	- maximum string length

Returns

pointer to the match

Definition at line 252 of file [cudaModelMatrix.cu](#).

```

00252
00253     for ( ; ; ++p, s_len--) {
00254         if (*p == c)
00255             return ((char *)p);
00256         if (!*p)
00257             return ((char *)NULL);
00258     }
00259 }
```

8.7 Markov::API::CUDA::Random Namespace Reference

Namespace for [Random](#) engines operable under **device** space.

Classes

- class [Marsaglia](#)

*Extension of [Markov::Random::Marsaglia](#) which is capable o working on **device** space.*

Functions

- `__device__ unsigned long devrandom (unsigned long &x, unsigned long &y, unsigned long &z)`

*Marsaglia Random Generation function operable in **device** space.*

8.7.1 Detailed Description

Namespace for [Random](#) engines operable under **device** space.

8.7.2 Function Documentation

8.7.2.1 devrandom()

```
__device__ unsigned long Markov::API::CUDA::Random::devrandom (
    unsigned long & x,
    unsigned long & y,
    unsigned long & z)
```

Marsaglia Random Generation function operable in **device** space.

Parameters

x	marsaglia internal x. Not constant, (ref)
y	marsaglia internal y. Not constant, (ref)
z	marsaglia internal z. Not constant, (ref)

Returns

returns z

Definition at line 54 of file [cudarandom.h](#).

```
00054
00055     unsigned long t;
00056     x ^= x << 16;
00057     x ^= x >> 5;
00058     x ^= x << 1;
00059
00060     t = x;
00061     x = y;
00062     y = z;
00063     z = t ^ x ^ y;
00064
00065     return z;
00066 }
```

8.8 Markov::GUI Namespace Reference

namespace for MarkovPasswords [API GUI](#) wrapper

Classes

- class [about](#)
QT Class for about page.
- class [CLI](#)
QT CLI Class.
- class [Generate](#)
QT Generation page class.
- class [MarkovPasswordsGUI](#)
Reporting UI.
- class [menu](#)
QT Menu class.
- class [Train](#)
QT Training page class.

8.8.1 Detailed Description

namespace for MarkovPasswords [API GUI](#) wrapper

8.9 Markov::Markopy Namespace Reference

Functions

- [BOOST_PYTHON_MODULE](#) (markopy)

8.9.1 Function Documentation

8.9.1.1 BOOST_PYTHON_MODULE()

```
Markov::Markopy::BOOST_PYTHON_MODULE (
    markopy )
```

Definition at line 34 of file [markopy.cpp](#).


```
00035 {
00036     bool (Markov::API::MarkovPasswords::*Import) (const char*) = &Markov::Model<char>::Import;
00037     bool (Markov::API::MarkovPasswords::*Export) (const char*) = &Markov::Model<char>::Export;
00038     class_<Markov::API::MarkovPasswords>("MarkovPasswords", init<>())
00039         .def(init<>())
00040         .def("Train", &Markov::API::MarkovPasswords::Train)
00041         .def("Generate", &Markov::API::MarkovPasswords::Generate)
00042         .def("Import", Import, "Import a model file.")
00043         .def("Export", Export, "Export a model to file.")
00044     ;
00045
00046     int (Markov::API::ModelMatrix::*FastRandomWalk) (unsigned long int, const char*, int, int, int,
00047         bool) = &Markov::API::ModelMatrix::FastRandomWalk;
00048     class_<Markov::API::ModelMatrix>("ModelMatrix", init<>())
00049         .def(init<>())
00050         .def("Train", &Markov::API::ModelMatrix::Train)
00051         .def("Import", &Markov::API::ModelMatrix::Import, "Import a model file.")
00052         .def("Export", Export, "Export a model to file.")
00053         .def("ConstructMatrix", &Markov::API::ModelMatrix::ConstructMatrix)
00054         .def("DumpJSON", &Markov::API::ModelMatrix::DumpJSON)
00055         .def("FastRandomWalk", FastRandomWalk)
00056         ;
00057     };
00058 }
```

References [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), [Markov::Model< NodeStorageType >::Import\(\)](#),

[Markov::API::ModelMatrix::FastRandomWalk\(\)](#), [Markov::API::MarkovPasswords::Generate\(\)](#), [Markov::API::ModelMatrix::Import\(\)](#),

[Markov::Model< NodeStorageType >::Import\(\)](#), [Markov::API::MarkovPasswords::Train\(\)](#), and [Markov::API::ModelMatrix::Train\(\)](#).

Here is the call graph for this function:



8.10 Markov::Random Namespace Reference

Objects related to RNG.

Classes

- class [DefaultRandomEngine](#)
Implementation using [Random.h](#) default random engine.
- class [Marsaglia](#)
Implementation of [Marsaglia Random Engine](#).
- class [Mersenne](#)
Implementation of [Mersenne Twister Engine](#).

- class [RandomEngine](#)
An abstract class for Random Engine.

8.10.1 Detailed Description

Objects related to RNG.

8.11 model_2gram Namespace Reference

Variables

- [alphabet](#) = string.printable
password alphabet
- [f](#) = open('../models/2gram.mdl', "wb")
output file handle

8.11.1 Detailed Description

python script for generating a 2gram model

8.11.2 Variable Documentation

8.11.2.1 alphabet

```
model_2gram.alphabet = string.printable
password alphabet
Definition at line 10 of file model\_2gram.py.
```

8.11.2.2 f

```
model_2gram.f = open('../models/2gram.mdl', "wb")
output file handle
Definition at line 16 of file model\_2gram.py.
```

8.12 random Namespace Reference

8.12.1 Detailed Description

-model

python script for generating a 2gram model

8.13 random-model Namespace Reference

Variables

- [alphabet](#) = string.printable
password alphabet
- [f](#) = open('../models/random.mdl', "wb")
output file handle

8.13.1 Variable Documentation

8.13.1.1 alphabet

random-model.alphabet = string.printable

password alphabet

Definition at line 10 of file [random-model.py](#).

8.13.1.2 f

random-model.f = open('.../.../models/random.mdl', "wb")

output file handle

Definition at line 16 of file [random-model.py](#).

8.14 Testing Namespace Reference

Namespace for Microsoft Native Unit [Testing](#) Classes.

Namespaces

- [MarkovModel](#)

Testing namespace for [MarkovModel](#).

- [MarkovPasswords](#)

Testing namespace for [MarkovPasswords](#).

- [MVP](#)

Testing Namespace for Minimal Viable Product.

8.14.1 Detailed Description

Namespace for Microsoft Native Unit [Testing](#) Classes.

8.15 Testing::MarkovModel Namespace Reference

[Testing](#) namespace for [MarkovModel](#).

Functions

- [TEST_CLASS](#) (Edge)

Test class for rest of Edge cases.

- [TEST_CLASS](#) (Node)

Test class for rest of Node cases.

- [TEST_CLASS](#) (Model)

Test class for rest of model cases.

8.15.1 Detailed Description

[Testing](#) namespace for [MarkovModel](#).

8.15.2 Function Documentation

8.15.2.1 TEST_CLASS() [1/3]

```
Testing::MarkovModel::TEST_CLASS (
    Edge )
```

Test class for rest of Edge cases.

send exception on integer underflow

test integer overflows


Definition at line 500 of file [UnitTests.cpp](#).

```
00501     {
00502         public:
00503             TEST_METHOD(except_integer_underflow) {
00504                 auto _underflow_adjust = [] {
00505                     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00506                     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00507                     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00508                         RightNode);
00509                         e->AdjustEdge(15);
00510                         e->AdjustEdge(-30);
00511                         delete LeftNode;
00512                         delete RightNode;
00513                         delete e;
00514                     };
00515                 Assert::ExpectException<std::underflow_error>(_underflow_adjust);
00516             }
00517         }
00518     }
00519     TEST_METHOD(except_integer_overflow) {
00520         auto _overflow_adjust = [] {
00521             Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00522             Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00523             Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00524                 RightNode);
00525                         e->AdjustEdge(~0ull);
00526                         e->AdjustEdge(1);
00527                         delete LeftNode;
00528                         delete RightNode;
00529                         delete e;
00530                     };
00531                 Assert::ExpectException<std::underflow_error>(_overflow_adjust);
00532             }
00533         }
00534     };

```

References [TEST_CLASS\(\)](#).

Here is the call graph for this function:



8.15.2.2 TEST_CLASS() [2/3]

```
Testing::MarkovModel::TEST_CLASS (
    Model )
```

Test class for rest of model cases.

Definition at line 598 of file [UnitTests.cpp](#).

```
00599     {
00600         public:
00601             TEST_METHOD(functional_random_walk) {
00602                 unsigned char* res2 = new unsigned char[12 + 5];
00603                 Markov::Random::Marsaglia MarsagliaRandomEngine;
00604                 Markov::Model<unsigned char> m;
00605                 Markov::Node<unsigned char>* starter = m.StarterNode();
00606                 Markov::Node<unsigned char>* a = new Markov::Node<unsigned char>('a');
00607                 Markov::Node<unsigned char>* b = new Markov::Node<unsigned char>('b');
00608                 Markov::Node<unsigned char>* c = new Markov::Node<unsigned char>('c');
00609                 Markov::Node<unsigned char>* end = new Markov::Node<unsigned char>(0xff);
```

```

00610     starter->Link(a)->AdjustEdge(1);
00611     a->Link(b)->AdjustEdge(1);
00612     b->Link(c)->AdjustEdge(1);
00613     c->Link(end)->AdjustEdge(1);
00614
00615     char* res = (char*)m.RandomWalk(&MarsagliaRandomEngine,1,12,res2);
00616     Assert::IsFalse(strcmp(res, "abc"));
00617 }
00618 TEST_METHOD(functional_random_walk_without_any) {
00619     Markov::Model<unsigned char> m;
00620     Markov::Node<unsigned char>* starter = m.StarterNode();
00621     Markov::Node<unsigned char>* a = new Markov::Node<unsigned char>('a');
00622     Markov::Node<unsigned char>* b = new Markov::Node<unsigned char>('b');
00623     Markov::Node<unsigned char>* c = new Markov::Node<unsigned char>('c');
00624     Markov::Node<unsigned char>* end = new Markov::Node<unsigned char>(0xff);
00625     Markov::Edge<unsigned char>* res = NULL;
00626     starter->Link(a)->AdjustEdge(1);
00627     a->Link(b)->AdjustEdge(1);
00628     b->Link(c)->AdjustEdge(1);
00629     c->Link(end)->AdjustEdge(1);
00630
00631     res = starter->FindEdge('D');
00632     Assert::IsNull(res);
00633 }
00634 };
00635 
```


References [TEST_CLASS\(\)](#).

Referenced by [TEST_CLASS\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.15.2.3 TEST_CLASS() [3/3]

```
Testing::MarkovModel::TEST_CLASS (
    Node )
```

Test class for rest of Node cases.

test RandomNext with 64 bit high values

test RandomNext with 64 bit high values

randomNext when no edges are present

Definition at line 538 of file [UnitTests.cpp](#).


```
00539 {
```

```

00540     public:
00541
00542     TEST_METHOD(rand_next_u64) {
00543         Markov::Random::Marsaglia MarsagliaRandomEngine;
00544         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00545         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00546         Markov::Edge<unsigned char>* e = src->Link(target1);
00547         e->AdjustEdge((unsigned long)(lull << 63));
00548         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00549         Assert::IsTrue(res == target1);
00550         delete src;
00551         delete target1;
00552         delete e;
00553
00554     }
00555
00556
00557     TEST_METHOD(rand_next_u64_max) {
00558         Markov::Random::Marsaglia MarsagliaRandomEngine;
00559         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00560         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00561         Markov::Edge<unsigned char>* e = src->Link(target1);
00562         e->AdjustEdge((0xffffffff));
00563         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00564         Assert::IsTrue(res == target1);
00565         delete src;
00566         delete target1;
00567         delete e;
00568
00569     }
00570
00571     TEST_METHOD(uninitialized_rand_next) {
00572
00573         auto _invalid_next = [] {
00574             Markov::Random::Marsaglia MarsagliaRandomEngine;
00575             Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00576             Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00577             Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(src, target1);
00578             Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00579
00580             delete src;
00581             delete target1;
00582             delete e;
00583         };
00584
00585         Assert::ExpectException<std::logic_error>(_invalid_next);
00586     }
00587
00588 }
00589
00590 }
```

References [TEST_CLASS\(\)](#).

Here is the call graph for this function:



8.16 Testing::MarkovPasswords Namespace Reference

Testing namespace for [MarkovPasswords](#).

8.16.1 Detailed Description

Testing namespace for [MarkovPasswords](#).

8.17 Testing::MVP Namespace Reference

[Testing](#) Namespace for Minimal Viable Product.

Namespaces

- [MarkovModel](#)
Testing Namespace for [MVP MarkovModel](#).
- [MarkovPasswords](#)
Testing namespace for [MVP MarkovPasswords](#).

8.17.1 Detailed Description

[Testing](#) Namespace for Minimal Viable Product.

8.18 Testing::MVP::MarkovModel Namespace Reference

[Testing](#) Namespace for [MVP MarkovModel](#).

Functions

- [TEST_CLASS](#) ([Edge](#))
Test class for minimal viable Edge.
- [TEST_CLASS](#) ([Node](#))
Test class for minimal viable Node.
- [TEST_CLASS](#) ([Model](#))
Test class for minimal viable Model.

8.18.1 Detailed Description

[Testing](#) Namespace for [MVP MarkovModel](#).

8.18.2 Function Documentation

8.18.2.1 TEST_CLASS() [1/3]

```
Testing::MVP::MarkovModel::TEST_CLASS (
    Edge )
```

Test class for minimal viable Edge.

test default constructor

test linked constructor with two nodes

test AdjustEdge function

test TraverseNode returning RightNode

test LeftNode/RightNode setter

test negative adjustments

Definition at line 27 of file [UnitTests.cpp](#).

```
00028     {
00029         public:
00030
00033             TEST_METHOD(default_constructor) {
00034                 Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>;
00035                 Assert::IsNull(e->LeftNode());
00036                 Assert::IsNull(e->RightNode());
00037                 delete e;
00038             }
00039
00042             TEST_METHOD(linked_constructor) {
00043                 Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00044                 Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
```


```

00045     RightNode);
00046     Assert::IsTrue(LeftNode == e->LeftNode());
00047     Assert::IsTrue(RightNode == e->RightNode());
00048     delete LeftNode;
00049     delete RightNode;
00050     delete e;
00051 }
00052
00053 TEST_METHOD(AdjustEdge) {
00054     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00055     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00056     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00057     RightNode);
00058     e->AdjustEdge(15);
00059     Assert::AreEqual(15ull, e->EdgeWeight());
00060     e->AdjustEdge(15);
00061     Assert::AreEqual(30ull, e->EdgeWeight());
00062     delete LeftNode;
00063     delete RightNode;
00064     delete e;
00065 }
00066
00067 TEST_METHOD(TraverseNode) {
00068     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00069     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00070     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00071     RightNode);
00072     Assert::IsTrue(RightNode == e->TraverseNode());
00073     delete LeftNode;
00074     delete RightNode;
00075     delete e;
00076 }
00077
00078 TEST_METHOD(set_left_and_right) {
00079     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00080     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00081     Markov::Edge<unsigned char>* el = new Markov::Edge<unsigned char>(LeftNode,
00082     RightNode);
00083
00084     Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>;
00085     e2->SetLeftEdge(LeftNode);
00086     e2->SetRightEdge(RightNode);
00087
00088     Assert::IsTrue(el->LeftNode() == e2->LeftNode());
00089     Assert::IsTrue(el->RightNode() == e2->RightNode());
00090     delete LeftNode;
00091     delete RightNode;
00092     delete el;
00093     delete e2;
00094 }
00095
00096 TEST_METHOD(negative_adjust) {
00097     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00098     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00099     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00100     RightNode);
00101     e->AdjustEdge(15);
00102     Assert::AreEqual(15ull, e->EdgeWeight());
00103     e->AdjustEdge(-15);
00104     Assert::AreEqual(0ull, e->EdgeWeight());
00105     delete LeftNode;
00106     delete RightNode;
00107     delete e;
00108 }
00109
00110
00111
00112 }
00113

```

References [TEST_CLASS\(\)](#).

Here is the call graph for this function:



8.18.2.2 TEST_CLASS() [2/3]

```
Testing::MVP::MarkovModel::TEST_CLASS (
    Model )
```

Test class for minimal viable Model.

test model constructor for starter node

test import

test export

test random walk


Definition at line 353 of file [UnitTests.cpp](#).

```
00354     {
00355         public:
00356             TEST_METHOD(model_constructor) {
00357                 Markov::Model<unsigned char> m;
00358                 Assert::AreEqual((unsigned char)'\\0', m.StarterNode()->nodeValue());
00359             }
00360
00361             TEST_METHOD(import_filename) {
00362                 Markov::Model<unsigned char> m;
00363                 Assert::IsTrue(m.Import("../MarkovPasswords/Models/2gram.mdl"));
00364             }
00365
00366             TEST_METHOD(export_filename) {
00367                 Markov::Model<unsigned char> m;
00368                 Assert::IsTrue(m.Export("../MarkovPasswords/Models/testcase.mdl"));
00369             }
00370
00371             TEST_METHOD(random_walk) {
00372                 unsigned char* res = new unsigned char[12 + 5];
00373                 Markov::Random::Marsaglia MarsagliaRandomEngine;
00374                 Markov::Model<unsigned char> m;
00375                 Assert::IsTrue(m.Import("../Models/finished2.mdl"));
00376                 Assert::IsNotNull(m.RandomWalk(&MarsagliaRandomEngine, 1, 12, res));
00377             }
00378     };
```


References [TEST_CLASS\(\)](#).

Referenced by [TEST_CLASS\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



8.18.2.3 TEST_CLASS() [3/3]

```
Testing::MVP::MarkovModel::TEST_CLASS (
```

```

    Node  )
Test class for minimal viable Node.
test default constructor
test custom constructor with unsigned char
test link function
test link function
test RandomNext with low values
test RandomNext with 32 bit high values
random next on a node with no follow-ups
random next on a node with no follow-ups
test updateEdges
test updateEdges
test FindVertice
test FindVertice
test FindVertice

```

Definition at line 117 of file [UnitTests.cpp](#).

```

00118     {
00119         public:
00120
00123             TEST_METHOD(default_constructor) {
00124                 Markov::Node<unsigned char>* n = new Markov::Node<unsigned char>();
00125                 Assert::AreEqual((unsigned char)0, n->NodeValue());
00126                 delete n;
00127             }
00128
00131             TEST_METHOD(uchar_constructor) {
00132                 Markov::Node<unsigned char>* n = NULL;
00133                 unsigned char test_cases[] = { 'c', 0x00, 0xff, -32 };
00134                 for (unsigned char tcase : test_cases) {
00135                     n = new Markov::Node<unsigned char>(tcase);
00136                     Assert::AreEqual(tcase, n->NodeValue());
00137                     delete n;
00138                 }
00139             }
00140
00143             TEST_METHOD(link_left) {
00144                 Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00145                 Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00146
00147                 Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
00148                 delete LeftNode;
00149                 delete RightNode;
00150                 delete e;
00151             }
00152
00155             TEST_METHOD(link_right) {
00156                 Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00157                 Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00158
00159                 Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(NULL, RightNode);
00160                 LeftNode->Link(e);
00161                 Assert::IsTrue(LeftNode == e->LeftNode());
00162                 Assert::IsTrue(RightNode == e->RightNode());
00163                 delete LeftNode;
00164                 delete RightNode;
00165                 delete e;
00166             }
00167
00170             TEST_METHOD(rand_next_low) {
00171                 Markov::Random::Marsaglia MarsagliaRandomEngine;
00172                 Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00173                 Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00174                 Markov::Edge<unsigned char>* e = src->Link(target1);
00175                 e->AdjustEdge(15);
00176                 Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00177                 Assert::IsTrue(res == target1);
00178                 delete src;
00179                 delete target1;
00180                 delete e;
00181             }
00182
00183             TEST_METHOD(rand_next_u32) {
00184                 Markov::Random::Marsaglia MarsagliaRandomEngine;
00185                 Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00186                 Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00187                 Markov::Edge<unsigned char>* e = src->Link(target1);
00188                 e->AdjustEdge(1 << 31);
00189                 Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00190                 Assert::IsTrue(res == target1);
00191
00192
00193

```

```

00194         delete src;
00195         delete target1;
00196         delete e;
00197     }
00198
00199
00200     TEST_METHOD(rand_next_choice_1) {
00201         Markov::Random::Marsaglia MarsagliaRandomEngine;
00202         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00203         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00204         Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00205         Markov::Edge<unsigned char>* el = src->Link(target1);
00206         Markov::Edge<unsigned char>* e2 = src->Link(target2);
00207         el->AdjustEdge(1);
00208         e2->AdjustEdge((unsigned long)(ull << 31));
00209         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00210         Assert::IsNotNull(res);
00211         Assert::IsTrue(res == target2);
00212         delete src;
00213         delete target1;
00214         delete el;
00215         delete e2;
00216     }
00217
00218
00219
00220     TEST_METHOD(rand_next_choice_2) {
00221         Markov::Random::Marsaglia MarsagliaRandomEngine;
00222         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00223         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00224         Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00225         Markov::Edge<unsigned char>* el = src->Link(target1);
00226         Markov::Edge<unsigned char>* e2 = src->Link(target2);
00227         el->AdjustEdge(1);
00228         e2->AdjustEdge((unsigned long)(ull << 31));
00229         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00230         Assert::IsNotNull(res);
00231         Assert::IsTrue(res == target1);
00232         delete src;
00233         delete target1;
00234         delete e1;
00235         delete e2;
00236     }
00237
00238
00239
00240
00241     TEST_METHOD(update_edges_count) {
00242
00243         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00244         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00245         Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00246         Markov::Edge<unsigned char>* el = new Markov::Edge<unsigned char>(src, target1);
00247         Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target2);
00248         el->AdjustEdge(25);
00249         src->UpdateEdges(el);
00250         e2->AdjustEdge(30);
00251         src->UpdateEdges(e2);
00252
00253         Assert::AreEqual((size_t)2, src->Edges()->size());
00254
00255
00256         delete src;
00257         delete target1;
00258         delete e1;
00259         delete e2;
00260     }
00261
00262
00263
00264     TEST_METHOD(update_edges_total) {
00265
00266         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00267         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00268         Markov::Edge<unsigned char>* el = new Markov::Edge<unsigned char>(src, target1);
00269         Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target1);
00270         el->AdjustEdge(25);
00271         src->UpdateEdges(el);
00272         e2->AdjustEdge(30);
00273         src->UpdateEdges(e2);
00274
00275         //Assert::AreEqual(55ull, src->TotalEdgeWeights());
00276
00277
00278         delete src;
00279         delete target1;
00280         delete e1;
00281         delete e2;
00282     }
00283
00284
00285
00286     TEST_METHOD(find_vertice) {
00287
00288         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00289

```

```


00291     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00292     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00293     Markov::Edge<unsigned char>* res = NULL;
00294     src->Link(target1);
00295     src->Link(target2);

00296
00297     res = src->FindEdge('b');
00298     Assert::IsNotNull(res);
00299     Assert::AreEqual((unsigned char)'b', res->TraverseNode()->nodeValue());
00300     res = src->FindEdge('c');
00301     Assert::IsNotNull(res);
00302     Assert::AreEqual((unsigned char)'c', res->TraverseNode()->nodeValue());
00303
00304     delete src;
00305     delete target1;
00306     delete target2;
00307
00308
00309
00310 }
00311
00312
00313
00314 TEST_METHOD(find_vertice_without_any) {
00315
00316     auto _invalid_next = [] {
00317         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00318         Markov::Edge<unsigned char>* res = NULL;
00319
00320         res = src->FindEdge('b');
00321         Assert::IsNull(res);
00322
00323         delete src;
00324     };
00325
00326     //Assert::ExpectException<std::logic_error>(_invalid_next);
00327 }
00328
00329
00330 TEST_METHOD(find_vertice_nonexistent) {
00331
00332     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00333     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00334     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00335     Markov::Edge<unsigned char>* res = NULL;
00336     src->Link(target1);
00337     src->Link(target2);
00338
00339     res = src->FindEdge('D');
00340     Assert::IsNull(res);
00341
00342     delete src;
00343     delete target1;
00344     delete target2;
00345
00346
00347     }
00348 };
00349

```

References [TEST_CLASS\(\)](#).

Here is the call graph for this function:



8.19 Testing::MVP::MarkovPasswords Namespace Reference

Testing namespace for [MVP MarkovPasswords](#).

Functions

- [TEST_CLASS](#) (ArgParser)

Test Class for Argparse class.

8.19.1 Detailed Description

Testing namespace for [MVP MarkovPasswords](#).

8.19.2 Function Documentation

8.19.2.1 TEST_CLASS()

```
Testing::MVP::MarkovPasswords::TEST_CLASS (
    ArgParser  )
```

Test Class for Argparse class.

test basic generate

test basic generate reordered params

test basic generate param longnames

test basic generate

test basic train

test basic generate

Definition at line 395 of file [UnitTests.cpp](#).


```
00396         {
00397             public:
00400                 TEST_METHOD(generate_basic) {
00401                     int argc = 8;
00402                     char *argv[] = {"markov.exe", "generate", "-if", "model.mdl", "-of",
00403 "passwords.txt", "-n", "100"};
00404                     /*ProgramOptions *p = Argparse::parse(argc, argv);
00405                     Assert::IsNotNull(p);
00406
00407                     Assert::AreEqual(p->bImport, true);
00408                     Assert::AreEqual(p->bExport, false);
00409                     Assert::AreEqual(p->importname, "model.mdl");
00410                     Assert::AreEqual(p->outputfilename, "passwords.txt");
00411                     Assert::AreEqual(p->generateN, 100); */
00412
00413     }
00414
00417     TEST_METHOD(generate_basic_reorder) {
00418         int argc = 8;
00419         char *argv[] = { "markov.exe", "generate", "-n", "100", "-if", "model.mdl", "-of",
00420 "passwords.txt" };
00421         /*ProgramOptions* p = Argparse::parse(argc, argv);
00422         Assert::IsNotNull(p);
00423
00424         Assert::AreEqual(p->bImport, true);
00425         Assert::AreEqual(p->bExport, false);
00426         Assert::AreEqual(p->importname, "model.mdl");
00427         Assert::AreEqual(p->outputfilename, "passwords.txt");
00428         Assert::AreEqual(p->generateN, 100);*/
00429     }
00430
00433     TEST_METHOD(generate_basic_longname) {
00434         int argc = 8;
00435         char *argv[] = { "markov.exe", "generate", "-n", "100", "--inputfilename",
00436 "model.mdl", "--outputfilename", "passwords.txt" };
00437         /*ProgramOptions* p = Argparse::parse(argc, argv);
00438         Assert::IsNotNull(p);
00439
00440         Assert::AreEqual(p->bImport, true);
00441         Assert::AreEqual(p->bExport, false);
00442         Assert::AreEqual(p->importname, "model.mdl");
00443         Assert::AreEqual(p->outputfilename, "passwords.txt");
00444         Assert::AreEqual(p->generateN, 100); */
00445     }
00446
00449     TEST_METHOD(generate_fail_badmethod) {
00450         int argc = 8;
00451         char *argv[] = { "markov.exe", "junk", "-n", "100", "--inputfilename",
00452 "model.mdl", "--outputfilename", "passwords.txt" };
00453         /*ProgramOptions* p = Argparse::parse(argc, argv);
00454         Assert::IsNull(p); */
```

```
00455         }
00456
00457     TEST_METHOD(train_basic) {
00458         int argc = 4;
00459         char *argv[] = { "markov.exe", "train", "-ef", "model.mdl" };
00460
00461         /*ProgramOptions* p = Argparse::parse(argc, argv);
00462         Assert::IsNotNull(p);
00463
00464         Assert::AreEqual(p->bImport, false);
00465         Assert::AreEqual(p->bExport, true);
00466         Assert::AreEqual(p->exportname, "model.mdl"); */
00467
00468     }
00469
00470     TEST_METHOD(train_basic_longname) {
00471         int argc = 4;
00472         char *argv[] = { "markov.exe", "train", "--exportfilename", "model.mdl" };
00473
00474         /*ProgramOptions* p = Argparse::parse(argc, argv);
00475         Assert::IsNotNull(p);
00476
00477         Assert::AreEqual(p->bImport, false);
00478         Assert::AreEqual(p->bExport, true);
00479         Assert::AreEqual(p->exportname, "model.mdl"); */
00480
00481     }
00482
00483     }
00484
00485
00486
00487
00488 };
```


References [TEST_CLASS\(\)](#).

Referenced by [TEST_CLASS\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



CHAPTER9


Class Documentation

9.1 Markov::API::CLI::_programOptions Struct Reference

Structure to hold parsed cli arguments.

```
#include <argparse.h>
```

Collaboration diagram for Markov::API::CLI::_programOptions:



Public Attributes

- `bool bImport`
Import flag to validate import
- `bool bExport`
Export flag to validate export
- `bool bFailure`
Failure flag to validate succesfull running
- `char separator`
Seperator character to use with training data. (character between occurence and value)"
- `std::string importname`

- `std::string exportname`
Import name of our model.
- `std::string wordlistname`
Import name of our given wordlist
- `std::string outputfilename`
Output name of our generated password list
- `std::string datasetname`
The name of the given dataset
- `int generateN`
Number of passwords to be generated

9.1.1 Detailed Description

Structure to hold parsed cli arguements.

Definition at line 26 of file [argparse.h](#).

9.1.2 Member Data Documentation

9.1.2.1 bExport

`bool Markov::API::CLI::_programOptions::bExport`
 Export flag to validate export

Definition at line 35 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

9.1.2.2 bFailure

`bool Markov::API::CLI::_programOptions::bFailure`
 Failure flag to validate succesfull running

Definition at line 40 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

9.1.2.3 bImport

`bool Markov::API::CLI::_programOptions::bImport`
 Import flag to validate import

Definition at line 30 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

9.1.2.4 datasetname

`std::string Markov::API::CLI::_programOptions::datasetname`
 The name of the given dataset

Definition at line 70 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

9.1.2.5 exportname

`std::string Markov::API::CLI::_programOptions::exportname`

Import name of our given wordlist

Definition at line 55 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

9.1.2.6 generateN

`int Markov::API::CLI::_programOptions::generateN`

Number of passwords to be generated

Definition at line 75 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

9.1.2.7 importname

`std::string Markov::API::CLI::_programOptions::importname`

Import name of our model.

Definition at line 50 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

9.1.2.8 outputfilename

`std::string Markov::API::CLI::_programOptions::outputfilename`

Output name of our generated password list

Definition at line 65 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#), and [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

9.1.2.9 seperator

`char Markov::API::CLI::_programOptions::seperator`

Separator character to use with training data. (character between occurrence and value)"

Definition at line 45 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::setProgramOptions\(\)](#).

9.1.2.10 wordlistname

`std::string Markov::API::CLI::_programOptions::wordlistname`

Import name of our given wordlist

Definition at line 60 of file [argparse.h](#).

Referenced by [Markov::API::CLI::Argparse::Argparse\(\)](#).

The documentation for this struct was generated from the following file:


- [argparse.h](#)

9.2 Markov::GUI::about Class Reference


QT Class for about page.

```
#include <about.h>
```

Inheritance diagram for Markov::GUI::about:



Collaboration diagram for Markov::GUI::about:



Public Member Functions

- `about (QWidget *parent=Q_NULLPTR)`

Private Attributes

- [Ui::main ui](#)

9.2.1 Detailed Description

QT Class for about page.

Definition at line [18](#) of file [about.h](#).

9.2.2 Constructor & Destructor Documentation

9.2.2.1 [about\(\)](#)

```
about::about (
    QWidget * parent = Q_NULLPTR )
Definition at line 14 of file about.cpp.
00015     : QMainWindow(parent)
00016 {
00017     ui.setupUi(this);
00018 }
00019 }
```

References [ui](#).

9.2.3 Member Data Documentation

9.2.3.1 [ui](#)

Ui:: [main](#) Markov::GUI::about::ui [private]

Definition at line [24](#) of file [about.h](#).

Referenced by [about\(\)](#).

The documentation for this class was generated from the following files:


- [about.h](#)
- [about.cpp](#)

9.3 Markov::API::CLI::Argparse Class Reference

Parse command line arguments.

```
#include <argparse.h>
```

Collaboration diagram for Markov::API::CLI::Argparse:



Public Member Functions

- `Argparse ()`
- `Argparse (int argc, char **argv)`

Parse command line arguments.
- `Markov::API::CLI::ProgramOptions getProgramOptions () void`

Getter for command line options.
- `void setProgramOptions (bool i, bool e, bool bf, char s, std::string iName, std::string exName, std::string oName, std::string dName, int n)`

Initialize program options structure.

Static Public Member Functions

- static `Markov::API::CLI::ProgramOptions * parse (int argc, char **argv)`

parse cli commands and return

- static void [help \(\)](#)

Print help string.

Private Attributes

- [Markov::API::CLI::ProgramOptions po](#)

ProgramOptions structure object.

9.3.1 Detailed Description

Parse command line arguments.

Definition at line [82](#) of file [argparse.h](#).

9.3.2 Constructor & Destructor Documentation

9.3.2.1 Argparse() [1/2]

```
Markov::API::CLI::Argparse::Argparse ( )
```

9.3.2.2 Argparse() [2/2]

```
Markov::API::CLI::Argparse::Argparse (
    int argc,
    char ** argv ) [inline]
```

Parse command line arguments.

Parses command line arguments to populate ProgramOptions structure.

Parameters

<code>argc</code>	Number of command line arguments
<code>argv</code>	Array of command line parameters

Definition at line [94](#) of file [argparse.h](#).

```
00094
00095
00096     /*bool bImp;
00097     bool bExp;
00098     bool bFail;
00099     char sprt;
00100     std::string imports;
00101     std::string exports;
00102     std::string outputs;
00103     std::string datasets;
00104     int generateN;
00105     */
00106     opt::options_description desc("Options");
00107
00108     desc.add_options()
00109         ("generate", "Generate strings with given parameters")
00110         ("train", "Train model with given parameters")
00111         ("combine", "Combine")
00112         ("import", opt::value<std::string>(), "Import model file")
00113         ("output", opt::value<std::string>(), "Output model file. This model will be exported
when done. Will be ignored for generation mode")
00114         ("dataset", opt::value<std::string>(), "Dataset file to read input from training. Will
be ignored for generation mode")
00115         ("seperator", opt::value<char>(), "Seperator character to use with training data.
(character between occurrence and value)")
00116         ("wordlist", opt::value<std::string>(), "Wordlist file path to export generation
results to. Will be ignored for training mode")
00117         ("count", opt::value<int>(), "Number of lines to generate. Ignored in training mode")
00118         ("verbosity", "Output verbosity")
00119         ("help", "Option definitions");
00120
00121     opt::variables_map vm;
00122
```


```

00123
00124     opt::store(opt::parse_command_line(argc, argv, desc), vm);
00125
00126     opt::notify(vm);
00127
00128     //std::cout << desc << std::endl;
00129     if (vm.count("help")) {
00130         std::cout << desc << std::endl;
00131     }
00132
00133     if (vm.count("output") == 0) this->po.outputfilename = "NULL";
00134     else if (vm.count("output") == 1) {
00135         this->po.outputfilename = vm["output"].as<std::string>();
00136         this->po.bExport = true;
00137     }
00138     else {
00139         this->po.bFailure = true;
00140         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00141         std::cout << desc << std::endl;
00142     }
00143
00144
00145     if (vm.count("dataset") == 0) this->po.datasetname = "NULL";
00146     else if (vm.count("dataset") == 1) {
00147         this->po.datasetname = vm["dataset"].as<std::string>();
00148     }
00149     else {
00150         this->po.bFailure = true;
00151         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00152         std::cout << desc << std::endl;
00153     }
00154
00155
00156     if (vm.count("wordlist") == 0) this->po.wordlistname = "NULL";
00157     else if (vm.count("wordlist") == 1) {
00158         this->po.wordlistname = vm["wordlist"].as<std::string>();
00159     }
00160     else {
00161         this->po.bFailure = true;
00162         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00163         std::cout << desc << std::endl;
00164     }
00165
00166     if (vm.count("import") == 0) this->po.importname = "NULL";
00167     else if (vm.count("import") == 1) {
00168         this->po.importname = vm["import"].as<std::string>();
00169         this->po.bImport = true;
00170     }
00171     else {
00172         this->po.bFailure = true;
00173         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00174         std::cout << desc << std::endl;
00175     }
00176
00177
00178     if (vm.count("count") == 0) this->po.generateN = 0;
00179     else if (vm.count("count") == 1) {
00180         this->po.generateN = vm["count"].as<int>();
00181     }
00182     else {
00183         this->po.bFailure = true;
00184         std::cout << "UNIDENTIFIED INPUT" << std::endl;
00185         std::cout << desc << std::endl;
00186     }
00187
00188     /*std::cout << vm["output"].as<std::string>() << std::endl;
00189     std::cout << vm["dataset"].as<std::string>() << std::endl;
00190     std::cout << vm["wordlist"].as<std::string>() << std::endl;
00191     std::cout << vm["output"].as<std::string>() << std::endl;
00192     std::cout << vm["count"].as<int>() << std::endl;*/
00193
00194
00195     //else if (vm.count("train")) std::cout << "train oldu" << std::endl;
00196 }
```

References [Markov::API::CLI::_programOptions::bExport](#), [Markov::API::CLI::_programOptions::bFailure](#), [Markov::API::CLI::_programOptions::datasetname](#), [Markov::API::CLI::_programOptions::generateN](#), [Markov::API::CLI::_programOptions::outputfilename](#), [po](#), and [Markov::API::CLI::_programOptions::wordlistname](#).

Referenced by [main\(\)](#).

Here is the caller graph for this function:



9.3.3 Member Function Documentation

9.3.3.1 getProgramOptions()

```
Markov::API::CLI::ProgramOptions Markov::API::CLI::Argparse::getProgramOptions (
    void ) [inline]
```

Getter for command line options.

Getter for ProgramOptions populated by the argument parser

Returns

ProgramOptions structure.

Definition at line 203 of file [argparse.h](#).

```
00203
00204     return this->po;
00205 }
```

References [po](#).

9.3.3.2 help()

```
void Markov::API::CLI::Argparse::help ( ) [static]
```

Print help string.

Definition at line 15 of file [argparse.cpp](#).

```
00015
00016     std::cout <<
00017     "Markov Passwords - Help\n"
00018     "Options:\n"
00019     "  \n"
00020     "  -of --outputfilename\n"
00021     "    Filename to output the generation results\n"
00022     "  -ef --exportfilename\n"
00023     "    filename to export built model to\n"
00024     "  -if --importfilename\n"
00025     "    filename to import model from\n"
00026     "  -n (generate count)\n"
00027     "    Number of lines to generate\n"
00028     "  \n"
00029     "Usage: \n"
00030     "  markov.exe -if empty_model.mdl -ef model.mdl\n"
00031     "    import empty_model.mdl and train it with data from stdin. When done, output the model to
model.mdl\n"
00032     "\n"
00033     "  markov.exe -if empty_model.mdl -n 15000 -of wordlist.txt\n"
00034     "    import empty_model.mdl and generate 15000 words to wordlist.txt\n"
00035
00036     << std::endl;
00037 }
```

9.3.3.3 parse()

```
Markov::API::CLI::ProgramOptions * Markov::API::CLI::Argparse::parse (
    int argc,
    char ** argv ) [static]
parse cli commands and return
```

Parameters

<i>argc</i>	- Program arguement count
<i>argv</i>	- Program arguement values array

Returns

ProgramOptions structure.

Definition at line 11 of file [argparse.cpp](#).
00011 { **return** 0; }

9.3.3.4 setProgramOptions()

```
void Markov::API::CLI::Argparse::setProgramOptions (
    bool i,
    bool e,
    bool bf,
    char s,
    std::string iName,
    std::string exName,
    std::string oName,
    std::string dName,
    int n ) [inline]
```

Initialize program options structure.

Parameters

<i>i</i>	boolean, true if import operation is flagged
<i>e</i>	boolean, true if export operation is flagged
<i>bf</i>	boolean, true if there is something wrong with the command line parameters
<i>s</i>	seperator character for the import function
<i>iName</i>	import filename
<i>exName</i>	export filename
<i>oName</i>	output filename
<i>dName</i>	corpus filename
<i>n</i>	number of passwords to be generated

Definition at line 220 of file [argparse.h](#).

```
00220
00221     this->po.bImport = i;
00222     this->po.bExport = e;
00223     this->po.seperator = s;
00224     this->po.bFailure = bf;
00225     this->po.generateN = n;
00226     this->po.importname = iName;
00227     this->po.exportname = exName;
00228     this->po.outputfilename = oName;
00229     this->po.datasetname = dName;
00230
00231     /*strcpy_s(this->po.importname,256,iName);
00232     strcpy_s(this->po.exportname,256,exName);
```

```

00233     strcpy_s(this->po.outputfilename,256,oName);
00234     strcpy_s(this->po.datasetname,256,dName); */
00235 }

```

References [Markov::API::CLI::_programOptions::bExport](#), [Markov::API::CLI::_programOptions::bFailure](#), [Markov::API::CLI::_programOptions::datasetname](#), [Markov::API::CLI::_programOptions::exportname](#), [Markov::API::CLI::_programOptions::importname](#), [Markov::API::CLI::_programOptions::outputfilename](#), [po](#), and [Markov::API::CLI::_programOptions::separator](#).

9.3.4 Member Data Documentation

9.3.4.1 po

[Markov::API::CLI::ProgramOptions](#) [Markov::API::CLI::Argparse::po](#) [private]
ProgramOptions structure object.

Definition at line [255](#) of file [argparse.h](#).

Referenced by [Argparse\(\)](#), [getProgramOptions\(\)](#), and [setProgramOptions\(\)](#).

The documentation for this class was generated from the following files:


- [argparse.h](#)
- [argparse.cpp](#)

9.4 Markov::GUI::CLI Class Reference


QT [CLI](#) Class.

```
#include <CLI.h>
```

Inheritance diagram for Markov::GUI::CLI:



Collaboration diagram for Markov::GUI::CLI:



Public Slots

- void `start ()`
- void `statistics ()`
- void `about ()`

Public Member Functions

- `CLI (QWidget *parent=Q_NULLPTR)`

Private Attributes

- `Ui::CLI ui`

9.4.1 Detailed Description

QT `CLI` Class.

Definition at line 14 of file `CLI.h`.

9.4.2 Constructor & Destructor Documentation

9.4.2.1 `CLI()`

```

Markov::GUI::CLI::CLI (
    QWidget * parent = Q_NULLPTR )
Definition at line 15 of file CLI.cpp.
00016     : QMainWidget(parent)
00017 {
  
```


```

00018     ui.setupUi(this);
00019
00020     QObject::connect(ui.startButton, &QPushButton::clicked, this, [this] {start(); });
00021     QObject::connect(ui.commandLinkButton_2, &QPushButton::clicked, this, [this] {statistics(); });
00022     QObject::connect(ui.commandLinkButton, &QPushButton::clicked, this, [this] {about(); });
00023
00024 }

```

References [about\(\)](#), [start\(\)](#), [statistics\(\)](#), and [ui](#).

Here is the call graph for this function:



9.4.3 Member Function Documentation

9.4.3.1 about

```

void Markov::GUI::CLI::about ( ) [slot]
Definition at line 36 of file CLI.cpp.
00036 {
00037     /*
00038     about button
00039     */
00040 }

```

Referenced by [CLI\(\)](#).

Here is the caller graph for this function:



9.4.3.2 start

```

void Markov::GUI::CLI::start ( ) [slot]
Definition at line 26 of file CLI.cpp.
00026 {
00027     Train* w = new Train;
00028     w->show();
00029     this->close();
00030 }

```

Referenced by [CLI\(\)](#).

Here is the caller graph for this function:




9.4.3.3 statistics

```
void Markov::GUI::CLI::statistics ( ) [slot]
Definition at line 31 of file CLI.cpp.
00031
00032     /*
00033     statistic will show
00034     */
00035 }
```

Referenced by [CLI\(\)](#).

Here is the caller graph for this function:



9.4.4 Member Data Documentation

9.4.4.1 ui

```
Ui::CLI Markov::GUI::CLI::ui [private]
Definition at line 20 of file CLI.h.
```

Referenced by [CLI\(\)](#).

The documentation for this class was generated from the following files:


- [CLI.h](#)
- [CLI.cpp](#)

9.5 Markov::API::CUDA::CUDADeviceController Class Reference


Controller class for [CUDA](#) device.

```
#include <cudaDeviceController.h>
```

Inheritance diagram for Markov::API::CUDA::CUDADeviceController:



Collaboration diagram for Markov::API::CUDA::CUDADeviceController:



Static Public Member Functions

- static __host__ void [ListCudaDevices \(\)](#)
List CUDA devices in the system.

Static Protected Member Functions

- static __host__ int [CudaCheckNotifyErr \(cudaError_t _status, const char *msg, bool bExit=true\)](#)
Check results of the last operation on GPU.
- template<typename T >
 static __host__ cudaError_t [CudaMalloc2DToFlat \(T **dst, int row, int col\)](#)
Malloc a 2D array in device space.
- template<typename T >
 static __host__ cudaError_t [CudaMemcpy2DToFlat \(T *dst, T **src, int row, int col\)](#)
Memcpy a 2D array in device space after flattening.
- template<typename T >
 static __host__ cudaError_t [CudaMigrate2DFlat \(T **dst, T **src, int row, int col\)](#)
Both malloc and memcpy a 2D array into device VRAM.

9.5.1 Detailed Description

Controller class for [CUDA](#) device.

This implementation only supports Nvidia devices.

Definition at line 18 of file [cudaDeviceController.h](#).

9.5.2 Member Function Documentation

9.5.2.1 CudaCheckNotifyErr()

```

__host__ int Markov::API::CUDA::CUDADeviceController::CudaCheckNotifyErr (
    cudaError_t _status,
    const char * msg,
    bool bExit = true ) [static], [protected]

```

Check results of the last operation on GPU.

Check the status returned from cudaMalloc/cudaMemcpy to find failures.
If a failure occurs, its assumed beyond redemption, and exited.

Parameters

<code>_status</code>	Cuda error status to check
<code>msg</code>	Message to print in case of a failure

Returns

0 if successful, 1 if failure. **Example output:**

```
char *da, a = "test";
cudastatus = cudaMalloc((char **)&da, 5*sizeof(char *));
CudaCheckNotifyErr(cudastatus, "Failed to allocate VRAM for *da.\n");
```

Definition at line 32 of file [cudaDeviceController.cu](#).

```
00032
00033     {
00034         if (_status != cudaSuccess) {
00035             std::cerr << "\033[1;31m" << msg << " -> " << cudaGetErrorString(_status) << "(" << _status <
00036             ")" << "\033[0m" << "\n";
00037         if(bExit) {
00038             cudaDeviceReset();
00039             exit(1);
00040         }
00041     return 0;
00042 }
```

9.5.2.2 CudaMalloc2DToFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat (
    T ** dst,
    int row,
    int col ) [inline], [static], [protected]
```

Malloc a 2D array in device space.

This function will allocate enough space on VRAM for flattened 2D array.

Parameters

<code>dst</code>	destination pointer
<code>row</code>	row size of the 2d array
<code>col</code>	column size of the 2d array

Returns

`cudaError_t` status of the `cudaMalloc` operation

Example output:


```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
if(cudastatus!=cudaSuccess){
    CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
}
```

Definition at line 75 of file [cudaDeviceController.h](#).

```
00075
00076     cudaError_t cudastatus = cudaMalloc((T **)dst, row*col*sizeof(T));
00077     CudaCheckNotifyErr(cudastatus, "cudaMalloc Failed.", false);
00078     return cudastatus;
00079 }
```

References [CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



9.5.2.3 CudaMemcpy2DToFlat()

```

template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat (
    T * dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected]
Memcpy a 2D array in device space after flattening.
Resulting buffer will not be true 2D array.
  
```

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:

```

cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
cudastatus = CudaMemcpy2DToFlat<char>(*dst, src, 15, 15);
CudaCheckNotifyErr(cudastatus, " CudaMemcpy2DToFlat Failed.", false);
  
```


Definition at line 103 of file [cudaDeviceController.h](#).

```

00103
00104      T* tempbuf = new T[row*col];
00105      for(int i=0;i<row;i++){
00106          memcpy(&(tempbuf[row*i]), src[i], col);
00107      }
00108      return cudaMemcpy(dst, tempbuf, row*col*sizeof(T), cudaMemcpyHostToDevice);
00109
00110  }
  
```

References [CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



9.5.2.4 CudaMigrate2DFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat (
    T ** dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected]
```

Both malloc and memcpy a 2D array into device VRAM.

Resulting buffer will not be true 2D array.

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation


Example output:

```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMigrate2DFlat<long int>(
    &dst, this->valueMatrix, this->matrixSize, this->matrixSize);
CudaCheckNotifyErr(cudastatus, "    Cuda failed to initialize value matrix row.");
Definition at line 132 of file cudaDeviceController.h.
00132
00133     cudaError_t cudastatus;
00134     cudastatus = CudaMalloc2DToFlat<T>(dst, row, col);
00135     if(cudastatus!=cudaSuccess) {
00136         CudaCheckNotifyErr(cudastatus, "    CudaMalloc2DToFlat Failed.", false);
00137         return cudastatus;
00138     }
00139     cudastatus = CudaMemcpy2DToFlat<T>(*dst,src,row,col);
00140     CudaCheckNotifyErr(cudastatus, "    CudaMemcpy2DToFlat Failed.", false);
00141     return cudastatus;
00142 }
```


References [CudaMigrate2DFlat\(\)](#).

Referenced by [CudaMalloc2DToFlat\(\)](#), [CudaMemcpy2DToFlat\(\)](#), and [CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.5.2.5 ListCudaDevices()

`__host__ void Markov::API::CUDA::CUDADeviceController::ListCudaDevices () [static]`
 List **CUDA** devices in the system.

This function will print details of every **CUDA** capable device in the system.

Example output:

```

Device Number: 0
Device name: GeForce RTX 2070
Memory Clock Rate (KHz): 7001000
Memory Bus Width (bits): 256
Peak Memory Bandwidth (GB/s): 448.064
Max Linear Threads: 1024
  
```

Definition at line 16 of file [cudaDeviceController.cu](#).

```

00016
00017     host.                                     //list cuda Capable devices on
00018     int nDevices;
00019     cudaGetDeviceCount(&nDevices);
00020     for (int i = 0; i < nDevices; i++) {
00021         cudaDeviceProp prop;
00022         cudaGetDeviceProperties(&prop, i);
00023         std::cerr << "Device Number: " << i << "\n";
00024         std::cerr << "Device name: " << prop.name << "\n";
00025         std::cerr << "Memory Clock Rate (KHz): " << prop.memoryClockRate << "\n";
00026         std::cerr << "Memory Bus Width (bits): " << prop.memoryBusWidth << "\n";
00027         std::cerr << "Peak Memory Bandwidth (GB/s): " << 2.0 * prop.memoryClockRate *
00028             (prop.memoryBusWidth / 8) / 1.0e6 << "\n";
00029         std::cerr << "Max Linear Threads: " << prop.maxThreadsDim[0] << "\n";
00030     }
  
```

The documentation for this class was generated from the following files:


- [cudaDeviceController.h](#)
- [cudaDeviceController.cu](#)

9.6 Markov::API::CUDA::CUDAModelMatrix Class Reference


Extension of [Markov::API::ModelMatrix](#) which is modified to run on GPU devices.

```
#include <cudaModelMatrix.h>
```

Inheritance diagram for Markov::API::CUDA::CUDAModelMatrix:



Collaboration diagram for Markov::API::CUDA::CUDAModelMatrix::



Public Member Functions

- `__host__ void MigrateMatrix ()`
Migrate the class members to the VRAM.
 - `__host__ void FlattenMatrix ()`
Flatten migrated matrix from 2d to 1d.
 - `__host__ void FastRandomWalk (unsigned long int n, const char *wordlistFileName, int minLen, int maxLen, bool bFileIO, bool bInfinite)`
Random walk on the Matrix-reduced `Markov::Model`.
 - `bool ConstructMatrix ()`
Construct the related Matrix data for the model.
 - `void DumpJSON ()`
Debug function to dump the model to a JSON file.
 - `int FastRandomWalk (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20, bool bFileIO=true)`

- **Random** walk on the Matrix-reduced [Markov::Model](#).
- void **Import** (const char *filename)

Open a file to import with filename, and call bool Model::Import with std::ifstream.
- bool **Import** (std::ifstream *)

Import a file to construct the model.
- void **Train** (const char *datasetFileName, char delimiter, int threads)

Train the model with the dataset file.
- std::ifstream * **OpenDatasetFile** (const char *filename)

Open dataset file and return the ifstream pointer.
- std::ofstream * **Save** (const char *filename)

Export model to file.
- void **Generate** (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20)

Call Markov::Model::RandomWalk n times, and collect output.
- void **Buff** (const char *str, double multiplier, bool bDontAdjustSelfLoops=true, bool bDontAdjustExtendedLoops=false)

Buff expression of some characters in the model.
- char * **RandomWalk** (Markov::Random::RandomEngine *randomEngine, int minSetting, int maxSetting, char *buffer)

Do a random walk on this model.
- void **AdjustEdge** (const char *payload, long int occurrence)

Adjust the model with a single string.
- bool **Export** (std::ofstream *)

Export a file of the model.
- bool **Export** (const char *filename)

Open a file to export with filename, and call bool Model::Export with std::ofstream.
- **Node<char> * StarterNode()**

Return starter Node.
- std::vector<[Edge<char>](#)> * **Edges()**

Return a vector of all the edges in the model.
- std::map<char, [Node<char>](#)> * **Nodes()**

Return starter Node.
- void **OptimizeEdgeOrder()**

Sort edges of all nodes in the model ordered by edge weights.

Static Public Member Functions

- static __host__ void **ListCudaDevices()**

List CUDA devices in the system.

Protected Member Functions

- __host__ char * **AllocVRAMOutputBuffer** (long int n, long int singleGenMaxLen, long int CUDAKernelGridSize, long int sizePerGrid)

Allocate the output buffer for kernel operation.
- __host__ void **LaunchAsyncKernel** (int kernelID, int minLen, int maxLen)
- __host__ void **prepKernelMemoryChannel** (int numberOfWorkstreams)
- __host__ void **GatherAsyncKernelOutput** (int kernelID, bool bFileIO, std::ofstream &wordlist)
- int **FastRandomWalk** (unsigned long int n, std::ofstream *wordlist, int minLen=6, int maxLen=12, int threads=20, bool bFileIO=true)

Random walk on the Matrix-reduced Markov::Model.
- void **FastRandomWalkPartition** (std::mutex *mlock, std::ofstream *wordlist, unsigned long int n, int minLen, int maxLen, bool bFileIO, int threads)

- A single partition of *FastRandomWalk* event.
- void **FastRandomWalkThread** (std::mutex *mlock, std::ofstream *wordlist, unsigned long int n, int minLen, int maxLen, int id, bool bFileIO)
 - A single thread of a single partition of *FastRandomWalk*.
- bool **DeallocateMatrix** ()
 - Deallocate matrix and make it ready for re-construction.*

Static Protected Member Functions

- static __host__ int **CudaCheckNotifyErr** (cudaError_t _status, const char *msg, bool bExit=true)
 - Check results of the last operation on GPU.*
- template<typename T >
 static __host__ cudaError_t **CudaMalloc2DToFlat** (T **dst, int row, int col)
 - Malloc a 2D array in device space.*
- template<typename T >
 static __host__ cudaError_t **CudaMemcpy2DToFlat** (T *dst, T **src, int row, int col)
 - Memcpy a 2D array in device space after flattening.*
- template<typename T >
 static __host__ cudaError_t **CudaMigrate2DFlat** (T **dst, T **src, int row, int col)
 - Both malloc and memcpy a 2D array into device VRAM.*

Protected Attributes

- char ** **edgeMatrix**
 - 2-D Character array for the edge Matrix (The characters of Nodes)*
- long int ** **valueMatrix**
 - 2-d Integer array for the value Matrix (For the weights of Edges)*
- int **matrixSize**
 - to hold Matrix size*
- char * **matrixIndex**
 - to hold the Matrix index (To hold the orders of 2-D arrays')*
- long int * **totalEdgeWeights**
 - Array of the Total Edge Weights.*
- bool **ready**
 - True when matrix is constructed. False if not.*

Private Member Functions

- void **TrainThread** (Markov::API::Concurrency::ThreadSharedListHandler *listhandler, char delimiter)
 - A single thread invoked by the Train function.*
- void **GenerateThread** (std::mutex *outputLock, unsigned long int n, std::ofstream *wordlist, int minLen, int maxLen)
 - A single thread invoked by the Generate function.*

Private Attributes

- char * **device_edgeMatrix**
 - VRAM Address pointer of edge matrix (from *modelMatrix.h*)*
- long int * **device_valueMatrix**
 - VRAM Address pointer of value matrix (from *modelMatrix.h*)*
- char * **device_matrixIndex**
 - VRAM Address pointer of matrixIndex (from *modelMatrix.h*)*
- long int * **device_totalEdgeWeights**

- VRAM Address pointer of total edge weights (from `modelMatrix.h`)
- `char ** device_outputBuffer`
RandomWalk results in device.
 - `char ** outputBuffer`
RandomWalk results in host.
 - `char * flatEdgeMatrix`
Adding `Edge` matrix end-to-end and resize to 1-D array for better performance on traversing.
 - `long int * flatValueMatrix`
Adding Value matrix end-to-end and resize to 1-D array for better performance on traversing.
 - `int cudaBlocks`
 - `int cudaThreads`
 - `int iterationsPerKernelThread`
 - `long int totalOutputPerSync`
 - `long int totalOutputPerKernel`
 - `int numberOfPartitions`
 - `int cudaGridSize`
 - `int cudaMemPerGrid`
 - `long int cudaPerKernelAllocationSize`
 - `int alternatingKernels`
 - `unsigned long ** device_seeds`
 - `cudaStream_t * cudastreams`
 - `std::ifstream * datasetFile`
 - `std::ofstream * modelSavefile`
Dataset file input of our system
 - `std::ofstream * outputFile`
File to save model of our system
 - `std::map< char, Node< char > * > nodes`
Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
 - `Node< char > * starterNode`
Starter Node of this model.
 - `std::vector< Edge< char > * > edges`
A list of all edges in this model.

9.6.1 Detailed Description

Extension of `Markov::API::ModelMatrix` which is modified to run on GPU devices.

This implementation only supports Nvidia devices.

Class to flatten and reduce `Markov::Model` to a Matrix. Matrix level operations can be used for Generation events, with a significant performance optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)

To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for allocation. Threads are synchronized and files are flushed every 50M operations.

Definition at line 19 of file `cudaModelMatrix.h`.

9.6.2 Member Function Documentation

9.6.2.1 AdjustEdge()

```
void Markov::Model< char >::AdjustEdge (
    const NodeStorageType * payload,
    long int occurrence ) [inherited]
```

Adjust the model with a single string.

Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from current node to the next, until NULL character is reached.

Then, update the edge EdgeWeight from current node, to the terminator node.

This function is used for training purposes, as it can be used for adjusting the model with each line of the corpus file.

Example Use: Create an empty model and train it with string: "testdata"

```
Markov::Model<char> model;
char test[] = "testdata";
model.AdjustEdge(test, 15);
```

Parameters

string	- String that is passed from the training, and will be used to AdjustEdge the model with
occurrence	- Occurrence of this string.

Definition at line 337 of file [model.h](#).

```
00337
00338     NodeStorageType p = payload[0];
00339     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00340     Markov::Edge<NodeStorageType>* e;
00341     int i = 0;
00342
00343     if (p == 0) return;
00344     while (p != 0) {
00345         e = curnode->FindEdge(p);
00346         if (e == NULL) return;
00347         e->AdjustEdge(occurrence);
00348         curnode = e->RightNode();
00349         p = payload[++i];
00350     }
00351
00352     e = curnode->FindEdge('\xff');
00353     e->AdjustEdge(occurrence);
00354     return;
00355 }
```

9.6.2.2 AllocVRAMOutputBuffer()

```
__host__ char* Markov::API::CUDA::CUDAModelMatrix::AllocVRAMOutputBuffer (
    long int n,
    long int singleGenMaxLen,
    long int CUDAKernelGridSize,
    long int sizePerGrid ) [protected]
```

Allocate the output buffer for kernel operation.

TODO

Parameters

n	- Number of passwords to generate.
singleGenMaxLen	- maximum string length for a single generation
CUDAKernelGridSize	- Total number of grid members in CUDA kernel
sizePerGrid	- Size to allocate per grid member

Returns

pointer to the allocation on VRAM

9.6.2.3 Buff()

```
void Markov::API::MarkovPasswords::Buff (
    const char * str,
    double multiplier,
    bool bDontAdjustSelfLoops = true,
    bool bDontAdjustExtendedLoops = false ) [inherited]
```

Buff expression of some characters in the model.

Parameters

<i>str</i>	A string containing all the characters to be buffered
<i>multiplier</i>	A constant value to buffer the nodes with.
<i>bDontAdjustSelfEdges</i>	Do not adjust weights if target node is same as source node
<i>bDontAdjustExtendedLoops</i>	Do not adjust if both source and target nodes are in first parameter


Definition at line 153 of file [markovPasswords.cpp](#).

```
00153
00154     std::string buffstr(str);
00155     std::map< char, Node< char > * > *nodes;
00156     std::map< char, Edge< char > * > *edges;
00157     nodes = this->Nodes();
00158     int i=0;
00159     for (auto const& [repr, node] : *nodes) {
00160         edges = node->Edges();
00161         for (auto const& [targetrepr, edge] : *edges) {
00162             if(buffstr.find(targetrepr)!= std::string::npos) {
00163                 if(bDontAdjustSelfLoops && repr==targetrepr) continue;
00164                 if(bDontAdjustExtendedLoops) {
00165                     if(buffstr.find(repr)!= std::string::npos) {
00166                         continue;
00167                     }
00168                 }
00169                 long int weight = edge->EdgeWeight();
00170                 weight = weight*multiplier;
00171                 edge->AdjustEdge(weight);
00172             }
00173         }
00174     }
00175     i++;
00176 }
00177
00178 this->OptimizeEdgeOrder();
00179 }
```


References [Markov::Edge< NodeStorageType >::AdjustEdge\(\)](#), [Markov::Node< storageType >::Edges\(\)](#), [Markov::Edge< NodeStorageType >::EdgeWeight\(\)](#), [Markov::Model< NodeStorageType >::Nodes\(\)](#), and [Markov::Model< NodeStorageType >::OptimizeEdgeOrder\(\)](#).

Referenced by [main\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.4 ConstructMatrix()

`bool Markov::API::ModelMatrix::ConstructMatrix () [inherited]`

Construct the related Matrix data for the model.

This operation can be used after importing/training to allocate and populate the matrix content.

this will initialize: `char** edgeMatrix ->` a 2D array of mapping left and right connections of each edge. `long int **valueMatrix ->` a 2D array representing the edge weights. `int matrixSize ->` Size of the matrix, aka total number of nodes. `char* matrixIndex ->` order of nodes in the model `long int *totalEdgeWeights ->` total edge weights of each `Node`.

Returns

True if constructed. False if already constructed.

Definition at line 31 of file `modelMatrix.cpp`.

```

00031
00032     if(this->ready) return false;
00033     this->matrixSize = this->StarterNode()->edgesV.size() + 2;
00034
00035     this->matrixIndex = new char[this->matrixSize];
00036     this->totalEdgeWeights = new long int[this->matrixSize];
00037
00038     this->edgeMatrix = new char*[this->matrixSize];
00039     for(int i=0;i<this->matrixSize;i++){
00040         this->edgeMatrix[i] = new char[this->matrixSize];
00041     }
00042     this->valueMatrix = new long int*[this->matrixSize];
00043     for(int i=0;i<this->matrixSize;i++){
00044         this->valueMatrix[i] = new long int[this->matrixSize];
00045     }
00046     std::map< char, Node< char > * > *nodes;
00047     nodes = this->Nodes();
00048     int i=0;
00049     for (auto const& [repr, node] : *nodes){
00050         if(repr!=0) this->matrixIndex[i] = repr;
00051         else this->matrixIndex[i] = 199;
00052         this->totalEdgeWeights[i] = node->TotalEdgeWeights();
00053         for(int j=0;j<this->matrixSize;j++){
00054             char val = node->NodeValue();
00055             if(val < 0){
00056                 for(int k=0;k<this->matrixSize;k++){
00057                     this->valueMatrix[i][k] = 0;
00058                     this->edgeMatrix[i][k] = 255;
00059                 }
00060                 break;
00061             }
00062             else if(node->NodeValue() == 0 && j>(this->matrixSize-3)){
00063                 this->valueMatrix[i][j] = 0;
00064                 this->edgeMatrix[i][j] = 255;
00065             }else if(j==(this->matrixSize-1)) {
00066                 this->valueMatrix[i][j] = 0;
00067                 this->edgeMatrix[i][j] = 255;
00068             }else{
00069                 this->valueMatrix[i][j] = node->edgesV[j]->EdgeWeight();
00070                 this->edgeMatrix[i][j] = node->edgesV[j]->RightNode()->NodeValue();
00071             }
00072         }
00073     }
00074     i++;
00075 }

```


```

00076     this->ready = true;
00077     return true;
00078     //this->DumpJSON();
00079 }
```


References [Markov::API::ModelMatrix::edgeMatrix](#), [Markov::Edge< NodeStorageType >::EdgeWeight\(\)](#), [Markov::API::ModelMatrix::Markov::API::ModelMatrix::matrixSize](#), [Markov::Model< NodeStorageType >::Nodes\(\)](#), [Markov::Node< storageType >::NodeValue\(\)](#), [Markov::API::ModelMatrix::ready](#), [Markov::Edge< NodeStorageType >::RightNode\(\)](#), [Markov::Model< NodeStorageType >::StarterNode\(\)](#), [Markov::Node< storageType >::TotalEdgeWeights\(\)](#), [Markov::API::ModelMatrix::totalEdgeWeights](#), and [Markov::API::ModelMatrix::value\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), [Markov::API::ModelMatrix::Import\(\)](#), and [Markov::API::ModelMatrix::Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.5 CudaCheckNotifyErr()

```

__host__ int Markov::API::CUDA::CUDADeviceController::CudaCheckNotifyErr (
    cudaError_t _status,
    const char * msg,
    bool bExit = true ) [static], [protected], [inherited]
```

Check results of the last operation on GPU.

Check the status returned from cudaMalloc/cudaMemcpy to find failures.

If a failure occurs, its assumed beyond redemption, and exited.

Parameters

<code>_status</code>	Cuda error status to check
<code>msg</code>	Message to print in case of a failure

Returns

0 if successful, 1 if failure. **Example output:**

```
char *da, a = "test";
cudaStatus = cudaMalloc((char**)&da, 5*sizeof(char));
CudaCheckNotifyErr(cudaStatus, "Failed to allocate VRAM for *da.\n");
```

Definition at line 32 of file [cudaDeviceController.cu](#).

```
00032
00033     {
00034         if (_status != cudaSuccess) {
00035             std::cerr << "\033[1;31m" << msg << " -> " << cudaGetErrorString(_status) << "(" << _status <
00036             ")" << "\033[0m" << "\n";
00037         if(bExit) {
00038             cudaDeviceReset();
00039             exit(1);
00040         }
00041     return 0;
00042 }
```

9.6.2.6 CudaMalloc2DToFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat (
    T ** dst,
    int row,
    int col ) [inline], [static], [protected], [inherited]
```

Malloc a 2D array in device space.

This function will allocate enough space on VRAM for flattened 2D array.

Parameters

<i>dst</i>	destination pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:


```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
if(cudastatus!=cudaSuccess){
    CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
}
```

Definition at line 75 of file [cudaDeviceController.h](#).

```
00075
00076     cudaError_t cudastatus = cudaMalloc((T **)dst, row*col*sizeof(T));
00077     CudaCheckNotifyErr(cudastatus, "cudaMalloc Failed.", false);
00078     return cudastatus;
00079 }
```

References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



9.6.2.7 CudaMemcpy2DToFlat()

```

template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat (
    T * dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected], [inherited]
Memcpy a 2D array in device space after flattening.
Resulting buffer will not be true 2D array.

```

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:

```

cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
cudastatus = CudaMemcpy2DToFlat<char>(*dst,src,15,15);
CudaCheckNotifyErr(cudastatus, " CudaMemcpy2DToFlat Failed.", false);

```

Definition at line 103 of file [cudaDeviceController.h](#).


```

00103
00104     T* tempbuf = new T[row*col];
00105     for(int i=0;i<row;i++){
00106         memcpy(&(tempbuf[row*i]), src[i], col);
00107     }
00108     return cudaMemcpy(dst, tempbuf, row*col*sizeof(T), cudaMemcpyHostToDevice);
00109
00110 }

```

References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



9.6.2.8 CudaMigrate2DFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDADeviceController::CudaMigrate2DFlat (
    T ** dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected], [inherited]
```

Both malloc and memcpy a 2D array into device VRAM.
Resulting buffer will not be true 2D array.

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:

```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMigrate2DFlat<long int>(
    &dst, this->valueMatrix, this->matrixSize, this->matrixSize);
CudaCheckNotifyErr(cudastatus, "    Cuda failed to initialize value matrix row.");
```


Definition at line 132 of file [cudaDeviceController.h](#).

```
00132
00133     cudaError_t cudastatus;
00134     cudastatus = CudaMalloc2DToFlat<T>(dst, row, col);
00135     if(cudastatus!=cudaSuccess){
00136         CudaCheckNotifyErr(cudastatus, "    CudaMalloc2DToFlat Failed.", false);
00137         return cudastatus;
00138     }
00139     cudastatus = CudaMemcpy2DToFlat<T>(*dst,src,row,col);
00140     CudaCheckNotifyErr(cudastatus, "    CudaMemcpy2DToFlat Failed.", false);
00141     return cudastatus;
00142 }
```


References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Referenced by [Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat\(\)](#), [Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat\(\)](#) and [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.9 DeallocateMatrix()

```
bool Markov::API::ModelMatrix::DeallocateMatrix ( ) [protected], [inherited]
```

Deallocate matrix and make it ready for re-construction.

Returns

True if deallocated. False if matrix was not initialized


Definition at line 81 of file [modelMatrix.cpp](#).

```

00081
00082     if(!this->ready) return false;
00083     delete[] this->matrixIndex;
00084     delete[] this->totalEdgeWeights;
00085
00086     for(int i=0;i<this->matrixSize;i++) {
00087         delete[] this->edgeMatrix[i];
00088     }
00089     delete[] this->edgeMatrix;
00090
00091     for(int i=0;i<this->matrixSize;i++) {
00092         delete[] this->valueMatrix[i];
00093     }
00094     delete[] this->valueMatrix;
00095
00096     this->matrixSize = -1;
00097     this->ready = false;
00098     return true;
00099 }
```

References [Markov::API::ModelMatrix::edgeMatrix](#), [Markov::API::ModelMatrix::matrixIndex](#), [Markov::API::ModelMatrix::matrixSize](#), [Markov::API::ModelMatrix::ready](#), [Markov::API::ModelMatrix::totalEdgeWeights](#), and [Markov::API::ModelMatrix::valueMatrix](#).

Referenced by [Markov::API::ModelMatrix::Import\(\)](#), and [Markov::API::ModelMatrix::Train\(\)](#).
 Here is the caller graph for this function:



9.6.2.10 DumpJSON()

`void Markov::API::ModelMatrix::DumpJSON () [inherited]`

Debug function to dump the model to a JSON file.

Might not work 100%. Not meant for production use.

Definition at line 101 of file [modelMatrix.cpp](#).


```

00101
00102
00103     std::cout << "{\n      \"index\": \"";
00104     for(int i=0;i<this->matrixSize;i++) {
00105         if(this->matrixIndex[i]=='"') std::cout << "\\\\"";
00106         else if(this->matrixIndex[i]=='\\') std::cout << "\\\\\\";
00107         else if(this->matrixIndex[i]==0) std::cout << "\\\\\x00";
00108         else if(i==0) std::cout << "\\\\xff";
00109         else if(this->matrixIndex[i]=='\n') std::cout << "\\n";
00110         else std::cout << this->matrixIndex[i];
00111     }
00112     std::cout <<
00113     " \\",\\n"
00114     "   \"edgemap\": {\n\\n
00115
00116     for(int i=0;i<this->matrixSize;i++) {
00117         if(this->matrixIndex[i]=='"') std::cout << "      \"\\\\\"\\\"": [";
00118         else if(this->matrixIndex[i]=='\\') std::cout << "      \"\\\\\\\\\\\"": [";
00119         else if(this->matrixIndex[i]==0) std::cout << "      \"\\\\\\\\\\x00": [";
00120         else if(this->matrixIndex[i]<0) std::cout << "      \"\\\\\\\\\\xf\\\"": [";
00121         else std::cout << "      \"\" << this->matrixIndex[i] << "\": [";
00122         for(int j=0;j<this->matrixSize;j++) {
00123             if(this->edgeMatrix[i][j]=='"') std::cout << "        \"\\\\\"\\\"";
00124             else if(this->edgeMatrix[i][j]=='\\') std::cout << "        \"\\\\\\\\\\\"";
00125             else if(this->edgeMatrix[i][j]==0) std::cout << "        \"\\\\\\\\\\x00\"";
00126             else if(this->edgeMatrix[i][j]<0) std::cout << "        \"\\\\\\\\\\xf\\\"";
00127             else if(this->matrixIndex[i]=='\n') std::cout << "        \"\\\\n\"";
00128             else std::cout << "        \"\" << this->edgeMatrix[i][j] << "\": ";
00129             if(j!=this->matrixSize-1) std::cout << ", ";
00130         }
00131     std::cout << "],\\n";
00132   }
00133   std::cout << "},\\n";
00134
00135   std::cout << "  \"weightmap\": {\n\\n
00136     for(int i=0;i<this->matrixSize;i++) {
00137         if(this->matrixIndex[i]=='"') std::cout << "    \"\\\\\"\\\"": [";
00138         else if(this->matrixIndex[i]=='\\') std::cout << "    \"\\\\\\\\\\\"": [";
00139         else if(this->matrixIndex[i]==0) std::cout << "    \"\\\\\\\\\\x00": [";
00140         else if(this->matrixIndex[i]<0) std::cout << "    \"\\\\\\\\\\xf\\\"": [";
00141         else std::cout << "    \"\" << this->matrixIndex[i] << "\": [";
00142
00143         for(int j=0;j<this->matrixSize;j++) {
00144             std::cout << this->valueMatrix[i][j];
00145             if(j!=this->matrixSize-1) std::cout << ", ";
00146         }
00147     std::cout << "],\\n";
00148   }
00149   std::cout << "  }\\n}\\n";
00150 }
```

References [Markov::API::ModelMatrix::edgeMatrix](#), [Markov::API::ModelMatrix::matrixIndex](#), [Markov::API::ModelMatrix::matrixSize](#), and [Markov::API::ModelMatrix::valueMatrix](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the caller graph for this function:



9.6.2.11 Edges()

`std::vector<Edge<char>>* Markov::Model<char>::Edges () [inline], [inherited]`
Return a vector of all the edges in the model.

Returns

`vector of edges`

Definition at line 176 of file `model.h`.
00176 { **return** &edges; }

9.6.2.12 Export() [1/2]

`bool Markov::Model<char>::Export (const char * filename) [inherited]`

Open a file to export with filename, and call bool `Model::Export` with std::ofstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Export file to filename

```
Markov::Model<char> model;
model.Export("test.mdl");
```

Definition at line 300 of file `model.h`.

```
00300
00301     std::ofstream exportfile;
00302     exportfile.open(filename);
00303     return this->Export(&exportfile);
00304 }
```

9.6.2.13 Export() [2/2]

`bool Markov::Model<char>::Export (std::ofstream * f) [inherited]`

Export a file of the model.

File contains a list of edges. Format is: Left_repr;EdgeWeight;right_repr. For more information on the format, check out the project wiki or github readme.

Iterate over this vertices, and their edges, and write them to file.

Returns

True if successful, False for incomplete models.

Example Use: Export file to ofstream

```
Markov::Model<char> model;
std::ofstream file("test.mdl");
model.Export(&file);
```

Definition at line 288 of file `model.h`.

```
00288 }
```

```

00289     Markov::Edge<NodeStorageType>* e;
00290     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00291         e = this->edges[i];
00292         //std::cout << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," <
00293         e->RightNode()->NodeValue() << "\n";
00294         *f << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," << e->RightNode()->NodeValue() <<
00295         "\n";
00296     }
00297     return true;
00298 }
```

9.6.2.14 FastRandomWalk() [1/3]

```

__host__ void Markov::API::CUDA::CUDAModelMatrix::FastRandomWalk (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen,
    int maxLen,
    bool bFileIO,
    bool bInfinite )
```

Random walk on the Matrix-reduced [Markov::Model](#).

TODO

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

```

Markov::API::ModelMatrix mp;
mp.Import("models/finished.mdl");
mp.FastRandomWalk(50000000, "./wordlist.txt", 6, 12, 25, true);
```

Definition at line 58 of file [cudaModelMatrix.cu](#).

```

00058
00059     cudaDeviceProp prop;
00060     int device=0;
00061     cudaGetDeviceProperties(&prop, device);
00062     cudaChooseDevice(&device, &prop);
00063     //std::cout << "Flattening matrix." << std::endl;
00064     this->FlattenMatrix();
00065     //std::cout << "Migrating matrix." << std::endl;
00066     this->MigrateMatrix();
00067     //std::cout << "Migrated matrix." << std::endl;
00068     std::ifstream wordlist;
00069     if(bFileIO)
00070         wordlist.open(wordlistFileName);
00071
00072
00073     cudaBlocks = 1024;
00074     cudaThreads = 256;
00075     iterationsPerKernelThread = 100;
00076     alternatingKernels = 2;
00077     totalOutputPerKernel = (long int)cudaBlocks*(long int)cudaThreads*iterationsPerKernelThread;
00078     totalOutputPerSync= totalOutputPerKernel*alternatingKernels;
00079     numberofPartitions = n/totalOutputPerSync;
00080     cudaGridSize = cudaBlocks*cudaThreads;
00081     cudaMemPerGrid = (maxLen+2)*iterationsPerKernelThread;
00082     cudaPerKernelAllocationSize = cudaGridSize*cudaMemPerGrid;
00083     this->prepKernelMemoryChannel(alternatingKernels);
00084
00085     unsigned long int leftover = n - (totalOutputPerSync*numberofPartitions);
00086
00087     if(bInfinite && !numberofPartitions) numberofPartitions=5;
00088     std::cerr << cudaPerKernelAllocationSize << "\n";
00089
00090     if(n%totalOutputPerSync) std::cerr << "For optimization, request outputs multiples of " <<
00091     totalOutputPerSync << ".\n";
00092 }
```

```

00092     //start kernelID 1
00093     this->LaunchAsyncKernel(1, minLen, maxLen);
00094
00095     for(int i=1;i<numberOfPartitions;i++) {
00096         if(bInfinite) i=0;
00097
00098         //wait kernelID1 to finish, and start kernelID 0
00099         cudaStreamSynchronize(this->cudastreams[1]);
00100         this->LaunchAsyncKernel(0, minLen, maxLen);
00101
00102         //start memcpy from kernel 1 (block until done)
00103         this->GatherAsyncKernelOutput(1, bFileIO, wordlist);
00104
00105         //wait kernelID 0 to finish, then start kernelID1
00106         cudaStreamSynchronize(this->cudastreams[0]);
00107         this->LaunchAsyncKernel(1, minLen, maxLen);
00108
00109         //start memcpy from kernel 0 (block until done)
00110         this->GatherAsyncKernelOutput(0, bFileIO, wordlist);
00111
00112     }
00113
00114     //wait kernelID1 to finish, and start kernelID 0
00115     cudaStreamSynchronize(this->cudastreams[1]);
00116     this->LaunchAsyncKernel(0, minLen, maxLen);
00117     this->GatherAsyncKernelOutput(1, bFileIO, wordlist);
00118     cudaStreamSynchronize(this->cudastreams[0]);
00119     this->GatherAsyncKernelOutput(0, bFileIO, wordlist);
00120
00121
00122     if(!leftover) return;
00123     alternatingKernels=1;
00124     std::cerr << "Remaining line count (" << leftover << ") is lower than partition. Adjusting CUDA
workload..\n";
00125     this->iterationsPerKernelThread = leftover/cudaGridSize;
00126     this->LaunchAsyncKernel(0, minLen, maxLen);
00127     cudaStreamSynchronize(this->cudastreams[0]);
00128     this->GatherAsyncKernelOutput(0, bFileIO, wordlist);
00129
00130     leftover -= this->iterationsPerKernelThread*cudaGridSize;
00131     if(!leftover) return;
00132
00133     std::cerr << "Remaining line count (" << leftover << ") is lower than minimum possible. Handing
over to CPU generation.\n";
00134     this->iterationsPerKernelThread = leftover/cudaGridSize;
00135
00136     leftover -= this->iterationsPerKernelThread;
00137
00138     if(!leftover) return;
00139     std::cerr << "Remaining " << leftover << " lines are absolutely not worth printing.\n";
00140     Markov::API::ModelMatrix::ConstructMatrix();
00141     Markov::API::ModelMatrix::FastRandomWalk(leftover, &wordlist, minLen, maxLen, 1, bFileIO);
00142
00143 }
```

References [alternatingKernels](#), [cudaBlocks](#), [cudaGridSize](#), [cudaMemPerGrid](#), [cudaPerKernelAllocationSize](#), [cudaThreads](#), [iterationsPerKernelThread](#), [numberOfPartitions](#), [totalOutputPerKernel](#), and [totalOutputPerSync](#).

9.6.2.15 FastRandomWalk() [2/3]

```

int Markov::API::ModelMatrix::FastRandomWalk (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20,
    bool bFileIO = true ) [inherited]
```

[Random walk on the Matrix-reduced Markov::Model](#).

This has an O(N) Memory complexity. To limit the maximum usage, requests with $n > 50M$ are partitioned using [Markov::API::ModelMatrix::FastRandomWalkPartition](#).

If $n > 50M$, threads are going to be synced, files are going to be flushed, and buffers will be reallocated every 50M generations. This comes at a minor performance penalty.

While it has the same functionality, this operation reduces [Markov::API::MarkovPasswords::Generate](#) runtime by %96.5

This function has deprecated [Markov::API::MarkovPasswords::Generate](#), and will eventually replace it.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

```
Markov::API::ModelMatrix mp;
mp.Import("models/finished.mdl");
mp.FastRandomWalk(50000000, "./wordlist.txt", 6, 12, 25, true);
```


Definition at line 217 of file [modelMatrix.cpp](#).

```
00217
00218     std::ofstream wordlist;
00219     if(bFileIO)
00220         wordlist.open(wordlistFileName);
00221     this->FastRandomWalk(n, &wordlist, minLen, maxLen, threads, bFileIO);
00222     return 0;
00223 }
```


References [Markov::API::ModelMatrix::FastRandomWalk\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.16 FastRandomWalk() [3/3]

```
int Markov::API::ModelMatrix::FastRandomWalk (
    unsigned long int n,
    std::ofstream * wordlist,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20,
    bool bFileIO = true ) [protected], [inherited]
```

Random walk on the Matrix-reduced [Markov::Model](#).

This has an O(N) Memory complexity. To limit the maximum usage, requests with $n > 50M$ are partitioned using [Markov::API::ModelMatrix::FastRandomWalkPartition](#).

If $n > 50M$, threads are going to be synced, files are going to be flushed, and buffers will be reallocated every 50M generations. This comes at a minor performance penalty.

While it has the same functionality, this operation reduces [Markov::API::MarkovPasswords::Generate](#) runtime by %96.5

This function has deprecated [Markov::API::MarkovPasswords::Generate](#), and will eventually replace it.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

```
Markov::API::ModelMatrix mp;
mp.Import("models/finished.mdl");
mp.FastRandomWalk(50000000, "./wordlist.txt", 6, 12, 25, true);
```

Definition at line 204 of file [modelMatrix.cpp](#).

```
00204
00205
00206
00207     std::mutex mlock;
00208     if(n<=50000000ull) this->FastRandomWalkPartition(&mlock, wordlist, n, minLen, maxLen, bFileIO,
00209         threads);
00210     else{
00211         int numberOfPartitions = n/50000000ull;
00212         for(int i=0;i<numberOfPartitions;i++)
00213             this->FastRandomWalkPartition(&mlock, wordlist, 50000000ull, minLen, maxLen, bFileIO,
00214             threads);
00215     }
00216     return 0;
00217 }
```

References [Markov::API::ModelMatrix::FastRandomWalkPartition\(\)](#).

Referenced by [Markov::API::ModelMatrix::FastRandomWalk\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.17 FastRandomWalkPartition()

```
void Markov::API::ModelMatrix::FastRandomWalkPartition (
    std::mutex * mlock,
    std::ofstream * wordlist,
    unsigned long int n,
    int minLen,
    int maxLen,
    bool bFileIO,
    int threads ) [protected], [inherited]
```

A single partition of FastRandomWalk event.

Since FastRandomWalk has to allocate its output buffer before operation starts and writes data in chunks, large n parameters would lead to huge memory allocations. **Without Partitioning:**

- 50M results 12 characters max -> 550 Mb Memory allocation

- 5B results 12 characters max -> 55 Gb Memory allocation
- 50B results 12 characters max -> 550GB Memory allocation

Instead, FastRandomWalk is partitioned per 50M generations to limit the top memory need.

Parameters

<i>mlock</i>	- mutex lock to distribute to child threads
<i>wordlist</i>	- Reference to the wordlist file to write to
<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

Definition at line 225 of file [modelMatrix.cpp](#).


```

00225
00226
00227     int iterationsPerThread = n/threads;
00228     int iterationsPerThreadCarryOver = n%threads;
00229
00230     std::vector<std::thread*> threadsV;
00231
00232     int id = 0;
00233     for(int i=0;i<threads;i++) {
00234         threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this,
00235                                         mlock, wordlist, iterationsPerThread, minLen, maxLen, id, bFileIO));
00236         id++;
00237     }
00238     threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this, mlock,
00239                                         wordlist, iterationsPerThreadCarryOver, minLen, maxLen, id, bFileIO));
00240     for(int i=0;i<threads;i++) {
00241         threadsV[i]->join();
00242     }
00243 }
```

References [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

Referenced by [Markov::API::ModelMatrix::FastRandomWalk\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.18 FastRandomWalkThread()

```
void Markov::API::ModelMatrix::FastRandomWalkThread (
    std::mutex * mlock,
```

```

    std::ofstream * wordlist,
    unsigned long int n,
    int minLen,
    int maxLen,
    int id,
    bool bFileIO ) [protected], [inherited]

```

A single thread of a single partition of FastRandomWalk.

A FastRandomWalkPartition will initiate as many of this function as requested.

This function contains the bulk of the generation algorithm.

Parameters

<i>mlock</i>	- mutex lock to distribute to child threads
<i>wordlist</i>	- Reference to the wordlist file to write to
<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>id</i>	- DEPRECATED Thread id - No longer used
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

Definition at line 153 of file [modelMatrix.cpp](#).

```


00153
00154     if(n==0) return;
00155
00156     Markov::Random::Marsaglia MarsagliaRandomEngine;
00157     char* e;
00158     char *res = new char[(maxLen+2)*n];
00159     int index = 0;
00160     char next;
00161     int len=0;
00162     long int selection;
00163     char cur;
00164     long int bufferctr = 0;
00165     for (int i = 0; i < n; i++) {
00166         cur=199;
00167         len=0;
00168         while (true) {
00169             e = strchr(this->matrixIndex, cur);
00170             index = e - this->matrixIndex;
00171             selection = MarsagliaRandomEngine.random() % this->totalEdgeWeights[index];
00172             for(int j=0;j<this->matrixSize;j++){
00173                 selection -= this->valueMatrix[index][j];
00174                 if (selection < 0){
00175                     next = this->edgeMatrix[index][j];
00176                     break;
00177                 }
00178             }
00179             if (len >= maxLen) break;
00180             else if ((next < 0) && (len < minLen)) continue;
00181             else if (next < 0) break;
00182             cur = next;
00183             res[bufferctr + len++] = cur;
00184         }
00185     }
00186     res[bufferctr + len++] = '\n';
00187     bufferctr+=len;
00188
00189 }
00190 if(bFileIO){
00191     mlock->lock();
00192     *wordlist << res;
00193     mlock->unlock();
00194 }else{
00195     mlock->lock();
00196     std::cout << res;
00197     mlock->unlock();
00198 }
00199 delete res;
00200
00201 }

```


References [Markov::API::ModelMatrix::edgeMatrix](#), [Markov::API::ModelMatrix::matrixIndex](#), [Markov::API::ModelMatrix::matrixSize](#), [Markov::Random::Marsaglia::random\(\)](#), [Markov::API::ModelMatrix::totalEdgeWeights](#), and [Markov::API::ModelMatrix::valueMatrix](#).

Referenced by [Markov::API::ModelMatrix::FastRandomWalkPartition\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.19 FlattenMatrix()

```
__host__ void Markov::API::CUDA::CUDAModelMatrix::FlattenMatrix ( )
```

Flatten migrated matrix from 2d to 1d.

Definition at line 261 of file [cudaModelMatrix.cu](#).

```
00261     this->flatEdgeMatrix = new char[this->matrixSize*this->matrixSize];
00262     this->flatValueMatrix = new long int[this->matrixSize*this->matrixSize];
00263     for(int i=0;i<this->matrixSize;i++){
00264         memcpy(&this->flatEdgeMatrix[i*this->matrixSize], this->edgeMatrix[i], this->matrixSize );
00265         memcpy(&this->flatValueMatrix[i*this->matrixSize], this->valueMatrix[i],
00266                this->matrixSize*sizeof(long int) );
00267     }
00268 }
```

References [flatEdgeMatrix](#), [flatValueMatrix](#), and [Markov::API::ModelMatrix::matrixSize](#).

9.6.2.20 GatherAsyncKernelOutput()

```
__host__ void Markov::API::CUDA::CUDAModelMatrix::GatherAsyncKernelOutput (
    int kernelID,
    bool bFileIO,
    std::ofstream & wordlist ) [protected]
```

Definition at line 180 of file [cudaModelMatrix.cu](#).

```
00180     {
00181         cudaMemcpy(this->outputBuffer[kernelID],this->device_outputBuffer[kernelID],cudaPerKernelAllocationSize,
00182                     cudaMemcpyDeviceToHost);
00183         //std::cerr << "Kernel" << kernelID << " output copied\n";
00184         if(bFileIO){
00185             for(long int j=0;j<cudaPerKernelAllocationSize;j+=cudaMemPerGrid){
00186                 wordlist << &this->outputBuffer[kernelID][j];
00187             }
00188         }else{
00189             for(long int j=0;j<cudaPerKernelAllocationSize;j+=cudaMemPerGrid){
00190                 std::cout << &this->outputBuffer[kernelID][j];
00191             }
00192         }
00193     }
```

References [cudaMemPerGrid](#), [cudaPerKernelAllocationSize](#), and [outputBuffer](#).

9.6.2.21 Generate()

```
void Markov::API::MarkovPasswords::Generate (
```

```

    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20 ) [inherited]

```

Call [Markov::Model::RandomWalk](#) n times, and collect output.

Generate from model and write results to a file. a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Deprecated See [Markov::API::MatrixModel::FastRandomWalk](#) for more information.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn

Definition at line 118 of file [markovPasswords.cpp](#).

```

00118
00119     char* res;
00120     char print[100];
00121     std::ofstream wordlist;
00122     wordlist.open(wordlistFileName);
00123     std::mutex mlock;
00124     int iterationsPerThread = n/threads;
00125     int iterationsCarryOver = n%threads;
00126     std::vector<std::thread*> threadsV;
00127     for(int i=0;i<threads;i++) {
00128         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::GenerateThread, this,
00129             &mlock, iterationsPerThread, &wordlist, minLen, maxLen));
00130     }
00131     for(int i=0;i<threads;i++) {
00132         threadsV[i]->join();
00133         delete threadsV[i];
00134     }
00135     this->GenerateThread(&mlock, iterationsCarryOver, &wordlist, minLen, maxLen);
00136
00137
00138 }
```


References [Markov::API::MarkovPasswords::GenerateThread\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [Markov::GUI::Generate::generation\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.22 GenerateThread()

```
void Markov::API::MarkovPasswords::GenerateThread (
    std::mutex * outputLock,
    unsigned long int n,
    std::ofstream * wordlist,
    int minLen,
    int maxLen ) [private], [inherited]
```

A single thread invoked by the Generate function.

DEPRECATED: See [Markov::API::MatrixModel::FastRandomWalkThread](#) for more information. This has been replaced with a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Parameters

<i>outputLock</i>	- shared mutex lock to lock during output operation. Prevents race condition on write.
<i>n</i>	number of lines to be generated by this thread
<i>wordlist</i>	wordlistfile
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate


Definition at line 140 of file [markovPasswords.cpp](#).

```
00140
00141     char* res = new char[maxLen+5];
00142     if(n==0) return;
00143
00144     Markov::Random::Marsaglia MarsagliaRandomEngine;
00145     for (int i = 0; i < n; i++) {
00146         this->RandomWalk(&MarsagliaRandomEngine, minLen, maxLen, res);
00147         outputLock->lock();
00148         *wordlist << res << "\n";
00149         outputLock->unlock();
00150     }
00151 }
```


References [Markov::Model< NodeStorageType >::RandomWalk\(\)](#).

Referenced by [Markov::API::MarkovPasswords::Generate\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.23 Import() [1/2]

```
void Markov::API::ModelMatrix::Import (
    const char * filename ) [inherited]
```

Open a file to import with filename, and call bool [Model::Import](#) with std::ifstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file with filename

```
Markov::Model<char> model;
model.Import("test.mdl");
```

Construct the matrix when done.


Definition at line 19 of file [modelMatrix.cpp](#).

```
00019
00020     this->DeallocateMatrix(); {
00021     this->Markov::API::MarkovPasswords::Import(filename);
00022     this->ConstructMatrix();
00023 }
```


References [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), and [Markov::Model< NodeStorageType >::Import\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.24 Import() [2/2]

```
bool Markov::Model< char >::Import (
    std::ifstream * f ) [inherited]
```

Import a file to construct the model.

File contains a list of edges. For more info on the file format, check out the wiki and github readme pages. Format is: Left_repr;EdgeWeight;right_repr

Iterate over this list, and construct nodes and edges accordingly.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file from ifstream

```
Markov::Model<char> model;
std::ifstream file("test.mdl");
model.Import(&file);
```

Definition at line 216 of file [model.h](#).

```
00216     std::string cell; {
00217     std::string cell;
00218     char src;
00219     char target;
00220     long int oc;
00221
00222     while (std::getline(*f, cell)) {
00223         //std::cout << "cell: " << cell << std::endl;
00224         src = cell[0];
00225         target = cell[cell.length() - 1];
00226         char* j;
00227         oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(), &j, 10);
00228         //std::cout << oc << "\n";
00229         Markov::Node<NodeStorageType>* srcN;
00230         Markov::Node<NodeStorageType>* targetN;
00231         Markov::Edge<NodeStorageType>* e;
00232         if (this->nodes.find(src) == this->nodes.end()) {
00233             srcN = new Markov::Node<NodeStorageType>(src);
00234             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(src, srcN));
00235             //std::cout << "Creating new node at start.\n";
00236         }
00237         else {
00238             srcN = this->nodes.find(src)->second;
00239         }
00240
00241         if (this->nodes.find(target) == this->nodes.end()) {
00242             targetN = new Markov::Node<NodeStorageType>(target);
00243             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(target, targetN));
00244             //std::cout << "Creating new node at end.\n";
00245         }
00246         else {
00247             targetN = this->nodes.find(target)->second;
00248         }
00249         e = srcN->Link(targetN);
00250         e->AdjustEdge(oc);
00251         this->edges.push_back(e);
00252
00253         //std::cout << int(srcN->NodeValue()) << " --> " << e->EdgeWeight() << "--> " <<
00254         int(targetN->NodeValue()) << "\n";
```

```

00255
00256
00257     }
00258
00259     this->OptimizeEdgeOrder();
00260
00261     return true;
00262 }
```

9.6.2.25 LaunchAsyncKernel()

```
__host__ void Markov::API::CUDA::CUDAModelMatrix::LaunchAsyncKernel (
    int kernelID,
    int minLen,
    int maxLen ) [protected]
```

Definition at line 171 of file [cudaModelMatrix.cu](#).

```

00171
00172
00173     //if(kernelID == 0); // cudaStreamSynchronize(this->cuadstreams[2]);
00174     //else cudaStreamSynchronize(this->cuadstreams[kernelID-1]);
00175     FastRandomWalkCUDAKernel<<(cudaBlocks,cudaThreads,0,
00176     this->cuadstreams[kernelID]>>(iterationsPerKernelThread, minLen, maxLen,
00177     this->device_outputBuffer[kernelID], this->device_matrixIndex,
00178     this->device_totalEdgeWeights, this->device_valueMatrix, this->device_edgeMatrix,
00179     this->matrixSize, cudaMemPerGrid, this->device_seeds[kernelID]);
00180     //std::cerr << "Started kernel" << kernelID << "\n";
00181 }
```

9.6.2.26 ListCudaDevices()

```
__host__ void Markov::API::CUDA::CUDADeviceController::ListCudaDevices () [static], [inherited]
List CUDA devices in the system.
```

This function will print details of every CUDA capable device in the system.

Example output:

```

Device Number: 0
Device name: GeForce RTX 2070
Memory Clock Rate (KHz): 7001000
Memory Bus Width (bits): 256
Peak Memory Bandwidth (GB/s): 448.064
Max Linear Threads: 1024
```

Definition at line 16 of file [cudaDeviceController.cu](#).

```

00016
00017     host.                                     { //list cuda Capable devices on
00018         int nDevices;
00019         cudaGetDeviceCount(&nDevices);
00020         for (int i = 0; i < nDevices; i++) {
00021             cudaDeviceProp prop;
00022             cudaGetDeviceProperties(&prop, i);
00023             std::cerr << "Device Number: " << i << "\n";
00024             std::cerr << "Device name: " << prop.name << "\n";
00025             std::cerr << "Memory Clock Rate (KHz): " << prop.memoryClockRate << "\n";
00026             std::cerr << "Memory Bus Width (bits): " << prop.memoryBusWidth << "\n";
00027             std::cerr << "Peak Memory Bandwidth (GB/s): " << 2.0 * prop.memoryClockRate *
00028             (prop.memoryBusWidth / 8) / 1.0e6 << "\n";
00029             std::cerr << "Max Linear Threads: " << prop.maxThreadsDim[0] << "\n";
00030         }
00031 }
```

9.6.2.27 MigrateMatrix()

```
__host__ void Markov::API::CUDA::CUDAModelMatrix::MigrateMatrix ()
```

Migrate the class members to the VRAM.

Cannot be used without calling [Markov::API::ModelMatrix::ConstructMatrix](#) at least once. This function will manage the memory allocation and data transfer from CPU RAM to GPU VRAM.

Newly allocated VRAM pointers are set in the class member variables.

Definition at line 20 of file [cudaModelMatrix.cu](#).

```

00020
00021     cudaError_t cudastatus;
00022
00023     cudastatus = cudaMalloc((char**)&(this->device_matrixIndex),
```

```

00024     this->matrixSize*sizeof(char));
00025     CudaCheckNotifyErr(cudastatus, "Cuda failed to initialize device_matrixIndex.");
00026
00027     cudastatus = cudaMalloc((long int **)&(this->device_totalEdgeWeights),
00028     this->matrixSize*sizeof(long int));
00029     CudaCheckNotifyErr(cudastatus, "Cuda failed to initialize device_totalEdgeWeights.");
00030
00031     cudastatus = cudaMemcpy(this->device_matrixIndex, this->matrixIndex,
00032     this->matrixSize*sizeof(char), cudaMemcpyHostToDevice);
00033     CudaCheckNotifyErr(cudastatus, "Cuda failed to copy to device memory. (Index)");
00034
00035     cudastatus = cudaMemcpy(this->device_totalEdgeWeights, this->totalEdgeWeights,
00036     this->matrixSize*sizeof(long int), cudaMemcpyHostToDevice);
00037     CudaCheckNotifyErr(cudastatus, "Cuda failed to copy to device memory. (Total Edge Values)");
00038
00039     cudastatus = CudaMigrate2DFlat<char>(
00040     &(this->device_edgeMatrix), this->edgeMatrix, this->matrixSize, this->matrixSize);
00041     CudaCheckNotifyErr(cudastatus, "Cuda failed to initialize edge matrix.");
00042
00043     cudastatus = CudaMigrate2DFlat<long int>(
00044     &(this->device_valueMatrix), this->valueMatrix, this->matrixSize, this->matrixSize);
00045     CudaCheckNotifyErr(cudastatus, "Cuda failed to initialize value matrix row.");
00046 }

```

9.6.2.28 Nodes()

`std::map<char , Node<char >>*>* Markov::Model< char >::Nodes () [inline], [inherited]`
 Return starter Node.

Returns

starter node with 00 NodeValue

Definition at line 181 of file [model.h](#).

```
00181 { return &nodes; }
```

9.6.2.29 OpenDatasetFile()

`std::ifstream * Markov::API::MarkovPasswords::OpenDatasetFile (
 const char * filename) [inherited]`
 Open dataset file and return the ifstream pointer.

Parameters

<code>filename</code>	- Filename to open
-----------------------	--------------------

Returns

`ifstream*` to the the dataset file

Definition at line 51 of file [markovPasswords.cpp](#).

```

00051
00052
00053     std::ifstream* datasetFile;
00054
00055     std::ifstream newFile(filename);
00056
00057     datasetFile = &newFile;
00058
00059     this->Import(datasetFile);
00060     return datasetFile;
00061 }
```

References [Markov::Model< NodeStorageType >::Import\(\)](#).

Here is the call graph for this function:



9.6.2.30 OptimizeEdgeOrder()

`void Markov::Model< char >::OptimizeEdgeOrder [inherited]`

Sort edges of all nodes in the model ordered by edge weights.

Definition at line 265 of file `model.h`.

```

00265     for (std::pair<unsigned char, Markov::Node<NodeStorageType>> const& x : this->nodes) {
00266         //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
00267         std::sort (x.second->edgesV.begin(), x.second->edgesV.end(), [](Edge<NodeStorageType> *lhs,
00268             Edge<NodeStorageType> *rhs)->bool{
00269             return lhs->EdgeWeight() > rhs->EdgeWeight();
00270         });
00271         //for(int i=0;i<x.second->edgesV.size();i++)
00272         // std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00273         //std::cout << "\n";
00274     }
00275     //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00276     //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00277 }
```

9.6.2.31 prepKernelMemoryChannel()

`__host__ void Markov::API::CUDA::CUDAModelMatrix::prepKernelMemoryChannel (`
`int numberOfStreams) [protected]`


Definition at line 145 of file `cudaModelMatrix.cu`.

```

00145
00146
00147     this->cuadstreams = new cudaStream_t[numberOfStreams];
00148     for(int i=0;i<numberOfStreams;i++)
00149         cudaStreamCreate(&this->cuadstreams[i]);
00150
00151     this->outputBuffer = new char*[numberOfStreams];
00152     for(int i=0;i<numberOfStreams;i++)
00153         this->outputBuffer[i]= new char[cudaPerKernelAllocationSize];
00154
00155     cudaError_t cudastatus;
00156     this->device_outputBuffer = new char*[numberOfStreams];
00157     for(int i=0;i<numberOfStreams;i++){
00158         cudastatus = cudaMalloc((char**)&(device_outputBuffer[i]),
00159             cudaPerKernelAllocationSize);
00160         CudaCheckNotifyErr(cudastatus, "Failed to establish memory channel. Possibly out of
VRAM?");
00161     }
00162
00163     this->device_seeds = new unsigned long*[numberOfStreams];
00164     for(int i=0;i<numberOfStreams;i++){
00165         Markov::API::CUDA::Random::Marsaglia *MEarr = new
00166             Markov::API::CUDA::Random::Marsaglia[cudaGridSize];
00167         this->device_seeds[i] = Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM(MEarr,
00168             cudaGridSize);
00169         delete[] MEarr;
00170     }
00171 }
```

References `cudaGridSize`, `cudaPerKernelAllocationSize`, `device_outputBuffer`, `device_seeds`, `Markov::API::CUDA::Random::Marsaglia` and `outputBuffer`.

Here is the call graph for this function:



9.6.2.32 RandomWalk()

```
char * Markov::Model< char >::RandomWalk (
    Markov::Random::RandomEngine * randomEngine,
    int minSetting,
    int maxSetting,
    NodeStorageType * buffer ) [inherited]
```

Do a random walk on this model.

Start from the starter node, on each node, invoke RandomNext using the random engine on current node, until terminator node is reached. If terminator node is reached before minimum length criteria is reached, ignore the last selection and re-invoke randomNext

If maximum length criteria is reached but final node is not, cut off the generation and proceed to the final node. This function takes [Markov::Random::RandomEngine](#) as a parameter to generate pseudo random numbers from

This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne output is higher in entropy, most use cases don't really need super high entropy output, so [Markov::Random::Marsaglia](#) is preferable for better performance.

This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening via maximum length criteria.

Example Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use Marsaglia

```
Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}
```

Parameters

<i>randomEngine</i>	Random Engine to use for the random walks. For examples, see Markov::Random::Mersenne and Markov::Random::Marsaglia
<i>minSetting</i>	Minimum number of characters to generate
<i>maxSetting</i>	Maximum number of character to generate
<i>buffer</i>	buffer to write the result to

Returns

Null terminated string that was generated.

Definition at line 307 of file [model.h](#).

```
00307
00308     Markov::Node<NodeStorageType>* n = this->starterNode;
00309     int len = 0;
00310     Markov::Node<NodeStorageType>* temp_node;
00311     while (true) {
00312         temp_node = n->RandomNext(randomEngine);
00313         if (len >= maxSetting) {
00314             break;
00315         }
00316     }
```

```

00316     else if ((temp_node == NULL) && (len < minSetting)) {
00317         continue;
00318     }
00319
00320     else if (temp_node == NULL) {
00321         break;
00322     }
00323
00324     n = temp_node;
00325
00326     buffer[len++] = n->NodeValue();
00327 }
00328
00329 //null terminate the string
00330 buffer[len] = 0x00;
00331
00332 //do something with the generated string
00333 return buffer; //for now
00334 }
```

9.6.2.33 Save()

```
std::ofstream * Markov::API::MarkovPasswords::Save (
    const char * filename ) [inherited]
Export model to file.
```

Parameters

<i>filename</i>	- Export filename.
-----------------	--------------------

Returns

`std::ofstream*` of the exported file.


Definition at line 106 of file [markovPasswords.cpp](#).

```

00106
00107     std::ofstream* exportFile;
00108
00109     std::ofstream newFile(filename);
00110
00111     exportFile = &newFile;
00112
00113     this->Export(exportFile);
00114     return exportFile;
00115 }
```

References [Markov::Model< NodeStorageType >::Export\(\)](#).

Here is the call graph for this function:



9.6.2.34 StarterNode()

```
Node<char>*> Markov::Model< char >::StarterNode ( ) [inline], [inherited]
Return starter Node.
```

Returns

starter node with 00 NodeValue

Definition at line 171 of file [model.h](#).

```
00171 { return starterNode; }
```

9.6.2.35 Train()

```
void Markov::API::ModelMatrix::Train (
    const char * datasetFileName,
    char delimiter,
    int threads ) [inherited]
```

Train the model with the dataset file.

Parameters

<i>datasetFileName</i>	- ifstream* to the dataset. If null, use class member
<i>delimiter</i>	- a character, same as the delimiter in dataset content
<i>threads</i>	- number of OS threads to spawn

```
Markov::API::MarkovPasswords mp;
mp.Import("models/2gram.mdl");
mp.Train("password.corpus");
```

Construct the matrix when done.


Definition at line 25 of file [modelMatrix.cpp](#).

```
00025
00026     this->DeallocateMatrix();
00027     this->Markov::API::MarkovPasswords::Train(datasetFileName,delimiter,threads);
00028     this->ConstructMatrix();
00029 }
```


References [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), and [Markov::API::MarkovPasswords::Train\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.2.36 TrainThread()

```
void Markov::API::MarkovPasswords::TrainThread (
    Markov::API::Concurrency::ThreadSharedListHandler * listhandler,
    char delimiter ) [private], [inherited]
```

A single thread invoked by the Train function.

Parameters


<i>listhandler</i>	- Listhandler class to read corpus from
<i>delimiter</i>	- a character, same as the delimiter in dataset content

Definition at line 85 of file [markovPasswords.cpp](#).


```
00085
00086     char format_str[] = "%ld,%s";
00087     format_str[3]=delimiter;
00088     std::string line;
00089     while (listhandler->next(&line) && keepRunning) {
00090         long int oc;
00091         if (line.size() > 100) {
00092             line = line.substr(0, 100);
00093         }
00094         char* linebuf = new char[line.length()+5];
00095 #ifdef _WIN32
00096         sscanf_s(line.c_str(), "%ld,%s", &oc, linebuf, line.length()+5); //<== changed format_str to-
00097         "%ld,%s"
00098     else
00099         sscanf(line.c_str(), format_str, &oc, linebuf);
00100 #endif
00101     this->AdjustEdge((const char*)linebuf, oc);
00102     delete linebuf;
00103 }
```

References [Markov::Model< NodeStorageType >::AdjustEdge\(\)](#), [keepRunning](#), and [Markov::API::Concurrency::ThreadSharedListHandler::next](#).
Referenced by [Markov::API::MarkovPasswords::Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.6.3 Member Data Documentation

9.6.3.1 alternatingKernels

`int Markov::API::CUDA::CUDAModelMatrix::alternatingKernels [private]`

Definition at line 135 of file [cudaModelMatrix.h](#).

Referenced by [FastRandomWalk\(\)](#).

9.6.3.2 cudaBlocks

`int Markov::API::CUDA::CUDAModelMatrix::cudaBlocks [private]`

Definition at line 125 of file [cudaModelMatrix.h](#).

Referenced by [FastRandomWalk\(\)](#).

9.6.3.3 cudaGridSize

`int Markov::API::CUDA::CUDAModelMatrix::cudaGridSize [private]`

Definition at line 131 of file [cudaModelMatrix.h](#).

Referenced by [FastRandomWalk\(\)](#), and [prepKernelMemoryChannel\(\)](#).

9.6.3.4 cudaMemPerGrid

`int Markov::API::CUDA::CUDAModelMatrix::cudaMemPerGrid [private]`

Definition at line 132 of file [cudaModelMatrix.h](#).

Referenced by [FastRandomWalk\(\)](#), and [GatherAsyncKernelOutput\(\)](#).

9.6.3.5 cudaPerKernelAllocationSize

`long int Markov::API::CUDA::CUDAModelMatrix::cudaPerKernelAllocationSize [private]`

Definition at line 133 of file [cudaModelMatrix.h](#).

Referenced by [FastRandomWalk\(\)](#), [GatherAsyncKernelOutput\(\)](#), and [prepKernelMemoryChannel\(\)](#).

9.6.3.6 cudastreams

`cudaStream_t* Markov::API::CUDA::CUDAModelMatrix::cudastreams [private]`

Definition at line 139 of file [cudaModelMatrix.h](#).

9.6.3.7 cudaThreads

int Markov::API::CUDA::CUDAModelMatrix::cudaThreads [private]

Definition at line 126 of file [cudaModelMatrix.h](#).

Referenced by [FastRandomWalk\(\)](#).

9.6.3.8 datasetFile

std::ifstream* Markov::API::MarkovPasswords::datasetFile [private], [inherited]

Definition at line 123 of file [markovPasswords.h](#).

9.6.3.9 device_edgeMatrix

char* Markov::API::CUDA::CUDAModelMatrix::device_edgeMatrix [private]

VRAM Address pointer of edge matrix (from [modelMatrix.h](#))

Definition at line 88 of file [cudaModelMatrix.h](#).

9.6.3.10 device_matrixIndex

char* Markov::API::CUDA::CUDAModelMatrix::device_matrixIndex [private]

VRAM Address pointer of matrixIndex (from [modelMatrix.h](#))

Definition at line 98 of file [cudaModelMatrix.h](#).

9.6.3.11 device_outputBuffer

char** Markov::API::CUDA::CUDAModelMatrix::device_outputBuffer [private]

RandomWalk results in device.

Definition at line 108 of file [cudaModelMatrix.h](#).

Referenced by [prepKernelMemoryChannel\(\)](#).

9.6.3.12 device_seeds

unsigned long** Markov::API::CUDA::CUDAModelMatrix::device_seeds [private]

Definition at line 137 of file [cudaModelMatrix.h](#).

Referenced by [prepKernelMemoryChannel\(\)](#).

9.6.3.13 device_totalEdgeWeights

long int* Markov::API::CUDA::CUDAModelMatrix::device_totalEdgeWeights [private]

VRAM Address pointer of total edge weights (from [modelMatrix.h](#))

Definition at line 103 of file [cudaModelMatrix.h](#).

9.6.3.14 device_valueMatrix

long int* Markov::API::CUDA::CUDAModelMatrix::device_valueMatrix [private]

VRAM Address pointer of value matrix (from [modelMatrix.h](#))

Definition at line 93 of file [cudaModelMatrix.h](#).

9.6.3.15 edgeMatrix

char** Markov::API::ModelMatrix::edgeMatrix [protected], [inherited]

2-D Character array for the edge Matrix (The characters of Nodes)

Definition at line 175 of file [modelMatrix.h](#).

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), and [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

9.6.3.16 edges

```
std::vector<Edge<char>*> Markov::Model< char >::edges [private], [inherited]
```

A list of all edges in this model.

Definition at line 204 of file [model.h](#).

9.6.3.17 flatEdgeMatrix

```
char* Markov::API::CUDAModelMatrix::flatEdgeMatrix [private]
```

Adding [Edge](#) matrix end-to-end and resize to 1-D array for better perfomance on traversing.

Definition at line 118 of file [cudaModelMatrix.h](#).

Referenced by [FlattenMatrix\(\)](#).

9.6.3.18 flatValueMatrix

```
long int* Markov::API::CUDAModelMatrix::flatValueMatrix [private]
```

Adding Value matrix end-to-end and resize to 1-D array for better perfomance on traversing.

Definition at line 123 of file [cudaModelMatrix.h](#).

Referenced by [FlattenMatrix\(\)](#).

9.6.3.19 iterationsPerKernelThread

```
int Markov::API::CUDAModelMatrix::iterationsPerKernelThread [private]
```

Definition at line 127 of file [cudaModelMatrix.h](#).

Referenced by [FastRandomWalk\(\)](#).

9.6.3.20 matrixIndex

```
char* Markov::API::ModelMatrix::matrixIndex [protected], [inherited]
```

to hold the Matrix index (To hold the orders of 2-D arrays')

Definition at line 190 of file [modelMatrix.h](#).

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), and [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

9.6.3.21 matrixSize

```
int Markov::API::ModelMatrix::matrixSize [protected], [inherited]
```

to hold Matrix size

Definition at line 185 of file [modelMatrix.h](#).

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#), and [FlattenMatrix\(\)](#).

9.6.3.22 modelSavefile

```
std::ofstream* Markov::API::MarkovPasswords::modelSavefile [private], [inherited]
```

Dataset file input of our system

Definition at line 124 of file [markovPasswords.h](#).

9.6.3.23 nodes

std::map<char , Node<char *>> Markov::Model< char >::nodes [private], [inherited]
Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
Definition at line 193 of file [model.h](#).

9.6.3.24 numberOfPartitions

int Markov::API::CUDA::CUDAModelMatrix::numberOfPartitions [private]
Definition at line 130 of file [cudaModelMatrix.h](#).
Referenced by [FastRandomWalk\(\)](#).

9.6.3.25 outputBuffer

char** Markov::API::CUDA::CUDAModelMatrix::outputBuffer [private]
RandomWalk results in host.
Definition at line 113 of file [cudaModelMatrix.h](#).
Referenced by [GatherAsyncKernelOutput\(\)](#), and [prepKernelMemoryChannel\(\)](#).

9.6.3.26 outputFile

std::ofstream* Markov::API::MarkovPasswords::outputFile [private], [inherited]
File to save model of our system

Definition at line 125 of file [markovPasswords.h](#).

9.6.3.27 ready

bool Markov::API::ModelMatrix::ready [protected], [inherited]
True when matrix is constructed. False if not.
Definition at line 200 of file [modelMatrix.h](#).
Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), and [Markov::API::ModelMatrix::ModelMatrix\(\)](#).

9.6.3.28 starterNode

Node<char *>* Markov::Model< char >::starterNode [private], [inherited]
Starter [Node](#) of this model.
Definition at line 198 of file [model.h](#).

9.6.3.29 totalEdgeWeights

long int* Markov::API::ModelMatrix::totalEdgeWeights [protected], [inherited]
Array of the Total [Edge](#) Weights.
Definition at line 195 of file [modelMatrix.h](#).
Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), and [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

9.6.3.30 totalOutputPerKernel

long int Markov::API::CUDA::CUDAModelMatrix::totalOutputPerKernel [private]
Definition at line 129 of file [cudaModelMatrix.h](#).
Referenced by [FastRandomWalk\(\)](#).

9.6.3.31 totalOutputPerSync

```
long int Markov::API::CUDA::CUDAModelMatrix::totalOutputPerSync [private]
```

Definition at line 128 of file [cudaModelMatrix.h](#).

Referenced by [FastRandomWalk\(\)](#).

9.6.3.32 valueMatrix

```
long int** Markov::API::ModelMatrix::valueMatrix [protected], [inherited]
```

2-d Integer array for the value Matrix (For the weights of Edges)

Definition at line 180 of file [modelMatrix.h](#).

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#), [Markov::API::ModelMatrix::DeallocateMatrix\(\)](#), [Markov::API::ModelMatrix::DumpJSON\(\)](#), and [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

The documentation for this class was generated from the following files:

- [cudaModelMatrix.h](#)


- [cudaModelMatrix.cu](#)

9.7 Markov::Random::DefaultRandomEngine Class Reference


Implementation using [Random.h](#) default random engine.

```
#include <random.h>
```

Inheritance diagram for Markov::Random::DefaultRandomEngine:



Collaboration diagram for `Markov::Random::DefaultRandomEngine`:



Public Member Functions

- `unsigned long random ()`

Generate Random Number.

Protected Member Functions

- `std::random_device & rd ()`
Default random device for seeding.
- `std::default_random_engine & generator ()`
Default random engine for seeding.
- `std::uniform_int_distribution< long long unsigned > & distribution ()`
Distribution schema for seeding.

9.7.1 Detailed Description

Implementation using `Random.h` default random engine.

This engine is also used by other engines for seeding.

Example Use: Using Default Engine with `RandomWalk`

```

Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::DefaultRandomEngine randomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&randomEngine, 5, 10, res);
    std::cout << res << "\n";
}
  
```

Example Use: Generating a random number with `Marsaglia` Engine

```

Markov::Random::DefaultRandomEngine de;
std::cout << de.random();
  
```

Definition at line 61 of file `random.h`.

9.7.2 Member Function Documentation

9.7.2.1 distribution()

```
std::uniform_int_distribution<long long unsigned>& Markov::Random::DefaultRandomEngine::distribution
( ) [inline], [protected]
```


Distribution schema for seeding.

Definition at line 90 of file [random.h](#).

```
00090
00091     static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00092     return _distribution;
00093 }
```

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [random\(\)](#).

Here is the caller graph for this function:



9.7.2.2 generator()

```
std::default_random_engine& Markov::Random::DefaultRandomEngine::generator ( ) [inline],
[protected]
```

Default random engine for seeding.


Definition at line 82 of file [random.h](#).

```
00082
00083     static std::default_random_engine _generator(rd()());
00084     return _generator;
00085 }
```


References [rd\(\)](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [random\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.7.2.3 random()

`unsigned long Markov::Random::DefaultRandomEngine::random () [inline], [virtual]`
Generate Random Number.

Returns

random number in long range.

Implements [Markov::Random::RandomEngine](#).


Reimplemented in [Markov::Random::Marsaglia](#).

Definition at line 66 of file [random.h](#).

```
00066     {
00067         return this->distribution() (this->generator());
00068     }
```

References [distribution\(\)](#), and [generator\(\)](#).

Here is the call graph for this function:



9.7.2.4 rd()


`std::random_device& Markov::Random::DefaultRandomEngine::rd () [inline], [protected]`
Default random device for seeding.

Definition at line 74 of file [random.h](#).

```
00074     static std::random_device _rd;
00075     return _rd;
00076 }
00077 }
```

Referenced by [generator\(\)](#).

Here is the caller graph for this function:



The documentation for this class was generated from the following file:


- [random.h](#)

9.8 Markov::Edge< NodeStorageType > Class Template Reference

[Edge](#) class used to link nodes in the model together.

```
#include <model.h>
```

Collaboration diagram for Markov::Edge< NodeStorageType >:



Public Member Functions

- [Edge \(\)](#)
Default constructor.
- [Edge \(Node< NodeStorageType > *_left, Node< NodeStorageType > *_right\)](#)
Constructor. Initialize edge with given RightNode and LeftNode.
- void [AdjustEdge \(long int offset\)](#)
Adjust the edge EdgeWeight with offset. Adds the offset parameter to the edge EdgeWeight.
- [Node< NodeStorageType > * TraverseNode \(\)](#)
Traverse this edge to RightNode.
- void [SetLeftEdge \(Node< NodeStorageType > *\)](#)
Set LeftNode of this edge.
- void [SetRightEdge \(Node< NodeStorageType > *\)](#)
Set RightNode of this edge.
- uint64_t [EdgeWeight \(\)](#)
return edge's EdgeWeight.
- [Node< NodeStorageType > * LeftNode \(\)](#)
return edge's LeftNode

- `Node< NodeStorageType > * RightNode ()`
return edge's RightNode

Private Attributes

- `Node< NodeStorageType > * _left`
source node
- `Node< NodeStorageType > * _right`
target node
- long int `_weight`
Edge Edge Weight.

9.8.1 Detailed Description

```
template<typename NodeStorageType>
class Markov::Edge< NodeStorageType >
```

`Edge` class used to link nodes in the model together.

Has LeftNode, RightNode, and EdgeWeight of the edge. Edges are *UNIDIRECTIONAL* in this model. They can only be traversed LeftNode to RightNode.

Definition at line 30 of file `model.h`.

9.8.2 Constructor & Destructor Documentation

9.8.2.1 Edge() [1/2]

```
template<typename NodeStorageType >
Markov::Edge< NodeStorageType >::Edge
Default constructor.
Definition at line 123 of file edge.h.
00123           {
00124     this->_left = NULL;
00125     this->_right = NULL;
00126     this->_weight = 0;
00127 }
```

9.8.2.2 Edge() [2/2]

```
template<typename NodeStorageType >
Markov::Edge< NodeStorageType >::Edge (
    Markov::Node< NodeStorageType > * _left,
    Markov::Node< NodeStorageType > * _right )
Constructor. Initialize edge with given RightNode and LeftNode.
```

Parameters

<code>_left</code>	- Left node of this edge.
<code>_right</code>	- Right node of this edge.

Example Use: Construct edge

```
Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
```

Definition at line 130 of file `edge.h`.

```
00130 {
00131     this->_left = _left;
00132     this->_right = _right;
00133     this->_weight = 0;
```

```
00134 }
```

9.8.3 Member Function Documentation

9.8.3.1 AdjustEdge()

```
template<typename NodeStorageType >
void Markov::Edge< NodeStorageType >::AdjustEdge (
    long int offset )
```

Adjust the edge EdgeWeight with offset. Adds the offset parameter to the edge EdgeWeight.

Parameters

<i>offset</i>	- NodeValue to be added to the EdgeWeight
---------------	---

Example Use: Construct edge


```
Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
e1->AdjustEdge(25);
```

Definition at line 137 of file [edge.h](#).

```
00137
00138     this->weight += offset;
00139     this->LeftNode()->UpdateTotalVerticeWeight(offset);
00140 }
```

Referenced by [Markov::API::MarkovPasswords::Buff\(\)](#).

Here is the caller graph for this function:



9.8.3.2 EdgeWeight()

```
template<typename NodeStorageType >
uint64_t Markov::Edge< NodeStorageType >::EdgeWeight [inline]
return edge's EdgeWeight.
```

Returns


edge's EdgeWeight.

Definition at line 160 of file [edge.h](#).

```
00160
00161     return this->_weight;
00162 }
```

Referenced by [Markov::API::MarkovPasswords::Buff\(\)](#), and [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:

**9.8.3.3 LeftNode()**

```
template<typename NodeStorageType >
Markov::Node< NodeStorageType > * Markov::Edge< NodeStorageType >::LeftNode
return edge's LeftNode
```

Returns

edge's LeftNode.

Definition at line 165 of file [edge.h](#).

```
00165
00166     return this->_left;
00167 }
```

9.8.3.4 RightNode()

```
template<typename NodeStorageType >
Markov::Node< NodeStorageType > * Markov::Edge< NodeStorageType >::RightNode [inline]
return edge's RightNode
```

Returns


edge's RightNode.

Definition at line 170 of file [edge.h](#).

```
00170
00171     return this->_right;
00172 }
```

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:



9.8.3.5 SetLeftEdge()

```
template<typename NodeStorageType >
void Markov::Edge< NodeStorageType >::SetLeftEdge (
    Markov::Node< NodeStorageType > * n )
Set LeftNode of this edge.
```

Parameters

<i>node</i>	- Node to be linked with.
-------------	---------------------------

Definition at line 150 of file [edge.h](#).

```
00150
00151     this->left = n;
00152 }
```

9.8.3.6 SetRightEdge()

```
template<typename NodeStorageType >
void Markov::Edge< NodeStorageType >::SetRightEdge (
    Markov::Node< NodeStorageType > * n )
Set RightNode of this edge.
```

Parameters

<i>node</i>	- Node to be linked with.
-------------	---------------------------

Definition at line 155 of file [edge.h](#).

```
00155
00156     this->right = n;
00157 }
```

9.8.3.7 TraverseNode()

```
template<typename NodeStorageType >
Markov::Node< NodeStorageType > * Markov::Edge< NodeStorageType >::TraverseNode [inline]
Traverse this edge to RightNode.
```

Returns

Right node. If this is a terminator node, return NULL

Example Use: Traverse a node

```
Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
e1->AdjustEdge(25);
Markov::Edge<unsigned char>* e2 = e1->traverseNode();
```

Definition at line 143 of file [edge.h](#).

```
00143
00144     if (this->RightNode() ->NodeValue() == 0xff) //terminator node
00145         return NULL;
00146     return _right;
00147 }
```

9.8.4 Member Data Documentation

9.8.4.1 left

```
template<typename NodeStorageType >
Node<NodeStorageType>* Markov::Edge< NodeStorageType >::_left [private]
```

source node
 Definition at line 105 of file [edge.h](#).

9.8.4.2 _right

```
template<typename NodeStorageType >
Node<NodeStorageType>* Markov::Edge< NodeStorageType >::_right [private]
target node
Definition at line 110 of file edge.h.
Referenced by Markov::Edge< char >::TraverseNode\(\).
```

9.8.4.3 _weight

```
template<typename NodeStorageType >
long int Markov::Edge< NodeStorageType >::_weight [private]
Edge Edge Weight.
Definition at line 115 of file edge.h.
The documentation for this class was generated from the following files:
```


- [model.h](#)
- [edge.h](#)

9.9 Markov::GUI::Generate Class Reference


QT Generation page class.

```
#include <Generate.h>
```

Inheritance diagram for Markov::GUI::Generate:



Collaboration diagram for Markov::GUI::Generate:



Public Slots

- void [home \(\)](#)
- void [generation \(\)](#)
- void [train \(\)](#)
- void [vis \(\)](#)

Public Member Functions

- [Generate \(QWidget *parent=Q_NULLPTR\)](#)

Private Attributes

- [Ui::Generate ui](#)

9.9.1 Detailed Description

QT Generation page class.
Definition at line [15](#) of file [Generate.h](#).

9.9.2 Constructor & Destructor Documentation

9.9.2.1 Generate()

```
Generate::Generate (
    QWidget * parent = Q_NULLPTR )
```

Definition at line 20 of file [Generate.cpp](#).

```

00021     : QMainWindow(parent)
00022 {
00023     ui.setupUi(this);
00024
00025     QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {generation(); });
00026     QObject::connect(ui.pushButton_4, &QPushButton::clicked, this, [this] {home(); });
00027     QObject::connect(ui.pushButton_3, &QPushButton::clicked, this, [this] {train(); });
00028     QObject::connect(ui.pushButton_2, &QPushButton::clicked, this, [this] {vis(); });
00029
00030
00031     ui.pushButton->setVisible(false);
00032     ui.lineEdit->setVisible(false);
00033     ui.lineEdit_2->setVisible(false);
00034     ui.lineEdit_3->setVisible(false);
00035     ui.label_3->setVisible(false);
00036     ui.label_4->setVisible(false);
00037     ui.label_5->setVisible(false);
00038
00039
00040 }
```

References [ui](#).

9.9.3 Member Function Documentation

9.9.3.1 generation

`void Generate::generation () [slot]`

Definition at line 42 of file [Generate.cpp](#).

```

00042
00043
00044
00045
00046
00047     QString file_name = QFileDialog::getOpenFileName(this, "Open a File", QDir::homePath());
00048     QFile file(file_name);
00049
00050
00051
00052     int numberPass = ui.lineEdit->text().toInt();
00053     int minLen = ui.lineEdit_2->text().toInt();
00054     int maxLen = ui.lineEdit_3->text().toInt();
00055     char* cstr;
00056     std::string fname = file_name.toStdString();
00057     cstr = new char[fname.size() + 1];
00058     strcpy(cstr, fname.c_str());
00059
00060     ui.label_6->setText("GENERATING!");
00061
00062     Markov::API::MarkovPasswords mp;
00063     mp.Import("src\CLI\sample_models\2gram-trained.mdl");
00064
00065     mp.Generate(numberPass, cstr, minLen, maxLen);
00066
00067     if (!file.open(QFile::ReadOnly | QFile::Text)) {
00068         QMessageBox::warning(this, "Error", "File Not Open!");
00069     }
00070     QTextStream in(&file);
00071     QString text = in.readAll();
00072     ui.plainTextEdit->setPlainText(text);
00073
00074     ui.label_6->setText("DONE!");
00075
00076
00077
00078     file.close();
00079 }
```

References [Markov::API::MarkovPasswords::Generate\(\)](#), and [ui](#).

Here is the call graph for this function:



9.9.3.2 home


```
void Generate::home ( ) [slot]
Definition at line 121 of file Generate.cpp.
00121
00122     {
00123         CLI* w = new CLI;
00124         w->show();
00125         this->close();
00126 }
```

9.9.3.3 train

```
void Generate::train ( ) [slot]
Definition at line 82 of file Generate.cpp.
00082
00083     {
00084         QString file_name = QFileDialog::getOpenFileName(this, "Open a File", QDir::homePath());
00085         QFile file(file_name);
00086
00087         if (!file.open(QFile::ReadOnly | QFile::Text)) {
00088             QMessageBox::warning(this, "Error", "File Not Open!");
00089         }
00090         QTextStream in(&file);
00091         QString text = in.readAll();
00092
00093         char* cstr;
00094         std::string fname = file_name.toStdString();
00095         cstr = new char[fname.size() + 1];
00096         strcpy(cstr, fname.c_str());
00097
00098
00099
00100         char a = ',';
00101         Markov::API::MarkovPasswords mp;
00102         mp.Import("models\\2gram.mdl");
00103         mp.Train(cstr, a, 10);
00104         mp.Export("models\\finished.mdl");
00105
00106
00107
00108         ui.pushButton->setVisible(true);
00109         ui.lineEdit->setVisible(true);
00110         ui.lineEdit_2->setVisible(true);
00111         ui.lineEdit_3->setVisible(true);
00112         ui.label_3->setVisible(true);
00113         ui.label_4->setVisible(true);
00114         ui.label_5->setVisible(true);
00115
00116         file.close();
00117
00118
00119 }
```

References [Markov::API::MarkovPasswords::Train\(\)](#), and [ui](#).

Here is the call graph for this function:



9.9.3.4 vis

```
void Generate::vis ( ) [slot]
Definition at line 126 of file Generate.cpp.
```

```
00126      {
00127      MarkovPasswordsGUI* w = new MarkovPasswordsGUI;
00128      w->show();
00129      this->close();
00130 }
```

9.9.4 Member Data Documentation

9.9.4.1 ui


Ui::Generate Markov::GUI::Generate::ui [private]
Definition at line 21 of file [Generate.h](#).
Referenced by [Generate\(\)](#), [generation\(\)](#), and [train\(\)](#).
The documentation for this class was generated from the following files:

- [Generate.h](#)
- [Generate.cpp](#)


9.10 Markov::API::MarkovPasswords Class Reference

[Markov::Model](#) with char represented nodes.
`#include <markovPasswords.h>`

Inheritance diagram for Markov::API::MarkovPasswords:



Collaboration diagram for Markov::API::MarkovPasswords:



Public Member Functions

- **MarkovPasswords ()**
Initialize the markov model from MarkovModel::Markov::Model.
 - **MarkovPasswords (const char *filename)**
Initialize the markov model from MarkovModel::Markov::Model, with an import file.
 - **std::ifstream * OpenDatasetFile (const char *filename)**
Open dataset file and return the ifstream pointer.
 - void **Train (const char *datasetFileName, char delimiter, int threads)**
Train the model with the dataset file.
 - std::ofstream * **Save (const char *filename)**
Export model to file.
 - void **Generate (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20)**
Call Markov::Model::RandomWalk n times, and collect output.
 - void **Buff (const char *str, double multiplier, bool bDontAdjustSelfLoops=true, bool bDontAdjustExtendedLoops=false)**
Buff expression of some characters in the model.

- `char * RandomWalk (Markov::Random::RandomEngine *randomEngine, int minSetting, int maxSetting, char *buffer)`
Do a random walk on this model.
- `void AdjustEdge (const char *payload, long int occurrence)`
Adjust the model with a single string.
- `bool Import (std::ifstream *)`
Import a file to construct the model.
- `bool Import (const char *filename)`
Open a file to import with filename, and call bool Model::Import with std::ifstream.
- `bool Export (std::ofstream *)`
Export a file of the model.
- `bool Export (const char *filename)`
Open a file to export with filename, and call bool Model::Export with std::ofstream.
- `Node< char > * StarterNode ()`
Return starter Node.
- `std::vector< Edge< char > * > * Edges ()`
Return a vector of all the edges in the model.
- `std::map< char, Node< char > * > * Nodes ()`
Return starter Node.
- `void OptimizeEdgeOrder ()`
Sort edges of all nodes in the model ordered by edge weights.

Private Member Functions

- `void TrainThread (Markov::API::Concurrency::ThreadSharedListHandler *listhandler, char delimiter)`
A single thread invoked by the Train function.
- `void GenerateThread (std::mutex *outputLock, unsigned long int n, std::ofstream *wordlist, int minLen, int maxLen)`
A single thread invoked by the Generate function.

Private Attributes

- `std::ifstream * datasetFile`
Dataset file input of our system
- `std::ofstream * modelSavefile`
File to save model of our system
- `std::map< char, Node< char > * > nodes`
Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
- `Node< char > * starterNode`
Starter Node of this model.
- `std::vector< Edge< char > * > edges`
A list of all edges in this model.

9.10.1 Detailed Description

`Markov::Model` with `char` represented nodes.

Includes wrappers for `Markov::Model` and additional helper functions to handle file I/O

This class is an extension of `Markov::Model<char>`, with higher level abstractions such as train and generate.

Definition at line 26 of file `markovPasswords.h`.

9.10.2 Constructor & Destructor Documentation

9.10.2.1 MarkovPasswords() [1/2]

```
Markov::API::MarkovPasswords::MarkovPasswords ( )
Initialize the markov model from MarkovModel::Markov::Model.
Parent constructor. Has no extra functionality.
Definition at line 34 of file markovPasswords.cpp.
00034 : Markov::Model<char> () {
00035
00036
00037 }
```

9.10.2.2 MarkovPasswords() [2/2]

```
Markov::API::MarkovPasswords::MarkovPasswords (
    const char * filename )
Initialize the markov model from MarkovModel::Markov::Model, with an import file.
This function calls the Markov::Model::Import on the filename to construct the model. Same thing as creating an empty model, and calling MarkovPasswords::Import on the filename.
```

Parameters

<i>filename</i>	- Filename to import
-----------------	----------------------

Example Use: Construction via filename


```
MarkovPasswords mp("test.mdl");
```

Definition at line 39 of file markovPasswords.cpp.

```
00039
00040
00041     std::ifstream* importFile;
00042
00043     this->Import(filename);
00044
00045 //std::ifstream* newFile(filename);
00046
00047 //importFile = newFile;
00048
00049 }
```

References [Markov::Model< NodeStorageType >::Import\(\)](#).

Here is the call graph for this function:



9.10.3 Member Function Documentation

9.10.3.1 AdjustEdge()

```
void Markov::Model< char >::AdjustEdge (
    const char * payload,
    long int occurrence ) [inherited]
```

Adjust the model with a single string.

Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from current node to the next, until NULL character is reached.

Then, update the edge EdgeWeight from current node, to the terminator node.

This function is used for training purposes, as it can be used for adjusting the model with each line of the corpus file.

Example Use: Create an empty model and train it with string: "testdata"

```
Markov::Model<char> model;
char test[] = "testdata";
model.AdjustEdge(test, 15);
```

Parameters

<i>string</i>	- String that is passed from the training, and will be used to AdjustEdge the model with
<i>occurrence</i>	- Occurrence of this string.

Definition at line 337 of file [model.h](#).

```
00337
00338     NodeStorageType p = payload[0];
00339     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00340     Markov::Edge<NodeStorageType>* e;
00341     int i = 0;
00342
00343     if (p == 0) return;
00344     while (p != 0) {
00345         e = curnode->FindEdge(p);
00346         if (e == NULL) return;
00347         e->AdjustEdge(occurrence);
00348         curnode = e->RightNode();
00349         p = payload[++i];
00350     }
00351
00352     e = curnode->FindEdge('\xff');
00353     e->AdjustEdge(occurrence);
00354
00355 }
```

9.10.3.2 Buff()

```
void Markov::API::MarkovPasswords::Buff (
    const char * str,
    double multiplier,
    bool bDontAdjustSelfLoops = true,
    bool bDontAdjustExtendedLoops = false )
```

Buff expression of some characters in the model.

Parameters

<i>str</i>	A string containing all the characters to be buffed
<i>multiplier</i>	A constant value to buff the nodes with.
<i>bDontAdjustSelfEdges</i>	Do not adjust weights if target node is same as source node
<i>bDontAdjustExtendedLoops</i>	Do not adjust if both source and target nodes are in first parameter

Definition at line 153 of file [markovPasswords.cpp](#).

```
00153
00154     std::string buffstr(str);
00155     std::map< char, Node< char > * > *nodes;
00156     std::map< char, Edge< char > * > *edges;
00157     nodes = this->Nodes();
00158     int i=0;
00159     for (auto const& [repr, node] : *nodes){
00160         edges = node->Edges();
00161         for (auto const& [targetrepr, edge] : *edges){
00162             if(buffstr.find(targetrepr)!= std::string::npos){
00163                 if(bDontAdjustSelfLoops && repr==targetrepr) continue;
00164                 if(bDontAdjustExtendedLoops){
00165                     if(buffstr.find(repr)!= std::string::npos){
00166                         continue;
00167                     }
00168                 }
00169             }
00170         }
00171     }
00172 }
```


```

00168         }
00169         long int weight = edge->EdgeWeight();
00170         weight = weight*multiplier;
00171         edge->AdjustEdge(weight);
00172     }
00173 }
00174     i++;
00175 }
00176 }
00177 this->OptimizeEdgeOrder();
00178
00179 }
```


References [Markov::Edge< NodeStorageType >::AdjustEdge\(\)](#), [Markov::Node< storageType >::Edges\(\)](#), [Markov::Edge< NodeStorageType >::EdgeWeight\(\)](#), [Markov::Model< NodeStorageType >::Nodes\(\)](#), and [Markov::Model< NodeStorageType >::OptimizeEdgeOrder\(\)](#).

Referenced by [main\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.10.3.3 Edges()

`std::vector<Edge<char>*>* Markov::Model< char >::Edges [inline], [inherited]`
Return a vector of all the edges in the model.

Returns

`vector of edges`

Definition at line 176 of file [model.h](#).

```
00176 { return &edges; }
```

9.10.3.4 Export() [1/2]

```
bool Markov::Model< char >::Export (
    const char * filename ) [inherited]
```

Open a file to export with filename, and call bool [Model::Export](#) with std::ofstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Export file to filename

```
Markov::Model<char> model;
```

```
model.Export("test.mdl");
```

Definition at line 300 of file [model.h](#).

```
00300
00301     std::ofstream exportfile;
00302     exportfile.open(filename);
00303     return this->Export(&exportfile);
00304 }
```

9.10.3.5 Export() [2/2]

```
bool Markov::Model< char >::Export (
    std::ofstream * f ) [inherited]
```

Export a file of the model.

File contains a list of edges. Format is: Left_repr;EdgeWeight;right_repr. For more information on the format, check out the project wiki or github readme.

Iterate over this vertices, and their edges, and write them to file.

Returns

True if successful, False for incomplete models.

Example Use: Export file to ofstream

```
Markov::Model<char> model;
std::ofstream file("test.mdl");
model.Export(&file);
```

Definition at line 288 of file [model.h](#).

```
00288
00289     Markov::Edge<NodeStorageType>* e;
00290     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00291         e = this->edges[i];
00292         //std::cout << e->LeftNode() ->NodeValue() << "," << e->EdgeWeight() << "," <<
00293         //e->RightNode() ->NodeValue() << "\n";
00294         *f << e->LeftNode() ->NodeValue() << "," << e->EdgeWeight() << "," << e->RightNode() ->NodeValue() <<
00295         "\n";
00296     }
00297     return true;
00298 }
```

9.10.3.6 Generate()

```
void Markov::API::MarkovPasswords::Generate (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20 )
```

Call [Markov::Model::RandomWalk](#) n times, and collect output.

Generate from model and write results to a file. a much more performance-optimized method. [FastRandomWalk](#) will reduce the runtime by %96.5 on average.

Deprecated See [Markov::API::MatrixModel::FastRandomWalk](#) for more information.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn

Definition at line 118 of file [markovPasswords.cpp](#).


```

00118
00119     char* res;
00120     char print[100];
00121     std::ofstream wordlist;
00122     wordlist.open(wordlistFileName);
00123     std::mutex mlock;
00124     int iterationsPerThread = n/threads;
00125     int iterationsCarryOver = n%threads;
00126     std::vector<std::thread*> threadsV;
00127     for(int i=0;i<threads;i++) {
00128         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::GenerateThread, this,
00129                                         &mlock, iterationsPerThread, &wordlist, minLen, maxLen));
00130     }
00131     for(int i=0;i<threads;i++) {
00132         threadsV[i] ->join();
00133         delete threadsV[i];
00134     }
00135     this->GenerateThread(&mlock, iterationsCarryOver, &wordlist, minLen, maxLen);
00136
00137
00138 }
```


References [GenerateThread\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [Markov::GUI::Generate::generation\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.10.3.7 GenerateThread()

```

void Markov::API::MarkovPasswords::GenerateThread (
    std::mutex * outputLock,
    unsigned long int n,
    std::ofstream * wordlist,
```

```
int minLen,
int maxLen ) [private]
```

A single thread invoked by the Generate function.

DEPRECATED: See `Markov::API::MatrixModel::FastRandomWalkThread` for more information. This has been replaced with a much more performance-optimized method. `FastRandomWalk` will reduce the runtime by %96.5 on average.

Parameters

<code>outputLock</code>	- shared mutex lock to lock during output operation. Prevents race condition on write.
<code>n</code>	number of lines to be generated by this thread
<code>wordlist</code>	wordlistfile
<code>minLen</code>	- Minimum password length to generate
<code>maxLen</code>	- Maximum password length to generate


Definition at line 140 of file `markovPasswords.cpp`.

```
00140
00141     char* res = new char[maxLen+5];
00142     if(n==0) return;
00143
00144     Markov::Random::Marsaglia MarsagliaRandomEngine;
00145     for (int i = 0; i < n; i++) {
00146         this->RandomWalk(&MarsagliaRandomEngine, minLen, maxLen, res);
00147         outputLock->lock();
00148         *wordlist << res << "\n";
00149         outputLock->unlock();
00150     }
00151 }
```

References `Markov::Model< NodeStorageType >::RandomWalk()`.

Referenced by `Generate()`.

Here is the call graph for this function:



Here is the caller graph for this function:



9.10.3.8 Import() [1/2]

```
bool Markov::Model< char >::Import (
    const char * filename ) [inherited]
```

Open a file to import with `filename`, and call `bool Model::Import` with `std::ifstream`.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file with filename

```
Markov::Model<char> model;
model.Import("test.mdl");
```

Definition at line 280 of file model.h.

```
00280
00281     std::ifstream importfile;
00282     importfile.open(filename);
00283     return this->Import(&importfile);
00284
00285 }
```

9.10.3.9 Import() [2/2]

```
bool Markov::Model< char >::Import (
    std::ifstream * f ) [inherited]
```

Import a file to construct the model.

File contains a list of edges. For more info on the file format, check out the wiki and github readme pages. Format is: Left_repr;EdgeWeight;right_repr

Iterate over this list, and construct nodes and edges accordingly.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file from ifstream

```
Markov::Model<char> model;
std::ifstream file("test.mdl");
model.Import(&file);
```

Definition at line 216 of file model.h.

```
00216
00217     std::string cell;
00218
00219     char src;
00220     char target;
00221     long int oc;
00222
00223     while (std::getline(*f, cell)) {
00224         //std::cout << "cell: " << cell << std::endl;
00225         src = cell[0];
00226         target = cell[cell.length() - 1];
00227         char* j;
00228         oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(), &j, 10);
00229         //std::cout << oc << "\n";
00230         Markov::Node<NodeStorageType>* srcN;
00231         Markov::Node<NodeStorageType>* targetN;
00232         Markov::Edge<NodeStorageType>* e;
00233         if (this->nodes.find(src) == this->nodes.end()) {
00234             srcN = new Markov::Node<NodeStorageType>(src);
00235             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(src, srcN));
00236             //std::cout << "Creating new node at start.\n";
00237         }
00238         else {
00239             srcN = this->nodes.find(src)->second;
00240         }
00241
00242         if (this->nodes.find(target) == this->nodes.end()) {
00243             targetN = new Markov::Node<NodeStorageType>(target);
00244             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(target, targetN));
00245             //std::cout << "Creating new node at end.\n";
00246         }
00247         else {
00248             targetN = this->nodes.find(target)->second;
00249         }
00250         e = srcN->Link(targetN);
00251         e->AdjustEdge(oc);
00252         this->edges.push_back(e);
00253
00254         //std::cout << int(srcN->NodeValue()) << " --" << e->EdgeWeight() << "--> " <<
00255         int(targetN->NodeValue()) << "\n";
00256
00257     }
00258
00259     this->OptimizeEdgeOrder();
00260 }
```

```
00261     return true;
00262 }
```

9.10.3.10 Nodes()

`std::map<char , Node<char *>>* Markov::Model< char >::Nodes [inline], [inherited]`
 Return starter Node.

Returns

starter node with 00 NodeValue

Definition at line 181 of file [model.h](#).

```
00181 { return &nodes; }
```

9.10.3.11 OpenDatasetFile()

```
std::ifstream * Markov::API::MarkovPasswords::OpenDatasetFile (
    const char * filename )
```

Open dataset file and return the ifstream pointer.

Parameters

<code>filename</code>	- Filename to open
-----------------------	--------------------

Returns

`ifstream*` to the the dataset file


Definition at line 51 of file [markovPasswords.cpp](#).

```
00051
00052
00053     std::ifstream* datasetFile;
00054
00055     std::ifstream newFile(filename);
00056
00057     datasetFile = &newFile;
00058
00059     this->Import(datasetFile);
00060     return datasetFile;
00061 }
```

{

References [Markov::Model< NodeStorageType >::Import\(\)](#).

Here is the call graph for this function:



9.10.3.12 OptimizeEdgeOrder()

`void Markov::Model< char >::OptimizeEdgeOrder [inherited]`

Sort edges of all nodes in the model ordered by edge weights.

Definition at line 265 of file [model.h](#).

```
00265
00266     for (std::pair<unsigned char, Markov::Node<NodeStorageType*>> const& x : this->nodes) {
00267         //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
```

```

00268     std::sort (x.second->edgesV.begin(), x.second->edgesV.end(), [] (Edge<NodeStorageType> *lhs,
00269         Edge<NodeStorageType> *rhs) >bool{
00270         return lhs->EdgeWeight() > rhs->EdgeWeight();
00271     });
00272     //for(int i=0;i<x.second->edgesV.size();i++)
00273     // std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00274     //std::cout << "\n";
00275     //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00276     //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00277 }

```

9.10.3.13 RandomWalk()

```

char * Markov::Model< char >::RandomWalk (
    Markov::Random::RandomEngine * randomEngine,
    int minSetting,
    int maxSetting,
    char * buffer ) [inherited]

```

Do a random walk on this model.

Start from the starter node, on each node, invoke RandomNext using the random engine on current node, until terminator node is reached. If terminator node is reached before minimum length criteria is reached, ignore the last selection and re-invoke randomNext

If maximum length criteria is reached but final node is not, cut off the generation and proceed to the final node. This function takes [Markov::Random::RandomEngine](#) as a parameter to generate pseudo random numbers from

This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne output is higher in entropy, most use cases don't really need super high entropy output, so [Markov::Random::Marsaglia](#) is preferable for better performance.

This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening via maximum length criteria.

Example Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use Marsaglia

```

Markov::Model<char> model;
Model import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}

```

Parameters

<i>randomEngine</i>	Random Engine to use for the random walks. For examples, see Markov::Random::Mersenne and Markov::Random::Marsaglia
<i>minSetting</i>	Minimum number of characters to generate
<i>maxSetting</i>	Maximum number of character to generate
<i>buffer</i>	buffer to write the result to

Returns

Null terminated string that was generated.

Definition at line 307 of file [model.h](#).

```

00307
00308     Markov::Node<NodeStorageType>* n = this->starterNode;
00309     int len = 0;
00310     Markov::Node<NodeStorageType>* temp_node;
00311     while (true) {
00312         temp_node = n->RandomNext(randomEngine);
00313         if (len >= maxSetting) {
00314             break;
00315         }
00316         else if ((temp_node == NULL) && (len < minSetting)) {
00317             continue;
00318         }
00319         else if (temp_node == NULL) {

```

```

00321         break;
00322     }
00323     n = temp_node;
00324     buffer[len++] = n->NodeValue();
00325   }
00326   //null terminate the string
00327   buffer[len] = 0x00;
00328   //do something with the generated string
00329   return buffer; //for now
00330 }
00331
00332 }
```

9.10.3.14 Save()

```
std::ofstream * Markov::API::MarkovPasswords::Save (
    const char * filename )
```

Export model to file.

Parameters

<i>filename</i>	- Export filename.
-----------------	--------------------

Returns

`std::ofstream*` of the exported file.


Definition at line 106 of file [markovPasswords.cpp](#).

```

00106
00107     std::ofstream* exportFile;
00108
00109     std::ofstream newFile(filename);
00110
00111     exportFile = &newFile;
00112
00113     this->Export(exportFile);
00114     return exportFile;
00115 }
```

References [Markov::Model< NodeStorageType >::Export\(\)](#).

Here is the call graph for this function:



9.10.3.15 StarterNode()

```
Node<char>*> Markov::Model< char >::StarterNode [inline], [inherited]
```

Return starter Node.

Returns

starter node with 00 NodeValue

Definition at line 171 of file [model.h](#).

```
00171 { return starterNode; }
```

9.10.3.16 Train()

```
void Markov::API::MarkovPasswords::Train (
    const char * datasetFileName,
    char delimiter,
    int threads )
```

Train the model with the dataset file.

Parameters

<i>datasetFileName</i>	- ifstream* to the dataset. If null, use class member
<i>delimiter</i>	- a character, same as the delimiter in dataset content
<i>threads</i>	- number of OS threads to spawn

```
Markov::API::MarkovPasswords mp;
mp.Import("models/2gram.mdl");
mp.Train("password.corpus");
```


Definition at line 65 of file [markovPasswords.cpp](#).

```
00065
00066     signal(SIGINT, intHandler);
00067     Markov::API::Concurrency::ThreadSharedListHandler listhandler(datasetFileName);
00068     auto start = std::chrono::high_resolution_clock::now();
00069
00070     std::vector<std::thread*> threadsV;
00071     for(int i=0;i<threads;i++) {
00072         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::TrainThread, this,
00073                                         &listhandler, delimiter));
00074     }
00075     for(int i=0;i<threads;i++) {
00076         threadsV[i]->join();
00077         delete threadsV[i];
00078     }
00079     auto finish = std::chrono::high_resolution_clock::now();
00080     std::chrono::duration<double> elapsed = finish - start;
00081     std::cout << "Elapsed time: " << elapsed.count() << " s\n";
00082
00083 }
```


References [intHandler\(\)](#), [Markov::API::Concurrency::ThreadSharedListHandler::ThreadSharedListHandler\(\)](#), and [TrainThread\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), [Markov::GUI::Train::train\(\)](#), [Markov::GUI::Generate::train\(\)](#), and [Markov::API::ModelMatrix::Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.10.3.17 TrainThread()

```
void Markov::API::MarkovPasswords::TrainThread (
    Markov::API::Concurrency::ThreadSharedListHandler * listhandler,
    char delimiter ) [private]
```

A single thread invoked by the Train function.

Parameters


<i>listhandler</i>	- Listhandler class to read corpus from
<i>delimiter</i>	- a character, same as the delimiter in dataset content

Definition at line 85 of file markovPasswords.cpp.


```
00085
00086     char format_str[] = "%ld,%s";
00087     format_str[3]=delimiter;
00088     std::string line;
00089     while (listhandler->next(&line) && keepRunning) {
00090         long int oc;
00091         if (line.size() > 100) {
00092             line = line.substr(0, 100);
00093         }
00094         char* linebuf = new char[line.length()+5];
00095 #ifdef _WIN32
00096         sscanf_s(line.c_str(), "%ld,%s", &oc, linebuf, line.length()+5); //<== changed format_str to-
00097         "%ld,%s"
00098     #else
00099         sscanf(line.c_str(), format_str, &oc, linebuf);
00100     #endif
00101     this->AdjustEdge((const char*)linebuf, oc);
00102     delete linebuf;
00103 }
```

References [Markov::Model< NodeStorageType >::AdjustEdge\(\)](#), [keepRunning](#), and [Markov::API::Concurrency::ThreadSharedListHandler::next](#). Referenced by [Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.10.4 Member Data Documentation

9.10.4.1 datasetFile

```
std::ifstream* Markov::API::MarkovPasswords::datasetFile [private]
Definition at line 123 of file markovPasswords.h.
```

9.10.4.2 edges

```
std::vector<Edge<char *>> Markov::Model< char >::edges [private], [inherited]
A list of all edges in this model.
Definition at line 204 of file model.h.
```

9.10.4.3 modelSavefile

```
std::ofstream* Markov::API::MarkovPasswords::modelSavefile [private]
Dataset file input of our system
```

Definition at line 124 of file markovPasswords.h.

9.10.4.4 nodes

```
std::map<char , Node<char *>> Markov::Model< char >::nodes [private], [inherited]
Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
Definition at line 193 of file model.h.
```

9.10.4.5 outputFile

```
std::ofstream* Markov::API::MarkovPasswords::outputFile [private]
File to save model of our system
```

Definition at line 125 of file markovPasswords.h.

9.10.4.6 starterNode

```
Node<char *>* Markov::Model< char >::starterNode [private], [inherited]
Starter Node of this model.
Definition at line 198 of file model.h.
```

The documentation for this class was generated from the following files:


- markovPasswords.h
- markovPasswords.cpp

9.11 Markov::GUI::MarkovPasswordsGUI Class Reference


Reporting UI.

```
#include <MarkovPasswordsGUI.h>
```

Inheritance diagram for Markov::GUI::MarkovPasswordsGUI:



Collaboration diagram for Markov::GUI::MarkovPasswordsGUI:



Public Slots

- void `benchmarkSelected ()`
- void `home ()`
- void `pass ()`
- void `model ()`

Public Member Functions

- `MarkovPasswordsGUI (QWidget *parent=Q_NULLPTR)`

Private Attributes

- `Ui::MarkovPasswordsGUIClass ui`

9.11.1 Detailed Description

Reporting UI.

UI for reporting and debugging tools for MarkovPassword

Definition at line 19 of file [MarkovPasswordsGUI.h](#).

9.11.2 Constructor & Destructor Documentation

9.11.2.1 `MarkovPasswordsGUI()`

```
Markov::GUI::MarkovPasswordsGUI::MarkovPasswordsGUI (
```

```
    QWidget * parent = Q_NULLPTR )
```

Definition at line 14 of file [MarkovPasswordsGUI.cpp](#).

```

00014                               : QMainWindow(parent){
00015     ui.setupUi(this);
00016
00017
00018     QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {home(); });
00019     QObject::connect(ui.pushButton_2, &QPushButton::clicked, this, [this] {model(); });
00020     QObject::connect(ui.pushButton_3, &QPushButton::clicked, this, [this] {pass(); });
00021 }

```

References [ui](#).

9.11.3 Member Function Documentation

9.11.3.1 benchmarkSelected

```
void Markov::GUI::MarkovPasswordsGUI::benchmarkSelected () [slot]
```

9.11.3.2 home

```

void MarkovPasswordsGUI::home () [slot]
Definition at line 24 of file MarkovPasswordsGUI.cpp.
00024
00025     {
00026         CLI* w = new CLI;
00027         w->show();
00028     }

```

9.11.3.3 model

```

void MarkovPasswordsGUI::model () [slot]
Definition at line 42 of file MarkovPasswordsGUI.cpp.
00042
00043     {
00044         QWebEngineView* webkit = ui.centralWidget->findChild<QWebEngineView*>("chartArea");
00045
00046         //get working directory
00047         char path[255];
00048         GetCurrentDirectoryA(255, path);
00049
00050         //get absolute path to the layout html
00051         std::string layout = "file:/// " + std::string(path) + "\\views\\index.html";
00052         std::replace(layout.begin(), layout.end(), '\\', '/');
00053         webkit->setUrl(QUrl(layout.c_str()));
00054     }

```

9.11.3.4 pass

```

void MarkovPasswordsGUI::pass () [slot]
Definition at line 29 of file MarkovPasswordsGUI.cpp.
00029
00030     {
00031         QWebEngineView* webkit = ui.centralWidget->findChild<QWebEngineView*>("chartArea");
00032
00033         //get working directory
00034         char path[255];
00035         GetCurrentDirectoryA(255, path);
00036
00037         //get absolute path to the layout html
00038         std::string layout = "file:/// " + std::string(path) + "\\views\\bar.html";
00039         std::replace(layout.begin(), layout.end(), '\\', '/');
00040         webkit->setUrl(QUrl(layout.c_str()));
00041     }

```

9.11.4 Member Data Documentation

9.11.4.1 ui

Ui::MarkovPasswordsGUIClass Markov::GUI::MarkovPasswordsGUI::ui [private]

Definition at line 25 of file [MarkovPasswordsGUI.h](#).

Referenced by [MarkovPasswordsGUI\(\)](#).

The documentation for this class was generated from the following files:

- [MarkovPasswordsGUI.h](#)


- [MarkovPasswordsGUI.cpp](#)

9.12 Markov::Random::Marsaglia Class Reference


Implementation of [Marsaglia Random](#) Engine.

```
#include <random.h>
```

Inheritance diagram for Markov::Random::Marsaglia:



Collaboration diagram for Markov::Random::Marsaglia:



Public Member Functions

- `Marsaglia ()`
Construct `Marsaglia` Engine.
- `unsigned long random ()`
Generate `Random` Number.

Public Attributes

- `unsigned long x`
- `unsigned long y`
- `unsigned long z`

Protected Member Functions

- `std::random_device & rd ()`
Default random device for seeding.
- `std::default_random_engine & generator ()`
Default random engine for seeding.
- `std::uniform_int_distribution< long long unsigned > & distribution ()`
Distribution schema for seeding.

9.12.1 Detailed Description

Implementation of [Marsaglia Random](#) Engine.

This is an implementation of [Marsaglia Random](#) engine, which for most use cases is a better fit than other solutions. Very simple mathematical formula to generate pseudorandom integer, so its crazy fast.

This implementation of the [Marsaglia](#) Engine is seeded by [random.h](#) default random engine. [RandomEngine](#) is only seeded once so its not a performance issue.

Example Use: Using [Marsaglia](#) Engine with [RandomWalk](#)

```
Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}
```

Example Use: Generating a random number with [Marsaglia](#) Engine

```
Markov::Random::Marsaglia me;
```

```
std::cout << me.random();
```

Definition at line [125](#) of file [random.h](#).

9.12.2 Constructor & Destructor Documentation

9.12.2.1 Marsaglia()

[Markov::Random::Marsaglia::Marsaglia](#) () [inline]

Construct [Marsaglia](#) Engine.


Initialize [x](#),[y](#) and [z](#) using the default random engine.

Definition at line [132](#) of file [random.h](#).

```
00132     {
00133         this->x = this->distribution()(this->generator());
00134         this->y = this->distribution()(this->generator());
00135         this->z = this->distribution()(this->generator());
00136         //std::cout << "x: " << x << ", y: " << y << ", z: " << z << "\n";
00137     }
```

References [Markov::Random::DefaultRandomEngine::distribution\(\)](#), [Markov::Random::DefaultRandomEngine::generator\(\)](#), [x](#), [y](#), and [z](#).

Here is the call graph for this function:



9.12.3 Member Function Documentation

9.12.3.1 distribution()

[std::uniform_int_distribution<long long unsigned>](#)& [Markov::Random::DefaultRandomEngine::distribution](#) () [inline], [protected], [inherited]


Distribution schema for seeding.

Definition at line [90](#) of file [random.h](#).

```
00090
00091     static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00092     return _distribution;
00093 }
```

Referenced by [Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the caller graph for this function:



9.12.3.2 generator()

`std::default_random_engine& Markov::Random::DefaultRandomEngine::generator () [inline], [protected], [inherited]`

Default random engine for seeding.

Definition at line 82 of file [random.h](#).

```

00082     static std::default_random_engine _generator(rd()());
00083     return _generator;
00084 }
00085 }
```


References [Markov::Random::DefaultRandomEngine::rd\(\)](#).

Referenced by [Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.12.3.3 random()

`unsigned long Markov::Random::Marsaglia::random () [inline], [virtual]`

Generate Random Number.

Returns

random number in long range.

Reimplemented from [Markov::Random::DefaultRandomEngine](#).


Definition at line 140 of file [random.h](#).

```
00140         unsigned long t;
00141         x ^= x << 16;
00142         x ^= x >> 5;
00143         x ^= x << 1;
00145
00146         t = x;
00147         x = y;
00148         y = z;
00149         z = t ^ x ^ y;
00150
00151     return z;
00152 }
```

References [x](#), [y](#), and [z](#).

Referenced by [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

Here is the caller graph for this function:

**9.12.3.4 rd()**

```
std::random_device& Markov::Random::DefaultRandomEngine::rd () [inline], [protected], [inherited]
```


Default random device for seeding.

Definition at line 74 of file [random.h](#).

```
00074     static std::random_device _rd;
00075     return _rd;
00076 }
00077 }
```

Referenced by [Markov::Random::DefaultRandomEngine::generator\(\)](#).

Here is the caller graph for this function:

**9.12.4 Member Data Documentation****9.12.4.1 x**

`unsigned long Markov::Random::Marsaglia::x`

Definition at line 155 of file [random.h](#).

Referenced by [Marsaglia\(\)](#), [Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM\(\)](#), and [random\(\)](#).

9.12.4.2 y

`unsigned long Markov::Random::Marsaglia::y`

Definition at line 156 of file [random.h](#).

Referenced by [Marsaglia\(\)](#), [Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM\(\)](#), and [random\(\)](#).

9.12.4.3 z

unsigned long Markov::Random::Marsaglia::z
 Definition at line 157 of file [random.h](#).

Referenced by [Marsaglia\(\)](#), [Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM\(\)](#), and [random\(\)](#).
 The documentation for this class was generated from the following file:


- [random.h](#)

9.13 Markov::API::CUDA::Random::Marsaglia Class Reference


Extension of [Markov::Random::Marsaglia](#) which is capable of working on **device** space.

#include <cudarandom.h>

Inheritance diagram for Markov::API::CUDA::Random::Marsaglia:



Collaboration diagram for Markov::API::CUDA::Random::Marsaglia:



Public Member Functions

- `unsigned long random ()`
Generate Random Number.

Static Public Member Functions

- `static unsigned long * MigrateToVRAM (Markov::API::CUDA::Random::Marsaglia *MEarr, long int gridSize)`
Migrate a Marsaglia[] to VRAM as seedChunk.
- `static __host__ void ListCudaDevices ()`
List CUDA devices in the system.

Public Attributes

- `unsigned long x`
- `unsigned long y`
- `unsigned long z`

Protected Member Functions

- `std::random_device & rd ()`

- std::default_random_engine & [generator](#) ()
Default random engine for seeding.
- std::uniform_int_distribution< long long unsigned > & [distribution](#) ()
Distribution schema for seeding.

Static Protected Member Functions

- static __host__ int [CudaCheckNotifyErr](#) (cudaError_t _status, const [char](#) *msg, bool bExit=true)
Check results of the last operation on GPU.
- template<typename T>
 static __host__ [cudaError_t](#) [CudaMalloc2DToFlat](#) (T **dst, int row, int col)
Malloc a 2D array in device space.
- template<typename T>
 static __host__ [cudaError_t](#) [CudaMemcpy2DToFlat](#) (T *dst, T **src, int row, int col)
Memcpy a 2D array in device space after flattening.
- template<typename T>
 static __host__ [cudaError_t](#) [CudaMigrate2DFlat](#) (T **dst, T **src, int row, int col)
Both malloc and memcpy a 2D array into device VRAM.

9.13.1 Detailed Description

Extension of [Markov::Random::Marsaglia](#) which is capable of working on **device** space.
 Implementation of [Marsaglia Random Engine](#). This is an implementation of [Marsaglia Random](#) engine, which for most use cases is a better fit than other solutions. Very simple mathematical formula to generate pseudorandom integer, so its crazy fast.

This implementation of the [Marsaglia](#) Engine is seeded by [random.h](#) default random engine. RandomEngine is only seeded once so its not a performance issue.

Example Use: Using [Marsaglia](#) Engine with RandomWalk

```
Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}
```

Example Use: Generating a random number with [Marsaglia](#) Engine

```
Markov::Random::Marsaglia me;
std::cout << me.random();
```

Definition at line 20 of file [cudarandom.h](#).

9.13.2 Member Function Documentation

9.13.2.1 CudaCheckNotifyErr()

```
__host__ int Markov::API::CUDA::CUDADeviceController::CudaCheckNotifyErr (
    cudaError_t _status,
    const char * msg,
    bool bExit = true) [static], [protected], [inherited]
```

Check results of the last operation on GPU.

Check the status returned from [cudaMalloc](#)/[cudaMemcpy](#) to find failures.

If a failure occurs, its assumed beyond redemption, and exited.

Parameters

_status	Cuda error status to check
msg	Message to print in case of a failure

Returns

0 if successful, 1 if failure. **Example output:**

```
char *da, a = "test";
cudaStatus = cudaMalloc((char **)da, 5*sizeof(char));
CudaCheckNotifyErr(cudaStatus, "Failed to allocate VRAM for *da.\n");
```

Definition at line 32 of file [cudaDeviceController.cu](#).

```
00032
00033     {
00034         if (_status != cudaSuccess) {
00035             std::cerr << "\033[1;31m" << msg << " -> " << cudaGetErrorString(_status) << "(" << _status <
00035             ") " << "\033[0m" << "\n";
00036         if(bExit) {
00037             cudaDeviceReset();
00038             exit(1);
00039         }
00040     }
00041     return 0;
00042 }
```

9.13.2.2 CudaMalloc2DToFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat (
    T ** dst,
    int row,
    int col ) [inline], [static], [protected], [inherited]
```

Malloc a 2D array in device space.

This function will allocate enough space on VRAM for flattened 2D array.

Parameters

<i>dst</i>	destination pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:


```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
if(cudastatus!=cudaSuccess){
    CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
}
```

Definition at line 75 of file [cudaDeviceController.h](#).

```
00075
00076     cudaError_t cudastatus = cudaMalloc((T **)dst, row*col*sizeof(T));
00077     CudaCheckNotifyErr(cudastatus, "cudaMalloc Failed.", false);
00078     return cudastatus;
00079 }
```

References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



9.13.2.3 CudaMemcpy2DToFlat()

```

template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat (
    T * dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected], [inherited]
Memcpy a 2D array in device space after flattening.
Resulting buffer will not be true 2D array.
  
```

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:

```

cudaError_t cudastatus;
char* dst;
cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
cudastatus = CudaMemcpy2DToFlat<char>(*dst,src,15,15);
CudaCheckNotifyErr(cudastatus, " CudaMemcpy2DToFlat Failed.", false);
  
```


Definition at line 103 of file [cudaDeviceController.h](#).

```

00103
00104      T* tempbuf = new T[row*col];
00105      for(int i=0;i<row;i++){
00106          memcpy(&(tempbuf[row*i]), src[i], col);
00107      }
00108      return cudaMemcpy(dst, tempbuf, row*col*sizeof(T), cudaMemcpyHostToDevice);
00109
00110  }
  
```

References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



9.13.2.4 CudaMigrate2DFlat()

```
template<typename T >
static __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat (
    T ** dst,
    T ** src,
    int row,
    int col ) [inline], [static], [protected], [inherited]
```

Both malloc and memcpy a 2D array into device VRAM.
Resulting buffer will not be true 2D array.

Parameters

<i>dst</i>	destination pointer
<i>rc</i>	source pointer
<i>row</i>	row size of the 2d array
<i>col</i>	column size of the 2d array

Returns

cudaError_t status of the cudaMalloc operation

Example output:

```
cudaError_t cudastatus;
char* dst;
cudastatus = CudaMigrate2DFlat<long int>(
    &dst, this->valueMatrix, this->matrixSize, this->matrixSize);
CudaCheckNotifyErr(cudastatus, "    Cuda failed to initialize value matrix row.");
```


Definition at line 132 of file [cudaDeviceController.h](#).

```
00132
00133     cudaError_t cudastatus;
00134     cudastatus = CudaMalloc2DToFlat<T>(dst, row, col);
00135     if(cudastatus!=cudaSuccess){
00136         CudaCheckNotifyErr(cudastatus, "    CudaMalloc2DToFlat Failed.", false);
00137         return cudastatus;
00138     }
00139     cudastatus = CudaMemcpy2DToFlat<T>(*dst,src,row,col);
00140     CudaCheckNotifyErr(cudastatus, "    CudaMemcpy2DToFlat Failed.", false);
00141     return cudastatus;
00142 }
```


References [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Referenced by [Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat\(\)](#), [Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat\(\)](#) and [Markov::API::CUDA::CUDADeviceController::CudaMigrate2DFlat\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.13.2.5 distribution()

```
std::uniform_int_distribution<long long unsigned>& Markov::Random::DefaultRandomEngine::distribution()
() [inline], [protected], [inherited]
```


Distribution schema for seeding.

Definition at line 90 of file [random.h](#).

```
00090
00091     static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00092     return _distribution;
00093 }
```

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the caller graph for this function:



9.13.2.6 generator()

```
std::default_random_engine& Markov::Random::DefaultRandomEngine::generator ( ) [inline],  
[protected], [inherited]
```

Default random engine for seeding.


Definition at line 82 of file [random.h](#).

```
00082         static std::default_random_engine _generator(rd()());  
00083         return _generator;  
00084     }  
00085 }
```


References [Markov::Random::DefaultRandomEngine::rd\(\)](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.13.2.7 ListCudaDevices()

```
__host__ void Markov::API::CUDA::CUDADeviceController::ListCudaDevices ( ) [static], [inherited]  
List CUDA devices in the system.
```

This function will print details of every CUDA capable device in the system.

Example output:

```
Device Number: 0  
Device name: GeForce RTX 2070  
Memory Clock Rate (KHz): 7001000  
Memory Bus Width (bits): 256  
Peak Memory Bandwidth (GB/s): 448.064  
Max Linear Threads: 1024
```

Definition at line 16 of file [cudaDeviceController.cu](#).

```
00016                                         { //list cuda Capable devices on  
00017     host.  
00018         int nDevices;  
00019         cudaGetDeviceCount(&nDevices);  
00020         for (int i = 0; i < nDevices; i++) {  
00021             cudaDeviceProp prop;  
00022             cudaGetDeviceProperties(&prop, i);  
00023             std::cerr << "Device Number: " << i << "\n";  
00024             std::cerr << "Device name: " << prop.name << "\n";  
00025             std::cerr << "Memory Clock Rate (KHz): " << prop.memoryClockRate << "\n";  
00026             std::cerr << "Memory Bus Width (bits): " << prop.memoryBusWidth << "\n";  
00027             std::cerr << "Peak Memory Bandwidth (GB/s): " << 2.0 * prop.memoryClockRate *  
00028             (prop.memoryBusWidth / 8) / 1.0e6 << "\n";  
00029             std::cerr << "Max Linear Threads: " << prop.maxThreadsDim[0] << "\n";  
00030         }
```

9.13.2.8 MigrateToVRAM()

```
static unsigned long* Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM (
    Markov::API::CUDA::Random::Marsaglia * MEarr,
    long int gridSize) [inline], [static]
Migrate a Marsaglia[] to VRAM as seedChunk.
```

Parameters

<i>MEarr</i>	Array of Marsaglia Engines
<i>gridSize</i>	GridSize of the CUDA Kernel, aka size of array

Returns

pointer to the resulting seed chunk in device VRAM.


Definition at line 28 of file [cudarandom.h](#).

```
00028
00029     cudaError_t cudastatus;
00030     unsigned long* seedChunk;
00031     cudastatus = cudaMalloc((unsigned long**)&seedChunk, gridSize*3*sizeof(unsigned long));
00032     CudaCheckNotifyErr(cudastatus, "Failed to allocate seed buffer");
00033     unsigned long *temp = new unsigned long[gridSize*3];
00034     for(int i=0;i<gridSize;i++){
00035         temp[i*3] = MEarr[i].x;
00036         temp[i*3+1] = MEarr[i].y;
00037         temp[i*3+2] = MEarr[i].z;
00038     }
00039     //for(int i=0;i<gridSize*3;i++) std::cout << temp[i] << "\n";
00040     cudaMemcpy(seedChunk, temp, gridSize*3*sizeof(unsigned long), cudaMemcpyHostToDevice);
00041     CudaCheckNotifyErr(cudastatus, "Failed to memcpy seed buffer.");
00042
00043     delete[] temp;
00044     return seedChunk;
00045 }
```

References [Markov::Random::Marsaglia::x](#), [Markov::Random::Marsaglia::y](#), and [Markov::Random::Marsaglia::z](#).

Referenced by [Markov::API::CUDA::CUDAModelMatrix::prepKernelMemoryChannel\(\)](#).

Here is the caller graph for this function:



9.13.2.9 random()

```
unsigned long Markov::Random::Marsaglia::random () [inline], [virtual], [inherited]
Generate Random Number.
```

Returns

random number in long range.

Reimplemented from [Markov::Random::DefaultRandomEngine](#).

Definition at line 140 of file [random.h](#).


```
00140
00141     unsigned long t;
00142     x ^= x << 16;
00143     x ^= x >> 5;
00144     x ^= x << 1;
00145
00146     t = x;
```

```

00147     x = y;
00148     y = z;
00149     z = t ^ x ^ y;
00150
00151     return z;
00152 }
```

References [Markov::Random::Marsaglia::x](#), [Markov::Random::Marsaglia::y](#), and [Markov::Random::Marsaglia::z](#).
Referenced by [Markov::API::ModelMatrix::FastRandomWalkThread\(\)](#).

Here is the caller graph for this function:



9.13.2.10 rd()

`std::random_device& Markov::Random::DefaultRandomEngine::rd () [inline], [protected], [inherited]`
Default random device for seeding.


Definition at line 74 of file [random.h](#).

```

00074     static std::random_device _rd;
00075     return _rd;
00076 }
00077 }
```

Referenced by [Markov::Random::DefaultRandomEngine::generator\(\)](#).

Here is the caller graph for this function:



9.13.3 Member Data Documentation

9.13.3.1 x

`unsigned long Markov::Random::Marsaglia::x [inherited]`

Definition at line 155 of file [random.h](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), [MigrateToVRAM\(\)](#), and [Markov::Random::Marsaglia::random\(\)](#).

9.13.3.2 y

`unsigned long Markov::Random::Marsaglia::y [inherited]`

Definition at line 156 of file [random.h](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), [MigrateToVRAM\(\)](#), and [Markov::Random::Marsaglia::random\(\)](#).

9.13.3.3 z

`unsigned long Markov::Random::Marsaglia::z [inherited]`

Definition at line 157 of file [random.h](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), [MigrateToVRAM\(\)](#), and [Markov::Random::Marsaglia::random\(\)](#).

The documentation for this class was generated from the following file:


- [cudarandom.h](#)

9.14 Markov::GUI::menu Class Reference


QT Menu class.

```
#include <menu.h>
```

Inheritance diagram for Markov::GUI::menu:



Collaboration diagram for Markov::GUI::menu:



Public Slots

- void [about \(\)](#)
- void [visualization \(\)](#)

Public Member Functions

- [menu \(QWidget *parent=Q_NULLPTR\)](#)

Private Attributes

- [Ui::main ui](#)

9.14.1 Detailed Description

QT Menu class.

Definition at line [15](#) of file [menu.h](#).


9.14.2 Constructor & Destructor Documentation

9.14.2.1 menu()

```
menu::menu (
    QWidget * parent = Q_NULLPTR )
Definition at line 14 of file menu.cpp.
00015     : QMainWindow(parent)
00016 {
00017     ui.setupUi(this);
00018
00019
00020     //QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {about(); });
00021     QObject::connect(ui.visu, &QPushButton::clicked, this, [this] {visualization(); });
00022 }
```

References [ui](#), and [visualization\(\)](#).

Here is the call graph for this function:



9.14.3 Member Function Documentation

9.14.3.1 about


```
void menu::about ( ) [slot]
Definition at line 23 of file menu.cpp.
00023 {
00024
00025
00026 }
```

9.14.3.2 visualization

```
void menu::visualization ( ) [slot]
Definition at line 27 of file menu.cpp.
00027     {
00028         MarkovPasswordsGUI* w = new MarkovPasswordsGUI;
00029         w->show();
00030         this->close();
00031     }
```

Referenced by [menu\(\)](#).

Here is the caller graph for this function:



9.14.4 Member Data Documentation

9.14.4.1 ui

```
Ui::main Markov::GUI::menu::ui [private]
```

Definition at line 21 of file [menu.h](#).

Referenced by [menu\(\)](#).

The documentation for this class was generated from the following files:


- [menu.h](#)
- [menu.cpp](#)

9.15 Markov::Random::Mersenne Class Reference


Implementation of [Mersenne](#) Twister Engine.

```
#include <random.h>
```

Inheritance diagram for Markov::Random::Mersenne:



Collaboration diagram for Markov::Random::Mersenne:



Public Member Functions

- `unsigned long random ()`
Generate Random Number.

Protected Member Functions

- `std::random_device & rd ()`
Default random device for seeding.
- `std::default_random_engine & generator ()`
Default random engine for seeding.
- `std::uniform_int_distribution< long long unsigned > & distribution ()`
Distribution schema for seeding.

9.15.1 Detailed Description

Implementation of [Mersenne](#) Twister Engine.

This is an implementation of [Mersenne](#) Twister Engine, which is slow but is a good implementation for high entropy pseudorandom.

Example Use: Using [Mersenne](#) Engine with RandomWalk

```

Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Mersenne MersenneTwisterEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MersenneTwisterEngine, 5, 10, res);
    std::cout << res << "\n";
}

```

Example Use: Generating a random number with [Marsaglia](#) Engine

```

Markov::Random::Mersenne me;
std::cout << me.random();

```

Definition at line 185 of file [random.h](#).

9.15.2 Member Function Documentation

9.15.2.1 distribution()

```

std::uniform_int_distribution<long long unsigned>& Markov::Random::DefaultRandomEngine::distribution
( ) [inline], [protected], [inherited]

```

Distribution schema for seeding.

Definition at line 90 of file [random.h](#).


```

00090
00091     static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00092     return _distribution;
00093 }

```

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the caller graph for this function:



9.15.2.2 generator()

```

std::default_random_engine& Markov::Random::DefaultRandomEngine::generator ( ) [inline],
[protected], [inherited]

```

Default random engine for seeding.

Definition at line 82 of file [random.h](#).

```


00082
00083     static std::default_random_engine _generator(rd()());
00084     return _generator;
00085 }

```


References [Markov::Random::DefaultRandomEngine::rd\(\)](#).

Referenced by [Markov::Random::Marsaglia::Marsaglia\(\)](#), and [Markov::Random::DefaultRandomEngine::random\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.15.2.3 random()

`unsigned long Markov::Random::DefaultRandomEngine::random () [inline], [virtual], [inherited]`
Generate Random Number.

Returns

random number in long range.

Implements [Markov::Random::RandomEngine](#).


Reimplemented in [Markov::Random::Marsaglia](#).

Definition at line 66 of file [random.h](#).

```
00066     {
00067         return this->distribution() (this->generator());
00068     }
```

References [Markov::Random::DefaultRandomEngine::distribution\(\)](#), and [Markov::Random::DefaultRandomEngine::generator\(\)](#).

Here is the call graph for this function:



9.15.2.4 rd()


`std::random_device& Markov::Random::DefaultRandomEngine::rd () [inline], [protected], [inherited]`
Default random device for seeding.

Definition at line 74 of file [random.h](#).

```
00074     static std::random_device _rd;
00075     return _rd;
00076 }
00077 }
```

Referenced by [Markov::Random::DefaultRandomEngine::generator\(\)](#).

Here is the caller graph for this function:



The documentation for this class was generated from the following file:


- random.h

9.16 `Markov::Model< NodeStorageType >` Class Template Reference

class for the final [Markov Model](#), constructed from nodes and edges.

```
#include <model.h>
```

Collaboration diagram for Markov::Model< NodeStorageType >:



Public Member Functions

- **Model ()**
Initialize a model with only start and end nodes.
 - NodeStorageType * **RandomWalk** (Markov::Random::RandomEngine *randomEngine, int minSetting, int maxSetting, NodeStorageType *buffer)
Do a random walk on this model.
 - void **AdjustEdge** (const NodeStorageType *payload, long int occurrence)
Adjust the model with a single string.
 - bool **Import** (std::ifstream *)
Import a file to construct the model.
 - bool **Import** (const char *filename)

- Open a file to import with filename, and call bool `Model::Import` with std::ifstream.*
- bool `Export` (std::ofstream *)
Export a file of the model.
 - bool `Export` (const char *filename)
Open a file to export with filename, and call bool `Model::Export` with std::ofstream.
 - `Node< NodeStorageType > * StarterNode ()`
Return starter Node.
 - `std::vector< Edge< NodeStorageType > * > * Edges ()`
Return a vector of all the edges in the model.
 - `std::map< NodeStorageType, Node< NodeStorageType > * > * Nodes ()`
Return starter Node.
 - void `OptimizeEdgeOrder ()`
Sort edges of all nodes in the model ordered by edge weights.

Private Attributes

- `std::map< NodeStorageType, Node< NodeStorageType > * > nodes`
Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
- `Node< NodeStorageType > * starterNode`
Starter Node of this model.
- `std::vector< Edge< NodeStorageType > * > edges`
A list of all edges in this model.

9.16.1 Detailed Description

```
template<typename NodeStorageType>
class Markov::Model< NodeStorageType >
```

class for the final **Markov Model**, constructed from nodes and edges.

Each atomic piece of the generation result is stored in a node, while edges contain the relation weights. *Extending:* To extend the class, implement the template and inherit from it, as "class MyModel : public Markov::Model<char>". For a complete demonstration of how to extend the class, see [MarkovPasswords](#).

Whole model can be defined as a list of the edges, as dangling nodes are pointless. This approach is used for the import/export operations. For more information on importing/exporting model, check out the [github readme](#) and [wiki page](#).

Definition at line 45 of file [model.h](#).

9.16.2 Constructor & Destructor Documentation

9.16.2.1 Model()

```
template<typename NodeStorageType >
Markov::Model< NodeStorageType >::Model
Initialize a model with only start and end nodes.
```

Initialize an empty model with only a `starterNode` Starter node is a special kind of node that has constant 0x00 value, and will be used to initiate the generation execution from.

Definition at line 210 of file [model.h](#).

```
00210      {
00211      this->starterNode = new Markov::Node<NodeStorageType>(0);
00212      this->nodes.insert({ 0, this->starterNode });
00213 }
```

9.16.3 Member Function Documentation

9.16.3.1 AdjustEdge()

```
template<typename NodeStorageType >
void Markov::Model< NodeStorageType >::AdjustEdge (
    const NodeStorageType * payload,
    long int occurrence )
```

Adjust the model with a single string.

Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from current node to the next, until NULL character is reached.

Then, update the edge EdgeWeight from current node, to the terminator node.

This function is used for training purposes, as it can be used for adjusting the model with each line of the corpus file.

Example Use: Create an empty model and train it with string: "testdata"

```
Markov::Model<char> model;
char test[] = "testdata";
model.AdjustEdge(test, 15);
```

Parameters


string	- String that is passed from the training, and will be used to AdjustEdge the model with
occurrence	- Occurrence of this string.

Definition at line 337 of file [model.h](#).

```
00337
00338     NodeStorageType p = payload[0];
00339     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00340     Markov::Edge<NodeStorageType>* e;
00341     int i = 0;
00342
00343     if (p == 0) return;
00344     while (p != 0) {
00345         e = curnode->FindEdge(p);
00346         if (e == NULL) return;
00347         e->AdjustEdge(occurrence);
00348         curnode = e->RightNode();
00349         p = payload[++i];
00350     }
00351
00352     e = curnode->FindEdge('\xff');
00353     e->AdjustEdge(occurrence);
00354     return;
00355 }
```

Referenced by [Markov::API::MarkovPasswords::TrainThread\(\)](#).

Here is the caller graph for this function:



9.16.3.2 Edges()

```
template<typename NodeStorageType >
std::vector<Edge<NodeStorageType*>>* Markov::Model< NodeStorageType >::Edges ( ) [inline]
```

Return a vector of all the edges in the model.

Returns

vector of edges

Definition at line 176 of file [model.h](#).

```
00176 { return &edges; }
```

9.16.3.3 Export() [1/2]

```
template<typename NodeStorageType >
bool Markov::Model< NodeStorageType >::Export (
    const char * filename )
```

Open a file to export with filename, and call bool [Model::Export](#) with std::ofstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Export file to filename


```
Markov::Model<char> model;
model.Export("test.mdl");
```

Definition at line 300 of file [model.h](#).

```
00300
00301     std::ofstream exportfile;
00302     exportfile.open(filename);
00303     return this->Export(&exportfile);
00304 }
```

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

Here is the caller graph for this function:



9.16.3.4 Export() [2/2]

```
template<typename NodeStorageType >
bool Markov::Model< NodeStorageType >::Export (
    std::ofstream * f )
```

Export a file of the model.

File contains a list of edges. Format is: Left_repr;EdgeWeight;right_repr. For more information on the format, check out the project wiki or github readme.

Iterate over this vertices, and their edges, and write them to file.

Returns

True if successful, False for incomplete models.

Example Use: Export file to ofstream

```
Markov::Model<char> model;
std::ofstream file("test.mdl");
model.Export(&file);
```

Definition at line 288 of file [model.h](#).

```
00288
00289     Markov::Edge<NodeStorageType>* e;
00290     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00291         e = this->edges[i];
00292         //std::cout << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," <<
00293         *f << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," << e->RightNode()->NodeValue() <<
00294         "\n";
00295     }
00296     return true;
00297 }
```

Referenced by [Markov::API::MarkovPasswords::Save\(\)](#).

Here is the caller graph for this function:



9.16.3.5 Import() [1/2]

```
template<typename NodeStorageType >
bool Markov::Model< NodeStorageType >::Import (
    const char * filename )
```

Open a file to import with filename, and call bool [Model::Import](#) with std::ifstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file with filename


```
Markov::Model<char> model;
model.Import("test.mdl");
```

Definition at line 280 of file model.h.

```
00280
00281     std::ifstream importfile;
00282     importfile.open(filename);
00283     return this->Import(&importfile);
00284
00285 }
```

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), [Markov::API::ModelMatrix::Import\(\)](#), and [Markov::API::MarkovPasswords::MarkovPasswords\(\)](#).

Here is the caller graph for this function:



9.16.3.6 Import() [2/2]

```
template<typename NodeStorageType >
bool Markov::Model< NodeStorageType >::Import (
    std::ifstream * f )
```

Import a file to construct the model.

File contains a list of edges. For more info on the file format, check out the wiki and github readme pages. Format is: Left_repr;EdgeWeight;right_repr

Iterate over this list, and construct nodes and edges accordingly.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file from ifstream


```
Markov::Model<char> model;
std::ifstream file("test.mdl");
model.Import(&file);
```

Definition at line 216 of file model.h.

```
00216     std::string cell;
00217     {
00218         std::string cell;
00219         char src;
00220         char target;
00221         long int oc;
00222
00223         while (std::getline(*f, cell)) {
00224             //std::cout << "cell: " << cell << std::endl;
00225             src = cell[0];
00226             target = cell[cell.length() - 1];
00227             char* j;
00228             oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(), &j, 10);
00229             //std::cout << oc << "\n";
00230             Markov::Node<NodeStorageType>* srcN;
00231             Markov::Node<NodeStorageType>* targetN;
00232             Markov::Edge<NodeStorageType>* e;
00233             if (this->nodes.find(src) == this->nodes.end()) {
00234                 srcN = new Markov::Node<NodeStorageType>(src);
00235                 this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(src, srcN));
00236                 //std::cout << "Creating new node at start.\n";
00237             }
00238             else {
00239                 srcN = this->nodes.find(src)->second;
00240             }
00241
00242             if (this->nodes.find(target) == this->nodes.end()) {
00243                 targetN = new Markov::Node<NodeStorageType>(target);
00244                 this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(target, targetN));
00245                 //std::cout << "Creating new node at end.\n";
00246             }
00247             else {
00248                 targetN = this->nodes.find(target)->second;
00249             }
00250             e = srcN->Link(targetN);
00251             e->AdjustEdge(oc);
00252             this->edges.push_back(e);
00253
00254             //std::cout << int(srcN->NodeValue()) << " --" << e->EdgeWeight() << "--> " <<
00255             int(targetN->NodeValue()) << "\n";
00256
00257         }
00258
00259         this->OptimizeEdgeOrder();
00260
00261     return true;
00262 }
```

Referenced by [Markov::API::MarkovPasswords::OpenDatasetFile\(\)](#).

Here is the caller graph for this function:

**9.16.3.7 Nodes()**

```
template<typename NodeStorageType >
std::map<NodeStorageType, Node<NodeStorageType>*>* Markov::Model< NodeStorageType >::Nodes (
) [inline]
Return starter Node.
```

Returns


starter node with 00 NodeValue

Definition at line 181 of file [model.h](#).

```
00181 { return &nodes; }
```

Referenced by [Markov::API::MarkovPasswords::Buff\(\)](#), and [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:

**9.16.3.8 OptimizeEdgeOrder()**


```
template<typename NodeStorageType >
void Markov::Model< NodeStorageType >::OptimizeEdgeOrder
Sort edges of all nodes in the model ordered by edge weights.
```

Definition at line 265 of file [model.h](#).

```
00265 {
00266     for (std::pair<unsigned char, Markov::Node<NodeStorageType>> const& x : this->nodes) {
00267         //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
00268         std::sort (x.second->edgesV.begin(), x.second->edgesV.end(), [] (Edge<NodeStorageType> *lhs,
00269             Edge<NodeStorageType> *rhs) ->bool{
00270             return lhs->EdgeWeight() > rhs->EdgeWeight();
00271         });
00272         //for(int i=0;i<x.second->edgesV.size();i++)
00273         //    std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00274         //std::cout << "\n";
00275     }
00276     //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00277     //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00278 }
```

Referenced by [Markov::API::MarkovPasswords::Buff\(\)](#).

Here is the caller graph for this function:

**9.16.3.9 RandomWalk()**

```
template<typename NodeStorageType >
NodeStorageType * Markov::Model< NodeStorageType >::RandomWalk (
    Markov::Random::RandomEngine * randomEngine,
    int minSetting,
    int maxSetting,
    NodeStorageType * buffer )
```

Do a random walk on this model.

Start from the starter node, on each node, invoke RandomNext using the random engine on current node, until terminator node is reached. If terminator node is reached before minimum length criteria is reached, ignore the last selection and re-invoke randomNext

If maximum length criteria is reached but final node is not, cut off the generation and proceed to the final node. This function takes [Markov::Random::RandomEngine](#) as a parameter to generate pseudo random numbers from. This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne output is higher in entropy, most use cases don't really need super high entropy output, so [Markov::Random::Marsaglia](#) is preferable for better performance.

This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening via maximum length criteria.

Example Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use Marsaglia

```
Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}
```

Parameters

<i>randomEngine</i>	Random Engine to use for the random walks. For examples, see Markov::Random::Mersenne and Markov::Random::Marsaglia
<i>minSetting</i>	Minimum number of characters to generate
<i>maxSetting</i>	Maximum number of character to generate
<i>buffer</i>	buffer to write the result to

Returns


Null terminated string that was generated.

Definition at line 307 of file [model.h](#).

```
00307
00308     Markov::Node<NodeStorageType>* n = this->starterNode;
00309     int len = 0;
00310     Markov::Node<NodeStorageType>* temp_node;
00311     while (true) {
00312         temp_node = n->RandomNext(randomEngine);
00313         if (len >= maxSetting) {
00314             break;
00315         }
00316         else if ((temp_node == NULL) && (len < minSetting)) {
00317             continue;
00318         }
00319         else if (temp_node == NULL) {
00320             break;
00321         }
00322         n = temp_node;
00323         n->RandomWalk(randomEngine, minSetting, maxSetting, buffer, len);
00324         buffer[len] = n->NodeValue();
00325         len++;
00326     }
00327     //null terminate the string
00328     buffer[len] = 0x00;
00329     //do something with the generated string
00330     return buffer; //for now
00331
00332
00333
00334 }
```

Referenced by [Markov::API::MarkovPasswords::GenerateThread\(\)](#).

Here is the caller graph for this function:



9.16.3.10 StarterNode()

```
template<typename NodeStorageType >
Node<NodeStorageType>* Markov::Model< NodeStorageType >::StarterNode ( ) [inline]
Return starter Node.
```

Returns


starter node with 00 NodeValue

Definition at line 171 of file [model.h](#).

```
00171 { return starterNode; }
```

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:



9.16.4 Member Data Documentation

9.16.4.1 edges

```
template<typename NodeStorageType >
std::vector<Edge<NodeStorageType>>* Markov::Model< NodeStorageType >::edges [private]
```

A list of all edges in this model.

Definition at line 204 of file [model.h](#).

Referenced by [Markov::Model< char >::Edges\(\)](#).

9.16.4.2 nodes

```
template<typename NodeStorageType >
std::map<NodeStorageType, Node<NodeStorageType>*>* Markov::Model< NodeStorageType >::nodes [private]
```

Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.

Definition at line 193 of file [model.h](#).

Referenced by [Markov::Model< char >::Nodes\(\)](#).

9.16.4.3 starterNode

```
template<typename NodeStorageType >
Node<NodeStorageType>* Markov::Model< NodeStorageType >::starterNode [private]
```

Starter Node of this model.

Definition at line 198 of file [model.h](#).

Referenced by [Markov::Model< char >::StarterNode\(\)](#).

The documentation for this class was generated from the following file:


- [model.h](#)

9.17 Markov::API::ModelMatrix Class Reference


Class to flatten and reduce [Markov::Model](#) to a Matrix.

```
#include <modelMatrix.h>
```

Inheritance diagram for Markov::API::ModelMatrix:



Collaboration diagram for Markov::API::ModelMatrix:



Public Member Functions

- **ModelMatrix ()**
 - **bool ConstructMatrix ()**

Construct the related Matrix data for the model.
 - **void DumpJSON ()**

Debug function to dump the model to a JSON file.
 - **int FastRandomWalk (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20, bool bFileIO=true)**

Random walk on the Matrix-reduced `Markov::Model`.
 - **void Import (const char *filename)**

Open a file to import with filename, and call `bool Model::Import` with `std::ifstream`.
 - **void Train (const char *datasetFileName, char delimiter, int threads)**

Train the model with the dataset file.
 - **std::ifstream * OpenDatasetFile (const char *filename)**

Open dataset file and return the ifstream pointer.
 - **std::ofstream * Save (const char *filename)**

Export model to file.
 - **void Generate (unsigned long int n, const char *wordlistFileName, int minLen=6, int maxLen=12, int threads=20)**

- Call `Markov::Model::RandomWalk` n times, and collect output.*
- void `Buff` (const `char` *str, double multiplier, bool bDontAdjustSelfLoops=true, bool bDontAdjustExtendedLoops=false)

Buff expression of some characters in the model.
 - `char * RandomWalk (Markov::Random::RandomEngine *randomEngine, int minSetting, int maxSetting, char *buffer)`

Do a random walk on this model.
 - void `AdjustEdge` (const `char` *payload, long int occurrence)

Adjust the model with a single string.
 - bool `Import` (`std::ifstream` *)

Import a file to construct the model.
 - bool `Export` (`std::ofstream` *)

Export a file of the model.
 - bool `Export` (const `char` *filename)

Open a file to export with filename, and call `bool Model::Export` with `std::ofstream`.
 - `Node< char > * StarterNode ()`

Return starter Node.
 - `std::vector< Edge< char > * > * Edges ()`

Return a vector of all the edges in the model.
 - `std::map< char, Node< char > * > * Nodes ()`

Return starter Node.
 - void `OptimizeEdgeOrder ()`

Sort edges of all nodes in the model ordered by edge weights.

Protected Member Functions

- int `FastRandomWalk` (unsigned long int n, `std::ofstream` *wordlist, int minLen=6, int maxLen=12, int threads=20, bool bFileIO=true)

Random walk on the Matrix-reduced `Markov::Model`.
- void `FastRandomWalkPartition` (`std::mutex` *mlock, `std::ofstream` *wordlist, unsigned long int n, int minLen, int maxLen, bool bFileIO, int threads)

A single partition of `FastRandomWalk` event.
- void `FastRandomWalkThread` (`std::mutex` *mlock, `std::ofstream` *wordlist, unsigned long int n, int minLen, int maxLen, int id, bool bFileIO)

A single thread of a single partition of `FastRandomWalk`.
- bool `DeallocateMatrix ()`

Deallocate matrix and make it ready for re-construction.

Protected Attributes

- `char ** edgeMatrix`

2-D Character array for the edge Matrix (The characters of Nodes)
- `long int ** valueMatrix`

2-d Integer array for the value Matrix (For the weights of Edges)
- `int matrixSize`

to hold Matrix size
- `char * matrixIndex`

to hold the Matrix index (To hold the orders of 2-D arrays')
- `long int * totalEdgeWeights`

Array of the Total `Edge` Weights.
- `bool ready`

True when matrix is constructed. False if not.

Private Member Functions

- void [TrainThread](#) (Markov::API::Concurrency::ThreadSharedListHandler *listhandler, [char delimiter](#))

A single thread invoked by the Train function.
- void [GenerateThread](#) (std::mutex *outputLock, unsigned long int n, std::ofstream *wordlist, int minLen, int maxLen)

A single thread invoked by the Generate function.

Private Attributes

- std::ifstream * [datasetFile](#)

Dataset file input of our system
- std::ofstream * [outputFile](#)

File to save model of our system
- std::map< [char](#), Node< [char](#) > * > [nodes](#)

Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
- Node< [char](#) > * [starterNode](#)

Starter Node of this model.
- std::vector< Edge< [char](#) > * > [edges](#)

A list of all edges in this model.

9.17.1 Detailed Description

Class to flatten and reduce [Markov::Model](#) to a Matrix.

Matrix level operations can be used for Generation events, with a significant performance optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)

To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for allocation. Threads are synchronized and files are flushed every 50M operations.

Definition at line 23 of file [modelMatrix.h](#).

9.17.2 Constructor & Destructor Documentation

9.17.2.1 ModelMatrix()

```
Markov::API::ModelMatrix::ModelMatrix ( )
Definition at line 15 of file modelMatrix.cpp.
00015
00016     this->ready = false;
00017 }
```

References [ready](#).

9.17.3 Member Function Documentation

9.17.3.1 AdjustEdge()

```
void Markov::Model< char >::AdjustEdge (
    const NodeStorageType * payload,
    long int occurrence ) [inherited]
```

Adjust the model with a single string.

Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from current node to the next, until NULL character is reached.

Then, update the edge EdgeWeight from current node, to the terminator node.

This function is used for training purposes, as it can be used for adjusting the model with each line of the corpus file.

Example Use: Create an empty model and train it with string: "testdata"

```
Markov::Model<char> model;
char test[] = "testdata";
model.AdjustEdge(test, 15);
```

Parameters

string	- String that is passed from the training, and will be used to AdjustEdge the model with
occurrence	- Occurrence of this string.

Definition at line 337 of file [model.h](#).

```
00337
00338     NodeStorageType p = payload[0];
00339     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00340     Markov::Edge<NodeStorageType>* e;
00341     int i = 0;
00342
00343     if (p == 0) return;
00344     while (p != 0) {
00345         e = curnode->FindEdge(p);
00346         if (e == NULL) return;
00347         e->AdjustEdge(occurrence);
00348         curnode = e->RightNode();
00349         p = payload[++i];
00350     }
00351
00352     e = curnode->FindEdge('\xff');
00353     e->AdjustEdge(occurrence);
00354     return;
00355 }
```

9.17.3.2 Buff()

```
void Markov::API::MarkovPasswords::Buff (
    const char * str,
    double multiplier,
    bool bDontAdjustSelfLoops = true,
    bool bDontAdjustExtendedLoops = false ) [inherited]
```

Buff expression of some characters in the model.

Parameters

str	A string containing all the characters to be buffed
multiplier	A constant value to buff the nodes with.
bDontAdjustSelfEdges	Do not adjust weights if target node is same as source node
bDontAdjustExtendedLoops	Do not adjust if both source and target nodes are in first parameter

Definition at line 153 of file [markovPasswords.cpp](#).

```
00153
00154     std::string buffstr(str);
00155     std::map< char, Node< char > * > *nodes;
00156     std::map< char, Edge< char > * > *edges;
00157     nodes = this->Nodes();
00158     int i=0;
00159     for (auto const& [repr, node] : *nodes) {
00160         edges = node->Edges();
00161         for (auto const& [targetrepr, edge] : *edges){
00162             if(buffstr.find(targetrepr) != std::string::npos) {
00163                 if(bDontAdjustSelfLoops && repr==targetrepr) continue;
00164                 if(bDontAdjustExtendedLoops) {
00165                     if(buffstr.find(repr) != std::string::npos) {
00166                         continue;
00167                     }
00168                 }
00169                 long int weight = edge->EdgeWeight();
00170                 weight = weight*multiplier;
```


```

00171             edge->AdjustEdge(weight);
00172         }
00173     }
00174     i++;
00175 }
00176
00177 this->OptimizeEdgeOrder();
00178
00179 }
```


References [Markov::Edge< NodeStorageType >::AdjustEdge\(\)](#), [Markov::Node< storageType >::Edges\(\)](#), [Markov::Edge< NodeStorageType >::EdgeWeight\(\)](#), [Markov::Model< NodeStorageType >::Nodes\(\)](#), and [Markov::Model< NodeStorageType >::OptimizeEdgeOrder\(\)](#).

Referenced by [main\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.3 ConstructMatrix()

```
bool Markov::API::ModelMatrix::ConstructMatrix( )
```

Construct the related Matrix data for the model.

This operation can be used after importing/training to allocate and populate the matrix content.

this will initialize: char** edgeMatrix -> a 2D array of mapping left and right connections of each edge. long int **valueMatrix -> a 2D array representing the edge weights. int matrixSize -> Size of the matrix, aka total number of nodes. char* matrixIndex -> order of nodes in the model long int *totalEdgeWeights -> total edge weights of each [Node](#).

Returns

True if constructed. False if already constructed.

Definition at line 31 of file [modelMatrix.cpp](#).

```

00031         {
00032     if(this->ready) return false;
00033     this->matrixSize = this->StarterNode()->edgesV.size() + 2;
00034
00035     this->matrixIndex = new char[this->matrixSize];
00036     this->totalEdgeWeights = new long int[this->matrixSize];
00037
00038     this->edgeMatrix = new char*[this->matrixSize];
00039     for(int i=0;i<this->matrixSize;i++){
00040         this->edgeMatrix[i] = new char[this->matrixSize];
00041     }
00042     this->valueMatrix = new long int*[this->matrixSize];
00043     for(int i=0;i<this->matrixSize;i++){
00044         this->valueMatrix[i] = new long int[this->matrixSize];
00045     }
00046     std::map< char, Node< char > * > *nodes;
00047     nodes = this->Nodes();
00048     int i=0;
00049     for (auto const& [repr, node] : *nodes){
00050         if(repr!=0) this->matrixIndex[i] = repr;
00051         else this->matrixIndex[i] = 199;
00052         this->totalEdgeWeights[i] = node->TotalEdgeWeights();
00053         for(int j=0;j<this->matrixSize;j++){
00054             char val = node->NodeValue();
00055             if(val < 0){
00056                 for(int k=0;k<this->matrixSize;k++){
00057                     this->valueMatrix[i][k] = 0;
00058                     this->edgeMatrix[i][k] = 255;
00059                 }
00060                 break;
00061             }
00062             else if(node->NodeValue() == 0 && j>(this->matrixSize-3)){
00063                 this->valueMatrix[i][j] = 0;
00064                 this->edgeMatrix[i][j] = 255;
00065             }else if(j==(this->matrixSize-1)) {
00066                 this->valueMatrix[i][j] = 0;
00067                 this->edgeMatrix[i][j] = 255;
00068             }else{
00069                 this->valueMatrix[i][j] = node->edgesV[j]->EdgeWeight();
00070                 this->edgeMatrix[i][j] = node->edgesV[j]->RightNode()->NodeValue();
00071             }
00072         }
00073     }
00074     i++;
00075 }
00076 this->ready = true;
00077 return true;
00078 //this->DumpJSON();
00079 }
```


References [edgeMatrix](#), [Markov::Edge< NodeStorageType >::EdgeWeight\(\)](#), [matrixIndex](#), [matrixSize](#), [Markov::Model< NodeStorageType >::Model\(\)](#),

[Markov::Node< storageType >::NodeValue\(\)](#), [ready](#), [Markov::Edge< NodeStorageType >::RightNode\(\)](#), [Markov::Model< NodeStorageType >::TotalEdgeWeights\(\)](#),


[totalEdgeWeights](#), and [valueMatrix](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), [Import\(\)](#), and [Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.4 DeallocateMatrix()

```
bool Markov::API::ModelMatrix::DeallocateMatrix () [protected]
```

Deallocate matrix and make it ready for re-construction.

Returns

True if deallocated. False if matrix was not initialized

Definition at line 81 of file `modelMatrix.cpp`.


```

00081     if(!this->ready) return false;
00082     delete[] this->matrixIndex;
00083     delete[] this->totalEdgeWeights;
00084
00085     for(int i=0;i<this->matrixSize;i++) {
00086         delete[] this->edgeMatrix[i];
00087     }
00088     delete[] this->edgeMatrix;
00089
00090     for(int i=0;i<this->matrixSize;i++) {
00091         delete[] this->valueMatrix[i];
00092     }
00093     delete[] this->valueMatrix;
00094
00095     this->matrixSize = -1;
00096     this->ready = false;
00097     return true;
00098 }
```

References `edgeMatrix`, `matrixIndex`, `matrixSize`, `ready`, `totalEdgeWeights`, and `valueMatrix`.

Referenced by [Import\(\)](#), and [Train\(\)](#).

Here is the caller graph for this function:



9.17.3.5 DumpJSON()

```
void Markov::API::ModelMatrix::DumpJSON ( )
```

Debug function to dump the model to a JSON file.

Might not work 100%. Not meant for production use.

Definition at line 101 of file [modelMatrix.cpp](#).


```

00101
00102
00103     std::cout << "{\n      \"index\": \"";
00104     for(int i=0;i<this->matrixSize;i++){
00105         if(this->matrixIndex[i]=='"') std::cout << "\\\\"\"";
00106         else if(this->matrixIndex[i]=='\\') std::cout << "\\\\\\"";
00107         else if(this->matrixIndex[i]==0) std::cout << "\\\\x00";
00108         else if(i==0) std::cout << "\\\\xff";
00109         else if(this->matrixIndex[i]=='\n') std::cout << "\\\n";
00110         else std::cout << this->matrixIndex[i];
00111     }
00112     std::cout <
00113     "\\",\\n"
00114     "  \"edgemap\": {\n";
00115
00116     for(int i=0;i<this->matrixSize;i++){
00117         if(this->matrixIndex[i]=='"') std::cout << "      \"\\\\\"\\\"": [";
00118         else if(this->matrixIndex[i]=='\\') std::cout << "      \"\\\\\\\\\\\"": [";
00119         else if(this->matrixIndex[i]==0) std::cout << "      \"\\\\\\\\x00\\\"": [";
00120         else if(this->matrixIndex[i]<0) std::cout << "      \"\\\\\\\\xf\\\"": [";
00121         else std::cout << "      \" \" << this->matrixIndex[i] << "\": [";
00122         for(int j=0;j<this->matrixSize;j++){
00123             if(this->edgeMatrix[i][j]=='"') std::cout << "        \"\\\\\"\\\"";
00124             else if(this->edgeMatrix[i][j]=='\\') std::cout << "        \"\\\\\\\\\\\"";
00125             else if(this->edgeMatrix[i][j]==0) std::cout << "        \"\\\\\\\\x00\\\"";
00126             else if(this->edgeMatrix[i][j]<0) std::cout << "        \"\\\\\\\\xf\\\"";
00127             else if(this->matrixIndex[i]=='\n') std::cout << "        \"\\\\\\n\\\"";
00128             else std::cout << "        \" \" << this->edgeMatrix[i][j] << "\": ";
00129             if(j!=this->matrixSize-1) std::cout << ", ";
00130         }
00131     }
00132     std::cout << "],\\n";
00133 }
00134 std::cout << "},\\n";
00135 std::cout << "  \"weightmap\": {\n";
00136 for(int i=0;i<this->matrixSize;i++){
00137     if(this->matrixIndex[i]=='"') std::cout << "    \"\\\\\"\\\"": [";
00138     else if(this->matrixIndex[i]=='\\') std::cout << "    \"\\\\\\\\\\\"": [";
00139     else if(this->matrixIndex[i]==0) std::cout << "    \"\\\\\\\\x00\\\"": [";
00140     else if(this->matrixIndex[i]<0) std::cout << "    \"\\\\\\\\xf\\\"": [";
00141     else std::cout << "    \" \" << this->matrixIndex[i] << "\": [";
00142
00143     for(int j=0;j<this->matrixSize;j++){
00144         std::cout << this->valueMatrix[i][j];
00145         if(j!=this->matrixSize-1) std::cout << ", ";
00146     }
00147     std::cout << "],\\n";
00148 }
00149 std::cout << "  }\\n}\\n";
00150 }
```

References [edgeMatrix](#), [matrixIndex](#), [matrixSize](#), and [valueMatrix](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the caller graph for this function:



9.17.3.6 Edges()

`std::vector<Edge<char>>* Markov::Model<char>::Edges () [inherited]`
Return a vector of all the edges in the model.

Returns

`vector of edges`

Definition at line 176 of file `model.h`.
00176 { `return &edges;` }

9.17.3.7 Export() [1/2]

`bool Markov::Model<char>::Export (`
 `const char * filename) [inherited]`

Open a file to export with filename, and call bool `Model::Export` with std::ofstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Export file to filename

```
Markov::Model<char> model;
model.Export("test.mdl");
```

Definition at line 300 of file `model.h`.

```
00300
00301     std::ofstream exportfile;
00302     exportfile.open(filename);
00303     return this->Export(&exportfile);
00304 }
```

9.17.3.8 Export() [2/2]

`bool Markov::Model<char>::Export (`
 `std::ofstream * f) [inherited]`

Export a file of the model.

File contains a list of edges. Format is: Left_repr;EdgeWeight;right_repr. For more information on the format, check out the project wiki or github readme.

Iterate over this vertices, and their edges, and write them to file.

Returns

True if successful, False for incomplete models.

Example Use: Export file to ofstream

```
Markov::Model<char> model;
std::ofstream file("test.mdl");
model.Export(&file);
```

Definition at line 288 of file `model.h`.

```
00288 }
```

```

00289     Markov::Edge<NodeStorageType>* e;
00290     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00291         e = this->edges[i];
00292         //std::cout << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," <
00293         *f << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," << e->RightNode()->NodeValue() <
00294         "\n";
00295     }
00296     return true;
00297 }
```

9.17.3.9 FastRandomWalk() [1/2]

```

int Markov::API::ModelMatrix::FastRandomWalk (
    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20,
    bool bFileIO = true )
```

Random walk on the Matrix-reduced [Markov::Model](#).

This has an O(N) Memory complexity. To limit the maximum usage, requests with $n > 50M$ are partitioned using [Markov::API::ModelMatrix::FastRandomWalkPartition](#).

If $n > 50M$, threads are going to be synced, files are going to be flushed, and buffers will be reallocated every 50M generations. This comes at a minor performance penalty.

While it has the same functionality, this operation reduces [Markov::API::MarkovPasswords::Generate](#) runtime by ~96.5

This function has deprecated [Markov::API::MarkovPasswords::Generate](#), and will eventually replace it.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

```

Markov::API::ModelMatrix mp;
mp.Import("models/finished.mdl");
mp.FastRandomWalk(50000000,"./wordlist.txt",6,12,25, true);
```

Definition at line 217 of file [modelMatrix.cpp](#).

```

00217
00218     std::ofstream wordlist;
00219     if(bFileIO)
00220         wordlist.open(wordlistFileName);
00221     this->FastRandomWalk(n, &wordlist, minLen, maxLen, threads, bFileIO);
00222     return 0;
00223 }
```


References [FastRandomWalk\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.10 FastRandomWalk() [2/2]

```
int Markov::API::ModelMatrix::FastRandomWalk (
    unsigned long int n,
    std::ofstream * wordlist,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20,
    bool bFileIO = true ) [protected]
```

[Random walk on the Matrix-reduced Markov::Model.](#)

This has an O(N) Memory complexity. To limit the maximum usage, requests with $n > 50M$ are partitioned using [Markov::API::ModelMatrix::FastRandomWalkPartition](#).

If $n > 50M$, threads are going to be synced, files are going to be flushed, and buffers will be reallocated every 50M generations. This comes at a minor performance penalty.

While it has the same functionality, this operation reduces [Markov::API::MarkovPasswords::Generate](#) runtime by 99.6.5

This function has deprecated [Markov::API::MarkovPasswords::Generate](#), and will eventually replace it.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

```
Markov::API::ModelMatrix mp;
mp.Import("models/finished.mdl");
mp.FastRandomWalk(50000000, "./wordlist.txt", 6, 12, 25, true);
```


[Definition at line 204 of file modelMatrix.cpp.](#)

```
00204
00205
00206
00207     std::mutex mlock;
00208     if(n<=50000000ull) this->FastRandomWalkPartition(&mlock, wordlist, n, minLen, maxLen, bFileIO,
00209     threads);
00210     else{
00211         int numberOfPartitions = n/50000000ull;
00212         for(int i=0;i<numberOfPartitions;i++)
00213             this->FastRandomWalkPartition(&mlock, wordlist, 50000000ull, minLen, maxLen, bFileIO,
00214             threads);
00215 }
```

[References FastRandomWalkPartition\(\).](#)

[Referenced by FastRandomWalk\(\).](#)

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.11 FastRandomWalkPartition()

```
void Markov::API::ModelMatrix::FastRandomWalkPartition (
    std::mutex * mlock,
    std::ofstream * wordlist,
    unsigned long int n,
    int minLen,
    int maxLen,
    bool bFileIO,
    int threads ) [protected]
```

A single partition of FastRandomWalk event.

Since FastRandomWalk has to allocate its output buffer before operation starts and writes data in chunks, large n parameters would lead to huge memory allocations. **Without Partitioning:**

- 50M results 12 characters max -> 550 Mb Memory allocation
- 5B results 12 characters max -> 55 Gb Memory allocation
- 50B results 12 characters max -> 550GB Memory allocation

Instead, FastRandomWalk is partitioned per 50M generations to limit the top memory need.

Parameters

<i>mlock</i>	- mutex lock to distribute to child threads
<i>wordlist</i>	- Reference to the wordlist file to write to
<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

Definition at line 225 of file [modelMatrix.cpp](#).

```
00225
00226
00227     int iterationsPerThread = n/threads;
00228     int iterationsPerThreadCarryOver = n%threads;
00229
00230     std::vector<std::thread*> threadsV;
00231 }
```


```

00232     int id = 0;
00233     for(int i=0;i<threads;i++) {
00234         threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this,
00235                                         mlock, wordlist, iterationsPerThread, minLen, maxLen, id, bFileIO));
00236         id++;
00237     }
00238     threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this, mlock,
00239                                         wordlist, iterationsPerThreadCarryOver, minLen, maxLen, id, bFileIO));
00240     for(int i=0;i<threads;i++) {
00241         threadsV[i]~>join();
00242     }
00243 }
```

References [FastRandomWalkThread\(\)](#).

Referenced by [FastRandomWalk\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.12 FastRandomWalkThread()

```

void Markov::API::ModelMatrix::FastRandomWalkThread (
    std::mutex * mlock,
    std::ofstream * wordlist,
    unsigned long int n,
    int minLen,
    int maxLen,
    int id,
    bool bFileIO ) [protected]
```

A single thread of a single partition of [FastRandomWalk](#).

A [FastRandomWalkPartition](#) will initiate as many of this function as requested.

This function contains the bulk of the generation algorithm.

Parameters

<i>mlock</i>	- mutex lock to distribute to child threads
<i>wordlist</i>	- Reference to the wordlist file to write to
<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>id</i>	- DEPRECATED Thread id - No longer used
<i>bFileIO</i>	- If false, filename will be ignored and will output to stdout.

Definition at line 153 of file [modelMatrix.cpp](#).

00153


```

00154     if(n==0)  return;
00155
00156     Markov::Random::Marsaglia MarsagliaRandomEngine;
00157     char* e;
00158     char *res = new char[(maxLen+2)*n];
00159     int index = 0;
00160     char next;
00161     int len=0;
00162     long int selection;
00163     char cur;
00164     long int bufferctr = 0;
00165     for (int i = 0; i < n; i++) {
00166         cur=199;
00167         len=0;
00168         while (true) {
00169             e = strchr(this->matrixIndex, cur);
00170             index = e - this->matrixIndex;
00171             selection = MarsagliaRandomEngine.random() % this->totalEdgeWeights[index];
00172             for(int j=0;j<this->matrixSize;j++){
00173                 selection -= this->valueMatrix[index][j];
00174                 if (selection < 0){
00175                     next = this->edgeMatrix[index][j];
00176                     break;
00177                 }
00178             }
00179             if (len >= maxLen) break;
00180             else if ((next < 0) && (len < minLen)) continue;
00181             else if (next < 0) break;
00182             cur = next;
00183             res[bufferctr + len++] = cur;
00184         }
00185     }
00186     res[bufferctr + len++] = '\n';
00187     bufferctr+=len;
00188
00189 }
00190 if(bFileIO) {
00191     mlock->lock();
00192     *wordlist << res;
00193     mlock->unlock();
00194 }else{
00195     mlock->lock();
00196     std::cout << res;
00197     mlock->unlock();
00198 }
00199 delete res;
00200
00201 }
```

References **edgeMatrix**, **matrixIndex**, **matrixSize**, **Markov::Random::Marsaglia::random()**, **totalEdgeWeights**, and **valueMatrix**.

Referenced by **FastRandomWalkPartition()**.

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.13 Generate()

```
void Markov::API::MarkovPasswords::Generate (
```

```

    unsigned long int n,
    const char * wordlistFileName,
    int minLen = 6,
    int maxLen = 12,
    int threads = 20 ) [inherited]

```

Call [Markov::Model::RandomWalk](#) n times, and collect output.

Generate from model and write results to a file. a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Deprecated See [Markov::API::MatrixModel::FastRandomWalk](#) for more information.

Parameters

<i>n</i>	- Number of passwords to generate.
<i>wordlistFileName</i>	- Filename to write to
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate
<i>threads</i>	- number of OS threads to spawn

Definition at line 118 of file [markovPasswords.cpp](#).


```

00118
00119     char* res;
00120     char print[100];
00121     std::ofstream wordlist;
00122     wordlist.open(wordlistFileName);
00123     std::mutex mlock;
00124     int iterationsPerThread = n/threads;
00125     int iterationsCarryOver = n%threads;
00126     std::vector<std::thread*> threadsV;
00127     for(int i=0;i<threads;i++) {
00128         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::GenerateThread, this,
00129             &mlock, iterationsPerThread, &wordlist, minLen, maxLen));
00130     }
00131     for(int i=0;i<threads;i++) {
00132         threadsV[i]->join();
00133         delete threadsV[i];
00134     }
00135     this->GenerateThread(&mlock, iterationsCarryOver, &wordlist, minLen, maxLen);
00136
00137
00138 }
```


References [Markov::API::MarkovPasswords::GenerateThread\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [Markov::GUI::Generate::generation\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.14 GenerateThread()

```
void Markov::API::MarkovPasswords::GenerateThread (
    std::mutex * outputLock,
    unsigned long int n,
    std::ofstream * wordlist,
    int minLen,
    int maxLen ) [private], [inherited]
```

A single thread invoked by the Generate function.

DEPRECATED: See [Markov::API::MatrixModel::FastRandomWalkThread](#) for more information. This has been replaced with a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5 on average.

Parameters

<i>outputLock</i>	- shared mutex lock to lock during output operation. Prevents race condition on write.
<i>n</i>	number of lines to be generated by this thread
<i>wordlist</i>	wordlistfile
<i>minLen</i>	- Minimum password length to generate
<i>maxLen</i>	- Maximum password length to generate


Definition at line 140 of file [markovPasswords.cpp](#).

```
00140
00141     char* res = new char[maxLen+5];
00142     if(n==0) return;
00143
00144     Markov::Random::Marsaglia MarsagliaRandomEngine;
00145     for (int i = 0; i < n; i++) {
00146         this->RandomWalk(&MarsagliaRandomEngine, minLen, maxLen, res);
00147         outputLock->lock();
00148         *wordlist << res << "\n";
00149         outputLock->unlock();
00150     }
00151 }
```


References [Markov::Model< NodeStorageType >::RandomWalk\(\)](#).

Referenced by [Markov::API::MarkovPasswords::Generate\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.15 Import() [1/2]

```
void Markov::API::ModelMatrix::Import (
    const char * filename )
```

Open a file to import with filename, and call bool [Model::Import](#) with std::ifstream.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file with filename

```
Markov::Model<char> model;
model.Import("test.mdl");
```

Construct the matrix when done.


Definition at line 19 of file [modelMatrix.cpp](#).

```
00019
00020     this->DeallocateMatrix();
00021     this->Markov::API::MarkovPasswords::Import(filename);
00022     this->ConstructMatrix();
00023 }
```


References [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), and [Markov::Model< NodeStorageType >::Import\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.16 Import() [2/2]

```
bool Markov::Model< char >::Import (
    std::ifstream * f ) [inherited]
```

Import a file to construct the model.

File contains a list of edges. For more info on the file format, check out the wiki and github readme pages. Format is: Left_repr;EdgeWeight;right_repr

Iterate over this list, and construct nodes and edges accordingly.

Returns

True if successful, False for incomplete models or corrupt file formats

Example Use: Import a file from ifstream

```
Markov::Model<char> model;
std::ifstream file("test.mdl");
model.Import(&file);
```

Definition at line 216 of file [model.h](#).

```
00216     std::string cell; {
00217     std::string cell;
00218     char src;
00219     char target;
00220     long int oc;
00221
00222     while (std::getline(*f, cell)) {
00223         //std::cout << "cell: " << cell << std::endl;
00224         src = cell[0];
00225         target = cell[cell.length() - 1];
00226         char* j;
00227         oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(), &j, 10);
00228         //std::cout << oc << "\n";
00229         Markov::Node<NodeStorageType>* srcN;
00230         Markov::Node<NodeStorageType>* targetN;
00231         Markov::Edge<NodeStorageType>* e;
00232         if (this->nodes.find(src) == this->nodes.end()) {
00233             srcN = new Markov::Node<NodeStorageType>(src);
00234             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(src, srcN));
00235             //std::cout << "Creating new node at start.\n";
00236         }
00237         else {
00238             srcN = this->nodes.find(src)->second;
00239         }
00240
00241         if (this->nodes.find(target) == this->nodes.end()) {
00242             targetN = new Markov::Node<NodeStorageType>(target);
00243             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(target, targetN));
00244             //std::cout << "Creating new node at end.\n";
00245         }
00246         else {
00247             targetN = this->nodes.find(target)->second;
00248         }
00249         e = srcN->Link(targetN);
00250         e->AdjustEdge(oc);
00251         this->edges.push_back(e);
00252
00253         //std::cout << int(srcN->NodeValue()) << " --> " << e->EdgeWeight() << "--> " <<
00254         int(targetN->NodeValue()) << "\n";
```

```

00255
00256
00257     }
00258
00259     this->OptimizeEdgeOrder();
00260
00261     return true;
00262 }
```

9.17.3.17 Nodes()

`std::map<char , Node<char >>* Markov::Model< char >::Nodes () [inline], [inherited]`
 Return starter Node.

Returns

starter node with 00 NodeValue

Definition at line 181 of file [model.h](#).

```
00181 { return &nodes; }
```

9.17.3.18 OpenDatasetFile()

`std::ifstream * Markov::API::MarkovPasswords::OpenDatasetFile (`
 `const char * filename) [inherited]`
 Open dataset file and return the ifstream pointer.

Parameters

<code>filename</code>	- Filename to open
-----------------------	--------------------

Returns

`ifstream*` to the the dataset file


Definition at line 51 of file [markovPasswords.cpp](#).

```

00051
00052
00053     std::ifstream* datasetFile;
00054
00055     std::ifstream newFile(filename);
00056
00057     datasetFile = &newFile;
00058
00059     this->Import(datasetFile);
00060     return datasetFile;
00061 }
```

References [Markov::Model< NodeStorageType >::Import\(\)](#).

Here is the call graph for this function:



9.17.3.19 OptimizeEdgeOrder()

`void Markov::Model< char >::OptimizeEdgeOrder [inherited]`

Sort edges of all nodes in the model ordered by edge weights.

Definition at line 265 of file [model.h](#).

```
00265     {
00266     for (std::pair<unsigned char, Markov::Node<NodeStorageType>*> const& x : this->nodes) {
00267         //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
00268         std::sort (x.second->edgesV.begin(), x.second->edgesV.end(), [](Edge<NodeStorageType> *lhs,
00269             Edge<NodeStorageType> *rhs) ->bool{
00270             return lhs->EdgeWeight() > rhs->EdgeWeight();
00271         });
00272         //for(int i=0;i<x.second->edgesV.size();i++)
00273         // std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00274         //std::cout << "\n";
00275     }
00276     //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00277     //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00278 }
```

9.17.3.20 RandomWalk()

```
char * Markov::Model< char >::RandomWalk (
    Markov::Random::RandomEngine * randomEngine,
    int minSetting,
    int maxSetting,
    NodeStorageType * buffer ) [inherited]
```

Do a random walk on this model.

Start from the starter node, on each node, invoke RandomNext using the random engine on current node, until terminator node is reached. If terminator node is reached before minimum length criteria is reached, ignore the last selection and re-invoke randomNext

If maximum length criteria is reached but final node is not, cut off the generation and proceed to the final node. This function takes [Markov::Random::RandomEngine](#) as a parameter to generate pseudo random numbers from

This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne output is higher in entropy, most use cases don't really need super high entropy output, so [Markov::Random::Marsaglia](#) is preferable for better performance.

This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening via maximum length criteria.

Example Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use Marsaglia

```
Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}
```

Parameters

<i>randomEngine</i>	Random Engine to use for the random walks. For examples, see Markov::Random::Mersenne and Markov::Random::Marsaglia
<i>minSetting</i>	Minimum number of characters to generate
<i>maxSetting</i>	Maximum number of character to generate
<i>buffer</i>	buffer to write the result to

Returns

Null terminated string that was generated.

Definition at line 307 of file [model.h](#).

```
00307     {
00308     Markov::Node<NodeStorageType>* n = this->starterNode;
00309     int len = 0;
00310     Markov::Node<NodeStorageType>* temp_node;
00311     while (true) {
00312         temp_node = n->RandomNext(randomEngine);
00313         if (len >= maxSetting) {
00314             break;
00315         }
00316     }
00317 }
```

```

00316     else if ((temp_node == NULL) && (len < minSetting)) {
00317         continue;
00318     }
00319
00320     else if (temp_node == NULL) {
00321         break;
00322     }
00323
00324     n = temp_node;
00325
00326     buffer[len++] = n->NodeValue();
00327 }
00328
00329 //null terminate the string
00330 buffer[len] = 0x00;
00331
00332 //do something with the generated string
00333 return buffer; //for now
00334 }
```

9.17.3.21 Save()

```
std::ofstream * Markov::API::MarkovPasswords::Save (
    const char * filename ) [inherited]
Export model to file.
```

Parameters

<i>filename</i>	- Export filename.
-----------------	--------------------

Returns

`std::ofstream*` of the exported file.


Definition at line 106 of file [markovPasswords.cpp](#).

```

00106
00107     std::ofstream* exportFile;
00108
00109     std::ofstream newFile(filename);
00110
00111     exportFile = &newFile;
00112
00113     this->Export(exportFile);
00114     return exportFile;
00115 }
```

References [Markov::Model< NodeStorageType >::Export\(\)](#).

Here is the call graph for this function:



9.17.3.22 StarterNode()

```
Node<char>*>* Markov::Model< char >::StarterNode ( ) [inline], [inherited]
Return starter Node.
```

Returns

starter node with 00 NodeValue

Definition at line 171 of file [model.h](#).

```
00171 { return starterNode; }
```

9.17.3.23 Train()

```
void Markov::API::ModelMatrix::Train (
    const char * datasetFileName,
    char delimiter,
    int threads )
```

Train the model with the dataset file.

Parameters

<i>datasetFileName</i>	- ifstream* to the dataset. If null, use class member
<i>delimiter</i>	- a character, same as the delimiter in dataset content
<i>threads</i>	- number of OS threads to spawn

```
Markov::API::MarkovPasswords mp;
mp.Import("models/2gram.mdl");
mp.Train("password.corpus");
```

Construct the matrix when done.


Definition at line 25 of file [modelMatrix.cpp](#).

```
00025
00026     this->DeallocateMatrix();
00027     this->Markov::API::MarkovPasswords::Train(datasetFileName,delimiter,threads);
00028     this->ConstructMatrix();
00029 }
```


References [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), and [Markov::API::MarkovPasswords::Train\(\)](#).

Referenced by [Markov::Markopy::BOOST_PYTHON_MODULE\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.3.24 TrainThread()

```
void Markov::API::MarkovPasswords::TrainThread (
    Markov::API::Concurrency::ThreadSharedListHandler * listhandler,
    char delimiter ) [private], [inherited]
```

A single thread invoked by the Train function.

Parameters

<i>listhandler</i>	- Listhandler class to read corpus from
<i>delimiter</i>	- a character, same as the delimiter in dataset content


Definition at line 85 of file [markovPasswords.cpp](#).

```
00085
00086     char format_str[] = "%ld,%s";
00087     format_str[3]=delimiter;
00088     std::string line;
00089     while (listhandler->next(&line) && keepRunning) {
00090         long int oc;
00091         if (line.size() > 100) {
00092             line = line.substr(0, 100);
00093         }
00094         char* linebuf = new char[line.length()+5];
00095 #ifdef _WIN32
00096         sscanf_s(line.c_str(), "%ld,%s", &oc, linebuf, line.length()+5); //<== changed format_str to-
00097         "%ld,%s"
00098     else
00099         sscanf(line.c_str(), format_str, &oc, linebuf);
00100 #endif
00101     this->AdjustEdge((const char*)linebuf, oc);
00102     delete linebuf;
00103 }
```


References [Markov::Model< NodeStorageType >::AdjustEdge\(\)](#), [keepRunning](#), and [Markov::API::Concurrency::ThreadSharedListHandler::next\(\)](#).

Referenced by [Markov::API::MarkovPasswords::Train\(\)](#).

Here is the call graph for this function:



Here is the caller graph for this function:



9.17.4 Member Data Documentation

9.17.4.1 datasetFile

`std::ifstream* Markov::API::MarkovPasswords::datasetFile [private], [inherited]`
 Definition at line 123 of file [markovPasswords.h](#).

9.17.4.2 edgeMatrix

`char** Markov::API::ModelMatrix::edgeMatrix [protected]`
 2-D Character array for the edge Matrix (The characters of Nodes)
 Definition at line 175 of file [modelMatrix.h](#).
 Referenced by [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), [DumpJSON\(\)](#), and [FastRandomWalkThread\(\)](#).

9.17.4.3 edges

`std::vector<Edge<char>*> Markov::Model<char>::edges [private], [inherited]`
 A list of all edges in this model.
 Definition at line 204 of file [model.h](#).

9.17.4.4 matrixIndex

`char* Markov::API::ModelMatrix::matrixIndex [protected]`
 to hold the Matrix index (To hold the orders of 2-D arrays)
 Definition at line 190 of file [modelMatrix.h](#).
 Referenced by [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), [DumpJSON\(\)](#), and [FastRandomWalkThread\(\)](#).

9.17.4.5 matrixSize

`int Markov::API::ModelMatrix::matrixSize [protected]`
 to hold Matrix size
 Definition at line 185 of file [modelMatrix.h](#).
 Referenced by [ConstructMatrix\(\)](#), [DeallocateMatrix\(\)](#), [DumpJSON\(\)](#), [FastRandomWalkThread\(\)](#), and [Markov::API::CUDA::CUDAMode](#)

9.17.4.6 modelSavefile

`std::ofstream* Markov::API::MarkovPasswords::modelSavefile [private], [inherited]`
 Dataset file input of our system
 Definition at line 124 of file [markovPasswords.h](#).

9.17.4.7 nodes

`std::map<char, Node<char>*> Markov::Model<char>::nodes [private], [inherited]`
 Map LeftNode is the Nodes NodeValue Map RightNode is the node pointer.
 Definition at line 193 of file [model.h](#).

9.17.4.8 outputFile

`std::ofstream* Markov::API::MarkovPasswords::outputFile [private], [inherited]`
 File to save model of our system

Definition at line 125 of file [markovPasswords.h](#).

9.17.4.9 ready

```
bool Markov::API::ModelMatrix::ready [protected]  
True when matrix is constructed. False if not.  
Definition at line 200 of file modelMatrix.h.  
Referenced by ConstructMatrix\(\), DeallocateMatrix\(\), and ModelMatrix\(\).
```

9.17.4.10 starterNode

```
Node<char>*>* Markov::Model< char >::starterNode [private], [inherited]  
Starter Node of this model.  
Definition at line 198 of file model.h.
```

9.17.4.11 totalEdgeWeights

```
long int* Markov::API::ModelMatrix::totalEdgeWeights [protected]  
Array of the Total Edge Weights.  
Definition at line 195 of file modelMatrix.h.  
Referenced by ConstructMatrix\(\), DeallocateMatrix\(\), and FastRandomWalkThread\(\).
```

9.17.4.12 valueMatrix


```
long int** Markov::API::ModelMatrix::valueMatrix [protected]  
2-d Integer array for the value Matrix (For the weights of Edges)  
Definition at line 180 of file modelMatrix.h.  
Referenced by ConstructMatrix\(\), DeallocateMatrix\(\), DumpJSON\(\), and FastRandomWalkThread\(\).  
The documentation for this class was generated from the following files:
```

- [modelMatrix.h](#)
- [modelMatrix.cpp](#)

9.18 **Markov::Node< storageType >** Class Template Reference

A node class that for the vertices of model. Connected with eachother using [Edge](#).
`#include <model.h>`

Collaboration diagram for `Markov::Node< storageType >`:



Public Member Functions

- [Node \(\)](#)
Default constructor. Creates an empty `Node`.
- [Node \(storageType _value\)](#)
Constructor. Creates a `Node` with no edges and with given `NodeValue`.
- [Edge<storageType> * Link \(Node<storageType> *\)](#)
Link this node with another, with this node as its source.
- [Edge<storageType> * Link \(Edge<storageType> *\)](#)
Link this node with another, with this node as its source.
- [Node<storageType> * RandomNext \(Markov::Random::RandomEngine *randomEngine\)](#)
Choose a random node from the list of edges, with regards to its `EdgeWeight`, and `TraverseNode` to that.
- [bool UpdateEdges \(Edge<storageType> *\)](#)
Insert a new edge to the `this.edges`.
- [Edge<storageType> * FindEdge \(storageType repr\)](#)
Find an edge with its character representation.
- [Edge<storageType> * FindEdge \(Node<storageType> *target\)](#)
Find an edge with its pointer. Avoid unless necessary because computational cost of find by character is cheaper (because of `std::map`)
- [unsigned char NodeValue \(\)](#)
Return character representation of this node.

- void [UpdateTotalVertexWeight](#) (long int offset)
Change total weights with offset.
- std::map< storageType, [Edge](#)< storageType > * > * [Edges](#) ()
return edges
- long int [TotalEdgeWeights](#) ()
return total edge weights

Public Attributes

- std::vector< [Edge](#)< storageType > * > [edgesV](#)

Private Attributes

- storageType [_value](#)
Character representation of this node. 0 for starter, 0xff for terminator.
- long int [total_edge_weights](#)
Total weights of the vertices, required by RandomNext.
- std::map< storageType, [Edge](#)< storageType > * > [edges](#)
A map of all edges connected to this node, where this node is at the LeftNode. Map is indexed by unsigned char, which is the character representation of the node.

9.18.1 Detailed Description

```
template<typename storageType>
class Markov::Node< storageType >
```

A node class that for the vertices of model. Connected with eachother using [Edge](#).

This class will later be templated to accept other data types than char*.

Definition at line 27 of file [model.h](#).

9.18.2 Constructor & Destructor Documentation

9.18.2.1 Node() [1/2]

```
template<typename storageType >
Markov::Node< storageType >::Node
Default constructor. Creates an empty Node.
Definition at line 209 of file node.h.
00209
00210     this->\_value = 0;
00211     this->total\_edge\_weights = 0L;
00212 }
```

9.18.2.2 Node() [2/2]

```
template<typename storageType >
Markov::Node< storageType >::Node (
    storageType \_value)
Constructor. Creates a Node with no edges and with given NodeValue.
```

Parameters

_value	- Nodes character representation.
------------------------	-----------------------------------

Example Use: Construct nodes

```
Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
```

```

Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
Definition at line 203 of file node.h.
00203
00204     this->_value = _value;
00205     this->total_edge_weights = 0L;
00206 };

```


9.18.3 Member Function Documentation

9.18.3.1 Edges()

```

template<typename storageType >
std::map< storageType, Markov::Edge< storageType > * > * Markov::Node< storageType >::Edges
[inline]
return edges
Definition at line 272 of file node.h.
00272
00273     return &(this->edges);
00274 }
Referenced by Markov::API::MarkovPasswords::Buff\(\).
Here is the caller graph for this function:

```



9.18.3.2 FindEdge() [1/2]

```

template<typename storageType >
Edge<storageType>* Markov::Node< storageType >::FindEdge (
    Node< storageType > * target )

```

Find an edge with its pointer. Avoid unless necessary because computational cost of find by character is cheaper (because of std::map)

Parameters

<i>target</i>	- target node.
---------------	----------------

Returns

[Edge](#) that is connected between this node, and the target node.

9.18.3.3 FindEdge() [2/2]

```

template<typename storageType >
Markov::Edge< storageType > * Markov::Node< storageType >::FindEdge (
    storageType repr )

```

Find an edge with its character representation.

Parameters

<i>repr</i>	- character NodeValue of the target node.
-------------	---

Returns

[Edge](#) that is connected between this node, and the target node.

Example Use: Construct and update edges

```
Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
Markov::Edge<unsigned char>* res = NULL;
src->Link(target1);
src->Link(target2);
res = src->FindEdge('b');
```

Definition at line 260 of file [node.h](#).

```
00260
00261     auto e = this->edges.find(repr);
00262     if (e == this->edges.end()) return NULL;
00263     return e->second;
00264 };
```

9.18.3.4 Link() [1/2]

```
template<typename storageType >
Markov::Edge< storageType > * Markov::Node< storageType >::Link (
    Markov::Edge< storageType > * v )
```

Link this node with another, with this node as its source.

DOES NOT create a new [Edge](#).

Parameters

Edge	- Edge that will accept this node as its LeftNode.
----------------------	--

Returns

the same edge as parameter target.

Example Use: Construct and link nodes

```
Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
LeftNode->Link(e);
```

Definition at line 227 of file [node.h](#).

```
00227
00228     v->SetLeftEdge(this);
00229     this->UpdateEdges(v);
00230     return v;
00231 }
```

9.18.3.5 Link() [2/2]

```
template<typename storageType >
Markov::Edge< storageType > * Markov::Node< storageType >::Link (
    Markov::Node< storageType > * n )
```

Link this node with another, with this node as its source.

Creates a new [Edge](#).

Parameters

target	- Target node which will be the RightNode() of new edge.
------------------------	--

Returns

A new node with LeftNode as this, and RightNode as parameter target.

Example Use: Construct nodes

```
Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
```

```

Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
Definition at line 220 of file node.h.
00220
00221     Markov::Edge<storageType>* v = new Markov::Edge<storageType>(this, n);
00222     this->UpdateEdges(v);
00223     return v;
00224 }

```

9.18.3.6 NodeValue()

```

template<typename storageType >
unsigned char Markov::Node< storageType >::NodeValue [inline]
Return character representation of this node.

```

Returns

character representation at _value.

Definition at line 215 of file node.h.


```

00215
00216     return _value;
00217 }

```

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:



9.18.3.7 RandomNext()

```

template<typename storageType >
Markov::Node< storageType > * Markov::Node< storageType >::RandomNext (
    Markov::Random::RandomEngine * randomEngine )

```

Chose a random node from the list of edges, with regards to its EdgeWeight, and TraverseNode to that.

This operation is done by generating a random number in range of 0-this.total_edge_weights, and then iterating over the list of edges. At each step, EdgeWeight of the edge is subtracted from the random number, and once it is 0, next node is selected.

Returns

`Node` that was chosen at EdgeWeight biased random.

Example Use: Use randomNext to do a random walk on the model

```

char* buffer[64];
Markov::Model<char> model;
model.Import("model.mdl");
Markov::Node<char>* n = model.starterNode;
int len = 0;
Markov::Node<char>* temp_node;
while (true) {
    temp_node = n->RandomNext(randomEngine);
    if (len >= maxSetting) {
        break;
    }
    else if ((temp_node == NULL) && (len < minSetting)) {
        continue;
    }
    else if (temp_node == NULL){
        break;
    }
}

```

```

n = temp_node;
buffer[len++] = n->NodeValue();
}

Definition at line 234 of file node.h.
00234
00235
00236     //get a random NodeValue in range of total_vertex_weight
00237     long int selection = randomEngine->random() %
00238         this->total_edge_weights;/distribution()(generator());// distribution(generator);
00239     //make absolute, no negative modulus values wanted
00240     //selection = (selection >= 0) ? selection : (selection + this->total_edge_weights);
00241     for(int i=0;i<this->edgesV.size();i++){
00242         selection -= this->edgesV[i]->EdgeWeight();
00243         if (selection < 0) return this->edgesV[i]->TraverseNode();
00244     }
00245     //if this assertion is reached, it means there is an implementation error above
00246     std::cout << "This should never be reached (node failed to walk to next)\n"; //cant assert from
00247     child thread
00248     assert(true && "This should never be reached (node failed to walk to next)");
00249     return NULL;
00249 }
```


9.18.3.8 TotalEdgeWeights()

```

template<typename storageType >
long int Markov::Node< storageType >::TotalEdgeWeights [inline]
return total edge weights
Definition at line 277 of file node.h.
00277
00278     return this->total_edge_weights;
00279 }
```

Referenced by [Markov::API::ModelMatrix::ConstructMatrix\(\)](#).

Here is the caller graph for this function:



9.18.3.9 UpdateEdges()

```

template<typename storageType >
bool Markov::Node< storageType >::UpdateEdges (
    Markov::Edge< storageType > * v )
Insert a new edge to the this.edges.
```

Parameters

<code>edge</code>	- New edge that will be inserted.
-------------------	-----------------------------------

Returns

true if insertion was successful, false if it fails.

Example Use: Construct and update edges

```

Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target2);
e1->AdjustEdge(25);
src->UpdateEdges(e1);
```

```
e2->AdjustEdge(30);
src->UpdateEdges(e2);
Definition at line 252 of file node.h.
00252
00253     this->edges.insert({ v->RightNode()->NodeValue(), v });
00254     this->edgesV.push_back(v);
00255     //this->total_edge_weights += v->EdgeWeight();
00256     return v->TraverseNode();
00257 }
```

9.18.3.10 UpdateTotalVerticeWeight()

```
template<typename storageType >
void Markov::Node< storageType >::UpdateTotalVerticeWeight (
    long int offset )
Change total weights with offset.
```

Parameters

<i>offset</i>	to adjust the vertice weight with
---------------	-----------------------------------

Definition at line 267 of file node.h.

```
00267
00268     this->total_edge_weights += offset;
00269 }
```

9.18.4 Member Data Documentation

9.18.4.1 _value

```
template<typename storageType >
storageType Markov::Node< storageType >::_value [private]
Character representation of this node. 0 for starter, 0xff for terminator.
Definition at line 179 of file node.h.
Referenced by Markov::Node< NodeStorageType >::NodeValue\(\).
```

9.18.4.2 edges

```
template<typename storageType >
std::map<storageType, Edge<storageType>*> Markov::Node< storageType >::edges [private]
A map of all edges connected to this node, where this node is at the LeftNode. Map is indexed by unsigned char,
which is the character representation of the node.
Definition at line 190 of file node.h.
```

9.18.4.3 edgesV

```
template<typename storageType >
std::vector<Edge<storageType>*> Markov::Node< storageType >::edgesV
Definition at line 173 of file node.h.
```

9.18.4.4 total_edge_weights


```
template<typename storageType >
long int Markov::Node< storageType >::total_edge_weights [private]
Total weights of the vertices, required by RandomNext.
Definition at line 184 of file node.h.
```

The documentation for this class was generated from the following files:


- [model.h](#)
- [node.h](#)

9.19 QMainWindow Class Reference

Inheritance diagram for QMainWindow:



Collaboration diagram for QMainWindow:



The documentation for this class was generated from the following file:


- [menu.h](#)

9.20 Markov::Random::RandomEngine Class Reference


An abstract class for [Random](#) Engine.

```
#include <random.h>
```

Inheritance diagram for `Markov::Random::RandomEngine`:



Collaboration diagram for `Markov::Random::RandomEngine`:



Public Member Functions

- `virtual unsigned long random ()=0`

9.20.1 Detailed Description

An abstract class for [Random](#) Engine.

This class is used for generating random numbers, which are used for random walking on the graph.

Main reason behind allowing different random engines is that some use cases may favor performance, while some favor good random.

[Mersenne](#) can be used for truer random, while [Marsaglia](#) can be used for deterministic but fast random.

Definition at line 30 of file [random.h](#).

9.20.2 Member Function Documentation


9.20.2.1 random()

```
virtual unsigned long Markov::Random::RandomEngine::random () [inline], [pure virtual]
```

Implemented in [Markov::Random::Marsaglia](#), and [Markov::Random::DefaultRandomEngine](#).

Referenced by [Markov::Node< NodeStorageType >::RandomNext\(\)](#).

Here is the caller graph for this function:



The documentation for this class was generated from the following file:


- [random.h](#)

9.21 Markov::API::CLI::Terminal Class Reference

pretty colors for [Terminal](#). Windows Only.

```
#include <term.h>
```

Collaboration diagram for `Markov::API::CLI::Terminal`:



Public Types

- enum `color` {

RESET, BLACK, RED, GREEN,

YELLOW, BLUE, MAGENTA, CYAN,

WHITE, LIGHTGRAY, DARKGRAY, BROWN
 }

Public Member Functions

- [Terminal \(\)](#)

Static Public Attributes

- static std::map< [Markov::API::CLI::Terminal::color](#), int > [colormap](#)
- static std::ostream [endl](#)

9.21.1 Detailed Description

pretty colors for [Terminal](#). Windows Only.

Definition at line [25](#) of file [term.h](#).

9.21.2 Member Enumeration Documentation

9.21.2.1 color

```
enum Markov::API::CLI::Terminal::color
```

Enumerator

RESET	
BLACK	
RED	
GREEN	
YELLOW	
BLUE	
MAGENTA	
CYAN	
WHITE	
LIGHTGRAY	
DARKGRAY	
BROWN	

Definition at line [33](#) of file [term.h](#).

```
00033 { RESET, BLACK, RED, GREEN, YELLOW, BLUE, MAGENTA, CYAN, WHITE, LIGHTGRAY, DARKGRAY, BROWN };
```

9.21.3 Constructor & Destructor Documentation

9.21.3.1 Terminal()

```
Terminal::Terminal ( )
```

Default constructor. Get references to stdout and stderr handles.

Definition at line [62](#) of file [term.cpp](#).

```
00062 {  
00063 /*this->;*/  
00064 }
```

9.21.4 Member Data Documentation

9.21.4.1 colormap

```
std::map< Terminal::color, int > Terminal::colormap [static]
```

Initial value:

```
= {
    {Terminal::color::BLACK, 30},
    {Terminal::color::BLUE, 34},
    {Terminal::color::GREEN, 32},
    {Terminal::color::CYAN, 36},
    {Terminal::color::RED, 31},
    {Terminal::color::MAGENTA, 35},
    {Terminal::color::BROWN, 01},
    {Terminal::color::LIGHTGRAY, 0},
    {Terminal::color::DARKGRAY, 0},
    {Terminal::color::YELLOW, 33},
    {Terminal::color::WHITE, 37},
    {Terminal::color::RESET, 0},
}
```

Definition at line 39 of file [term.h](#).

Referenced by [operator<<\(\)](#).

9.21.4.2 endl

```
std::ostream Markov::API::CLI::Terminal::endl [static]
```

Definition at line 44 of file [term.h](#).

The documentation for this class was generated from the following files:

- [term.h](#)


- [term.cpp](#)

9.22 Markov::API::Concurrency::ThreadSharedListHandler Class Reference

Simple class for managing shared access to file.

```
#include <threadSharedListHandler.h>
```

Collaboration diagram for Markov::API::Concurrency::ThreadSharedListHandler:



Public Member Functions

- `ThreadSharedListHandler (const char *filename)`

Construct the Thread Handler with a filename.

- `bool next (std::string *line)`

Read the next line from the file.

Private Attributes

- std::ifstream [listfile](#)
- std::mutex [mlock](#)

9.22.1 Detailed Description

Simple class for managing shared access to file.

This class maintains the handover of each line from a file to multiple threads.

When two different threads try to read from the same file while reading a line isn't completed, it can have unexpected results. Line might be split, or might be read twice. This class locks the read action on the list until a line is completed, and then proceeds with the handover.

Definition at line 25 of file [threadSharedListHandler.h](#).

9.22.2 Constructor & Destructor Documentation

9.22.2.1 ThreadSharedListHandler()

```
Markov::API::Concurrency::ThreadSharedListHandler::ThreadSharedListHandler (
    const char * filename )
```

Construct the Thread Handler with a filename.

Simply open the file, and initialize the locks.

Example Use: Simple file read

```
ThreadSharedListHandler listhandler("test.txt");
std::string line;
std::cout << listhandler->next(&line) << "\n";
```

Example Use: Example use case from [MarkovPasswords](#) showing multithreaded access

```
void MarkovPasswords::Train(const char* datasetFileName, char delimiter, int threads) {
    ThreadSharedListHandler listhandler(datasetFileName);
    auto start = std::chrono::high_resolution_clock::now();
    std::vector<std::thread*> threadsV;
    for(int i=0;i<threads;i++) {
        threadsV.push_back(new std::thread(&MarkovPasswords::TrainThread, this, &listhandler,
        datasetFileName, delimiter));
    }
    for(int i=0;i<threads;i++){
        threadsV[i]->join();
        delete threadsV[i];
    }
    auto finish = std::chrono::high_resolution_clock::now();
    std::chrono::duration<double> elapsed = finish - start;
    std::cout << "Elapsed time: " << elapsed.count() << " s\n";
}
void MarkovPasswords::TrainThread(ThreadSharedListHandler *listhandler, const char* datasetFileName, char
    delimiter){
    char format_str[] ="%ld,%s";
    format_str[2]=delimiter;
    std::string line;
    while (listhandler->next(&line)) {
        long int oc;
        if (line.size() > 100) {
            line = line.substr(0, 100);
        }
        char* linebuf = new char[line.length()+5];
        sscanf_s(line.c_str(), format_str, &oc, linebuf, line.length()+5);
        this->AdjustEdge((const char*)linebuf, oc);
        delete linebuf;
    }
}
```

Parameters

filename	Filename for the file to manage.
--------------------------	----------------------------------


Definition at line 12 of file [threadSharedListHandler.cpp](#).

```
00012
00013     this->listfile;
00014     this->listfile.open(filename, std::ios_base::binary);
00015 }
```

References [listfile](#).

Referenced by [Markov::API::MarkovPasswords::Train\(\)](#).

Here is the caller graph for this function:



9.22.3 Member Function Documentation

9.22.3.1 next()

```
bool Markov::API::Concurrency::ThreadSharedListHandler::next (
    std::string * line )
```

Read the next line from the file.

This action will be blocked until another thread (if any) completes the read operation on the file.

Example Use: Simple file read

```
ThreadSharedListHandler listhandler("test.txt");
std::string line;
std::cout << listhandler->next(&line) << "\n";
```

Definition at line 18 of file [threadSharedListHandler.cpp](#).

```
00018
00019     bool res = false;
00020     this->mlock.lock();
00021     res = (std::getline(this->listfile,*line,'\'\n'))? true : false;
00022     this->mlock.unlock();
00023
00024     return res;
00025 }
```

References [listfile](#), and [mlock](#).

Referenced by [Markov::API::MarkovPasswords::TrainThread\(\)](#).

Here is the caller graph for this function:



9.22.4 Member Data Documentation

9.22.4.1 listfile

```
std::ifstream Markov::API::Concurrency::ThreadSharedListHandler::listfile [private]
```

Definition at line 95 of file [threadSharedListHandler.h](#).

Referenced by [next\(\)](#), and [ThreadSharedListHandler\(\)](#).

9.22.4.2 mlock

```
std::mutex Markov::API::Concurrency::ThreadSharedListHandler::mlock [private]
```

Definition at line 96 of file [threadSharedListHandler.h](#).

Referenced by [next\(\)](#).

The documentation for this class was generated from the following files:


- [threadSharedListHandler.h](#)
- [threadSharedListHandler.cpp](#)

9.23 Markov::GUI::Train Class Reference


QT Training page class.

```
#include <Train.h>
```

Inheritance diagram for Markov::GUI::Train:



Collaboration diagram for Markov::GUI::Train:



Public Slots

- void [home \(\)](#)
- void [train \(\)](#)

Public Member Functions

- [Train \(QWidget *parent=Q_NULLPTR\)](#)

Private Attributes

- [Ui::Train ui](#)

9.23.1 Detailed Description

QT Training page class.

Definition at line [15](#) of file [Train.h](#).

9.23.2 Constructor & Destructor Documentation

9.23.2.1 Train()

```
Markov::GUI::Train::Train (
    QWidget * parent = Q_NULLPTR )
```

Definition at line [22](#) of file [Train.cpp](#).

```
00023     : QMainWidget(parent)
00024 {
00025     ui.setupUi(this);
00026
00027
00028
```

```

00029     QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {train(); });
00030     QObject::connect(ui.pushButton_2, &QPushButton::clicked, this, [this] {home(); });
00031     //QObject::connect(ui.pushButton_3, &QPushButton::clicked, this, [this] {goGenerate(); });
00032
00033     //ui.pushButton_3->setVisible(false);
00034
00035
00036 }
```

References [ui](#).

9.23.3 Member Function Documentation

9.23.3.1 home

```
void Markov::GUI::Train::home ( ) [slot]
```

Definition at line 73 of file [Train.cpp](#).

```

00073     {
00074         CLI* w = new CLI;
00075         w->show();
00076         this->close();
00077 }
```

9.23.3.2 train

```
void Markov::GUI::Train::train ( ) [slot]
```


Definition at line 38 of file [Train.cpp](#).

```

00038     {
00039
00040
00041
00042     QString file_name = QFileDialog::getOpenFileName(this, "Open a File", QDir::homePath());
00043     QFile file(file_name);
00044
00045     if (!file.open(QFile::ReadOnly | QFile::Text)) {
00046         QMessageBox::warning(this, "Error", "File Not Open!");
00047     }
00048     QTextStream in(&file);
00049     QString text = in.readAll();
00050     ui.plainTextEdit->setPlainText(text);
00051
00052
00053     char* cstr;
00054     std::string fname = file_name.toStdString();
00055     cstr = new char[fname.size() + 1];
00056     strcpy(cstr, fname.c_str());
00057
00058
00059
00060     char a=',' ;
00061     Markov::API::MarkovPasswords mp;
00062     mp.Import("models/2gram.mdl");
00063     mp.Train(cstr, a, 10); //please parameterize this hardcoded 10 threads
00064     mp.Export("models/finished.mdl");
00065
00066     ui.label_2->setText("Training DONE!");
00067     //ui.pushButton_3->setVisible(true);
00068
00069
00070     file.close();
00071 }
```

References [Markov::API::MarkovPasswords::Train\(\)](#), and [ui](#).

Here is the call graph for this function:



9.23.4 Member Data Documentation

9.23.4.1 ui

`Ui::Train` `Markov::GUI::Train::ui` [private]

Definition at line 21 of file [Train.h](#).

Referenced by [Train\(\)](#), and [train\(\)](#).

The documentation for this class was generated from the following files:

- [Train.h](#)
- [Train.cpp](#)

CHAPTER10


File Documentation

10.1 about.cpp File Reference

About page.

```
#include <fstream>
#include <QtWidgets/QApplication>
#include "about.h"
```

Include dependency graph for about.cpp:



10.1.1 Detailed Description

About page.

Authors

Yunus Emre Yilmaz

Definition in file [about.cpp](#).


10.2 about.cpp

```
00001
00002 /** @file about.cpp
00003 * @brief About page
00004 * @authors Yunus Emre Yilmaz
00005 *
00006 */
00007
00008 #include <fstream>
00009 #include <QtWidgets/QApplication>
00010 #include "about.h"
00011
00012 using namespace Markov::GUI;
00013
00014 about::about(QWidget* parent)
00015     : QMainWindow(parent)
00016 {
00017     ui.setupUi(this);
00018 }
00019 }
```


10.3 about.h File Reference

About page.

```
#include <QtWidgets/QMainWindow>
#include "ui_about.h"
#include <ui_menu.h>
Include dependency graph for about.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::GUI::about](#)

QT Class for about page.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::GUI](#)

namespace for MarkovPasswords [API GUI](#) wrapper

10.3.1 Detailed Description

About page.

Authors

Yunus Emre Yılmaz

Definition in file [about.h](#).

10.4 about.h

```


00001 /** @file about.h
00002 * @brief About page
00003 * @authors Yunus Emre Yilmaz
00004 *
00005 */
00006
00007 #pragma once
00008 #include <QtWidgets/QMainWindow>
00009 #include "ui_about.h"
00010 #include <ui_menu.h>
00011
00012 /** @brief namespace for MarkovPasswords API GUI wrapper
00013 */
00014 namespace Markov::GUI{
00015
00016     /** @brief QT Class for about page
00017     */
00018     class about :public QMainWindow {
00019     Q_OBJECT
00020     public:
00021         about(QWidget* parent = Q_NULLPTR);
00022
00023     private:
00024         Ui:: main ui;
00025
00026     };
00027 };
00028 
```

10.5 argparse.cpp File Reference

Arguement handler class for native CPP cli.

```
#include "argparse.h"
#include "color/term.h"
```

Include dependency graph for argparse.cpp:



10.5.1 Detailed Description

Arguement handler class for native CPP cli.

Authors

Celal Sahir Çetiner

Parse command line arguements.

Definition in file [argparse.cpp](#).

10.6 argparse.cpp

```

00001 /** @file argparse.cpp
00002 * @brief Arguement handler class for native CPP cli
  
```


```

00003 * @authors Celal Sahir Çetiner
00004 *
00005 * @copydoc Markov::API::CLI::Argparse
00006 */
00007
00008 #include "argparse.h"
00009 #include "color/term.h"
00010
00011 Markov::API::CLI::ProgramOptions* Markov::API::CLI::Argparse::parse(int argc, char** argv) { return 0;
00012 }
00013
00014
00015 void Markov::API::CLI::Argparse::help() {
00016     std::cout <<
00017     "Markov Passwords - Help\n"
00018     "Options:\n"
00019     "\n"
00020     " -of --outputfilename\n"
00021     "     Filename to output the generation results\n"
00022     " -ef --exportfilename\n"
00023     "     filename to export built model to\n"
00024     " -if --importfilename\n"
00025     "     filename to import model from\n"
00026     " -n (generate count)\n"
00027     "     Number of lines to generate\n"
00028     "\n"
00029     "Usage: \n"
00030     "     markov.exe -if empty_model.mdl -ef model.mdl\n"
00031     "             import empty_model.mdl and train it with data from stdin. When done, output the model to
model.mdl\n"
00032     "\n"
00033     "     markov.exe -if empty_model.mdl -n 15000 -of wordlist.txt\n"
00034     "             import empty_model.mdl and generate 15000 words to wordlist.txt\n"
00035
00036     << std::endl;
00037 }
```


10.7 argparse.h File Reference

Argument handler class for native CPP cli.

```
#include <string>
#include <iostream>
#include <boost/program_options.hpp>
Include dependency graph for argparse.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- struct [Markov::API::CLI::_programOptions](#)
Structure to hold parsed cli arguments.
- class [Markov::API::CLI::Argparse](#)
Parse command line arguments.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords API](#).
- [Markov::API::CLI](#)
Structure to hold parsed cli arguments.

Macros

- `#define BOOST_ALL_STATIC_LIB 1`
- `#define BOOST_PROGRAM_OPTIONS_STATIC_LIB 1`

Typedefs

- typedef struct [Markov::API::CLI::_programOptions](#) [Markov::API::CLI::ProgramOptions](#)
Structure to hold parsed cli arguments.

10.7.1 Detailed Description

Argument handler class for native CPP cli.

Authors

Celal Sahir Çetiner

Definition in file [argparse.h](#).

10.7.2 Macro Definition Documentation

10.7.2.1 BOOST_ALL_STATIC_LIB

```
#define BOOST_ALL_STATIC_LIB 1
Definition at line 11 of file argparse.h.
```

10.7.2.2 BOOST_PROGRAM_OPTIONS_STATIC_LIB

```
#define BOOST_PROGRAM_OPTIONS_STATIC_LIB 1
Definition at line 12 of file argparse.h.
```

10.8 argparse.h

```
00001 /** @file argparse.h
00002 * @brief Argument handler class for native CPP cli
00003 * @authors Celal Sahir Çetiner
00004 *
00005 * @copydoc Markov::API::CLI::Argparse:
00006 */
00007
00008 #include<string>
00009 #include<iostream>
00010
00011 #define BOOST_ALL_STATIC_LIB 1
00012 #define BOOST_PROGRAM_OPTIONS_STATIC_LIB 1
00013
00014 #include <boost/program_options.hpp>
00015
00016 /** @brief Structure to hold parsed cli arguments.
00017 */
00018 namespace opt = boost::program_options;
00019
00020 /**
00021      @brief Namespace for the CLI objects
00022 */
00023 namespace Markov::API::CLI{
00024
00025     /** @brief Structure to hold parsed cli arguments. */
00026     typedef struct _programOptions {
00027         /**
00028                  @brief Import flag to validate import
00029             */
00030             bool bImport;
00031
00032         /**
00033                  @brief Export flag to validate export
00034             */
00035             bool bExport;
00036
00037         /**
00038                  @brief Failure flag to validate succesfull running
00039             */
00040             bool bFailure;
00041
00042         /**
00043                  @brief Separator character to use with training data. (character between occurrence and
00044             value)"
00045             */
00046             char separator;
00047
00048         /**
00049                  @brief Import name of our model
00050             */
00051             std::string importname;
00052
00053         /**
00054                  @brief Import name of our given wordlist
00055             */
00056             std::string exportname;
00057
00058         /**
00059                  @brief Import name of our given wordlist
00060             */
00061             std::string wordlistname;
00062
00063         /**
00064                  @brief Output name of our generated password list
00065             */
00066             std::string outputfilename;
00067         /**
```

```

00068      @brief The name of the given dataset
00069      */
00070      std::string datasetname;
00071
00072      /**
00073          @brief Number of passwords to be generated
00074      */
00075      int generateN;
00076
00077  } ProgramOptions;
00078
00079
00080  /** @brief Parse command line arguments
00081  */
00082  class Argparse {
00083  public:
00084      Argparse();
00085
00086      /** @brief Parse command line arguments.
00087      *
00088      * Parses command line arguments to populate ProgramOptions structure.
00089      *
00090      * @param argc Number of command line arguments
00091      * @param argv Array of command line parameters
00092      */
00093
00094  Argparse(int argc, char** argv) {
00095
00096      /*bool bImp;
00097      bool bExp;
00098      bool bFail;
00099      char sprt;
00100      std::string imports;
00101      std::string exports;
00102      std::string outputs;
00103      std::string datasets;
00104      int generateN;
00105      */
00106      opt::options_description desc("Options");
00107
00108
00109      desc.add_options()
00110          ("generate", "Generate strings with given parameters")
00111          ("train", "Train model with given parameters")
00112          ("combine", "Combine")
00113          ("import", opt::value<std::string>(), "Import model file")
00114          ("output", opt::value<std::string>(), "Output model file. This model will be exported
when done. Will be ignored for generation mode")
00115          ("dataset", opt::value<std::string>(), "Dataset file to read input from training. Will
be ignored for generation mode")
00116          ("separator", opt::value<char>(), "Separator character to use with training data.
(character between occurrence and value)")
00117          ("wordlist", opt::value<std::string>(), "Wordlist file path to export generation
results to. Will be ignored for training mode")
00118          ("count", opt::value<int>(), "Number of lines to generate. Ignored in training mode")
00119          ("verbosity", "Output verbosity")
00120          ("help", "Option definitions");
00121
00122      opt::variables_map vm;
00123
00124      opt::store(opt::parse_command_line(argc, argv, desc), vm);
00125
00126      opt::notify(vm);
00127
00128      //std::cout << desc << std::endl;
00129      if (vm.count("help")) {
00130          std::cout << desc << std::endl;
00131      }
00132
00133      if (vm.count("output") == 0) this->po.outputfilename = "NULL";
00134      else if (vm.count("output") == 1) {
00135          this->po.outputfilename = vm["output"].as<std::string>();
00136          this->po.bExport = true;
00137      }
00138      else {
00139          this->po.bFailure = true;
00140          std::cout << "UNIDENTIFIED INPUT" << std::endl;
00141          std::cout << desc << std::endl;
00142      }
00143
00144      if (vm.count("dataset") == 0) this->po.datasetname = "NULL";
00145      else if (vm.count("dataset") == 1) {
00146          this->po.datasetname = vm["dataset"].as<std::string>();
00147      }
00148      else {
00149          this->po.bFailure = true;

```

```

00151             std::cout << "UNIDENTIFIED INPUT" << std::endl;
00152             std::cout << desc << std::endl;
00153         }
00154
00155
00156         if (vm.count("wordlist") == 0) this->po.wordlistname = "NULL";
00157         else if (vm.count("wordlist") == 1) {
00158             this->po.wordlistname = vm["wordlist"].as<std::string>();
00159         }
00160         else {
00161             this->po.bFailure = true;
00162             std::cout << "UNIDENTIFIED INPUT" << std::endl;
00163             std::cout << desc << std::endl;
00164         }
00165
00166         if (vm.count("import") == 0) this->po.importname = "NULL";
00167         else if (vm.count("import") == 1) {
00168             this->po.importname = vm["import"].as<std::string>();
00169             this->po.bImport = true;
00170         }
00171         else {
00172             this->po.bFailure = true;
00173             std::cout << "UNIDENTIFIED INPUT" << std::endl;
00174             std::cout << desc << std::endl;
00175         }
00176
00177
00178         if (vm.count("count") == 0) this->po.generateN = 0;
00179         else if (vm.count("count") == 1) {
00180             this->po.generateN = vm["count"].as<int>();
00181         }
00182         else {
00183             this->po.bFailure = true;
00184             std::cout << "UNIDENTIFIED INPUT" << std::endl;
00185             std::cout << desc << std::endl;
00186         }
00187
00188         /*std::cout << vm["output"].as<std::string>() << std::endl;
00189         std::cout << vm["dataset"].as<std::string>() << std::endl;
00190         std::cout << vm["wordlist"].as<std::string>() << std::endl;
00191         std::cout << vm["output"].as<std::string>() << std::endl;
00192         std::cout << vm["count"].as<int>() << std::endl;*/
00193
00194
00195         //else if (vm.count("train")) std::cout << "train oldu" << std::endl;
00196     }
00197
00198     /** @brief Getter for command line options
00199      *
00200      * @return ProgramOptions populated by the argument parser
00201      * @returns ProgramOptions structure.
00202      */
00203     Markov::API::CLI::ProgramOptions getProgramOptions(void) {
00204         return this->po;
00205     }
00206
00207     /** @brief Initialize program options structure.
00208      *
00209      * @param i boolean, true if import operation is flagged
00210      * @param e boolean, true if export operation is flagged
00211      * @param bf boolean, true if there is something wrong with the command line parameters
00212      * @param s separator character for the import function
00213      * @param iName import filename
00214      * @param exName export filename
00215      * @param oName output filename
00216      * @param dName corpus filename
00217      * @param n number of passwords to be generated
00218      *
00219      */
00220     void setProgramOptions(bool i, bool e, bool bf, char s, std::string iName, std::string exName,
00221     std::string oName, std::string dName, int n) {
00222         this->po.bImport = i;
00223         this->po.bExport = e;
00224         this->po.separator = s;
00225         this->po.bFailure = bf;
00226         this->po.generateN = n;
00227         this->po.importname = iName;
00228         this->po.exportname = exName;
00229         this->po.outputfilename = oName;
00230         this->po.datasetname = dName;
00231
00232         /*strcpy_s(this->po.importname,256,iName);
00233         strcpy_s(this->po.exportname,256,exName);
00234         strcpy_s(this->po.outputfilename,256,oName);
00235         strcpy_s(this->po.datasetname,256,dName);*/
00236     }

```

```

00237     /**
00238      * @brief parse cli commands and return
00239      * @param argc - Program argument count
00240      * @param argv - Program argument values array
00241      * @return ProgramOptions structure.
00242      */
00243     static Markov::API::CLI::ProgramOptions* parse(int argc, char** argv);
00244
00245
00246     /**
00247      * @brief Print help string.
00248      */
00249     static void help();
00250
00251     /**
00252      * @brief ProgramOptions structure object
00253      */
00254
00255     Markov::API::CLI::ProgramOptions po;
00256
00257 };
00258 };


```

10.9 CLI.cpp File Reference

CLI page.

```
#include "CLI.h"
#include <fstream>
#include "Train.h"
```

Include dependency graph for CLI.cpp:



10.9.1 Detailed Description

CLI page.

Authors

Yunus Emre Yılmaz

Definition in file [CLI.cpp](#).

10.10 CLI.cpp

```

00001 /**
00002  * @file cli.cpp
00003  * @brief CLI page
00004  * @authors Yunus Emre Yılmaz
00005  */
00006
00007 #include "CLI.h"

```

```

00008 #include <fstream>
00009 #include "Train.h"
00010
00011
00012
00013 using namespace Markov::GUI;
00014
00015 Markov::GUI::CLI::CLI(QWidget* parent)
00016     : QMainWindow(parent)
00017 {
00018     ui.setupUi(this);
00019
00020     QObject::connect(ui.startButton, &QPushButton::clicked, this, [this] {start(); });
00021     QObject::connect(ui.commandLinkButton_2, &QPushButton::clicked, this, [this] {statistics(); });
00022     QObject::connect(ui.commandLinkButton, &QPushButton::clicked, this, [this] {about(); });
00023
00024 }
00025
00026 void Markov::GUI::CLI::start() {
00027     Train* w = new Train;
00028     w->show();
00029     this->close();
00030 }
00031 void Markov::GUI::CLI::statistics() {
00032     /*
00033     statistic will show
00034     */
00035 }
00036 void Markov::GUI::CLI::about() {
00037     /*
00038     about button
00039     */
00040 }

```


10.11 CLI.h File Reference

CLI page.


```
#include <QtWidgets/QMainWindow>
```

```
#include "ui_CLI.h"
```

Include dependency graph for CLI.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::GUI::CLI](#)

QT CLI Class.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::GUI](#)

namespace for MarkovPasswords API GUI wrapper

10.11.1 Detailed Description

CLI page.

Authors

Yunus Emre Yilmaz

Definition in file [CLI.h](#).

10.12 CLI.h


```
00001 /** @file cli.h
00002 * @brief CLI page
00003 * @authors Yunus Emre Yilmaz
00004 *
00005 */
00006
00007 #pragma once
00008 #include <QtWidgets/QMainWindow>
00009 #include "ui_CLI.h"
00010
00011 namespace Markov::GUI{
00012     /** @brief QT CLI Class
00013     */
00014     class CLI :public QMainWindow {
00015         Q_OBJECT
00016     public:
00017         CLI(QWidget* parent = Q_NULLPTR);
00018
00019     private:
00020         Ui::CLI ui;
00021
00022     public slots:
00023         void start();
00024         void statistics();
00025         void about();
00026     };
00027 };
```

10.13 cudaDeviceController.cu File Reference

Simple static class for basic CUDA device controls.

```
#include "cudaDeviceController.h"
#include <iostream>
#include <curand_kernel.h>
#include <cuda.h>
#include <cuda_runtime.h>
#include <device_launch_parameters.h>
```

Include dependency graph for cudaDeviceController.cu:



Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords API](#).
- [Markov::API::CUDA](#)
Namespace for objects requiring [CUDA](#) libraries.

10.13.1 Detailed Description

Simple static class for basic CUDA device controls.

Authors

Ata Hakçıl

Controller class for CUDA device. This implementation only supports Nvidia devices.

Definition in file [cudaDeviceController.cu](#).

10.14 cudaDeviceController.cu

```

00001 /**
00002 * @file cudaDeviceController.cu
00003 * @brief Simple static class for basic CUDA device controls.
00004 * @authors Ata Hakçıl
00005 * @copydoc Markov::API::CUDA::CUDADeviceController
00006 */
00007
00008 #include "cudaDeviceController.h"
00009 #include <iostream>
00010 #include <curand_kernel.h>
00011 #include <cuda.h>
00012 #include <cuda_runtime.h>
00013 #include <device_launch_parameters.h>
00014
00015 namespace Markov::API::CUDA{
00016     __host__ void Markov::API::CUDA::CUDADeviceController::ListCudaDevices() { //list cuda Capable
00017         int nDevices;
00018         cudaGetDeviceCount(&nDevices);
00019         for (int i = 0; i < nDevices; i++) {
00020             cudaDeviceProp prop;
00021             cudaGetDeviceProperties(&prop, i);
00022             std::cerr << "Device Number: " << i << "\n";
00023             std::cerr << "Device name: " << prop.name << "\n";
00024             std::cerr << "Memory Clock Rate (KHz): " << prop.memoryClockRate << "\n";
00025             std::cerr << "Memory Bus Width (bits): " << prop.memoryBusWidth << "\n";
00026             std::cerr << "Peak Memory Bandwidth (GB/s): " << 2.0 * prop.memoryClockRate *
00027             (prop.memoryBusWidth / 8) / 1.0e6 << "\n";
00028             std::cerr << "Max Linear Threads: " << prop.maxThreadsDim[0] << "\n";
00029         }
00030     }
00031
00032     __host__ int Markov::API::CUDA::CUDADeviceController::CudaCheckNotifyErr(cudaError_t _status,
00033     const char* msg, bool bExit) {
00034         if (_status != cudaSuccess) {
  
```

```

00034     std::cerr << "\033[1;31m" << msg << " -> " << cudaGetErrorString(_status) << "(" << _status <
00035     ")" << "\033[0m" << "\n";
00036     if(bExit) {
00037         cudaDeviceReset();
00038         exit(1);
00039     }
00040 }
00041     return 0;
00042 }
00043
00044 */
00045     template <typename T>
00046     __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMalloc2DToFlat(T* dst, int row,
00047     int col){
00048         return cudaMalloc((T **) &dst, row*col*sizeof(T));
00049     }
00050     template <typename T>
00051     __host__ cudaError_t Markov::API::CUDA::CUDADeviceController::CudaMemcpy2DToFlat(T* dst, T** src,
00052     int row, int col){
00053         cudaError_t cudastatus;
00054         for(int i=0;i<row;i++){
00055             cudastatus = cudaMemcpy(dst + (i*col*sizeof(T)),
00056             src[i], col*sizeof(T), cudaMemcpyHostToDevice);
00057             if(cudastatus != cudaSuccess) return cudastatus;
00058         }
00059     }
00060 */
00061
00062 };


```

10.15 cudaDeviceController.h File Reference


Simple static class for basic CUDA device controls.

```
#include <iostream>
```

Include dependency graph for cudaDeviceController.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::CUDA::CUDADeviceController](#)

Controller class for CUDA device.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains Model, Node and Edge classes.
- [Markov::API](#)
Namespace for the MarkovPasswords API.
- [Markov::API::CUDA](#)
Namespace for objects requiring CUDA libraries.

10.15.1 Detailed Description

Simple static class for basic CUDA device controls.

Authors

Ata Hakçıl

Controller class for CUDA device. This implementation only supports Nvidia devices.

Definition in file [cudaDeviceController.h](#).

10.16 cudaDeviceController.h

```

00001 /** @file cudaDeviceController.h
00002  * @brief Simple static class for basic CUDA device controls.
00003  * @authors Ata Hakçıl
00004  *
00005  * @copydoc Markov::API::CUDA::CUDADeviceController
00006  */
00007
00008 #pragma once
00009 #include <iostream>
00010
00011 /** @brief Namespace for objects requiring CUDA libraries.
00012  */
00013 namespace Markov::API::CUDA{
00014     /** @brief Controller class for CUDA device
00015      *
00016      * This implementation only supports Nvidia devices.
00017      */
00018     class CUDADeviceController{
00019         public:
00020             /** @brief List CUDA devices in the system.
00021              *

```

```

00022     * This function will print details of every CUDA capable device in the system.
00023
00024     *
00025     * @b Example @b output:
00026     * @code{.txt}
00027     * Device Number: 0
00028     * Device name: GeForce RTX 2070
00029     * Memory Clock Rate (KHz): 7001000
00030     * Memory Bus Width (bits): 256
00031     * Peak Memory Bandwidth (GB/s): 448.064
00032     * Max Linear Threads: 1024
00033     * @endcode
00034
00035     */
00036
00037     __host__ static void ListCudaDevices();
00038
00039     protected:
00040         /** @brief Check results of the last operation on GPU.
00041         *
00042         * Check the status returned from cudaMalloc/cudaMemcpy to find failures.
00043         *
00044         * If a failure occurs, its assumed beyond redemption, and exited.
00045         * @param _status Cuda error status to check
00046         * @param msg Message to print in case of a failure
00047         * @return 0 if successful, 1 if failure.
00048         * @b Example @b output:
00049         * @code{.cpp}
00050         * char *da, a = "test";
00051         * cudastatus = cudaMalloc((char **)&da, 5*sizeof(char));
00052         * CudaCheckNotifyErr(cudastatus, "Failed to allocate VRAM for *da.\n");
00053         * @endcode
00054
00055     __host__ static int CudaCheckNotifyErr(cudaError_t _status, const char* msg, bool bExit=true);
00056
00057     /** @brief Malloc a 2D array in device space
00058     *
00059     * This function will allocate enough space on VRAM for flattened 2D array.
00060     *
00061     * @param dst destination pointer
00062     * @param row row size of the 2d array
00063     * @param col column size of the 2d array
00064     * @return cudaError_t status of the cudaMalloc operation
00065
00066     * @b Example @b output:
00067     * @code{.cpp}
00068     *     cudaError_t cudastatus;
00069     *     char* dst;
00070     *     cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
00071     *     if(cudastatus!=cudaSuccess){
00072     *         CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
00073     *     }
00074     *     @endcode
00075
00076     template <typename T>
00077     __host__ static cudaError_t CudaMalloc2DToFlat(T** dst, int row, int col){
00078         cudaError_t cudastatus = cudaMalloc((T **)dst, row*col*sizeof(T));
00079         CudaCheckNotifyErr(cudastatus, "cudaMalloc Failed.", false);
00080         return cudastatus;
00081     }
00082
00083     /** @brief Memcpy a 2D array in device space after flattening
00084     *
00085     * Resulting buffer will not be true 2D array.
00086     *
00087     * @param dst destination pointer
00088     * @param rc source pointer
00089     * @param row row size of the 2d array
00090     * @param col column size of the 2d array
00091     * @return cudaError_t status of the cudaMemcpy operation
00092
00093     * @b Example @b output:
00094     * @code{.cpp}
00095     *     cudaError_t cudastatus;
00096     *     char* dst;
00097     *     cudastatus = CudaMalloc2DToFlat<char>(&dst, 5, 15);
00098     *     CudaCheckNotifyErr(cudastatus, " CudaMalloc2DToFlat Failed.", false);
00099     *     cudastatus = CudaMemcpy2DToFlat<char>(*dst,src,15,15);
00100     *     CudaCheckNotifyErr(cudastatus, " CudaMemcpy2DToFlat Failed.", false);
00101     *     @endcode
00102
00103     template <typename T>
00104     __host__ static cudaError_t CudaMemcpy2DToFlat(T* dst, T** src, int row, int col){
00105         T* tempbuf = new T[row*col];
00106         for(int i=0;i<row;i++){
00107             memcpy(&(tempbuf[row*i]), src[i], col);
00108         }
00109         return cudaMemcpy(dst, tempbuf, row*col*sizeof(T), cudaMemcpyHostToDevice);
00110

```

```

00109
00110     }
00111
00112     /** @brief Both malloc and memcpy a 2D array into device VRAM.
00113     *
00114     * Resulting buffer will not be true 2D array.
00115     *
00116     * @param dst destination pointer
00117     * @param rc source pointer
00118     * @param row row size of the 2d array
00119     * @param col column size of the 2d array
00120     * @return cudaError_t status of the cudaMalloc operation
00121     *
00122     * @b Example @b output:
00123     * @code{.cpp}
00124     *   cudaError_t cudastatus;
00125     *   char* dst;
00126     *   cudastatus = CudaMigrate2DFlat<long int>(
00127     *       &dst, this->valueMatrix, this->matrixSize, this->matrixSize);
00128     *   CudaCheckNotifyErr(cudastatus, "    Cuda failed to initialize value matrix row.");
00129     * @endcode
00130   */
00131   template <typename T>
00132   __host__ static cudaError_t CudaMigrate2DFlat(T** dst, T** src, int row, int col){
00133     cudaError_t cudastatus;
00134     cudastatus = CudaMalloc2DToFlat<T>(dst, row, col);
00135     if(cudastatus!=cudaSuccess){
00136       CudaCheckNotifyErr(cudastatus, "    CudaMalloc2DToFlat Failed.", false);
00137       return cudastatus;
00138     }
00139     cudastatus = CudaMemcpy2DToFlat<T>(*dst,src,row,col);
00140     CudaCheckNotifyErr(cudastatus, "    CudaMemcpy2DToFlat Failed.", false);
00141     return cudastatus;
00142   }
00143
00144
00145   private:
00146 };
00147 };

```

10.17 cudaModelMatrix.cu File Reference


CUDA accelerated extension of [Markov::API::ModelMatrix](#).

```

#include "cudaModelMatrix.h"
#include "cudarandom.h"
#include <curand_kernel.h>
#include <cuda.h>
#include <cuda_runtime.h>
#include <device_launch_parameters.h>

```

Include dependency graph for `cudaModelMatrix.cu`:



Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::API](#)

Namespace for the [MarkovPasswords API](#).

- [Markov::API::CUDA](#)

Namespace for objects requiring CUDA libraries.

Functions

- `__global__ void Markov::API::CUDA::FastRandomWalkCUDAKernel (unsigned long int n, int minLen, int maxLen, char *outputBuffer, char *matrixIndex, long int *totalEdgeWeights, long int *valueMatrix, char *edgeMatrix, int matrixSize, int memoryPerKernelGrid, unsigned long *seed)`
CUDA kernel for the FastRandomWalk operation.
- `__device__ char * Markov::API::CUDA::strchr (char *p, char c, int s_len)`
strchr implementation on device space

10.17.1 Detailed Description

CUDA accelerated extension of [Markov::API::ModelMatrix](#).

Authors

Ata Hakçıl

Extension of [Markov::API::ModelMatrix](#) which is modified to run on GPU devices. This implementation only supports Nvidia devices.

Class to flatten and reduce [Markov::Model](#) to a Matrix. Matrix level operations can be used for Generation events, with a significant performance optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)

To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for allocation. Threads are synchronized and files are flushed every 50M operations.

Definition in file [cudaModelMatrix.cu](#).

10.18 cudaModelMatrix.cu

```

00001 /**
00002  * @file cudaModelMatrix.cu
00003  * @brief CUDA accelerated extension of Markov::API::ModelMatrix
00004  * @authors Ata Hakçıl
00005  * @copydoc Markov::API::CUDA::CUDAModelMatrix
00006 */
00007
00008 #include "cudaModelMatrix.h"
00009 #include "cudarandom.h"
00010
00011
00012 #include <curand_kernel.h>
00013 #include <cuda.h>
00014 #include <cuda_runtime.h>
00015 #include <device_launch_parameters.h>
00016
00017 using Markov::API::CUDA::CUDADeviceController;
00018
00019 namespace Markov::API::CUDA{
00020     __host__ void Markov::API::CUDA::CUDAModelMatrix::MigrateMatrix(){
00021         cudaError_t cudastatus;
00022
00023         cudastatus = cudaMalloc((char**)&(this->device_matrixIndex),
00024             this->matrixSize*sizeof(char));
00025         CudaCheckNotifyErr(cudastatus, "Cuda failed to initialize device_matrixIndex.");
00026
00027         cudastatus = cudaMalloc((long int **)&(this->device_totalEdgeWeights),
00028             this->matrixSize*sizeof(long int));
00029         CudaCheckNotifyErr(cudastatus, "Cuda failed to initialize device_totalEdgeWeights.");
00030
00031         cudastatus = cudaMemcpy(this->device_matrixIndex, this->matrixIndex,
00032             this->matrixSize*sizeof(char), cudaMemcpyHostToDevice);
00033         CudaCheckNotifyErr(cudastatus, "Cuda failed to copy to device memory. (Index)");
00034
00035         cudastatus = cudaMemcpy(this->device_totalEdgeWeights, this->totalEdgeWeights,
00036             this->matrixSize*sizeof(long int), cudaMemcpyHostToDevice);
00037         CudaCheckNotifyErr(cudastatus, "Cuda failed to copy to device memory. (Total Edge Values)");
00038
00039         cudastatus = CudaMigrate2DFlat<char>(
00040             &(this->device_edgeMatrix), this->edgeMatrix, this->matrixSize, this->matrixSize);
00041         CudaCheckNotifyErr(cudastatus, "Cuda failed to initialize edge matrix.");

```

```

00041     cudastatus = CudaMigrate2DFlat<long int>(
00042         &(this->device_valueMatrix), this->valueMatrix, this->matrixSize, this->matrixSize);
00043     CudaCheckNotifyErr(cudastatus, "    Cuda failed to initialize value matrix row.");
00044 }
00045
00046 */
00047
00048 /*__host__ char* Markov::API::CUDAModelMatrix::AllocVRAMOutputBuffer(long int n, long int
00049 singleGenMaxLen, long int CUDAKernelGridSize, long int sizePerGrid){
00050     cudaError_t cudastatus;
00051     cudastatus = cudaMalloc((char **)&this->device_outputBuffer1, CUDAKernelGridSize*sizePerGrid);
00052     CudaCheckNotifyErr(cudastatus, "Failed to allocate VRAM buffer. (Possibly out of VRAM.)");
00053
00054     return this->device_outputBuffer1;
00055 */
00056
00057
00058 __host__ void Markov::API::CUDAModelMatrix::FastRandomWalk(unsigned long int n, const char*
00059 wordlistFileName, int minLen, int maxLen, bool bFileIO, bool bInfinite){
00060     cudaDeviceProp prop;
00061     int device=0;
00062     cudaGetDeviceProperties(&prop, device);
00063     cudaChooseDevice(&device, &prop);
00064     //std::cout << "Flattening matrix." << std::endl;
00065     this->FlattenMatrix();
00066     //std::cout << "Migrating matrix." << std::endl;
00067     this->MigrateMatrix();
00068     //std::cout << "Migrated matrix." << std::endl;
00069     std::ofstream wordlist;
00070     if(bFileIO)
00071         wordlist.open(wordlistFileName);

00072
00073     cudaBlocks = 1024;
00074     cudaThreads = 256;
00075     iterationsPerKernelThread = 100;
00076     alternatingKernels = 2;
00077     totalOutputPerKernel = (long int)cudaBlocks*(long int)cudaThreads*iterationsPerKernelThread;
00078     totalOutputPerSync= totalOutputPerKernel*alternatingKernels;
00079     numberofPartitions = n/totalOutputPerSync;
00080     cudaGridSize = cudaBlocks*cudaThreads;
00081     cudaMemPerGrid = (maxLen+2)*iterationsPerKernelThread;
00082     cudaPerKernelAllocationSize = cudaGridSize*cudaMemPerGrid;
00083     this->prepKernelMemoryChannel(alternatingKernels);

00084
00085     unsigned long int leftover = n - (totalOutputPerSync*numberofPartitions);
00086
00087     if(bInfinite && !numberofPartitions) numberofPartitions=5;
00088     std::cerr << cudaPerKernelAllocationSize << "\n";
00089
00090     if(n%totalOutputPerSync) std::cerr << "For optimization, request outputs muliples of " <<
00091     totalOutputPerSync << ".\n";
00092
00093     //start kernelID 1
00094     this->LaunchAsyncKernel(1, minLen, maxLen);
00095
00096     for(int i=1;i<numberofPartitions;i++){
00097         if(bInfinite) i=0;
00098
00099         //wait kernelID1 to finish, and start kernelID 0
00100         cudaStreamSynchronize(this->cudastreams[1]);
00101         this->LaunchAsyncKernel(0, minLen, maxLen);
00102
00103         //start memcpy from kernel 1 (block until done)
00104         this->GatherAsyncKernelOutput(1, bFileIO, wordlist);
00105
00106         //wait kernelID 0 to finish, then start kernelID1
00107         cudaStreamSynchronize(this->cudastreams[0]);
00108         this->LaunchAsyncKernel(1, minLen, maxLen);
00109
00110         //start memcpy from kernel 0 (block until done)
00111         this->GatherAsyncKernelOutput(0, bFileIO, wordlist);
00112     }
00113
00114     //wait kernelID1 to finish, and start kernelID 0
00115     cudaStreamSynchronize(this->cudastreams[1]);
00116     this->LaunchAsyncKernel(0, minLen, maxLen);
00117     this->GatherAsyncKernelOutput(1, bFileIO, wordlist);
00118     cudaStreamSynchronize(this->cudastreams[0]);
00119     this->GatherAsyncKernelOutput(0, bFileIO, wordlist);
00120
00121
00122     if(!leftover) return;
00123     alternatingKernels=1;
00124     std::cerr << "Remaining line count (" << leftover << ") is lower than partition. Adjusting CUDA

```

```

        workload..\n";
00125    this->iterationsPerKernelThread = leftover/cudaGridSize;
00126    this->LaunchAsyncKernel(0, minLen, maxLen);
00127    cudaStreamSynchronize(this->cuadastreams[0]);
00128    this->GatherAsyncKernelOutput(0, bFileIO, wordlist);
00129
00130    leftover -= this->iterationsPerKernelThread*cudaGridSize;
00131    if(!leftover) return;
00132
00133    std::cerr << "Remaining line count (" << leftover << ") is lower than minimum possible. Handing
over to CPU generation.\n";
00134    this->iterationsPerKernelThread = leftover/cudaGridSize;
00135
00136    leftover -= this->iterationsPerKernelThread;
00137
00138    if(!leftover) return;
00139    std::cerr << "Remaining " << leftover << " lines are absolutely not worth printing.\n";
00140    Markov::API::ModelMatrix::ConstructMatrix();
00141    Markov::API::ModelMatrix::FastRandomWalk(leftover, &wordlist, minLen, maxLen, 1, bFileIO);
00142
00143 }
00144
00145 __host__ void Markov::API::CUDA::CUDAModelMatrix::prepKernelMemoryChannel(int numberOfStreams) {
00146
00147     this->cuadastreams = new cudaStream_t[numberOfStreams];
00148     for(int i=0;i<numberOfStreams;i++)
00149         cudaStreamCreate(&this->cuadastreams[i]);
00150
00151     this->outputBuffer = new char*[numberOfStreams];
00152     for(int i=0;i<numberOfStreams;i++)
00153         this->outputBuffer[i] = new char[cudaPerKernelAllocationSize];
00154
00155     cudaError_t cudastatus;
00156     this->device_outputBuffer = new char*[numberOfStreams];
00157     for(int i=0;i<numberOfStreams;i++){
00158         cudastatus = cudaMalloc((char**)&(device_outputBuffer[i]),
00159             cudaPerKernelAllocationSize);
00160         CudaCheckNotifyErr(cudastatus, "Failed to establish memory channel. Possibly out of
VRAM?");
00161     }
00162
00163     this->device_seeds = new unsigned long*[numberOfStreams];
00164     for(int i=0;i<numberOfStreams;i++){
00165         Markov::API::CUDA::Random::Marsaglia *MEarr = new
00166         Markov::API::CUDA::Random::Marsaglia[cudaGridSize];
00167         this->device_seeds[i] = Markov::API::CUDA::Random::Marsaglia::MigrateToVRAM(MEarr,
00168             cudaGridSize);
00169         delete[] MEarr;
00170     }
00171
00172     __host__ void Markov::API::CUDA::CUDAModelMatrix::LaunchAsyncKernel(int kernelID, int minLen, int
maxLen){
00173
00174     //if(kernelID == 0); // cudaStreamSynchronize(this->cuadastreams[2]);
00175     //else cudaStreamSynchronize(this->cuadastreams[kernelID-1]);
00176     FastRandomWalkCUDAKernel<<(cudaBlocks,cudaThreads,0,
00177     this->cuadastreams[kernelID]>>(iterationsPerKernelThread, minLen, maxLen,
00178     this->device_outputBuffer[kernelID], this->device_matrixIndex,
00179     this->device_totalEdgeWeights, this->device_valueMatrix, this->device_edgeMatrix,
00180     this->matrixSize, cudaMemPerGrid, this->device_seeds[kernelID]);
00181     //std::cerr << "Started kernel" << kernelID << "\n";
00182 }
00183
00184 __host__ void Markov::API::CUDA::CUDAModelMatrix::GatherAsyncKernelOutput(int kernelID, bool
bFileIO, std::ofstream &wordlist){
00185
00186     cudaMemcpy(this->outputBuffer[kernelID],this->device_outputBuffer[kernelID],cudaPerKernelAllocationSize,
00187     cudaMemcpyDeviceToHost);
00188     //std::cerr << "Kernel" << kernelID << " output copied\n";
00189     if(bFileIO){
00190         for(long int j=0;j<cudaPerKernelAllocationSize;j+=cudaMemPerGrid){
00191             wordlist << &this->outputBuffer[kernelID][j];
00192         }
00193     }else{
00194         for(long int j=0;j<cudaPerKernelAllocationSize;j+=cudaMemPerGrid){
00195             std::cout << &this->outputBuffer[kernelID][j];
00196         }
00197     }
00198
00199     __global__ void FastRandomWalkCUDAKernel(unsigned long int n, int minLen, int maxLen, char*
00200     outputBuffer,
00201     char* matrixIndex, long int* totalEdgeWeights, long int* valueMatrix, char *edgeMatrix, int
00202     matrixSize, int memoryPerKernelGrid, unsigned long *seed);
00203

```

```

00197     int kernelWorkerIndex = threadIdx.x + blockIdx.x * blockDim.x;
00198
00199     if(n==0) return;
00200
00201     char* e;
00202     int index = 0;
00203     char next;
00204     int len=0;
00205     long int selection;
00206     char cur;
00207     long int bufferctr = 0;
00208     unsigned long int *x,*y,*z,t;
00209     char* res = &outputBuffer[kernelWorkerIndex*memoryPerKernelGrid];
00210     x=&seed[kernelWorkerIndex*3];
00211     y=&seed[kernelWorkerIndex*3+1];
00212     z=&seed[kernelWorkerIndex*3+2];
00213     for (int i = 0; i < n; i++) {
00214         cur=199;
00215         len=0;
00216         while (true) {
00217             e = strchr(matrixIndex, cur, matrixSize);
00218             index = e - matrixIndex;
00219             /*selection = Markov::API::CUDA::Random::devrandom(
00220                 seed[kernelWorkerIndex*3],
00221                 seed[kernelWorkerIndex*3+1],
00222                 seed[kernelWorkerIndex*3+2]) % totalEdgeWeights[index];*/
00223             *x ^= *x « 16;
00224             *x ^= *x » 5;
00225             *x ^= *x « 1;
00226
00227             t = *x;
00228             *x = *y;
00229             *y = *z;
00230             *z = t ^ *x ^ *y;
00231             selection = *z % totalEdgeWeights[index];
00232             for(int j=0;j<matrixSize-1;j++){
00233                 selection -= valueMatrix[index*matrixSize + j];
00234                 if (selection < 0){
00235                     next = edgeMatrix[index*sizeof(char)*matrixSize + j];
00236                     break;
00237                 }
00238             }
00239
00240             if (len >= maxLen) break;
00241             else if ((next < 0) && (len < minLen)) continue;
00242             else if (next < 0) break;
00243             cur = next;
00244             res[bufferctr + len++] = cur;
00245         }
00246         res[bufferctr + len+] = '\n';
00247         bufferctr+=len;
00248     }
00249     res[bufferctr] = '\0';
00250 }
00251
00252 __device__ char* strchr(char* p, char c, int s_len){
00253     for (; ++p, s_len--) {
00254         if (*p == c)
00255             return((char *)p);
00256         if (!*p)
00257             return((char *)NULL);
00258     }
00259 }
00260
00261 __host__ void Markov::API::CUDA::CUDAModelMatrix::FlattenMatrix(){
00262     this->flatEdgeMatrix = new char[this->matrixSize*this->matrixSize];
00263
00264     this->flatValueMatrix = new long int[this->matrixSize*this->matrixSize];
00265     for(int i=0;i<this->matrixSize;i++){
00266         memcpy(&this->flatEdgeMatrix[i*this->matrixSize], this->edgeMatrix[i], this->matrixSize );
00267         memcpy(&this->flatValueMatrix[i*this->matrixSize], this->valueMatrix[i],
00268             this->matrixSize*sizeof(long int) );
00269     }
00270 }
00271
00272 };


```

10.19 cudaModelMatrix.h File Reference


CUDA accelerated extension of [Markov::API::ModelMatrix](#).

```
#include "MarkovAPI/src/modelMatrix.h"
#include "cudaDeviceController.h"
```

Include dependency graph for cudaModelMatrix.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::CUDA::CUDAModelMatrix](#)
Extension of `Markov::API::ModelMatrix` which is modified to run on GPU devices.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains `Model`, `Node` and `Edge` classes.
- [Markov::API](#)
Namespace for the `MarkovPasswords API`.
- [Markov::API::CUDA](#)
Namespace for objects requiring `CUDA` libraries.

Functions

- `__global__ void Markov::API::CUDA::FastRandomWalkCUDAKernel (unsigned long int n, int minLen, int maxLen, char *outputBuffer, char *matrixIndex, long int *totalEdgeWeights, long int *valueMatrix, char *edgeMatrix, int matrixSize, int memoryPerKernelGrid, unsigned long *seed)`

- CUDA kernel for the FastRandomWalk operation.*
- `__device__ char * Markov::API::CUDA::strchr (char *p, char c, int s_len)`
srtchr implementation on device space

10.19.1 Detailed Description

CUDA accelerated extension of [Markov::API::ModelMatrix](#).

Authors

Ata Hakçıl

Extension of [Markov::API::ModelMatrix](#) which is modified to run on GPU devices. This implementation only supports Nvidia devices.

Class to flatten and reduce [Markov::Model](#) to a Matrix. Matrix level operations can be used for Generation events, with a significant performance optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)

To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for allocation. Threads are synchronized and files are flushed every 50M operations.

Definition in file [cudaModelMatrix.h](#).

10.20 cudaModelMatrix.h

```

00001 /**
00002  * @file cudaModelMatrix.h
00003  * @brief CUDA accelerated extension of Markov::API::ModelMatrix
00004  * @authors Ata Hakçıl
00005  * @copydoc Markov::API::CUDAModelMatrix
00006 */
00007
00008 #include "MarkovAPI/src/modelMatrix.h"
00009 #include "cudaDeviceController.h"
00010
00011 /** @brief Namespace for objects requiring CUDA libraries.
00012 */
00013 namespace Markov::API::CUDA{
00014     /** @brief Extension of Markov::API::ModelMatrix which is modified to run on GPU devices.
00015      *
00016      * This implementation only supports Nvidia devices.
00017      * @copydoc Markov::API::ModelMatrix
00018 */
00019 class CUDAModelMatrix : public Markov::API::ModelMatrix, public CUDADeviceController{
00020 public:
00021     /** @brief Migrate the class members to the VRAM
00022      *
00023      * Cannot be used without calling Markov::API::ModelMatrix::ConstructMatrix at least once.
00024      * This function will manage the memory allocation and data transfer from CPU RAM to GPU VRAM.
00025      *
00026      * Newly allocated VRAM pointers are set in the class member variables.
00027      *
00028 */
00029     __host__ void MigrateMatrix();
00030
00031     /** @brief Flatten migrated matrix from 2d to 1d
00032      *
00033      */
00034     __host__ void FlattenMatrix();
00035
00036     /** @brief Random walk on the Matrix-reduced Markov::Model
00037      *
00038      * TODO
00039      *
00040      *
00041      *
00042      * @param n - Number of passwords to generate.
00043      * @param wordlistFileName - Filename to write to
00044      * @param minLen - Minimum password length to generate
00045      * @param maxLen - Maximum password length to generate
00046      * @param threads - number of OS threads to spawn
00047      * @param bFileIO - If false, filename will be ignored and will output to stdout.
00048      *
00049      *
00050      *
00051      * @code{.cpp}
00052      * Markov::API::ModelMatrix mp;
00053      * mp.Import("models/finished.mdl");
00054      * mp.FastRandomWalk(50000000,"./wordlist.txt",6,12,25, true);

```

```

00055     * @endcode
00056     *
00057     */
00058     __host__ void FastRandomWalk(unsigned long int n, const char* wordlistFileName, int minLen,
00059     int maxLen, bool bFileIO, bool bInfinite);
00060
00061     protected:
00062
00063         /** @brief Allocate the output buffer for kernel operation
00064         *
00065         * TODO
00066         *
00067         * @param n - Number of passwords to generate.
00068         * @param singleGenMaxLen - maximum string length for a single generation
00069         * @param CUDAKernelGridSize - Total number of grid members in CUDA kernel
00070         * @param sizePerGrid - Size to allocate per grid member
00071         * @return pointer to the allocation on VRAM
00072         *
00073         *
00074         */
00075     __host__ char* AllocVRAMOutputBuffer(long int n, long int singleGenMaxLen, long int
00076     CUDAKernelGridSize, long int sizePerGrid);
00077
00078     __host__ void LaunchAsyncKernel(int kernelID, int minLen, int maxLen);
00079
00080     __host__ void prepKernelMemoryChannel(int numberOfWorkstreams);
00081
00082     __host__ void GatherAsyncKernelOutput(int kernelID, bool bFileIO, std::ofstream &wordlist);
00083
00084     private:
00085
00086         /**
00087         * @brief VRAM Address pointer of edge matrix (from modelMatrix.h)
00088         */
00089     char* device_edgeMatrix;
00090
00091         /**
00092         * @brief VRAM Address pointer of value matrix (from modelMatrix.h)
00093         */
00094     long int *device_valueMatrix;
00095
00096         /**
00097         * @brief VRAM Address pointer of matrixIndex (from modelMatrix.h)
00098         */
00099     char *device_matrixIndex;
00100
00101         /**
00102         * @brief VRAM Address pointer of total edge weights (from modelMatrix.h)
00103         */
00104     long int *device_totalEdgeWeights;
00105
00106         /**
00107         * @brief RandomWalk results in device
00108         */
00109     char** device_outputBuffer;
00110
00111         /**
00112         * @brief RandomWalk results in host
00113         */
00114     char** outputBuffer;
00115
00116         /**
00117         * @brief Adding Edge matrix end-to-end and resize to 1-D array for better performance on
00118         * traversing
00119         */
00120     char* flatEdgeMatrix;
00121
00122         /**
00123         * @brief Adding Value matrix end-to-end and resize to 1-D array for better performance on
00124         * traversing
00125         */
00126     long int* flatValueMatrix;
00127
00128     int cudaBlocks;
00129     int cudaThreads;
00130     int iterationsPerKernelThread;
00131     long int totalOutputPerSync;
00132     long int totalOutputPerKernel;
00133     int numberOfWorkPartitions;
00134     int cudaGridSize;
00135     int cudaMemPerGrid;
00136     long int cudaPerKernelAllocationSize;
00137     int alternatingKernels;
00138
00139     unsigned long** device_seeds;

```

```

00138
00139     cudaStream_t *cudastreams;
00140
00141 };
00142
00143 /** @brief CUDA kernel for the FastRandomWalk operation
00144 *
00145 * Will be initiated by CPU and continued by GPU (__global__ tag)
00146 *
00147 *
00148 * @param n - Number of passwords to generate.
00149 * @param minlen - minimum string length for a single generation
00150 * @param maxlen - maximum string length for a single generation
00151 * @param outputBuffer - VRAM ptr to the output buffer
00152 * @param matrixIndex - VRAM ptr to the matrix indices
00153 * @param totalEdgeWeights - VRAM ptr to the totalEdgeWeights array
00154 * @param valueMatrix - VRAM ptr to the edge weights array
00155 * @param edgeMatrix - VRAM ptr to the edge representations array
00156 * @param matrixSize - Size of the matrix dimensions
00157 * @param memoryPerKernelGrid - Maximum memory usage per kernel grid
00158 * @param seed - seed chunk to generate the random from (generated & used by Marsaglia)
00159 *
00160 *
00161 *
00162 */
00163 __global__ void FastRandomWalkCUDAKernel(unsigned long int n, int minLen, int maxlen, char*
00164     outputBuffer,
00165     char* matrixIndex, long int* totalEdgeWeights, long int* valueMatrix, char *edgeMatrix,
00166     int matrixSize, int memoryPerKernelGrid, unsigned long *seed); //, unsigned long mex, unsigned
00167     long mey, unsigned long mez);
00168
00169 /**
00170 * @brief srtchr implementation on __device__ space
00171 *
00172 * Find the first matching index of a string
00173 *
00174 * @param p - string to check
00175 * @param c - character to match
00176 * @param s_len - maximum string length
00177 * @returns pointer to the match
00178 */
00179 __device__ char* strchr(char* p, char c, int s_len);
00180 };


```

10.21 cudarandom.h File Reference


Extension of [Markov::Random::Marsaglia](#) for CUDA.

```
#include "MarkovModel/src/random.h"
#include "cudaDeviceController.h"
```

Include dependency graph for cudarandom.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::CUDA::Random::Marsaglia](#)

*Extension of [Markov::Random::Marsaglia](#) which is capable of working on **device** space.*

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::API](#)

Namespace for the [MarkovPasswords API](#).

- [Markov::API::CUDA](#)

Namespace for objects requiring [CUDA](#) libraries.

- [Markov::API::CUDA::Random](#)

*Namespace for [Random](#) engines operable under **device** space.*

Functions

- `__device__ unsigned long Markov::API::CUDA::Random::devrandom (unsigned long &x, unsigned long &y, unsigned long &z)`

*Marsaglia Random Generation function operable in **device** space.*

10.21.1 Detailed Description

Extension of [Markov::Random::Marsaglia](#) for CUDA.

Authors

Ata Hakçıl

Implementation of Marsaglia Random Engine. This is an implementation of Marsaglia Random engine, which for most use cases is a better fit than other solutions. Very simple mathematical formula to generate pseudorandom integer, so its crazy fast.

This implementation of the Marsaglia Engine is seeded by [random.h](#) default random engine. RandomEngine is only seeded once so its not a performance issue.

Example Use: Using Marsaglia Engine with RandomWalk

```

Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
  
```

```
}
```

Example Use: Generating a random number with Marsaglia Engine

```
Markov::Random::Marsaglia me;
```

```
std::cout << me.random();
```

Definition in file [cudarandom.h](#).


10.22 cudarandom.h

```
00001 /** @file cudarandom.h
00002 * @brief Extension of Markov::Random::Marsaglia for CUDA
00003 * @authors Ata Hakçıl
00004 *
00005 * @copydoc Markov::Random::Marsaglia
00006 */
00007
00008 #pragma once
00009 #include "MarkovModel/src/random.h"
00010 #include "cudaDeviceController.h"
00011
00012 /** @brief Namespace for Random engines operable under __device__ space.
00013 */
00014 namespace Markov::API::CUDA::Random{
00015
00016 /** @brief Extension of Markov::Random::Marsaglia which is capable of working on __device__ space.
00017 *
00018 * @copydoc Markov::Random::Marsaglia
00019 */
00020 class Marsaglia : public Markov::Random::Marsaglia, public CUDADeviceController{
00021 public:
00022
00023     /** @brief Migrate a Marsaglia[] to VRAM as seedChunk
00024     * @param MEarr Array of Marsaglia Engines
00025     * @param gridSize GridSize of the CUDA Kernel, aka size of array
00026     * @returns pointer to the resulting seed chunk in device VRAM.
00027     */
00028     static unsigned long* MigrateToVRAM(Markov::API::CUDA::Random::Marsaglia *MEarr, long int
gridSize) {
00029         cudaError_t cudastatus;
00030         unsigned long* seedChunk;
00031         cudastatus = cudaMalloc((unsigned long**)&seedChunk, gridSize*3*sizeof(unsigned long));
00032         CudaCheckNotifyErr(cudastatus, "Failed to allocate seed buffer");
00033         unsigned long *temp = new unsigned long[gridSize*3];
00034         for(int i=0;i<gridSize;i++){
00035             temp[i*3] = MEarr[i].x;
00036             temp[i*3+1] = MEarr[i].y;
00037             temp[i*3+2] = MEarr[i].z;
00038         }
00039         //for(int i=0;i<gridSize*3;i++) std::cout << temp[i] << "\n";
00040         cudaMemcpy(seedChunk, temp, gridSize*3*sizeof(unsigned long), cudaMemcpyHostToDevice);
00041         CudaCheckNotifyErr(cudastatus, "Failed to memcpy seed buffer.");
00042
00043         delete[] temp;
00044         return seedChunk;
00045     }
00046 };
00047
00048 /** @brief Marsaglia Random Generation function operable in __device__ space
00049 * @param x marsaglia internal x. Not constant, (ref)
00050 * @param y marsaglia internal y. Not constant, (ref)
00051 * @param z marsaglia internal z. Not constant, (ref)
00052 * @returns returns z
00053 */
00054 __device__ unsigned long devrandom(unsigned long &x, unsigned long &y, unsigned long &z){
00055     unsigned long t;
00056     x ^= x << 16;
00057     x ^= x >> 5;
00058     x ^= x << 1;
00059
00060     t = x;
00061     x = y;
00062     y = z;
00063     z = t ^ x ^ y;
00064
00065     return z;
00066 }
00067 };
```

10.23 dllmain.cpp File Reference

DLLMain for dynamic windows library.

```
#include "pch.h"
#include "model.h"
#include <iostream>
Include dependency graph for dllmain.cpp:
```



10.23.1 Detailed Description

DLLMain for dynamic windows library.

Authors

Ata Hakçıl

class for the final [Markov](#) Model, constructed from nodes and edges. Each atomic piece of the generation result is stored in a node, while edges contain the relation weights. *Extending:* To extend the class, implement the template and inherit from it, as "class MyModel : public Markov::Model<char>". For a complete demonstration of how to extend the class, see [MarkovPasswords](#).

Whole model can be defined as a list of the edges, as dangling nodes are pointless. This approach is used for the import/export operations. For more information on importing/exporting model, check out the [github](#) [readme](#) and [wiki](#) page.

Definition in file [dllmain.cpp](#).

10.24 dllmain.cpp


```

00001 /**
00002 * @brief DLLMain for dynamic windows library
00003 * @authors Ata Hakçıl
00004 *
00005 * @copydoc Markov::Model
00006 */
00007
00008 #include "pch.h"
00009 #include "model.h"
00010 #include <iostream>
00011
00012
00013 #ifdef _WIN32
00014 __declspec(dllexport) void dll_loadtest() {
00015     std::cout << "External function called.\n";
00016     //cudaTestEntry();
00017 }
00018
00019 BOOL APIENTRY DllMain(HMODULE hModule, DWORD ul_reason_for_call, LPVOID lpReserved)
00020 {
00021     switch (ul_reason_for_call)
00022     {
00023         case DLL_PROCESS_ATTACH:
00024         case DLL_THREAD_ATTACH:
00025         case DLL_THREAD_DETACH:
00026             case DLL_PROCESS_DETACH:
00027                 break;
00028     }
00029     return TRUE;
00030 }
00031
00032 #endif
  
```


10.25 edge.h File Reference

Edge class template.

```
#include <cstdint>
#include <cstddef>
Include dependency graph for edge.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::Node< storageType >](#)
A node class that for the vertices of model. Connected with eachother using [Edge](#).
- class [Markov::Edge< NodeStorageType >](#)
Edge class used to link nodes in the model together.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

10.25.1 Detailed Description

Edge class template.

Authors

Ata Hakçıl, Osman Ömer Yıldıztugay

Edge class used to link nodes in the model together. Has LeftNode, RightNode, and EdgeWeight of the edge. Edges are *UNIDIRECTIONAL* in this model. They can only be traversed LeftNode to RightNode.

Definition in file [edge.h](#).

10.26 edge.h

```

00001 /** @file edge.h
00002 * @brief Edge class template
00003 * @authors Ata Hakçıl, Osman Ömer Yıldıztugay
00004 *
00005 * @copydoc Markov::Edge
00006 */
00007
00008 #pragma once
00009 #include <cstdint>
00010 #include <cstddef>
00011
00012 namespace Markov {
00013
00014     template <typename NodeStorageType>
00015     class Node;
00016
00017     /** @brief Edge class used to link nodes in the model together.
00018     *
00019     Has LeftNode, RightNode, and EdgeWeight of the edge.
00020     Edges are *UNIDIRECTIONAL* in this model. They can only be traversed LeftNode to RightNode.
00021     */
00022     template <typename NodeStorageType>
00023     class Edge {
00024         public:
00025
00026         /** @brief Default constructor.
00027         *
00028         Edge<NodeStorageType>();
00029
00030         /** @brief Constructor. Initialize edge with given RightNode and LeftNode
00031         * @param _left - Left node of this edge.
00032         * @param _right - Right node of this edge.
00033         *
00034         * @b Example @b Use: Construct edge
00035         * @code{.cpp}
00036         * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00037         * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00038         * Markov::Edge<unsigned char>* el = new Markov::Edge<unsigned char>(src, target1);
00039         * @endcode
00040         *
00041         */
00042         Edge<NodeStorageType>*> _left, Node<NodeStorageType>*> _right);
00043
00044         /** @brief Adjust the edge EdgeWeight with offset.
00045         * Adds the offset parameter to the edge EdgeWeight.
00046         * @param offset - NodeValue to be added to the EdgeWeight
00047         *
00048         * @b Example @b Use: Construct edge
00049         * @code{.cpp}
00050         * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00051         * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00052         * Markov::Edge<unsigned char>* el = new Markov::Edge<unsigned char>(src, target1);
00053         *
00054         * el->AdjustEdge(25);
00055         *
00056         * @endcode
00057         */
00058         void AdjustEdge(long int offset);
00059
00060         /** @brief Traverse this edge to RightNode.
00061         * @return Right node. If this is a terminator node, return NULL
00062         *
00063         *
00064         * @b Example @b Use: Traverse a node
00065         * @code{.cpp}
00066         * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00067         * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00068         * Markov::Edge<unsigned char>* el = new Markov::Edge<unsigned char>(src, target1);

```

```

00069      *
00070      * e1->AdjustEdge(25);
00071      * Markov::Edge<unsigned char>* e2 = e1->traverseNode();
00072      * @endcode
00073      *
00074      */
00075  inline Node<NodeStorageType>* TraverseNode();
00076
00077  /** @brief Set LeftNode of this edge.
00078  * @param node - Node to be linked with.
00079  */
00080 void SetLeftEdge (Node<NodeStorageType>* );
00081 /** @brief Set RightNode of this edge.
00082  * @param node - Node to be linked with.
00083  */
00084 void SetRightEdge(Node<NodeStorageType>* );
00085
00086 /** @brief return edge's EdgeWeight.
00087  * @return edge's EdgeWeight.
00088  */
00089 inline uint64_t EdgeWeight();
00090
00091 /** @brief return edge's LeftNode
00092  * @return edge's LeftNode.
00093  */
00094 Node<NodeStorageType>* LeftNode();
00095
00096 /** @brief return edge's RightNode
00097  * @return edge's RightNode.
00098  */
00099 inline Node<NodeStorageType>* RightNode();
00100
00101 private:
00102     /**
00103      * @brief source node
00104     */
00105 Node<NodeStorageType>* _left;
00106
00107     /**
00108      * @brief target node
00109     */
00110 Node<NodeStorageType>* _right;
00111
00112     /**
00113      * Edge Edge Weight
00114     */
00115 long int _weight;
00116 };
00117
00118 };
00119 };
00120
00121 //default constructor of edge
00122 template <typename NodeStorageType>
00123 Markov::Edge<NodeStorageType>::Edge() {
00124     this->_left = NULL;
00125     this->_right = NULL;
00126     this->_weight = 0;
00127 }
00128 //constructor of edge
00129 template <typename NodeStorageType>
00130 Markov::Edge<NodeStorageType>::Edge(Markov::Node<NodeStorageType>* _left,
00131                                         Markov::Node<NodeStorageType>* _right) {
00132     this->_left = _left;
00133     this->_right = _right;
00134     this->_weight = 0;
00135 }
00136 //to AdjustEdge the edges by the edge with its offset
00137 template <typename NodeStorageType>
00138 void Markov::Edge<NodeStorageType>::AdjustEdge(long int offset) {
00139     this->_weight += offset;
00140     this->LeftNode()->UpdateTotalVerticeWeight(offset);
00141 }
00142 //to TraverseNode the node
00143 template <typename NodeStorageType>
00144 inline Markov::Node<NodeStorageType>* Markov::Edge<NodeStorageType>::TraverseNode() {
00145     if (this->RightNode()->NodeValue() == 0xff) //terminator node
00146         return NULL;
00147     return _right;
00148 }
00149 //to set the LeftNode of the node
00150 template <typename NodeStorageType>
00151 void Markov::Edge<NodeStorageType>::SetLeftEdge(Markov::Node<NodeStorageType>* n) {
00152     this->_left = n;
00153 }
00154 //to set the RightNode of the node

```

```


00155 void Markov::Edge<NodeStorageType>::SetRightEdge(Markov::Node<NodeStorageType>* n) {
00156     this->_right = n;
00157 }
00158 //to get the EdgeWeight of the node
00159 template <typename NodeStorageType>
00160 inline uint64_t Markov::Edge<NodeStorageType>::EdgeWeight() {
00161     return this->_weight;
00162 }
00163 //to get the LeftNode of the node
00164 template <typename NodeStorageType>
00165 Markov::Node<NodeStorageType>* Markov::Edge<NodeStorageType>::LeftNode() {
00166     return this->_left;
00167 }
00168 //to get the RightNode of the node
00169 template <typename NodeStorageType>
00170 inline Markov::Node<NodeStorageType>* Markov::Edge<NodeStorageType>::RightNode() {
00171     return this->_right;
00172 }

```

10.27 framework.h File Reference

for windows dynamic library

This graph shows which files directly or indirectly include this file:



Macros

- #define WIN32_LEAN_AND_MEAN

10.27.1 Detailed Description

for windows dynamic library

Authors

Ata Hakçıl

Definition in file [framework.h](#).

10.27.2 Macro Definition Documentation

10.27.2.1 WIN32_LEAN_AND_MEAN

```
#define WIN32_LEAN_AND_MEAN
Definition at line 9 of file framework.h.
```

10.28 framework.h


```
00001 /** @file framework.h
00002 * @brief for windows dynamic library
00003 * @authors Ata Hakçıl
00004 *
00005 */
00006
00007 #pragma once
00008
00009 #define WIN32_LEAN_AND_MEAN // Exclude rarely-used stuff from Windows headers
00010 // Windows Header Files
00011
00012 #ifdef _WIN32
00013 #include <windows.h>
00014 #endif
```

10.29 Generate.cpp File Reference

Generation Page.

```
#include "Generate.h"
#include <fstream>
#include <QFileDialog>
#include <QMMessageBox>
#include <QTextStream>
#include <QDir>
#include "CLI.h"
#include "MarkovAPI/src/markovPasswords.h"
#include <QtWidgets/QApplication>
#include "MarkovPasswordsGUI.h"
```

Include dependency graph for Generate.cpp:



10.29.1 Detailed Description

Generation Page.

Authors

Yunus Emre Yılmaz

Definition in file [Generate.cpp](#).

10.30 Generate.cpp

```
00001 /** @file Generate.cpp
00002 * @brief Generation Page
00003 * @authors Yunus Emre Yılmaz
00004 *
00005 */
00006
```

```
00007 #include "Generate.h"
00008 #include <fstream>
00009 #include<QFileDialog>
00010 #include<QMessageBox>
00011 #include<QTextStream>
00012 #include<QDir>
00013 #include "CLI.h"
00014 #include "MarkovAPI/src/markovPasswords.h"
00015 #include <QtWidgets/QApplication>
00016 #include "MarkovPasswordsGUI.h"
00017 using namespace Markov::GUI;
00018
00019
00020 Generate::Generate(QWidget* parent)
00021     : QMainWindow(parent)
00022 {
00023     ui.setupUi(this);
00024
00025     QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {generation(); });
00026     QObject::connect(ui.pushButton_4, &QPushButton::clicked, this, [this] {home(); });
00027     QObject::connect(ui.pushButton_3, &QPushButton::clicked, this, [this] {train(); });
00028     QObject::connect(ui.pushButton_2, &QPushButton::clicked, this, [this] {vis(); });
00029
00030
00031     ui.pushButton->setVisible(false);
00032     ui.lineEdit->setVisible(false);
00033     ui.lineEdit_2->setVisible(false);
00034     ui.lineEdit_3->setVisible(false);
00035     ui.label_3->setVisible(false);
00036     ui.label_4->setVisible(false);
00037     ui.label_5->setVisible(false);
00038
00039 }
00040
00041 void Generate::generation() {
00042
00043
00044
00045
00046
00047     QString file_name = QFileDialog::getOpenFileName(this, "Open a File", QDir::homePath());
00048     QFile file(file_name);
00049
00050
00051
00052     int numberPass = ui.lineEdit->text().toInt();
00053     int minLen = ui.lineEdit_2->text().toInt();
00054     int maxLen = ui.lineEdit_3->text().toInt();
00055     char* cstr;
00056     std::string fname = file_name.toStdString();
00057     cstr = new char[fname.size() + 1];
00058     strcpy(cstr, fname.c_str());
00059
00060     ui.label_6->setText("GENERATING!");
00061
00062     Markov::API::MarkovPasswords mp;
00063     mp.Import("src\\CLI\\sample_models\\2gram-trained.mdl");
00064
00065     mp.Generate(numberPass, cstr, minLen, maxLen);
00066
00067     if (!file.open(QFile::ReadOnly | QFile::Text)) {
00068         QMessageBox::warning(this, "Error", "File Not Open!");
00069     }
00070     QTextStream in(&file);
00071     QString text = in.readAll();
00072     ui.plainTextEdit->setPlainText(text);
00073
00074     ui.label_6->setText("DONE!");
00075
00076
00077
00078     file.close();
00079 }
00080
00081
00082 void Generate::train() {
00083
00084     QString file_name = QFileDialog::getOpenFileName(this, "Open a File", QDir::homePath());
00085     QFile file(file_name);
00086
00087     if (!file.open(QFile::ReadOnly | QFile::Text)) {
00088         QMessageBox::warning(this, "Error", "File Not Open!");
00089     }
00090     QTextStream in(&file);
00091     QString text = in.readAll();
00092
00093     char* cstr;
```

```


00094     std::string fname = file_name.toStdString();
00095     cstr = new char[fname.size() + 1];
00096     strcpy(cstr, fname.c_str());
00097
00098
00099
00100    char a = ',';
00101    Markov::API::MarkovPasswords mp;
00102    mp.Import("models\\2gram.mdl");
00103    mp.Train(cstr, a, 10);
00104    mp.Export("models\\finished.mdl");
00105
00106
00107
00108    ui.pushButton->setVisible(true);
00109    ui.lineEdit->setVisible(true);
00110    ui.lineEdit_2->setVisible(true);
00111    ui.lineEdit_3->setVisible(true);
00112    ui.label_3->setVisible(true);
00113    ui.label_4->setVisible(true);
00114    ui.label_5->setVisible(true);
00115
00116    file.close();
00117
00118
00119 }
00120
00121 void Generate::home() {
00122     CLI* w = new CLI;
00123     w->show();
00124     this->close();
00125 }
00126 void Generate :: vis() {
00127     MarkovPasswordsGUI* w = new MarkovPasswordsGUI;
00128     w->show();
00129     this->close();
00130 }
```

10.31 Generate.h File Reference


Generation Page.

```
#include <QtWidgets/QMainWindow>
#include "ui_Generate.h"
```

Include dependency graph for Generate.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::GUI::Generate](#)

QT Generation page class.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains Model, Node and Edge classes.

- [Markov::GUI](#)

namespace for MarkovPasswords API GUI wrapper

10.31.1 Detailed Description

Generation Page.

Authors

Yunus Emre Yilmaz

Definition in file [Generate.h](#).

10.32 Generate.h

```

00001 /** @file Generate.h
00002  * @brief Generation Page
00003  * @authors Yunus Emre Yilmaz
00004  *
00005  */
00006
00007 #pragma once
00008 #include <QtWidgets/QMainWindow>
00009 #include "ui_Generate.h"
0010
0011
0012 namespace Markov::GUI{
0013     /** @brief QT Generation page class
0014     */
0015     class Generate :public QMainWindow {
0016         Q_OBJECT
0017     public:
0018         Generate(QWidget* parent = Q_NULLPTR);
0019
0020     private:
0021         Ui::Generate ui;
0022
0023     public slots:
0024         void home();
0025         void generation();
  
```

```

00026     void train();
00027     void vis();
00028 };
00029 };

```

10.33 main.cpp File Reference


Test cases for [Markov::API::ModelMatrix](#).

```

#include <iostream>
#include "color/term.h"
#include "argparse.h"
#include <string>
#include <cstring>
#include <sstream>
#include "MarkovAPI/src/markovPasswords.h"
#include "MarkovAPI/src/modelMatrix.h"
#include <chrono>

```

Include dependency graph for [MarkovAPICLI/src/main.cpp](#):



Functions

- int [main](#) (int argc, char **argv)
- Launch CLI tool.*

10.33.1 Detailed Description

Test cases for [Markov::API::ModelMatrix](#).

Authors

Ata Hakçıl, Celal Sahir Çetiner

Parse command line arguments.

Class to flatten and reduce [Markov::Model](#) to a Matrix. Matrix level operations can be used for Generation events, with a significant performance optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)

To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for allocation. Threads are synchronized and files are flushed every 50M operations.

[Markov::Model](#) with char represented nodes. Includes wrappers for [Markov::Model](#) and additional helper functions to handle file I/O

This class is an extension of [Markov::Model<char>](#), with higher level abstractions such as train and generate.

Definition in file [MarkovAPICLI/src/main.cpp](#).

10.33.2 Function Documentation

10.33.2.1 main()

```

int main (
    int argc,
    char ** argv )

```

Launch CLI tool.

Definition at line 23 of file [MarkovAPICLI/src/main.cpp](#).


```

00023     {
00024
00025     Markov::API::CLI::Terminal t;
00026     /*
00027     ProgramOptions* p = Argparse::parse(argc, argv);
00028
00029     if (p==0 || p->bFailure) {
00030         std::cout << TERM_FAIL << "Arguments Failed to Parse" << std::endl;
00031         Argparse::help();
00032     }*/
00033     Markov::API::Argparse a(argc,argv);
00034
00035     Markov::API::ModelMatrix markovPass;
00036     std::cerr << "Importing model.\n";
00037     markovPass.Import("models/finished.mdl");
00038     std::cerr << "Import done. \n";
00039
00040     markovPass.Buff("!\\"#$%&'()*)+,-./;=>?@[\\"]^_`{|}~", 100);
00041
00042     markovPass.Export("models/buffed-symbols-100fold.mdl");
00043     //markovPass.ConstructMatrix();
00044     //std::chrono::steady_clock::time_point begin = std::chrono::steady_clock::now();
00045     //markovPass.FastRandomWalk(50000000, "/media/ignis/Stuff/wordlist.txt", 6, 12, 25, true);
00046     //markovPass.FastRandomWalk(500000000, "/media/ignis/Stuff/wordlist2.txt", 6, 12, 25, true);
00047     //std::chrono::steady_clock::time_point end = std::chrono::steady_clock::now();
00048
00049     //std::cerr << "Finished in:" << std::chrono::duration_cast<std::chrono::milliseconds> (end -
00050     begin).count() << " milliseconds" << std::endl;
00051     return 0;
00051 }

```

References [Markov::API::CLI::Argparse::Argparse\(\)](#), [Markov::API::MarkovPasswords::Buff\(\)](#), [Markov::Model< NodeStorageType >::Buff\(\)](#) and [Markov::API::ModelMatrix::Import\(\)](#).

Here is the call graph for this function:



10.34 MarkovAPICLI/src/main.cpp

```

00001 /** @file main.cpp
00002 * @brief Test cases for Markov::API::ModelMatrix
00003 * @authors Ata Hakçıl, Celal Sahir Çetiner
00004 *
00005 * @copydoc Markov::API::CLI::Argparse
00006 * @copydoc Markov::API::ModelMatrix
00007 * @copydoc Markov::API::MarkovPasswords
00008 */
00009
00010 #pragma once
00011 #include <iostream>

```

```


00012 #include "color/term.h"
00013 #include "argparse.h"
00014 #include <string>
00015 #include <cstring>
00016 #include <sstream>
00017 #include "MarkovAPI/src/markovPasswords.h"
00018 #include "MarkovAPI/src/modelMatrix.h"
00019 #include <chrono>
00020
00021 /** @brief Launch CLI tool.
00022 */
00023 int main(int argc, char** argv) {
00024     Markov::API::CLI::Terminal t;
00025     /*
00026     ProgramOptions* p = Argparse::parse(argc, argv);
00027
00028     if (p==0 || p->bFailure) {
00029         std::cout << TERM_FAIL << "Arguments Failed to Parse" << std::endl;
00030         Argparse::help();
00031     }
00032 */
00033     Markov::API::Argparse a(argc,argv);
00034
00035     Markov::API::ModelMatrix markovPass;
00036     std::cerr << "Importing model.\n";
00037     markovPass.Import("models/finished.mdl");
00038     std::cerr << "Import done. \n";
00039
00040     markovPass.Buff("!\\"#$%&' ()*+, -./:;<=>?@[\\"\\]^_`{|}~, 100");
00041
00042     markovPass.Export("models/buffed-symbols-100fold.mdl");
00043     //markovPass.ConstructMatrix();
00044     //std::chrono::steady_clock::time_point begin = std::chrono::steady_clock::now();
00045     //markovPass.FastRandomWalk(50000000, "/media/ignis/Stuff/wordlist.txt", 6, 12, 25, true);
00046     //markovPass.FastRandomWalk(50000000, "/media/ignis/Stuff/wordlist2.txt", 6, 12, 25, true);
00047     //std::chrono::steady_clock::time_point end = std::chrono::steady_clock::now();
00048
00049     //std::cerr << "Finished in:" << std::chrono::duration_cast<std::chrono::milliseconds> (end -
00050     begin).count() << " milliseconds" << std::endl;
00051     return 0;
00051 }
```

10.35 main.cpp File Reference

Entry point for GUI.

```
#include "menu.h"
#include <QtWidgets/QApplication>
#include <QSplashScreen>
#include <QDateTime>
#include "CLI.h"
```

Include dependency graph for MarkovPasswordsGUI/src/main.cpp:



Functions

- int `main (int argc, char *argv[])`

Launch UI.

10.35.1 Detailed Description

Entry point for GUI.

Authors

Yunus Emre Yılmaz

Definition in file [MarkovPasswordsGUI/src/main.cpp](#).

10.35.2 Function Documentation

10.35.2.1 main()

```
int main (
    int argc,
    char * argv[] )
```

Launch UI.

Definition at line 18 of file [MarkovPasswordsGUI/src/main.cpp](#).

```
00019 {
00020
00021
00022
00023     QApplication a(argc, argv);
00024
00025     QPixmap loadingPix("views/startup.jpg");
00026     QSplashScreen splash(loadingPix);
00027     splash.show();
00028     QDateTime time = QDateTime::currentDateTime();
00029     QDateTime currentTime = QDateTime::currentDateTime();           //Record current time
00030     while (time.secsTo(currentTime) <= 5)                         //5 is the number of seconds to delay
00031     {
00032         currentTime = QDateTime::currentDateTime();
00033         a.processEvents();
00034     };
00035
00036
00037     CLI w;
00038     w.show();
00039     splash.finish(&w);
00040     return a.exec();
00041 }
```

10.36 MarkovPasswordsGUI/src/main.cpp

```
00001 /** @file main.cpp
00002 * @brief Entry point for GUI
00003 * @authors Yunus Emre Yılmaz
00004 *
00005 */
00006
00007 //##include "MarkovPasswordsGUI.h"
00008 #include "menu.h"
00009 #include <QtWidgets/QApplication>
00010 #include <QSplashScreen>
00011 #include <QDateTime>
00012 #include "CLI.h"
00013
00014 using namespace Markov::GUI;
00015
00016 /** @brief Launch UI.
00017 */
00018 int main(int argc, char *argv[])
00019 {
00020
00021
00022
00023     QApplication a(argc, argv);
00024
00025     QPixmap loadingPix("views/startup.jpg");
00026     QSplashScreen splash(loadingPix);
00027     splash.show();
00028     QDateTime time = QDateTime::currentDateTime();
00029     QDateTime currentTime = QDateTime::currentDateTime();           //Record current time
00030     while (time.secsTo(currentTime) <= 5)                         //5 is the number of seconds to delay
```

```

00031     {
00032         currentTime = QDateTime::currentDateTime();
00033         a.processEvents();
00034     };
00035
00036
00037     CLI w;
00038     w.show();
00039     splash.finish(&w);
00040     return a.exec();
00041 }

```

10.37 main.cu File Reference


Simple test file to check libcudamarkov.

```

#include <iostream>
#include <string>
#include <cstring>
#include <sstream>
#include <chrono>
#include "cudaModelMatrix.h"
#include <cuda_runtime_api.h>
#include <cuda.h>
#include <device_launch_parameters.h>

```

Include dependency graph for main.cu:



Functions

- int [main](#) (int argc, char **argv)

10.37.1 Detailed Description

Simple test file to check libcudamarkov.

Authors

Ata Hakçıl

Controller class for CUDA device. This implementation only supports Nvidia devices.
Definition in file [main.cu](#).

10.37.2 Function Documentation

10.37.2.1 main()

```

int main (
    int argc,
    char ** argv )

```

Definition at line 21 of file [main.cu](#).

```

00022
00023
00024
00025     Markov::API::CUDA::CUDAModelMatrix markovPass;
00026     std::cerr << "Importing model.\n";
00027     markovPass.Import("models/finished.mdl");
00028     markovPass.Buff("!\\"#$%&'()*+,-./:;=>?@[\\\]^_`{|}~, 10, true, true);
00029     std::cerr << "Import done. \n";
00030     markovPass.ConstructMatrix();
00031     //markovPass.DumpJSON();
00032     CUDADeviceController::ListCudaDevices();
00033
00034     std::chrono::steady_clock::time_point begin = std::chrono::steady_clock::now();
00035     std::cerr << "Starting walk. \n";
00036     markovPass.FastRandomWalk(1000000000, "/media/ignis/Stuff/wordlist.txt", 12, 12, false, false);
00037     //markovPass.FastRandomWalk(500000000, "/media/ignis/Stuff/wordlist2.txt", 6, 12, 25, true);
00038     std::chrono::steady_clock::time_point end = std::chrono::steady_clock::now();
00039
00040     std::cerr << "Finished in:" << std::chrono::duration_cast<std::chrono::milliseconds> (end -
00041     begin).count() << " milliseconds" << std::endl;
00042
00043 }
```

10.38 main.cu

```


00001 /** @file main.cu
00002 * @brief Simple test file to check libcudamarkov
00003 * @authors Ata Hakçıl
00004 *
00005 * @copydoc Markov::API::CUDA::CUDAModelMatrix
00006 * @copydoc Markov::API::CUDA::CUDADeviceController
00007 */
00008
00009 #include <iostream>
00010 #include <string>
00011 #include <cstring>
00012 #include <sstream>
00013 #include <chrono>
00014 #include "cudaModelMatrix.h"
00015 #include <cuda_runtime_api.h>
00016 #include <cuda.h>
00017 #include <device_launch_parameters.h>
00018
00019 using Markov::API::CUDA::CUDADeviceController;
00020
00021 int main(int argc, char** argv) {
00022
00023
00024
00025     Markov::API::CUDA::CUDAModelMatrix markovPass;
00026     std::cerr << "Importing model.\n";
00027     markovPass.Import("models/finished.mdl");
00028     markovPass.Buff("!\\"#$%&'()*+,-./:;=>?@[\\\]^_`{|}~, 10, true, true);
00029     std::cerr << "Import done. \n";
00030     markovPass.ConstructMatrix();
00031     //markovPass.DumpJSON();
00032     CUDADeviceController::ListCudaDevices();
00033
00034     std::chrono::steady_clock::time_point begin = std::chrono::steady_clock::now();
00035     std::cerr << "Starting walk. \n";
00036     markovPass.FastRandomWalk(1000000000, "/media/ignis/Stuff/wordlist.txt", 12, 12, false, false);
00037     //markovPass.FastRandomWalk(500000000, "/media/ignis/Stuff/wordlist2.txt", 6, 12, 25, true);
00038     std::chrono::steady_clock::time_point end = std::chrono::steady_clock::now();
00039
00040     std::cerr << "Finished in:" << std::chrono::duration_cast<std::chrono::milliseconds> (end -
00041     begin).count() << " milliseconds" << std::endl;
00042
00043 }
```

10.39 markopy.cpp File Reference

CPython wrapper for libmarkov utils.

```
#include <Python.h>
#include <boost/python.hpp>
#include <MarkovAPI/src/modelMatrix.h>
```

Include dependency graph for markopy.cpp:



Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::Markopy](#)

Macros

- `#define BOOST_ALL_STATIC_LIB 1`
- `#define BOOST_PYTHON_STATIC_LIB 1`

Functions

- [Markov::Markopy::BOOST_PYTHON_MODULE](#) (markopy)

10.39.1 Detailed Description

CPython wrapper for libmarkov utils.

Authors

Ata Hakçıl, Celal Sahir Çetiner

This file is a wrapper for libmarkov utilities, exposing:

- [MarkovPasswords](#)
 - Import
 - Export
 - Train
 - Generate
- [ModelMatrix](#)
 - Import
 - Export
 - Train
 - ConstructMatrix

- DumpJSON
- FastRandomWalk

`Markov::Model` with char represented nodes. Includes wrappers for `Markov::Model` and additional helper functions to handle file I/O

This class is an extension of `Markov::Model<char>`, with higher level abstractions such as train and generate. Class to flatten and reduce `Markov::Model` to a Matrix. Matrix level operations can be used for Generation events, with a significant performance optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)

To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for allocation. Threads are synchronized and files are flushed every 50M operations.

Definition in file [markopy.cpp](#).

10.39.2 Macro Definition Documentation

10.39.2.1 BOOST_ALL_STATIC_LIB

```
#define BOOST_ALL_STATIC_LIB 1
```

Definition at line [24](#) of file [markopy.cpp](#).

10.39.2.2 BOOST_PYTHON_STATIC_LIB

```
#define BOOST_PYTHON_STATIC_LIB 1
```

Definition at line [25](#) of file [markopy.cpp](#).

10.40 markopy.cpp

```
00001 /** @file markopy.cpp
00002 * @brief CPython wrapper for libmarkov utils.
00003 * @authors Ata Hakçıl, Celal Sahir Çetiner
00004 *
00005 * This file is a wrapper for libmarkov utilities, exposing:
00006 * - MarkovPasswords
00007 * - Import
00008 * - Export
00009 * - Train
00010 * - Generate
00011 * - ModelMatrix
00012 * - Import
00013 * - Export
00014 * - Train
00015 * - ConstructMatrix
00016 * - DumpJSON
00017 * - FastRandomWalk
00018 *
00019 * @copydoc Markov::API::MarkovPasswords
00020 * @copydoc Markov::API::ModelMatrix
00021 *
00022 */
00023
00024 #define BOOST_ALL_STATIC_LIB 1
00025 #define BOOST_PYTHON_STATIC_LIB 1
00026 #include <Python.h>
00027 #include <boost/python.hpp>
00028 #include <MarkovAPI/src/modelMatrix.h>
00029
00030
00031 using namespace boost::python;
00032
00033 namespace Markov::Markopy{
00034     BOOST_PYTHON_MODULE(markopy)
00035     {
00036         bool (Markov::API::MarkovPasswords::*Import)(const char*) = &Markov::Model<char>::Import;
00037         bool (Markov::API::MarkovPasswords::*Export)(const char*) = &Markov::Model<char>::Export;
00038         class_<Markov::API::MarkovPasswords>("MarkovPasswords", init<>())
00039             .def(init<>())
00040             .def("Train", &Markov::API::MarkovPasswords::Train)
00041             .def("Generate", &Markov::API::MarkovPasswords::Generate)
00042             .def("Import", Import, "Import a model file.")
00043     }
00044 }
```

```

00043     .def("Export", Export, "Export a model to file.")
00044     ;
00045
00046     int (Markov::API::ModelMatrix::*FastRandomWalk)(unsigned long int, const char*, int, int, int,
00047     bool) = &Markov::API::ModelMatrix::FastRandomWalk;
00048     class<Markov::API::ModelMatrix>("ModelMatrix", init<>())
00049
00050     .def(init<>())
00051     .def("Train", &Markov::API::ModelMatrix::Train)
00052     .def("Import", &Markov::API::ModelMatrix::Import, "Import a model file.")
00053     .def("Export", Export, "Export a model to file.")
00054     .def("ConstructMatrix", &Markov::API::ModelMatrix::ConstructMatrix)
00055     .def("DumpJSON", &Markov::API::ModelMatrix::DumpJSON)
00056     .def("FastRandomWalk", FastRandomWalk)
00057     ;
00058 };
00059 };

```

10.41 markopy.py File Reference

Namespaces

- [markopy](#)

Functions

- def [markopy.cli_init](#) (str input_model)
- def [markopy.cli_train](#) (markopy.ModelMatrix model, str dataset, str seperator, str output, bool output_← forced=False, bool bulk=False)
- def [markopy.cli_generate](#) (markopy.ModelMatrix model, str wordlist, bool bulk=False)

Variables

- [markopy.parser](#)
- [markopy.help](#)
- [markopy.default](#)
- [markopy.action](#)
- [markopy.args](#) = parser.parse_args()

10.42 markopy.py

```

00001 """ @package markopy
00002 @file markopy.py
00003 @namespace Python::Markopy
00004 @brief Command line
00005 @authors Ata Hakçıl
00006 """
00007
00008 import markopy
00009 import argparse
00010 import allegate as logging
00011 import re
00012 import os
00013
00014 parser = argparse.ArgumentParser(description="Python wrapper for MarkovPasswords.",
00015 epilog=f"""Sample runs:
00016 {__file__} train untrained.mdl -d dataset.dat -s "\t" -o trained.mdl
00017     Import untrained.mdl, train it with dataset.dat which has tab delimited data, output resulting
model to trained.mdl\n
00018
00019 {__file__} generate trained.mdl -n 500 -w output.txt
00020     Import trained.mdl, and generate 500 lines to output.txt
00021
00022 {__file__} combine untrained.mdl -d dataset.dat -s "\t" -n 500 -w output.txt
00023     Train and immediately generate 500 lines to output.txt. Do not export trained model.
00024
00025 {__file__} combine untrained.mdl -d dataset.dat -s "\t" -n 500 -w output.txt -o trained.mdl
00026     Train and immediately generate 500 lines to output.txt. Export trained model.
00027 """, formatter_class=argparse.RawTextHelpFormatter)
00028 parser.add_argument("mode", help="Operation mode, supported modes:
    \\"generate\\", \\"train\\" and \\"combine\\\"")

```

```

00029 parser.add_argument("input",
00030     help="Input model file. This model will be
00031     imported before starting operation.")
00032 parser.add_argument("--o", "--output",
00033     help="Output model file. This model will be
00034     exported when done. Will be ignored for generation mode.")
00035 parser.add_argument("-d", "--dataset",
00036     help="Dataset file to read input from for
00037     training. Will be ignored for generation mode.")
00038 parser.add_argument("-s", "--separator",
00039     help="Separator character to use with training
00040     data.(character between occurrence and value)")
00041 parser.add_argument("-w", "--wordlist",
00042     help="Wordlist file path to export generation
00043     results to. Will be ignored for training mode")
00044 parser.add_argument("--min", default=6,
00045     help="Minimum length that is allowed during
00046     generation")
00047 parser.add_argument("--max", default=12,
00048     help="Maximum length that is allowed during
00049     generation")
00050 parser.add_argument("-n", "--count",
00051     help="Number of lines to generate. Ignored in
00052     training mode.")
00053 parser.add_argument("-t", "--threads", default=10,
00054     help="Number of lines to generate. Ignored in
00055     training mode.")
00056 parser.add_argument("-v", "--verbosity", action="count",
00057     help="Output verbosity.")
00058 parser.add_argument("-b", "--bulk", action="store_true",
00059     help="Bulk generate or bulk train every
00060     corpus/model in the folder.")
00061 args = parser.parse_args()
00062
00063
00064
00065
00066
00067
00068 def cli_init(input_model : str):
00069     """ Initialize the model for CLI interation
00070     @param input_model Model filename
00071     """
00072     logging.VERBOSITY = 0
00073     if args.verbosity:
00074         logging.VERBOSITY = args.verbosity
00075         logging pprint(f"Verbosity set to {args.verbosity}.", 2)
00076
00077     logging pprint("Initializing model.", 1)
00078     model = markopy.ModelMatrix()
00079     logging pprint("Model initialized.", 2)
00080
00081     logging pprint("Importing model file.", 1)
00082
00083     if(not os.path.isfile(input_model)):
00084         logging pprint(f"Model file at {input_model} not found. Check the file path, or working
00085         directory")
00086         exit(1)
00087
00088     model.Import(input_model)
00089     logging pprint("Model imported successfully.", 2)
00090
00091     return model
00092
00093
00094
00095
00096
00097
00098
00099
00100
00101
00102
00103
00104
00105
00106
00107
00108
00109
00110
00111
00112
00113
00114
00115
00116
00117
00118
00119
00120
00121
00122
00123
00124
00125
00126
00127
00128
00129
00130
00131
00132
00133
00134
00135
00136
00137
00138
00139
00140
00141
00142
00143
00144
00145
00146
00147
00148
00149
00150
00151
00152
00153
00154
00155
00156
00157
00158
00159
00160
00161
00162
00163
00164
00165
00166
00167
00168
00169
00170
00171
00172
00173
00174
00175
00176
00177
00178
00179
00180
00181
00182
00183
00184
00185
00186
00187
00188
00189
00190
00191
00192
00193
00194
00195
00196
00197
00198
00199
00200
00201
00202
00203
00204
00205
00206
00207
00208
00209
00210
00211
00212
00213
00214
00215
00216
00217
00218
00219
00220
00221
00222
00223
00224
00225
00226
00227
00228
00229
00230
00231
00232
00233
00234
00235
00236
00237
00238
00239
00240
00241
00242
00243
00244
00245
00246
00247
00248
00249
00250
00251
00252
00253
00254
00255
00256
00257
00258
00259
00260
00261
00262
00263
00264
00265
00266
00267
00268
00269
00270
00271
00272
00273
00274
00275
00276
00277
00278
00279
00280
00281
00282
00283
00284
00285
00286
00287
00288
00289
00290
00291
00292
00293
00294
00295
00296
00297
00298
00299
00300
00301
00302
00303
00304
00305
00306
00307
00308
00309
00310
00311
00312
00313
00314
00315
00316
00317
00318
00319
00320
00321
00322
00323
00324
00325
00326
00327
00328
00329
00330
00331
00332
00333
00334
00335
00336
00337
00338
00339
00340
00341
00342
00343
00344
00345
00346
00347
00348
00349
00350
00351
00352
00353
00354
00355
00356
00357
00358
00359
00360
00361
00362
00363
00364
00365
00366
00367
00368
00369
00370
00371
00372
00373
00374
00375
00376
00377
00378
00379
00380
00381
00382
00383
00384
00385
00386
00387
00388
00389
00390
00391
00392
00393
00394
00395
00396
00397
00398
00399
00400
00401
00402
00403
00404
00405
00406
00407
00408
00409
00410
00411
00412
00413
00414
00415
00416
00417
00418
00419
00420
00421
00422
00423
00424
00425
00426
00427
00428
00429
00430
00431
00432
00433
00434
00435
00436
00437
00438
00439
00440
00441
00442
00443
00444
00445
00446
00447
00448
00449
00450
00451
00452
00453
00454
00455
00456
00457
00458
00459
00460
00461
00462
00463
00464
00465
00466
00467
00468
00469
00470
00471
00472
00473
00474
00475
00476
00477
00478
00479
00480
00481
00482
00483
00484
00485
00486
00487
00488
00489
00490
00491
00492
00493
00494
00495
00496
00497
00498
00499
00500
00501
00502
00503
00504
00505
00506
00507
00508
00509
00510
00511
00512
00513
00514
00515
00516
00517
00518
00519
00520
00521
00522
00523
00524
00525
00526
00527
00528
00529
00530
00531
00532
00533
00534
00535
00536
00537
00538
00539
00540
00541
00542
00543
00544
00545
00546
00547
00548
00549
00550
00551
00552
00553
00554
00555
00556
00557
00558
00559
00560
00561
00562
00563
00564
00565
00566
00567
00568
00569
00570
00571
00572
00573
00574
00575
00576
00577
00578
00579
00580
00581
00582
00583
00584
00585
00586
00587
00588
00589
00590
00591
00592
00593
00594
00595
00596
00597
00598
00599
00600
00601
00602
00603
00604
00605
00606
00607
00608
00609
00610
00611
00612
00613
00614
00615
00616
00617
00618
00619
00620
00621
00622
00623
00624
00625
00626
00627
00628
00629
00630
00631
00632
00633
00634
00635
00636
00637
00638
00639
00640
00641
00642
00643
00644
00645
00646
00647
00648
00649
00650
00651
00652
00653
00654
00655
00656
00657
00658
00659
00660
00661
00662
00663
00664
00665
00666
00667
00668
00669
00670
00671
00672
00673
00674
00675
00676
00677
00678
00679
00680
00681
00682
00683
00684
00685
00686
00687
00688
00689
00690
00691
00692
00693
00694
00695
00696
00697
00698
00699
00700
00701
00702
00703
00704
00705
00706
00707
00708
00709
00710
00711
00712
00713
00714
00715
00716
00717
00718
00719
00720
00721
00722
00723
00724
00725
00726
00727
00728
00729
00730
00731
00732
00733
00734
00735
00736
00737
00738
00739
00740
00741
00742
00743
00744
00745
00746
00747
00748
00749
00750
00751
00752
00753
00754
00755
00756
00757
00758
00759
00760
00761
00762
00763
00764
00765
00766
00767
00768
00769
00770
00771
00772
00773
00774
00775
00776
00777
00778
00779
00780
00781
00782
00783
00784
00785
00786
00787
00788
00789
00790
00791
00792
00793
00794
00795
00796
00797
00798
00799
00800
00801
00802
00803
00804
00805
00806
00807
00808
00809
00810
00811
00812
00813
00814
00815
00816
00817
00818
00819
00820
00821
00822
00823
00824
00825
00826
00827
00828
00829
00830
00831
00832
00833
00834
00835
00836
00837
00838
00839
00840
00841
00842
00843
00844
00845
00846
00847
00848
00849
00850
00851
00852
00853
00854
00855
00856
00857
00858
00859
00860
00861
00862
00863
00864
00865
00866
00867
00868
00869
00870
00871
00872
00873
00874
00875
00876
00877
00878
00879
00880
00881
00882
00883
00884
00885
00886
00887
00888
00889
00890
00891
00892
00893
00894
00895
00896
00897
00898
00899
00900
00901
00902
00903
00904
00905
00906
00907
00908
00909
00910
00911
00912
00913
00914
00915
00916
00917
00918
00919
00920
00921
00922
00923
00924
00925
00926
00927
00928
00929
00930
00931
00932
00933
00934
00935
00936
00937
00938
00939
00940
00941
00942
00943
00944
00945
00946
00947
00948
00949
00950
00951
00952
00953
00954
00955
00956
00957
00958
00959
00960
00961
00962
00963
00964
00965
00966
00967
00968
00969
00970
00971
00972
00973
00974
00975
00976
00977
00978
00979
00980
00981
00982
00983
00984
00985
00986
00987
00988
00989
00990
00991
00992
00993
00994
00995
00996
00997
00998
00999
00999
01000
01001
01002
01003
01004
01005
01006
01007
01008
01009
010010
010011
010012
010013
010014
010015
010016
010017
010018
010019
010020
010021
010022
010023
010024
010025
010026
010027
010028
010029
010030
010031
010032
010033
010034
010035
010036
010037
010038
010039
010040
010041
010042
010043
010044
010045
010046
010047
010048
010049
010050
010051
010052
010053
010054
010055
010056
010057
010058
010059
010060
010061
010062
010063
010064
010065
010066
010067
010068
010069
010070
010071
010072
010073
010074
010075
010076
010077
010078
010079
010080
010081
010082
010083
010084
010085
010086
010087
010088
010089
010090
010091
010092
010093
010094
010095
010096
010097
010098
010099
0100100
0100101
0100102
0100103
0100104
0100105
0100106
0100107
0100108
0100109
0100110
0100111
0100112
0100113
0100114
0100115
0100116
0100117
0100118
0100119
0100120
0100121
0100122
0100123
0100124
0100125
0100126
0100127
0100128
0100129
0100130
0100131
0100132
0100133
0100134
0100135
0100136
0100137
0100138
0100139
0100140
0100141
0100142
0100143
0100144
0100145
0100146
0100147
0100148
0100149
0100150
0100151
0100152
0100153
0100154
0100155
0100156
0100157
0100158
0100159
0100160
0100161
0100162
0100163
0100164
0100165
0100166
0100167
0100168
0100169
0100170
0100171
0100172
0100173
0100174
0100175
0100176
0100177
0100178
0100179
0100180
0100181
0100182
0100183
0100184
0100185
0100186
0100187
0100188
0100189
0100190
0100191
0100192
0100193
0100194
0100195
0100196
0100197
0100198
0100199
0100200
0100201
0100202
0100203
0100204
0100205
0100206
0100207
0100208
0100209
0100210
0100211
0100212
0100213
0100214
0100215
0100216
0100217
0100218
0100219
0100220
0100221
0100222
0100223
0100224
0100225
0100226
0100227
0100228
0100229
0100230
0100231
0100232
0100233
0100234
0100235
0100236
0100237
0100238
0100239
0100240
0100241
0100242
0100243
0100244
0100245
0100246
0100247
0100248
0100249
0100250
0100251
0100252
0100253
0100254
0100255
0100256
0100257
0100258
0100259
0100260
0100261
0100262
0100263
0100264
0100265
0100266
0100267
0100268
0100269
0100270
0100271
0100272
0100273
0100274
0100275
0100276
0100277
0100278
0100279
0100280
0100281
0100282
0100283
0100284
0100285
0100286
0100287
0100288
0100289
0100290
0100291
0100292
0100293
0100294
0100295
0100296
0100297
0100298
0100299
0100300
0100301
0100302
0100303
0100304
0100305
0100306
0100307
0100308
0100309
0100310
0100311
0100312
0100313
0100314
0100315
0100316
0100317
0100318
0100319
0100320
0100321
0100322
0100323
0100324
0100325
0100326
0100327
0100328
0100329
0100330
0100331
0100332
0100333
0100334
0100335
0100336
0100337
0100338
0100339
0100340
0100341
0100342
0100343
0100344
0100345
0100346
0100347
0100348
0100349
0100350
0100351
0100352
0100353
0100354
0100355
0100356
0100357
0100358
0100359
0100360
0100361
0100362
0100363
0100364
0100365
0100366
0100367
0100368
0100369
0100370
0100371
0100372
0100373
0100374
0100375
0100376
0100377
0100378
0100379
0100380
0100381
0100382
0100383
0100384
0100385
0100386
0100387
0100388
0100389
0100390
0100391
0100392
0100393
0100394
0100395
0100396
0100397
0100398
0100399
0100400
0100401
0100402
0100403
0100404
0100405
0100406
0100407
0100408
0100409
0100410
0100411
0100412
0100413
0100414
0100415
0100416
0100417
0100418
0100419
0100420
0100421
0100422
0100423
0100424
0100425
0100426
0100427
0100428
0100429
0100430
0100431
0100432
0100433
0100434
0100435
0100436
0100437
0100438
0100439
0100440
0100441
0100442
0100443
0100444
0100445
0100446
0100447
0100448
0100449
0100450
0100451
0100452
0100453
0100454
0100455
0100456
0100457
0100458
0100459
0100460
0100461
0100462
0100463
0100464
0100465
0100466
0100467
0100468
0100469
0100470
0100471
0100472
0100473
0100474
0100475
0100476
0100477
0100478
0100479
0100480
0100481
0100482
0100483
0100484
0100485
0100486
0100487
0100488
0100489
0100490
0100491
0100492
0100493
0100494
0100495
0100496
0100497
0100498
0100499
0100500
0100501
0100502
0100503
0100504
0100505
0100506
0100507
0100508
0100509
0100510
0100511
0100512
0100513
0100514
0100515
0100516
0100517
0100518
0100519
0100520
0100521
0100522
0100523
0100524
0100525
0100526
0100527
0100528
0100529
0100530
0100531
0100532
0100533
0100534
0100535
0100536
0100537
0100538
0100539
0100540
0100541
0100542
0100543
0100544
0100545
0100546
0100547
0100548
0100549
0100550
0100551
0100552
0100553
0100554
0100555
0100556
0100557
0100558
0100559
0100560
0100561
0100562
0100563
0100564
0100565
0100566
0100567
0100568
0100569
0100570
0100571
0100572
0100573
0100574
0100575
0100576
0100577
0100578
0100579
0100580
0100581
0100582
0100583
0100584
0100585
0100586
0100587
0100588
0100589
0100590
0100591
0100592
0100593
0100594
0100595
0100596
0100597
0100598
0100599
0100600
0100601
0100602
0100603
0100604
0100605
0100606
0100607
0100608
0100609
0100610
0100611
0100612
0100613
0100614
0100615
01006
```

```

00103     else:
00104         logging pprint(f'Model will not be exported.', 1)
00105
00106 def cli_generate(model : markopy.ModelMatrix, wordlist : str, bulk : bool=False):
00107     """ Generate strings from the model
00108     @param model: model instance
00109     @param wordlist wordlist filename
00110     @param bulk marks bulk operation with directories
00111     """
00112     if not (wordlist or args.count):
00113         logging pprint("Generation mode requires -w/--wordlist and -n/--count parameters. Exiting.")
00114         exit(2)
00115
00116     if(bulk and os.path.isfile(wordlist)):
00117         logging pprint(f'{wordlist} exists and will be overwritten.", 1)
00118     model.Generate(int(args.count), wordlist, int(args.min), int(args.max), int(args.threads))
00119
00120
00121 if(args.bulk):
00122     logging pprint(f'Bulk mode operation chosen.', 4)
00123
00124     if (args.mode.lower() == "train"):
00125         if (os.path.isdir(args.output) and not os.path.isfile(args.output)) and
00126             (os.path.isdir(args.dataset) and not os.path.isfile(args.dataset)):
00127             corpus_list = os.listdir(args.dataset)
00128             for corpus in corpus_list:
00129                 model = cli_init(args.input)
00130                 logging pprint(f"Training {args.input} with {corpus}", 2)
00131                 output_file_name = corpus
00132                 model_extension = ""
00133                 if "." in args.input:
00134                     model_extension = args.input.split(".")[-1]
00135                 cli_train(model, f'{args.dataset}/{corpus}', args.separator,
00136                           f'{args.output}/{corpus}.{model_extension}', output_forced=True, bulk=True)
00137             else:
00138                 logging pprint("In bulk training, output and dataset should be a directory.")
00139                 exit(1)
00140
00141     elif (args.mode.lower() == "generate"):
00142         if (os.path.isdir(args.wordlist) and not os.path.isfile(args.wordlist)) and
00143             (os.path.isdir(args.input) and not os.path.isfile(args.input)):
00144             model_list = os.listdir(args.input)
00145             print(model_list)
00146             for input in model_list:
00147                 logging pprint(f"Generating from {args.input}/{input} to {args.wordlist}/{input}.txt",
00148                               2)
00149
00150             model = cli_init(f'{args.input}/{input}')
00151             model_base = input
00152             if "." in args.input:
00153                 model_base = input.split(".")[1]
00154             cli_generate(model, f'{args.wordlist}/{model_base}.txt', bulk=True)
00155         else:
00156             logging pprint("In bulk generation, input and wordlist should be directory.")
00157
00158     model = cli_init(args.input)
00159     if (args.mode.lower() == "generate"):
00160         cli_generate(model, args.wordlist)
00161
00162     elif (args.mode.lower() == "train"):
00163         cli_train(model, args.dataset, args.separator, args.output, output_forced=True)
00164
00165     elif(args.mode.lower() == "combine"):
00166         cli_train(model, args.dataset, args.separator, args.output)
00167         cli_generate(model, args.wordlist)
00168
00169     else:
00170         logging pprint("Invalid mode argument given.")
00171         logging pprint("Accepted modes: 'Generate', 'Train', 'Combine'")
00172         exit(5)


```

10.43 markovPasswords.cpp File Reference

Wrapper for [Markov::Model](#) to use with char represented models.

```
#include "markovPasswords.h"
#include <string.h>
#include <chrono>
#include <thread>
```

```
#include <vector>
#include <mutex>
#include <string>
#include <signal.h>
#include <unistd.h>
Include dependency graph for markovPasswords.cpp:
```



Functions

- void [intHandler](#) (int dummy)

Variables

- static volatile int [keepRunning](#) = 1

10.43.1 Detailed Description

Wrapper for [Markov::Model](#) to use with char represented models.

Authors

Ata Hakçıl, Osman Ömer Yıldıztugay

This file contains the implementation for [Markov::API::MarkovPasswords](#) class.

[Markov::Model](#) with char represented nodes. Includes wrappers for [Markov::Model](#) and additional helper functions to handle file I/O

This class is an extension of [Markov::Model<char>](#), with higher level abstractions such as train and generate.
Definition in file [markovPasswords.cpp](#).

10.43.2 Function Documentation


10.43.2.1 [intHandler\(\)](#)

```
void intHandler (
    int dummy )
Definition at line 26 of file markovPasswords.cpp.
00026     {
00027         std::cout << "You wanted this man by presing CTRL-C ! Ok bye." ;
00028         //Sleep(5000);
00029         keepRunning = 0;
00030         exit(0);
00031 }
```

References [keepRunning](#).

Referenced by [Markov::API::MarkovPasswords::Train\(\)](#).

Here is the caller graph for this function:



10.43.3 Variable Documentation

10.43.3.1 keepRunning

```
volatile int keepRunning = 1 [static]
Definition at line 24 of file markovPasswords.cpp.
Referenced by intHandler(), and Markov::API::MarkovPasswords::TrainThread().
```

10.44 markovPasswords.cpp

```

00001 /**
00002 * @file markovPasswords.cpp
00003 * @brief Wrapper for Markov::Model to use with char represented models.
00004 * @authors Ata Hakçıl, Osman Ömer Yıldıztugay
00005 * This file contains the implementation for Markov::API::MarkovPasswords class.
00006 *
00007 * @copydoc Markov::API::MarkovPasswords
00008 */
00009
00010 #include "markovPasswords.h"
00011 #include <string.h>
00012 #include <chrono>
00013 #include <thread>
00014 #include <vector>
00015 #include <mutex>
00016 #include <string>
00017 #include <signal.h>
00018 #ifdef _WIN32
00019 #include <Windows.h>
00020 #else
00021 #include <unistd.h>
00022 #endif
00023
00024 static volatile int keepRunning = 1;
00025
00026 void intHandler(int dummy) {
00027     std::cout << "You wanted this man by presing CTRL-C ! Ok bye." ;
00028     //Sleep(5000);
00029     keepRunning = 0;
00030     exit(0);
00031 }
00032
00033
00034 Markov::API::MarkovPasswords::MarkovPasswords() : Markov::Model<char>()
00035
00036
00037 }
00038
00039 Markov::API::MarkovPasswords::MarkovPasswords(const char* filename) {
00040
00041     std::ifstream* importFile;
00042
00043     this->Import(filename);
00044
00045     //std::ifstream* newFile(filename);
00046
00047     //importFile = newFile;
00048
00049 }
00050
  
```

```

00051 std::ifstream* Markov::API::MarkovPasswords::OpenDatasetFile(const char* filename) {
00052
00053     std::ifstream* datasetFile;
00054
00055     std::ifstream newFile(filename);
00056
00057     datasetFile = &newFile;
00058
00059     this->Import(datasetFile);
00060     return datasetFile;
00061 }
00062
00063
00064
00065 void Markov::API::MarkovPasswords::Train(const char* datasetFileName, char delimiter, int threads) {
00066     signal(SIGINT, intHandler);
00067     Markov::API::Concurrency::ThreadSharedListHandler listhandler(datasetFileName);
00068     auto start = std::chrono::high_resolution_clock::now();
00069
00070     std::vector<std::thread*> threadsV;
00071     for(int i=0;i<threads;i++) {
00072         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::TrainThread, this,
00073             &listhandler, delimiter));
00074     }
00075     for(int i=0;i<threads;i++) {
00076         threadsV[i]->join();
00077         delete threadsV[i];
00078     }
00079     auto finish = std::chrono::high_resolution_clock::now();
00080     std::chrono::duration<double> elapsed = finish - start;
00081     std::cout << "Elapsed time: " << elapsed.count() << " s\n";
00082
00083 }
00084
00085 void Markov::API::MarkovPasswords::TrainThread(Markov::API::Concurrency::ThreadSharedListHandler
00086     *listhandler, char delimiter) {
00087     char format_str[] = "%ld,%s";
00088     format_str[3]=delimiter;
00089     std::string line;
00090     while (listhandler->next(&line) && keepRunning) {
00091         long int oc;
00092         if (line.size() > 100) {
00093             line = line.substr(0, 100);
00094         }
00095         char* linebuf = new char[line.length()+5];
00096         sscanf_s(line.c_str(), "%ld,%s", &oc, linebuf, line.length()+5); //<== changed format_str to->
00097         "%ld,%s"
00098         sscanf(line.c_str(), format_str, &oc, linebuf);
00099     #endif
00100         this->AdjustEdge((const char*)linebuf, oc);
00101         delete linebuf;
00102     }
00103 }
00104
00105
00106 std::ofstream* Markov::API::MarkovPasswords::Save(const char* filename) {
00107     std::ofstream* exportFile;
00108
00109     std::ofstream newFile(filename);
00110
00111     exportFile = &newFile;
00112
00113     this->Export(exportFile);
00114     return exportFile;
00115 }
00116
00117
00118 void Markov::API::MarkovPasswords::Generate(unsigned long int n, const char* wordlistFileName, int
00119     minLen, int maxLen, int threads) {
00120     char* res;
00121     char print[100];
00122     std::ofstream wordlist;
00123     wordlist.open(wordlistFileName);
00124     std::mutex mlock;
00125     int iterationsPerThread = n/threads;
00126     int iterationsCarryOver = n%threads;
00127     std::vector<std::thread*> threadsV;
00128     for(int i=0;i<threads;i++) {
00129         threadsV.push_back(new std::thread(&Markov::API::MarkovPasswords::GenerateThread, this,
00130             &mlock, iterationsPerThread, &wordlist, minLen, maxLen));
00131     }
00132     for(int i=0;i<threads;i++) {
00133         threadsV[i]->join();
00134     }

```

```

00133     delete threadsV[i];
00134 }
00135
00136     this->GenerateThread(&mlock, iterationsCarryOver, &wordlist, minLen, maxLen);
00137
00138 }
00139
00140 void Markov::API::MarkovPasswords::GenerateThread(std::mutex *outputLock, unsigned long int n,
00141     std::ofstream *wordlist, int minLen, int maxLen) {
00142     char* res = new char[maxLen+5];
00143     if(n==0) return;
00144
00145     Markov::Random::Marsaglia MarsagliaRandomEngine;
00146     for (int i = 0; i < n; i++) {
00147         this->RandomWalk(&MarsagliaRandomEngine, minLen, maxLen, res);
00148         outputLock->lock();
00149         *wordlist << res << "\n";
00150         outputLock->unlock();
00151     }
00152 }
00153 void Markov::API::MarkovPasswords::Buff(const char* str, double multiplier, bool bDontAdjustSelfLoops,
00154     bool bDontAdjustExtendedLoops) {
00155     std::string buffstr(str);
00156     std::map< char, Node< char > * > *nodes;
00157     std::map< char, Edge< char > * > *edges;
00158     nodes = this->Nodes();
00159     int i=0;
00160     for (auto const& [repr, node] : *nodes) {
00161         edges = node->Edges();
00162         for (auto const& [targetrepr, edge] : *edges){
00163             if(buffstr.find(targetrepr)!= std::string::npos) {
00164                 if(bDontAdjustSelfLoops && repr==targetrepr) continue;
00165                 if(bDontAdjustExtendedLoops) {
00166                     if(buffstr.find(repr) != std::string::npos) {
00167                         continue;
00168                     }
00169                     long int weight = edge->EdgeWeight ();
00170                     weight = weight*multiplier;
00171                     edge->AdjustEdge (weight);
00172                 }
00173             }
00174         }
00175         i++;
00176     }
00177
00178     this->OptimizeEdgeOrder ();
00179 }

```


10.45 markovPasswords.h File Reference

Wrapper for [Markov::Model](#) to use with char represented models.


```
#include "threadSharedListHandler.h"
```

```
#include "MarkovModel/src/model.h"
```

Include dependency graph for markovPasswords.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::MarkovPasswords](#)
Markov::Model with char represented nodes.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains Model, Node and Edge classes.
- [Markov::API](#)
Namespace for the MarkovPasswords API.

10.45.1 Detailed Description

Wrapper for [Markov::Model](#) to use with char represented models.

Authors

Ata Hakçıl, Osman Ömer Yıldıztugay

This file contains the declarations for [Markov::API::MarkovPasswords](#) class.

[Markov::Model](#) with char represented nodes. Includes wrappers for [Markov::Model](#) and additional helper functions to handle file I/O

This class is an extension of [Markov::Model<char>](#), with higher level abstractions such as train and generate.
 Definition in file [markovPasswords.h](#).

10.46 markovPasswords.h

```

00001 /** @file markovPasswords.h
00002 * @brief Wrapper for Markov::Model to use with char represented models.
00003 * @authors Ata Hakçıl, Osman Ömer Yıldıztugay
00004 *
00005 * This file contains the declarations for Markov::API::MarkovPasswords class.
00006 *
00007 * @copydoc Markov::API::MarkovPasswords
00008 */
00009
00010 #pragma once
00011 #include "threadSharedListHandler.h"
00012 #include "MarkovModel/src/model.h"
00013
00014
00015 /** @brief Namespace for the MarkovPasswords API
00016 */
00017 namespace Markov::API{
00018
00019     /** @brief Markov::Model with char represented nodes.
00020     *
00021     * Includes wrappers for Markov::Model and additional helper functions to handle file I/O
  
```

```

00022      *
00023      * This class is an extension of Markov::Model<char>, with higher level abstractions such as train
00024      *
00025      */
00026  class MarkovPasswords : public Markov::Model<char>{
00027  public:
00028
00029      /** @brief Initialize the markov model from MarkovModel::Markov::Model.
00030      *
00031      * Parent constructor. Has no extra functionality.
00032      */
00033  MarkovPasswords();
00034
00035      /** @brief Initialize the markov model from MarkovModel::Markov::Model, with an import file.
00036      *
00037      * This function calls the Markov::Model::Import on the filename to construct the model.
00038      * Same thing as creating an empty model, and calling MarkovPasswords::Import on the
00039      * filename.
00040      * @param filename - Filename to import
00041      *
00042      *
00043      * @b Example @b Use: Construction via filename
00044      * @code{.cpp}
00045      * MarkovPasswords mp("test.mdl");
00046      * @endcode
00047      */
00048  MarkovPasswords(const char* filename);
00049
00050      /** @brief Open dataset file and return the ifstream pointer
00051      * @param filename - Filename to open
00052      * @return ifstream* to the dataset file
00053      */
00054  std::ifstream* OpenDatasetFile(const char* filename);
00055
00056
00057      /** @brief Train the model with the dataset file.
00058      * @param datasetFileName - Ifstream* to the dataset. If null, use class member
00059      * @param delimiter - a character, same as the delimiter in dataset content
00060      * @param threads - number of OS threads to spawn
00061      *
00062      * @code{.cpp}
00063      * Markov::API::MarkovPasswords mp;
00064      * mp.Import("models/2gram.mdl");
00065      * mp.Train("password.corpus");
00066      * @endcode
00067      */
00068  void Train(const char* datasetFileName, char delimiter, int threads);
00069
00070
00071
00072      /** @brief Export model to file.
00073      * @param filename - Export filename.
00074      * @return std::ofstream* of the exported file.
00075      */
00076  std::ofstream* Save(const char* filename);
00077
00078      /** @brief Call Markov::Model::RandomWalk n times, and collect output.
00079      *
00080      * Generate from model and write results to a file.
00081      * A much more performance-optimized method. FastRandomWalk will reduce the runtime by ~96.5
00082      * on average.
00083      *
00084      * @deprecated See Markov::API::MatrixModel::FastRandomWalk for more information.
00085      * @param n - Number of passwords to generate.
00086      * @param wordlistFileName - Filename to write to
00087      * @param minLen - Minimum password length to generate
00088      * @param maxLen - Maximum password length to generate
00089      * @param threads - number of OS threads to spawn
00090      *
00091      void Generate(unsigned long int n, const char* wordlistFileName, int minLen=6, int maxLen=12,
00092      int threads=20);
00093
00094      /** @brief Buff expression of some characters in the model
00095      * @param str A string containing all the characters to be buffed
00096      * @param multiplier A constant value to buff the nodes with.
00097      * @param bDontAdjustSelfEdges Do not adjust weights if target node is same as source node
00098      * @param bDontAdjustExtendedLoops Do not adjust if both source and target nodes are in first
00099      * parameter
00100      */
00101  void Buff(const char* str, double multiplier, bool bDontAdjustSelfLoops=true, bool
bDontAdjustExtendedLoops=false);
00102
00103  private:
00104

```

```

00103     /** @brief A single thread invoked by the Train function.
00104      * @param listhandler - Listhandler class to read corpus from
00105      * @param delimiter - a character, same as the delimiter in dataset content
00106      *
00107      */
00108     void TrainThread(Markov::API::Concurrency::ThreadSharedListHandler *listhandler, char
00109     delimiter);
00110
00111     /** @brief A single thread invoked by the Generate function.
00112      *
00113      * @b DEPRECATED: See Markov::API::MatrixModel::FastRandomWalkThread for more information.
00114      This has been replaced with
00115      * a much more performance-optimized method. FastRandomWalk will reduce the runtime by %96.5
00116      on average.
00117      *
00118      * @param outputLock - shared mutex lock to lock during output operation. Prevents race
00119      condition on write.
00120      *
00121      */
00122     void GenerateThread(std::mutex *outputLock, unsigned long int n, std::ofstream *wordlist, int
00123     minLen, int maxLen);
00124     std::ifstream* datasetFile; /* @brief Dataset file input of our system */
00125     std::ofstream* modelSavefile; /* @brief File to save model of our system */
00126     std::ofstream* outputFile; /* @brief Generated output file of our system */
00127
00128
00129
00130 };


```

10.47 MarkovPasswordsGUI.cpp File Reference

Main activity page for GUI.

```
#include "MarkovPasswordsGUI.h"
#include <fstream>
#include <qwebengineview.h>
#include "CLI.h"
```

Include dependency graph for MarkovPasswordsGUI.cpp:



10.47.1 Detailed Description

Main activity page for GUI.

Authors

Yunus Emre Yılmaz

Definition in file [MarkovPasswordsGUI.cpp](#).

10.48 MarkovPasswordsGUI.cpp

```
00001 /** @file MarkovPasswordsGUI.cpp
```

```


00002 * @brief Main activity page for GUI
00003 * @authors Yunus Emre Yilmaz
00004 *
00005 */
00006
00007 #include "MarkovPasswordsGUI.h"
00008 #include <fstream>
00009 #include <qwebengineview.h>
00010 #include "CLI.h"
00011
00012 using namespace Markov::GUI;
00013
00014 Markov::GUI::MarkovPasswordsGUI::MarkovPasswordsGUI(QWidget *parent) : QMainWindow(parent){
00015     ui.setupUi(this);
00016
00017
00018     QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {home(); });
00019     QObject::connect(ui.pushButton_2, &QPushButton::clicked, this, [this] {model(); });
00020     QObject::connect(ui.pushButton_3, &QPushButton::clicked, this, [this] {pass(); });
00021 }
00022
00023
00024 void MarkovPasswordsGUI::home() {
00025     CLI* w = new CLI;
00026     w->show();
00027     this->close();
00028 }
00029 void MarkovPasswordsGUI::pass() {
00030     QWebEngineView* webkit = ui.centralWidget->findChild<QWebEngineView*>("chartArea");
00031
00032     //get working directory
00033     char path[255];
00034     GetCurrentDirectoryA(255, path);
00035
00036     //get absolute path to the layout html
00037     std::string layout = "file:/// " + std::string(path) + "\\views\\bar.html";
00038     std::replace(layout.begin(), layout.end(), '\\', '/');
00039     webkit->setUrl(QUrl(layout.c_str()));
00040 }
00041
00042 void MarkovPasswordsGUI::model() {
00043     QWebEngineView* webkit = ui.centralWidget->findChild<QWebEngineView*>("chartArea");
00044
00045     //get working directory
00046     char path[255];
00047     GetCurrentDirectoryA(255, path);
00048
00049     //get absolute path to the layout html
00050     std::string layout = "file:/// " + std::string(path) + "\\views\\index.html";
00051     std::replace(layout.begin(), layout.end(), '\\', '/');
00052     webkit->setUrl(QUrl(layout.c_str()));
00053 }

```


10.49 MarkovPasswordsGUI.h File Reference

Main activity page for GUI.

```
#include <QtWidgets/QMainWindow>
#include "ui_MarkovPasswordsGUI.h"
Include dependency graph for MarkovPasswordsGUI.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::GUI::MarkovPasswordsGUI](#)
Reporting UI.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::GUI](#)
namespace for MarkovPasswords API GUI wrapper

10.49.1 Detailed Description

Main activity page for GUI.

Authors

Yunus Emre Yilmaz

Definition in file [MarkovPasswordsGUI.h](#).

10.50 MarkovPasswordsGUI.h

```

00001 /** @file MarkovPasswordsGUI.h
00002 * @brief Main activity page for GUI
00003 * @authors Yunus Emre Yilmaz
00004 *
00005 */
00006
00007 #pragma once
00008
00009 #include <QtWidgets/QMainWindow>
00010 #include "ui_MarkovPasswordsGUI.h"
00011
00012
00013
00014 namespace Markov::GUI{
00015     /** @brief Reporting UI.
00016     *
00017     * UI for reporting and debugging tools for MarkovPassword
00018     */
00019     class MarkovPasswordsGUI : public QMainWindow {
00020         Q_OBJECT
00021     public:
00022         MarkovPasswordsGUI(QWidget* parent = Q_NULLPTR);
00023
00024     private:
00025         Ui::MarkovPasswordsGUIClass ui;
00026
00027
00028         //Slots for buttons in GUI.
00029     public slots:
00030
  
```

```


00031     void benchmarkSelected();
00032     //void MarkovPasswordsGUI::modelvisSelected();
00033     //void MarkovPasswordsGUI::visualDebugSelected();
00034     //void MarkovPasswordsGUI::comparisonSelected();
00035
00036
00037 public slots:
00038
00039     void home();
00040     void pass();
00041     void model();
00042 };
00043 };

```

10.51 menu.cpp File Reference

menu page

```
#include "menu.h"
#include <fstream>
#include "MarkovPasswordsGUI.h"
#include <QtWidgets/QApplication>
Include dependency graph for menu.cpp:
```



10.51.1 Detailed Description

menu page

Authors

Yunus Emre Yılmaz

Definition in file [menu.cpp](#).

10.52 menu.cpp

```

00001 /**
00002 * @file menu.cpp
00003 * @brief menu page
00004 * @authors Yunus Emre Yılmaz
00005 */
00006
00007 #include "menu.h"
00008 #include <fstream>
00009 #include "MarkovPasswordsGUI.h"
00010 #include <QtWidgets/QApplication>
00011
00012 using namespace Markov::GUI;
00013
00014 menu::menu(QWidget* parent)
00015     : QMainWindow(parent)
00016 {
00017     ui.setupUi(this);
00018
00019
00020     //QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {about(); });
00021     QObject::connect(ui.visu, &QPushButton::clicked, this, [this] {visualization(); });
00022 }
00023 void menu::about() {


```

```


00024
00025
00026 }
00027 void menu::visualization() {
00028     MarkovPasswordsGUI* w = new MarkovPasswordsGUI;
00029     w->show();
00030     this->close();
00031 }
```

10.53 menu.h File Reference

menu page
`#include <QtWidgets/QMainWindow>`
`#include "ui_menu.h"`
Include dependency graph for menu.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `Markov::GUI::menu`
QT Menu class.

Namespaces

- `Markov`
Namespace for the markov-model related classes. Contains `Model`, `Node` and `Edge` classes.
- `Markov::GUI`
namespace for MarkovPasswords API GUI wrapper

10.53.1 Detailed Description

menu page

Authors

Yunus Emre Yılmaz

Definition in file [menu.h](#).

10.54 menu.h

```

00001 /** @file menu.h
00002 * @brief menu page
00003 * @authors Yunus Emre Yılmaz
00004 *
00005 */
00006
00007 #pragma once
00008 #include <QtWidgets/QMainWindow>
00009 #include "ui_menu.h"
00010
00011
00012 namespace Markov::GUI{
00013     /** @brief QT Menu class
00014     */
00015     class menu:public QMainWindow {
00016     Q_OBJECT
00017     public:
00018         menu(QWidget* parent = Q_NULLPTR);
00019
00020     private:
00021         Ui::main ui;
00022
00023     public slots:
00024         void about();
00025         void visualization();
00026     };
00027 };


```

10.55 model.h File Reference


Model class template.

```
#include <map>
#include <vector>
#include <fstream>
#include <assert.h>
#include <string>
#include <algorithm>
#include "node.h"
#include "edge.h"
```

Include dependency graph for model.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::Node< storageType >](#)
A node class that for the vertices of model. Connected with eachother using [Edge](#).
- class [Markov::Edge< NodeStorageType >](#)
Edge class used to link nodes in the model together.
- class [Markov::Model< NodeStorageType >](#)
class for the final [Markov Model](#), constructed from nodes and edges.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

10.55.1 Detailed Description

Model class template.

Authors

Ata Hakçıl, Osman Ömer Yıldıztugay

class for the final [Markov](#) Model, constructed from nodes and edges. Each atomic piece of the generation result is stored in a node, while edges contain the relation weights. *Extending:* To extend the class, implement the template and inherit from it, as "class MyModel : public Markov::Model<char>". For a complete demonstration of how to extend the class, see [MarkovPasswords](#).

Whole model can be defined as a list of the edges, as dangling nodes are pointless. This approach is used for the import/export operations. For more information on importing/exporting model, check out the [github](#) [readme](#) and [wiki](#) page.

Definition in file [model.h](#).

10.56 model.h

```

00001 /** @file model.h
00002 * @brief Model class template
00003 * @authors Ata Hakçıl, Osman Ömer Yıldıztugay
00004 *
00005 * @copydoc Markov::Model
00006 */
00007
00008
00009
00010 #pragma once
  
```

```

00011 #include <map>
00012 #include <vector>
00013 #include <fstream>
00014 #include <assert.h>
00015 #include <string>
00016 #include <algorithm>
00017 #include "node.h"
00018 #include "edge.h"
00019 /**
00020  * @brief Namespace for the markov-model related classes.
00021  * Contains Model, Node and Edge classes
00022 */
00023 namespace Markov {
00024
00025     template <typename NodeStorageType>
00026     class Node;
00027
00028     template <typename NodeStorageType>
00029     class Edge;
00030
00031     template <typename NodeStorageType>
00032
00033     /** @brief class for the final Markov Model, constructed from nodes and edges.
00034      *
00035      * Each atomic piece of the generation result is stored in a node, while edges contain the
00036      * relation weights.
00037      * *Extending:*
00038      * To extend the class, implement the template and inherit from it, as "class MyModel : public
00039      * Markov::Model<char>".
00040      * For a complete demonstration of how to extend the class, see MarkovPasswords.
00041      * Whole model can be defined as a list of the edges, as dangling nodes are pointless. This
00042      * approach is used for the import/export operations.
00043      * For more information on importing/exporting model, check out the github readme and wiki page.
00044      */
00045     class Model {
00046     public:
00047
00048     /** @brief Initialize a model with only start and end nodes.
00049      *
00050      * Initialize an empty model with only a starterNode
00051      * Starter node is a special kind of node that has constant 0x00 value, and will be used to
00052      * initiate the generation execution from.
00053     Model<NodeStorageType>();
00054
00055     /** @brief Do a random walk on this model.
00056      *
00057      * Start from the starter node, on each node, invoke RandomNext using the random engine on
00058      * current node, until terminator node is reached.
00059      * If terminator node is reached before minimum length criteria is reached, ignore the last
00060      * selection and re-invoke randomNext
00061      * If maximum length criteria is reached but final node is not, cut off the generation and
00062      * proceed to the final node.
00063      * This function takes Markov::Random::RandomEngine as a parameter to generate pseudo random
00064      * numbers from
00065      * This library is shipped with two random engines, Marsaglia and Mersenne. While mersenne
00066      * output is higher in entropy, most use cases
00067      * don't really need super high entropy output, so Markov::Random::Marsaglia is preferable for
00068      * better performance.
00069      *
00070      * This function WILL NOT reallocate buffer. Make sure no out of bound writes are happening
00071      * via maximum length criteria.
00072
00073     * @b Example @b Use: Generate 10 lines, with 5 to 10 characters, and print the output. Use
00074     * Marsaglia
00075     * @code{.cpp}
00076     * Markov::Model<char> model;
00077     * Model.import("model.mdl");
00078     * char* res = new char[11];
00079     * Markov::Random::Marsaglia MarsagliaRandomEngine;
00080     * for (int i = 0; i < 10; i++) {
00081     *     this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
00082     *     std::cout << res << "\n";
00083     * }
00084
00085     * @endcode
00086
00087     * @param randomEngine Random Engine to use for the random walks. For examples, see
00088     * Markov::Random::Mersenne and Markov::Random::Marsaglia
00089     * @param minSetting Minimum number of characters to generate
00090     * @param maxSetting Maximum number of character to generate
00091     * @param buffer buffer to write the result to
00092     * @return Null terminated string that was generated.

```

```

00085      */
00086      NodeStorageType* RandomWalk(Markov::Random::RandomEngine* randomEngine, int minSetting, int
00087      maxSetting, NodeStorageType* buffer);
00088
00089      /** @brief Adjust the model with a single string.
00090      *
00091      * Start from the starter node, and for each character, AdjustEdge the edge EdgeWeight from
00092      * current node to the next, until NULL character is reached.
00093      *
00094      * Then, update the edge EdgeWeight from current node, to the terminator node.
00095      *
00096      * This function is used for training purposes, as it can be used for adjusting the model with
00097      * each line of the corpus file.
00098      *
00099      * @b Example @b Use: Create an empty model and train it with string: "testdata"
00100      * @code{.cpp}
00101      * Markov::Model<char> model;
00102      * char test[] = "testdata";
00103      * model.AdjustEdge(test, 15);
00104      * @endcode
00105      *
00106      * @param string - String that is passed from the training, and will be used to AdjustEdge the
00107      * model with
00108      * @param occurrence - Occurrence of this string.
00109      */
00110      void AdjustEdge(const NodeStorageType* payload, long int occurrence);
00111
00112      /** @brief Import a file to construct the model.
00113      *
00114      * File contains a list of edges. For more info on the file format, check out the wiki and
00115      * github readme pages.
00116      * Format is: Left_repr;EdgeWeight;right_repr
00117      *
00118      * Iterate over this list, and construct nodes and edges accordingly.
00119      * @return True if successful, False for incomplete models or corrupt file formats
00120      *
00121      * @b Example @b Use: Import a file from ifstream
00122      * @code{.cpp}
00123      * Markov::Model<char> model;
00124      * std::ifstream file("test.mdl");
00125      * model.Import(&file);
00126      * @endcode
00127      */
00128      bool Import(std::ifstream* );
00129
00130      /** @brief Open a file to import with filename, and call bool Model::Import with std::ifstream
00131      * @return True if successful, False for incomplete models or corrupt file formats
00132      *
00133      * @b Example @b Use: Import a file with filename
00134      * @code{.cpp}
00135      * Markov::Model<char> model;
00136      * model.Import("test.mdl");
00137      * @endcode
00138      */
00139      bool Import(const char* filename);
00140
00141      /** @brief Export a file of the model.
00142      *
00143      * File contains a list of edges.
00144      * Format is: Left_repr;EdgeWeight;right_repr.
00145      * For more information on the format, check out the project wiki or github readme.
00146      *
00147      * Iterate over this vertices, and their edges, and write them to file.
00148      * @return True if successful, False for incomplete models.
00149      *
00150      * @b Example @b Use: Export file to ofstream
00151      * @code{.cpp}
00152      * Markov::Model<char> model;
00153      * std::ofstream file("test.mdl");
00154      * model.Export(&file);
00155      * @endcode
00156      */
00157      bool Export(std::ofstream* );
00158
00159      /** @brief Open a file to export with filename, and call bool Model::Export with std::ofstream
00160      * @return True if successful, False for incomplete models or corrupt file formats
00161      *
00162      * @b Example @b Use: Export file to filename
00163      * @code{.cpp}
00164      * Markov::Model<char> model;
00165      * model.Export("test.mdl");
00166      * @endcode
00167      */
00168      bool Export(const char* filename);

```

```

00167
00168     /** @brief Return starter Node
00169      * @return starter node with 00 NodeValue
00170      */
00171     Node<NodeStorageType>* StarterNode() { return starterNode; }
00172
00173     /** @brief Return a vector of all the edges in the model
00174      * @return vector of edges
00175      */
00176     std::vector<Edge<NodeStorageType>>* Edges () { return &edges; }
00177
00178     /** @brief Return starter Node
00179      * @return starter node with 00 NodeValue
00180      */
00181     std::map<NodeStorageType, Node<NodeStorageType>>* Nodes () { return &nodes; }
00182
00183     /** @brief Sort edges of all nodes in the model ordered by edge weights
00184      *
00185      */
00186     void OptimizeEdgeOrder();
00187
00188 private:
00189     /**
00190      * @brief Map LeftNode is the Nodes NodeValue
00191      * Map RightNode is the node pointer
00192      */
00193     std::map<NodeStorageType, Node<NodeStorageType>> nodes;
00194
00195     /**
00196      * @brief Starter Node of this model.
00197      */
00198     Node<NodeStorageType>* starterNode;
00199
00200     /**
00201      * @brief A list of all edges in this model.
00202      */
00203     std::vector<Edge<NodeStorageType>> edges;
00204 };
00205
00206
00207 };
00208
00209 template <typename NodeStorageType>
00210 Markov::Model<NodeStorageType>::Model() {
00211     this->starterNode = new Markov::Node<NodeStorageType>(0);
00212     this->nodes.insert({ 0, this->starterNode });
00213 }
00214
00215 template <typename NodeStorageType>
00216 bool Markov::Model<NodeStorageType>::Import(std::ifstream* f) {
00217     std::string cell;
00218
00219     char src;
00220     char target;
00221     long int oc;
00222
00223     while (std::getline(*f, cell)) {
00224         //std::cout << "cell: " << cell << std::endl;
00225         src = cell[0];
00226         target = cell[cell.length() - 1];
00227         char* j;
00228         oc = std::strtol(cell.substr(2, cell.length() - 2).c_str(),&j,10);
00229         //std::cout << oc << "\n";
00230         Markov::Node<NodeStorageType>* srcN;
00231         Markov::Node<NodeStorageType>* targetN;
00232         Markov::Edge<NodeStorageType>* e;
00233         if (this->nodes.find(src) == this->nodes.end()) {
00234             srcN = new Markov::Node<NodeStorageType>(src);
00235             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(src, srcN));
00236             //std::cout << "Creating new node at start.\n";
00237         }
00238         else {
00239             srcN = this->nodes.find(src)->second;
00240         }
00241
00242         if (this->nodes.find(target) == this->nodes.end()) {
00243             targetN = new Markov::Node<NodeStorageType>(target);
00244             this->nodes.insert(std::pair<char, Markov::Node<NodeStorageType>>(target, targetN));
00245             //std::cout << "Creating new node at end.\n";
00246         }
00247         else {
00248             targetN = this->nodes.find(target)->second;
00249         }
00250         e = srcN->Link(targetN);
00251         e->AdjustEdge(oc);
00252         this->edges.push_back(e);
00253

```

```

00254     //std::cout << int(srcN->NodeValue()) << " --" << e->EdgeWeight() << "--> " <
00255     int(targetN->NodeValue()) << "\n";
00256
00257 }
00258
00259     this->OptimizeEdgeOrder();
00260
00261     return true;
00262 }
00263
00264 template <typename NodeStorageType>
00265 void Markov::Model<NodeStorageType>::OptimizeEdgeOrder(){
00266     for (std::pair<unsigned char, Markov::Node<NodeStorageType>*> const& x : this->nodes) {
00267         //std::cout << "Total edges in EdgesV: " << x.second->edgesV.size() << "\n";
00268         std::sort (x.second->edgesV.begin(), x.second->edgesV.end(), [](Edge<NodeStorageType> *lhs,
00269             Edge<NodeStorageType> *rhs)->bool{
00270             return lhs->EdgeWeight() > rhs->EdgeWeight();
00271         });
00272         //for(int i=0;i<x.second->edgesV.size();i++)
00273         //    std::cout << x.second->edgesV[i]->EdgeWeight() << ", ";
00274         //std::cout << "\n";
00275     }
00276     //std::cout << "Total number of nodes: " << this->nodes.size() << std::endl;
00277     //std::cout << "Total number of edges: " << this->edges.size() << std::endl;
00278 }
00279
00280 template <typename NodeStorageType>
00281 bool Markov::Model<NodeStorageType>::Import(const char* filename) {
00282     std::ifstream importfile;
00283     importfile.open(filename);
00284     return this->Import(&importfile);
00285 }
00286
00287 template <typename NodeStorageType>
00288 bool Markov::Model<NodeStorageType>::Export(std::ofstream* f) {
00289     Markov::Edge<NodeStorageType>* e;
00290     for (std::vector<int>::size_type i = 0; i != this->edges.size(); i++) {
00291         e = this->edges[i];
00292         //std::cout << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," <
00293         //e->RightNode()->NodeValue() << "\n";
00294         *f << e->LeftNode()->NodeValue() << "," << e->EdgeWeight() << "," << e->RightNode()->NodeValue() <
00295         "\n";
00296     }
00297 }
00298
00299 template <typename NodeStorageType>
00300 bool Markov::Model<NodeStorageType>::Export(const char* filename) {
00301     std::ofstream exportfile;
00302     exportfile.open(filename);
00303     return this->Export(&exportfile);
00304 }
00305
00306 template <typename NodeStorageType>
00307 NodeStorageType* Markov::Model<NodeStorageType>::RandomWalk(Markov::Random::RandomEngine*
00308     randomEngine, int minSetting, int maxSetting, NodeStorageType* buffer) {
00309     Markov::Node<NodeStorageType>* n = this->starterNode;
00310     int len = 0;
00311     Markov::Node<NodeStorageType>* temp_node;
00312     while (true) {
00313         temp_node = n->RandomNext(randomEngine);
00314         if (len >= maxSetting) {
00315             break;
00316         } else if ((temp_node == NULL) && (len < minSetting)) {
00317             continue;
00318         }
00319         else if (temp_node == NULL) {
00320             break;
00321         }
00322         n = temp_node;
00323         buffer[len++] = n->NodeValue();
00324     }
00325
00326     //null terminate the string
00327     buffer[len] = 0x00;
00328
00329     //do something with the generated string
00330     return buffer; //for now
00331
00332 }
00333
00334 }
00335

```

```

00336 template <typename NodeStorageType>
00337 void Markov::Model<NodeStorageType>::AdjustEdge(const NodeStorageType* payload, long int occurrence) {
00338     NodeStorageType p = payload[0];
00339     Markov::Node<NodeStorageType>* curnode = this->starterNode;
00340     Markov::Edge<NodeStorageType>* e;
00341     int i = 0;
00342
00343     if (p == 0) return;
00344     while (p != 0) {
00345         e = curnode->FindEdge(p);
00346         if (e == NULL) return;
00347         e->AdjustEdge(occurrence);
00348         curnode = e->RightNode();
00349         p = payload[+i];
00350     }
00351
00352     e = curnode->FindEdge('\xff');
00353     e->AdjustEdge(occurrence);
00354     return;
00355 }
```

10.57 model_2gram.py File Reference

Namespaces

- [model_2gram](#)

Variables

- [model_2gram.alphabet](#) = string.printable
password alphabet
- [model_2gram.f](#) = open('../models/2gram.mdl', "wb")
output file handle

10.58 model_2gram.py

```


00001 #!/usr/bin/python3
00002 """
00003     python script for generating a 2gram model
00004 """
00005
00006 import string
00007 import re
00008
00009
00010 alphabet = string.printable
00011 alphabet = re.sub('\s', " ", alphabet)
00012 print(f"alphabet={alphabet}")
00013 #exit()
00014
00015
00016 f = open('../models/2gram.mdl', "wb")
00017 #tie start nodes
00018 for sym in alphabet:
00019     f.write(b"\x00,1," + bytes(sym, encoding='ascii') + b"\n")
00020
00021 #tie terminator nodes
00022 for sym in alphabet:
00023     f.write(bytes(sym, encoding='ascii')+ b",1,\xff\n")
00024
00025 #tie internals
00026 for src in alphabet:
00027     for target in alphabet:
00028         f.write(bytes(src, encoding='ascii') + b",1," + bytes(target, encoding='ascii') + b"\n")
```

10.59 modelMatrix.cpp File Reference

An extension of [Markov::API::MarkovPasswords](#).

```
#include "modelMatrix.h"
#include <map>
#include <cstring>
```

```
#include <thread>
Include dependency graph for modelMatrix.cpp:
```



10.59.1 Detailed Description

An extension of [Markov::API::MarkovPasswords](#).

Authors

Ata Hakçıl

This class shows superior performance compared to the traditional model at [Markov::API::MarkovPasswords](#). Class to flatten and reduce [Markov::Model](#) to a Matrix. Matrix level operations can be used for Generation events, with a significant performance optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)

To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for allocation. Threads are synchronized and files are flushed every 50M operations.

Definition in file [modelMatrix.cpp](#).

10.60 modelMatrix.cpp

```

00001 /**
00002 * @brief An extension of Markov::API::MarkovPasswords
00003 * @authors Ata Hakçıl
00004 *
00005 * This class shows superior performance compared to the traditional model at
00006 * Markov::API::MarkovPasswords
00007 * @copydoc Markov::API::ModelMatrix
00008 */
00009
00010 #include "modelMatrix.h"
00011 #include <map>
00012 #include <cstring>
00013 #include <thread>
00014
00015 Markov::API::ModelMatrix::ModelMatrix() {
00016     this->ready = false;
00017 }
00018
00019 void Markov::API::ModelMatrix::Import(const char *filename) {
00020     this->DeallocateMatrix();
00021     this->Markov::API::MarkovPasswords::Import(filename);
00022     this->ConstructMatrix();
00023 }
00024
00025 void Markov::API::ModelMatrix::Train(const char *datasetFileName, char delimiter, int threads){
00026     this->DeallocateMatrix();
00027     this->Markov::API::MarkovPasswords::Train(datasetFileName, delimiter, threads);
00028     this->ConstructMatrix();
00029 }
00030
00031 bool Markov::API::ModelMatrix::ConstructMatrix() {

```

```

00032     if(this->ready)  return false;
00033     this->matrixSize = this->StarterNode()->edgesV.size() + 2;
00034
00035     this->matrixIndex = new char[this->matrixSize];
00036     this->totalEdgeWeights = new long int[this->matrixSize];
00037
00038     this->edgeMatrix = new char*[this->matrixSize];
00039     for(int i=0;i<this->matrixSize;i++){
00040         this->edgeMatrix[i] = new char[this->matrixSize];
00041     }
00042     this->valueMatrix = new long int*[this->matrixSize];
00043     for(int i=0;i<this->matrixSize;i++){
00044         this->valueMatrix[i] = new long int[this->matrixSize];
00045     }
00046     std::map< char, Node< char > * > *nodes;
00047     nodes = this->Nodes();
00048     int i=0;
00049     for (auto const& [repr, node] : *nodes){
00050         if(repr!=0) this->matrixIndex[i] = repr;
00051         else this->matrixIndex[i] = 199;
00052         this->totalEdgeWeights[i] = node->TotalEdgeWeights();
00053         for(int j=0;j<this->matrixSize;j++){
00054             char val = node->NodeValue();
00055             if(val < 0){
00056                 for(int k=0;k<this->matrixSize;k++) {
00057                     this->valueMatrix[i][k] = 0;
00058                     this->edgeMatrix[i][k] = 255;
00059                 }
00060                 break;
00061             }
00062             else if(node->NodeValue() == 0 && j>(this->matrixSize-3)){
00063                 this->valueMatrix[i][j] = 0;
00064                 this->edgeMatrix[i][j] = 255;
00065             }else if(j==(this->matrixSize-1)) {
00066                 this->valueMatrix[i][j] = 0;
00067                 this->edgeMatrix[i][j] = 255;
00068             }else{
00069                 this->valueMatrix[i][j] = node->edgesV[j]->EdgeWeight();
00070                 this->edgeMatrix[i][j] = node->edgesV[j]->RightNode()->NodeValue();
00071             }
00072         }
00073     }
00074     i++;
00075 }
00076 this->ready = true;
00077 return true;
00078 //this->DumpJSON();
00079 }
00080
00081 bool Markov::API::ModelMatrix::DeallocateMatrix(){
00082     if(!this->ready) return false;
00083     delete[] this->matrixIndex;
00084     delete[] this->totalEdgeWeights;
00085
00086     for(int i=0;i<this->matrixSize;i++){
00087         delete[] this->edgeMatrix[i];
00088     }
00089     delete[] this->edgeMatrix;
00090
00091     for(int i=0;i<this->matrixSize;i++){
00092         delete[] this->valueMatrix[i];
00093     }
00094     delete[] this->valueMatrix;
00095
00096     this->matrixSize = -1;
00097     this->ready = false;
00098     return true;
00099 }
00100
00101 void Markov::API::ModelMatrix::DumpJSON(){
00102
00103     std::cout << "\n  \"index\":=\"";
00104     for(int i=0;i<this->matrixSize;i++){
00105         if(this->matrixIndex[i]=='') std::cout << "\\\"\\\"";
00106         else if(this->matrixIndex[i]=='\\') std::cout << "\\\\\\\\";
00107         else if(this->matrixIndex[i]==0) std::cout << "\\\\\\\\x00";
00108         else if(i==0) std::cout << "\\\\\\\\x0f";
00109         else if(this->matrixIndex[i]=='\n') std::cout << "\\n";
00110         else std::cout << this->matrixIndex[i];
00111     }
00112     std::cout <<
00113     "\",\n"
00114     "  \"edgemap\": {\n";
00115
00116     for(int i=0;i<this->matrixSize;i++){
00117         if(this->matrixIndex[i]=='') std::cout << "    \\\"\\\"\\\"": "[";
00118         else if(this->matrixIndex[i]=='\\') std::cout << "    \\\\\\\\\"": "[";

```

```

00119     else if(this->matrixIndex[i]==0) std::cout << "      \\\\\\x00\: [";
00120     else if(this->matrixIndex[i]<0) std::cout << "      \\\\\\xf": [";
00121     else std::cout << "      \" " << this->matrixIndex[i] << "\": [";
00122     for(int j=0;j<this->matrixSize;j++){
00123         if(this->edgeMatrix[i][j]=='') std::cout << "\\"\\\"\\\"\\";
00124         else if(this->edgeMatrix[i][j]=='\\') std::cout << "\\"\\\"\\\"\\";
00125         else if(this->edgeMatrix[i][j]==0) std::cout << "\\"\\\"\\\"\\x00\\";
00126         else if(this->edgeMatrix[i][j]<0) std::cout << "\\"\\\"\\\"\\xf\\";
00127         else if(this->matrixIndex[i]=='\\n') std::cout << "\\"\\\"\\n\\";
00128         else std::cout << "\\\" " << this->edgeMatrix[i][j] << "\\\"";
00129         if(j!=this->matrixSize-1) std::cout << ", ";
00130     }
00131     std::cout << "],\\n";
00132 }
00133 std::cout << "},\\n";
00134
00135 std::cout << "\\\" weightmap\\": {\n";
00136 for(int i=0;i<this->matrixSize;i++){
00137     if(this->matrixIndex[i]==''') std::cout << "      \\"\\\"\\\"\\": [";
00138     else if(this->matrixIndex[i]=='\\') std::cout << "      \\"\\\"\\\"\\": [";
00139     else if(this->matrixIndex[i]==0) std::cout << "      \\"\\\"\\\"\\x00\\": [";
00140     else if(this->matrixIndex[i]<0) std::cout << "      \\"\\\"\\\"\\xf\\": [";
00141     else std::cout << "      \" " << this->matrixIndex[i] << "\": [";
00142
00143     for(int j=0;j<this->matrixSize;j++){
00144         std::cout << this->valueMatrix[i][j];
00145         if(j!=this->matrixSize-1) std::cout << ", ";
00146     }
00147     std::cout << "],\\n";
00148 }
00149 std::cout << " }\\n}\\n";
00150 }
00151
00152
00153 void Markov::API::ModelMatrix::FastRandomWalkThread(std::mutex *mlock, std::ofstream *wordlist,
00154     unsigned long int n, int minLen, int maxLen, int id, bool bFileIO){
00155     if(n==0) return;
00156     Markov::Random::Marsaglia MarsagliaRandomEngine;
00157     char* e;
00158     char *res = new char[(maxLen+2)*n];
00159     int index = 0;
00160     char next;
00161     int len=0;
00162     long int selection;
00163     char cur;
00164     long int bufferctr = 0;
00165     for (int i = 0; i < n; i++) {
00166         cur=199;
00167         len=0;
00168         while (true) {
00169             e = strchr(this->matrixIndex, cur);
00170             index = e - this->matrixIndex;
00171             selection = MarsagliaRandomEngine.random() % this->totalEdgeWeights[index];
00172             for(int j=0;j<this->matrixSize;j++){
00173                 selection -= this->valueMatrix[index][j];
00174                 if (selection < 0){
00175                     next = this->edgeMatrix[index][j];
00176                     break;
00177                 }
00178             }
00179             if (len >= maxLen) break;
00180             else if ((next < 0) && (len < minLen)) continue;
00181             else if (next < 0) break;
00182             cur = next;
00183             res[bufferctr + len++] = cur;
00184         }
00185         res[bufferctr + len++] = '\\n';
00186         bufferctr+=len;
00187     }
00188 }
00189
00190 if(bFileIO){
00191     mlock->lock();
00192     *wordlist << res;
00193     mlock->unlock();
00194 }else{
00195     mlock->lock();
00196     std::cout << res;
00197     mlock->unlock();
00198 }
00199 delete res;
00200
00201 }
00202
00203
00204 int Markov::API::ModelMatrix::FastRandomWalk(unsigned long int n, std::ofstream *wordlist, int minLen,

```

```
00205
00206
00207     std::mutex mlock;
00208     if(n<=50000000ull) this->FastRandomWalkPartition(&mlock, wordlist, n, minLen, maxLen, bFileIO,
00209     threads);
00210     else{
00211         int numberOfPartitions = n/50000000ull;
00212         for(int i=0;i<numberOfPartitions;i++)
00213             this->FastRandomWalkPartition(&mlock, wordlist, 50000000ull, minLen, maxLen, bFileIO,
00214             threads);
00215     }
00216     return 0;
00217 }
00218
00219 int Markov::API::ModelMatrix::FastRandomWalk(unsigned long int n, const char* wordlistFileName, int
00220     minLen, int maxLen, int threads, bool bFileIO){
00221     std::ofstream wordlist;
00222     if(bFileIO)
00223         wordlist.open(wordlistFileName);
00224     this->FastRandomWalk(n, &wordlist, minLen, maxLen, threads, bFileIO);
00225     return 0;
00226 }
00227
00228 void Markov::API::ModelMatrix::FastRandomWalkPartition(std::mutex *mlock, std::ofstream *wordlist,
00229     unsigned long int n, int minLen, int maxLen, bool bFileIO, int threads){
00230     std::vector<std::thread*> threadsV;
00231
00232     int id = 0;
00233     for(int i=0;i<threads;i++){
00234         threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this,
00235             mlock, wordlist, iterationsPerThread, minLen, maxLen, id, bFileIO));
00236         id++;
00237     }
00238
00239     threadsV.push_back(new std::thread(&Markov::API::ModelMatrix::FastRandomWalkThread, this, mlock,
00240         wordlist, iterationsPerThreadCarryOver, minLen, maxLen, id, bFileIO));
00241     for(int i=0;i<threads;i++){
00242         threadsV[i]->join();
00243     }
00244 }
```


10.61 modelMatrix.h File Reference

An extension of [Markov::API::MarkovPasswords](#).


```
#include "markovPasswords.h"
```

```
#include <mutex>
```

Include dependency graph for modelMatrix.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::ModelMatrix](#)

Class to flatten and reduce [Markov::Model](#) to a Matrix.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::API](#)

Namespace for the [MarkovPasswords API](#).

10.61.1 Detailed Description

An extension of [Markov::API::MarkovPasswords](#).

Authors

Ata Hakçıl

This class shows superior performance compared to the traditional model at [Markov::API::MarkovPasswords](#). Class to flatten and reduce [Markov::Model](#) to a Matrix. Matrix level operations can be used for Generation events, with a significant performance optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)

To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for allocation. Threads are synchronized and files are flushed every 50M operations.

Definition in file [modelMatrix.h](#).

10.62 modelMatrix.h

```

00001 /**
00002 * @file modelMatrix.h
00003 * @brief An extension of Markov::API::MarkovPasswords
00004 * @authors Ata Hakçıl
00005 * This class shows superior performance compared to the traditional model at
00006 * Markov::API::MarkovPasswords
00007 * @copydoc Markov::API::ModelMatrix
00008 *
00009 */
00010
00011 #include "markovPasswords.h"
00012 #include <mutex>
00013
00014 namespace Markov::API{
00015
00016     /** @brief Class to flatten and reduce Markov::Model to a Matrix
00017     *
00018         * Matrix level operations can be used for Generation events, with a significant performance
00019         * optimization at the cost of O(N) memory complexity (O(1) memory space for slow mode)
  
```

```

00019      *
00020      * To limit the maximum memory usage, each generation operation is partitioned into 50M chunks for
00021      * allocation. Threads are synchronized and files are flushed every 50M operations.
00022      *
00023      */
00024  class ModelMatrix : public Markov::API::MarkovPasswords{
00025  public:
00026      ModelMatrix();
00027
00028      /** @brief Construct the related Matrix data for the model.
00029      *
00030      * This operation can be used after importing/training to allocate and populate the matrix
00031      * content.
00032      *
00033      * this will initialize:
00034      * char** edgeMatrix -> a 2D array of mapping left and right connections of each edge.
00035      * long int **valueMatrix -> a 2D array representing the edge weights.
00036      * int matrixSize -> Size of the matrix, aka total number of nodes.
00037      * char* matrixIndex -> order of nodes in the model
00038      * long int *totalEdgeWeights -> total edge weights of each Node.
00039      *
00040      * @returns True if constructed. False if already constructed.
00041      */
00042  bool ConstructMatrix();
00043
00044      /** @brief Debug function to dump the model to a JSON file.
00045      *
00046      * Might not work 100%. Not meant for production use.
00047      */
00048  void DumpJSON();
00049
00050      /** @brief Random walk on the Matrix-reduced Markov::Model
00051      *
00052      * This has an O(N) Memory complexity. To limit the maximum usage, requests with n>50M are
00053      * partitioned using Markov::API::ModelMatrix::FastRandomWalkPartition.
00054      *
00055      * If n>50M, threads are going to be synced, files are going to be flushed, and buffers will
00056      * be reallocated every 50M generations.
00057      *
00058      * While it has the same functionality, this operation reduces
00059      * Markov::API::MarkovPasswords::Generate runtime by ~96.5
00060      *
00061      * This function has deprecated Markov::API::MarkovPasswords::Generate, and will eventually
00062      * replace it.
00063      *
00064      * @param n - Number of passwords to generate.
00065      * @param wordlistFileName - Filename to write to
00066      * @param minLen - Minimum password length to generate
00067      * @param maxLen - Maximum password length to generate
00068      * @param threads - number of OS threads to spawn
00069      * @param bFileIO - If false, filename will be ignored and will output to stdout.
00070      *
00071      * @endcode{.cpp}
00072      * Markov::API::ModelMatrix mp;
00073      * mp.Import("models/finished.mdl");
00074      * mp.FastRandomWalk(50000000,"./wordlist.txt",6,12,25, true);
00075      *
00076      int FastRandomWalk(unsigned long int n, const char* wordlistFileName, int minLen=6, int
00077      maxLen=12, int threads=20, bool bFileIO=true);
00078      /** @copydoc Markov::Model::Import(const char *filename)
00079      * Construct the matrix when done.
00080      *
00081      */
00082  void Import(const char *filename);
00083
00084      /** @copydoc Markov::API::MarkovPasswords::Train(const char *datasetFileName, char delimiter,
00085      * int threads)
00086      * Construct the matrix when done.
00087      *
00088      void Train(const char *datasetFileName, char delimiter, int threads);
00089
00090  protected:
00091
00092      /** @brief Random walk on the Matrix-reduced Markov::Model
00093      *
00094      * This has an O(N) Memory complexity. To limit the maximum usage, requests with n>50M are
00095      * partitioned using Markov::API::ModelMatrix::FastRandomWalkPartition.
00096      *
00097      * If n>50M, threads are going to be synced, files are going to be flushed, and buffers will

```

```

        be reallocated every 50M generations.
00097     * This comes at a minor performance penalty.
00098     *
00099     * While it has the same functionality, this operation reduces
Markov::API::MarkovPasswords::Generate runtime by %96.5
00100     *
00101     * This function has deprecated Markov::API::MarkovPasswords::Generate, and will eventually
replace it.
00102     *
00103     * @param n - Number of passwords to generate.
00104     * @param wordlistFileName - Filename to write to
00105     * @param minLen - Minimum password length to generate
00106     * @param maxLen - Maximum password length to generate
00107     * @param threads - number of OS threads to spawn
00108     * @param bFileIO - If false, filename will be ignored and will output to stdout.
00109     *
00110     *
00111     * @endcode{.cpp}
00112     * Markov::API::ModelMatrix mp;
00113     * mp.Import("models/finished.mdl");
00114     * mp.FastRandomWalk(50000000,"./wordlist.txt",6,12,25, true);
00115     * @endcode
00116     *
00117     */
00118     int FastRandomWalk(unsigned long int n, std::ofstream *wordlist, int minLen=6, int maxLen=12,
int threads=20, bool bFileIO=true);
00119
00120
00121     /** @brief A single partition of FastRandomWalk event
00122     *
00123     * Since FastRandomWalk has to allocate its output buffer before operation starts and writes
data in chunks,
00124     * large n parameters would lead to huge memory allocations.
00125     * @b Without @b Partitioning:
00126     * - 50M results 12 characters max -> 550 Mb Memory allocation
00127     *
00128     * - 5B results 12 characters max -> 55 Gb Memory allocation
00129     *
00130     * - 50B results 12 characters max -> 550GB Memory allocation
00131     *
00132     * Instead, FastRandomWalk is partitioned per 50M generations to limit the top memory need.
00133     *
00134     * @param mlock - mutex lock to distribute to child threads
00135     * @param wordlist - Reference to the wordlist file to write to
00136     * @param n - Number of passwords to generate.
00137     * @param wordlistFileName - Filename to write to
00138     * @param minLen - Minimum password length to generate
00139     * @param maxLen - Maximum password length to generate
00140     * @param threads - number of OS threads to spawn
00141     * @param bFileIO - If false, filename will be ignored and will output to stdout.
00142     *
00143     *
00144     */
00145     void FastRandomWalkPartition(std::mutex *mlock, std::ofstream *wordlist, unsigned long int n,
int minLen, int maxLen, bool bFileIO, int threads);
00146
00147     /** @brief A single thread of a single partition of FastRandomWalk
00148     *
00149     * A FastRandomWalkPartition will initiate as many of this function as requested.
00150     *
00151     * This function contains the bulk of the generation algorithm.
00152     *
00153     * @param mlock - mutex lock to distribute to child threads
00154     * @param wordlist - Reference to the wordlist file to write to
00155     * @param n - Number of passwords to generate.
00156     * @param wordlistFileName - Filename to write to
00157     * @param minLen - Minimum password length to generate
00158     * @param maxLen - Maximum password length to generate
00159     * @param id - @b DEPRECATED Thread id - No longer used
00160     * @param bFileIO - If false, filename will be ignored and will output to stdout.
00161     *
00162     *
00163     */
00164     void FastRandomWalkThread(std::mutex *mlock, std::ofstream *wordlist, unsigned long int n, int
minLen, int maxLen, int id, bool bFileIO);
00165
00166     /** @brief Deallocate matrix and make it ready for re-construction
00167     *
00168     * @returns True if deallocated. False if matrix was not initialized
00169     */
00170     bool DeallocateMatrix();
00171
00172     /**
00173         @brief 2-D Character array for the edge Matrix (The characters of Nodes)
00174     */
00175     char** edgeMatrix;
00176

```

```

00177     /**
00178      @brief 2-d Integer array for the value Matrix (For the weights of Edges)
00179 */
00180 long int **valueMatrix;
00181
00182 /**
00183  @brief to hold Matrix size
00184 */
00185 int matrixSize;
00186
00187 /**
00188  @brief to hold the Matrix index (To hold the orders of 2-D arrays')
00189 */
00190 char* matrixIndex;
00191
00192 /**
00193  @brief Array of the Total Edge Weights
00194 */
00195 long int *totalEdgeWeights;
00196
00197 /**
00198  @brief True when matrix is constructed. False if not.
00199 */
00200 bool ready;
00201 };
00202
00203
00204
00205 };


```

10.63 node.h File Reference


Node class template.

```
#include <vector>
#include <map>
#include <assert.h>
#include <iostream>
#include <stdexcept>
#include "edge.h"
#include "random.h"
```

Include dependency graph for node.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::Node< storageType >](#)

A node class that for the vertices of model. Connected with eachother using [Edge](#).

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

10.63.1 Detailed Description

Node class template.

Authors

Ata Hakçıl, Osman Ömer Yıldıztugay

A node class that for the vertices of model. Connected with eachother using Edge. This class will later be templated to accept other data types than char*.

Definition in file [node.h](#).

10.64 node.h

```

00001 /** @file node.h
00002 * @brief Node class template
00003 * @authors Ata Hakçıl, Osman Ömer Yıldıztugay
00004 *
00005 * @copydoc Markov::Node
00006 */
00007
00008
00009 #pragma once
00010 #include <vector>
00011 #include <map>
00012 #include <assert.h>
00013 #include <iostream>
00014 #include <stdexcept> // To use runtime_error
00015 #include "edge.h"
00016 #include "random.h"
00017 namespace Markov {
00018     /** @brief A node class that for the vertices of model. Connected with eachother using Edge
00020     *
  
```

```

00021 * This class will later be templated to accept other data types than char*.
00022 */
00023 template <typename storageType>
00024 class Node {
00025 public:
00026     /** @brief Default constructor. Creates an empty Node.
00027     */
00028     Node<storageType>();
00029
00030     /** @brief Constructor. Creates a Node with no edges and with given NodeValue.
00031      * @param _value - Nodes character representation.
00032      */
00033     * @b Example @b Use: Construct nodes
00034     * @code{.cpp}
00035     * Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00036     * Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00037     * @endcode
00038     */
00039
00040     Node<storageType>(storageType _value);
00041
00042     /** @brief Link this node with another, with this node as its source.
00043     */
00044     * Creates a new Edge.
00045     * @param target - Target node which will be the RightNode() of new edge.
00046     * @return A new node with LeftNode as this, and RightNode as parameter target.
00047     */
00048     * @b Example @b Use: Construct nodes
00049     * @code{.cpp}
00050     * Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00051     * Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00052     * Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
00053     * @endcode
00054     */
00055     Edge<storageType>* Link(Node<storageType>* );
00056
00057     /** @brief Link this node with another, with this node as its source.
00058     */
00059     * *DOES NOT* create a new Edge.
00060     * @param Edge - Edge that will accept this node as its LeftNode.
00061     * @return the same edge as parameter target.
00062     */
00063     * @b Example @b Use: Construct and link nodes
00064     * @code{.cpp}
00065     * Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00066     * Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00067     * Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
00068     * LeftNode->Link(e);
00069     * @endcode
00070     */
00071     Edge<storageType>* Link(Edge<storageType>* );
00072
00073     /** @brief Chose a random node from the list of edges, with regards to its EdgeWeight, and
00074      * TraverseNode to that.
00075      */
00076     * This operation is done by generating a random number in range of 0-this.total_edge_weights,
00077     * and then iterating over the list of edges.
00078     * At each step, EdgeWeight of the edge is subtracted from the random number, and once it is
00079     * 0, next node is selected.
00080     * @return Node that was chosen at EdgeWeight biased random.
00081
00082     * @b Example @b Use: Use randomNext to do a random walk on the model
00083     * @code{.cpp}
00084     * char* buffer[64];
00085     * Markov::Model<char> model;
00086     * model.Import("model.mdl");
00087     * Markov::Node<char>* n = model.starterNode;
00088     * int len = 0;
00089     * Markov::Node<char>* temp_node;
00090     * while (true) {
00091     *     temp_node = n->RandomNext(randomEngine);
00092     *     if (len >= maxSetting) {
00093     *         break;
00094     *     }
00095     *     else if ((temp_node == NULL) && (len < minSetting)) {
00096     *         continue;
00097     *     }
00098     *     else if (temp_node == NULL){
00099     *         break;
00100     *     }
00101     *     n = temp_node;
00102     *     buffer[len++] = n->NodeValue();
00103     * }
00104     * @endcode

```

```

00105      */
00106      Node<storageType>* RandomNext(Markov::Random::RandomEngine* randomEngine);
00107
00108  /** @brief Insert a new edge to the this.edges.
00109   * @param edge - New edge that will be inserted.
00110   * @return true if insertion was successful, false if it fails.
00111   */
00112  /** @b Example @b Use: Construct and update edges
00113   */
00114  /** @code{.cpp}
00115   * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00116   * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00117   * Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00118   * Markov::Edge<unsigned char>* el = new Markov::Edge<unsigned char>(src, target1);
00119   * Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target2);
00120   * el->AdjustEdge(25);
00121   * src->UpdateEdges(el);
00122   * e2->AdjustEdge(30);
00123   * src->UpdateEdges(e2);
00124   * @endcode
00125   */
00126  bool UpdateEdges(Edge<storageType>* );
00127
00128  /** @brief Find an edge with its character representation.
00129   * @param repr - character NodeValue of the target node.
00130   * @return Edge that is connected between this node, and the target node.
00131   */
00132  /** @b Example @b Use: Construct and update edges
00133   */
00134  /** @code{.cpp}
00135   * Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00136   * Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00137   * Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00138   * Markov::Edge<unsigned char>* res = NULL;
00139   * src->Link(target1);
00140   * src->Link(target2);
00141   * res = src->FindEdge('b');
00142   *
00143   * @endcode
00144   */
00145  */
00146  Edge<storageType>* FindEdge(storageType repr);
00147
00148  /** @brief Find an edge with its pointer. Avoid unless neccessary because computational cost
00149  * of find by character is cheaper (because of std::map)
00150  * @param target - target node.
00151  * @return Edge that is connected between this node, and the target node.
00152  */
00153  Edge<storageType>* FindEdge(Node<storageType>* target);
00154
00155  /** @brief Return character representation of this node.
00156  * @return character representation at _value.
00157  */
00158  inline unsigned char NodeValue();
00159
00160  /** @brief Change total weights with offset
00161  * @param offset to adjust the vertice weight with
00162  */
00163  void UpdateTotalVerticeWeight(long int offset);
00164
00165  /** @brief return edges
00166  */
00167  inline std::map<storageType, Edge<storageType>*>* Edges();
00168
00169  /** @brief return total edge weights
00170  */
00171  inline long int TotalEdgeWeights();
00172
00173  std::vector<Edge<storageType>*> edgesV;
00174 private:
00175
00176  /**
00177   * @brief Character representation of this node. 0 for starter, 0xff for terminator.
00178   */
00179  storageType _value;
00180
00181  /**
00182   * @brief Total weights of the vertices, required by RandomNext
00183   */
00184  long int total_edge_weights;
00185
00186  /**
00187   * @brief A map of all edges connected to this node, where this node is at the LeftNode.
00188   * Map is indexed by unsigned char, which is the character representation of the node.
00189   */
00190  std::map<storageType, Edge<storageType>*> edges;

```

```

00191     };
00192 };
00193
00194
00195
00196
00197
00198
00199
00200
00201
00202 template <typename storageType>
00203 Markov::Node<storageType>::Node(storageType _value) {
00204     this->_value = _value;
00205     this->total_edge_weights = 0L;
00206 };
00207
00208 template <typename storageType>
00209 Markov::Node<storageType>::Node() {
00210     this->_value = 0;
00211     this->total_edge_weights = 0L;
00212 };
00213
00214 template <typename storageType>
00215 inline unsigned char Markov::Node<storageType>::NodeValue() {
00216     return _value;
00217 }
00218
00219 template <typename storageType>
00220 Markov::Edge<storageType>* Markov::Node<storageType>::Link(Markov::Node<storageType>* n) {
00221     Markov::Edge<storageType>* v = new Markov::Edge<storageType>(this, n);
00222     this->UpdateEdges(v);
00223     return v;
00224 }
00225
00226 template <typename storageType>
00227 Markov::Edge<storageType>* Markov::Node<storageType>::Link(Markov::Edge<storageType>* v) {
00228     v->SetLeftEdge(this);
00229     this->UpdateEdges(v);
00230     return v;
00231 }
00232
00233 template <typename storageType>
00234 Markov::Node<storageType>* Markov::Node<storageType>::RandomNext(Markov::Random::RandomEngine* randomEngine) {
00235
00236     //get a random NodeValue in range of total_vertex_weight
00237     long int selection = randomEngine->random() %
00238         this->total_edge_weights; //distribution()(generator()); // distribution(generator);
00239     //make absolute, no negative modulus values wanted
00240     //selection = (selection >= 0) ? selection : (selection + this->total_edge_weights);
00241     for(int i=0;i<this->edgesV.size();i++){
00242         selection -= this->edgesV[i]->EdgeWeight();
00243         if (selection < 0) return this->edgesV[i]->TraverseNode();
00244     }
00245
00246     //if this assertion is reached, it means there is an implementation error above
00247     std::cout << "This should never be reached (node failed to walk to next)\n"; //cant assert from
00248     child thread
00249     assert(true && "This should never be reached (node failed to walk to next)");
00250     return NULL;
00251 }
00252
00253 template <typename storageType>
00254 bool Markov::Node<storageType>::UpdateEdges(Markov::Edge<storageType>* v) {
00255     this->edges.insert({ v->RightNode()->NodeValue(), v });
00256     this->edgesV.push_back(v);
00257     //this->total_edge_weights += v->EdgeWeight();
00258     return v->TraverseNode();
00259 }
00260
00261 template <typename storageType>
00262 Markov::Edge<storageType>* Markov::Node<storageType>::FindEdge(storageType repr) {
00263     auto e = this->edges.find(repr);
00264     if (e == this->edges.end()) return NULL;
00265     return e->second;
00266 }
00267
00268 template <typename storageType>
00269 void Markov::Node<storageType>::UpdateTotalVerticeWeight(long int offset) {
00270     this->total_edge_weights += offset;
00271 }
00272
00273 template <typename storageType>
00274 inline std::map<storageType, Markov::Edge<storageType>*>& Markov::Node<storageType>::Edges() {
00275     return &(this->edges);
00276 }
```

```


00275
00276 template <typename storageType>
00277 inline long int Markov::Node<storageType>::TotalEdgeWeights() {
00278     return this->total_edge_weights;
00279 }
```

10.65 pch.cpp File Reference

For windows dynamic library.

```
#include "pch.h"
```

Include dependency graph for MarkovModel/src/pch.cpp:



10.65.1 Detailed Description

For windows dynamic library.

Authors

Ata Hakçıl

Definition in file [MarkovModel/src/pch.cpp](#).

10.66 MarkovModel/src/pch.cpp


```

00001 /**
00002 * @file pch.cpp
00003 * @brief For windows dynamic library
00004 * @authors Ata Hakçıl
00005 */
00006
00007 // pch.cpp: source file corresponding to the pre-compiled header
00008
00009 #include "pch.h"
00010
00011 // When you are using pre-compiled headers, this source file is necessary for compilation to succeed.
```

10.67 pch.cpp File Reference

For windows dynamic library.

```
#include "pch.h"
Include dependency graph for UnitTests/pch.cpp:
```



10.67.1 Detailed Description

For windows dynamic library.

Authors

Ata Hakçıl

Definition in file [UnitTests/pch.cpp](#).

10.68 UnitTests/pch.cpp


```
00001 /** @file pch.cpp
00002 * @brief For windows dynamic library
00003 * @authors Ata Hakçıl
00004 *
00005 */
00006 // pch.cpp: source file corresponding to the pre-compiled header
00007
00008 #include "pch.h"
00009
00010 // When you are using pre-compiled headers, this source file is necessary for compilation to succeed.
```

10.69 pch.h File Reference


For windows dynamic library.

```
#include "framework.h"
```

Include dependency graph for MarkovModel/src/pch.h:



This graph shows which files directly or indirectly include this file:



10.69.1 Detailed Description

For windows dynamic library.

Authors

Ata Hakçıl

Definition in file [MarkovModel/src/pch.h](#).


10.70 MarkovModel/src/pch.h

```
00001 /** @file pch.h
00002 * @brief For windows dynamic library
00003 * @authors Ata Hakçıl
00004 *
00005 */
00006 // pch.h: This is a precompiled header file.
00007 // Files listed below are compiled only once, improving build performance for future builds.
00008 // This also affects IntelliSense performance, including code completion and many code browsing
00009 // features.
00010 // However, files listed here are ALL re-compiled if any one of them is updated between builds.
00011 // Do not add files here that you will be updating frequently as this negates the performance
00012 // advantage.
00013 #ifndef PCH_H
00014 #define PCH_H
00015 // add headers that you want to pre-compile here
00016 #include "framework.h"
00017
00018 #endif //PCH_H
```

10.71 pch.h File Reference

For windows dynamic library.

This graph shows which files directly or indirectly include this file:



10.71.1 Detailed Description

For windows dynamic library.

Authors

Ata Hakçıl

Definition in file [UnitTests/pch.h](#).

10.72 UnitTests/pch.h

```

00001 /**
00002 * @brief For windows dynamic library
00003 * @authors Ata Hakçıl
00004 *
00005 */
00006 // pch.h: This is a precompiled header file.
00007 // Files listed below are compiled only once, improving build performance for future builds.
00008 // This also affects IntelliSense performance, including code completion and many code browsing
00009 // features.
00010 // However, files listed here are ALL re-compiled if any one of them is updated between builds.
00011 // Do not add files here that you will be updating frequently as this negates the performance
00012 // advantage.
00013 #ifndef PCH_H
00014 #define PCH_H
00015 // add headers that you want to pre-compile here
00016
00017 #endif //PCH_H
  
```

10.73 random-model.py File Reference

Namespaces

- [random-model](#)
- [random](#)

Variables

- `random-model.alphabet = string.printable`
password alphabet
- `random-model.f = open('..../models/random.mdl', "wb")`
output file handle

10.74 random-model.py

```


00001 #!/usr/bin/python3
00002 """
00003     python script for generating a 2gram model
00004 """
00005
00006 import string
00007 import re
00008
00009
00010 alphabet = string.printable
00011 alphabet = re.sub('\s', " ", alphabet)
00012 print(f"alphabet={alphabet}")
00013 #exit()
00014
00015
00016 f = open('../models/random.mdl', "wb")
00017 #tie start nodes
00018 for sym in alphabet:
00019     f.write(b"\x00,1," + bytes(sym, encoding='ascii') + b"\n")
00020
00021 #tie terminator nodes
00022 for sym in alphabet:
00023     f.write(bytes(sym, encoding='ascii')+ b",1,\xff\n")
00024
00025 #tie internals
00026 for src in alphabet:
00027     for target in alphabet:
00028         f.write(bytes(src, encoding='ascii') + b",1," + bytes(target, encoding='ascii') + b"\n")

```


10.75 random.h File Reference

Random engine implementations for [Markov](#).

```
#include <random>
#include <iostream>
Include dependency graph for random.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::Random::RandomEngine](#)
An abstract class for Random Engine.
- class [Markov::Random::DefaultRandomEngine](#)
Implementation using Random.h default random engine.
- class [Markov::Random::Marsaglia](#)
Implementation of Marsaglia Random Engine.
- class [Markov::Random::Mersenne](#)
Implementation of Mersenne Twister Engine.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains Model, Node and Edge classes.
- [Markov::Random](#)
Objects related to RNG.

10.75.1 Detailed Description

Random engine implementations for [Markov](#).

Authors

Ata Hakçıl

An abstract class for Random Engine. This class is used for generating random numbers, which are used for random walking on the graph.

Main reason behind allowing different random engines is that some use cases may favor performance, while some favor good random.

Mersenne can be used for truer random, while Marsaglia can be used for deterministic but fast random.

Implementation using [Random.h](#) default random engine. This engine is also used by other engines for seeding.

Example Use: Using Default Engine with RandomWalk

```

Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::DefaultRandomEngine randomEngine;
  
```

```

for (int i = 0; i < 10; i++) {
    this->RandomWalk(&randomEngine, 5, 10, res);
    std::cout << res << "\n";
}

```

Example Use: Generating a random number with Marsaglia Engine

```

Markov::Random::DefaultRandomEngine de;
std::cout << de.random();

```

Implementation of Marsaglia Random Engine. This is an implementation of Marsaglia Random engine, which for most use cases is a better fit than other solutions. Very simple mathematical formula to generate pseudorandom integer, so its crazy fast.

This implementation of the Marsaglia Engine is seeded by [random.h](#) default random engine. RandomEngine is only seeded once so its not a performance issue.

Example Use: Using Marsaglia Engine with RandomWalk

```

Markov::Model<char> model;
Model.import("model.mdl");
char* res = new char[11];
Markov::Random::Marsaglia MarsagliaRandomEngine;
for (int i = 0; i < 10; i++) {
    this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
    std::cout << res << "\n";
}

```

Example Use: Generating a random number with Marsaglia Engine

```

Markov::Random::Marsaglia me;
std::cout << me.random();

```

Definition in file [random.h](#).

10.76 random.h

```

00001
00002 /** @file random.h
00003 * @brief Random engine implementations for Markov
00004 * @authors Ata Hakçıl
00005 *
00006 * @copydoc Markov::Random::RandomEngine
00007 * @copydoc Markov::Random::DefaultRandomEngine
00008 * @copydoc Markov::Random::Marsaglia
00009 */
00010
00011 #pragma once
00012 #include <random>
00013 #include <iostream>
00014
00015 /**
00016     @brief Objects related to RNG
00017 */
00018 namespace Markov::Random{
00019
00020     /** @brief An abstract class for Random Engine
00021     *
00022     * This class is used for generating random numbers, which are used for random walking on the
00023     * graph.
00024     *
00025     * Main reason behind allowing different random engines is that some use cases may favor
00026     * performance,
00027     * while some favor good random.
00028     *
00029     */
00030     class RandomEngine{
00031     public:
00032         virtual inline unsigned long random() = 0;
00033     };
00034
00035
00036
00037     /** @brief Implementation using Random.h default random engine
00038     *
00039     * This engine is also used by other engines for seeding.
00040     *
00041     */
00042     * @b Example @b Use: Using Default Engine with RandomWalk
00043     * @code{.cpp}
00044     * Markov::Model<char> model;
00045     * Model.import("model.mdl");
00046     * char* res = new char[11];
00047     * Markov::Random::DefaultRandomEngine randomEngine;
00048     * for (int i = 0; i < 10; i++) {
00049         *     this->RandomWalk(&randomEngine, 5, 10, res);

```

```

00050     *      std::cout << res << "\n";
00051     *
00052     * @endcode
00053     *
00054     * @b Example @b Use: Generating a random number with Marsaglia Engine
00055     * @code{.cpp}
00056     * Markov::Random::DefaultRandomEngine de;
00057     * std::cout << de.random();
00058     * @endcode
00059     *
00060 */
00061 class DefaultRandomEngine : public RandomEngine{
00062 public:
00063     /** @brief Generate Random Number
00064      * @return random number in long range.
00065      */
00066     inline unsigned long random(){
00067         return this->distribution()(this->generator());
00068     }
00069 protected:
00070     /** @brief Default random device for seeding
00071      *
00072      */
00073     inline std::random_device& rd() {
00074         static std::random_device _rd;
00075         return _rd;
00076     }
00077
00078     /** @brief Default random engine for seeding
00079      *
00080      */
00081     inline std::default_random_engine& generator() {
00082         static std::default_random_engine _generator(rd());
00083         return _generator;
00084     }
00085
00086     /** @brief Distribution schema for seeding.
00087      *
00088      */
00089     inline std::uniform_int_distribution<long long unsigned>& distribution() {
00090         static std::uniform_int_distribution<long long unsigned> _distribution(0, 0xffffffff);
00091         return _distribution;
00092     }
00093 }
00094
00095 /**
00096 /**
00097     * @brief Implementation of Marsaglia Random Engine
00098     *
00099     * This is an implementation of Marsaglia Random engine, which for most use cases is a better fit
00100 than other solutions.
00101     * Very simple mathematical formula to generate pseudorandom integer, so its crazy fast.
00102     *
00103     * This implementation of the Marsaglia Engine is seeded by random.h default random engine.
00104     * RandomEngine is only seeded once so its not a performance issue.
00105     *
00106     * @b Example @b Use: Using Marsaglia Engine with RandomWalk
00107     * @code{.cpp}
00108     * Markov::Model<char> model;
00109     * Model.import("model.mdl");
00110     * char* res = new char[11];
00111     * Markov::Random::Marsaglia MarsagliaRandomEngine;
00112     * for (int i = 0; i < 10; i++) {
00113         this->RandomWalk(&MarsagliaRandomEngine, 5, 10, res);
00114         std::cout << res << "\n";
00115     }
00116     * @endcode
00117
00118     * @b Example @b Use: Generating a random number with Marsaglia Engine
00119     * @code{.cpp}
00120     * Markov::Random::Marsaglia me;
00121     * std::cout << me.random();
00122     * @endcode
00123     *
00124 */
00125 class Marsaglia : public DefaultRandomEngine{
00126 public:
00127     /** @brief Construct Marsaglia Engine
00128     *
00129     * Initialize x,y and z using the default random engine.
00130     */
00131     Marsaglia(){
00132         this->x = this->distribution()(this->generator());
00133         this->y = this->distribution()(this->generator());
00134         this->z = this->distribution()(this->generator());
00135

```

```

00136         //std::cout << "x: " << x << ", y: " << y << ", z: " << z << "\n";
00137     }
00138
00139
00140     inline unsigned long random() {
00141         unsigned long t;
00142         x ^= x << 16;
00143         x ^= x >> 5;
00144         x ^= x << 1;
00145
00146         t = x;
00147         x = y;
00148         y = z;
00149         z = t ^ x ^ y;
00150
00151         return z;
00152     }
00153
00154
00155     unsigned long x;
00156     unsigned long y;
00157     unsigned long z;
00158 };
00159
00160
00161     /** @brief Implementation of Mersenne Twister Engine
00162     *
00163     * This is an implementation of Mersenne Twister Engine, which is slow but is a good
00164     * implementation for high entropy pseudorandom.
00165     *
00166     * @b Example @b Use: Using Mersenne Engine with RandomWalk
00167     * @code{.cpp}
00168     * Markov::Model<char> model;
00169     * Model.import("model.mdl");
00170     * char* res = new char[11];
00171     * Markov::Random::Mersenne MersenneTwisterEngine;
00172     * for (int i = 0; i < 10; i++) {
00173     *     this->RandomWalk(&MersenneTwisterEngine, 5, 10, res);
00174     *     std::cout << res << "\n";
00175     * }
00176     * @endcode
00177     *
00178     * @b Example @b Use: Generating a random number with Marsaglia Engine
00179     * @code{.cpp}
00180     * Markov::Random::Mersenne me;
00181     * std::cout << me.random();
00182     * @endcode
00183     *
00184     */
00185     class Mersenne : public DefaultRandomEngine{
00186
00187 };
00188
00189
00190 };

```

10.77 README.md File Reference


10.78 report.md File Reference

10.79 term.cpp File Reference

Terminal handler for pretty stuff like colors.

```
#include "term.h"
#include <string>
```

Include dependency graph for term.cpp:



Functions

- std::ostream & [operator<<](#) (std::ostream &os, const Terminal::color &c)

10.79.1 Detailed Description

Terminal handler for pretty stuff like colors.

Authors

Ata Hakçıl

pretty colors for Terminal. Windows Only.

Definition in file [term.cpp](#).

10.79.2 Function Documentation

10.79.2.1 operator<<()

```
std::ostream& operator<< (
    std::ostream & os,
    const Markov::API::CLI::Terminal::color & c )
```

overload for std::cout.

Definition at line 66 of file [term.cpp](#).

```
00066
00067     char buf[6];
00068     sprintf(buf,"%d",Terminal::colormap.find(c)->second);
00069     os << "\e[1;" << buf << "m";
00070     return os;
00071 }
```

References [Markov::API::CLI::Terminal::colormap](#).

10.80 term.cpp

```
00001 /** @file term.cpp
00002 * @brief Terminal handler for pretty stuff like colors
00003 * @authors Ata Hakçıl
00004 *
```

```

00005 * @copydoc Markov::API::CLI::Terminal
00006 */
00007
00008 #include "term.h"
00009 #include <string>
00010
00011 using namespace Markov::API::CLI;
00012
00013 //Windows text processing is different from unix systems, so use windows header and text attributes
00014 #ifdef _WIN32
00015
00016 HANDLE Terminal::_stdout;
00017 HANDLE Terminal::_stderr;
00018
00019 std::map<Terminal::color, DWORD> Terminal::colormap = {
00020     {Terminal::color::BLACK, 0},
00021     {Terminal::color::BLUE, 1},
00022     {Terminal::color::GREEN, 2},
00023     {Terminal::color::CYAN, 3},
00024     {Terminal::color::RED, 4},
00025     {Terminal::color::MAGENTA, 5},
00026     {Terminal::color::BROWN, 6},
00027     {Terminal::color::LIGHTGRAY, 7},
00028     {Terminal::color::DARKGRAY, 8},
00029     {Terminal::color::YELLOW, 14},
00030     {Terminal::color::WHITE, 15},
00031     {Terminal::color::RESET, 15},
00032 };
00033
00034
00035 Terminal::Terminal() {
00036     Terminal::_stdout = GetStdHandle(STD_OUTPUT_HANDLE);
00037     Terminal::_stderr = GetStdHandle(STD_ERROR_HANDLE);
00038 }
00039
00040 std::ostream& operator<<(std::ostream& os, const Terminal::color& c) {
00041     SetConsoleTextAttribute(Terminal::_stdout, Terminal::colormap.find(c)->second);
00042     return os;
00043 }
00044
00045 #else
00046
00047 std::map<Terminal::color, int> Terminal::colormap = {
00048     {Terminal::color::BLACK, 30},
00049     {Terminal::color::BLUE, 34},
00050     {Terminal::color::GREEN, 32},
00051     {Terminal::color::CYAN, 36},
00052     {Terminal::color::RED, 31},
00053     {Terminal::color::MAGENTA, 35},
00054     {Terminal::color::BROWN, 0},
00055     {Terminal::color::LIGHTGRAY, 0},
00056     {Terminal::color::DARKGRAY, 0},
00057     {Terminal::color::YELLOW, 33},
00058     {Terminal::color::WHITE, 37},
00059     {Terminal::color::RESET, 0},
00060 };
00061
00062 Terminal::Terminal() {
00063     /*this->;*/
00064 }
00065
00066 std::ostream& operator<<(std::ostream& os, const Terminal::color& c) {
00067     char buf[6];
00068     sprintf(buf, "%d", Terminal::colormap.find(c)->second);
00069     os << "\e[1;" << buf << "m";
00070     return os;
00071 }
00072
00073
00074
00075
00076 #endif


```

10.81 term.h File Reference


Terminal handler for pretty stuff like colors.

```
#include <iostream>
#include <map>
```

Include dependency graph for term.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::CLI::Terminal](#)
pretty colors for Terminal. Windows Only.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains Model, Node and Edge classes.
- [Markov::API](#)
Namespace for the MarkovPasswords API.
- [Markov::API::CLI](#)
Structure to hold parsed cli arguements.

Macros

- `#define TERM_FAIL "[" << Markov::API::CLI::Terminal::color::RED << "+" << Markov::API::CLI::Terminal::color::RESET << "] "`
- `#define TERM_INFO "[" << Markov::API::CLI::Terminal::color::BLUE << "+" << Markov::API::CLI::Terminal::color::RESET << "] "`
- `#define TERM_WARN "[" << Markov::API::CLI::Terminal::color::YELLOW << "+" << Markov::API::CLI::Terminal::color::RESET << "] "`
- `#define TERM_SUCC "[" << Markov::API::CLI::Terminal::color::GREEN << "+" << Markov::API::CLI::Terminal::color::RESET << "] "`

Functions

- std::ostream & [Markov::API::CLI::operator<<](#) (std::ostream &os, const Markov::API::CLI::Terminal::color &c)

10.81.1 Detailed Description

Terminal handler for pretty stuff like colors.

Authors

Ata Hakçıl

pretty colors for Terminal. Windows Only.

Definition in file [term.h](#).

10.81.2 Macro Definition Documentation

10.81.2.1 TERM_FAIL

```
#define TERM_FAIL "[" << Markov::API::CLI::Terminal::color::RED << "+" << Markov::API::CLI::Terminal::color
<< "] "
```

Definition at line 17 of file [term.h](#).

10.81.2.2 TERM_INFO

```
#define TERM_INFO "[" << Markov::API::CLI::Terminal::color::BLUE << "+" << Markov::API::CLI::Terminal::color
<< "] "
```

Definition at line 18 of file [term.h](#).

10.81.2.3 TERM_SUCC

```
#define TERM_SUCC "[" << Markov::API::CLI::Terminal::color::GREEN << "+" << Markov::API::CLI::Terminal::color
<< "] "
```

Definition at line 20 of file [term.h](#).

10.81.2.4 TERM_WARN

```
#define TERM_WARN "[" << Markov::API::CLI::Terminal::color::YELLOW << "+" << Markov::API::CLI::Terminal::color
<< "] "
```

Definition at line 19 of file [term.h](#).

10.82 term.h

```
00001 /* @file term.h
00002 * @brief Terminal handler for pretty stuff like colors
00003 * @authors Ata Hakçıl
00004 *
00005 * @copydoc Markov::API::CLI::Terminal
00006 */
00007
00008 #pragma once
00009
00010 #ifdef _WIN32
00011 #include <Windows.h>
00012 #endif
00013
00014 #include <iostream>
00015 #include <map>
00016
00017 #define TERM_FAIL "[" << Markov::API::CLI::Terminal::color::RED << "+" <<
Markov::API::CLI::Terminal::color::RESET << "] "
```

```


00018 #define TERM_INFO "[" « Markov::API::CLI::Terminal::color::BLUE « "+" «
Markov::API::CLI::Terminal::color::RESET « "] "
00019 #define TERM_WARN "[" « Markov::API::CLI::Terminal::color::YELLOW « "+" «
Markov::API::CLI::Terminal::color::RESET « "] "
00020 #define TERM_SUCC "[" « Markov::API::CLI::Terminal::color::GREEN « "+" «
Markov::API::CLI::Terminal::color::RESET « "] "
00021
00022 namespace Markov::API::CLI{
00023     /** @brief pretty colors for Terminal. Windows Only.
00024     */
00025     class Terminal {
00026     public:
00027         /** Default constructor.
00028         * Get references to stdout and stderr handles.
00029         */
00030         Terminal();
00031
00032         enum color { RESET, BLACK, RED, GREEN, YELLOW, BLUE, MAGENTA, CYAN, WHITE, LIGHTGRAY,
DARKGRAY, BROWN };
00033         #ifdef _WIN32
00034             static HANDLE _stdout;
00035             static HANDLE _stderr;
00036             static std::map<Markov::API::CLI::Terminal::color, DWORD> colormap;
00037         #else
00038             static std::map<Markov::API::CLI::Terminal::color, int> colormap;
00039         #endif
00040
00041
00042
00043         static std::ostream endl;
00044
00045
00046
00047     };
00048
00049     /** overload for std::cout.
00050     */
00051     std::ostream& operator<<(std::ostream& os, const Markov::API::CLI::Terminal::color& c);
00052 }
00053 }
```

10.83 threadSharedListHandler.cpp File Reference

Thread-safe wrapper for std::ifstream.

```
#include "threadSharedListHandler.h"
```

Include dependency graph for threadSharedListHandler.cpp:



10.83.1 Detailed Description

Thread-safe wrapper for std::ifstream.

Authors

Ata Hakçıl

Simple class for managing shared access to file. This class maintains the handover of each line from a file to multiple threads.

When two different threads try to read from the same file while reading a line isn't completed, it can have unexpected results. Line might be split, or might be read twice. This class locks the read action on the list until a line is completed, and then proceeds with the handover.

Definition in file [threadSharedListHandler.cpp](#).

10.84 threadSharedListHandler.cpp


```

00001 /** @file threadSharedListHandler.cpp
00002  * @brief Thread-safe wrapper for std::ifstream
00003  * @authors Ata Hakçıl
00004  *
00005  * @copydoc Markov::API::Concurrency::ThreadSharedListHandler
00006  *
00007  */
00008
00009 #include "threadSharedListHandler.h"
00010
00011
00012 Markov::API::Concurrency::ThreadSharedListHandler::ThreadSharedListHandler(const char* filename) {
00013     this->listfile;
00014     this->listfile.open(filename, std::ios_base::binary);
00015 }
00016
00017
00018 bool Markov::API::Concurrency::ThreadSharedListHandler::next(std::string* line) {
00019     bool res = false;
00020     this->mlock.lock();
00021     res = (std::getline(this->listfile,*line,'\n'))? true : false;
00022     this->mlock.unlock();
00023
00024     return res;
00025 }
```


10.85 threadSharedListHandler.h File Reference

Thread-safe wrapper for std::ifstream.

```
#include <string>
#include <fstream>
#include <mutex>
Include dependency graph for threadSharedListHandler.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::API::Concurrency::ThreadSharedListHandler](#)

Simple class for managing shared access to file.

Namespaces

- [Markov](#)
Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.
- [Markov::API](#)
Namespace for the [MarkovPasswords API](#).
- [Markov::API::Concurrency](#)
Namespace for [Concurrency](#) related classes.

10.85.1 Detailed Description

Thread-safe wrapper for std::ifstream.

Authors

Ata Hakçıl

Simple class for managing shared access to file. This class maintains the handover of each line from a file to multiple threads.

When two different threads try to read from the same file while reading a line isn't completed, it can have unexpected results. Line might be split, or might be read twice. This class locks the read action on the list until a line is completed, and then proceeds with the handover.

Definition in file [threadSharedListHandler.h](#).

10.86 threadSharedListHandler.h

```

00001 /** @file threadSharedListHandler.h
00002 * @brief Thread-safe wrapper for std::ifstream
00003 * @authors Ata Hakçıl
00004 *
00005 * @copydoc Markov::API::Concurrency::ThreadSharedListHandler
00006 */
00007
00008 #include <string>
00009 #include <fstream>
00010 #include <mutex>
00011
00012 /** @brief Namespace for Concurrency related classes
00013 */
  
```

```

00014 namespace Markov::API::Concurrency{
00015
00016 /** @brief Simple class for managing shared access to file
00017 *
00018 * This class maintains the handover of each line from a file to multiple threads.
00019 *
00020 * When two different threads try to read from the same file while reading a line isn't completed, it
00021 * can have unexpected results.
00022 * Line might be split, or might be read twice.
00023 * This class locks the read action on the list until a line is completed, and then proceeds with the
00024 * handover.
00025 */
00026 class ThreadSharedListHandler{
00027 public:
00028     /** @brief Construct the Thread Handler with a filename
00029     *
00030     * Simply open the file, and initialize the locks.
00031     *
00032     * @b Example @b Use: Simple file read
00033     * @code{.cpp}
00034     * ThreadSharedListHandler listhandler("test.txt");
00035     * std::string line;
00036     * std::cout << listhandler->next(&line) << "\n";
00037     * @endcode
00038     *
00039     * @b Example @b Use: Example use case from MarkovPasswords showing multithreaded access
00040     * @code{.cpp}
00041     * void MarkovPasswords::Train(const char* datasetFileName, char delimiter, int threads) {
00042     *     ThreadSharedListHandler listhandler(datasetFileName);
00043     *     auto start = std::chrono::high_resolution_clock::now();
00044     *     std::vector<std::thread*> threadsV;
00045     *     for(int i=0;i<threads;i++){
00046         *         threadsV.push_back(new std::thread(&MarkovPasswords::TrainThread, this, &listhandler,
00047         * datasetFileName, delimiter));
00048         *
00049         *         for(int i=0;i<threads;i++){
00050         *             threadsV[i]->join();
00051         *             delete threadsV[i];
00052         *         }
00053         *         auto finish = std::chrono::high_resolution_clock::now();
00054         *         std::chrono::duration<double> elapsed = finish - start;
00055         *         std::cout << "Elapsed time: " << elapsed.count() << " s\n";
00056         *
00057         *     }
00058         *
00059         *     void MarkovPasswords::TrainThread(ThreadSharedListHandler *listhandler, const char*
00060         * datasetFileName, char delimiter){
00061         *         char format_str[] ="%ld,%s";
00062         *         format_str[2]=delimiter;
00063         *         std::string line;
00064         *         while (listhandler->next(&line)) {
00065         *             long int oc;
00066         *             if (line.size() > 100) {
00067         *                 line = line.substr(0, 100);
00068         *             }
00069         *             char* linebuf = new char[line.length()+5];
00070         *             sscanf_s(line.c_str(), format_str, &oc, linebuf, line.length()+5);
00071         *             this->AdjustEdge((const char*)linebuf, oc);
00072         *             delete linebuf;
00073         *         }
00074         *     @endcode
00075         *
00076         * @param filename Filename for the file to manage.
00077     */
00078     ThreadSharedListHandler(const char* filename);
00079
00080     /** @brief Read the next line from the file.
00081     *
00082     * This action will be blocked until another thread (if any) completes the read operation on the
00083     * file.
00084     *
00085     * @b Example @b Use: Simple file read
00086     * @code{.cpp}
00087     * ThreadSharedListHandler listhandler("test.txt");
00088     * std::string line;
00089     * std::cout << listhandler->next(&line) << "\n";
00090     * @endcode
00091     *
00092     * @return bool next(std::string* line);
00093
00094 private:
00095     std::ifstream listfile;

```


```
00096     std::mutex mlock;
00097 };
00098
00099 };
```

10.87 Train.cpp File Reference

training page for GUI

```
#include "Train.h"
#include <fstream>
#include <QFileDialog>
#include <QMMessageBox>
#include <QTextStream>
#include <QDir>
#include "CLI.h"
#include "MarkovAPI/src/markovPasswords.h"
#include <QtWidgets/QApplication>
#include "Generate.h"
```

Include dependency graph for Train.cpp:



10.87.1 Detailed Description

training page for GUI

Authors

Yunus Emre Yılmaz

Definition in file [Train.cpp](#).

10.88 Train.cpp

```
00001 /** @file Train.cpp
00002 * @brief training page for GUI
00003 * @authors Yunus Emre Yilmaz
00004 *
00005 */
00006
00007 #include "Train.h"
00008 #include <fstream>
00009 #include<QFileDialog>
00010 #include<QMMessageBox>
00011 #include<QTextStream>
00012 #include<QDir>
00013 #include "CLI.h"
00014 #include "MarkovAPI/src/markovPasswords.h"
00015
00016 #include <QtWidgets/QApplication>
00017 #include "Generate.h"
00018
00019
00020 using namespace Markov::GUI;
00021
00022 Markov::GUI::Train::Train(QWidget* parent)
00023     : QMainWindow(parent)
00024 {
00025     ui.setupUi(this);
00026 }
```

```

00027
00028
00029     QObject::connect(ui.pushButton, &QPushButton::clicked, this, [this] {train(); });
00030     QObject::connect(ui.pushButton_2, &QPushButton::clicked, this, [this] {home(); });
00031 //QObject::connect(ui.pushButton_3, &QPushButton::clicked, this, [this] {goGenerate(); });
00032
00033 //ui.pushButton_3->setVisible(false);
00034
00035
00036 }
00037
00038 void Markov::GUI::Train::train() {
00039
00040
00041
00042     QString file_name = QFileDialog::getOpenFileName(this, "Open a File", QDir::homePath());
00043     QFile file(file_name);
00044
00045     if (!file.open(QFile::ReadOnly | QFile::Text)) {
00046         QMessageBox::warning(this, "Error", "File Not Open!");
00047     }
00048     QTextStream in(&file);
00049     QString text = in.readAll();
00050     ui.plainTextEdit->setPlainText(text);
00051
00052
00053     char* cstr;
00054     std::string fname = file_name.toStdString();
00055     cstr = new char[fname.size() + 1];
00056     strcpy(cstr, fname.c_str());
00057
00058
00059
00060     char a=','; 
00061     Markov::API::MarkovPasswords mp;
00062     mp.Import("models/2gram.mdl");
00063     mp.Train(cstr, a, 10); //please parameterize this hardcoded 10 threads
00064     mp.Export("models/finished.mdl");
00065
00066     ui.label_2->setText("Training DONE!");
00067 //ui.pushButton_3->setVisible(true);
00068
00069
00070     file.close();
00071 }
00072
00073 void Markov::GUI::Train::home() {
00074     CLI* w = new CLI;
00075     w->show();
00076     this->close();
00077 }
00078 /*void Train::goGenerate() {
00079     Generate* w = new Generate;
00080     w->show();
00081     this->close();
00082 }*/


```

10.89 Train.h File Reference


training page for GUI

```
#include <QtWidgets/QMainWindow>
#include "ui_Train.h"
```

Include dependency graph for Train.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Markov::GUI::Train](#)

QT Training page class.

Namespaces

- [Markov](#)

Namespace for the markov-model related classes. Contains [Model](#), [Node](#) and [Edge](#) classes.

- [Markov::GUI](#)

namespace for MarkovPasswords [API GUI](#) wrapper

10.89.1 Detailed Description

training page for GUI

Authors

Yunus Emre Yılmaz

Definition in file [Train.h](#).

10.90 Train.h

```

00001 /** @file Train.h
00002 * @brief training page for GUI
00003 * @authors Yunus Emre Yilmaz
00004 *
00005 */
00006
00007 #pragma once
00008 #include <QtWidgets/QMainWindow>
00009 #include "ui_Train.h"
00010
00011 namespace Markov::GUI{
00012
00013     /** @brief QT Training page class
00014     */
00015     class Train :public QMainWindow {
00016     Q_OBJECT
00017     public:
00018         Train(QWidget* parent = Q_NULLPTR);
00019
00020     private:
00021         Ui::Train ui;
00022
00023     public slots:
00024         void home();
00025         void train();
00026     };
00027 };

```

10.91 UnitTests.cpp File Reference


Unit tests with Microsoft::VisualStudio::CppUnitTestFramework.

```

#include "pch.h"
#include "CppUnitTest.h"
#include "MarkovModel/src/model.h"

```

Include dependency graph for UnitTests.cpp:



Namespaces

- [Testing](#)
Namespace for Microsoft Native Unit Testing Classes.
- [Testing::MVP](#)
Testing Namespace for Minimal Viable Product.
- [Testing::MVP::MarkovModel](#)
Testing Namespace for MVP MarkovModel.
- [Testing::MVP::MarkovPasswords](#)
Testing namespace for MVP MarkovPasswords.

- [Testing::MarkovModel](#)
Testing namespace for [MarkovModel](#).
- [Testing::MarkovPasswords](#)
Testing namespace for [MarkovPasswords](#).

Functions

- [Testing::MVP::MarkovModel::TEST_CLASS \(Edge\)](#)
Test class for minimal viable Edge.
- [Testing::MVP::MarkovModel::TEST_CLASS \(Node\)](#)
Test class for minimal viable Node.
- [Testing::MVP::MarkovModel::TEST_CLASS \(Model\)](#)
Test class for minimal viable Model.
- [Testing::MVP::MarkovPasswords::TEST_CLASS \(ArgParser\)](#)
Test Class for Argparse class.
- [Testing::MarkovModel::TEST_CLASS \(Edge\)](#)
Test class for rest of Edge cases.
- [Testing::MarkovModel::TEST_CLASS \(Node\)](#)
Test class for rest of Node cases.
- [Testing::MarkovModel::TEST_CLASS \(Model\)](#)
Test class for rest of model cases.

10.91.1 Detailed Description

Unit tests with Microsoft::VisualStudio::CppUnitTestFramework.

Authors

Ata Hakçıl, Osman Ömer Yıldıztugay, Yunus Emre Yılmaz

Definition in file [UnitTests.cpp](#).

10.92 UnitTests.cpp

```

00001 /**
00002 * @file UnitTests.cpp
00003 * @brief Unit tests with Microsoft::VisualStudio::CppUnitTestFramework
00004 * @authors Ata Hakçıl, Osman Ömer Yıldıztugay, Yunus Emre Yılmaz
00005 */
00006
00007 #include "pch.h"
00008 #include "CppUnitTest.h"
00009 #include "MarkovModel/src/model.h"
0010
0011 using namespace Microsoft::VisualStudio::CppUnitTestFramework;
0012
0013
0014 /** @brief Namespace for Microsoft Native Unit Testing Classes
0015 */
0016 namespace Testing {
0017
0018     /** @brief Testing Namespace for Minimal Viable Product
0019     */
0020     namespace MVP {
0021         /** @brief Testing Namespace for MVP MarkovModel
0022         */
0023         namespace MarkovModel {
0024             {
0025                 /** @brief Test class for minimal viable Edge
0026                 */
0027                 TEST_CLASS(Edge)
0028                 {
0029                     public:
0030
0031                         /** @brief test default constructor
0032                         */
0033                         TEST_METHOD(default_constructor) {

```

```

00034         Markov::Edge<unsigned char*>* e = new Markov::Edge<unsigned char>;
00035         Assert::IsNull(e->LeftNode());
00036         Assert::IsNull(e->RightNode());
00037         delete e;
00038     }
00039
00040     /** @brief test linked constructor with two nodes
00041     */
00042     TEST_METHOD(linked_constructor) {
00043         Markov::Node<unsigned char*>* LeftNode = new Markov::Node<unsigned char>('l');
00044         Markov::Node<unsigned char*>* RightNode = new Markov::Node<unsigned char>('r');
00045         Markov::Edge<unsigned char*>* e = new Markov::Edge<unsigned char>(LeftNode,
00046             RightNode);
00047         Assert::IsTrue(LeftNode == e->LeftNode());
00048         Assert::IsTrue(RightNode == e->RightNode());
00049         delete LeftNode;
00050         delete RightNode;
00051         delete e;
00052     }
00053
00054     /** @brief test AdjustEdge function
00055     */
00056     TEST_METHOD(AdjustEdge) {
00057         Markov::Node<unsigned char*>* LeftNode = new Markov::Node<unsigned char>('l');
00058         Markov::Node<unsigned char*>* RightNode = new Markov::Node<unsigned char>('r');
00059         Markov::Edge<unsigned char*>* e = new Markov::Edge<unsigned char>(LeftNode,
00060             RightNode);
00061         e->AdjustEdge(15);
00062         Assert::AreEqual(15ull, e->EdgeWeight());
00063         e->AdjustEdge(15);
00064         Assert::AreEqual(30ull, e->EdgeWeight());
00065         delete LeftNode;
00066         delete RightNode;
00067         delete e;
00068     }
00069
00070     /** @brief test TraverseNode returning RightNode
00071     */
00072     TEST_METHOD(TraverseNode) {
00073         Markov::Node<unsigned char*>* LeftNode = new Markov::Node<unsigned char>('l');
00074         Markov::Node<unsigned char*>* RightNode = new Markov::Node<unsigned char>('r');
00075         Markov::Edge<unsigned char*>* e = new Markov::Edge<unsigned char>(LeftNode,
00076             RightNode);
00077         Assert::IsTrue(RightNode == e->TraverseNode());
00078         delete LeftNode;
00079         delete RightNode;
00080         delete e;
00081     }
00082
00083     /** @brief test LeftNode/RightNode setter
00084     */
00085     TEST_METHOD(set_left_and_right) {
00086         Markov::Node<unsigned char*>* LeftNode = new Markov::Node<unsigned char>('l');
00087         Markov::Node<unsigned char*>* RightNode = new Markov::Node<unsigned char>('r');
00088         Markov::Edge<unsigned char*>* e1 = new Markov::Edge<unsigned char>(LeftNode,
00089             RightNode);
00090
00091         Markov::Edge<unsigned char*>* e2 = new Markov::Edge<unsigned char>;
00092         e2->SetLeftEdge(LeftNode);
00093         e2->SetRightEdge(RightNode);
00094
00095         Assert::IsTrue(e1->LeftNode() == e2->LeftNode());
00096         Assert::IsTrue(e1->RightNode() == e2->RightNode());
00097         delete LeftNode;
00098         delete RightNode;
00099         delete e1;
00100         delete e2;
00101     }
00102
00103     /** @brief test negative adjustments
00104     */
00105     TEST_METHOD(negative_adjust) {
00106         Markov::Node<unsigned char*>* LeftNode = new Markov::Node<unsigned char>('l');
00107         Markov::Node<unsigned char*>* RightNode = new Markov::Node<unsigned char>('r');
00108         Markov::Edge<unsigned char*>* e = new Markov::Edge<unsigned char>(LeftNode,
00109             RightNode);
00110         e->AdjustEdge(15);
00111         Assert::AreEqual(15ull, e->EdgeWeight());
00112         e->AdjustEdge(-15);
00113         Assert::AreEqual(0ull, e->EdgeWeight());
00114         delete LeftNode;
00115         delete RightNode;
00116         delete e;
00117     };
00118
00119     /** @brief Test class for minimal viable Node

```

```

00116      */
00117  TEST_CLASS(Node)
00118  {
00119  public:
00120
00121  /** @brief test default constructor
00122  */
00123  TEST_METHOD(default_constructor) {
00124      Markov::Node<unsigned char>* n = new Markov::Node<unsigned char>();
00125      Assert::AreEqual((unsigned char)0, n->nodeValue());
00126      delete n;
00127  }
00128
00129  /** @brief test custom constructor with unsigned char
00130  */
00131  TEST_METHOD(uchar_constructor) {
00132      Markov::Node<unsigned char>* n = NULL;
00133      unsigned char test_cases[] = { 'c', 0x00, 0xff, -32 };
00134      for (unsigned char tcase : test_cases) {
00135          n = new Markov::Node<unsigned char>(tcase);
00136          Assert::AreEqual(tcase, n->nodeValue());
00137          delete n;
00138      }
00139  }
00140
00141  /** @brief test link function
00142  */
00143  TEST_METHOD(link_left) {
00144      Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00145      Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00146
00147      Markov::Edge<unsigned char>* e = LeftNode->Link(RightNode);
00148      delete LeftNode;
00149      delete RightNode;
00150      delete e;
00151  }
00152
00153  /** @brief test link function
00154  */
00155  TEST_METHOD(link_right) {
00156      Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00157      Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00158
00159      Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(NULL, RightNode);
00160      LeftNode->Link(e);
00161      Assert::IsTrue(LeftNode == e->LeftNode());
00162      Assert::IsTrue(RightNode == e->RightNode());
00163      delete LeftNode;
00164      delete RightNode;
00165      delete e;
00166  }
00167
00168  /** @brief test RandomNext with low values
00169  */
00170  TEST_METHOD(rand_next_low) {
00171      Markov::Random::Marsaglia MarsagliaRandomEngine;
00172      Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>'a';
00173      Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>'b';
00174      Markov::Edge<unsigned char>* e = src->Link(target1);
00175      e->AdjustEdge(15);
00176      Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00177      Assert::IsTrue(res == target1);
00178      delete src;
00179      delete target1;
00180      delete e;
00181  }
00182
00183
00184  /** @brief test RandomNext with 32 bit high values
00185  */
00186  TEST_METHOD(rand_next_u32) {
00187      Markov::Random::Marsaglia MarsagliaRandomEngine;
00188      Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>'a';
00189      Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>'b';
00190      Markov::Edge<unsigned char>* e = src->Link(target1);
00191      e->AdjustEdge(1 << 31);
00192      Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00193      Assert::IsTrue(res == target1);
00194      delete src;
00195      delete target1;
00196      delete e;
00197  }
00198
00199
00200  /** @brief random next on a node with no follow-ups
00201  */
00202  TEST_METHOD(rand_next_choice_1) {

```

```

00203     Markov::Random::Marsaglia MarsagliaRandomEngine;
00204     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00205     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00206     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00207     Markov::Edge<unsigned char>* e1 = src->Link(target1);
00208     Markov::Edge<unsigned char>* e2 = src->Link(target2);
00209     e1->AdjustEdge(1);
00210     e2->AdjustEdge((unsigned long)(ull << 31));
00211     Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00212     Assert::IsNotNull(res);
00213     Assert::IsTrue(res == target2);
00214     delete src;
00215     delete target1;
00216     delete e1;
00217     delete e2;
00218 }
00219
00220 /** @brief random next on a node with no follow-ups
00221 */
00222 TEST_METHOD(rand_next_choice_2) {
00223     Markov::Random::Marsaglia MarsagliaRandomEngine;
00224     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00225     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00226     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00227     Markov::Edge<unsigned char>* e1 = src->Link(target1);
00228     Markov::Edge<unsigned char>* e2 = src->Link(target2);
00229     e2->AdjustEdge(1);
00230     e1->AdjustEdge((unsigned long)(ull << 31));
00231     Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00232     Assert::IsNotNull(res);
00233     Assert::IsTrue(res == target1);
00234     delete src;
00235     delete target1;
00236     delete e1;
00237     delete e2;
00238 }
00239
00240
00241 /** @brief test updateEdges
00242 */
00243 TEST_METHOD(update_edges_count) {
00244
00245     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00246     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00247     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00248     Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00249     Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target2);
00250     e1->AdjustEdge(25);
00251     src->UpdateEdges(e1);
00252     e2->AdjustEdge(30);
00253     src->UpdateEdges(e2);
00254
00255     Assert::AreEqual((size_t)2, src->Edges()->size());
00256
00257     delete src;
00258     delete target1;
00259     delete e1;
00260     delete e2;
00261
00262 }
00263
00264 /** @brief test updateEdges
00265 */
00266 TEST_METHOD(update_edges_total) {
00267
00268     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00269     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00270     Markov::Edge<unsigned char>* e1 = new Markov::Edge<unsigned char>(src, target1);
00271     Markov::Edge<unsigned char>* e2 = new Markov::Edge<unsigned char>(src, target1);
00272     e1->AdjustEdge(25);
00273     src->UpdateEdges(e1);
00274     e2->AdjustEdge(30);
00275     src->UpdateEdges(e2);
00276
00277 //Assert::AreEqual(55ull, src->TotalEdgeWeights());
00278
00279     delete src;
00280     delete target1;
00281     delete e1;
00282     delete e2;
00283
00284
00285
00286 /** @brief test FindVertice
00287 */
00288 TEST_METHOD(find_vertice) {
00289

```

```

00290     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00291     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00292     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00293     Markov::Edge<unsigned char>* res = NULL;
00294     src->Link(target1);
00295     src->Link(target2);
00296
00297
00298     res = src->FindEdge('b');
00299     Assert::IsNotNull(res);
00300     Assert::AreEqual((unsigned char)'b', res->TraverseNode()->nodeValue());
00301     res = src->FindEdge('c');
00302     Assert::IsNotNull(res);
00303     Assert::AreEqual((unsigned char)'c', res->TraverseNode()->nodeValue());
00304
00305     delete src;
00306     delete target1;
00307     delete target2;
00308
00309
00310 }
00311
00312
00313 /** @brief test FindVertice
00314 */
00315 TEST_METHOD(find_vertice_without_any) {
00316
00317     auto _invalid_next = [] {
00318         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00319         Markov::Edge<unsigned char>* res = NULL;
00320
00321         res = src->FindEdge('b');
00322         Assert::IsNull(res);
00323
00324         delete src;
00325     };
00326
00327     //Assert::ExpectException<std::logic_error>(_invalid_next);
00328 }
00329
00330
00331 /** @brief test FindVertice
00332 */
00333 TEST_METHOD(find_vertice_nonexistent) {
00334
00335     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00336     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00337     Markov::Node<unsigned char>* target2 = new Markov::Node<unsigned char>('c');
00338     Markov::Edge<unsigned char>* res = NULL;
00339     src->Link(target1);
00340     src->Link(target2);
00341
00342     res = src->FindEdge('D');
00343     Assert::IsNull(res);
00344
00345     delete src;
00346     delete target1;
00347     delete target2;
00348 }
00349 }
00350
00351
00352 /** @brief Test class for minimal viable Model
00353 */
00354 TEST_CLASS(Model)
00355 {
00356     public:
00357         /** @brief test model constructor for starter node
00358 */
00359         TEST_METHOD(model_constructor) {
00360             Markov::Model<unsigned char> m;
00361             Assert::AreEqual((unsigned char)'\\0', m.StarterNode()->nodeValue());
00362
00363         /** @brief test import
00364 */
00365         TEST_METHOD(import_filename) {
00366             Markov::Model<unsigned char> m;
00367             Assert::IsTrue(m.Import("../MarkovPasswords/Models/2gram.mdl"));
00368         }
00369
00370         /** @brief test export
00371 */
00372         TEST_METHOD(export_filename) {
00373             Markov::Model<unsigned char> m;
00374             Assert::IsTrue(m.Export("../MarkovPasswords/Models/testcase.mdl"));
00375         }
00376

```

```

00377         /** @brief test random walk
00378         */
00379         TEST_METHOD(random_walk) {
00380             unsigned char* res = new unsigned char[12 + 5];
00381             Markov::Random::Marsaglia MarsagliaRandomEngine;
00382             Markov::Model<unsigned char> m;
00383             Assert::IsTrue(m.Import("../Models/finished2.mdl"));
00384             Assert::IsNotNull(m.RandomWalk(&MarsagliaRandomEngine, 1, 12, res));
00385         }
00386     };
00387 }
00388
00389 /** @brief Testing namespace for MVP MarkovPasswords
00390 */
00391 namespace MarkovPasswords
00392 {
00393     /** @brief Test Class for Argparse class
00394     */
00395     TEST_CLASS(ArgParser)
00396     {
00397         public:
00398             /** @brief test basic generate
00399             */
00400             TEST_METHOD(generate_basic) {
00401                 int argc = 8;
00402                 char *argv[] = {"markov.exe", "generate", "-if", "model.mdl", "-of",
00403 "passwords.txt", "-n", "100"};
00404
00405                 /*ProgramOptions *p = Argparse::parse(argc, argv);
00406                 Assert::IsNotNull(p);
00407
00408                 Assert::AreEqual(p->bImport, true);
00409                 Assert::AreEqual(p->bExport, false);
00410                 Assert::AreEqual(p->importname, "model.mdl");
00411                 Assert::AreEqual(p->outputfilename, "passwords.txt");
00412                 Assert::AreEqual(p->generateN, 100); */
00413             }
00414
00415             /** @brief test basic generate reordered params
00416             */
00417             TEST_METHOD(generate_basic_reordered) {
00418                 int argc = 8;
00419                 char *argv[] = { "markov.exe", "generate", "-n", "100", "-if", "model.mdl", "-of",
00420 "passwords.txt" };
00421
00422                 /*ProgramOptions* p = Argparse::parse(argc, argv);
00423                 Assert::IsNotNull(p);
00424
00425                 Assert::AreEqual(p->bImport, true);
00426                 Assert::AreEqual(p->bExport, false);
00427                 Assert::AreEqual(p->importname, "model.mdl");
00428                 Assert::AreEqual(p->outputfilename, "passwords.txt");
00429                 Assert::AreEqual(p->generateN, 100); */
00430
00431             /** @brief test basic generate param longnames
00432             */
00433             TEST_METHOD(generate_basic_longname) {
00434                 int argc = 8;
00435                 char *argv[] = { "markov.exe", "generate", "-n", "100", "--inputfilename",
00436 "model.mdl", "--outputfilename", "passwords.txt" };
00437
00438                 /*ProgramOptions* p = Argparse::parse(argc, argv);
00439                 Assert::IsNotNull(p);
00440
00441                 Assert::AreEqual(p->bImport, true);
00442                 Assert::AreEqual(p->bExport, false);
00443                 Assert::AreEqual(p->importname, "model.mdl");
00444                 Assert::AreEqual(p->outputfilename, "passwords.txt");
00445                 Assert::AreEqual(p->generateN, 100); */
00446
00447             /** @brief test basic generate
00448             */
00449             TEST_METHOD(generate_fail_badmethod) {
00450                 int argc = 8;
00451                 char *argv[] = { "markov.exe", "junk", "-n", "100", "--inputfilename",
00452 "model.mdl", "--outputfilename", "passwords.txt" };
00453
00454                 /*ProgramOptions* p = Argparse::parse(argc, argv);
00455                 Assert::IsNull(p); */
00456
00457             /** @brief test basic train
00458             */
00459             TEST_METHOD(train_basic) {

```

```

00460         int argc = 4;
00461         char *argv[] = { "markov.exe", "train", "-ef", "model.mdl" };
00462
00463         /*ProgramOptions* p = Argparse::parse(argc, argv);
00464         Assert::IsNotNull(p);
00465
00466         Assert::AreEqual(p->bImport, false);
00467         Assert::AreEqual(p->bExport, true);
00468         Assert::AreEqual(p->exportname, "model.mdl"); */
00469
00470     }
00471
00472     /** @brief test basic generate
00473     */
00474     TEST_METHOD(train_basic_longname) {
00475         int argc = 4;
00476         char *argv[] = { "markov.exe", "train", "--exportfilename", "model.mdl" };
00477
00478         /*ProgramOptions* p = Argparse::parse(argc, argv);
00479         Assert::IsNotNull(p);
00480
00481         Assert::AreEqual(p->bImport, false);
00482         Assert::AreEqual(p->bExport, true);
00483         Assert::AreEqual(p->exportname, "model.mdl"); */
00484     }
00485
00486
00487
00488     };
00489 }
00490
00491 /**
00492 ** @brief Testing namespace for MarkovModel
00493 */
00494 namespace MarkovModel {
00495
00496     /** @brief Test class for rest of Edge cases
00497     */
00498     TEST_CLASS(Edge)
00499     {
00500         public:
00501             /** @brief send exception on integer underflow
00502             */
00503             TEST_METHOD(except_integer_underflow) {
00504                 auto _underflow_adjust = [] {
00505                     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00506                     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00507                     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00508
00509                     RightNode);
00510                     e->AdjustEdge(15);
00511                     e->AdjustEdge(-30);
00512                     delete LeftNode;
00513                     delete RightNode;
00514                     delete e;
00515                 };
00516                 Assert::ExpectException<std::underflow_error>(_underflow_adjust);
00517             }
00518
00519             /** @brief test integer overflows
00520             */
00521             TEST_METHOD(except_integer_overflow) {
00522                 auto _overflow_adjust = [] {
00523                     Markov::Node<unsigned char>* LeftNode = new Markov::Node<unsigned char>('l');
00524                     Markov::Node<unsigned char>* RightNode = new Markov::Node<unsigned char>('r');
00525                     Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(LeftNode,
00526
00527                     RightNode);
00528                     e->AdjustEdge(~0ull);
00529                     e->AdjustEdge(1);
00530                     delete LeftNode;
00531                     delete RightNode;
00532                     delete e;
00533                 };
00534                 Assert::ExpectException<std::underflow_error>(_overflow_adjust);
00535             };
00536
00537             /** @brief Test class for rest of Node cases
00538             */
00539             TEST_CLASS(Node)
00540             {
00541                 public:
00542                     /** @brief test RandomNext with 64 bit high values
00543                     */
00544                     TEST_METHOD(rand_next_u64) {

```

```

00545     Markov::Random::Marsaglia MarsagliaRandomEngine;
00546     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00547     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00548     Markov::Edge<unsigned char>* e = src->Link(target1);
00549     e->AdjustEdge((unsigned long)(ull << 63));
00550     Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00551     Assert::IsTrue(res == target1);
00552     delete src;
00553     delete target1;
00554     delete e;
00555
00556 }
00557
00558 /** @brief test RandomNext with 64 bit high values
00559 */
00560 TEST_METHOD(rand_next_u64_max) {
00561     Markov::Random::Marsaglia MarsagliaRandomEngine;
00562     Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00563     Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00564     Markov::Edge<unsigned char>* e = src->Link(target1);
00565     e->AdjustEdge((0xffffffff));
00566     Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00567     Assert::IsTrue(res == target1);
00568     delete src;
00569     delete target1;
00570     delete e;
00571
00572 }
00573
00574 /** @brief randomNext when no edges are present
00575 */
00576 TEST_METHOD(uninitialized_rand_next) {
00577
00578     auto _invalid_next = [] {
00579         Markov::Random::Marsaglia MarsagliaRandomEngine;
00580         Markov::Node<unsigned char>* src = new Markov::Node<unsigned char>('a');
00581         Markov::Node<unsigned char>* target1 = new Markov::Node<unsigned char>('b');
00582         Markov::Edge<unsigned char>* e = new Markov::Edge<unsigned char>(src, target1);
00583         Markov::Node<unsigned char>* res = src->RandomNext(&MarsagliaRandomEngine);
00584
00585         delete src;
00586         delete target1;
00587         delete e;
00588     };
00589
00590     Assert::ExpectException<std::logic_error>(_invalid_next);
00591 }
00592
00593
00594 };
00595
00596 /** @brief Test class for rest of model cases
00597 */
00598 TEST_CLASS(Model)
00599 {
00600     public:
00601     TEST_METHOD(functional_random_walk) {
00602         unsigned char* res2 = new unsigned char[12 + 5];
00603         Markov::Random::Marsaglia MarsagliaRandomEngine;
00604         Markov::Model<unsigned char> m;
00605         Markov::Node<unsigned char>* starter = m.StarterNode();
00606         Markov::Node<unsigned char>* a = new Markov::Node<unsigned char>('a');
00607         Markov::Node<unsigned char>* b = new Markov::Node<unsigned char>('b');
00608         Markov::Node<unsigned char>* c = new Markov::Node<unsigned char>('c');
00609         Markov::Node<unsigned char>* end = new Markov::Node<unsigned char>(0xff);
00610         starter->Link(a)->AdjustEdge(1);
00611         a->Link(b)->AdjustEdge(1);
00612         b->Link(c)->AdjustEdge(1);
00613         c->Link(end)->AdjustEdge(1);
00614
00615         char* res = (char*)m.RandomWalk(&MarsagliaRandomEngine, 1, 12, res2);
00616         Assert::IsFalse(strcmp(res, "abc"));
00617     }
00618     TEST_METHOD(functionoal_random_walk_without_any) {
00619         Markov::Model<unsigned char> m;
00620         Markov::Node<unsigned char>* starter = m.StarterNode();
00621         Markov::Node<unsigned char>* a = new Markov::Node<unsigned char>('a');
00622         Markov::Node<unsigned char>* b = new Markov::Node<unsigned char>('b');
00623         Markov::Node<unsigned char>* c = new Markov::Node<unsigned char>('c');
00624         Markov::Node<unsigned char>* end = new Markov::Node<unsigned char>(0xff);
00625         Markov::Edge<unsigned char>* res = NULL;
00626         starter->Link(a)->AdjustEdge(1);
00627         a->Link(b)->AdjustEdge(1);
00628         b->Link(c)->AdjustEdge(1);
00629         c->Link(end)->AdjustEdge(1);
00630
00631         res = starter->FindEdge('D');
00632     }

```

```
00632             Assert::IsNull(res);
00633
00634         }
00635     } ;
00636
00637 }
00638
00639 /** @brief Testing namespace for MarkovPasswords
00640  */
00641 namespace MarkovPasswords {
00642
00643 } ;
00644
00645 }
```

Index

_left
 Markov::Edge< NodeStorageType >, 119
_right
 Markov::Edge< NodeStorageType >, 120
_value
 Markov::Node< storageType >, 208
_weight
 Markov::Edge< NodeStorageType >, 120

about
 Markov::GUI::about, 57
 Markov::GUI::CLI, 65
 Markov::GUI::menu, 161

about.cpp, 223

about.h, 223, 225

action
 markopy, 32

AdjustEdge
 Markov::API::CUDA::CUDAModelMatrix, 77
 Markov::API::MarkovPasswords, 128
 Markov::API::ModelMatrix, 179
 Markov::Edge< NodeStorageType >, 117
 Markov::Model< NodeStorageType >, 168

AllocVRAMOutputBuffer
 Markov::API::CUDA::CUDAModelMatrix, 78

alphabet
 model_2gram, 40
 random-model, 41

alternatingKernels
 Markov::API::CUDA::CUDAModelMatrix, 106

Argparse
 Markov::API::CLI::Argparse, 59

argparse.cpp, 225

argparse.h, 226, 228
 BOOST_ALL_STATIC_LIB, 227
 BOOST_PROGRAM_OPTIONS_STATIC_LIB, 228

args
 markopy, 32

benchmarkSelected
 Markov::GUI::MarkovPasswordsGUI, 143

bExport
 Markov::API::CLI::_programOptions, 54

bFailure
 Markov::API::CLI::_programOptions, 54

blImport
 Markov::API::CLI::_programOptions, 54

BLACK
 Markov::API::CLI::Terminal, 213

BLUE
 Markov::API::CLI::Terminal, 213

BOOST_ALL_STATIC_LIB
 argparse.h, 227
 markopy.cpp, 265

BOOST_PROGRAM_OPTIONS_STATIC_LIB
 argparse.h, 228

BOOST_PYTHON_MODULE
 Markov::Markopy, 39

BOOST_PYTHON_STATIC_LIB
 markopy.cpp, 265

BROWN
 Markov::API::CLI::Terminal, 213

Buff
 Markov::API::CUDA::CUDAModelMatrix, 78
 Markov::API::MarkovPasswords, 129
 Markov::API::ModelMatrix, 180

CLI
 Markov::GUI::CLI, 64

CLI.cpp, 231

CLI.h, 232, 233

cli_generate
 markopy, 29

cli_init
 markopy, 30

cli_train
 markopy, 31

color
 Markov::API::CLI::Terminal, 213

colormap
 Markov::API::CLI::Terminal, 213

ConstructMatrix
 Markov::API::CUDA::CUDAModelMatrix, 80
 Markov::API::ModelMatrix, 181

cudaBlocks
 Markov::API::CUDA::CUDAModelMatrix, 106

CudaCheckNotifyErr
 Markov::API::CUDA::CUDADeviceController, 68
 Markov::API::CUDA::CUDAModelMatrix, 81
 Markov::API::CUDA::Random::Marsaglia, 152

cudaDeviceController.cu, 233, 234

cudaDeviceController.h, 235, 236

cudaGridSize
 Markov::API::CUDA::CUDAModelMatrix, 106

CudaMalloc2DToFlat
 Markov::API::CUDA::CUDADeviceController, 69
 Markov::API::CUDA::CUDAModelMatrix, 82
 Markov::API::CUDA::Random::Marsaglia, 153

CudaMemcpy2DToFlat
 Markov::API::CUDA::CUDADeviceController, 70
 Markov::API::CUDA::CUDAModelMatrix, 83
 Markov::API::CUDA::Random::Marsaglia, 154

cudaMemPerGrid
 Markov::API::CUDA::CUDAModelMatrix, 106

CudaMigrate2DFlat
 Markov::API::CUDA::CUDADeviceController, 71
 Markov::API::CUDA::CUDAModelMatrix, 84
 Markov::API::CUDA::Random::Marsaglia, 155

cudaModelMatrix.cu, 238, 239
 cudaModelMatrix.h, 242, 244
 cudaPerKernelAllocationSize
 Markov::API::CUDA::CUDAModelMatrix, 106
 cudarandom.h, 246, 248
 cudastreams
 Markov::API::CUDA::CUDAModelMatrix, 106
 cudaThreads
 Markov::API::CUDA::CUDAModelMatrix, 106
 CYAN
 Markov::API::CLI::Terminal, 213

DARKGRAY
 Markov::API::CLI::Terminal, 213

datasetFile
 Markov::API::CUDA::CUDAModelMatrix, 107
 Markov::API::MarkovPasswords, 140
 Markov::API::ModelMatrix, 199

datasetname
 Markov::API::CLI::_programOptions, 54

DeallocateMatrix
 Markov::API::CUDA::CUDAModelMatrix, 85
 Markov::API::ModelMatrix, 183

default
 markopy, 32

device_edgeMatrix
 Markov::API::CUDA::CUDAModelMatrix, 107

device_matrixIndex
 Markov::API::CUDA::CUDAModelMatrix, 107

device_outputBuffer
 Markov::API::CUDA::CUDAModelMatrix, 107

device_seeds
 Markov::API::CUDA::CUDAModelMatrix, 107

device_totalEdgeWeights
 Markov::API::CUDA::CUDAModelMatrix, 107

device_valueMatrix
 Markov::API::CUDA::CUDAModelMatrix, 107

devrandom
 Markov::API::CUDA::Random, 37

distribution
 Markov::API::CUDA::Random::Marsaglia, 156
 Markov::Random::DefaultRandomEngine, 113
 Markov::Random::Marsaglia, 147
 Markov::Random::Mersenne, 165

dllmain.cpp, 248, 249

DumpJSON
 Markov::API::CUDA::CUDAModelMatrix, 86
 Markov::API::ModelMatrix, 184

Edge
 Markov::Edge< NodeStorageType >, 116

edge.h, 250, 251

edgeMatrix
 Markov::API::CUDA::CUDAModelMatrix, 107
 Markov::API::ModelMatrix, 200

Edges
 Markov::API::CUDA::CUDAModelMatrix, 87
 Markov::API::MarkovPasswords, 130
 Markov::API::ModelMatrix, 185

Markov::Model< NodeStorageType >, 169
 Markov::Node< storageType >, 204

edges
 Markov::API::CUDA::CUDAModelMatrix, 108
 Markov::API::MarkovPasswords, 140
 Markov::API::ModelMatrix, 200
 Markov::Model< NodeStorageType >, 175
 Markov::Node< storageType >, 208

edgesV
 Markov::Node< storageType >, 208

EdgeWeight
 Markov::Edge< NodeStorageType >, 117

endl
 Markov::API::CLI::Terminal, 214

Export
 Markov::API::CUDA::CUDAModelMatrix, 87
 Markov::API::MarkovPasswords, 130, 131
 Markov::API::ModelMatrix, 185
 Markov::Model< NodeStorageType >, 169, 170

exportname
 Markov::API::CLI::_programOptions, 55

f
 model_2gram, 40
 random-model, 41

FastRandomWalk
 Markov::API::CUDA::CUDAModelMatrix, 88–90
 Markov::API::ModelMatrix, 186, 187

FastRandomWalkCUDAKernel
 Markov::API::CUDA, 35

FastRandomWalkPartition
 Markov::API::CUDA::CUDAModelMatrix, 91
 Markov::API::ModelMatrix, 188

FastRandomWalkThread
 Markov::API::CUDA::CUDAModelMatrix, 92
 Markov::API::ModelMatrix, 189

FindEdge
 Markov::Node< storageType >, 204

flatEdgeMatrix
 Markov::API::CUDA::CUDAModelMatrix, 108

FlattenMatrix
 Markov::API::CUDA::CUDAModelMatrix, 94

flatValueMatrix
 Markov::API::CUDA::CUDAModelMatrix, 108

framework.h, 253, 254
 WIN32_LEAN_AND_MEAN, 253

GatherAsyncKernelOutput
 Markov::API::CUDA::CUDAModelMatrix, 94

Generate
 Markov::API::CUDA::CUDAModelMatrix, 94
 Markov::API::MarkovPasswords, 131
 Markov::API::ModelMatrix, 190
 Markov::GUI::Generate, 121

Generate.cpp, 254

Generate.h, 256, 257

generateN
 Markov::API::CLI::_programOptions, 55

GenerateThread

Markov::API::CUDA::CUDAModelMatrix, 96
Markov::API::MarkovPasswords, 132
Markov::API::ModelMatrix, 192
generation
 Markov::GUI::Generate, 122
generator
 Markov::API::CUDA::Random::Marsaglia, 156
 Markov::Random::DefaultRandomEngine, 113
 Markov::Random::Marsaglia, 148
 Markov::Random::Mersenne, 165
getProgramOptions
 Markov::API::CLI::Argparse, 61
GREEN
 Markov::API::CLI::Terminal, 213

help
 markopy, 32
 Markov::API::CLI::Argparse, 61
home
 Markov::GUI::Generate, 123
 Markov::GUI::MarkovPasswordsGUI, 143
 Markov::GUI::Train, 220

Import
 Markov::API::CUDA::CUDAModelMatrix, 97, 98
 Markov::API::MarkovPasswords, 133, 134
 Markov::API::ModelMatrix, 193, 194
 Markov::Model< NodeStorageType >, 171
importname
 Markov::API::CLI::__programOptions, 55
intHandler
 markovPasswords.cpp, 269
iterationsPerKernelThread
 Markov::API::CUDA::CUDAModelMatrix, 108

keepRunning
 markovPasswords.cpp, 270

LaunchAsyncKernel
 Markov::API::CUDA::CUDAModelMatrix, 99
LeftNode
 Markov::Edge< NodeStorageType >, 118
LIGHTGRAY
 Markov::API::CLI::Terminal, 213
Link
 Markov::Node< storageType >, 205
ListCudaDevices
 Markov::API::CUDA::CUDADeviceController, 72
 Markov::API::CUDA::CUDAModelMatrix, 99
 Markov::API::CUDA::Random::Marsaglia, 157
listfile
 Markov::API::Concurrency::ThreadSharedListHandler, 217

MAGENTA
 Markov::API::CLI::Terminal, 213
main
 main.cu, 262
 MarkovAPICLI/src/main.cpp, 258
 MarkovPasswordsGUI/src/main.cpp, 261
 main.cpp, 258–261
 main.cu, 262, 263
 main, 262
 markopy, 29
 action, 32
 args, 32
 cli_generate, 29
 cli_init, 30
 cli_train, 31
 default, 32
 help, 32
 parser, 33
 markopy.cpp, 263, 265
 BOOST_ALL_STATIC_LIB, 265
 BOOST_PYTHON_STATIC_LIB, 265
 markopy.py, 266
 Markov, 33
 Markov::API, 33
 Markov::API::CLI, 34
 operator<<, 34
 ProgramOptions, 34
 Markov::API::CLI::__programOptions, 53
 bExport, 54
 bFailure, 54
 bImport, 54
 datasetname, 54
 exportname, 55
 generateN, 55
 importname, 55
 outputfilename, 55
 seperator, 55
 wordlistname, 55
 Markov::API::CLI::Argparse, 57
 Argparse, 59
 getProgramOptions, 61
 help, 61
 parse, 61
 po, 63
 setProgramOptions, 62
 Markov::API::CLI::Terminal, 211
 BLACK, 213
 BLUE, 213
 BROWN, 213
 color, 213
 colormap, 213
 CYAN, 213
 DARKGRAY, 213
 endl, 214
 GREEN, 213
 LIGHTGRAY, 213
 MAGENTA, 213
 RED, 213
 RESET, 213
 Terminal, 213
 WHITE, 213
 YELLOW, 213
 Markov::API::Concurrency, 35

Markov::API::Concurrency::ThreadSharedListHandler,
 214
 listfile, 217
 mlock, 217
 next, 217
 ThreadSharedListHandler, 216
 Markov::API::CUDA, 35
 FastRandomWalkCUDAKernel, 35
 strchr, 37
 Markov::API::CUDA::CUDADeviceController, 66
 CudaCheckNotifyErr, 68
 CudaMalloc2DToFlat, 69
 CudaMemcpy2DToFlat, 70
 CudaMigrate2DFlat, 71
 ListCudaDevices, 72
 Markov::API::CUDA::CUDAModelMatrix, 73
 AdjustEdge, 77
 AllocVRAMOutputBuffer, 78
 alternatingKernels, 106
 Buff, 78
 ConstructMatrix, 80
 cudaBlocks, 106
 CudaCheckNotifyErr, 81
 cudaGridSize, 106
 CudaMalloc2DToFlat, 82
 CudaMemcpy2DToFlat, 83
 cudaMemPerGrid, 106
 CudaMigrate2DFlat, 84
 cudaPerKernelAllocationSize, 106
 cudastreams, 106
 cudaThreads, 106
 datasetFile, 107
 DeallocateMatrix, 85
 device_edgeMatrix, 107
 device_matrixIndex, 107
 device_outputBuffer, 107
 device_seeds, 107
 device_totalEdgeWeights, 107
 device_valueMatrix, 107
 DumpJSON, 86
 edgeMatrix, 107
 Edges, 87
 edges, 108
 Export, 87
 FastRandomWalk, 88–90
 FastRandomWalkPartition, 91
 FastRandomWalkThread, 92
 flatEdgeMatrix, 108
 FlattenMatrix, 94
 flatValueMatrix, 108
 GatherAsyncKernelOutput, 94
 Generate, 94
 GenerateThread, 96
 Import, 97, 98
 iterationsPerKernelThread, 108
 LaunchAsyncKernel, 99
 ListCudaDevices, 99
 matrixIndex, 108
 matrixSize, 108
 MigrateMatrix, 99
 modelSavefile, 108
 Nodes, 100
 nodes, 108
 numberOfPartitions, 109
 OpenDatasetFile, 100
 OptimizeEdgeOrder, 101
 outputBuffer, 109
 outputFile, 109
 prepKernelMemoryChannel, 101
 RandomWalk, 102
 ready, 109
 Save, 103
 StarterNode, 103
 starterNode, 109
 totalEdgeWeights, 109
 totalOutputPerKernel, 109
 totalOutputPerSync, 110
 Train, 104
 TrainThread, 105
 valueMatrix, 110
 Markov::API::CUDA::Random, 37
 devrandom, 37
 Markov::API::CUDA::Random::Marsaglia, 150
 CudaCheckNotifyErr, 152
 CudaMalloc2DToFlat, 153
 CudaMemcpy2DToFlat, 154
 CudaMigrate2DFlat, 155
 distribution, 156
 generator, 156
 ListCudaDevices, 157
 MigrateToVRAM, 157
 random, 158
 rd, 159
 x, 159
 y, 159
 z, 159
 Markov::API::MarkovPasswords, 124
 AdjustEdge, 128
 Buff, 129
 datasetFile, 140
 Edges, 130
 edges, 140
 Export, 130, 131
 Generate, 131
 GenerateThread, 132
 Import, 133, 134
 MarkovPasswords, 128
 modelSavefile, 140
 Nodes, 135
 nodes, 140
 OpenDatasetFile, 135
 OptimizeEdgeOrder, 135
 outputFile, 140
 RandomWalk, 136
 Save, 137
 StarterNode, 137

starterNode, 140
Train, 137
TrainThread, 139
Markov::API::ModelMatrix, 175
 AdjustEdge, 179
 Buff, 180
 ConstructMatrix, 181
 datasetFile, 199
 DeallocateMatrix, 183
 DumpJSON, 184
 edgeMatrix, 200
 Edges, 185
 edges, 200
 Export, 185
 FastRandomWalk, 186, 187
 FastRandomWalkPartition, 188
 FastRandomWalkThread, 189
 Generate, 190
 GenerateThread, 192
 Import, 193, 194
 matrixIndex, 200
 matrixSize, 200
 ModelMatrix, 179
 modelSavefile, 200
 Nodes, 195
 nodes, 200
 OpenDatasetFile, 195
 OptimizeEdgeOrder, 195
 outputFile, 200
 RandomWalk, 196
 ready, 200
 Save, 197
 StarterNode, 197
 starterNode, 201
 totalEdgeWeights, 201
 Train, 198
 TrainThread, 199
 valueMatrix, 201
Markov::Edge< NodeStorageType >, 115
 _left, 119
 _right, 120
 _weight, 120
 AdjustEdge, 117
 Edge, 116
 EdgeWeight, 117
 LeftNode, 118
 RightNode, 118
 SetLeftEdge, 118
 SetRightEdge, 119
 TraverseNode, 119
Markov::GUI, 38
Markov::GUI::about, 56
 about, 57
 ui, 57
Markov::GUI::CLI, 63
 about, 65
 CLI, 64
 start, 65
 statistics, 66
 ui, 66
Markov::GUI::Generate, 120
 Generate, 121
 generation, 122
 home, 123
 train, 123
 ui, 124
 vis, 123
Markov::GUI::MarkovPasswordsGUI, 141
 benchmarkSelected, 143
 home, 143
 MarkovPasswordsGUI, 142
 model, 143
 pass, 143
 ui, 143
Markov::GUI::menu, 160
 about, 161
 menu, 161
 ui, 162
 visualization, 161
Markov::GUI::Train, 218
 home, 220
 Train, 219
 train, 220
 ui, 221
Markov::Markopy, 38
 BOOST_PYTHON_MODULE, 39
Markov::Model< NodeStorageType >, 167
 AdjustEdge, 168
 Edges, 169
 edges, 175
 Export, 169, 170
 Import, 171
 Model, 168
 Nodes, 172
 nodes, 175
 OptimizeEdgeOrder, 173
 RandomWalk, 173
 StarterNode, 174
 starterNode, 175
Markov::Node< storageType >, 201
 _value, 208
 Edges, 204
 edges, 208
 edgesV, 208
 FindEdge, 204
 Link, 205
 Node, 203
 nodeValue, 206
 RandomNext, 206
 total_edge_weights, 208
 TotalEdgeWeights, 207
 UpdateEdges, 207
 UpdateTotalVertexWeight, 208
Markov::Random, 39
Markov::Random::DefaultRandomEngine, 110
 distribution, 113

generator, 113
 random, 114
 rd, 114
Markov::Random::Marsaglia, 144
 distribution, 147
 generator, 148
 Marsaglia, 147
 random, 148
 rd, 149
 x, 149
 y, 149
 z, 149
Markov::Random::Mersenne, 162
 distribution, 165
 generator, 165
 random, 166
 rd, 166
Markov::Random::RandomEngine, 209
 random, 211
MarkovAPICLI/src/main.cpp
 main, 258
MarkovPasswords
 Markov::API::MarkovPasswords, 128
markovPasswords.cpp, 268, 270
 intHandler, 269
 keepRunning, 270
markovPasswords.h, 272, 273
MarkovPasswordsGUI
 Markov::GUI::MarkovPasswordsGUI, 142
MarkovPasswordsGUI.cpp, 275
MarkovPasswordsGUI.h, 276, 277
MarkovPasswordsGUI/src/main.cpp
 main, 261
Marsaglia
 Markov::Random::Marsaglia, 147
matrixIndex
 Markov::API::CUDA::CUDAModelMatrix, 108
 Markov::API::ModelMatrix, 200
matrixSize
 Markov::API::CUDA::CUDAModelMatrix, 108
 Markov::API::ModelMatrix, 200
menu
 Markov::GUI::menu, 161
menu.cpp, 278
menu.h, 279, 280
MigrateMatrix
 Markov::API::CUDA::CUDAModelMatrix, 99
MigrateToVRAM
 Markov::API::CUDA::Random::Marsaglia, 157
mlock
 Markov::API::Concurrency::ThreadSharedListHandler, 217
Model
 Markov::Model< NodeStorageType >, 168
model
 Markov::GUI::MarkovPasswordsGUI, 143
model.h, 280, 281
model_2gram, 40
 alphabet, 40
 f, 40
model_2gram.py, 286
ModelMatrix
 Markov::API::ModelMatrix, 179
modelMatrix.cpp, 286, 287
modelMatrix.h, 290, 291
modelSavefile
 Markov::API::CUDA::CUDAModelMatrix, 108
 Markov::API::MarkovPasswords, 140
 Markov::API::ModelMatrix, 200
next
 Markov::API::Concurrency::ThreadSharedListHandler, 217
Node
 Markov::Node< storageType >, 203
node.h, 294, 295
Nodes
 Markov::API::CUDA::CUDAModelMatrix, 100
 Markov::API::MarkovPasswords, 135
 Markov::API::ModelMatrix, 195
 Markov::Model< NodeStorageType >, 172
nodes
 Markov::API::CUDA::CUDAModelMatrix, 108
 Markov::API::MarkovPasswords, 140
 Markov::API::ModelMatrix, 200
 Markov::Model< NodeStorageType >, 175
nodeValue
 Markov::Node< storageType >, 206
numberOfPartitions
 Markov::API::CUDA::CUDAModelMatrix, 109
OpenDatasetFile
 Markov::API::CUDA::CUDAModelMatrix, 100
 Markov::API::MarkovPasswords, 135
 Markov::API::ModelMatrix, 195
operator<<
 Markov::API::CLI, 34
 term.cpp, 308
OptimizeEdgeOrder
 Markov::API::CUDA::CUDAModelMatrix, 101
 Markov::API::MarkovPasswords, 135
 Markov::API::ModelMatrix, 195
 Markov::Model< NodeStorageType >, 173
outputBuffer
 Markov::API::CUDA::CUDAModelMatrix, 109
outputFile
 Markov::API::CUDA::CUDAModelMatrix, 109
 Markov::API::MarkovPasswords, 140
 Markov::API::ModelMatrix, 200
outputfilename
 Markov::CLI::__programOptions, 55
parse
 Markov::API::CLI::Argparse, 61
parser
 markopy, 33
pass

Markov::GUI::MarkovPasswordsGUI, 143
pch.cpp, 299, 300
pch.h, 300–302
po
 Markov::API::CLI::Argparse, 63
prepKernelMemoryChannel
 Markov::API::CUDA::CUDAModelMatrix, 101
ProgramOptions
 Markov::API::CLI, 34

QMainWindow, 209

random, 40
 Markov::API::CUDA::Random::Marsaglia, 158
 Markov::Random::DefaultRandomEngine, 114
 Markov::Random::Marsaglia, 148
 Markov::Random::Mersenne, 166
 Markov::Random::RandomEngine, 211
random-model, 40
 alphabet, 41
 f, 41
random-model.py, 302, 303
random.h, 303, 305
RandomNext
 Markov::Node<storageType>, 206
RandomWalk
 Markov::API::CUDA::CUDAModelMatrix, 102
 Markov::API::MarkovPasswords, 136
 Markov::API::ModelMatrix, 196
 Markov::Model<NodeStorageType>, 173
rd
 Markov::API::CUDA::Random::Marsaglia, 159
 Markov::Random::DefaultRandomEngine, 114
 Markov::Random::Marsaglia, 149
 Markov::Random::Mersenne, 166
README.md, 307
ready
 Markov::API::CUDA::CUDAModelMatrix, 109
 Markov::API::ModelMatrix, 200
RED
 Markov::API::CLI::Terminal, 213
report.md, 307
RESET
 Markov::API::CLI::Terminal, 213
RightNode
 Markov::Edge<NodeStorageType>, 118

Save
 Markov::API::CUDA::CUDAModelMatrix, 103
 Markov::API::MarkovPasswords, 137
 Markov::API::ModelMatrix, 197
seperator
 Markov::API::CLI::_programOptions, 55
SetLeftEdge
 Markov::Edge<NodeStorageType>, 118
setProgramOptions
 Markov::API::CLI::Argparse, 62
SetRightEdge
 Markov::Edge<NodeStorageType>, 119

start
 Markov::GUI::CLI, 65
StarterNode
 Markov::API::CUDA::CUDAModelMatrix, 103
 Markov::API::MarkovPasswords, 137
 Markov::API::ModelMatrix, 197
 Markov::Model<NodeStorageType>, 174
starterNode
 Markov::API::CUDA::CUDAModelMatrix, 109
 Markov::API::MarkovPasswords, 140
 Markov::API::ModelMatrix, 201
 Markov::Model<NodeStorageType>, 175
statistics
 Markov::GUI::CLI, 66
strchr
 Markov::API::CUDA, 37

term.cpp, 307, 308
 operator<<, 308
term.h, 309, 311
 TERM_FAIL, 311
 TERM_INFO, 311
 TERM_SUCC, 311
 TERM_WARN, 311
TERM_FAIL
 term.h, 311
TERM_INFO
 term.h, 311
TERM_SUCC
 term.h, 311
TERM_WARN
 term.h, 311
Terminal
 Markov::API::CLI::Terminal, 213
TEST_CLASS
 Testing::MarkovModel, 41–43
 Testing::MVP::MarkovModel, 45–47
 Testing::MVP::MarkovPasswords, 51
Testing, 41
Testing::MarkovModel, 41
 TEST_CLASS, 41–43
Testing::MarkovPasswords, 44
Testing::MVP, 45
Testing::MVP::MarkovModel, 45
 TEST_CLASS, 45–47
Testing::MVP::MarkovPasswords, 50
 TEST_CLASS, 51
ThreadSharedListHandler
 Markov::Concurrency::ThreadSharedListHandler, 216
threadSharedListHandler.cpp, 312, 313
threadSharedListHandler.h, 313, 314
total_edge_weights
 Markov::Node<storageType>, 208
TotalEdgeWeights
 Markov::Node<storageType>, 207
totalEdgeWeights
 Markov::API::CUDA::CUDAModelMatrix, 109
 Markov::API::ModelMatrix, 201

totalOutputPerKernel
 Markov::API::CUDA::CUDAModelMatrix, 109

totalOutputPerSync
 Markov::API::CUDA::CUDAModelMatrix, 110

Train
 Markov::API::CUDA::CUDAModelMatrix, 104
 Markov::API::MarkovPasswords, 137
 Markov::API::ModelMatrix, 198
 Markov::GUI::Train, 219

train
 Markov::GUI::Generate, 123
 Markov::GUI::Train, 220

Train.cpp, 316

Train.h, 317, 319

TrainThread
 Markov::API::CUDA::CUDAModelMatrix, 105
 Markov::API::MarkovPasswords, 139
 Markov::API::ModelMatrix, 199

TraverseNode
 Markov::Edge< NodeStorageType >, 119

ui
 Markov::GUI::about, 57
 Markov::GUI::CLI, 66
 Markov::GUI::Generate, 124
 Markov::GUI::MarkovPasswordsGUI, 143
 Markov::GUI::menu, 162
 Markov::GUI::Train, 221

UnitTests.cpp, 319, 320

UpdateEdges
 Markov::Node< storageType >, 207

UpdateTotalVerticeWeight
 Markov::Node< storageType >, 208

valueMatrix
 Markov::API::CUDA::CUDAModelMatrix, 110
 Markov::API::ModelMatrix, 201

vis
 Markov::GUI::Generate, 123

visualization
 Markov::GUI::menu, 161

WHITE
 Markov::API::CLI::Terminal, 213

WIN32_LEAN_AND_MEAN
 framework.h, 253

wordlistname
 Markov::API::CLI::_programOptions, 55

x
 Markov::API::CUDA::Random::Marsaglia, 159
 Markov::Random::Marsaglia, 149

y
 Markov::API::CUDA::Random::Marsaglia, 159
 Markov::Random::Marsaglia, 149

YELLOW
 Markov::API::CLI::Terminal, 213

z