

# BLOC: BINARY LARGE OBJECTS WITH CONCURRENCY

---

Anshu Avinash


Thesis supervisor: Piyush Kurur

June 15, 2015

Department of CSE, IIT Kanpur

# WHAT IS A BLOB?

BLOB stands for “Binary Large OBject”.



Store the entire content of the blob in the database.

- PostgreSQL breaks large objects into “chunks” and these chunks are stored in rows in the database.
- MongoDB also divides large objects using the GridFS specification and stores them in the “chunks” collection.

Store the blob in a file and store the file name in the database.

- Number and size of blobs are now limited only by the file system.
- Requires to develop an interface to keep track of all the blobs of a database.

# HERE COMES BLOC!

We provide a library which will keep track of all the blobs stored in a database.

- Our design is inspired from the maildir format<sup>1</sup>.

---

<sup>1</sup>Daniel J Bernstein. *Using maildir format*. 1995.

- Our design is inspired from the maildir format<sup>1</sup>.
- All the blobs of a database are stored inside a directory which we also call a **BlobStore**.

---

<sup>1</sup>Daniel J Bernstein. *Using maildir format*. 1995.

- Our design is inspired from the maildir format<sup>1</sup>.
- All the blobs of a database are stored inside a directory which we also call a BlobStore.
- Each blob is stored as a different file inside the BlobStore.

---

<sup>1</sup>Daniel J Bernstein. *Using maildir format*. 1995.



- Our design is inspired from the maildir format<sup>1</sup>.
- All the blobs of a database are stored inside a directory which we also call a **BlobStore**.
- Each blob is stored as a different file inside the BlobStore.
- We provide an incremental interface for writing to a blob as well as reading from a blob.

---

<sup>1</sup>Daniel J Bernstein. *Using maildir format*. 1995.

## CREATING A NEW BLOB

```
openBlobStore :: FilePath -> IO BlobStore
newBlob       :: BlobStore -> IO WriteContext
```

```
blobstore
├── tmp
│   ├── 1a4c5091-1295-4c9c-b8d3-8e6123a51b41
│   └── 4af0ac03-0b79-43fd-a2b0-2cc7c62947bc
```

## ADDING CONTENTS TO A BLOB

```
writePartial :: WriteContext  
             -> Blob  
             -> IO WriteContext  
endWrite     :: WriteContext -> IO BlobId
```

```
blobstore  
├── tmp  
│   └── 1a4c5091-1295-4c9c-b8d3-8e6123a51b41  
└── curr  
    └── sha512-861844d6704e8573fec34d967e20b..
```

```
startRead      :: BlobId -> IO ReadContext
readPartial    :: ReadContext -> Int -> IO Blob
skipBytes      :: ReadContext -> Integer -> IO ()
endRead        :: ReadContext -> IO ()
```


- A blob can be shared by multiple “records” of the database.

- A blob can be shared by multiple “records” of the database.
- We provide an interface for garbage collection of deleted blobs.


# STARTING A GC

```
startGC :: BlobStore -> IO ()
```

Before startGC




After startGC




# MARKING A BLOB AS ACCESSIBLE

`markAsAccessible :: BlobId -> IO ()`

Before



After






# ENDING A GC

`endGC :: BlobStore -> Int -> IO ()`

Before



After

