

Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	The company suffered a DoS attack caused by an ICMP flood. The attack made network services unavailable for two hours. The team blocked ICMP traffic and restored critical services.
Identify	• **Attack:** DoS (ICMP flood). • **Cause:** A misconfigured firewall. • **Affected systems:** The internal network and its services. • **Impact:** Network services were unavailable for two hours.
Protect	• **Configure the firewall correctly.** • **Limit incoming ICMP packets.** • **Block fake IP addresses.** • **Use IDS/IPS to block suspicious traffic.** • **Update security rules regularly.**
Detect	• Monitor network traffic. • Check firewall logs. • Set alerts for unusual traffic. • Use IDS/IPS to detect suspicious activity.

	• Check network performance regularly.
Respond	• Block malicious ICMP traffic. • Identify affected systems. • Check network logs to understand the attack. • Inform the security team. • Fix the firewall configuration.
Recover	• Restore critical network services. • Check that the network is working normally. • Monitor traffic for new attacks. • Test the firewall rules. • Update the incident response plan.

Reflections/Notes: This incident showed the importance of firewall configuration and network monitoring. The NIST CSF helps organizations identify risks, protect systems, detect attacks, respond to incidents, and recover services.