

Schema — Sistema de Pizzaria

Schema completo gerado durante sessão de modelagem

CLIENTES

```
CREATE TABLE clients (  
  id SERIAL PRIMARY KEY,  
  name VARCHAR(100) NOT NULL,  
  phone VARCHAR(20) NOT NULL,  
  street VARCHAR(150) NOT NULL,  
  number VARCHAR(10) NOT NULL,  
  complement VARCHAR(100),  
  neighborhood VARCHAR(100) NOT NULL,  
  city VARCHAR(100) NOT NULL,  
  zip_code VARCHAR(10) NOT NULL,  
  created_at TIMESTAMP DEFAULT NOW()  
);
```

FORMAS DE PAGAMENTO

```
CREATE TABLE payments (  
  id SERIAL PRIMARY KEY,  
  name VARCHAR(50) NOT NULL, -- "Pix", "Cartão", "Dinheiro"  
  active BOOLEAN DEFAULT TRUE  
);
```

INGREDIENTES

```
CREATE TABLE ingredients (  
  id SERIAL PRIMARY KEY,  
  name VARCHAR(100) NOT NULL UNIQUE,  
  category VARCHAR(50), -- "queijo", "carne", "vegetal"  
  created_at TIMESTAMP DEFAULT NOW()  
);
```

PIZZAS

```
CREATE TABLE pizzas (  
  id SERIAL PRIMARY KEY,  
  name VARCHAR(100) NOT NULL UNIQUE,  
  description TEXT,  
  price_small DECIMAL(8, 2),  
  price_medium DECIMAL(8, 2),  
  price_large DECIMAL(8, 2),  
  active BOOLEAN DEFAULT TRUE,  
  created_at TIMESTAMP DEFAULT NOW()  
);
```

RELAÇÃO PIZZA ↔ INGREDIENTES (composição base)

```
CREATE TABLE pizza_ingredients (  
  pizza_id INT REFERENCES pizzas(id) ON DELETE CASCADE,  
  ingredient_id INT REFERENCES ingredients(id) ON DELETE RESTRICT,  
  quantity VARCHAR(50),  
  PRIMARY KEY (pizza_id, ingredient_id)  
);
```

PREÇO DOS INGREDIENTES ADICIONAIS

```
CREATE TABLE ingredient_prices (  
  ingredient_id INT REFERENCES ingredients(id) ON DELETE CASCADE PRIMARY KEY,  
  price_small DECIMAL(8, 2),  
  price_medium DECIMAL(8, 2),  
  price_large DECIMAL(8, 2)  
);
```

BORDAS RECHEADAS

```
CREATE TABLE crusts (  
  id SERIAL PRIMARY KEY,  
  name VARCHAR(100) NOT NULL, -- "Catupiry", "Cheddar"  
  description TEXT,  
  price_small DECIMAL(8, 2),  
  price_medium DECIMAL(8, 2),  
  price_large DECIMAL(8, 2),  
  active BOOLEAN DEFAULT TRUE  
);
```

PRODUTOS (refrigerantes, doces, etc.)

```
CREATE TABLE products (  
  id SERIAL PRIMARY KEY,  
  name VARCHAR(100) NOT NULL,  
  description TEXT,  
  price DECIMAL(8, 2) NOT NULL,  
  active BOOLEAN DEFAULT TRUE,  
  created_at TIMESTAMP DEFAULT NOW()  
);
```

PEDIDOS

```
CREATE TABLE orders (  
  id SERIAL PRIMARY KEY,  
  client_id INT REFERENCES clients(id),  
  payment_id INT REFERENCES payments(id),  
  total DECIMAL(8, 2),  
  status VARCHAR(50) DEFAULT 'pending', -- pending, preparing, delivered  
  created_at TIMESTAMP DEFAULT NOW()  
);
```

```
);
```

ITENS DO PEDIDO (cada pizza individualmente)

```
CREATE TABLE order_items (  
  id SERIAL PRIMARY KEY,  
  order_id INT REFERENCES orders(id) ON DELETE CASCADE,  
  crust_id INT REFERENCES crusts(id),  
  size VARCHAR(10) NOT NULL CHECK (size IN ('small', 'medium', 'large')),  
  quantity INT DEFAULT 1  
);
```

METADES DE CADA ITEM (pizza meio a meio)

```
CREATE TABLE order_item_halves (  
  id SERIAL PRIMARY KEY,  
  order_item_id INT REFERENCES order_items(id) ON DELETE CASCADE,  
  pizza_id INT REFERENCES pizzas(id),  
  half INT NOT NULL CHECK (half IN (1, 2))  
);
```

INGREDIENTES CUSTOMIZADOS POR METADE (add / remove)

```
CREATE TABLE order_item_half_ingredients (  
  order_item_half_id INT REFERENCES order_item_halves(id) ON DELETE CASCADE,  
  ingredient_id INT REFERENCES ingredients(id),  
  action VARCHAR(10) NOT NULL CHECK (action IN ('add', 'remove')),  
  PRIMARY KEY (order_item_half_id, ingredient_id)  
);
```

PRODUTOS NO PEDIDO

```
CREATE TABLE order_products (  
  id SERIAL PRIMARY KEY,  
  order_id INT REFERENCES orders(id) ON DELETE CASCADE,  
  product_id INT REFERENCES products(id),  
  quantity INT DEFAULT 1  
);
```