



## Technical Test

### DEV - E

Date: 27/03/2025 City/State: Recife - PE

Course: Computer Science Educational Institution: CESAR School

Course Duration (in years): 4 Current Semester: 5 Graduation Year (expected): 2026

Availability to work: ☐ 20h ☒ 30h ☐ 40h Estimated Start Date: Immediately

Instructions: This test consists of 8 multiple choice questions, 1 algorithm implementation and 1 non-technical question. The algorithm is worth 60% of the total score. The non-technical question must be answered in Portuguese. You may use any blank space on this test as a draft. Use the table below to record your answers. Good luck!

Answer Sheet

	1	2	3	4	5	6	7	8
A								
B	X							
C				X	X			X
D		X	X			X	X	

## Question 1

Given:

```
1.  import java.util.Date;
3.  public class Example {
5.      6.public static void main(String args[]) {
7.          8.Date d1 = new Date (92, 11, 31);
9.              Date d2 = new Date (94, 11, 31);
10.                 method(d1, d2);
11.         System.out.println("d1=" + d1.getYear() + "\nd2=" + d2.getYear());
12.     }
13. } public static void method(Date d1, Date d2) {
        d2.setYear(98);
        d1 = d2;
    }
```

What's the output?

- A. d1=92  
d2=94
- B. d1=92  
d2=98
- C. d1=98  
d2=98
- D. d1=98  
d2=94

## Question 2

Given:

```
1.  //*****
2.  // file A.java
3.  //*****
4.  package a;
5.  public class A {
6.      private int x;
7.      protected int y;
8.      public int m1() {return x;}
9.  }
10. //*****
11. // file B.java
12. //*****
13. package b;
14. import a.A;
15. public class B extends A {
16.     private int z;
17.     public void m2(A a) {
18.         z = x;
19.         z = y;
20.         z = a.m1();
21.     }
22. }
```

Consider the following statements:

- I. Line 18 is valid because B extends A
- II. Line 19 is not valid because y is protected
- III. Line 20 is valid because m1() is public

- A. Only I and II are correct
- B. Only I and III are correct
- C. Only II and III are correct
- D. Only III is correct


### Question 3

What best defines an abstract class?

- A. The class must not have method definitions.
- B. The class must have a method definition returning nothing.
- C. The class must have a constructor that takes no arguments.
- D. The class cannot be instantiated as it is mainly for inheritance.

### Question 4

Consider this small binary tree:



What is the order of nodes visited using a post-order traversal?

- A. 1 2 3 7 10 11 14 30 40
- B. 1 2 3 14 7 10 11 40 30
- C. 1 3 2 7 10 40 30 11 14
- D. 14 2 1 3 11 10 7 30 40

### Question 5

Consider the following statements:

- I. A Binary tree is a tree data structure in which each node has at most two child nodes, usually distinguished as "left" and "right", and a tree with  $n$  nodes has exactly  $n-1$  branches which means its height is always  $n-1$ .
- II. A Queue is a FIFO data structure, which means that the first element added to the queue will be the first one to be removed.
- III. A Hash Map is a data structure in which, if there's no collision among the keys, you can always find an element in  $O(1)$  time, even in the worst case.

- A. Only I and II are correct
- B. Only I and III are correct
- C. Only II and III are correct
- D. I, II and III are correct

## Question 6

In the following code, assume that Queue is not thread-safe, there is more than one Producer thread and more than one Consumer thread running and this program is crashing on runtime. In order to fix the code below how should you fill in lines (1), (2), (3) and (4)?

Global variables	
Queue q; (1)	
Producer thread	Consumer thread
<pre>runProducer(){ while(true){     item = new item();     (2)     if (q is not full){         q.enqueue(item);         (3)     }     (4) } }</pre>	<pre>runConsumer(){ while(true){     (2)     if (q is not empty){         item = q.dequeue();         (3)     }     (4) } }</pre>

- A. (1) mutex m;  
(2) m.lock();  
(3)  
(4) m.unlock();
- B. (1)  
(2)  
(3)  
(4) if(Consumer) sleep(1); else sleep(2);
- C. (1) semaphore guard;  
(2) wait(guard);  
(3)  
(4) signal(guard);

D. Alternatives A and C are correct.

## Question 7

Considering the following tables and data information, what would be the correct result of the SQL command below?

Salesperson			
ID	Name	Age	Salary
1	Abe	61	140,000
2	Bob	34	44,000
5	Chris	34	40,000
7	Dan	41	52,000
8	Ken	57	115,000
11	Joe	38	38,000

Customer			
ID	Name	City	Industry_Type
4	Samsonic	Pleasant	G
6	Panasung	Oaktown	N
7	Samony	Jackson	N
9	Ornange	Hayward	G
8	Hepoul	Cupertino	I

Orders				
Number	Order_Date	cust_id	salesperson_id	Amount
10	8/2/2010	4	2	540
20	5/6/2012	9	7	150
30	3/12/2012	8	5	1,500
40	1/30/2013	4	8	1,800
50	7/14/2009	9	1	460
60	1/29/2012	7	2	2,400
70	2/3/2012	6	7	600
80	4/1/2013	8	2	2,300
90	3/2/2012	6	7	720

```
SELECT Salesperson.Name from Salesperson
WHERE Salesperson.ID NOT IN(
    SELECT Orders.salesperson_id FROM Orders
    INNER JOIN Customer ON Orders.cust_id = Customer.ID
    WHERE Customer.Name = 'Panasung')
AND Salesperson.ID IN
    (SELECT DISTINCT Orders.salesperson_id FROM Orders);
```

A. Bob  
Chris  
Ken

B. Abe  
Bob  
Ken

C. Abe  
Bob  
Chris  
Ken  
Joe

D. Abe  
Bob  
Chris  
Ken

## Question 8

Given this output on a Linux terminal:

```
$ cat linux_distributions.txt
Debian distribution
Ubuntu distribution derived from Debian
Fedora distribution
Red Hat Enterprise Linux distribution derived from Fedora
CentOS distribution derived from Fedora
MINIX and Linux operating system
```

What will be the correct result of the command below?

```
$ cat linux_distributions.txt | grep Fedora | sort
```

- A. Fedora distribution  
Red Hat Enterprise Linux distribution derived from Fedora  
CentOS distribution derived from Fedora
- B. CentOS derived distribution Fedora from  
distribution Fedora  
derived distribution Enterprise Fedora from Hat Linux Red
- C. CentOS distribution derived from Fedora  
Fedora distribution  
Red Hat Enterprise Linux distribution derived from Fedora
- D. distribution Fedora  
derived distribution Enterprise Fedora from Hat Linux Red  
CentOS derived distribution Fedora from

## Subsets

Write the function `getSubSets()` to compute and return all subsets of a given set A, which has at most 4 elements.

Use the Set data structure to represent all sets and sub-sets of your solution. A Set is a collection that contains no duplicate elements and the order of elements is irrelevant. Consider the following interface defined for Set:

Method signature	Method description
<code>boolean add(Element e)</code>	Adds the specified element to this set if it is not already present (optional operation).
<code>boolean addAll(Set s)</code>	Adds all elements from s that are not already present in this set.
<code>boolean contains(Element e)</code>	Returns true if this set contains the specified element.
<code>boolean equals(Set s)</code>	Compares the specified set s with this set for equality.
<code>Iterator&lt;Element&gt; iterator()</code>	Returns an iterator over the elements in this set.
<code>boolean remove(Element e)</code>	Removes the specified element from this set if it is present (optional operation).
<code>int size()</code>	Returns the number of elements in this set (its cardinality).
<code>Element[] toArray()</code>	Returns an array containing all of the elements in this set.

**Table: Set interface**

Input example:

A=[1,2,3]

Output for the given example:

[[1,2,3], [1,2], [1,3], [2,3], [1], [2], [3], []]\*

\* this is the content of the Set which should be returned by the function.

Your proposed solution can be written in pseudo-code or any well-known language (C, C++, Java, etc) and you are free to implement any auxiliary functions. Besides, write down a comment to the main function explaining how your function will work like the one below.

```
/**
 * The function below will ...
 * - Obtain the input
 * - Iterate over the elements
 * ...
 * - Print the output and return ...
 */
```

# Algorithm Solution

```
Subsets.java X
Subsets.java > Java > Subsets
1 import java.util.*;
2
3 public class Subsets {
4     /**
5      * The function below will compute and return all subsets of a given set A
6      * -Step 1: convert the input Set A into an array to allow indexed access
7      * -Step 2: calculate the number of subsets using 2^n
8      * -Step 3: for each number from 0 to 2^n - 1 generate a subset,
9      *           for each bit in the bitmask, if it is set, include the corresponding element
10     * -Step 4: add each generated subset to the result set
11     * -return a Set of all the subsets
12     */
13     public Set<Set<Integer>> getSubSets(Set<Integer> A) {
14         Set<Set<Integer>> result = new HashSet<>();
15
16         //Step 1: convert the input Set A into an array to allow indexed access
17         Integer[] elements = new Integer[A.size()];
18         Iterator<Integer> it = A.iterator();
19         int index = 0;
20         while (it.hasNext()) {
21             elements[index++] = it.next();
22         }
23
24         //Step 2: calculate the number of subsets using 2^n
25         int n = elements.length;
26         int totalSubsets = 1 << n;
27
28         //Step 3: for each number from 0 to 2^n - 1 generate a subset
29         for (int i = 0; i < totalSubsets; i++) {
30             Set<Integer> subset = new HashSet<>();
31             for (int j = 0; j < n; j++){
32                 //if bit j is set in i, include elements[j]
33                 if ((i & (1 << j)) != 0) {
34                     subset.add(elements[j]);
35                 }
36             }
37             //Step 4: add each generated subset to the result set
38             result.add(subset);
39         }
40
41         return result;
42     }
43
44     /**
45     * the main method below will:
46     * - create a sample set A with elements {1, 2, 3}
47     * - call the getSubSets method to compute all subsets of A
48     * - print each subset
49     */
50     public static void main(String[] args) {
51         Set<Integer> A = new HashSet<>();
52         A.add(1);
53         A.add(2);
54         A.add(3);
55
56         Subsets sub = new Subsets();
57         Set<Set<Integer>> subsets = sub.getSubSets(A);
58
59         for (Set<Integer> subset : subsets) {
60             System.out.println(subset);
61         }
62     }
63
64 }
```



Qual a disciplina que você mais gostou de cursar na faculdade e por quê? (Responder em português)

Estou cursando atualmente, no 5º período, a disciplina de “**Requisitos, Projeto e Validação de Software**”, e tem sido a que mais me interessei até agora. Nela, estou tendo a oportunidade de desenvolver um projeto completo desde o início, utilizando ferramentas e tecnologias como Maven, Spring Boot, JPA e React no front-end.

O mais legal é que além da parte técnica, também estamos trabalhando na criação de histórias de usuário, no levantamento de requisitos e na validação das funcionalidades com testes automatizados usando JUnit, utilizando a metodologia TDD. Essa abordagem mais prática tem me ajudado bastante a compreender melhor todo o ciclo de desenvolvimento de software.

