

# BlendShapes System

In order for you to set up your model to work with the blendshape system you will need to

1. Right-click on the Hierarchy window and create an AR-Renderer/ar-face-tracking-scene.
2. Next you need to right click on the Hierarchy window and create AR-Renderer AR-BlendShapeSystem.
3. Select the "Ar BlendShape Controller" component you created in the "Face-Track-Controller" script.
4. Enable the "use blendshapes" option.

Done, now you need to create a script that will contain all the settings for this model, you can use the standard script "Demo Face Tracking" and the settings for it you will find on the demo scene "FaceTrackingBlendShapesExample".

The AR-BlendShapeSystem object you have created has basic blends set up, you can change the settings or leave them as they are.

But if you want to create your own script, here's what you need to know:

You need to pass data to the "Init" method of the "Ar BlendShape Controller" class such as :

"blendShapesMapRef">The dictionary created to work in the inspector is needed for converting to a regular dictionary for gartering the names of blendshapes and internal enum .

"model">Reference to an object in the scene.

"headBone"(Optional) Needed to implement head rotation relative to the virtual face.

"jawBoneRef">(Optional) On some models, the jaw is implemented as a separate object and does not change when changing the blendshape, in order to implement the opening of the jaw, in this case, you need to have a "bone" of the jaw.

Note that in the sample scene all blendshapes that can be processed are set up, if you don't like the performance of a particular blendshape you can try to change the points used there, or the multiplier.

But if you are happy with the configuration you can copy all the settings into your script or use the demo script.