

Signal API

APISignal (sgnl.pro)BIM-
URL: https://api.sgnl.pro/public/v1



Endpoint: POST /auth/token

:

```
{
  "clientId": "your_client_id",
  "clientSecret": "your_client_secret",
  "scopes": [
    "project:read", "project:list",
    "docs:folder:read", "docs:folder:list",
    "docs:item:read", "docs:item:list",
    "docs:version:read", "docs:version:list",
    "docs:object:read", "docs:object:list"
  ]
}
```

:

```
{
  "token": "eyJhbGciOiJIUzI1NiIs..."
}
```

: Authorization: Bearer <token>



Endpoint: GET /projects

:

```
Authorization: Bearer <token>
Accept: application/json
```

:

```
[
  {
    "id": "uuid-project-1",
    "name": "ЖК МЫ ПОЗ.6.2",
    "description": "...",
    "createdAt": "2024-01-15T10:00:00Z"
  }
]
```

```
]

```



Endpoint: GET /docs/projects/{projectId}

:

```
{
  "id": "uuid-root-folder",
  "name": "root",
  "rootFolderId": "uuid-root-folder",
  "createdAt": "2024-01-15T10:00:00Z"
}
```

Endpoint: GET /folders/{folderId}/children

:

```
[
  {
    "id": "uuid-folder-1",
    "name": "6. CMP",
    "parentId": "uuid-root-folder",
    "createdAt": "2024-01-15T10:00:00Z"
  }
]
```

:

```
const sameName = (a, b) =>
  (a ?? '').toString().trim().toLowerCase() ===
  (b ?? '').toString().trim().toLowerCase();

const folder = children.find(f => sameName(f.name, "Журнал бетонных работ"));
```

"6. CMP/Журнал бетонных работ":

```
const splitPath = (p) =>
  (p ?? '').toString()
    .replaceAll('\\', '/')
    .split('/')
    .map(x => x.trim())
    .filter(Boolean);
```

```
// ["6. СМР", "Журнал бетонных работ"]
```



(Items)

Endpoint: GET /items?folderId={folderId}

:

```
[
  {
    "id": "uuid-item-1",
    "name": "12.csv",
    "folderId": "uuid-folder-1",
    "topVersionId": "uuid-version-1",
    "createdAt": "2024-01-15T10:00:00Z",
    "updatedAt": "2024-01-15T10:00:00Z"
  }
]
```

: topVersionId

Endpoint: GET /items/download?itemId={itemId}&versionId={versionId}

:

```
{
  "signedUrl": "https://storage.sgnl.pro/...?token=...",
  "expiresAt": "2024-01-15T12:00:00Z"
}
```

: signedUrl —



workflow

1. POST /auth/token → получить JWT
2. GET /projects → найти projectId по имени
3. GET /docs/projects/{projectId} → получить rootFolderId
4. GET /folders/{rootFolderId}/children → найти первую папку
5. GET /folders/{folderId}/children → найти следующую папку (рекурсивно)
6. GET /items?folderId={finalFolderId} → найти itemId и versionId
7. GET /items/download?itemId={itemId}&versionId={versionId} → получить signedUrl
8. GET {signedUrl} → скачать файл



200	OK		
401	Unauthorized		—
403	Forbidden	scopes	—
404	Not Found		— ID
429	Too Many Requests	Rate limit	—
500	Internal Error		—

```
const httpJsonLenient = async (method, url, { headers = {}, body } = {}) =>
  await this.helpers.httpRequest({
    method,
    url,
    headers: { accept: 'application/json', ...headers },
    body,
    json: true,
    returnFullResponse: true,
    ignoreHttpStatusCode: true,
  });

// Проверка ответа
if (!(res.statusCode >= 200 && res.statusCode < 300 && res.body?.token)) {
  throw new Error(`Auth failed: ${res.statusCode} ${JSON.stringify(res.body || {})}`);
}
```

 Scopes ()

Scope
project:read
project:list
docs:folder:read
docs:folder:list
docs:item:read
docs:item:list
docs:version:read
docs:version:list
docs:object:read
docs:object:list



- [Signal](#)
- [API \(](#))
- [n8n Community](#) —