

Target Mapping Parameters

Disclaimer: Not all parameters are available for all SAP S/4HANA releases and SAPUI5 versions.

Parameter Name	Default Value	Description
sap-ach	(text)	Support component to be shown in the About dialog. This is used for apps/UIs that don't have an app descriptor (i.e. manifest.json file).
sap-fiori-id	(text)	For most SAP Fiori apps the SAP Fiori app id is included in the app descriptor (i.e. manifest.json file). This parameter provides an alternative way to assign the SAP Fiori app id to the app when this is not possible, e.g. for some apps based on generic analytics frameworks. This is used for apps/UIs that don't have an app descriptor (i.e. manifest.json file).
sap-iapp-state	(long alphanumeric)	This is the internal application state of the app. RESERVED. DO NOT USE.
sap-keep-alive	false	When true this keeps the app alive when the user navigates away. Refer to your SAP Fiori launchpad guide section Keeping SAPUI5 Apps Alive
sap-prelaunch-operations	(delete, split or merge)	Operation to be entered as Default Value, e.g. [{"type": "merge", "source": ["P_FromPostingDate", "P_ToPostingDate"], "target": "PostingDate"}]
sap-personas-flavor	(flavor id)	Add a SAP Screen Personas flavor to a GUI transaction or Web Dynpro application
sap-priority	(integer)	Default value is 10. Setting a higher value, e.g. 1, can be used to resolve conflicting target mappings. Refer to SAP Note 2257864 - Resolution for Conflicting Target Mappings
sap-tag	(enum)	This parameter allows a label to be assigned to any target mapping. Some

		<p>labels have specific meanings.</p> <p>When primaryAction this makes the target mapping the default link on the Semantic Object, overriding the default action displayFactSheet. Make sure to define no more than one primary action per semantic object.</p> <p>When superiorAction on a List of Links dialog the current link is shown as a favourite link (instead of only in More Links)</p> <p>When suppressInEnterpriseSearch this will remove the app from the dynamic links in the Search results.</p>
sap-ui-tech-hint	UI5, GUI, or WDA	Quick hint support info to identify the technology used by the app associated with a tile/link from the launch URL.
sap-ushell-next-navmode	(inplace or explace)	If explace , app is opened in a new web browser tab/window. If inplace , app is opened in the current web browser tab/window.
sap-ushell-plugin-type	(text)	e.g. UserDefaults

You find some more useful parameters and details on when and how to use them in your SAP Fiori Launchpad guide in section [Passing User Settings to URL Applications](#). A quick overview below:

Parameter Name	Default Value	Description
sap-accessibility	%%User.env.sap-accessibility%%	Indicates whether accessibility mode is active for the respective user.
sap-language	%%User.env.sap-language%%	The user's logon language, for example EN, ZH or ZF
sap-statistics	%%User.env.sap-statistics%%	Indicates whether performance statistics in response headers are active.
sap-theme	%%User.env.sap-theme%%	The name of the theme, including the theme root if the theme originates from a

		different server than the front-end server.
sap-theme-name	%%User.env.sap-theme-name%%	The name of the theme, without the theme root.
sap-theme-NWBC	%%User.env.sap-theme-NWBC%%	The name of the theme including the theme root. This parameter is primarily used for Web Dynpro applications and transactions.
sap-ui-legacy-date-format	%%User.env.sap-ui-legacy-date-format%%	Fixed value representing the date format on the ABAP platform.
sap-ui-legacy-number-format	%%User.env.sap-ui-legacy-number-format%%	Fixed value representing the number format for decimal notation on the ABAP platform.
sap-ui-legacy-time-format	%%User.env.sap-legacy-time-format%%	Fixed value representing the time format on the ABAP platform.