HOW TO PROCEED WITH TROUBLESHOOTING

05I2G−01

HINT:
- Use this procedure to troubleshoot the fuel lid opener system.
- The intelligent tester II should be used in steps 3 and 5.

1	VEHICLE BROUGHT TO WORKSHOP

2	CUSTOMER PROBLEM ANALYSIS CHECK AND SYMPTOM CHECK

3	INSPECT COMMUNICATION FUNCTION OF LARGE−SCALE MULTIPLEX COMMU-NICATION SYSTEM (BEAN)

(a) Use the intelligent tester II to check for normal function of the multiplex communication system.
    (1)   (ECU unconnected, communication line malfunctioning) Without code outputs, proceed to A.
    (2)   (ECU unconnected, communication line malfunctioning) With code outputs, proceed to B.

B	Go to MULTIPLEX COMMUNICATION SECTION (See page 05−3162)

A

4	PROBLEM SYMPTOMS TABLE (See page 05−2529)

(a) If the fault is not listed on the problem symptoms table, proceed to A.
(b) If the fault is listed on the problem symptoms table, proceed to B.

B	Go to step 6

A

5	OVERALL ANALYSIS AND TROUBLESHOOTING

(a) DATA LIST/ACTIVE TEST (see page 05−1301).
    (1)   Inspection with the intelligent tester II (ECU DATA LIST).
    (2)   Inspection with the intelligent tester II (ACTIVE TEST).
(b) Terminals of ECU (see page 05−2531).
(c) On−vehicle inspection (see page 05−2611).
(d) Inspection (see page 05−2613).

6	ADJUST, REPAIR OR REPLACE

7	CONFIRMATION TEST

END