## **TORQUE SPECIFICATION**

030MV-05

Part Tightened	N⋅m	kgf⋅cm	ft·lbf
Bleeder plug	11	110	8
Brake booster clevis lock nut	26	265	19
Stop lamp switch assy lock nut	17	173	12
Brake pedal support sub-assy x Brake pedal sub-assy	37	375	27
Brake pedal support sub-assy x Body	13	130	9
Brake pedal support sub-assy x Instrument panel reinforcement	19	195	14
Brake master cylinder x Vacuum check valve bracket	13	127	9
Brake master cylinder x Brake tube	15	155	11
Brake master cylinder x ABS&TRACTION actuator assy	15	155	11
Brake booster x Body	13	130	9
Wheel nut	103	1,050	76
Front brake cylinder x Steering knuckle	110	1,122	81
Front disc brake cylinder x Flexible hose	39	400	29
Rear disc brake cylinder x Rear axle	78	800	58
Rear disc brake cylinder x Flexible hose	39	400	29
ABS&TRACTION actuator x ABS&TRACTION actuator bracket assy	5.4	55	48 in.·lbf
ABS&TRACTION actuator with bracket x Body	19	195	14
ABS&TRACTION actuator assy x Brake tube	15	155	11
Rear speed sensor x Rear axle	8.0	82	71 in.·lbf
Rear speed sensor wire harness clamp x Body	5.0	51	44 in.·lbf
Yawrate sensor x Body	12.5	127.5	9