

TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Intermediate shaft x Flexible coupling	79	805	58
Propeller shaft assy x Flexible coupling	79	805	58
Intermediate shaft assy x Adjusting nut	69	700	51
Propeller shaft heat insulator x Body	5.4	55	48 in.·lbf
Front floor heat insulator No. 1 x Body	5.4	55	48 in.·lbf
Propeller shaft assy x Front flange	79	805	58
Propeller shaft assy x Rear differential	79	805	58
Center support bearing assy No. 1 x Body	37	375	27
Front wheel set nut	103	1,050	76
Lower ball joint assy x Steering knuckle	113	1,150	83
Steering knuckle x Upper suspension arm	87	887	64
Front axle hub sub-assy x Steering knuckle	69	700	51
Front disc brake caliper assy x Steering knuckle	78	800	58
Skid control sensor wire clamp x Steering knuckle	5.5	56	49 in.·lbf
Rear wheel set nut	103	1,050	76
Speed sensor rear x Rear axle carrier sub-assy	8.0	82	71 in.·lbf
Rear drive shaft x Rear axle shaft nut	290	2,960	214
Rear axle carrier sub-assy x Rear disc brake caliper	78	800	58
Rear stabilizer link assy x Rear suspension arm assy No.2	65	663	48
Height control sensor link x Rear suspension arm assy No.2	5.4	55	48 in.·lbf
Rear axle carrier sub-assy x Toe control link sub-assy	50	510	37
Rear axle carrier sub-assy x Rear axle hub & bearing assy	65	663	48
Rear axle carrier sub-assy x Upper control arm assy rear	70	714	52
Rear axle carrier sub-assy x Rear suspension arm assy No.2	70	714	52
Rear suspension member brace x Body	50	510	37
Rear axle carrier sub-assy x Rear suspension arm assy No.1	70	714	52
Differential support protector No.2 x Body	5.4	55	48 in.·lbf
Parking brake cable assy No.3 x Body	19	194	14