

WIRELESS DOOR LOCK BUZZER CIRCUIT


CIRCUIT DESCRIPTION

When the answer-back function does not operate even though the wireless door LOCK/UNLOCK function is operating, the theft warning ECU's (theft deterrent ECU's) wireless door lock buzzer outputs may be abnormal.

NOTICE:

Before troubleshooting, confirm that the ON/OFF switch is not set to OFF and that the wireless buzzer volume is not OFF.

WIRING DIAGRAM



INSPECTION PROCEDURE

1 PERFORM ACTIVE TEST USING INTELLIGENT TESTER

- (a) Connect the intelligent tester to DLC3.
- (b) Turn the ignition switch ON.
- (c) Perform the ACTIVE TEST according to the display on the tester.

OK: Wireless buzzer is operating (sounding) normally.

Item	Test Detail	Diagnostic Note
Buzz Resp Sound	Turns wireless buzzer ON/OFF	-


NG

Go to step 2

OK

PROCEED TO NEXT CIRCUIT INSPECTION SHOWN IN PROBLEM SYMPTOMS TABLE
(See page 05-2876)

2 INSPECT WIRELESS DOOR LOCK BUZZER



- (a) Measure the resistance between terminals 1 and 3 of the buzzer.

Standard: Approximately 1 kΩ

NOTICE:

- The buzzer circuit is built into the theft warning ECU, not into the buzzer itself.
- When battery voltage is directly applied to the buzzer, the buzzer does not sound.

NG

REPLACE WIRELESS DOOR LOCK BUZZER

OK

3


CHECK WIRE HARNESS (WIRELESS DOOR LOCK BUZZER – THEFT WARNING ECU ASSY)

Wire Harness Side

K1
Wireless Door Lock Buzzer



T5
Theft Warning ECU Assy



BZR
BZR2

- (a) Disconnect the K1 buzzer connector.
- (b) Disconnect the T5 ECU connector.
- (c) Measure the resistance of the wire harness side connectors.

Standard:

Tester Connection	Specified Condition
K1-1 – T5-5 (BZR2)	Below 1 Ω
K1-2 – T5-4 (BZR)	Below 1 Ω

NG

REPAIR OR REPLACE HARNESS AND CONNECTOR

OK

PROCEED TO NEXT CIRCUIT INSPECTION SHOWN IN PROBLEM SYMPTOMS TABLE
(See page 05-2852)