

Projectile Motion with Air Resistance

Ivan Pestana

August 22, 2026

1 Physical Model

1.1 Motivation

When we consider a projectile launched from ground level with an initial velocity v_0 at an angle θ above the horizontal, the motion can be described by Newton's second law. If we ask the question of which angle provides the maximum range, in the absence of air resistance, the answer is famously 45° . However this is not the case if we include air resistance.

1.2 Newton's Second Law

Newton's second law for the projectile reads

$$\mathbf{F}_r + \mathbf{F}_g = m\mathbf{a}, \quad (1)$$

where $\mathbf{F}_g = (0, -mg)$ is the force of gravity. Writing this equation component by component,

$$a_x = \frac{F_{r,x}}{m}, \quad a_y = -g - \frac{F_{r,y}}{m}, \quad (2)$$

where $F_{r,x}$ and $F_{r,y}$ are still unknown, since we have not yet written $\mathbf{F}_r$ explicitly.

1.3 The Drag Force

When air resistance is included, the projectile is subject to a drag force $\mathbf{F}_r$ that always acts in the opposite direction of the velocity $\mathbf{v}$. Throughout this document, bold symbols denote vectors (e.g. $\mathbf{v}$), while the same symbol in italics denotes its magnitude (e.g. $v = |\mathbf{v}|$).

The form of the drag force depends on the Reynolds number,

$$\text{Re} = \frac{Dv\rho}{\eta}, \quad (3)$$

where D is the projectile's size, ρ the density of air, and η its viscosity.

Re is the ratio of inertial to viscous forces in the surrounding flow. If we have a low Re, viscous forces dominate and the drag force is linear,

$$F_r \propto v \quad (\text{linear, or Stokes, drag}), \quad (4)$$

which is a regime typical of small objects moving slowly through a viscous fluid, such as a droplet. This regime holds for $\text{Re} \lesssim 1$; for example, a $10 \mu\text{m}$ fog droplet settling in air at roughly 2.7 cm/s has $\text{Re} \approx 0.016$ [1]. Turning the proportionality into an equality introduces a constant b , the linear drag coefficient, which for a sphere is given by Stokes' law as $b = 3\pi\eta D$. Since the force points opposite to the velocity,

$$\mathbf{F}_r = -b\mathbf{v}. \quad (5)$$

On the other hand, if we have a high Re , inertial forces dominate and the drag force is quadratic,

$$F_r \propto v^2 \quad (\text{quadratic, or Newtonian, drag}), \quad (6)$$

which is a regime typical of bigger objects moving through air, such as a thrown ball or a fired projectile. This regime holds for speeds between approximately 0.25 m/s and 53 m/s, corresponding to $10^3 < \text{Re} < 2 \times 10^5$ [2].

Between these two regimes, roughly $1 \lesssim \text{Re} \lesssim 10^3$, there is a middle zone where neither law works well, and the drag force has no simple formula, instead being found from experiments or lookup tables [1]. This middle zone does not matter here, since projectile motion falls well inside the quadratic regime.

So far we only know that the drag force grows with the square of the speed – we do not yet have an exact formula. To turn this proportionality into a real equation, we introduce a constant, C , called the drag coefficient:

$$F_r = C v^2. \quad (7)$$

This constant packages together everything else that affects the force: the projectile's shape, its cross-sectional area, and the density of the air. In reality, C can itself change slightly with the speed of the projectile, $C = C(\mathbf{v})$. However, this variation is small within the range of speeds we consider, so throughout this document we treat C as a fixed, known constant. This is an approximation, but a reasonable one: it greatly simplifies the equations while still capturing the essential physics of drag.

We still need the force as a vector, not just a size. To point it in the right direction, we multiply by a unit vector – a vector of length one – that points opposite to the motion. Dividing $\mathbf{v}$ by its own length, $\mathbf{v}/v$, gives exactly that: it keeps the direction of the velocity but has length one. So the drag force is

$$\mathbf{F}_r = -C v^2 \frac{\mathbf{v}}{v} = -C v \mathbf{v}, \quad v = |\mathbf{v}| = \sqrt{v_x^2 + v_y^2}, \quad (8)$$

where the minus sign flips the direction, and one factor of v cancels against the denominator.

Substituting this into the component equations above,

$$a_x = -\frac{C}{m} v v_x, \quad a_y = -g - \frac{C}{m} v v_y. \quad (9)$$

2 System of Differential Equations

The equations for a_x and a_y derived above are completed by the definitions of velocity and acceleration,

$$\mathbf{v} = \frac{d\mathbf{r}}{dt}, \quad \mathbf{a} = \frac{d\mathbf{v}}{dt} = \frac{d^2\mathbf{r}}{dt^2}, \quad (10)$$

together with the initial condition

$$\mathbf{v}(t=0) = \mathbf{v}_0, \quad (11)$$

where $\mathbf{v}_0$ is a given constant.

Written out, this gives the following system of differential equations:

$$\frac{dv_x}{dt} = -\frac{C}{m} v v_x, \quad \frac{dv_y}{dt} = -g - \frac{C}{m} v v_y, \quad (12)$$

$$\frac{dx}{dt} = v_x, \quad \frac{dy}{dt} = v_y. \quad (13)$$

In principle, this system cannot be solved analytically. This is due to the nonlinear coupling introduced by $v = \sqrt{v_x^2 + v_y^2}$: unlike the linear drag case, where the equation for v_x depends only on v_x and can be solved on its own, here the equation for v_x also depends on v_y (and vice versa), so the two cannot be solved independently.

3 Numerical Integration

We have just shown that this system of differential equations cannot be solved analytically. This does not mean the motion is unknown, only that we cannot write $\mathbf{v}(t)$ and $\mathbf{r}(t)$ as a closed formula. Instead, we approximate them numerically, by advancing the motion one small step at a time rather than jumping straight to the answer.

One way to do this is the following. We split the flight of the projectile, of total duration τ , into a large number of steps of small duration Δt , say $\Delta t/\tau \leq 10^{-3}$, with τ estimated from the case without air resistance. We then assume that, within each such short step, $\mathbf{v}$ and $\mathbf{a}$ do not change appreciably, i.e. they are approximately constant.

This assumption lets us reuse the constant-acceleration formulas from introductory kinematics,

$$v = v_0 + at, \quad x = x_0 + v_0 t + \frac{1}{2}at^2, \quad (14)$$

but only over one short step at a time, since here $\mathbf{a}$ is not truly constant – it depends on the velocity, which keeps changing. Concretely, this comes from the definition of acceleration, $\mathbf{a} = d\mathbf{v}/dt$, which for a small but finite Δt gives

$$\mathbf{a} \approx \frac{\mathbf{v}(t + \Delta t) - \mathbf{v}(t)}{\Delta t} \implies \mathbf{v}(t + \Delta t) \approx \mathbf{v}(t) + \mathbf{a}(t) \Delta t. \quad (15)$$

Writing $\mathbf{v}_n$ for $\mathbf{v}(t_n)$, and $\mathbf{a}_n$ for the acceleration evaluated using the velocity at step n (from Eq. (9)), this is

$$\mathbf{v}_{n+1} = \mathbf{v}_n + \mathbf{a}_n \Delta t, \quad \mathbf{a}_n = \left(-\frac{C}{m} v_n v_{n,x}, -g - \frac{C}{m} v_n v_{n,y} \right). \quad (16)$$

In other words, we repeatedly apply the ordinary constant-acceleration formula, but only for one short step, and we recompute $\mathbf{a}_n$ from the updated velocity before taking the next step.

Similarly, for the position, the second formula in Eq. (14) gives

$$\mathbf{r}_{n+1} = \mathbf{r}_n + \mathbf{v}_n \Delta t + \frac{1}{2} \mathbf{a}_n (\Delta t)^2. \quad (17)$$

The last term is negligible compared to the first as $\Delta t \rightarrow 0$. To see why, compare the two terms for a typical speed $v \sim 20$ m/s, acceleration $a \sim 10$ m/s², and $\Delta t = 10^{-3}$ s:

$$v \Delta t \sim 2 \times 10^{-2} \text{ m}, \quad \frac{1}{2} a (\Delta t)^2 \sim 5 \times 10^{-6} \text{ m}. \quad (18)$$

The quadratic term is smaller than the linear one by a factor on the order of Δt itself, since it carries an extra power of Δt ; for $\Delta t \ll 1$, squaring makes it far smaller still. This is why the term is said to be of order $O[(\Delta t)^2]$: it shrinks much faster than the linear term as Δt is made smaller, and can safely be dropped, leaving

$$\mathbf{r}_{n+1} = \mathbf{r}_n + \mathbf{v}_n \Delta t. \quad (19)$$

4 Stopping Condition

5 How this turns into Code

References

- [1] M. V. Lubarda, V. A. Lubarda, *A review of the analysis of wind-influenced projectile motion in the presence of linear and nonlinear drag force*, Archive of Applied Mechanics **92** (2022) 1997–2017.
- [2] P. S. Chudinov, V. A. Eltyshev, Y. A. Barykin, *Simple analytical description of projectile motion in a medium with quadratic drag force*, Latin American Journal of Physics Education **7** (2013).