

Multiclass classification: Takeaways

by Dataquest Labs, Inc. - All rights reserved © 2020

Syntax

- Returning a DataFrame containing binary columns:

```
dummy_df = pd.get_dummies(cars["cylinders"])
```

- Concatenating DataFrames:

```
cars = pd.concat([cars, dummy_df], axis=1)
```

- Returning a Series containing the index of the maximum value:

```
predicted_origins=testing_probs.idxmax(axis=1)
```

Concepts

- In the instance where two values are just two different labels, it is safer to turn the discrete values into categorical variables.
- Dummy variables are for columns that represent categorical values.
- A problem is a multiclass classification problem when there are three or more categories or classes. There are existing multiclassification techniques that can be categorized into the following:
 - Transformation to Binary: Reducing the problem to multiple binary classification problems.
 - Extension from Binary: Extending existing binary classifiers to solve multi-class classification problems.
 - Hierarchical classification: Dividing the output into a tree where each parent node is divided into multiple child nodes and the process is continued until each child node represents only one class.
- The one-versus-all method, which is a transformation to binary technique, is a technique where we choose a single category as the Positive case and group the rest of the categories as the False case.

Resources

- [Documentation for idxmax\(\)](#)
- [Multiclass Classification](#)



Takeaways by Dataquest Labs, Inc. - All rights reserved © 2020