Connecting the Second Brain: quick reference

October 2026 · © 2026 Isa Haskologlu, PhD · CC BY 4.0

One key action and one check per integration. Full steps: Integration-Setup-Guides (Word/PDF).

working · working with limits · planned / not authorised

#	Integration	Key action	Check
0	**Claude Code**	`curl -fsSL https://claude.ai/install.sh | bash`	*claude --version · claude doctor*
1	**Obsidian**	Vault profile → Manage Vaults… → Open folder as vault	*folders visible; graph view works*
2	**Git**	`git init · .gitignore key files FIRST · commit`	*git check-ignore -v <key file>*
3	**Zotero: read**	Zotero Settings → Advanced → allow other apps · /zotero-sources doctor	*doctor passes; import one item*
4	**Zotero: write**	Web API key (write) → read -s → key file, chmod 600	*api.zotero.org/keys/... shows write*
5	**Mendeley**	dev portal app → OAuth login → tokens in git-ignored file	*PLANNED: doctor passes*
6	**Claude in Chrome**	install extension · claude --chrome	*/chrome: Enabled · Installed*
7	**NotebookLM**	sign in via Chrome · paste text as source	*output saved; watch quota*
8	**Jev**	`/plugin install jev@jev-mcp (user) · key via read -s`	*/mcp: plugin:jev:jev · 6 tools*
9	**Google connectors**	`/mcp → Show unused connectors → sign in`	*NOT AUTHORISED yet*
10	**Skills + plugins**	`.claude/skills/<name>/SKILL.md · /plugin install`	*claude plugin list: each once*
11	**Pipeline tools**	`brew install poppler ocrmypdf pandoc · .venv + requirements.txt`	*process-source.py --doctor: all available*

Security, every time

Never paste keys into chat, screenshots or commands (use read -s) · git-ignore secret files before creating them · prefer read-only access · slash commands go inside Claude Code, shell commands in the Terminal