

Data Warehousing

Lecture 10 – Advanced Cypher and APOC

CITS3401
CITS5504

Dr. Sirui Li

Computer Science and
Software Engineering

School of Maths, Physics
and Computing

Acknowledgement: The lecture slides are adopted from online sources.

Outline of This Week's Lectures

- Cypher recap
- Aggregation and other useful Cypher clauses
- Awesome Procedures on Cypher (APOC)
- Importing data in APOC
- APOC text functions
- Path Expansion in Cypher & APOC
- Virtual Graph

2


Outline of This Week's Lectures

- Cypher recap
- Aggregation and other useful Cypher clauses
- Awesome Procedures on Cypher (APOC)
- Importing data in APOC
- APOC text functions
- Path Expansion in Cypher & APOC
- Virtual Graph

3

Cypher Recap

```
(Person { name: "Jennifer" }) -  
  [:WORKS_FOR] ->  
  (Company { name: "Neo4j" })
```



4

Cypher Recap



- So far we have looked at several Cypher clauses for Creating, Reading, Updating and Deleting data:
 - **CREATE**, **MERGE**, and **LOAD CSV**
 - **MATCH** and **RETURN**, with **WHERE**
 - **SET** and **REMOVE**
 - **DELETE**
- We have also briefly looked at **WITH**

5

Cypher Recap



- The Cypher queries we have looked at so far tend to either return nodes, relationships or properties, e.g.

```
MATCH (Person {name: 'Jim'})-[:KNOWS]->(b:Person)
RETURN b
```

```
MATCH (a:Person {name: 'Jim'})-[:KNOWS]->(b:Person)
      -[:KNOWS]->(c:Person),
      (a)-[:KNOWS]->(c)
RETURN b.name, c.name
```

6

Aggregation



- Sometimes we need to group records together to answer certain questions. For example:
 - For each person, list **the number of friends** they have.
 - For each movie, list the names of **all people** who watched that movie.
 - For each person named “Jack”, list the **name of all of their pets**.
- To be able to answer these questions we need to use **aggregation**.

7

Aggregation



For example, for “For each person, list **the number of friends** they have”, we would like our result to look as follows:

Person	Number of friends
Jack	5
Freddy	12
Jane	7
Wanda	16

Note we do not care about returning the friends of each person individually – we are only interested in the **total number**.

8

Aggregating by Count

- The simplest aggregation is to aggregate by **count**. This simply returns the count of the results found in the database, rather than returning the objects themselves.
- To do this, we can use the **COUNT** function in Cypher:

```
MATCH (p1:Person)-[:FRIENDS_WITH]->(p2:Person)
RETURN p1.name, COUNT(p2)
```

- This will count the number of occurrences of p2 for each distinct value of p1.name (which is the **grouping key**).

9

Aggregating by Count Example

Without COUNT:

```
1 MATCH (p1:Person)-[:FRIENDS_WITH]->(p2:Person)
2 RETURN p1.name, p2
```

"p1.name"	"p2"
"jim"	{ "name": "fred" }
"jim"	{ "name": "bill" }
"fred"	{ "name": "bill" }

With COUNT:

```
1 MATCH (p1:Person)-[:FRIENDS_WITH]->(p2:Person)
2 RETURN p1.name, COUNT(p2)
```

"p1.name"	"COUNT(p2)"
"jim"	2
"fred"	1

10

Aggregating by Count Example

- We can also use the asterisk (*) inside a COUNT function to count the total number of rows for each grouping key, for example:

```
1 MATCH (p1:Person)-[:FRIENDS_WITH]->(Person)
2 RETURN p1.name, COUNT(*)
```

"p1.name"	"COUNT(*)"
"jim"	2
"fred"	1

11

Aggregating by Value

- Sometimes we need to return lists of values – for example for listing all of the friends of a person.
- To do this, we can use the **COLLECT** function in Cypher:

```
MATCH (p1:Person)-[:FRIENDS_WITH]->(p2:Person)
RETURN p1.name, COLLECT(p2.name)
```

- All values of p2.name for each grouping key will be stored in a list.

12

Aggregating by Value Example

```
1 MATCH (p1:Person)-[:FRIENDS_WITH]-(p2:Person)
2 RETURN p1.name, COLLECT(p2.name)
```

	p1.name	COLLECT(p2.name)
1	"jim"	["fred", "bill"]
2	"fred"	["bill"]

13

Other useful aggregation functions

The following aggregation functions work on numeric values:

- **AVG** – Calculates the average value
- **MAX** – Calculates the maximum value
- **MIN** – Calculates the minimum value
- **SUM** – Calculates the total sum (also works on durations)
- **stDev** – Standard deviation

<https://neo4j.com/docs/cypher-manual/current/functions/aggregating>

14

Data Profiling with Cypher

- Counting all nodes that exist in the graph:
`MATCH (n) RETURN COUNT(n)`
- Counting all relationships that exist in the graph:
`MATCH (n)-[r]-(m) RETURN COUNT(r)`
- Finding all distinct labels that exist in the graph:
 1. `MATCH (n) RETURN DISTINCT LABELS(n)`
 2. `CALL db.labels()`
- Finding all distinct relationship types:
 1. `MATCH n-[r]-() RETURN DISTINCT TYPE(r)`
 2. `CALL db.relationshipTypes()`

15

Data Profiling with Cypher

- Finding all nodes that are disjoint, i.e. nodes that do not have any relationship with the other nodes:
`MATCH (n) WHERE NOT (n)-[]-() RETURN n`
- Finding all nodes that have some specific property:
`MATCH (n) WHERE HAS(n.name) RETURN n`
- Finding all nodes that have some specific relationship, regardless of the direction:
`MATCH (n)-[:ORIGIN]-() RETURN DISTINCT n`
- Show **metagraph** (or **schema graph**) to illustrate what is related, and how
`CALL db.schema.visualization()`

16

List Comprehension in Python (recall)

```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
newlist = []
```

```
for x in fruits:
    if "a" in x:
        newlist.append(x)
```

```
print(newlist)
```


```
fruits = ["apple", "banana", "cherry", "kiwi", "mango"]
```

```
newlist = [x for x in fruits if "a" in x]
```

```
print(newlist)
```

17

Pattern and List Comprehension in Cypher



<https://neo4j.com/docs/cypher-manual/current/values-and-types/lists/#cypher-pattern-comprehension>

18

Pattern and List Comprehension in Cypher

CREATE

```
(keanu:Person {name: 'Keanu Reeves'}),
(johnnyMnemonic:Movie {title: 'Johnny Mnemonic', released: 1995}),
(theMatrixRevolutions:Movie {title: 'The Matrix Revolutions', released: 2003}),
(theMatrixReloaded:Movie {title: 'The Matrix Reloaded', released: 2003}),
(theReplacements:Movie {title: 'The Replacements', released: 2000}),
(theMatrix:Movie {title: 'The Matrix', released: 1999}),
(theDevilsAdvocate:Movie {title: 'The Devils Advocate', released: 1997}),
(theMatrixResurrections:Movie {title: 'The Matrix Resurrections', released: 2021}),
(keanu)-[:ACTED_IN]->(johnnyMnemonic),
(keanu)-[:ACTED_IN]->(theMatrixRevolutions),
(keanu)-[:ACTED_IN]->(theMatrixReloaded),
(keanu)-[:ACTED_IN]->(theReplacements),
(keanu)-[:ACTED_IN]->(theMatrix),
(keanu)-[:ACTED_IN]->(theDevilsAdvocate),
(keanu)-[:ACTED_IN]->(theMatrixResurrections)
```

<https://neo4j.com/docs/cypher-manual/current/values-and-types/lists/#cypher-pattern-comprehension>

19

Pattern Comprehension in Cypher

A syntactic construct in Cypher for creating a list based on matchings of a pattern.

```
MATCH (keanu:Person {name: 'Keanu Reeves'})
RETURN [(keanu)-->(b:Movie) WHERE b.title CONTAINS 'Matrix' | b.released] AS years
```

A pattern comprehension

- matches the specified pattern like a normal MATCH clause,
- with predicates like a normal WHERE clause, but yields a custom projection as specified.

```
MATCH (keanu:Person {name: 'Keanu Reeves'})
WITH keanu, [(keanu)-->(b:Movie) | b.title] AS movieTitles
SET keanu.resume = movieTitles
RETURN keanu.resume
```

<https://neo4j.com/docs/cypher-manual/current/values-and-types/lists/#cypher-pattern-comprehension>

20

List Comprehension in Cypher



A syntactic construct in Cypher for creating a list based on an existing list.

```
MATCH (keanu:Person {name: 'Keanu Reeves'})
WITH keanu, [(keanu-->(b:Movie) | b.title] AS movieTitles
SET keanu.resume = movieTitles
RETURN keanu.resume
```

`keanu.resume` is an existing list, and we could do

```
MATCH (keanu:Person {name: 'Keanu Reeves'})
RETURN [x IN keanu.resume WHERE x contains 'The Matrix'] AS matrixList
```

What will the following return?

```
RETURN [x IN range(0,10) WHERE x % 2 = 0 | x^3 ] AS result
```

```
[0.0, 8.0, 64.0, 216.0, 512.0, 1000.0]
```

<https://neo4j.com/docs/cypher-manual/current/values-and-types/lists/#cypher-pattern-comprehension>

21

Summary



- We have looked at **aggregation** in Cypher, which allows us to **group similar records together** and optionally run calculations on them rather than returning records individually.
- There are several aggregation functions available in Neo4j, notably **COUNT** and **COLLECT**.
- **Pattern** and **list comprehension**, which creating a list based on matchings of a pattern or an existing list.

22

Outline of This Week's Lectures



- Cypher recap
- Aggregation and other useful Cypher clauses
- Awesome Procedures on Cypher (APOC)
- Importing data in APOC
- APOC text functions
- Path Expansion in Cypher & APOC
- Virtual Graph

23

Awesome Procedures on Cypher (APOC)



- The APOC library is a massive library for Neo4j that contains over **450** standard procedures and functions.
- It provides a wide range of functionality, such as:
 - More powerful tools for importing/exporting data
 - Text parsing functions
 - Path expansion
 - Virtual graphs

<https://neo4j.com/developer/neo4j-apoc/>

24

- APOC contains both procedures and functions:
 - Procedures** generally return a list (of nodes, etc) that are unwound.
 - Functions** are simpler, and typically return a single value i.e. a map, list, string or number.
- APOC often replaces the need to write your own functions in other scripting languages e.g. Python etc, and can therefore be a huge timesaver if you familiarise yourself with the functionality it offers.

<https://neo4j.com/developer/neo4j-apoc/>

25

- Before using APOC we need to **enable it from the plugins window** (just like with GDS).
- APOC functions can be run using CALL
- You can get a list of available APOC procedures and functions using:

```
CALL apoc.help("")
```

- You can search by keywords:

```
CALL apoc.help("import")
```

<https://neo4j.com/developer/neo4j-apoc/>

26

Importing data with APOC

- So far we have looked at **LOAD CSV**, which allows us to import data from a CSV file.
- APOC has a much **wider range of functionality for importing data** – it can load CSV, JSON files, excel spreadsheets, web APIs, etc.
- In this lecture we will focus on loading CSVs using APOC, but feel free to check out the other functionality in the Neo4j documentation.


27

Importing CSVs - nodes

people.csv

	A	B
1	name	occupation
2	Kellsie	Forester
3	Jacquelynn	Welder
4	Allissa	Dancer
5	Colly	Engineer
6	Aline	Welder

```
CALL apoc.import.csv([{'fileName': 'file:/people.csv',
labels: ['Person']}], [], {})
```



28

- APOC's CSV import will import nodes and relationships from a CSV file directly into your Neo4j database:

```
apoc.import.csv(<nodes>, <relationships>, <config>)
```

- Each argument is a list, where each element is a map of the filename and labels. For example:

```
apoc.import.csv([
  {filename: "file:/people.csv", labels: ["Person"]},
  ...
])
```

29

A complete import CSV call might look as follows:

```
CALL apoc.import.csv(
  [{fileName: "file:/persons.csv", labels: ["Person"]}],
  [{fileName: "file:/knows.csv", type: "KNOWS"}],
  { delimiter: "|", arrayDelimiter: ",", stringIds:
    false } )
```

persons.csv

```
:ID|name:STRING|speaks:STRING[]
1|John|en,fr
2|Jane|en,de
```

knows.csv

```
:START_ID|:END_ID|since:INT
1|2|2016
```

https://neo4j.com/labs/apoc/4.3/import/import-csv/#_usage

30

- An interesting use case for APOC is creating **dynamic relationship types** from a single CSV file.
- For example, imagine you had many **different types of relationships** between people – 'knows', 'friends_with', 'enemies_of', 'brother_of', 'sister_of'... etc.
- Without APOC, the simplest way to do this would be to create a CSV for each type of relationship in your data:
 - people.csv
 - knows.csv
 - friends_with.csv
 - enemies_of.csv...

31

- APOC has a function called `apoc.create.relationship` that creates a relationship of a given type between two nodes.
- You can combine this with standard Cypher's **LOAD CSV** to create relationship types based on the value stored in a column:

```
LOAD CSV WITH HEADERS from "file:///people.csv" AS row
```

```
MERGE (p1:Person {name: row.node1})
```

```
MERGE (p2:Person {name: row.node2}) WITH p1, p2, row
```

```
CALL apoc.create.relationship(p1, row.relationship, {}, p2)
```

```
YIELD rel RETURN rel
```

node1	node2	relationship
Mark	Reshmee	MARRIED_TO
Mark	Alistair	FRIENDS

<https://www.markhneedham.com/blog/2016/10/30/neo4j-create-dynamic-relationship-type/>

32

APOC's Text Functions



APOC features a substantial number of **text functions** which you can use on strings in your database. Some notable ones include:

- `apoc.text.levenshteinSimilarity` – measure the distance between two strings.
- `apoc.text.clean` – strip the given string of everything except alpha numeric characters and convert it to lower case.
- `apoc.text.fuzzyMatch` – check if two words can be matched in a fuzzy way.
- `apoc.text.indexOf` – find first occurrence of the lookup string in the text.

<https://neo4j.com/labs/apoc/4.3/overview/apoc.text/>

33

Summary



- We have looked at **APOC** (Awesome Procedures for Cypher), which offers a range of useful functions and procedures to extend Cypher.
- APOC has functions for **loading/importing data** that can be much quicker to write than many individual Cypher statements.
- It can also **create dynamic relationships** based on a value inside a column of a CSV file.
- We have also looked at some of APOC's **text functions**.

34

Outline of This Week's Lectures



- Cypher recap
- Aggregation and other useful Cypher clauses
- Awesome Procedures on Cypher (APOC)
- Importing data in APOC
- APOC text functions
- Path Expansion in Cypher & APOC
- Virtual Graph

35

Path Expansion in Cypher



- Sometimes it can be useful to describe a pattern containing a **long path**. For example, we might write:
`(a)-->()-->(b)`
... which is a path of length 2.
- With longer paths, though, the Cypher can become long-winded...
`(a)-->()-->()-->()-->()-->(b)`
`(a)-->()-->()-->()-->()-->()-->()-->(b)...`

36

Path Expansion in Cypher



Cypher allows us to specify a **variable path length**:

- (a) - [*5] -> (b) Paths of length 5
- (a) - [*..5] -> (b) Paths of length ranging from 0 to 5 inclusive
- (a) - [*5..] -> (b) Paths of length 5 or more
- (a) - [*3..5] -> (b) Paths from length 3 to 5 inclusive

37

Path Expansion in Cypher



This can be useful for many applications, such as querying for friends as well as friends of friends, e.g.:


```
MATCH (me)-[:KNOWS*1..2]-(remote_friend)
WHERE me.name = "Filipa"
RETURN remote_friend.name
```

38

Path Expansion in Cypher



We can also capture the path as a variable and return it – that way Neo4j will visualise the entire path.



39

Path Expansion in APOC



- APOC contains functions and procedures for working with paths as part of its **Path Expander** module.
- Unlike regular Cypher, APOC allows for:
 - The direction of the relationship to be specified per relationship type.
 - Whitelist/blacklisted label types.
 - Specification of end nodes for the expansion.

<https://neo4j.com/labs/apoc/4.1/graph-querying/path-expander/>

40

Path Expansion in APOC

- The most simple function is `apoc.path.expand`, which allows us to traverse paths based on relationship filters or node filters.
- We specify the start node, relationship filter, label filter, and path length.
- To demonstrate this we will use the graph on the right as an example.



<https://neo4j.com/labs/apoc/4.1/graph-querying/expand-paths/>

41

Path Expansion in APOC

The following returns the paths to people that Praveena KNOWS from 1 to 2 hops


```

Cypher
Copy to Clipboard
Run in Neo4j Browser

MATCH (p:Person (name: "Praveena"))
CALL apoc.path.expand(p, "KNOWS", null, 1, 2)
YIELD path
RETURN path, length(path) AS hops
ORDER BY hops;
```

Table 1. Results

path	hops
(Person:Engineering (name: "Praveena"))-[:KNOWS]-(:Person:Engineering (name: "Zhen"))	1
(Person:Engineering (name: "Praveena"))-[:KNOWS]-(:Person:Engineering (name: "Zhen"))-[:KNOWS]-(:Person:Engineering (name: "Martin"))	2
(Person:Engineering (name: "Praveena"))-[:KNOWS]-(:Person:Engineering (name: "Zhen"))-[:KNOWS]-(:Person:DevRel (name: "Liu"))	2
(Person:Engineering (name: "Praveena"))-[:KNOWS]-(:Person:Engineering (name: "Zhen"))-[:KNOWS]-(:Person:Field (name: "Stefan"))	2



<https://neo4j.com/labs/apoc/4.1/graph-querying/expand-paths/>

42

Path Expansion in APOC

The following returns paths containing only Engineering people that Praveena KNOWS from 1 to 2 hops


```

Cypher
Copy to Clipboard
Run in Neo4j Browser

MATCH (p:Person (name: "Praveena"))
CALL apoc.path.expand(p, "KNOWS", "+Engineering", 1, 2)
YIELD path
RETURN path, length(path) AS hops
ORDER BY hops;
```

Table 2. Results

path	hops
(Person:Engineering (name: "Praveena"))-[:KNOWS]-(:Person:Engineering (name: "Zhen"))	1
(Person:Engineering (name: "Praveena"))-[:KNOWS]-(:Person:Engineering (name: "Zhen"))-[:KNOWS]-(:Person:Engineering (name: "Martin"))	2



<https://neo4j.com/labs/apoc/4.1/graph-querying/expand-paths/>

43

Path Expansion in APOC

The following returns paths containing people that Alicia FOLLOWS or KNOWS from 1 to 3 hops


```

Cypher
Copy to Clipboard
Run in Neo4j Browser

MATCH (p:Person (name: "Alicia"))
CALL apoc.path.expand(p, "FOLLOWS|KNOWS", "", 1, 3)
YIELD path
RETURN path, length(path) AS hops
ORDER BY hops;
```

Table 3. Results

path	hops
(Person:Product (name: "Alicia"))-[:FOLLOWS]-(:Person:Field (name: "Joe"))	1
(Person:Product (name: "Alicia"))-[:FOLLOWS]-(:Person:Sales (name: "Jonny"))	1
(Person:Product (name: "Alicia"))-[:KNOWS]-(:Person:Product (name: "Jake"))	1



<https://neo4j.com/labs/apoc/4.1/graph-querying/expand-paths/>

44

Expanding to Subgraph

APOC also has a procedure for **expanding to a subgraph**.

The procedure returns **nodes and relationships**, excluding the starting node.

The following returns the subgraph reachable by the KNOWS relationship at 1 to 2 hops from Praveena

```
cypher
MATCH (p:Person {name: "Praveena"})
CALL apoc.path.subgraphAll(p, {
  relationshipFilter: "KNOWS",
  minLevel: 1,
  maxLevel: 2
})
YIELD nodes, relationships
RETURN nodes, relationships;
```

We can see a Neo4j Browser visualization of the returned subgraph in Subgraph from Praveena.




Figure 2. Subgraph from Praveena

<https://neo4j.com/labs/apoc/4.1/graph-querying/expand-subgraph/>

45

Virtual Nodes & Relationships

- APOC allows us to create **virtual nodes and relationships**, which don't exist in the graph – they are **stored in memory** and **returned to the UI**.
- A good use case for this is representing **transitive relationships** between nodes – rather than visualising the entire graph from point A to point B, we could draw a link between A and B with a property set to the total distance between them.

<https://neo4j.com/labs/apoc/4.1/virtual/virtual-nodes-rels/>

46

Virtual Nodes & Relationships

For example, we can create a **virtual relationship** between two accounts where some money has been sent from one account to another:

Simple example aggregate Relationships Cypher

```
cypher
MATCH (from:Account)-[:SENT]->(p:Payment)-[:RECEIVED]->(to:Account)
RETURN from, to, apoc.create.vRelationship(from, 'PAID', {amount:sum(p.amount)}, to) as rel;
```

*(4) Account(2) One(1) Two(1)

*(1) PAID(1)


<https://neo4j.com/labs/apoc/4.1/virtual/virtual-nodes-rels/>

47

Summary

- In this lecture we have looked at describing **variable length paths** in Cypher.
- We have also seen APOC's Path Expander module, which allows more control over path expansion.
- APOC also provides the ability to create **virtual nodes and relationships**, giving us a lot more control over our Neo4j visualisations.

48



Copyright Notice

Material used in this recording may have been reproduced and communicated to you by or on behalf of **The University of Western Australia** in accordance with section 113P of the *Copyright Act 1968*.

Unless stated otherwise, all teaching and learning materials provided to you by the University are protected under the Copyright Act and is for your personal use only. This material must not be shared or distributed without the permission of the University and the copyright owner/s.