

Nanopore automata

Ian Holmes^{1,2,*}

1 Lawrence Berkeley National Laboratory, Berkeley, CA, USA

2 Department of Bioengineering, University of California, Berkeley, CA, USA

Contents

1	Abstract	2
2	Specification	2
2.1	Parameterization algorithm	2
2.2	Reference search algorithm	2
2.3	Implementation	3
2.4	Evaluation	3
3	Methods	3
3.1	Model	3
3.2	Parameterization	3
3.2.1	Baum-Welch algorithm	3
3.3	Search	3
3.3.1	Prefiltering heuristic	3
3.3.2	Viterbi algorithm	3
4	Results	4
5	Discussion	4
6	Acknowledgments	5
7	Figure Legends	6

1 Abstract

State machine algorithms for aligning Nanopore read pairs.

2 Specification

2.1 Parameterization algorithm

Given the following inputs

- Reference genome (FASTA)
- Segment-called reads (FAST5/HDF5)

Perform the following steps

- Perform Baum-Welch to fit a rich model

Rich model incorporates segment statistics.

2.2 Reference search algorithm

Given the following inputs

- Segment-called reads (FAST5/HDF5)
- Parameterized rich model

Perform the following steps

- Prefilter read pairs using k-mer threshold heuristics
- Perform Viterbi alignment using intersection of two rich models

2.3 Implementation

2.4 Evaluation

3 Methods

3.1 Model

3.2 Parameterization

3.2.1 Baum-Welch algorithm

3.3 Search

3.3.1 Prefiltering heuristic

(Omit this step in first implementation?)

- Build database of k-mer frequencies across all reads
- Compute likelihood of each read using a “bag of words” model
- Compute likelihood of each read-pair using a “bag of paired words” model
- Compute posterior probability of a match

3.3.2 Viterbi algorithm

4 Results

5 Discussion

6 Acknowledgments

7 Figure Legends