

Classification of task-unrelated thoughts based on single-trial fMRI data

Matthias Mittner¹, Wouter Boekel¹, Gilles de Hollander¹, Adrienne Tucker¹, Andrew Heathcote², Birte Forstmann¹

¹ Cognitive Science Center Amsterdam, ² University of Newcastle



mittner@uva.nl



Introduction

During episodes of rest, a network of specific brain regions known as the default-mode network (DMN) is activated [1]. This network is also related to mind-wandering (task-unrelated thoughts, TUT) as measured by introspective thought-probes. Using a multivariate pattern analysis (MVPA) approach using data from fMRI and eyetracking, we classify trials in a stop-signal paradigm into on-task or TUT trials. By applying a cognitive model [2] to the behaviour as predicted by the classifier, we investigate latent cognitive processes underlying mind-wandering.


fMRI features



- calculate residuals $\rho_i = y_i - \sum_i \beta_i x_i$ using fcMRI GLM (task, motion, blinkrate, WM, CSF regressors)
- calculate voxel-pairwise correlations $corr(\rho_i, \rho_j)$ using a seed in the posterior cingulate cortex
- choose 5% most (anti-)correlated voxels to extract DMN and anti-correlated (task-positive) network (ACN; [4])
- project ROI (peak voxels + 3x3x3 cube) into individual space and extract mean activity across voxels per subject
- sliding-window correlation $corr_w(\rho_i(t), \rho_j(t))$ for $t \in \{k, \dots, k+w\}$ between all ROIs

Pupillometric features


- baseline-pupil diameter before probe (mean over $[-1000, 0]$ ms)
- pupillometric response extracted using GLM:



References

- [1] Raichle ME, MacLeod AM, Snyder AZ, Powers WJ, Gusnard DA, Shulman GL (2001) A default mode of brain function. Proc Natl Acad Sci 98:676-682.
- [2] Logan GD, Van Zandt T, Verbruggen F, Wagenmakers EJ (in press) On the ability to inhibit thought and action: General and special theories of an act of control. Psych Rev.
- [3] Schölkopf B, Smola AJ (2002) Learning with Kernels. MIT Press, Cambridge, MA.
- [4] Fox MD, Snyder AZ, Vincent JL, Corbetta M, Van Essen DC, Raichle ME (2005) The human brain is intrinsically organized into dynamic, anticorrelated functional networks. Proc Natl Acad Sci U S A 102:9673-9678.

Approach




Experimental Setup

- N=20 subjects in an 2-AFC, auditory Stop-Signal task
- simultaneous fMRI and eyetracking


Classifier Setup

- Support-vector machine with gaussian radial basis functions [3]
- binarize extreme-valued thought-probes to get labeled data
- optimize RBF-SVM parameters (C, γ) using AUC criterion
- Cross-Subject Crossvalidation Accuracy: **79.5%**
- label all trials using this classifier → extract statistics


Parameter Optimization



Feature Selection




Random Permutation Test




Classification Results

Feature-activation by Noise-Perturbation Sensitivity in TUT vs. on-task trials




Classifier Extracts Theoretical Plausible Discrimination



- ACN more active in on-task trials
- DMN more active in TUT trials
- reduced pupillary response in TUT trials

Analysis of frequency of TUT over trials



- TUTs increase with time
- TUTs are mainly short

Cognitive Model (work in progress)

Stop-Signal Diffusion Model [2]

- include classifier uncertainty: $p(t|\theta) = p_{acc}p_{TUT}(t) + (1 - p_{acc})p_{on}(t)$
- Bayesian Parameter estimation