


EM3566 Block Diagram



Boardcon Confidential

RK3566I2C MAP

Port	Pin name	Domain	Bus name	Pull-up voltage	Slave Device	Slave Addr (MS 7Bits)	Note	Slave Bus Capability
			I2C_SDA_HDMI I2C_SCL_HDMI				HDMI	
I2C2				VCC1V8_DVP			Camera	
I2C1				3V3			Touch	

Boardcon Confidential



Boardcon Inc

Room702-710, XinAn Business Building, 45Zone,
BaoAn District, Shenzhen China+86-755-27571591



Title

I2C Map

Size	Document Number	Drawn	Rev
A4	EM3566	Yhg	3
Date:	Tuesday, May 31, 2022	Sheet 2 of 14	

Main Power

DC=12V 3A




$$V_{out} = 0.6 * (1 + R_{444}/R_{446})$$




RTC Power

KEY






RECOVER

IR



UART2DBG_TX
UART2DBG_RX



Mark

Hole




Boardcon Confidential

Boardcon Inc. Room702-710, XinAn Business Building, 452Zone, BaoAn District, Shenzhen China +86-755-27571591



Title **Power/Micro SD/KEY**

Size	Document Number	Drawn	Rev
Custom	EM3566	Yhg	3
Date:	Thursday, June 02, 2022	Sheet	3 of 14

HDMI




HDMI OUTPUT





I2C Level Shift

Micro SD





Boardcon Confidential

Pin configuration diagram for the R402 module. The diagram shows a top header with pins R2, R28, R29, R38, R40, and R42. R2 is connected to VCCIO_WL. R28, R29, R38, and R40 are connected to NC/10K. R42 is connected to R0402. The bottom header shows pins for SDMMC1 (D0, D1, D2, D3, CMD, CLK), UART1 (TX_M0, RX_M0, CTSn_M0, RTSn_M0), WIFI (REG_ON_H, WAKE_HOST_H), BT (WAKE_HOST_H, REG_ON_H), and I2S2 (SCLK_TX_M0, LRCK_TX_M0, SDO_M0, SDI_M0).





供电电流至少400mA



	Boardcon Inc		Room702-710, XinAn Business Building, 45Zone, BaoAn District, Shenzhen China		+86-755-27571599
	Title				
	WIF/BT				
	Size	Document Number	Drawn	Rev	
A3	EM3566	<i>Yhg</i>	3		
Date:	Friday, July 22, 2022		Sheet	6	of 14

PCI.Express




Boardcon Confidential




Boardcon Inc		Room702-710, XinAn Business Building, 452Zone, BaoAn District, Shenzhen China		+86-755-27571591	
Title PCI-E NVME					
Size A3	Document Number EM3566			Drawn Yhg	Rev 3
Date: Tuesday, May 31, 2022				Sheet 8 of 14	

USB2.0 HOST




USB3.0




option

SATA









USB2.0 OTG



Boardcon Confidential

MIPI Camera



>>>MIPI_DSI_TX0_D0P/LVDS_TX0_D0P
>>>MIPI_DSI_TX0_D0N/LVDS_TX0_D0N

>>>MIPI_DSI_TX0_D1P/LVDS_TX0_D1P
>>>MIPI_DSI_TX0_D1N/LVDS_TX0_D1N

>>>MIPI_DSI_TX0_D2P/LVDS_TX0_D2P
>>>MIPI_DSI_TX0_D2N/LVDS_TX0_D2N

>>>MIPI_DSI_TX0_D3P/LVDS_TX0_D3P
>>>MIPI_DSI_TX0_D3N/LVDS_TX0_D3N

>>>MIPI_DSI_TX0_CLKP/LVDS_TX0_CLKP
>>>MIPI_DSI_TX0_CLKN/LVDS_TX0_CLKN

>>>EDP_TX_D0P
>>>EDP_TX_D0N

>>>EDP_TX_D1P
>>>EDP_TX_D1N

>>>EDP_TX_D2P
>>>EDP_TX_D2N

>>>EDP_TX_D3P
>>>EDP_TX_D3N




>>>EDP_TX_AUXP
>>>EDP_TX_AUXN

>>>LCD_BL_PWM
>>>LCD_PWREN_H

TOUCH_INT >>>SPI0_MISO_M0
TOUCH_RST >>>SPI0_CS0_M0

GPIO0_C5
GPIO0_C6

>>>PWM0_M0



Boardcon Confidential





Boardcon Inc			
Room703-710, XinAn Business Building, 45Zone, BaoAn District, Shenzhen China +86-755-27571591			
Title			
MIPI&LVDS/EDP			
Size	Document Number	Drawn	Rev
A3	EM3566	Yhg	3
Date:	Tuesday, May 31, 2022	Sheet	11 of 14


1V8 GPIO

[illegible]


UART1



UART2



RS485



Boardcon Confidential







Boardcon Inc Room702-710, XinAn Business Building, 45Zone,
BaoAn District, Shenzhen China +86-755-27571591

Title ***GPIO/UART***

Size	Document Number
A3	EM3566

Drawn <i>Yhg</i>	Rev 3
---------------------	----------




```
CFG_EXT=1:Use the external power source for the IO pad.  
CFG_LD01=1, CFG_LD00=0: IO pad 1.8V  
CFG_LD01=0,CFG_LD00=0: IO pad 3.3V      Default: IO pad=3.3V
```


RGMI Power Source	CFG EXT	CFG LDO	1:0
External 3.3V(default)	1'b1	2'b00	
External 1.8V	1'b1	2'b10	
Internal 1.8V	1'b0	2'b10	



VCCIO_PHY Voltage Config



PHY Address Config	PHY Address	PHYAD[2:0]
0	00000000	000
1	00000001	001
2	00000002	010
3	00000003	011
4	00000004	100
5	00000005	101
6	00000006	110
7	00000007	111




Pull-up for additional 2ns delay to RXC for data latching



Pull-up for additional 2ns delay to TXC for data latching



Pull-up to disable PLL @ ALDPS mode



SPDIF-OUT

