

Open Queueing Networks

Himanshu Singh Vikaskumar Kalsariya Aditya Kulkarni Kiran Gullapalli
Keshava V

March 2, 2024

- 1 Introduction
- 2 Solving the Jackson Network
- 3 Simulation

Queueing Networks

- ▶ A queueing network is a connected directed graph, whose nodes represent servers (each with their own queue), and edges between nodes represent channels through which jobs can be routed.




Figure: Intel Ivy Bridge queue model

Open Networks

- ▶ A network is said to be open if there is at least one edge for an 'external' arrival, and from every node there is a path for an 'external' departure.




Figure: An open queueing network

Jackson Network

► A general form of open network

- Unbounded queues, with FCFS service order
- External arrivals $\sim \text{Poisson}(r_i)$
- Service rates $\sim \text{Exp}(\mu_i)$
- Probabilistic routing - P_{ij}
- States: (n_1, n_2, \dots, n_k)





Figure: A Jackson network

Poisson Arrivals?

- ▶ $\lambda_i = r_i + \sum_j \lambda_j P_{ji}$
- ▶ Consider a single server network with properties:
 - Low arrival rate
 - High service rate
 - High P_{ii}



Violates independent increment property!

Balance Equations

- Rate of jobs leaving the state = Rate of jobs entering the state.

$$\begin{aligned}
 & \pi_{n_1, n_2, \dots, n_k} \cdot \left[\sum_{i=1}^k r_i + \sum_{i=1}^k \mu_i (1 - P_{ii}) \right] = \\
 & \underbrace{\sum_{i=1}^k \pi_{n_1, \dots, n_i-1, \dots, n_k} \cdot r_i}_{\text{outside arrival}} + \underbrace{\sum_{i=1}^k \pi_{n_1, \dots, n_i+1, \dots, n_k} \cdot \mu_i P_{i, \text{out}}}_{\text{departure to outside}} \\
 & + \underbrace{\sum_{i=1}^k \sum_{j \neq i} \pi_{n_1, \dots, n_i-1, \dots, n_j+1, \dots, n_k} \cdot \mu_j P_{ji}}_{\text{internal transition from server } j \text{ to server } i, j \neq i}
 \end{aligned}$$

Balance Equations (Contd.)

- ▶ In general, very hard to solve.
- ▶ Local Balance Approach
 - Break both sides of the equation into $k + 1$ matching components and equate each component.
 - Define A = Rate of leaving state due to an external arrival.
 - Define A' = Rate of entering state due to an external departure.
 - Define B_i = Rate of leaving state due to a departure from server i .
 - Define B'_i = Rate of entering state due to an arrival at server i .

Balance Equations (Contd.)

- ▶ Solving $A = A'$

$$\sum_{i=1}^k \pi_{n_1, \dots, n_i, \dots, n_k} \cdot r_i = \sum_{i=1}^k \pi_{n_1, \dots, n_i+1, \dots, n_k} \cdot \mu_i P_{i, \text{out}}$$

- ▶ Can we make a guess for π_{n_1, \dots, n_k} such that it satisfies the above equality?
- ▶ Observe that $\pi_{n_1, \dots, n_i, \dots, n_k}$ term in A and the $\pi_{n_1, \dots, n_i+1, \dots, n_k}$ term in A' only differ in n_i .
- ▶ Let us assume that

$$\pi_{n_1, \dots, n_i, \dots, n_k} \cdot c_i = \pi_{n_1, \dots, n_i+1, \dots, n_k}$$

- ▶ Substituting, we get

$$\sum_{i=1}^k r_i = \sum_{i=1}^k (c_i \cdot \mu_i) P_{i, \text{out}}$$

Balance Equations (Contd.)

- ▶ If we further assume $c_i \cdot \mu_i = \lambda_i$, we get

$$\sum_{i=1}^k r_i = \sum_{i=1}^k \lambda_i P_{i,\text{out}}$$

- ▶ By our assumption, $c_i = \frac{\lambda_i}{\mu_i} = \rho_i$. Substituting this we get

$$\pi_{n_1}, \dots, \pi_{n_i}, \dots, \pi_{n_k} \cdot \rho_i = \pi_{n_1}, \dots, \pi_{n_i+1}, \dots, \pi_{n_k}$$

- ▶ Repeating the argument yields the following equation

$$\pi_{n_1}, \dots, \pi_{n_k} = C \rho_1^{n_1} \dots \rho_k^{n_k}$$

Balance Equations (Contd.)

- We still need to check if our assumption yields a valid solution to $B_i = B'_i$

$$B_i = B'_i$$

$$C \rho_1^{n_1} \rho_2^{n_2} \cdots \rho_k^{n_k} \mu_i (1 - P_{ii}) = \sum_{j \neq i} C \rho_1^{n_1} \rho_2^{n_2} \cdots \rho_k^{n_k} \left(\frac{\rho_j}{\rho_i} \right) \mu_j P_{ji}$$

$$+ C \rho_1^{n_1} \rho_2^{n_2} \cdots \rho_k^{n_k} \left(\frac{1}{\rho_i} \right) r_i$$

$$\mu_i (1 - P_{ii}) = \sum_{j \neq i} \frac{\rho_j \mu_j P_{ji}}{\rho_i} + \frac{r_i}{\rho_i}$$

$$\rho_i \mu_i (1 - P_{ii}) = \sum_{j \neq i} \rho_j \mu_j P_{ji} + r_i$$

$$\lambda_i (1 - P_{ii}) = \sum_{j \neq i} \lambda_j P_{ji} + r_i$$

Balance Equations (Contd.)

- Lastly, we need to find the normalizing constant C .

$$\sum_{n_1, \dots, n_k} \pi_{n_1, \dots, n_k} = 1$$

$$C \sum_{n_1, \dots, n_k} \rho_1^{n_1} \cdots \rho_k^{n_k} = 1$$

$$C \left(\sum_{n_1} \rho_1^{n_1} \right) \left(\sum_{n_2} \rho_2^{n_2} \right) \cdots \left(\sum_{n_k} \rho_k^{n_k} \right) = 1$$

$$C \left(\frac{1}{1 - \rho_1} \right) \left(\frac{1}{1 - \rho_2} \right) \cdots \left(\frac{1}{1 - \rho_k} \right) = 1$$

$$C = (1 - \rho_1)(1 - \rho_2) \cdots (1 - \rho_k).$$

$$\pi_{n_1, \dots, n_k} = \rho_1^{n_1} (1 - \rho_1) \rho_2^{n_2} (1 - \rho_2) \cdots \rho_k^{n_k} (1 - \rho_k)$$

Balance Equations (Contd.)


- What about the jobs at a given server?

$$\begin{aligned}P\{n_1 \text{ jobs at server 1}\} &= \sum_{n_2, \dots, n_k} \pi_{n_1, \dots, n_k} \\&= \sum_{n_2, \dots, n_k} \rho_1^{n_1} (1 - \rho_1) \rho_2^{n_2} (1 - \rho_2) \cdots \rho_k^{n_k} (1 - \rho_k) \\&= \rho_1^{n_1} (1 - \rho_1)\end{aligned}$$


$$P\{n_i \text{ jobs at server } i\} = \rho_i^{n_i} (1 - \rho_i).$$

- Thus, all servers behave like M/M/1 queues in terms of their stationary queue length distributions, even though their arrival processes are not necessarily Poisson.

Case 1



Case 2



Case 3

