

Contents

Notes: By Nota	1
Nota	1
Running Times	1
Algorithm Analysis	1
Running Time	1
Big O	1
Formula	1
ADTs	2
ADT #01- List ADT	2
Primitive Operations	2
Implementations	2

Notes: By Nota

Nota

Nota, is a simple script to manage notes. It manages all my class notes which are markdown files and compiles them to PDF versions. This is so people can see my notes and I can share them easier. Not only that but the PDF version makes for easier reading, while the markdown versions are easy to edit and easy to search for items. Hope you enjoy!

Running Times

Algorithm Analysis

- Space Efficiency: Somewhat Important
- Time Efficiency: **SUPER IMPORTANT!**

Running Time

Running Time = $T(n)$ - N is usually the size of the input: - Number of items to sort - Number of items to search - Size of objects

- Cases:
 - Worst Case (Most Common)
 - Average Case
 - Amortized
 - Best Case
- Factors To Ignore:
 - Small Input Size
 - Speed of the Machine

Big O

Formula

$$n \geq n_0, f(n) \leq g(n)$$

ADTs

- A description of a data structure containing:
 - I. Some information about how the data is organized (maybe)
 - II. A list of primitive operations that access or modify the data
 - **No Implementation Details**

ADT #01- List ADT

An ordered sequence of elements (not necessarily sorted)

Primitive Operations

- `Length(list)` - Returns the number of elements in the list
- `GetFirst(list)` - Returns the first element in the list
- `GetLast(list)` - Returns the last element in the list
- `Prepend(list, x)` - Inserts x into list at the beginning
- `Append(list, x)` - Inserts x into list at the end
- `RemoveFirst(list)` - Removes the first element in the list
- `RemoveLast(list)` - Removes the last element in the list
- `CreateEmptyList()` - Returns a newly created, empty list
- `IsEmpty(list)` - Returns True if list has no elements, else False

Implementations

Array

Description

Continuous block of memory which is not dynamically allocated. Ex. Java. ##### Advantages - Easy to work with and write - Easy access to any element within the array

Disadvantages

- $O(n)$ time to insert new elements
- Memory allocation issues
- Can't increase size without $O(n)$

Linked List

Description

- There are two types of objects - Node & Header:
 - List elements are stored in the nodes
 - Header is used to access the list

Advantages

- Improved running time over array
- Solves storage problems since it's dynamic

Disadvantages

- Harder to work with and implement
- Inserting elements is still $O(n)$