

# WetInk Next

Технический снимок исходного кода P0-P7

Актуальное состояние Android-проекта после P7: GPU-движок P0-P6 и Compose UI для Undo/Redo, слоёв и настроек кисти.

Собрано: 2026-08-06

## Состояние этапов

| Этап | Статус | Результат                                                                        |
|------|--------|----------------------------------------------------------------------------------|
| P0   | Готово | Запускаемый Kotlin / Compose / GLSurfaceView проект.                             |
| P1   | Готово | Камера, ввод, преобразования координат, dirty rect.                              |
| P2   | Готово | OpenGL ES 3 инфраструктура.                                                      |
| P3   | Готово | Offscreen canvas и present.                                                      |
| P4   | Готово | Стабилизация, StampEmitter, DabBuffer и DabRenderer.                             |
| P5   | Готово | Оpaque-кисть: stroke target, premultiplied preview и commit.                     |
| P6   | Готово | LayerStack, compositor и tile-based Undo/Redo с лимитом 96 MB.                   |
| P7   | Готово | Compose UI: команды Undo/Redo, слои, visibility/opacity, размер и opacity кисти. |

### Архитектура P7

Compose не меняет GL-ресурсы напрямую. Пользовательское действие идёт через `PaintSurfaceView.queueEvent` в `EngineRenderer`. После мутации GL-поток публикует immutable `EditorUiState`, а `PaintSurfaceView.post` передаёт его на главный поток Compose.

```
Compose UI -> PaintSurfaceView -> queueEvent -> EngineRenderer / GL
Engine state -> publishState -> PaintSurfaceView.post -> Compose snapshot
```

### Проверки и устройство

P7 успешно проходит `compileDebugKotlin`, `testDebugUnitTest` и `lintDebug`. Новый APK собран, установлен и запущен на планшете. Визуально подтверждены Compose-панели кисти и слоёв, а изменение размера кисти прошло по цепочке `UI -> GL -> state`.

# Полный актуальный код

Ниже приведено итоговое состояние репозитория, накопленное с P0 по P7.

## settings.gradle.kts

```
pluginManagement {
    repositories {
        google()
        mavenCentral()
        gradlePluginPortal()
    }
}

dependencyResolutionManagement {
    repositoriesMode.set(RepositoriesMode.FAIL_ON_PROJECT_REPOS)
    repositories {
        google()
        mavenCentral()
    }
}

rootProject.name = "WetInk Next"
include(":app")
```

## build.gradle.kts

```
plugins {
    id("com.android.application") version "8.6.1" apply false
    id("org.jetbrains.kotlin.android") version "2.0.21" apply false
    id("org.jetbrains.kotlin.plugin.compose") version "2.0.21" apply false
}
```

## app/build.gradle.kts

```
plugins {
    id("com.android.application")
    id("org.jetbrains.kotlin.android")
    id("org.jetbrains.kotlin.plugin.compose")
}

android {
    namespace = "com.wetinknext"
    compileSdk = 36

    defaultConfig {
        applicationId = "com.wetinknext"
        minSdk = 26
        targetSdk = 36
        versionCode = 1
        versionName = "0.1.0"
        testInstrumentationRunner = "androidx.test.runner.AndroidJUnitRunner"
    }

    buildTypes {
        release {
            isMinifyEnabled = false
        }
    }

    compileOptions {
        sourceCompatibility = JavaVersion.VERSION_17
        targetCompatibility = JavaVersion.VERSION_17
    }

    kotlinOptions {
        jvmTarget = "17"
    }

    buildFeatures {
        compose = true
    }
}

dependencies {
    val composeBom = platform("androidx.compose:compose-bom:2024.09.03")
    implementation(composeBom)
    androidTestImplementation(composeBom)

    implementation("androidx.core:core-ktx:1.13.1")
    implementation("androidx.activity:activity-compose:1.9.2")
    implementation("androidx.compose.ui:ui")
    implementation("androidx.compose.ui:ui-tooling-preview")
    implementation("androidx.compose.material3:material3")

    testImplementation("junit:junit:4.13.2")
}
```

```

        debugImplementation("androidx.compose.ui:ui-tooling")
        debugImplementation("androidx.compose.ui:ui-test-manifest")
    }

```

## app/src/main/AndroidManifest.xml

```

<?xml version="1.0" encoding="utf-8"?>
<manifest xmlns:android="http://schemas.android.com/apk/res/android">
    <application
        android:allowBackup="true"
        android:label="@string/app_name"
        android:supportRtl="true"
        android:theme="@style/Theme.WetInkNext">
        <activity
            android:name=".app.MainActivity"
            android:exported="true">
            <intent-filter>
                <action android:name="android.intent.action.MAIN" />
                <category android:name="android.intent.category.LAUNCHER" />
            </intent-filter>
        </activity>
    </application>
</manifest>

```

## app/src/main/java/com/wetinknext/app/EditorScreen.kt

```

package com.wetinknext.app

import androidx.compose.foundation.background
import androidx.compose.foundation.border
import androidx.compose.foundation.clickable
import androidx.compose.foundation.layout.Arrangement
import androidx.compose.foundation.layout.Box
import androidx.compose.foundation.layout.Column
import androidx.compose.foundation.layout.Row
import androidx.compose.foundation.layout.fillMaxSize
import androidx.compose.foundation.layout.fillMaxWidth
import androidx.compose.foundation.layout.heightIn
import androidx.compose.foundation.layout.padding
import androidx.compose.foundation.layout.width
import androidx.compose.foundation.lazy.LazyColumn
import androidx.compose.foundation.lazy.items
import androidx.compose.foundation.shape.RoundedCornerShape
import androidx.compose.material3.Checkbox
import androidx.compose.material3.Slider
import androidx.compose.material3.Text
import androidx.compose.material3.TextButton
import androidx.compose.runtime.Composable
import androidx.compose.runtime.getValue
import androidx.compose.runtime.mutableStateOf
import androidx.compose.runtime.remember
import androidx.compose.runtime.setValue
import androidx.compose.ui.Alignment
import androidx.compose.ui.Modifier
import androidx.compose.ui.draw.clip
import androidx.compose.ui.unit.dp
import androidx.compose.ui.viewinterop.AndroidView
import com.wetinknext.engine.core.EditorUiState
import com.wetinknext.engine.core.LayerUiModel
import com.wetinknext.engine.core.PaintSurfaceView
import com.wetinknext.ui.theme.WetInkNextPalette

/** P7 shell: Compose reads immutable engine snapshots and posts commands to PaintSurfaceView. */
@Composable
fun EditorScreen() {
    val palette = WetInkNextPalette.default
    var uiState by remember { mutableStateOf(EditorUiState.empty) }
    var surface by remember { mutableStateOf<PaintSurfaceView?>(null) }

    Box(
        modifier = Modifier
            .fillMaxSize()
            .background(palette.appBg),
    ) {
        AndroidView(
            modifier = Modifier.fillMaxSize(),
            factory = { context ->
                PaintSurfaceView(context).also { view ->
                    view.onEditorStateChange = { uiState = it }
                    surface = view
                    view.requestState()
                }
            },
        ),

        EditorTopBar(
            state = uiState,
            palette = palette,
            modifier = Modifier
                .align(Alignment.TopCenter)
                .padding(top = 12.dp),
        )
    }

```

```

        onUndo = { surface?.undo() },
        onRedo = { surface?.redo() },
    )

    BrushControls(
        state = uiState,
        palette = palette,
        modifier = Modifier
            .align(Alignment.BottomStart)
            .padding(12.dp),
        onBrushSizeCommit = { surface?.setBrushSize(it) },
        onBrushOpacityCommit = { surface?.setBrushOpacity(it) },
    )

    LayersPanel(
        state = uiState,
        palette = palette,
        modifier = Modifier
            .align(Alignment.CenterEnd)
            .padding(end = 12.dp)
            .width(300.dp),
        onSelectLayer = { surface?.setActiveLayer(it) },
        onAddLayer = { surface?.addLayer() },
        onDeleteLayer = { surface?.removeLayer(it) },
        onLayerVisible = { id, visible -> surface?.setLayerVisible(id, visible) },
        onLayerOpacity = { id, opacity -> surface?.setLayerOpacity(id, opacity) },
    )
}

@Composable
private fun EditorTopBar(
    state: EditorUiState,
    palette: WetInkNextPalette,
    modifier: Modifier = Modifier,
    onUndo: () -> Unit,
    onRedo: () -> Unit,
) {
    Row(
        modifier = modifier
            .background(palette.panelBg.copy(alpha = 0.94f), RoundedCornerShape(24.dp))
            .border(1.dp, palette.panelStroke, RoundedCornerShape(24.dp))
            .padding(horizontal = 8.dp, vertical = 4.dp),
        verticalAlignment = Alignment.CenterVertically,
        horizontalArrangement = Arrangement.spacedBy(4.dp),
    ) {
        TextButton(onClick = onUndo, enabled = state.canUndo) { Text("Undo") }
        TextButton(onClick = onRedo, enabled = state.canRedo) { Text("Redo") }
    }
}

@Composable
private fun BrushControls(
    state: EditorUiState,
    palette: WetInkNextPalette,
    modifier: Modifier = Modifier,
    onBrushSizeCommit: (Float) -> Unit,
    onBrushOpacityCommit: (Float) -> Unit,
) {
    Column(
        modifier = modifier.panel(palette).width(260.dp).padding(14.dp),
        verticalArrangement = Arrangement.spacedBy(10.dp),
    ) {
        Text(text = "Кисть", color = palette.textPrimary)
        CommitSlider(
            label = "Размер",
            value = state.brushSizePx,
            range = 1f..200f,
            palette = palette,
            format = { "${it.toInt()} px" },
            onCommit = onBrushSizeCommit,
        )
        CommitSlider(
            label = "Непрозрачность",
            value = state.brushOpacity,
            range = 0f..1f,
            palette = palette,
            format = { "${(it * 100f).toInt()}%" },
            onCommit = onBrushOpacityCommit,
        )
    }
}

@Composable
private fun LayersPanel(
    state: EditorUiState,
    palette: WetInkNextPalette,
    modifier: Modifier = Modifier,
    onSelectLayer: (Long) -> Unit,
    onAddLayer: () -> Unit,
    onDeleteLayer: (Long) -> Unit,
    onLayerVisible: (Long, Boolean) -> Unit,

```

```

        onLayerOpacity: (Long, Float) -> Unit,
    ) {
        Column(
            modifier = modifier.panel(palette).padding(14.dp),
            verticalArrangement = Arrangement.spacedBy(10.dp),
        ) {
            Row(
                modifier = Modifier.fillMaxWidth(),
                verticalAlignment = Alignment.CenterVertically,
            ) {
                Text(text = "Сюж", color = palette.textPrimary, modifier = Modifier.weight(1f))
                TextButton(onClick = onAddLayer, enabled = state.ready) { Text("Добавить") }
            }

            LazyColumn(
                modifier = Modifier.heightIn(max = 380.dp),
                verticalArrangement = Arrangement.spacedBy(8.dp),
            ) {
                items(items = state.layers.asReversed(), key = LayerUiModel::id) { layer ->
                    LayerRow(
                        layer = layer,
                        palette = palette,
                        onSelect = { onSelectLayer(layer.id) },
                        onDelete = { onDeleteLayer(layer.id) },
                        onVisible = { visible -> onLayerVisible(layer.id, visible) },
                        onOpacity = { opacity -> onLayerOpacity(layer.id, opacity) },
                    )
                }
            }
        }
    }
}

@Composable
private fun LayerRow(
    layer: LayerUiModel,
    palette: WetInkNextPalette,
    onSelect: () -> Unit,
    onDelete: () -> Unit,
    onVisible: (Boolean) -> Unit,
    onOpacity: (Float) -> Unit,
) {
    Column(
        modifier = Modifier
            .fillMaxWidth()
            .clip(RoundedCornerShape(14.dp))
            .background(if (layer.active) palette.accent.copy(alpha = 0.18f) else palette.panelBg.copy(alpha = 0.72f))
            .border(1.dp, if (layer.active) palette.accent else palette.panelStroke, RoundedCornerShape(14.dp))
            .clickable(onClick = onSelect)
            .padding(10.dp),
        verticalArrangement = Arrangement.spacedBy(8.dp),
    ) {
        Row(
            modifier = Modifier.fillMaxWidth(),
            verticalAlignment = Alignment.CenterVertically,
        ) {
            Checkbox(checked = layer.isVisible, onCheckedChange = onVisible)
            Text(text = layer.name, color = palette.textPrimary, modifier = Modifier.weight(1f))
            if (layer.canDelete) TextButton(onClick = onDelete) { Text("Удалить") }
        }
        if (layer.active) {
            CommitSlider(
                label = "Непрозрачность",
                value = layer.opacity,
                range = 0f..1f,
                palette = palette,
                format = { "${(it * 100f).toInt()}%" },
                onCommit = onOpacity,
            )
        }
    }
}

@Composable
private fun CommitSlider(
    label: String,
    value: Float,
    range: ClosedFloatingPointRange<Float>,
    palette: WetInkNextPalette,
    format: (Float) -> String,
    onCommit: (Float) -> Unit,
) {
    var localValue by remember(value) { mutableStateOf(value) }
    Column(modifier = Modifier.fillMaxWidth(), verticalArrangement = Arrangement.spacedBy(4.dp)) {
        Row(modifier = Modifier.fillMaxWidth(), verticalAlignment = Alignment.CenterVertically) {
            Text(text = label, color = palette.textSecondary, modifier = Modifier.weight(1f))
            Text(text = format(localValue), color = palette.textPrimary)
        }
        Slider(
            value = localValue,
            onValueChange = { localValue = it },
            onValueChangeFinished = { onCommit(localValue) },
            valueRange = range,
        )
    }
}

```

```

    )
}
}

private fun Modifier.panel(palette: WetInkNextPalette): Modifier =
    background(palette.panelBg.copy(alpha = 0.94f), RoundedCornerShape(24.dp))
        .border(1.dp, palette.panelStroke, RoundedCornerShape(24.dp))

```

## app/src/main/java/com/wetinknext/app/MainActivity.kt

```

package com.wetinknext.app

import android.os.Bundle
import androidx.activity.ComponentActivity
import androidx.activity.compose.setContent

class MainActivity : ComponentActivity() {
    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        setContent { EditorScreen() }
    }
}

```

## app/src/main/java/com/wetinknext/engine/brush/BrushSettings.kt

```

package com.wetinknext.engine.brush

enum class BrushRenderMode { STAMP, RIBBON, WET }
enum class BlendPolicy { NORMAL_BUILDUP, NON_BUILDUP }
data class RibbonSettings(val minWidthRatio: Float = 0.06f, val taperStartPx: Float = 8f, val taperEndPx: Float = 14f, val miterLimit: Float = 3f, val aaWidth: Float = 1f)
data class WetSettings(val wetness: Float = 0f, val spread: Float = 0f, val bleed: Float = 0f)
data class BrushSettings(
    val name: String = "Debug Stamp", val category: String = "Debug", val renderMode: BrushRenderMode = BrushRenderMode.STAMP,
    val baseRadiusPx: Float = 14f, val opacity: Float = 1f, val flow: Float = 1f, val spacing: Float = 0.16f,
    val spacingUsesDiameter: Boolean = true, val hardness: Float = 1f, val colorArgb: Long = 0xFF000000L,
    val smoothing: Float = 0f, val streamline: Float = 0f, val antiAliasLevel: Int = 2, val useTempStrokeBuffer: Boolean = false,
    val pressureToSize: Boolean = true, val pressureToOpacity: Boolean = true, val pressureGamma: Float = 1f,
    val minSizeRatio: Float = 0.05f, val velocityToSize: Float = 0f, val velocityToOpacity: Float = 0f,
    val tiltToSize: Float = 0f, val tiltToOpacity: Float = 0f, val tiltToRotation: Float = 0f,
    val rotationJitter: Float = 0f, val sizeJitter: Float = 0f, val opacityJitter: Float = 0f, val scatter: Float = 0f,
    val shapeAssetPath: String? = null, val grainAssetPath: String? = null, val grainScale: Float = 1f,
    val grainCanvasLocked: Boolean = true, val rgbToAlpha: Boolean = false, val textureContrast: Float = 1f,
    val textureDepth: Float = 1f, val pixelPen: Boolean = false, val squareStroke: Boolean = false,
    val noAntialias: Boolean = false, val blendPolicy: BlendPolicy = BlendPolicy.NORMAL_BUILDUP,
    val ribbon: RibbonSettings = RibbonSettings(), val wet: WetSettings = WetSettings(),
)

```

## app/src/main/java/com/wetinknext/engine/brush/ColorSpaces.kt

```

package com.wetinknext.engine.brush

import kotlin.math.pow

object ColorSpaces {
    fun srgbToLinear(value: Float): Float { val v=value.coerceIn(0f,1f); return if(v<=.04045f)v/12.92f else ((v+.055f)/1.055f).pow(2.4f) }
    fun linearToSrgb(value: Float): Float { val v=value.coerceIn(0f,1f); return if(v<=.0031308f)v*12.92f else 1.055f*v.pow(1f/2.4f)-.055f }
    fun srgb8ToLinear(rgba: Long,out:FloatArray){require(out.size>=3);out[0]=srgbToLinear(((rgba shr 16)and 0xFF)/255f);out[1]=srgbToLinear(((rgba shr 8)and 0xFF)/255f);out[2]=srgbToLinear(rgba and 0xFF)/255f}
}

```

## app/src/main/java/com/wetinknext/engine/brush/DabBuffer.kt

```

package com.wetinknext.engine.brush

import java.nio.ByteBuffer
import java.nio.ByteOrder

class DabBuffer(val capacity: Int = DEFAULT_CAPACITY) {
    init { require(capacity > 0) }
    val floats = ByteBuffer.allocateDirect(capacity * FLOATS_PER_DAB * Float.SIZE_BYTES).order(ByteOrder.nativeOrder()).asFloatBuffer()
    var count = 0; private set; var overflowCount = 0L; private set
    fun clear() { count = 0; overflowCount = 0L; floats.clear() }
    fun add(x: Float, y: Float, radius: Float, rotation: Float, alpha: Float): Boolean { if (count >= capacity) { overflowCount++; return false }; floats.put(x,y,radius,rotation,alpha) }
    fun prepareForUpload() { floats.position(0); floats.limit(count * FLOATS_PER_DAB) }
    /** Restores the direct buffer for appending after a GL upload. */
    fun finishUpload() {
        floats.limit(capacity * FLOATS_PER_DAB)
        floats.position(count * FLOATS_PER_DAB)
    }
    companion object { const val FLOATS_PER_DAB = 5; const val DEFAULT_CAPACITY = 8192 }
}

```

## app/src/main/java/com/wetinknext/engine/brush/DabRenderer.kt

```

package com.wetinknext.engine.brush

import android.opengl.GLES30
import com.wetinknext.engine.gl.GlProgram
import com.wetinknext.engine.gl.RenderTarget
import com.wetinknext.engine.gl.ShaderLib

```

```

import java.nio.ByteBuffer
import java.nio.ByteOrder

/** Instanced circular dab renderer. All colour values are premultiplied linear output. */
class DabRenderer(private val maxDabs: Int) {
    private var program: GLProgram? = null
    private var vaoId = 0
    private var quadBufferId = 0
    private var instanceBufferId = 0
    private var uCanvasToClip = -1
    private var uColorLinear = -1

    fun create() {
        release()
        program = GLProgram(ShaderLib.dabVertex, ShaderLib.dabFragment)
        val currentProgram = checkNotNull(program)
        currentProgram.use()
        uCanvasToClip = GLES30.glGetUniformLocation(currentProgram.id, "uCanvasToClip")
        uColorLinear = GLES30.glGetUniformLocation(currentProgram.id, "uColorLinear")
        check(uCanvasToClip >= 0 && uColorLinear >= 0) { "Dab shader uniforms missing" }

        val quad = floatArrayOf(-1f, -1f, 1f, -1f, -1f, 1f, 1f, 1f)
        val quadData = ByteBuffer.allocateDirect(quad.size * Float.SIZE_BYTES)
            .order(ByteOrder.nativeOrder())
            .asFloatBuffer()
        quadData.put(quad).position(0)

        val ids = IntArray(1)
        GLES30.glGenVertexArrays(1, ids, 0)
        vaoId = ids[0]
        GLES30.glGenBuffers(1, ids, 0)
        quadBufferId = ids[0]
        GLES30.glGenBuffers(1, ids, 0)
        instanceBufferId = ids[0]

        GLES30.glBindVertexArray(vaoId)
        GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, quadBufferId)
        GLES30.glBufferData(
            GLES30.GL_ARRAY_BUFFER,
            quad.size * Float.SIZE_BYTES,
            quadData,
            GLES30.GL_STATIC_DRAW,
        )
        GLES30.glEnableVertexAttribArray(0)
        GLES30.glVertexAttribPointer(0, 2, GLES30.GL_FLOAT, false, 0, 0)

        GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, instanceBufferId)
        GLES30.glBufferData(
            GLES30.GL_ARRAY_BUFFER,
            maxDabs * DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES,
            null,
            GLES30.GL_DYNAMIC_DRAW,
        )
        GLES30.glEnableVertexAttribArray(1)
        GLES30.glVertexAttribPointer(1, 4, GLES30.GL_FLOAT, false, 20, 0)
        GLES30.glVertexAttribDivisor(1, 1)
        GLES30.glEnableVertexAttribArray(2)
        GLES30.glVertexAttribPointer(2, 1, GLES30.GL_FLOAT, false, 20, 16)
        GLES30.glVertexAttribDivisor(2, 1)
        GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0)
        GLES30.glBindVertexArray(0)
    }

    /** Draws all buffered dabs into a document-space RenderTarget. */
    fun drawInto(
        target: RenderTarget,
        width: Int,
        height: Int,
        canvasToFbo: FloatArray,
        dabs: DabBuffer,
        colorLinear: FloatArray,
    ) {
        if (dabs.count == 0) return
        val currentProgram = program ?: return
        require(colorLinear.size >= 3)

        target.bind()
        GLES30.glViewport(0, 0, width, height)
        GLES30.glEnable(GLES30.GL_BLEND)
        GLES30.glBlendEquation(GLES30.GL_FUNC_ADD)
        GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)

        currentProgram.use()
        GLES30.glUniformMatrix4fv(uCanvasToClip, 1, false, canvasToFbo, 0)
        GLES30.glUniform3fv(uColorLinear, colorLinear[0], colorLinear[1], colorLinear[2])
        dabs.prepareForUpload()
        GLES30.glBindVertexArray(vaoId)
        GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, instanceBufferId)
        GLES30.glBufferSubData(
            GLES30.GL_ARRAY_BUFFER,
            0,
            dabs.count * DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES,

```

```

dabs.floats,
)
dabs.finishUpload()
GL ES30.glDrawArraysInstanced(GL ES30.GL_TRIANGLE_STRIP, 0, 4, dabs.count)
GL ES30.glBindBuffer(GL ES30.GL_ARRAY_BUFFER, 0)
GL ES30.glBindVertexArray(0)
GL ES30.glDisable(GL ES30.GL_BLEND)
GL ES30.glBindFramebuffer(GL ES30.GL_FRAMEBUFFER, 0)
}

fun release() {
    program?.release()
    program = null
    if (instanceBufferId != 0) GL ES30.glDeleteBuffers(1, intArrayOf(instanceBufferId), 0)
    if (quadBufferId != 0) GL ES30.glDeleteBuffers(1, intArrayOf(quadBufferId), 0)
    if (vaoId != 0) GL ES30.glDeleteVertexArrays(1, intArrayOf(vaoId), 0)
    vaoId = 0
    quadBufferId = 0
    instanceBufferId = 0
    uCanvasToClip = -1
    uColorLinear = -1
}
}

```

## app/src/main/java/com/wetinknext/engine/brush/OneEuroFilter.kt

```
package com.wetinknext.engine.brush
```

```
import kotlin.math.PI
import kotlin.math.sqrt
```

```
class OneEuroFilter(private var minutoff: Float = 1.6f, private var beta: Float = 0.25f, private var dCutoff: Float = 1f) {
    private var initialized = false; private var lastTimestampNanos = 0L
    private var x = 0f; private var y = 0f; private var dx = 0f; private var dy = 0f
    fun reset() { initialized = false; lastTimestampNanos = 0L; x = 0f; y = 0f; dx = 0f; dy = 0f }
    fun filter(timestampNanos: Long, rawX: Float, rawY: Float, out: FloatArray) {
        require(out.size >= 2)
        if (!initialized) { initialized = true; lastTimestampNanos = timestampNanos; x = rawX; y = rawY; out[0] = x; out[1] = y; return }
        var dt = (timestampNanos - lastTimestampNanos) / 1_000_000_000f
        if (dt < MIN_DT) dt = MIN_DT
        lastTimestampNanos = timestampNanos
        val rate = 1f / dt; val alphaD = alpha(rate, dCutoff)
        dx = alphaD * ((rawX - x) * rate) + (1f - alphaD) * dx; dy = alphaD * ((rawY - y) * rate) + (1f - alphaD) * dy
        val alpha = alpha(rate, (minCutoff + beta * sqrt(dx * dx + dy * dy)).coerceAtLeast(0.01f))
        x = alpha * rawX + (1f - alpha) * x; y = alpha * rawY + (1f - alpha) * y; out[0] = x; out[1] = y
    }
    private fun alpha(rate: Float, cutoff: Float): Float { val tau = 1f / (2f * PI.toFloat() * cutoff); return 1f / (1f + tau * rate) }
    private companion object { const val MIN_DT = 1f / 1000f }
}
```

## app/src/main/java/com/wetinknext/engine/brush/Stabilizer.kt

```
package com.wetinknext.engine.brush
```

```
import kotlin.math.sqrt
```

```
class Stabilizer(private val filter: OneEuroFilter = OneEuroFilter()) {
    var strength = 0f; var x = 0f; private set; var y = 0f; private set; var velocity = 0f; private set
    private var hasLast = false; private var lastX = 0f; private var lastY = 0f; private var lastT = 0L; private val filtered = FloatArray(2)
    fun reset() { filter.reset(); x = 0f; y = 0f; velocity = 0f; hasLast = false; lastX = 0f; lastY = 0f; lastT = 0L }
    fun process(timestampNanos: Long, rawX: Float, rawY: Float) {
        if (strength <= 0f) { x = rawX; y = rawY } else { filter.filter(timestampNanos, rawX, rawY, filtered); x = filtered[0]; y = filtered[1] }
        if (hasLast) { var dt = (timestampNanos - lastT) / 1_000_000_000f; if (dt < 1f / 1000f) dt = 1f / 1000f; val d = sqrt((x-lastX)*(x-lastX)+(y-lastY)*(y-lastY));
            hasLast = true; lastX = x; lastY = y; lastT = timestampNanos
        }
    }
}
```

## app/src/main/java/com/wetinknext/engine/brush/StampEmitter.kt

```
package com.wetinknext.engine.brush
```

```
import com.wetinknext.engine.input.InputBatch
import kotlin.math.pow
import kotlin.math.sqrt
```

```

class StampEmitter(initialSettings: BrushSettings) {
    var settings: BrushSettings = initialSettings
    private set

    fun updateSettings(newSettings: BrushSettings) {
        settings = newSettings
    }

    private val stabilizer = Stabilizer(); private var active = false; private var pointerId = -1; private var hasLast = false
    private var lastX = 0f; private var lastY = 0f; private var lastPressure = 0f; private var carried = 0f; private var spacingPx = 1f
    fun reset() { active = false; pointerId = -1; hasLast = false; carried = 0f; stabilizer.reset() }
    fun begin(batch: InputBatch, out: DabBuffer) { reset(); if (batch.isEmpty()) return; stabilizer.strength = (settings.smoothing*.7f + settings.streamline*
    fun append(batch: InputBatch, out: DabBuffer) { if(!active)return; for(i in 0 until batch.sampleCount){val s=batch.samples[i];if(s.pointerId==pointerId){
    fun finish(out: DabBuffer, cancel: Boolean) { if(active && !cancel && carried > .001f) addDab(lastX,lastY,lastPressure,out); reset() }
    private fun addPoint(x:Float,y:Float,p:Float,out:DabBuffer){ val dx=x-lastX;val dy=y-lastY;val dist=sqrt(dx*dx+dy*dy);if(!hasLast||dist<1e-5f){lastX=x;la

```

```

    private fun addDab(x:Float,y:Float,p:Float,out:DabBuffer){val pressure=p.coerceIn(0f,1f).let{if(settings.pressureGamma>0f)it.pow(settings.pressureGamma)}
}

```

## app/src/main/java/com/wetinknext/engine/canvas/BlendMode.kt

```

package com.wetinknext.engine.canvas

/** Stored per layer now; shader implementations beyond NORMAL are scheduled after P6. */
enum class BlendMode(val id: Int) {
    NORMAL(0),
    MULTIPLY(1),
    SCREEN(2),
    OVERLAY(3),
    DARKEN(4),
    LIGHTEN(5),
    ADD(6),
}

```

## app/src/main/java/com/wetinknext/engine/canvas/Compositor.kt

```

package com.wetinknext.engine.canvas

import android.opengl.GLES30
import com.wetinknext.engine.gl.CanvasGeometry
import com.wetinknext.engine.gl.GlCheck
import com.wetinknext.engine.gl.GlProgram
import com.wetinknext.engine.gl.ShaderLib

/** Presents visible layers bottom-to-top, inserting the active preview at its layer position. */
class Compositor {
    private var program: GlProgram? = null
    private var uCanvasToClip = -1
    private var uCanvasSize = -1
    private var uLayerTex = -1
    private var uStrokeTex = -1
    private var uStrokeActive = -1
    private var uOpacity = -1

    fun create() {
        release()
        program = GlProgram(ShaderLib.compositorVertex, ShaderLib.compositorFragment)
        val currentProgram = checkNotNull(program)
        currentProgram.use()
        uCanvasToClip = GLES30.glGetUniformLocation(currentProgram.id, "uCanvasToClip")
        uCanvasSize = GLES30.glGetUniformLocation(currentProgram.id, "uCanvasSize")
        uLayerTex = GLES30.glGetUniformLocation(currentProgram.id, "uLayerTex")
        uStrokeTex = GLES30.glGetUniformLocation(currentProgram.id, "uStrokeTex")
        uStrokeActive = GLES30.glGetUniformLocation(currentProgram.id, "uStrokeActive")
        uOpacity = GLES30.glGetUniformLocation(currentProgram.id, "uOpacity")
        check(uCanvasToClip >= 0 && uCanvasSize >= 0 && uLayerTex >= 0 &&
            uStrokeTex >= 0 && uStrokeActive >= 0 && uOpacity >= 0) {
            "Compositor uniforms missing: canvasToClip=$uCanvasToClip, " +
                "canvasSize=$uCanvasSize, layerTex=$uLayerTex, strokeTex=$uStrokeTex, " +
                "strokeActive=$uStrokeActive, opacity=$uOpacity"
        }
        GlCheck.noError("Compositor create")
    }

    fun render(
        geometry: CanvasGeometry,
        layers: LayerStack,
        activeLayerId: Long,
        strokeTextureId: Int,
        canvasToClip: FloatArray,
    ) {
        val currentProgram = program ?: return
        currentProgram.use()
        GLES30.glUniformMatrix4fv(uCanvasToClip, 1, false, canvasToClip, 0)
        GLES30.glUniform2f(uCanvasSize, layers.canvasWidth.toFloat(), layers.canvasHeight.toFloat())
        GLES30.glEnable(GLES30.GL_BLEND)
        GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)

        for (layer in layers.allLayers()) {
            if (!layer.created || !layer.isVisible) continue
            val hasStroke = layer.id == activeLayerId && strokeTextureId != 0

            GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
            GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, layer.target.textureId)
            GLES30.glUniform1i(uLayerTex, 0)
            if (hasStroke) {
                GLES30.glActiveTexture(GLES30.GL_TEXTURE1)
                GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, strokeTextureId)
                GLES30.glUniform1i(uStrokeTex, 1)
            }
            GLES30.glUniform1i(uStrokeActive, if (hasStroke) 1 else 0)
            GLES30.glUniform1f(uOpacity, layer.opacity.coerceIn(0f, 1f))
            geometry.draw()
        }

        GLES30.glDisable(GLES30.GL_BLEND)
        GLES30.glActiveTexture(GLES30.GL_TEXTURE1)
    }
}

```

```

        GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
        GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
        GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
    }

    fun release() {
        program?.release()
        program = null
        uCanvasToClip = -1
        uCanvasSize = -1
        uLayerTex = -1
        uStrokeTex = -1
        uStrokeActive = -1
        uOpacity = -1
    }
}

```

## app/src/main/java/com/wetinknext/engine/canvas/LayerStack.kt

```

package com.wetinknext.engine.canvas

import com.wetinknext.engine.core.Camera
import com.wetinknext.engine.gl.GLCaps

/**
 * Render-thread-owned ordered collection of document layers.
 * Index 0 is the bottom-most layer and the final item is the top-most layer.
 */
class LayerStack {
    val camera = Camera()

    private val layers = mutableListOf<PaintLayer>()
    private var nextId = 1L

    var activeLayerId: Long = NO_LAYER
    private set
    var canvasWidth: Int = 0
    private set
    var canvasHeight: Int = 0
    private set

    val count: Int get() = layers.size

    fun allLayers(): List<PaintLayer> = layers

    fun activeLayer(): PaintLayer? = findLayerById(activeLayerId)

    fun findLayerById(id: Long): PaintLayer? = layers.firstOrNull { it.id == id }

    /** Creates the locked opaque white background and one transparent drawing layer. */
    fun create(caps: GLCaps, width: Int, height: Int) {
        require(width > 0 && height > 0)
        release()
        canvasWidth = width
        canvasHeight = height

        val background = newLayer("Фон", caps.supportsHalfFloatColorBuffer).also {
            it.isLocked = true
            it.target.clear(1f, 1f, 1f, 1f)
        }
        layers += background

        val drawing = newLayer("Слой 1", caps.supportsHalfFloatColorBuffer)
        layers += drawing
        activeLayerId = drawing.id
    }

    fun addLayer(name: String, insertAt: Int = layers.size): PaintLayer {
        check(canvasWidth > 0 && canvasHeight > 0) { "LayerStack has not been created" }
        val layer = newLayer(name, activeLayer()?.target?.usesHalfFloat == true)
        layers.add(insertAt.coerceIn(0, layers.size), layer)
        activeLayerId = layer.id
        return layer
    }

    /** A document must retain at least one layer; locked layers cannot be removed. */
    fun removeLayer(id: Long): PaintLayer? {
        val index = layers.indexOfFirst { it.id == id }
        if (index < 0 || layers.size <= 1) return null
        val layer = layers[index]
        if (layer.isLocked) return null

        layers.removeAt(index)
        layer.release()
        if (activeLayerId == id) {
            activeLayerId = layers[index.coerceAtMost(layers.lastIndex)].id
        }
        return layer
    }

    fun setActive(id: Long): Boolean {

```

```

        if (findLayerById(id) == null) return false
        activeLayerId = id
        return true
    }

    fun moveLayer(id: Long, delta: Int): Boolean {
        val index = layers.indexOfFirst { it.id == id }
        if (index < 0) return false
        val newIndex = (index + delta).coerceIn(0, layers.lastIndex)
        if (newIndex == index) return false
        val layer = layers.removeAt(index)
        layers.add(newIndex, layer)
        return true
    }

    fun release() {
        layers.forEach(PaintLayer::release)
        layers.clear()
        activeLayerId = NO_LAYER
        canvasWidth = 0
        canvasHeight = 0
    }

    private fun newLayer(name: String, useHalfFloat: Boolean): PaintLayer =
        PaintLayer(nextId++, name).also { it.create(canvasWidth, canvasHeight, useHalfFloat) }

    private companion object {
        const val NO_LAYER = -1L
    }
}

```

## app/src/main/java/com/wetinknext/engine/canvas/PaintLayer.kt

```

package com.wetinknext.engine.canvas

import com.wetinknext.engine.gl.RenderTarget

/** One paintable document layer and its private GPU target. */
class PaintLayer(
    val id: Long,
    var name: String,
) {
    val target = RenderTarget()

    var isVisible = true
    var isLocked = false
    var opacity = 1f
    var blendMode = BlendMode.NORMAL
    var version = 0L

    var created = false
    private set

    fun create(width: Int, height: Int, preferHalfFloat: Boolean) {
        if (created && target.width == width && target.height == height) return
        target.create(width, height, preferHalfFloat)
        target.clear(0f, 0f, 0f, 0f)
        created = true
    }

    fun clear() {
        if (created) target.clear(0f, 0f, 0f, 0f)
    }

    fun release() {
        target.release()
        created = false
    }
}

```

## app/src/main/java/com/wetinknext/engine/core/Camera.kt

```

package com.wetinknext.engine.core

import java.util.concurrent.atomic.AtomicReference
import kotlin.math.min

/** Thread-safe camera state shared by the UI and GL threads. */
class Camera(initial: ViewTransform = ViewTransform()) {
    private val state = AtomicReference(initial)

    fun snapshot(): ViewTransform = state.get()

    fun set(transform: ViewTransform) {
        state.set(transform)
    }

    fun update(transform: (ViewTransform) -> ViewTransform) {
        while (true) {
            val current = state.get()
            if (state.compareAndSet(current, transform(current))) return
        }
    }
}

```

```

    }
}

fun reset() {
    state.set(ViewTransform())
}

fun fitCanvas(
    canvasWidth: Int,
    canvasHeight: Int,
    viewWidth: Int,
    viewHeight: Int,
    marginRatio: Float = 0.04f,
) {
    if (canvasWidth <= 0 || canvasHeight <= 0 || viewWidth <= 0 || viewHeight <= 0) return
    val usableWidth = viewWidth * (1f - marginRatio * 2f)
    val usableHeight = viewHeight * (1f - marginRatio * 2f)
    val scale = min(usableWidth / canvasWidth, usableHeight / canvasHeight)
        .coerceIn(ViewTransform.MIN_SCALE, ViewTransform.MAX_SCALE)
    state.set(
        ViewTransform(
            scale = scale,
            translateX = (viewWidth - canvasWidth * scale) * 0.5f,
            translateY = (viewHeight - canvasHeight * scale) * 0.5f,
        ),
    )
}
}
}

```

## app/src/main/java/com/wetinknext/engine/core/DirtyRect.kt

```

package com.wetinknext.engine.core

import kotlin.math.ceil
import kotlin.math.floor
import kotlin.math.max
import kotlin.math.min

/** Reusable mutable dirty rectangle in canvas coordinates. */
class DirtyRect {
    var left = 0f; private set
    var top = 0f; private set
    var right = 0f; private set
    var bottom = 0f; private set
    var isEmpty = true; private set

    fun clear() {
        left = 0f; top = 0f; right = 0f; bottom = 0f; isEmpty = true
    }

    fun include(x: Float, y: Float, radius: Float) = include(x - radius, y - radius, x + radius, y + radius)

    fun include(left: Float, top: Float, right: Float, bottom: Float) {
        if (right < left || bottom < top) return
        if (isEmpty) {
            this.left = left; this.top = top; this.right = right; this.bottom = bottom; isEmpty = false
            return
        }
        this.left = min(this.left, left); this.top = min(this.top, top)
        this.right = max(this.right, right); this.bottom = max(this.bottom, bottom)
    }

    fun include(other: DirtyRect) {
        if (!other.isEmpty) include(other.left, other.top, other.right, other.bottom)
    }

    fun expand(pixels: Float) {
        if (!isEmpty && pixels > 0f) {
            left -= pixels; top -= pixels; right += pixels; bottom += pixels
        }
    }

    fun clamp(canvasWidth: Float, canvasHeight: Float) {
        if (isEmpty) return
        left = left.coerceIn(0f, canvasWidth); top = top.coerceIn(0f, canvasHeight)
        right = right.coerceIn(0f, canvasWidth); bottom = bottom.coerceIn(0f, canvasHeight)
        if (right <= left || bottom <= top) clear()
    }

    fun copyTo(out: DirtyRect) {
        out.left = left; out.top = top; out.right = right; out.bottom = bottom; out.isEmpty = isEmpty
    }

    fun toPixelBounds(out: IntArray) {
        require(out.size >= 4)
        if (isEmpty) {
            out[0] = 0; out[1] = 0; out[2] = 0; out[3] = 0
            return
        }
        out[0] = floor(left).toInt(); out[1] = floor(top).toInt()
        out[2] = ceil(right).toInt(); out[3] = ceil(bottom).toInt()
    }
}

```

```
    }
}
```

## app/src/main/java/com/wetinknext/engine/core/EditorState.kt

```
package com.wetinknext.engine.core

/** Immutable state published by the GL thread for Compose to render. */
data class LayerUiModel(
    val id: Long,
    val name: String,
    val isVisible: Boolean,
    val isLocked: Boolean,
    val opacity: Float,
    val active: Boolean,
    val canDelete: Boolean,
)

data class EditorUiState(
    val layers: List<LayerUiModel>,
    val canUndo: Boolean,
    val canRedo: Boolean,
    val brushSizePx: Float,
    val brushOpacity: Float,
    val activeLayerId: Long,
    val ready: Boolean,
) {
    companion object {
        val empty = EditorUiState(
            layers = emptyList(),
            canUndo = false,
            canRedo = false,
            brushSizePx = 16f,
            brushOpacity = 1f,
            activeLayerId = -1L,
            ready = false,
        )
    }
}
```

## app/src/main/java/com/wetinknext/engine/core/EngineRenderer.kt

```
package com.wetinknext.engine.core

import android.opengl.GLES30
import android.opengl.GLSurfaceView
import android.view.MotionEvent
import com.wetinknext.engine.brush.BrushSettings
import com.wetinknext.engine.brush.ColorSpaces
import com.wetinknext.engine.brush.DabBuffer
import com.wetinknext.engine.brush.DabRenderer
import com.wetinknext.engine.brush.StampEmitter
import com.wetinknext.engine.canvas.Compositor
import com.wetinknext.engine.canvas.LayerStack
import com.wetinknext.engine.gl.CanvasGeometry
import com.wetinknext.engine.gl.GlCaps
import com.wetinknext.engine.gl.GlCheck
import com.wetinknext.engine.gl.RenderTarget
import com.wetinknext.engine.input.InputAction
import com.wetinknext.engine.input.InputBatch
import com.wetinknext.engine.input.InputBatchPool
import com.wetinknext.engine.input.StrokeInputCapturer
import com.wetinknext.engine.undo.TileSnapshotCapture
import com.wetinknext.engine.undo.TileSnapshotRestore
import com.wetinknext.engine.undo.UndoEntry
import com.wetinknext.engine.undo.UndoManager
import java.util.concurrent.ArrayBlockingQueue
import java.util.concurrent.atomic.AtomicBoolean
import javax.microedition.khronos.egl.EGLConfig
import javax.microedition.khronos.opengles.GL10

/**
 * The P6 render-thread owner. Active dabs are accumulated only in strokeTarget;
 * UP snapshots and merges them into the selected PaintLayer atomically.
 */
class EngineRenderer(
    private val documentWidth: Int = DEFAULT_CANVAS_WIDTH,
    private val documentHeight: Int = DEFAULT_CANVAS_HEIGHT,
) : GLSurfaceView.Renderer {
    private var caps: GlCaps? = null
    private val layerStack = LayerStack()
    private val undoManager = UndoManager()

    private var geometry: CanvasGeometry? = null
    private var compositor: Compositor? = null
    private var dabRenderer: DabRenderer? = null
    private val strokeTarget = RenderTarget()
    private val canvasToFboMatrix = FloatArray(16)
    private val canvasToClipMatrix = FloatArray(16)

    private var screenWidth = 1
```

```

private var screenHeight = 1

private val inputPool = InputBatchPool(batchCount = 64, maxSamplesPerBatch = 256)
private val inputQueue = ArrayBlockingQueue<InputBatch>(64)
private val inputCapturer = StrokeInputCapturer(layerStack.camera, inputPool, inputQueue)

private var brushSettings = BrushSettings(
    name = "Round Opaque",
    baseRadiusPx = 16f,
    spacing = 0.12f,
    colorArgb = 0xFF1B1F24L,
    smoothing = 0.25f,
    streamline = 0.05f,
    pressureToOpacity = false,
    pressureGamma = 1.1f,
    minSizeRatio = 0.12f,
)

private val stampEmitter = StampEmitter(brushSettings)
private val dabBuffer = DabBuffer()
private val strokeColorLinear = FloatArray(3)
private val strokeDirtyRect = DirtyRect()
private val dirtyBounds = IntArray(4)

private var strokeActive = false
private val cancelRequested = AtomicBoolean(false)

/** Assigned by PaintSurfaceView; invoked on the GL thread. */
var onStateChange: ((EditorUiState) -> Unit)? = null

fun onTouchEvent(event: MotionEvent): Boolean = inputCapturer.onTouchEvent(event)

/** These methods are called from GLSurfaceView.queueEvent by the UI layer. */
fun undo() {
    resetStroke()
    val entry = undoManager.popUndo() ?: return
    val layer = layerStack.findLayerById(entry.layerId) ?: return
    TileSnapshotRestore.restore(layer.target, entry.beforeTiles)
    layer.version++
    publishState()
}

fun redo() {
    resetStroke()
    val entry = undoManager.popRedo() ?: return
    val layer = layerStack.findLayerById(entry.layerId) ?: return
    TileSnapshotRestore.restore(layer.target, entry.afterTiles)
    layer.version++
    publishState()
}

fun setActiveLayer(id: Long): Boolean {
    resetStroke()
    return layerStack.setActive(id).also { changed ->
        if (changed) publishState()
    }
}

fun addLayer(): Long = addLayer(nextLayerName())

fun addLayer(name: String): Long {
    resetStroke()
    return layerStack.addLayer(name).id.also { publishState() }
}

fun removeLayer(id: Long): Boolean {
    resetStroke()
    return (layerStack.removeLayer(id) != null).also { removed ->
        if (removed) publishState()
    }
}

fun setLayerVisible(id: Long, visible: Boolean) {
    resetStroke()
    val layer = layerStack.findLayerById(id) ?: return
    layer.isVisible = visible
    publishState()
}

fun setLayerOpacity(id: Long, opacity: Float) {
    val layer = layerStack.findLayerById(id) ?: return
    layer.opacity = opacity.coerceIn(0f, 1f)
    publishState()
}

fun setBrushSize(px: Float) {
    resetStroke()
    brushSettings = brushSettings.copy(baseRadiusPx = px.coerceIn(1f, 200f))
    stampEmitter.updateSettings(brushSettings)
    publishState()
}

fun setBrushOpacity(opacity: Float) {

```

```

        resetStroke()
        brushSettings = brushSettings.copy(opacity = opacity.coerceIn(0f, 1f))
        stampEmitter.updateSettings(brushSettings)
        publishState()
    }

    fun requestState() {
        publishState()
    }

    override fun onSurfaceCreated(gl: GL10?, config: EGLConfig?) {
        releaseGLObjects()
        val nextCaps = GLCaps.query()
        caps = nextCaps
        layerStack.create(nextCaps, documentWidth, documentHeight)
        strokeTarget.create(documentWidth, documentHeight, nextCaps.supportsHalfFloatColorBuffer)
        strokeTarget.clear(0f, 0f, 0f, 0f)
        ViewTransform.buildCanvasToFbo(
            documentWidth.toFloat(),
            documentHeight.toFloat(),
            canvasToFboMatrix,
        )
        geometry = CanvasGeometry().also { it.create(documentWidth, documentHeight) }
        compositor = Compositor().also { it.create() }
        dabRenderer = DabRenderer(dabBuffer.capacity).also { it.create() }
        ColorSpaces.srgb8ToLinear(brushSettings.colorArgb, strokeColorLinear)
        publishState()
        GLCheck.noError("P6 surface creation")
    }

    override fun onSurfaceChanged(gl: GL10?, width: Int, height: Int) {
        screenWidth = width.coerceAtLeast(1)
        screenHeight = height.coerceAtLeast(1)
        GLES30.glViewport(0, 0, screenWidth, screenHeight)
        layerStack.camera.fitCanvas(layerStack.canvasWidth, layerStack.canvasHeight, screenWidth, screenHeight)
        GLCheck.noError("P6 surface changed")
    }

    override fun onDrawFrame(gl: GL10?) {
        if (cancelRequested.compareAndSet(true, false)) resetStroke()
        drainInput()

        if (strokeActive && dabBuffer.count > 0) {
            strokeTarget.clear(0f, 0f, 0f, 0f)
            dabRenderer?.drawInto(
                target = strokeTarget,
                width = layerStack.canvasWidth,
                height = layerStack.canvasHeight,
                canvasToFbo = canvasToFboMatrix,
                dabs = dabBuffer,
                colorLinear = strokeColorLinear,
            )
        }

        GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
        GLES30.glViewport(0, 0, screenWidth, screenHeight)
        GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
        GLES30.glDisable(GLES30.GL_BLEND)
        GLES30.glClearColor(0.08f, 0.09f, 0.12f, 1f)
        GLES30.glClear(GLES30.GL_COLOR_BUFFER_BIT)

        layerStack.camera.snapshot().buildCanvasToClip(
            screenWidth.toFloat(),
            screenHeight.toFloat(),
            canvasToClipMatrix,
        )
        compositor?.render(
            geometry = geometry ?: return,
            layers = layerStack,
            activeLayerId = layerStack.activeLayerId,
            strokeTextureId = if (strokeActive && dabBuffer.count > 0) strokeTarget.textureId else 0,
            canvasToClip = canvasToClipMatrix,
        )
    }

    /** Safe to call from the UI thread; cancellation is executed on the next GL frame. */
    fun cancelActiveStroke() {
        cancelRequested.set(true)
    }

    /** Must run on the GL thread while the context is still current. */
    fun releaseGLObjects() {
        discardPendingInput()
        strokeActive = false
        stampEmitter.reset()
        dabBuffer.clear()
        undoManager.clear()
        dabRenderer?.release()
        dabRenderer = null
        compositor?.release()
        compositor = null
        geometry?.release()
    }

```

```

        geometry = null
        strokeTarget.release()
        layerStack.release()
        caps = null
    }

private fun drainInput() {
    while (true) {
        val batch = inputQueue.poll() ?: return
        try {
            when (batch.action) {
                InputAction.DOWN -> {
                    if (!batch.isEmpty()) {
                        resetStroke()
                        strokeActive = true
                        ColorSpaces.srgb8ToLinear(batch.settings.colorArgb, strokeColorLinear)
                        stampEmitter.begin(batch, dabBuffer)
                    }
                }

                InputAction.MOVE -> if (strokeActive) {
                    stampEmitter.append(batch, dabBuffer)
                }

                InputAction.UP -> if (strokeActive) {
                    stampEmitter.finish(dabBuffer, cancel = false)
                    commitStroke()
                    resetStroke()
                }

                InputAction.CANCEL -> resetStroke()
            }
        } finally {
            inputPool.release(batch)
        }
    }
}

private fun commitStroke() {
    val layer = layerStack.activeLayer() ?: return
    if (layer.isLocked || dabBuffer.count == 0) return
    if (!computeDirtyPixelBounds(dirtyBounds)) return
    val renderer = dabRenderer ?: return

    // Both snapshots use the actual layer format (RGBA8 or RGBA16F).
    val beforeTiles = TileSnapshotCapture.capture(layer.target, dirtyBounds)
    renderer.drawInto(
        target = layer.target,
        width = layerStack.canvasWidth,
        height = layerStack.canvasHeight,
        canvasToFbo = canvasToFboMatrix,
        dabs = dabBuffer,
        colorLinear = strokeColorLinear,
    )
    layer.version++
    val afterTiles = TileSnapshotCapture.capture(layer.target, dirtyBounds)
    undoManager.push(UndoEntry(layer.id, beforeTiles, afterTiles))
    publishState()
}

/** Returns a clamped pixel region covering the exact emitted dabs and their AA fringe. */
private fun computeDirtyPixelBounds(out: IntArray): Boolean {
    if (dabBuffer.count == 0) return false
    strokeDirtyRect.clear()
    for (index in 0 until dabBuffer.count) {
        val offset = index * DabBuffer.FLOATS_PER_DAB
        val x = dabBuffer.floats.get(offset)
        val y = dabBuffer.floats.get(offset + 1)
        val radius = dabBuffer.floats.get(offset + 2)
        strokeDirtyRect.include(x, y, radius)
    }
    strokeDirtyRect.expand(AA_MARGIN_PX)
    strokeDirtyRect.clamp(layerStack.canvasWidth.toFloat(), layerStack.canvasHeight.toFloat())
    strokeDirtyRect.toPixelBounds(out)
    return out[2] > out[0] && out[3] > out[1]
}

private fun resetStroke() {
    strokeActive = false
    stampEmitter.reset()
    dabBuffer.clear()
    if (strokeTarget.framebufferId != 0) {
        strokeTarget.clear(0f, 0f, 0f, 0f)
    }
}

/** Releases pooled batches without interpreting them during shutdown/context recreation. */
private fun discardPendingInput() {
    while (true) {
        val batch = inputQueue.poll() ?: return
        inputPool.release(batch)
    }
}

```

```

    }

    private fun publishState() {
        val listener = onStateChange ?: return
        val layers = layerStack.allLayers()
        val activeLayerId = layerStack.activeLayerId
        val canDeleteLayers = layers.size > 1
        listener(
            EditorUiState(
                layers = layers.map { layer ->
                    LayerUiModel(
                        id = layer.id,
                        name = layer.name,
                        isVisible = layer.isVisible,
                        isLocked = layer.isLocked,
                        opacity = layer.opacity,
                        active = layer.id == activeLayerId,
                        canDelete = !layer.isLocked && canDeleteLayers,
                    )
                },
                canUndo = undoManager.canUndo,
                canRedo = undoManager.canRedo,
                brushSizePx = brushSettings.baseRadiusPx,
                brushOpacity = brushSettings.opacity,
                activeLayerId = activeLayerId,
                ready = layerStack.canvasWidth > 0 && layerStack.canvasHeight > 0,
            ),
        )
    }

    private fun nextLayerName(): String = "Слой ${layerStack.count + 1}"

    companion object {
        const val DEFAULT_CANVAS_WIDTH = 1500
        const val DEFAULT_CANVAS_HEIGHT = 2000
        private const val AA_MARGIN_PX = 2f
    }
}

```

## app/src/main/java/com/wetinknext/engine/core/PaintEngine.kt

```

package com.wetinknext.engine.core

import com.wetinknext.engine.canvas.LayerStack
import com.wetinknext.engine.gl.GLCaps
import com.wetinknext.engine.gl.RenderTarget

/** Lightweight document facade retained for engine callers outside the renderer. */
class PaintEngine {
    val layerStack = LayerStack()
    val camera: Camera get() = layerStack.camera
    val canvasTarget: RenderTarget get() = checkNotNull(layerStack.activeLayer()).target

    val canvasWidth: Int get() = layerStack.canvasWidth
    val canvasHeight: Int get() = layerStack.canvasHeight
    var initialized = false
    private set

    fun create(caps: GLCaps, width: Int, height: Int) {
        layerStack.create(caps, width, height)
        initialized = true
    }

    fun addLayer(name: String): Long = layerStack.addLayer(name).id

    fun removeLayer(id: Long): Boolean = layerStack.removeLayer(id) != null

    fun setActiveLayer(id: Long): Boolean = layerStack.setActive(id)

    fun release() {
        layerStack.release()
        initialized = false
    }
}

```

## app/src/main/java/com/wetinknext/engine/core/PaintSurfaceView.kt

```

package com.wetinknext.engine.core

import android.content.Context
import android.opengl.GLSurfaceView
import android.util.AttributeSet
import android.view.MotionEvent

/** Thread boundary between Compose commands and the GL-owned paint engine. */
class PaintSurfaceView @JvmOverloads constructor(
    context: Context,
    attrs: AttributeSet? = null,
) : GLSurfaceView(context, attrs) {
    private val engineRenderer = EngineRenderer()
}

```

```

var onEditorStateChange: ((EditorUiState) -> Unit)? = null

init {
    setEGLContextClientVersion(3)
    setRenderer(engineRenderer)
    renderMode = RENDERMODE_CONTINUOUSLY
    engineRenderer.onStateChange = { state ->
        post { onEditorStateChange?.invoke(state) }
    }
}

override fun onTouchEvent(event: MotionEvent): Boolean =
    engineRenderer.onTouchEvent(event) || super.onTouchEvent(event)

fun requestState() = queueEvent { engineRenderer.requestState() }

fun undo() = queueEvent { engineRenderer.undo() }

fun redo() = queueEvent { engineRenderer.redo() }

fun setActiveLayer(id: Long) = queueEvent { engineRenderer.setActiveLayer(id) }

fun addLayer() = queueEvent { engineRenderer.addLayer() }

fun removeLayer(id: Long) = queueEvent { engineRenderer.removeLayer(id) }

fun setLayerVisible(id: Long, visible: Boolean) =
    queueEvent { engineRenderer.setLayerVisible(id, visible) }

fun setLayerOpacity(id: Long, opacity: Float) =
    queueEvent { engineRenderer.setLayerOpacity(id, opacity) }

fun setBrushSize(px: Float) = queueEvent { engineRenderer.setBrushSize(px) }

fun setBrushOpacity(opacity: Float) = queueEvent { engineRenderer.setBrushOpacity(opacity) }

override fun onPause() {
    engineRenderer.cancelActiveStroke()
    super.onPause()
}

override fun onDetachedFromWindow() {
    queueEvent { engineRenderer.releaseGlobjects() }
    super.onDetachedFromWindow()
}
}

```

## app/src/main/java/com/wetinknext/engine/core/ViewTransform.kt

```

package com.wetinknext.engine.core

import kotlin.math.abs
import kotlin.math.cos
import kotlin.math.sin

/** Canonical canvas-to-view-local-screen transformation. */
data class ViewTransform(
    val translateX: Float = 0f,
    val translateY: Float = 0f,
    val scale: Float = 1f,
    val rotationRad: Float = 0f,
    val flipX: Boolean = false,
) {
    private val flipSign: Float
        get() = if (flipX) -1f else 1f

    val m00: Float get() = cos(rotationRad) * scale * flipSign
    val m01: Float get() = -sin(rotationRad) * scale
    val m10: Float get() = sin(rotationRad) * scale * flipSign
    val m11: Float get() = cos(rotationRad) * scale

    fun canvasToScreen(canvasX: Float, canvasY: Float, out: FloatArray) {
        require(out.size >= 2)
        out[0] = m00 * canvasX + m01 * canvasY + translateX
        out[1] = m10 * canvasX + m11 * canvasY + translateY
    }

    fun screenToCanvas(screenX: Float, screenY: Float, out: FloatArray) {
        require(out.size >= 2)
        val determinant = m00 * m11 - m01 * m10
        if (abs(determinant) < 1e-8f) {
            out[0] = 0f
            out[1] = 0f
            return
        }
        val inverseDeterminant = 1f / determinant
        val dx = screenX - translateX
        val dy = screenY - translateY
        out[0] = (m11 * dx - m01 * dy) * inverseDeterminant
        out[1] = (-m10 * dx + m00 * dy) * inverseDeterminant
    }
}

```

```

fun zoomAround(anchorX: Float, anchorY: Float, newScale: Float): ViewTransform {
    val safeScale = newScale.coerceIn(MIN_SCALE, MAX_SCALE)
    val factor = safeScale / scale
    return copy(
        scale = safeScale,
        translateX = anchorX - (anchorX - translateX) * factor,
        translateY = anchorY - (anchorY - translateY) * factor,
    )
}

fun rotateAround(anchorX: Float, anchorY: Float, deltaRad: Float): ViewTransform {
    val c = cos(deltaRad)
    val s = sin(deltaRad)
    val dx = translateX - anchorX
    val dy = translateY - anchorY
    return copy(
        rotationRad = rotationRad + deltaRad,
        translateX = anchorX + dx * c - dy * s,
        translateY = anchorY + dx * s + dy * c,
    )
}

/** Builds a column-major matrix for canvas to OpenGL clip coordinates. */
fun buildCanvasToClip(viewWidth: Float, viewHeight: Float, out: FloatArray) {
    require(out.size >= 16)
    require(viewWidth > 0f)
    require(viewHeight > 0f)
    val sx = 2f / viewWidth
    val sy = -2f / viewHeight
    out[0] = m00 * sx; out[1] = m10 * sy; out[2] = 0f; out[3] = 0f
    out[4] = m01 * sx; out[5] = m11 * sy; out[6] = 0f; out[7] = 0f
    out[8] = 0f; out[9] = 0f; out[10] = 1f; out[11] = 0f
    out[12] = translateX * sx - 1f; out[13] = translateY * sy + 1f
    out[14] = 0f; out[15] = 1f
}

companion object {
    const val MIN_SCALE = 0.02f
    const val MAX_SCALE = 64f

    fun buildCanvasToFbo(canvasWidth: Float, canvasHeight: Float, out: FloatArray) {
        require(out.size >= 16); require(canvasWidth > 0f); require(canvasHeight > 0f)
        out[0]=2f/canvasWidth;out[1]=0f;out[2]=0f;out[3]=0f;out[4]=0f;out[5]=2f/canvasHeight;out[6]=0f;out[7]=0f;out[8]=0f;out[9]=0f;out[10]=1f;out[11]=0f
    }
}

```

## app/src/main/java/com/wetinknext/engine/gl/CanvasGeometry.kt

```

package com.wetinknext.engine.gl

import android.opengl.GLES30
import java.nio.ByteBuffer
import java.nio.ByteOrder

/** A document-sized quad; GL resources are owned by the render thread. */
class CanvasGeometry {
    var vaoId = 0
    private set
    private var vboId = 0

    fun create(width: Int, height: Int) {
        release()
        val vertices = floatArrayOf(0f, 0f, width.toFloat(), 0f, 0f, height.toFloat(), width.toFloat(), height.toFloat())
        val data = ByteBuffer.allocateDirect(vertices.size * Float.SIZE_BYTES).order(ByteOrder.nativeOrder()).asFloatBuffer()
        data.put(vertices).position(0)
        val ids = IntArray(1)
        GLES30.glGenVertexArrays(1, ids, 0); vaoId = ids[0]
        GLES30.glGenBuffers(1, ids, 0); vboId = ids[0]
        GLES30.glBindVertexArray(vaoId); GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, vboId)
        GLES30.glBufferData(GLES30.GL_ARRAY_BUFFER, vertices.size * Float.SIZE_BYTES, data, GLES30.GL_STATIC_DRAW)
        GLES30.glEnableVertexAttribArray(0); GLES30.glVertexAttribPointer(0, 2, GLES30.GL_FLOAT, false, 0, 0)
        GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0); GLES30.glBindVertexArray(0)
    }

    fun draw() {
        check(vaoId != 0)
        GLES30.glBindVertexArray(vaoId); GLES30.glDrawArrays(GLES30.GL_TRIANGLE_STRIP, 0, 4); GLES30.glBindVertexArray(0)
    }

    fun release() {
        if (vboId != 0) GLES30.glDeleteBuffers(1, intArrayOf(vboId), 0)
        if (vaoId != 0) GLES30.glDeleteVertexArrays(1, intArrayOf(vaoId), 0)
        vaoId = 0; vboId = 0
    }
}

```

## app/src/main/java/com/wetinknext/engine/gl/GeometryCache.kt

```

package com.wetinknext.engine.gl

```

```

import android.opengl.GLES30
import java.nio.ByteBuffer
import java.nio.ByteOrder

/** A single cached fullscreen triangle for future present passes. */
class GeometryCache {
    private var vaoId = 0
    private var vboId = 0
    fun create() {
        if (vaoId != 0) return
        val vertices = floatArrayOf(-1f, -1f, 3f, -1f, -1f, 3f)
        val data = ByteBuffer.allocateDirect(vertices.size * Float.SIZE_BYTES).order(ByteOrder.nativeOrder()).asFloatBuffer()
        data.put(vertices).position(0)
        val ids = IntArray(1); GLES30.glGenVertexArrays(1, ids, 0); vaoId = ids[0]
        GLES30.glGenBuffers(1, ids, 0); vboId = ids[0]
        GLES30.glBindVertexArray(vaoId); GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, vboId)
        GLES30.glBufferData(GLES30.GL_ARRAY_BUFFER, vertices.size * Float.SIZE_BYTES, data, GLES30.GL_STATIC_DRAW)
        GLES30.glEnableVertexAttribArray(0); GLES30.glVertexAttribPointer(0, 2, GLES30.GL_FLOAT, false, 0, 0)
        GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0); GLES30.glBindVertexArray(0)
    }
    fun drawFullscreenTriangle() { check(vaoId != 0); GLES30.glBindVertexArray(vaoId); GLES30.glDrawArrays(GLES30.GL_TRIANGLES, 0, 3); GLES30.glBindVertexArray(0) }
    fun release() { if (vboId != 0) GLES30.glDeleteBuffers(1, intArrayOf(vboId), 0); if (vaoId != 0) GLES30.glDeleteVertexArrays(1, intArrayOf(vaoId), 0); vboId = 0; vaoId = 0 }
}

```

## app/src/main/java/com/wetinknext/engine/gl/GlCaps.kt

```

package com.wetinknext.engine.gl

import android.opengl.GLES30

/** Capabilities queried only after a GLES 3 context is current. */
data class GlCaps(
    val renderer: String,
    val version: String,
    val supportsHalfFloatColorBuffer: Boolean,
) {
    companion object {
        fun query(): GlCaps {
            val extensions = GLES30.glGetString(GLES30.GL_EXTENSIONS).orEmpty()
            return GlCaps(
                renderer = GLES30.glGetString(GLES30.GL_RENDERER).orEmpty(),
                version = GLES30.glGetString(GLES30.GL_VERSION).orEmpty(),
                supportsHalfFloatColorBuffer = extensions.contains("EXT_color_buffer_half_float"),
            )
        }
    }
}

```

## app/src/main/java/com/wetinknext/engine/gl/GlCheck.kt

```

package com.wetinknext.engine.gl

import android.opengl.GLES30

/** GL error checks intended for setup boundaries, never the render hot path. */
object GlCheck {
    fun noError(label: String) {
        val error = GLES30.glGetError()
        check(error == GLES30.GL_NO_ERROR) { "$label: GL error 0x${error.toString(16)}" }
    }

    fun framebufferComplete(label: String) {
        val status = GLES30.glCheckFramebufferStatus(GLES30.GL_FRAMEBUFFER)
        check(status == GLES30.GL_FRAMEBUFFER_COMPLETE) {
            "$label: framebuffer incomplete (0x${status.toString(16)})"
        }
    }
}

```

## app/src/main/java/com/wetinknext/engine/gl/GlProgram.kt

```

package com.wetinknext.engine.gl

import android.opengl.GLES30

/** Linked GLSL program. Construction and release must run on the GL thread. */
class GlProgram(vertexSource: String, fragmentSource: String) {
    val id: Int = GLES30.glCreateProgram().also { program ->
        check(program != 0) { "Unable to create GL program" }
        val vertex = compile(GLES30.GL_VERTEX_SHADER, vertexSource)
        val fragment = compile(GLES30.GL_FRAGMENT_SHADER, fragmentSource)
        GLES30.glAttachShader(program, vertex); GLES30.glAttachShader(program, fragment); GLES30.glLinkProgram(program)
        val linked = IntArray(1); GLES30.glGetProgramiv(program, GLES30.GL_LINK_STATUS, linked, 0)
        GLES30.glDeleteShader(vertex); GLES30.glDeleteShader(fragment)
        check(linked[0] == GLES30.GL_TRUE) { "Program link failed: ${GLES30.glGetProgramInfoLog(program)}" }
    }
    fun use() = GLES30.glUseProgram(id)
    fun release() = GLES30.glDeleteProgram(id)

    private fun compile(type: Int, source: String): Int = GLES30.glCreateShader(type).also { shader ->

```

```

        check(shader != 0) { "Unable to create shader" }
        GLES30.glShaderSource(shader, source); GLES30.glCompileShader(shader)
        val compiled = IntArray(1); GLES30.glGetShaderiv(shader, GLES30.GL_COMPILE_STATUS, compiled, 0)
        check(compiled[0] == GLES30.GL_TRUE) { "Shader compile failed: ${GLES30.glGetShaderInfoLog(shader)}" }
    }
}

```

## app/src/main/java/com/wetinknext/engine/gl/RenderTarget.kt

```

package com.wetinknext.engine.gl

import android.opengl.GLES30

/** Texture-backed FBO with RGBA16F probing and a guaranteed RGBA8 fallback. */
class RenderTarget {
    var framebufferId: Int = 0
        private set
    var textureId: Int = 0
        private set
    var width: Int = 0
        private set
    var height: Int = 0
        private set
    var usesHalfFloat: Boolean = false
        private set

    fun create(width: Int, height: Int, preferHalfFloat: Boolean) {
        require(width > 0 && height > 0)
        release()
        if (preferHalfFloat && createInternal(width, height, true)) return
        check(createInternal(width, height, false)) { "RGBA8 render target creation failed" }
    }

    /** A 4x4 completeness probe used before allocating a document-sized target. */
    fun probeHalfFloatColorBuffer(): Boolean {
        release()
        val result = createInternal(4, 4, true)
        release()
        return result
    }

    fun bind() {
        check(framebufferId != 0) { "RenderTarget is not created" }
        GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, framebufferId)
    }

    fun clear(red: Float, green: Float, blue: Float, alpha: Float) {
        bind()
        GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
        GLES30.glDisable(GLES30.GL_BLEND)
        GLES30.glClearColor(red, green, blue, alpha)
        GLES30.glClear(GLES30.GL_COLOR_BUFFER_BIT)
    }

    fun release() {
        if (framebufferId != 0) GLES30.glDeleteFramebuffers(1, intArrayOf(framebufferId), 0)
        if (textureId != 0) GLES30.glDeleteTextures(1, intArrayOf(textureId), 0)
        framebufferId = 0; textureId = 0; width = 0; height = 0; usesHalfFloat = false
    }

    private fun createInternal(targetWidth: Int, targetHeight: Int, halfFloat: Boolean): Boolean {
        val textures = IntArray(1)
        val framebuffers = IntArray(1)
        GLES30.glGenTextures(1, textures, 0)
        GLES30.glGenFramebuffers(1, framebuffers, 0)
        val texture = textures[0]
        val framebuffer = framebuffers[0]
        if (texture == 0 || framebuffer == 0) return false
        GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, texture)
        GLES30.glTexParameteri(GLES30.GL_TEXTURE_2D, GLES30.GL_TEXTURE_MIN_FILTER, GLES30.GL_LINEAR)
        GLES30.glTexParameteri(GLES30.GL_TEXTURE_2D, GLES30.GL_TEXTURE_MAG_FILTER, GLES30.GL_LINEAR)
        GLES30.glTexParameteri(GLES30.GL_TEXTURE_2D, GLES30.GL_TEXTURE_WRAP_S, GLES30.GL_CLAMP_TO_EDGE)
        GLES30.glTexParameteri(GLES30.GL_TEXTURE_2D, GLES30.GL_TEXTURE_WRAP_T, GLES30.GL_CLAMP_TO_EDGE)
        GLES30.glTexImage2D(GLES30.GL_TEXTURE_2D, 0, if (halfFloat) GLES30.GL_RGBA16F else GLES30.GL_RGBA8,
            targetWidth, targetHeight, 0, GLES30.GL_RGBA, if (halfFloat) GLES30.GL_HALF_FLOAT else GLES30.GL_UNSIGNED_BYTE, null)
        GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, framebuffer)
        GLES30.glFramebufferTexture2D(GLES30.GL_FRAMEBUFFER, GLES30.GL_COLOR_ATTACHMENT0, GLES30.GL_TEXTURE_2D, texture, 0)
        val complete = GLES30.glCheckFramebufferStatus(GLES30.GL_FRAMEBUFFER) == GLES30.GL_FRAMEBUFFER_COMPLETE
        GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
        GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
        if (!complete) {
            GLES30.glDeleteFramebuffers(1, framebuffers, 0); GLES30.glDeleteTextures(1, textures, 0)
            return false
        }
        framebufferId = framebuffer; textureId = texture; width = targetWidth; height = targetHeight; usesHalfFloat = halfFloat
        return true
    }
}

```

## app/src/main/java/com/wetinknext/engine/gl/ShaderLib.kt

```

package com.wetinknext.engine.gl

object ShaderLib {
    const val compositorVertex = """#version 300 es
        layout(location=0) in vec2 aPosition;uniform mat4 uCanvasToClip;uniform vec2 uCanvasSize;out vec2 vUv;void main(){vUv=aPosition/uCanvasSize;gl_Position=
    const val compositorFragment = """#version 300 es
        precision highp float;

        in vec2 vUv;
        uniform sampler2D uLayerTex;
        uniform sampler2D uStrokeTex;
        uniform int uStrokeActive;
        uniform float uOpacity;

        out vec4 fragColor;

        vec3 linearToSrgb(vec3 color) {
            vec3 c = clamp(color, 0.0, 1.0);
            vec3 low = c * 12.92;
            vec3 high = 1.055 * pow(c, vec3(1.0 / 2.4)) - 0.055;
            return mix(low, high, step(vec3(0.0031308), c));
        }

        vec3 unpremultiply(vec4 color) {
            return color.a <= 0.0001 ? vec3(0.0) : color.rgb / color.a;
        }

        void main() {
            vec4 layer = texture(uLayerTex, vUv);
            if (uStrokeActive == 1) {
                vec4 stroke = texture(uStrokeTex, vUv);
                layer = stroke + layer * (1.0 - stroke.a);
            }

            float alpha = layer.a * uOpacity;
            fragColor = vec4(linearToSrgb(unpremultiply(layer)) * alpha, alpha);
        }
    """
    const val dabVertex = """#version 300 es
        layout(location = 0) in vec2 aCorner;
        layout(location = 1) in vec4 iDab0;
        layout(location = 2) in float iAlpha;
        uniform mat4 uCanvasToClip;
        out vec2 vLocal; flat out float vAlpha;
        void main(){ float c=cos(iDab0.w), s=sin(iDab0.w); vec2 r=vec2(c*aCorner.x-s*aCorner.y,s*aCorner.x+c*aCorner.y); vLocal=aCorner;vAlpha=iAlpha;gl_Position=
    """
    const val dabFragment = """#version 300 es
        precision highp float; in vec2 vLocal; flat in float vAlpha; uniform vec3 uColorLinear; out vec4 fragColor;
        void main(){ float r=length(vLocal), aa=max(fwidth(r),.001), a=vAlpha*(1.-smoothstep(1.-aa,1.+aa,r));fragColor=vec4(uColorLinear*a,a); }
    """
    const val strokeCompositeFragment = """#version 300 es
        precision highp float; in vec2 vUv; uniform sampler2D uCanvasTex; uniform sampler2D uStrokeTex; uniform int uStrokeActive; out vec4 fragColor;
        vec3 toSrgb(vec3 c){c=clamp(c,0.,1.);return mix(c*12.92,1.055*pow(c,vec3(1./2.4))-.055,step(vec3(.0031308),c));}
        vec3 unpremultiply(vec4 c){return c.a<=.0001?vec3(0.):c.rgb/c.a;}
        void main(){vec4 c=texture(uCanvasTex,vUv);vec4 s=texture(uStrokeTex,vUv);float a=uStrokeActive==1?s.a+c.a*(1.-s.a):c.a;vec3 rgb=uStrokeActive==1?s.rgb+c.rgb*(1.-s.a):c.rgb;fragColor=vec4(rgb,a);}
    """
    const val canvasPresentVertex = """#version 300 es
        layout(location = 0) in vec2 aPosition;
        uniform mat4 uCanvasToClip;
        uniform vec2 uCanvasSize;
        out vec2 vUv;
        void main() {
            vUv = aPosition / uCanvasSize;
            gl_Position = uCanvasToClip * vec4(aPosition, 0.0, 1.0);
        }
    """
    const val presentFragment = """#version 300 es
        precision highp float;
        in vec2 vUv;
        uniform sampler2D uTexture;
        out vec4 fragColor;
        void main() { fragColor = texture(uTexture, vUv); }
    """
    const val fullscreenVertex = """#version 300 es
        layout(location = 0) in vec2 aPosition;
        out vec2 vUv;
        void main() { vUv = aPosition * 0.5 + 0.5; gl_Position = vec4(aPosition, 0.0, 1.0); }
    """
    const val solidFragment = """#version 300 es
        precision highp float;
        in vec2 vUv;
        out vec4 fragColor;
        void main() { fragColor = vec4(vUv, 0.0, 1.0); }
    """
}

```

## app/src/main/java/com/wetinknext/engine/input/InputAction.kt

```

package com.wetinknext.engine.input

enum class InputAction {

```

```

    DOWN,
    MOVE,
    UP,
    CANCEL,
}

```

## app/src/main/java/com/wetinknext/engine/input/InputBatch.kt

```

package com.wetinknext.engine.input

/** Fixed-capacity container for passing input from the UI thread to the GL thread. */
class InputBatch(val maxSamples: Int) {
    val samples = Array(maxSamples) { InputSample() }

    var action: InputAction = InputAction.MOVE
    private set
    var sampleCount: Int = 0
    private set
    var prediction: Boolean = false
    private set

    fun begin(action: InputAction, prediction: Boolean = false) {
        this.action = action
        this.prediction = prediction
        sampleCount = 0
    }

    fun addSample(
        canvasX: Float, canvasY: Float, pressure: Float, tiltX: Float, tiltY: Float,
        orientationRad: Float, timestampNanos: Long, pointerId: Int, tool: PointerTool,
        historical: Boolean,
    ): Boolean {
        if (sampleCount >= maxSamples) return false
        samples[sampleCount].set(
            canvasX, canvasY, pressure.coerceIn(0f, 1f), tiltX.coerceIn(-1f, 1f),
            tiltY.coerceIn(-1f, 1f), orientationRad, timestampNanos, pointerId, tool, historical,
        )
        sampleCount += 1
        return true
    }

    fun isEmpty(): Boolean = sampleCount == 0

    fun clear() {
        for (index in 0 until sampleCount) samples[index].clear()
        sampleCount = 0
        prediction = false
        action = InputAction.MOVE
    }
}

```

## app/src/main/java/com/wetinknext/engine/input/InputBatchPool.kt

```

package com.wetinknext.engine.input

import java.util.concurrent.atomic.AtomicInteger
import java.util.concurrent.atomic.AtomicReferenceArray

/** Fixed-size pool that returns null instead of allocating when exhausted. */
class InputBatchPool(
    batchCount: Int = DEFAULT_BATCH_COUNT,
    maxSamplesPerBatch: Int = DEFAULT_MAX_SAMPLES,
) {
    private val batches = AtomicReferenceArray<InputBatch>(batchCount)
    private val available = AtomicInteger(batchCount)

    init {
        require(batchCount > 0)
        require(maxSamplesPerBatch > 0)
        for (index in 0 until batchCount) batches.set(index, InputBatch(maxSamplesPerBatch))
    }

    fun acquire(): InputBatch? {
        while (true) {
            val current = available.get()
            if (current <= 0) return null
            if (available.compareAndSet(current, current - 1)) {
                for (index in 0 until batches.length()) {
                    val batch = batches.getAndSet(index, null)
                    if (batch != null) return batch
                }
                available.incrementAndGet()
                return null
            }
        }
    }

    fun release(batch: InputBatch) {
        batch.clear()
        for (index in 0 until batches.length()) {
            if (batches.compareAndSet(index, null, batch)) {

```

```

        available.incrementAndGet()
        return
    }
}
error("InputBatchPool overflow: released batch does not belong to pool")
}

val freeCount: Int get() = available.get()

companion object {
    const val DEFAULT_BATCH_COUNT = 96
    const val DEFAULT_MAX_SAMPLES = 64
}
}

```

## app/src/main/java/com/wetinknext/engine/input/InputSample.kt

```

package com.wetinknext.engine.input

/** Mutable input sample allocated only while a batch pool is initialized. */
class InputSample {
    var canvasX = 0f
    var canvasY = 0f
    var pressure = 0f
    var tiltX = 0f
    var tiltY = 0f
    var orientationRad = 0f
    var timestampNanos = 0L
    var pointerId = -1
    var tool = PointerTool.UNKNOWN
    var historical = false

    fun set(
        canvasX: Float, canvasY: Float, pressure: Float, tiltX: Float, tiltY: Float,
        orientationRad: Float, timestampNanos: Long, pointerId: Int, tool: PointerTool,
        historical: Boolean,
    ) {
        this.canvasX = canvasX; this.canvasY = canvasY; this.pressure = pressure
        this.tiltX = tiltX; this.tiltY = tiltY; this.orientationRad = orientationRad
        this.timestampNanos = timestampNanos; this.pointerId = pointerId; this.tool = tool
        this.historical = historical
    }

    fun clear() {
        canvasX = 0f; canvasY = 0f; pressure = 0f; tiltX = 0f; tiltY = 0f
        orientationRad = 0f; timestampNanos = 0L; pointerId = -1
        tool = PointerTool.UNKNOWN; historical = false
    }
}

```

## app/src/main/java/com/wetinknext/engine/input/PointerTool.kt

```

package com.wetinknext.engine.input

enum class PointerTool {
    FINGER,
    STYLUS,
    ERASER,
    UNKNOWN,
}

```

## app/src/main/java/com/wetinknext/engine/input/StrokeInputCapturer.kt

```

package com.wetinknext.engine.input

import android.view.MotionEvent
import com.wetinknext.engine.core.Camera
import java.util.concurrent.ArrayBlockingQueue

/** Converts View-local MotionEvent samples to canvas coordinates on the UI thread. */
class StrokeInputCapturer(private val camera: Camera, private val pool: InputBatchPool, private val queue: ArrayBlockingQueue<InputBatch>) {
    private var activePointerId = -1; private val canvasPoint = FloatArray(2)
    fun onTouchEvent(event: MotionEvent): Boolean = when(event.actionMasked) {
        MotionEvent.ACTION_DOWN, MotionEvent.ACTION_POINTER_DOWN -> { val i=if(event.actionMasked==MotionEvent.ACTION_DOWN) 0 else event.actionIndex; activePointerId = event.findPointerIndex(i); val i=event.findPointerIndex(activePointerId); i >= 0 && enqueue(event,InputAction.MOVE,i,true) }
        MotionEvent.ACTION_MOVE -> { val i=event.findPointerIndex(activePointerId); i >= 0 && enqueue(event,InputAction.MOVE,i,true) }
        MotionEvent.ACTION_UP, MotionEvent.ACTION_POINTER_UP -> { val i=if(event.actionMasked==MotionEvent.ACTION_UP) 0 else event.actionIndex; if(event.getPointerId(i) == activePointerId) enqueueEmpty(InputAction.CANCEL) }
        MotionEvent.ACTION_CANCEL -> { activePointerId=-1; enqueueEmpty(InputAction.CANCEL) }
        else -> false
    }

    private fun enqueue(event:MotionEvent, action:InputAction, index:Int, historical:Boolean):Boolean { val batch=pool.acquire():return false;batch.begin(action);batch.enqueue(event);if(!queue.offer(batch)){pool.release(batch)}
    private fun enqueueEmpty(action:InputAction):Boolean { val batch=pool.acquire():return false;batch.begin(action);batch.enqueueEmpty(action);if(!queue.offer(batch)){pool.release(batch)}
    private fun tool(e:MotionEvent,i:Int)=when(e.getToolType(i)){MotionEvent.TOOL_TYPE_STYLUS->PointerTool.STYLUS;MotionEvent.TOOL_TYPE_ERASER->PointerTool.ERASER;MotionEvent.TOOL_TYPE_FINGER->PointerTool.FINGER;MotionEvent.TOOL_TYPE_UNKNOWN->PointerTool.UNKNOWN}
    private fun pressure(e:MotionEvent,t:PointerTool,i:Int,h:Int):Float=if(t==PointerTool.FINGER||t==PointerTool.UNKNOWN).62f else (if(h>=0)e.getHistoricalPressure(i,h)).62f
    private fun orientation(e:MotionEvent,t:PointerTool,i:Int,h:Int):Float=if(t==PointerTool.FINGER||t==PointerTool.UNKNOWN)0f else (if(h>=0)e.getHistoricalOrientation(i,h)).62f
}

```

## app/src/main/java/com/wetinknext/engine/undo/TileCompressor.kt

```

package com.wetinknext.engine.undo

```

```

/**
 * Extension point for P6.5 compression. P6 uses the identity implementation,
 * so the 96 MB budget reflects the exact bytes that are currently retained.
 */
interface TileCompressor {
    fun compress(data: ByteArray): ByteArray

    fun decompress(data: ByteArray, expectedSize: Int): ByteArray
}

/** P6 storage policy: no compression and no extra byte-array allocation. */
object IdentityTileCompressor : TileCompressor {
    override fun compress(data: ByteArray): ByteArray = data

    override fun decompress(data: ByteArray, expectedSize: Int): ByteArray {
        check(data.size == expectedSize) {
            "Raw tile has ${data.size} bytes, expected $expectedSize"
        }
        return data
    }
}

```

## app/src/main/java/com/wetinknext/engine/undo/TileSnapshot.kt

```

package com.wetinknext.engine.undo

data class TileCoord(val tx: Int, val ty: Int)

/** One full 256 px tile (or an edge tile) in the source layer's native format. */
class TileSnapshot(
    val coord: TileCoord,
    val pixelLeft: Int,
    val pixelTop: Int,
    val pixelWidth: Int,
    val pixelHeight: Int,
    val bytesPerPixel: Int,
    private val storedData: ByteArray,
    private val compressor: TileCompressor = IdentityTileCompressor,
) {
    val memorySize: Int get() = storedData.size
    val rawSize: Int get() = pixelWidth * pixelHeight * bytesPerPixel

    /** Returns raw bytes. Under P6 identity storage this returns the retained array. */
    fun decompress(): ByteArray = compressor.decompress(storedData, rawSize)

    /** Avoids a redundant decompression/copy in the P6 identity restore path. */
    fun storedBytes(): ByteArray = storedData

    fun dispose() {
        // P6 keeps heap ByteArrays; a later off-heap implementation can release here.
    }

    companion object {
        const val TILE_SIZE = 256
        const val BYTES_PER_PIXEL_RGBA16F = 8
        const val BYTES_PER_PIXEL_RGBA8 = 4
    }
}

```

## app/src/main/java/com/wetinknext/engine/undo/TileSnapshotCapture.kt

```

package com.wetinknext.engine.undo
import android.opengl.GLES30
import com.wetinknext.engine.gl.RenderTarget
import java.nio.ByteBuffer
import java.nio.ByteOrder
object TileSnapshotCapture {
    private var reusable: ByteBuffer? = null

    /** Captures every 256 px tile intersecting [bounds] = left, top, right, bottom. */
    fun capture(target: RenderTarget, bounds: IntArray): List<TileSnapshot> {
        require(bounds.size >= 4)
        val left = bounds[0].coerceIn(0, target.width)
        val top = bounds[1].coerceIn(0, target.height)
        val right = bounds[2].coerceIn(0, target.width)
        val bottom = bounds[3].coerceIn(0, target.height)
        if (right <= left || bottom <= top) return emptyList()

        val bytesPerPixel = if (target.usesHalfFloat) {
            TileSnapshot.BYTES_PER_PIXEL_RGBA16F
        } else {
            TileSnapshot.BYTES_PER_PIXEL_RGBA8
        }
        val glType = if (target.usesHalfFloat) GLES30.GL_HALF_FLOAT else GLES30.GL_UNSIGNED_BYTE
        val result = ArrayList<TileSnapshot>()
        target.bind()
        GLES30.glPixelStorei(GLES30.GL_PACK_ALIGNMENT, 1)
        for (tileY in top / TileSnapshot.TILE_SIZE..(bottom - 1) / TileSnapshot.TILE_SIZE) {
            for (tileX in left / TileSnapshot.TILE_SIZE..(right - 1) / TileSnapshot.TILE_SIZE) {
                val pixelLeft = tileX * TileSnapshot.TILE_SIZE
                val pixelTop = tileY * TileSnapshot.TILE_SIZE

```

```

        val pixelWidth = minOf(TileSnapshot.TILE_SIZE, target.width - pixelLeft)
        val pixelHeight = minOf(TileSnapshot.TILE_SIZE, target.height - pixelTop)
        val byteCount = pixelWidth * pixelHeight * bytesPerPixel
        val buffer = obtainBuffer(byteCount)
        buffer.clear()
        GLES30.glReadPixels(
            pixelLeft, pixelTop, pixelWidth, pixelHeight,
            GLES30.GL_RGBA, glType, buffer,
        )
        buffer.rewind()
        val rawBytes = ByteArray(byteCount)
        buffer.get(rawBytes)
        result += TileSnapshot(
            coord = TileCoord(tileX, tileY),
            pixelLeft = pixelLeft,
            pixelTop = pixelTop,
            pixelWidth = pixelWidth,
            pixelHeight = pixelHeight,
            bytesPerPixel = bytesPerPixel,
            storedData = IdentityTileCompressor.compress(rawBytes),
            compressor = IdentityTileCompressor,
        )
    }
}
GLES30.glPixelStorei(GLES30.GL_PACK_ALIGNMENT, 4)
GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
return result
}

private fun obtainBuffer(size: Int): ByteBuffer {
    val current = reusable
    if (current != null && current.capacity() >= size) return current
    return ByteBuffer.allocateDirect(size).order(ByteOrder.nativeOrder()).also { reusable = it }
}
}

```

## app/src/main/java/com/wetinknext/engine/undo/TileSnapshotRestore.kt

```

package com.wetinknext.engine.undo

import android.opengl.GLES30
import com.wetinknext.engine.gl.RenderTarget
import java.nio.ByteBuffer
import java.nio.ByteOrder

/** Restores snapshot tiles into an already-created layer texture on the GL thread. */
object TileSnapshotRestore {
    private var reusableBuffer: ByteBuffer? = null

    fun restore(target: RenderTarget, tiles: List<TileSnapshot>) {
        if (tiles.isEmpty()) return
        GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, target.textureId)
        GLES30.glPixelStorei(GLES30.GL_UNPACK_ALIGNMENT, 1)
        for (tile in tiles) {
            val data = tile.storedBytes()
            val buffer = obtainBuffer(data.size)
            buffer.clear()
            buffer.put(data)
            buffer.position(0)
            val glType = if (tile.bytesPerPixel == TileSnapshot.BYTES_PER_PIXEL_RGBA16F) {
                GLES30.GL_HALF_FLOAT
            } else {
                GLES30.GL_UNSIGNED_BYTE
            }
            GLES30.glTexSubImage2D(
                GLES30.GL_TEXTURE_2D,
                0,
                tile.pixelLeft,
                tile.pixelTop,
                tile.pixelWidth,
                tile.pixelHeight,
                GLES30.GL_RGBA,
                glType,
                buffer,
            )
        }
        GLES30.glPixelStorei(GLES30.GL_UNPACK_ALIGNMENT, 4)
        GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
    }

    private fun obtainBuffer(size: Int): ByteBuffer {
        val current = reusableBuffer
        if (current != null && current.capacity() >= size) return current
        return ByteBuffer.allocateDirect(size).order(ByteOrder.nativeOrder()).also { reusableBuffer = it }
    }
}

```

## app/src/main/java/com/wetinknext/engine/undo/UndoEntry.kt

```

package com.wetinknext.engine.undo

```

```

/** One committed stroke, retaining exact states from before and after its merge. */
data class UndoEntry(
    val layerId: Long,
    val beforeTiles: List<TileSnapshot>,
    val afterTiles: List<TileSnapshot>,
    val tag: String = "stroke",
) {
    val memorySize: Int
        get() = beforeTiles.sumOf(TileSnapshot::memorySize) + afterTiles.sumOf(TileSnapshot::memorySize)

    fun dispose() {
        beforeTiles.forEach(TileSnapshot::dispose)
        afterTiles.forEach(TileSnapshot::dispose)
    }
}

```

## app/src/main/java/com/wetinknext/engine/undo/UndoManager.kt

```

package com.wetinknext.engine.undo

/**
 * Pure memory-bounded history. GPU reads and texture restores deliberately live
 * in EngineRenderer, keeping this class deterministic and unit-testable.
 */
class UndoManager(
    private val maxMemoryBytes: Long = DEFAULT_MAX_MEMORY_BYTES,
    private val maxSteps: Int = DEFAULT_MAX_STEPS,
) {
    private val undoStack = ArrayDeque<UndoEntry>()
    private val redoStack = ArrayDeque<UndoEntry>()
    private var undoMemoryBytes = 0L
    private var redoMemoryBytes = 0L

    val canUndo: Boolean get() = undoStack.isNotEmpty()
    val canRedo: Boolean get() = redoStack.isNotEmpty()
    val memoryBytes: Long get() = undoMemoryBytes + redoMemoryBytes
    val undoCount: Int get() = undoStack.size
    val redoCount: Int get() = redoStack.size

    /** Records a new operation and invalidates the alternate redo history. */
    fun push(entry: UndoEntry) {
        undoStack.addLast(entry)
        undoMemoryBytes += entry.memorySize
        clearRedo()
        trimToLimits()
    }

    /** Moves the newest undo entry onto redo and returns it for a before-restore. */
    fun popUndo(): UndoEntry? {
        val entry = undoStack.removeLastOrNull() ?: return null
        undoMemoryBytes -= entry.memorySize
        redoStack.addLast(entry)
        redoMemoryBytes += entry.memorySize
        trimToLimits()
        return entry
    }

    /** Moves the newest redo entry back to undo and returns it for an after-restore. */
    fun popRedo(): UndoEntry? {
        val entry = redoStack.removeLastOrNull() ?: return null
        redoMemoryBytes -= entry.memorySize
        undoStack.addLast(entry)
        undoMemoryBytes += entry.memorySize
        trimToLimits()
        return entry
    }

    fun clearRedo() {
        while (redoStack.isNotEmpty()) {
            val entry = redoStack.removeLast()
            redoMemoryBytes -= entry.memorySize
            entry.dispose()
        }
        redoMemoryBytes = 0L
    }

    fun clear() {
        while (undoStack.isNotEmpty()) undoStack.removeLast().dispose()
        undoMemoryBytes = 0L
        clearRedo()
    }

    private fun trimToLimits() {
        while (undoStack.size > maxSteps) evictOldestUndo()
        while (redoStack.size > maxSteps) evictOldestRedo()
        while (memoryBytes > maxMemoryBytes && undoStack.size + redoStack.size > 1) {
            when {
                redoStack.size > 1 && redoMemoryBytes >= undoMemoryBytes -> evictOldestRedo()
                undoStack.size > 1 -> evictOldestUndo()
                redoStack.size > 1 -> evictOldestRedo()
                else -> return
            }
        }
    }
}

```

```

        }
    }
}

private fun evictOldestUndo() {
    val entry = undoStack.removeFirstOrNull() ?: return
    undoMemoryBytes -= entry.memorySize
    entry.dispose()
}

private fun evictOldestRedo() {
    val entry = redoStack.removeFirstOrNull() ?: return
    redoMemoryBytes -= entry.memorySize
    entry.dispose()
}

companion object {
    const val DEFAULT_MAX_MEMORY_BYTES = 96L * 1024L * 1024L
    const val DEFAULT_MAX_STEPS = 50
}
}

```

## app/src/main/java/com/wetinknext/ui/theme/WetInkNextPalette.kt

```

package com.wetinknext.ui.theme

import androidx.compose.ui.graphics.Color

data class WetInkNextPalette(
    val appBg: Color,
    val panelBg: Color,
    val panelStroke: Color,
    val textPrimary: Color,
    val textSecondary: Color,
    val accent: Color,
) {
    companion object {
        val default = WetInkNextPalette(
            appBg = Color(0xFF17181C),
            panelBg = Color(0xFF25272D),
            panelStroke = Color(0xFF3A3D46),
            textPrimary = Color(0xFFFF3F4F6),
            textSecondary = Color(0xFFA4A8B3),
            accent = Color(0xFF4D7AFF),
        )
    }
}

```

## app/src/test/java/com/wetinknext/engine/brush/ColorSpacesTest.kt

```

package com.wetinknext.engine.brush
import org.junit.Assert.*
import org.junit.Test
class ColorSpacesTest { @Test fun blackAndWhiteAreStable(){val b=FloatArray(3);val w=FloatArray(3);ColorSpaces.srgb8ToLinear(0xFF000000L,b);ColorSpaces.srgb8

```

## app/src/test/java/com/wetinknext/engine/brush/DabBufferTest.kt

```

package com.wetinknext.engine.brush

import org.junit.Assert.*
import org.junit.Test

class DabBufferTest {
    @Test fun overFlowIsCounted(){val b=DabBuffer(2);assertTrue(b.add(0f,0f,1f,0f,1f));assertTrue(b.add(1f,1f,1f,0f,1f));assertFalse(b.add(2f,2f,1f,0f,1f));a
    @Test fun clearResets(){val b=DabBuffer(1);b.add(0f,0f,1f,0f,1f);b.clear();assertEquals(0,b.count)}
}

```

## app/src/test/java/com/wetinknext/engine/brush/OneEuroFilterTest.kt

```

package com.wetinknext.engine.brush

import org.junit.Assert.assertEquals
import org.junit.Assert.assertFalse
import org.junit.Test

class OneEuroFilterTest {
    @Test fun firstSamplePassesThrough() { val f=OneEuroFilter();val out=FloatArray(2);f.filter(0,10f,20f,out);assertEquals(10f,out[0],.0001f);assertEquals(20f,out[1],.0001f);
    @Test fun samplesRemainFinite() { val f=OneEuroFilter();val out=FloatArray(2);f.filter(0,0f,0f,out);f.filter(8_000_000,10f,5f,out);assertFalse(out[0].isNaN)
}

```

## app/src/test/java/com/wetinknext/engine/brush/StabilizerTest.kt

```

package com.wetinknext.engine.brush

import org.junit.Assert.assertEquals
import org.junit.Assert.assertTrue
import org.junit.Test

class StabilizerTest {

```

```

    @Test fun strengthZeroPassesRawThrough(){val s=Stabilizer();s.process(0,100f,200f);assertEquals(100f,s.x,.0001f);assertEquals(200f,s.y,.0001f)}
    @Test fun velocityIsPositiveAfterMovement(){val s=Stabilizer();s.process(0,0f,0f);s.process(1_000_000_000,100f,0f);assertTrue(s.velocity>0f)}
}

```

## app/src/test/java/com/wetinknext/engine/brush/StampEmitterTest.kt

```

package com.wetinknext.engine.brush

import com.wetinknext.engine.input.*
import org.junit.Assert.assertEquals
import org.junit.Test

class StampEmitterTest {
    @Test fun constantSpacingWithoutEndpointDuplicate(){val e=StampEmitter(BrushSettings(baseRadiusPx=10f,spacing=10f,spacingUsesDiameter=false,presureToSize=0f))}
}

```

## app/src/test/java/com/wetinknext/engine/core/DirtyRectTest.kt

```

package com.wetinknext.engine.core

import org.junit.Assert.assertArrayEquals
import org.junit.Assert.assertTrue
import org.junit.Test

class DirtyRectTest {
    @Test fun includesDabsAndConvertsToPixelBounds() {
        val rect = DirtyRect()
        rect.include(100f, 120f, 10f)
        rect.include(150f, 140f, 5f)
        val pixels = IntArray(4)
        rect.toPixelBounds(pixels)
        assertArrayEquals(intArrayOf(90, 110, 155, 145), pixels)
    }

    @Test fun clampCanMakeRectEmpty() {
        val rect = DirtyRect()
        rect.include(-100f, -100f, -10f)
        rect.clamp(100f, 100f)
        assertTrue(rect.isEmpty)
    }

    @Test fun clearResetsRect() {
        val rect = DirtyRect()
        rect.include(0f, 0f, 10f)
        rect.clear()
        assertTrue(rect.isEmpty)
    }
}

```

## app/src/test/java/com/wetinknext/engine/core/ViewTransformFboTest.kt

```

package com.wetinknext.engine.core
import org.junit.Assert.assertEquals
import org.junit.Test
class ViewTransformFboTest { @Test fun orthoValues(){val m=FloatArray(16);ViewTransform.buildCanvasToFbo(100f,200f,m);assertEquals(.02f,m[0],.0001f);assertEquals(

```

## app/src/test/java/com/wetinknext/engine/core/ViewTransformTest.kt

```

package com.wetinknext.engine.core

import org.junit.Assert.assertEquals
import org.junit.Test

class ViewTransformTest {
    @Test fun canvasAndScreenCoordinatesAreInverse() {
        val transform = ViewTransform(120f, 80f, 2.5f, 0.35f, true)
        val screen = FloatArray(2)
        val canvas = FloatArray(2)
        transform.canvasToScreen(240f, 310f, screen)
        transform.screenToCanvas(screen[0], screen[1], canvas)
        assertEquals(240f, canvas[0], 0.001f)
        assertEquals(310f, canvas[1], 0.001f)
    }

    @Test fun zoomAroundAnchorKeepsAnchorStable() {
        val initial = ViewTransform(translateX = 20f, translateY = 30f)
        val before = FloatArray(2)
        val after = FloatArray(2)
        initial.screenToCanvas(400f, 300f, before)
        initial.zoomAround(400f, 300f, 3f).screenToCanvas(400f, 300f, after)
        assertEquals(before[0], after[0], 0.001f)
        assertEquals(before[1], after[1], 0.001f)
    }
}

```

## app/src/test/java/com/wetinknext/engine/undo/TileSnapshotTest.kt

```

package com.wetinknext.engine.undo

```

```

import org.junit.Assert.assertArrayEquals
import org.junit.Assert.assertEquals
import org.junit.Test

class TileSnapshotTest {
    @Test
    fun rawIdentityTileKeepsItsExactBytes() {
        val bytes = arrayOf(0, 10, 20, 30, 40, 50, 60, 70)
        val tile = TileSnapshot(
            coord = TileCoord(2, 3),
            pixelLeft = 512,
            pixelTop = 768,
            pixelWidth = 1,
            pixelHeight = 2,
            bytesPerPixel = TileSnapshot.BYTES_PER_PIXEL_RGBA8,
            storedData = bytes,
        )

        assertEquals(bytes.size, tile.memorySize)
        assertEquals(bytes.size, tile.rawSize)
        assertArrayEquals(bytes, tile.decompress())
    }

    @Test
    fun tileSizeIsTheSpecified256Pixels() {
        assertEquals(256, TileSnapshot.TILE_SIZE)
    }
}

```

## app/src/test/java/com/wetinknext/engine/undo/UndoManagerTest.kt

```

package com.wetinknext.engine.undo

import org.junit.Assert.assertEquals
import org.junit.Assert.assertFalse
import org.junit.Assert.assertSame
import org.junit.Assert.assertTrue
import org.junit.Test

class UndoManagerTest {
    @Test
    fun undoAndRedoMoveTheSameEntryBetweenStacks() {
        val manager = UndoManager()
        val entry = entry(1L)
        manager.push(entry)

        assertTrue(manager.canUndo)
        assertFalse(manager.canRedo)
        assertSame(entry, manager.popUndo())
        assertFalse(manager.canUndo)
        assertTrue(manager.canRedo)
        assertSame(entry, manager.popRedo())
        assertTrue(manager.canUndo)
        assertFalse(manager.canRedo)
    }

    @Test
    fun aNewEntryClearsRedoHistory() {
        val manager = UndoManager()
        val first = entry(1L)
        manager.push(first)
        manager.popUndo()
        assertTrue(manager.canRedo)

        manager.push(entry(1L))

        assertFalse(manager.canRedo)
        assertEquals(1, manager.undoCount)
        assertEquals(0, manager.redoCount)
    }

    @Test
    fun stepLimitEvictsTheOldestHistoryEntry() {
        val manager = UndoManager(maxSteps = 2)
        manager.push(entry(1L))
        manager.push(entry(2L))
        manager.push(entry(3L))

        assertEquals(2, manager.undoCount)
    }

    private fun entry(layerId: Long): UndoEntry = UndoEntry(
        layerId = layerId,
        beforeTiles = listOf(tile(0)),
        afterTiles = listOf(tile(1)),
    )

    private fun tile(x: Int): TileSnapshot = TileSnapshot(
        coord = TileCoord(x, 0),
        pixelLeft = x,
        pixelTop = 0,
    )
}

```

```
        pixelWidth = 1,  
        pixelHeight = 1,  
        bytesPerPixel = TileSnapshot.BYTES_PER_PIXEL_RGBA8,  
        storedData = byteArrayOf(1, 2, 3, 4),  
    )  
}
```

## app/src/main/res/values/strings.xml

```
<resources>  
    <string name="app_name">WetInk Next</string>  
</resources>
```

## app/src/main/res/values/themes.xml

```
<resources>  
    <style name="Theme.WetInkNext" parent="android:style/Theme.Material.NoActionBar" />  
</resources>
```