

WetInk Next

Полный снимок исходного кода: P0-P33

Текущий этап: оптимизация рисования на больших холстах. В снимок включены экранный compose/present-pass, shader-фон вместо множества clear-вызовов, ограничение обработки input-batch за кадр, cache подтверждённых слоёв выше и ниже активного слоя во время preview, а также перенос сериализации tile-данных с GL-потока. Явный glFlush перед after-snapshot удалён. Фризы на 4K пока не считаются устранёнными: следующий подтверждённый узкий участок - синхронный glReadPixels на commit; ему нужен PBO/readback pipeline после измерения реального штриха.

Включено файлов: 165. Сгенерировано из текущей рабочей копии проекта.

1. app/build.gradle.kts

```
1  plugins {
2      id("com.android.application")
3      id("org.jetbrains.kotlin.android")
4      id("org.jetbrains.kotlin.plugin.compose")
5      id("org.jetbrains.kotlin.plugin.serialization")
6  }
7
8  android {
9      namespace = "com.wetinknext"
10     compileSdk = 36
11
12     defaultConfig {
13         applicationId = "com.wetinknext"
14         minSdk = 26
15         targetSdk = 36
16         versionCode = 1
17         versionName = "0.1.0"
18         testInstrumentationRunner = "androidx.test.runner.AndroidJUnitRunner"
19     }
20
21     buildTypes {
22         release {
23             isMinifyEnabled = false
24         }
25     }
26
27     compileOptions {
28         sourceCompatibility = JavaVersion.VERSION_17
29         targetCompatibility = JavaVersion.VERSION_17
30     }
31
32     kotlinOptions {
33         jvmTarget = "17"
34     }
35
36     buildFeatures {
37         compose = true
38         buildConfig = true
39     }
40 }
41
42
43 dependencies {
44     val composeBom = platform("androidx.compose:compose-bom:2024.09.03")
45     implementation(composeBom)
46     androidTestImplementation(composeBom)
47
48     implementation("androidx.core:core-ktx:1.13.1")
49     implementation("androidx.activity:activity-compose:1.9.2")
50     implementation("androidx.lifecycle:lifecycle-viewmodel-ktx:2.8.7")
51     implementation("androidx.compose.ui:ui")
52     implementation("androidx.compose.ui:ui-tooling-preview")
53     implementation("androidx.compose.material3:material3")
54     implementation("androidx.compose.material:material-icons-extended")
55     implementation("org.jetbrains.kotlinx:kotlinx-serialization-json:1.6.3")
56
57     testImplementation("junit:junit:4.13.2")
58
59     debugImplementation("androidx.compose.ui:ui-tooling")
60     debugImplementation("androidx.compose.ui:ui-test-manifest")
61 }
```

2. app/src/main/AndroidManifest.xml

```
1 <?xml version="1.0" encoding="utf-8"?>
2 <manifest xmlns:android="http://schemas.android.com/apk/res/android">
3     <application
4         android:allowBackup="true"
5         android:icon="@mipmap/ic_launcher"
6         android:roundIcon="@mipmap/ic_launcher_round"
7         android:label="@string/app_name"
8         android:supportRtl="true"
9         android:theme="@style/Theme.WetInkNext">
10        <activity
11            android:name=".app.MainActivity"
12            android:exported="true">
13            <intent-filter>
14                <action android:name="android.intent.action.MAIN" />
15                <category android:name="android.intent.category.LAUNCHER" />
16            </intent-filter>
17        </activity>
18    </application>
19 </manifest>
```

3. app/src/main/java/com/wetinknext/app/AppViewModel.kt

```
1 package com.wetinknext.app
2
3 import android.content.Context
4 import android.content.SharedPreferences
5 import androidx.compose.runtime.getValue
6 import androidx.compose.runtime.mutableStateOf
7 import androidx.compose.runtime.setValue
8 import androidx.lifecycle.ViewModel
9 import androidx.lifecycle.ViewModelProvider
10 import androidx.lifecycle.viewModelScope
11 import com.wetinknext.data.project.CreateProjectRequest
12 import com.wetinknext.data.project.AutosaveCoordinator
13 import com.wetinknext.data.project.FileProjectRepository
14 import com.wetinknext.data.project.ProjectRepository
15 import com.wetinknext.data.project.ProjectSummary
16 import com.wetinknext.data.project.TrashedProjectSummary
17 import com.wetinknext.domain.document.ProjectDocument
18 import com.wetinknext.engine.undo.TileCoord
19 import com.wetinknext.engine.core.ThumbnailCapture
20 import com.wetinknext.data.project.ThumbnailEncoder
21 import com.wetinknext.engine.thumbnail.ThumbnailBuildResult
22 import com.wetinknext.domain.document.LoadedWetInkProject
23 import java.io.File
24 import kotlinx.coroutines.launch
25 import kotlinx.coroutines.Dispatchers
26 import kotlinx.coroutines.withContext
27
28 sealed interface AppRoute {
29     data object Home : AppRoute
30     data class Editor(val projectId: String) : AppRoute
31 }
32
33 data class AppUiState(
34     val projects: List<ProjectSummary> = emptyList(),
35     val trashedProjects: List<TrashedProjectSummary> = emptyList(),
36     val isLoading: Boolean = true,
37     val recoveryProject: ProjectSummary? = null,
38     val errorMessage: String? = null,
39     val isDirty: Boolean = false,
40     val isSaving: Boolean = false,
41 )
42
43 /** Owns app navigation and project catalog state, never GL resources. */
44 class AppViewModel(
45     private val repository: ProjectRepository,
46     private val session: SharedPreferences,
47 ) : ViewModel() {
48     var route: AppRoute by mutableStateOf(AppRoute.Home)
49     private set
50     var uiState: AppUiState by mutableStateOf(AppUiState())
51     private set
52     var openedDocument: ProjectDocument? by mutableStateOf(null)
53     private set
54     var openedProject: LoadedWetInkProject? by mutableStateOf(null)
55     private set
56     private val autosaveCoordinator = AutosaveCoordinator(viewModelScope)
57     private var pendingSaveDocument: ProjectDocument? = null
58     private var pendingLayerPayloads: Map<Long, ByteArray> = emptyMap()
59     private var pendingTilesAcknowledgement: (() -> Unit)? = null
60     private var pendingThumbnailWebp: ByteArray? = null
61     private var pendingLayerPreviewsWebp: Map<Long, ByteArray> = emptyMap()
62     private var latestThumbnailSequence = 0L
63
64     init {
65         refreshProjects()
66     }
67
68     fun refreshProjects() {
69         viewModelScope.launch {
70             uiState = uiState.copy(isLoading = true, errorMessage = null)
71             runCatching { repository.list() to repository.listTrash() }
72                 .onSuccess { (projects, trashedProjects) ->
73                     val interruptedId = session.getString(PREF_ACTIVE_PROJECT_ID, null)
74                     val shouldRecover = session.getBoolean(PREF_EDITOR_SESSION_OPEN, false)
75                     uiState = AppUiState(
76                         projects = projects,
77                         trashedProjects = trashedProjects,
78                         isLoading = false,
79                         recoveryProject = if (shouldRecover) {
80                             projects.firstOrNull { it.id == interruptedId }
81                         } else {
82                             null
83                         },
84                     )
85                 }
86                 .onFailure { error ->
87                     uiState = uiState.copy(isLoading = false, errorMessage = error.message)
88                 }
89         }
90     }
```

```

91
92 fun createProject(request: CreateProjectRequest) {
93     viewModelScope.launch {
94         uiState = uiState.copy(isLoading = true, errorMessage = null)
95         runCatching {
96             val summary = repository.create(request)
97             summary to repository.openForEditor(summary.id)
98         }.onSuccess { (summary, loadedProject) ->
99             openedProject = loadedProject
100             openedDocument = loadedProject.document
101             route = AppRoute.Editor(summary.id)
102             markEditorSession(summary.id)
103             uiState = uiState.copy(
104                 projects = (uiState.projects + summary).sortedByDescending(ProjectSummary::updatedAt),
105                 isLoading = false,
106                 recoveryProject = null,
107             )
108         }.onFailure { error ->
109             uiState = uiState.copy(isLoading = false, errorMessage = error.message)
110         }
111     }
112 }
113
114 fun openProject(projectId: String) {
115     viewModelScope.launch {
116         uiState = uiState.copy(isLoading = true, errorMessage = null)
117         runCatching {
118             val recovery = repository.openRecovery(projectId)
119             if (recovery != null) {
120                 repository.save(recovery.document, recovery.assets.layerTiles)
121                 repository.clearRecovery(projectId)
122                 recovery
123             } else {
124                 repository.openForEditor(projectId)
125             }
126         }
127         .onSuccess { loadedProject ->
128             openedProject = loadedProject
129             openedDocument = loadedProject.document
130             route = AppRoute.Editor(projectId)
131             markEditorSession(projectId)
132             uiState = uiState.copy(isLoading = false, recoveryProject = null)
133         }
134         .onFailure { error ->
135             uiState = uiState.copy(isLoading = false, errorMessage = error.message)
136         }
137     }
138 }
139
140 fun renameProject(projectId: String, name: String) {
141     viewModelScope.launch {
142         runCatching { repository.rename(projectId, name) }
143         .onSuccess { refreshProjects() }
144         .onFailure { error -> uiState = uiState.copy(errorMessage = error.message) }
145     }
146 }
147
148 fun duplicateProject(projectId: String) {
149     viewModelScope.launch {
150         runCatching { repository.duplicate(projectId) }
151         .onSuccess { refreshProjects() }
152         .onFailure { error -> uiState = uiState.copy(errorMessage = error.message) }
153     }
154 }
155
156 fun moveProjectToTrash(projectId: String) {
157     viewModelScope.launch {
158         runCatching { repository.moveToTrash(projectId) }
159         .onSuccess { refreshProjects() }
160         .onFailure { error -> uiState = uiState.copy(errorMessage = error.message) }
161     }
162 }
163
164 fun restoreProject(projectId: String) {
165     viewModelScope.launch {
166         runCatching { repository.restore(projectId) }
167         .onSuccess { refreshProjects() }
168         .onFailure { error -> uiState = uiState.copy(errorMessage = error.message) }
169     }
170 }
171
172 fun deleteProjectForever(projectId: String) {
173     viewModelScope.launch {
174         runCatching { repository.deleteForever(projectId) }
175         .onSuccess { refreshProjects() }
176         .onFailure { error -> uiState = uiState.copy(errorMessage = error.message) }
177     }
178 }
179
180 fun dismissRecovery() {
181     session.edit().remove(PREF_ACTIVE_PROJECT_ID).putBoolean(PREF_EDITOR_SESSION_OPEN, false).apply()
182     uiState = uiState.copy(recoveryProject = null)

```

```

183     }
184
185     /** Coalesces document metadata changes from the GL thread. */
186     fun scheduleAutosave(document: ProjectDocument) {
187         if (document.id != openedDocument?.id) return
188         openedDocument = document
189         pendingSaveDocument = document
190         schedulePendingSave()
191     }
192
193     fun scheduleTileAutosave(
194         document: ProjectDocument,
195         payloads: Map<Long, ByteArray>,
196         dirty: Map<Long, Set<TileCoord>>,
197         onSaved: () -> Unit,
198     ) {
199         if (document.id != openedDocument?.id) return
200         openedDocument = document
201         pendingSaveDocument = document
202         // LayerTileStore keeps tiles dirty until this acknowledgement. Therefore
203         // the newest snapshot always contains every cancelled autosave's tiles.
204         pendingLayerPayloads = payloads
205         pendingTilesAcknowledgement = onSaved
206         schedulePendingSave()
207     }
208
209     fun submitThumbnail(image: ThumbnailCapture.Rgba) {
210         val document = openedDocument ?: return
211         val projectId = document.id
212         val sequence = ++latestThumbnailSequence
213         viewModelScope.launch {
214             val encoded = withContext(Dispatchers.Default) {
215                 ThumbnailEncoder.encodeWebp(image)
216             }
217             // Encoders may finish out of order. An older stroke must never
218             // replace the preview captured for a newer committed stroke.
219             if (sequence != latestThumbnailSequence) return@launch
220             if (projectId != openedDocument?.id) {
221                 // The editor may have just been closed while encoding was in
222                 // flight. Persist this last valid preview by itself instead of
223                 // dropping it and leaving the gallery with a stale card. Read
224                 // current metadata first: the captured callback must not
225                 // overwrite a later layer/property save with stale metadata.
226                 runCatching {
227                     val currentDocument = repository.open(projectId)
228                     repository.save(currentDocument, emptyMap(), encoded)
229                 }
230                 .onSuccess { refreshProjects() }
231                 .onFailure { error -> uiState = uiState.copy(errorMessage = error.message) }
232                 return@launch
233             }
234             pendingThumbnailWebp = encoded
235             pendingSaveDocument = openedDocument
236             schedulePendingSave()
237         }
238     }
239
240     /**
241     * Receives files already encoded by ThumbnailBuildScheduler. Reading their
242     * bytes on Dispatchers.IO keeps Android's main thread free; autosave then
243     * publishes the previews together with document.json in one .wetink write.
244     */
245     fun submitThumbnailBuild(result: ThumbnailBuildResult) {
246         val document = openedDocument ?: return
247         val projectId = document.id
248         viewModelScope.launch {
249             val previews = withContext(Dispatchers.IO) {
250                 val project = result.projectPreview
251                 ?.takeIf(File::isFile)
252                 ?.readBytes()
253                 val layers = result.layerPreviews.mapNotNull { (layerId, file) ->
254                     file.takeIf(File::isFile)?.readBytes()?.let { layerId to it }
255                 }.toMap()
256                 project to layers
257             }
258             if (projectId != openedDocument?.id) return@launch
259
260             previews.first?.let { pendingThumbnailWebp = it }
261             if (previews.second.isNotEmpty()) {
262                 pendingLayerPreviewsWebp = pendingLayerPreviewsWebp + previews.second
263             }
264             pendingSaveDocument = openedDocument
265             schedulePendingSave()
266         }
267     }
268
269     /**
270     * One coalesced save owns document metadata, changed layer payloads and the
271     * latest canvas thumbnail. Restarting its debounce is intentional: it keeps
272     * those three representations in the same atomic .wetink publication.
273     */
274     private fun schedulePendingSave() {

```

```

275     val document = pendingSaveDocument ?: return
276     uiState = uiState.copy(isDirty = true)
277     autosaveCoordinator.schedule {
278         val recoveryPayloads = pendingLayerPayloads
279         if (recoveryPayloads.isNotEmpty()) {
280             withContext(Dispatchers.IO) {
281                 runCatching { repository.saveRecovery(document, recoveryPayloads) }
282             }
283             .onFailure { error -> uiState = uiState.copy(errorMessage = error.message) }
284         }
285
286         val documentToSave = pendingSaveDocument ?: return@schedule
287         val payloadsToSave = pendingLayerPayloads
288         val thumbnailToSave = pendingThumbnailWebp
289         val layerPreviewsToSave = pendingLayerPreviewsWebp
290         val acknowledge = pendingTilesAcknowledgement
291
292         uiState = uiState.copy(isSaving = true)
293         withContext(Dispatchers.IO) {
294             runCatching {
295                 repository.save(
296                     document = documentToSave,
297                     changedLayerTiles = payloadsToSave,
298                     thumbnailWebp = thumbnailToSave,
299                     layerPreviewsWebp = layerPreviewsToSave,
300                 )
301             }
302         }
303         .onSuccess {
304             if (pendingSaveDocument == documentToSave) {
305                 pendingSaveDocument = null
306                 pendingLayerPayloads = emptyMap()
307                 pendingTilesAcknowledgement = null
308                 if (thumbnailToSave != null) pendingThumbnailWebp = null
309                 if (layerPreviewsToSave.isNotEmpty()) pendingLayerPreviewsWebp = emptyMap()
310             }
311             repository.clearRecovery(documentToSave.id)
312             uiState = uiState.copy(isDirty = false, isSaving = false)
313             acknowledge?.invoke()
314         }
315         .onFailure { error ->
316             uiState = uiState.copy(isSaving = false, errorMessage = error.message)
317         }
318     }
319 }
320
321 fun closeEditor() {
322     autosaveCoordinator.cancel()
323     val document = openedDocument
324     val payloads = pendingLayerPayloads
325     val thumbnail = pendingThumbnailWebp
326     val layerPreviews = pendingLayerPreviewsWebp
327     val acknowledge = pendingTilesAcknowledgement
328     document?.let { openDocument ->
329         viewModelScope.launch {
330             uiState = uiState.copy(isSaving = true)
331             runCatching { repository.save(openDocument, payloads, thumbnail, layerPreviews) }
332                 .onSuccess {
333                     repository.clearRecovery(openDocument.id)
334                     acknowledge?.invoke()
335                     uiState = uiState.copy(isDirty = false, isSaving = false)
336                     refreshProjects()
337                 }
338                 .onFailure { error -> uiState = uiState.copy(isSaving = false, errorMessage = error.message) }
339         }
340     }
341     pendingSaveDocument = null
342     pendingLayerPayloads = emptyMap()
343     pendingTilesAcknowledgement = null
344     pendingThumbnailWebp = null
345     pendingLayerPreviewsWebp = emptyMap()
346     openedDocument = null
347     openedProject = null
348     route = AppRoute.Home
349     dismissRecovery()
350     refreshProjects()
351 }
352
353 private fun markEditorSession(projectId: String) {
354     session.edit()
355         .putString(PREF_ACTIVE_PROJECT_ID, projectId)
356         .putBoolean(PREF_EDITOR_SESSION_OPEN, true)
357         .apply()
358 }
359
360 companion object {
361     private const val PREFS_NAME = "wetinknext_project_session"
362     private const val PREF_ACTIVE_PROJECT_ID = "active_project_id"
363     private const val PREF_EDITOR_SESSION_OPEN = "editor_session_open"
364 }
365
366 class Factory(context: Context) : ViewModelProvider.Factory {

```

```

367     private val appContext = context.applicationContext
368
369     @Suppress("UNCHECKED_CAST")
370     override fun <T : ViewModel> create(modelClass: Class<T>): T {
371         check(modelClass.isAssignableFrom(AppViewModel::class.java))
372         return AppViewModel(
373             repository = FileProjectRepository(File(appContext.filesDir, "projects")),
374             session = appContext.getSharedPreferences(PREFS_NAME, Context.MODE_PRIVATE),
375         ) as T
376     }
377 }
378 }

```


4. app/src/main/java/com/wetinknext/app/EditorScreen.kt

```
1 package com.wetinknext.app
2
3 import androidx.compose.foundation.background
4 import androidx.compose.foundation.border
5 import androidx.compose.foundation.clickable
6 import androidx.compose.foundation.rememberScrollState
7 import androidx.compose.foundation.verticalScroll
8 import androidx.compose.foundation.layout.*
9 import androidx.compose.foundation.lazy.grid.GridCells
10 import androidx.compose.foundation.lazy.grid.LazyVerticalGrid
11 import androidx.compose.material.icons.Icons
12 import androidx.compose.material.icons.automirrored.filled.ArrowBack
13 import androidx.compose.material.icons.filled.Settings
14 import androidx.compose.material3.Icon
15 import androidx.compose.runtime.*
16 import androidx.compose.ui.Alignment
17 import androidx.compose.ui.Modifier
18 import androidx.compose.ui.graphics.Color
19 import androidx.compose.ui.graphics.toArgb
20 import androidx.compose.ui.draw.clip
21 import androidx.compose.foundation.shape.RoundedCornerShape
22 import androidx.compose.ui.unit.dp
23 import androidx.compose.ui.unit.sp
24 import androidx.compose.ui.viewinterop.AndroidView
25 import androidx.compose.ui.platform.LocalContext
26 import com.wetinknext.domain.document.ProjectDocument
27 import com.wetinknext.engine.brush.BrushPreset
28 import com.wetinknext.engine.brush.BrushLibrary
29 import com.wetinknext.engine.core.EditorUiState
30 import com.wetinknext.engine.core.CanvasBackdropMode
31 import com.wetinknext.engine.core.PaintSurfaceView
32 import com.wetinknext.ui.animation.AnimationTimelineToolbar
33 import com.wetinknext.ui.color.ColorPanel
34 import com.wetinknext.ui.color.GlesColorState
35 import com.wetinknext.ui.components.*
36 import com.wetinknext.ui.state.LayerState
37 import com.wetinknext.ui.theme.WetInkTheme
38 import com.wetinknext.ui.theme.AppTheme
39 import com.wetinknext.ui.theme.AppThemes
40 import com.wetinknext.ui.theme.CustomThemeEditor
41 import com.wetinknext.ui.theme.ThemeController
42 import com.wetinknext.ui.theme.rememberThemeController
43
44 private enum class EditorPanel {
45     NONE,
46     BRUSH,
47     LAYERS,
48     COLOR,
49     SELECTION,
50     TRANSFORM,
51     ADJUSTMENTS,
52     ANIMATION,
53     SETTINGS,
54 }
55
56 @Composable
57 fun EditorScreen(
58     projectId: String,
59     document: ProjectDocument,
60     layerTiles: Map<Long, ByteArray> = emptyMap(),
61     layerPreviews: Map<Long, ByteArray> = emptyMap(),
62     saveStatus: String = "Сохранено",
63     onDocumentChanged: (ProjectDocument) -> Unit = {},
64     onDirtyLayerTiles: (ProjectDocument, Map<Long, ByteArray>, Map<Long, Set<com.wetinknext.engine.undo.TileCoord>>, () -> Unit) -> Unit = { _, _, _ -> },
65     onThumbnailCaptured: (com.wetinknext.engine.core.ThumbnailCapture.Rgba) -> Unit = {},
66     onThumbnailBuildSaved: (com.wetinknext.engine.thumbnail.ThumbnailBuildResult) -> Unit = {},
67     onBack: () -> Unit = {}
68 ) {
69     val context = LocalContext.current
70     val themeController = rememberThemeController()
71     val theme = themeController.current
72     var uiState by remember { mutableStateOf(EditorUiState.empty) }
73     var openPanel by remember { mutableStateOf(EditorPanel.NONE) }
74     var isEraser by remember { mutableStateOf(false) }
75     var documentLoading by remember(projectId) { mutableStateOf(true) }
76
77     val colorState = remember { GlesColorState(context) }
78     var brushColor by remember { mutableStateOf(Color.Black) }
79     var selectedBrush by remember { mutableStateOf<BrushPreset?>(BrushLibrary.pencil6B) }
80
81     val layerState = remember { LayerState() }
82
83     val surface = remember(projectId, document.id) {
84         PaintSurfaceView(
85             context = context,
86             document = document,
87             layerTiles = layerTiles,
88             layerPreviews = layerPreviews,
89             ).also { view ->
```

```

90         view.onEditorStateChange = { uiState = it }
91         view.onProjectDocumentChange = onDocumentChanged
92         view.onDirtyLayerTiles = { changed, payloads, dirty -> onDirtyLayerTiles(changed, payloads, dirty) { view.
acknowledgeSavedTiles(dirty) } }
93         view.onThumbnailCaptured = onThumbnailCaptured
94         view.onThumbnailBuildSaved = onThumbnailBuildSaved
95         view.onDocumentSessionLoaded = { documentLoading = false }
96     }
97 }
98
99 DisposableEffect(surface, onDocumentChanged) {
100     surface.onProjectDocumentChange = onDocumentChanged
101     surface.onDirtyLayerTiles = { changed, payloads, dirty -> onDirtyLayerTiles(changed, payloads, dirty) { surface.
acknowledgeSavedTiles(dirty) } }
102     surface.onThumbnailCaptured = onThumbnailCaptured
103     surface.onThumbnailBuildSaved = onThumbnailBuildSaved
104     surface.onDocumentSessionLoaded = { documentLoading = false }
105     onDispose {
106         surface.onProjectDocumentChange = null
107         surface.onDirtyLayerTiles = null
108         surface.onThumbnailCaptured = null
109         surface.onThumbnailBuildSaved = null
110         surface.onDocumentSessionLoaded = null
111     }
112 }
113
114 LaunchedEffect(uiState) {
115     layerState.syncFromEditor(uiState)
116 }
117
118 // Initialize state
119 LaunchedEffect(surface) {
120     surface.requestState()
121     surface.applyBrushPreset(BrushLibrary.pencil6B)
122     selectedBrush = BrushLibrary.pencil6B
123 }
124
125 LaunchedEffect(theme.canvasBackdrop, theme.canvasGrid, themeController.backdropMode) {
126     surface.setCanvasBackdrop(theme.canvasBackdrop.toArgb(), theme.canvasGrid.toArgb(), themeController.backdropMode)
127 }
128
129 WetInkTheme(theme = theme, fontMode = themeController.font) {
130     Box(
131         modifier = Modifier
132             .fillMaxSize()
133             .background(theme.appBg),
134     ) {
135         AndroidView(
136             modifier = Modifier.fillMaxSize(),
137             factory = { surface },
138         )
139
140         if (documentLoading) {
141             Box(
142                 modifier = Modifier.fillMaxSize().background(theme.appBg.copy(alpha = .92f)),
143                 contentAlignment = Alignment.Center,
144             ) {
145                 androidx.compose.material3.Text("Загрузка документа...", color = theme.textPrimary)
146             }
147         }
148
149         // Save status remains in state for diagnostics; it must not overlap the canvas.
150
151         Box(
152             modifier = Modifier
153                 .align(Alignment.TopStart)
154                 .padding(12.dp),
155         ) {
156             CanvasActionButton(
157                 icon = Icons.AutoMirrored.Filled.ArrowBack,
158                 description = "На главную",
159                 theme = theme,
160                 onClick = onBack,
161             )
162         }
163
164         // Top Toolbar
165         Box(
166             modifier = Modifier
167                 .align(Alignment.TopEnd)
168         ) {
169             TopToolbar(
170                 theme = theme,
171                 currentColor = brushColor,
172                 canUndo = uiState.canUndo,
173                 canRedo = uiState.canRedo,
174                 isSelectionActive = openPanel == EditorPanel.SELECTION,
175                 isTransformActive = openPanel == EditorPanel.TRANSFORM,
176                 isAnimationActive = openPanel == EditorPanel.ANIMATION,
177                 isAdjustmentsActive = openPanel == EditorPanel.ADJUSTMENTS,
178                 onUndoClick = { surface.undo() },
179                 onRedoClick = { surface.redo() },

```

```

180         onSelectionClick = {
181             openPanel = if (openPanel == EditorPanel.SELECTION) EditorPanel.NONE else EditorPanel.SELECTION
182         },
183         onTransformClick = {
184             openPanel = if (openPanel == EditorPanel.TRANSFORM) EditorPanel.NONE else EditorPanel.TRANSFORM
185         },
186         onAnimationClick = {
187             openPanel = if (openPanel == EditorPanel.ANIMATION) EditorPanel.NONE else EditorPanel.ANIMATION
188         },
189         onAdjustmentsClick = {
190             openPanel = if (openPanel == EditorPanel.ADJUSTMENTS) EditorPanel.NONE else EditorPanel.ADJUSTMENTS
191         },
192         onSettingsClick = {
193             openPanel = if (openPanel == EditorPanel.SETTINGS) EditorPanel.NONE else EditorPanel.SETTINGS
194         },
195         onLayersClick = {
196             openPanel = if (openPanel == EditorPanel.LAYERS) EditorPanel.NONE else EditorPanel.LAYERS
197         },
198         onColorClick = {
199             openPanel = if (openPanel == EditorPanel.COLOR) EditorPanel.NONE else EditorPanel.COLOR
200         },
201     )
202 }
203
204 // Left controls keep the same compact stack as the reference editor.
205 Column(
206     modifier = Modifier
207         .align(Alignment.TopStart)
208         .padding(top = 100.dp),
209     horizontalAlignment = Alignment.Start,
210 ) {
211     SideToolbar(
212         theme = theme,
213         brushSize = uiState.brushSizePx,
214         brushOpacity = uiState.brushOpacity,
215         isEraser = isEraser,
216         onBrushSizeChange = { surface.setBrushSize(it) },
217         onBrushOpacityChange = { surface.setBrushOpacity(it) },
218         onBrushClick = {
219             openPanel = if (openPanel == EditorPanel.BRUSH) EditorPanel.NONE else EditorPanel.BRUSH
220         },
221         onEraserClick = {
222             isEraser = it
223             surface.setEraserEnabled(it)
224         }
225     )
226     LeftCanvasActions(
227         theme = theme,
228         onClearLayerClick = { surface.clearActiveLayer() },
229         onMirrorClick = { surface.toggleCanvasMirror() },
230     )
231 }
232
233 // Panel Host
234 EditorPanelHost(
235     panel = openPanel,
236     theme = theme,
237     surface = surface,
238     layerState = layerState,
239     colorState = colorState,
240     brushColor = brushColor,
241     selectedBrush = selectedBrush,
242     themeController = themeController,
243     onBrushSelected = { preset ->
244         selectedBrush = preset
245         surface.applyBrushPreset(preset)
246     },
247     onColorChange = {
248         brushColor = it
249         surface.setBrushColor(it)
250     },
251     onDismiss = { openPanel = EditorPanel.NONE }
252 )
253 }
254 }
255 }
256
257 @Composable
258 private fun EditorPanelHost(
259     panel: EditorPanel,
260     theme: com.wetinknext.ui.theme.AppTheme,
261     surface: PaintSurfaceView?,
262     layerState: LayerState,
263     colorState: GlesColorState,
264     brushColor: Color,
265     selectedBrush: BrushPreset?,
266     themeController: ThemeController,
267     onBrushSelected: (BrushPreset) -> Unit,
268     onColorChange: (Color) -> Unit,
269     onDismiss: () -> Unit
270 ) {
271     Box(modifier = Modifier.fillMaxSize()) {

```

```

272 when (panel) {
273     EditorPanel.NONE -> Unit
274
275     EditorPanel.SETTINGS -> {
276         Box(modifier = Modifier.align(Alignment.TopEnd).padding(top = 70.dp, end = 16.dp)) {
277             ThemeSettingsPanel(
278                 theme = theme,
279                 themeController = themeController,
280                 onDismiss = onDismiss,
281             )
282         }
283     }
284
285     EditorPanel.BRUSH -> {
286         Box(modifier = Modifier.align(Alignment.CenterStart).padding(start = 72.dp)) {
287             BrushPanel(
288                 currentBrush = selectedBrush ?: BrushLibrary.pencil6B,
289                 onBrushSelect = onBrushSelected,
290                 onBrushStudioOpen = { /* TODO */ },
291                 theme = theme,
292                 onDismiss = onDismiss,
293                 onDuplicate = { /* TODO */ },
294                 onDelete = { /* TODO */ }
295             )
296         }
297     }
298
299     EditorPanel.LAYERS -> {
300         Box(modifier = Modifier.align(Alignment.TopEnd).padding(top = 80.dp, end = 16.dp)) {
301             LayersPanel(
302                 state = layerState,
303                 theme = theme,
304                 onDismiss = onDismiss,
305                 onAddLayer = { surface?.addLayer() },
306                 onSelectLayer = { surface?.setActiveLayer(it) },
307                 onVisibleChange = { id, visible -> surface?.setLayerVisible(id, visible) },
308                 onOpacityChange = { id, opacity -> surface?.setLayerOpacity(id, opacity) },
309                 onDuplicateLayer = { id -> surface?.duplicateLayer(id) },
310                 onRemoveLayer = { id -> surface?.removeLayer(id) }
311             )
312         }
313     }
314
315     EditorPanel.COLOR -> {
316         Box(modifier = Modifier.align(Alignment.TopEnd).padding(top = 80.dp, end = 16.dp)) {
317             ColorPanel(
318                 state = colorState,
319                 color = brushColor,
320                 theme = theme,
321                 onColorChange = onColorChange,
322                 onAddFromPhoto = { /* TODO */ },
323                 onDismiss = onDismiss
324             )
325         }
326     }
327
328     EditorPanel.SELECTION -> {
329         Box(modifier = Modifier.align(Alignment.BottomCenter).padding(bottom = 32.dp)) {
330             SelectionToolbar(
331                 theme = theme,
332                 currentShape = SelectionShapeUi.FREEHAND,
333                 onShapeChange = { /* TODO */ },
334                 onDone = onDismiss
335             )
336         }
337     }
338
339     EditorPanel.TRANSFORM -> {
340         Box(modifier = Modifier.align(Alignment.BottomCenter).padding(bottom = 32.dp)) {
341             TransformMenuView(
342                 theme = theme,
343                 currentMode = TransformModeUi.UNIFORM,
344                 actions = object : TransformActions {
345                     override fun reset() { /* TODO */ }
346                     override fun cancel() { onDismiss() }
347                     override fun apply() { onDismiss() }
348                     override fun flipHorizontal() { /* TODO */ }
349                     override fun flipVertical() { /* TODO */ }
350                     override fun setMode(mode: TransformModeUi) { /* TODO */ }
351                 }
352             )
353         }
354     }
355
356     EditorPanel.ADJUSTMENTS -> {
357         Box(modifier = Modifier.align(Alignment.TopEnd).padding(top = 80.dp, end = 16.dp)) {
358             AdjustmentsPanel(
359                 theme = theme,
360                 onClose = onDismiss,
361                 onAction = { /* TODO */ }
362             )
363         }
364     }

```

```

364     }
365
366     EditorPanel.ANIMATION -> {
367         Box(modifier = Modifier.align(Alignment.BottomCenter)) {
368             AnimationTimelineToolbar(
369                 theme = theme,
370                 document = com.wetinknext.domain.animation.AnimationDocument(enabled = true),
371                 currentFrameId = 0L,
372                 onFrameSelect = {},
373                 onFrameMove = { _, _ -> },
374                 onAddFrame = {},
375                 onDuplicateFrame = {},
376                 onDeleteFrame = {},
377                 onHoldChange = { _, _ -> },
378                 onRoleToggle = { _, _ -> },
379                 onAssembleLayers = {},
380                 onLayersClick = {},
381                 onClose = onDismiss
382             )
383         }
384     }
385 }
386
387 }
388
389 @Composable
390 private fun ThemeSettingsPanel(
391     theme: AppTheme,
392     themeController: ThemeController,
393     onDismiss: () -> Unit,
394 ) {
395     var preferencesOpen by remember { mutableStateOf(false) }
396     var customThemeOpen by remember { mutableStateOf(false) }
397     Column(
398         modifier = Modifier
399             .width(320.dp)
400             .heightIn(max = 620.dp)
401             .clip(RoundedCornerShape(22.dp))
402             .background(theme.panelBg)
403             .verticalScroll(rememberScrollState())
404             .padding(10.dp),
405         verticalArrangement = Arrangement.spacedBy(12.dp),
406     ) {
407         Row(verticalAlignment = Alignment.CenterVertically) {
408             androidx.compose.material3.Text(
409                 text = if (preferencesOpen) "Предпочтения" else "Меню",
410                 color = theme.textPrimary,
411                 style = androidx.compose.material3.MaterialTheme.typography.titleLarge,
412                 modifier = Modifier.weight(1f),
413             )
414             androidx.compose.material3.Text(
415                 text = "x",
416                 color = theme.textSecondary,
417                 style = androidx.compose.material3.MaterialTheme.typography.headlineSmall,
418                 modifier = Modifier.size(28.dp).clickable(onClick = onDismiss),
419             )
420         }
421
422         Row(
423             modifier = Modifier.fillMaxWidth().clip(RoundedCornerShape(10.dp))
424                 .background(theme.panelBgVariant.copy(alpha = .5f)).padding(3.dp),
425             horizontalArrangement = Arrangement.spacedBy(2.dp),
426         ) {
427             listOf("Меню", "Холст", "Экспорт", "Сведения").forEachIndexed { index, label ->
428                 Box(
429                     modifier = Modifier
430                         .weight(1f).clip(RoundedCornerShape(8.dp))
431                         .background(if (index == 0) theme.panelBgVariant else Color.Transparent)
432                         .padding(vertical = 8.dp),
433                     contentAlignment = Alignment.Center,
434                 ) {
435                     androidx.compose.material3.Text(
436                         text = label,
437                         color = if (index == 0) theme.textPrimary else theme.textSecondary,
438                         fontSize = 11.sp,
439                         maxLines = 1,
440                         softWrap = false,
441                     )
442                 }
443             }
444         }
445
446         if (customThemeOpen) {
447             CustomThemeEditor(
448                 colors = themeController.customColors,
449                 theme = theme,
450                 backdropMode = themeController.backdropMode,
451                 onChange = themeController::updateCustomColors,
452                 onBackdropModeChange = themeController::selectBackdropMode,
453                 onDismiss = { customThemeOpen = false },
454             )
455         } else if (!preferencesOpen) {

```

```

456         androidx.compose.material3.Text(
457             text = "Предпочтения",
458             color = theme.textPrimary,
459             modifier = Modifier.fillMaxWidth().clickable { preferencesOpen = true }.padding(vertical = 14.dp, horizontal
= 4.dp),
460         )
461     } else {
462         androidx.compose.material3.Text(
463             text = "Тема",
464             color = theme.textSecondary,
465             style = androidx.compose.material3.MaterialTheme.typography.labelMedium,
466             modifier = Modifier.padding(start = 10.dp),
467         )
468         val choices = AppThemes.all + themeController.customTheme.copy(id = "custom", displayName = "Своя")
469         choices.chunked(5).forEach { row ->
470             Row(modifier = Modifier.fillMaxWidth(), horizontalArrangement = Arrangement.SpaceBetween) {
471                 row.forEach { candidate ->
472                     val selected = candidate.id == themeController.current.id
473                     Box(
474                         modifier = Modifier.size(48.dp).clip(androidx.compose.foundation.shape.CircleShape)
475                         .background(if (selected) Color.White else Color.Transparent)
476                         .clickable {
477                             if (candidate.id == "custom") {
478                                 themeController.selectCustom()
479                                 customThemeOpen = true
480                             } else themeController.select(candidate)
481                         }
482                         .padding(2.dp),
483                         contentAlignment = Alignment.Center,
484                     ) {
485                         Box(
486                             modifier = Modifier.fillMaxSize().clip(androidx.compose.foundation.shape.CircleShape)
487                             .background(if (candidate.id == "custom") theme.panelBgVariant else candidate.appBg),
488                             contentAlignment = Alignment.Center,
489                         ) {
490                             if (candidate.id == "custom") {
491                                 Icon(
492                                     imageVector = Icons.Filled.Settings,
493                                     contentDescription = "Настроить свою тему",
494                                     tint = theme.textPrimary,
495                                     modifier = Modifier.size(21.dp),
496                                 )
497                             }
498                             else Box(Modifier.size(24.dp).clip(androidx.compose.foundation.shape.CircleShape).background(
candidate.accent))
499                         }
500                     }
501                 }
502             }
503         }
504     }
505 }
506 }
507 }
508
509 private fun PaintSurfaceView.applyBrushPreset(
510     preset: BrushPreset
511 ) {
512     val settings = preset.settings
513
514     applyBrush(settings)
515
516     val grainPath = settings.grainAssetPath
517         ?.trim()
518         ?.takeIf { it.isNotEmpty() }
519
520     if (grainPath == null) {
521         clearGrainTexture()
522     } else {
523         loadGrainTexture(
524             path = grainPath,
525             scale = settings.grainScale,
526             canvasLocked = settings.grainCanvasLocked,
527             depth = settings.textureDepth,
528             contrast = settings.textureContrast,
529         )
530     }
531
532     val shapePath = settings.shapeAssetPath?.trim()?.takeIf { it.isNotEmpty() }
533     if (shapePath == null) {
534         clearShapeTexture()
535     } else {
536         loadShapeTexture(path = shapePath, rgbToAlpha = settings.rgbToAlpha)
537     }
538 }

```

5. app/src/main/java/com/wetinknext/app/MainActivity.kt

```
1 package com.wetinknext.app
2
3 import android.os.Bundle
4 import androidx.activity.ComponentActivity
5 import androidx.activity.compose.setContent
6 import androidx.activity.viewModels
7 import androidx.core.view.WindowCompat
8 import androidx.core.view.WindowInsetsCompat
9 import androidx.core.view.WindowInsetsControllerCompat
10
11 class MainActivity : ComponentActivity() {
12     private val appViewModel: AppViewModel by viewModels {
13         AppViewModel.Factory(this)
14     }
15
16     override fun onCreate(savedInstanceState: Bundle?) {
17         super.onCreate(savedInstanceState)
18         WindowCompat.setDecorFitsSystemWindows(window, false)
19         WindowInsetsControllerCompat(window, window.decorView).apply {
20             hide(WindowInsetsCompat.Type.statusBars())
21             systemBarsBehavior = WindowInsetsControllerCompat.BEHAVIOR_SHOW_TRANSIENT_BARS_BY_SWIPE
22         }
23         setContent { AppRoot(appViewModel) }
24     }
25 }
```

6. app/src/main/java/com/wetinknext/app/WetInkApp.kt

```
1 package com.wetinknext.app
2
3 import androidx.activity.compose.BackHandler
4 import androidx.compose.material3.AlertDialog
5 import androidx.compose.material3.Text
6 import androidx.compose.material3.TextButton
7 import androidx.compose.runtime.Composable
8 import androidx.compose.runtime.LaunchedEffect
9 import androidx.compose.ui.text.font.FontWeight
10 import com.wetinknext.data.project.CreateProjectRequest
11 import com.wetinknext.data.project.ProjectSummary
12 import com.wetinknext.ui.home.HomeProject
13 import com.wetinknext.ui.home.HomeScreen
14 import com.wetinknext.ui.home.DeletedHomeProject
15 import com.wetinknext.ui.theme.WetInkTheme
16 import com.wetinknext.ui.theme.rememberThemeController
17
18 @Composable
19 fun AppRoot(viewModel: AppViewModel) {
20     when (val currentRoute = viewModel.route) {
21         AppRoute.Home -> ProjectHomeRoute(viewModel)
22         is AppRoute.Editor -> {
23             val document = viewModel.openedDocument
24             val loadedProject = viewModel.openedProject
25             if (document?.id == currentRoute.projectId && loadedProject?.document?.id == currentRoute.projectId) {
26                 BackHandler { viewModel.closeEditor() }
27                 EditorScreen(
28                     projectId = currentRoute.projectId,
29                     document = document,
30                     layerTiles = loadedProject.assets.layerTiles,
31                     layerPreviews = loadedProject.assets.layerPreviewsWebp,
32                     saveStatus = when {
33                         viewModel.uiState.isSaving -> "Сохраняется..."
34                         viewModel.uiState.isDirty -> "Есть несохранённые изменения"
35                         else -> "Сохранено"
36                     },
37                     onDocumentChanged = viewModel::scheduleAutosave,
38                     onDirtyLayerTiles = viewModel::scheduleTileAutosave,
39                     onThumbnailCaptured = viewModel::submitThumbnail,
40                     onThumbnailBuildSaved = viewModel::submitThumbnailBuild,
41                     onBack = viewModel::closeEditor,
42                 )
43             } else {
44                 LaunchedEffect(currentRoute.projectId) {
45                     viewModel.openProject(currentRoute.projectId)
46                 }
47             }
48         }
49     }
50 }
51
52 /** Kept for existing previews and callers while MainActivity uses AppRoot. */
53 @Composable
54 fun WetInkApp(viewModel: AppViewModel) = AppRoot(viewModel)
55
56 @Composable
57 private fun ProjectHomeRoute(viewModel: AppViewModel) {
58     val themeController = rememberThemeController()
59     val theme = themeController.current
60     val state = viewModel.uiState
61
62     WetInkTheme(theme = theme, fontMode = themeController.font) {
63         HomeScreen(
64             theme = theme,
65             projects = state.projects.map(ProjectSummary::toHomeProject),
66             deletedProjects = state.trashedProjects.map { trashed ->
67                 DeletedHomeProject(
68                     project = trashed.project.toHomeProject(),
69                     deletedAtMs = trashed.deletedAt,
70                 )
71             },
72             onOpenProject = { viewModel.openProject(it.id) },
73             onCreateProject = { name, width, height, dpi, colorProfile ->
74                 viewModel.createProject(
75                     CreateProjectRequest(
76                         name = name,
77                         width = width,
78                         height = height,
79                         dpi = dpi,
80                         colorProfile = colorProfile,
81                     ),
82                 )
83             },
84             onRenameProject = { project, name -> viewModel.renameProject(project.id, name) },
85             onDuplicateProject = { project -> viewModel.duplicateProject(project.id) },
86             onDeleteProject = { project -> viewModel.moveProjectToTrash(project.id) },
87             onRestoreProject = { deleted -> viewModel.restoreProject(deleted.project.id) },
88             onDeleteForever = { deleted -> viewModel.deleteProjectForever(deleted.project.id) },
89         )
90     }
```



```

91     state.recoveryProject?.let { project ->
92         AlertDialog(
93             onDismissRequest = viewModel::dismissRecovery,
94             title = { Text("Восстановить работу?" ) },
95             text = { Text("Приложение было закрыто во время работы с «${project.name}»." ) },
96             confirmButton = {
97                 TextButton(onClick = { viewModel.openProject(project.id) }) {
98                     Text("Открыть", fontWeight = FontWeight.SemiBold)
99                 }
100             },
101             dismissButton = {
102                 TextButton(onClick = viewModel::dismissRecovery) {
103                     Text("Не сейчас")
104                 }
105             },
106         )
107     }
108 }
109 }
110
111 private fun ProjectSummary.toHomeProject(): HomeProject = HomeProject(
112     id = id,
113     name = name,
114     canvasWidth = width,
115     canvasHeight = height,
116     updatedAtMs = updatedAt,
117     thumbnailBytes = thumbnailBytes,
118     thumbnailVersion = thumbnailVersion,
119 )

```

7. app/src/main/java/com/wetinknext/data/project/AutosaveCoordinator.kt

```
1 package com.wetinknext.data.project
2
3 import kotlinx.coroutines.CoroutineScope
4 import kotlinx.coroutines.Job
5 import kotlinx.coroutines.delay
6 import kotlinx.coroutines.launch
7
8 /**
9  * Coalesces completed document edits into one disk publication.
10  *
11  * Callers only schedule after transactional changes (UP, clear, layer or
12  * property operations), never for high-frequency MOVE events.
13  */
14 class AutosaveCoordinator(
15     private val scope: CoroutineScope,
16     private val debounceMillis: Long = DEFAULT_DEBOUNCE_MILLIS,
17 ) {
18     private var pendingJob: Job? = null
19
20     fun schedule(save: suspend () -> Unit) {
21         pendingJob?.cancel()
22         pendingJob = scope.launch {
23             delay(debounceMillis)
24             save()
25         }
26     }
27
28     fun cancel() {
29         pendingJob?.cancel()
30         pendingJob = null
31     }
32
33     companion object {
34         const val DEFAULT_DEBOUNCE_MILLIS = 700L
35     }
36 }
```

8. app/src/main/java/com/wetinknext/data/project/DirectoryProjectStore.kt

```
1 package com.wetinknext.data.project
2
3 import com.wetinknext.domain.document.LoadedWetInkProject
4 import com.wetinknext.domain.document.ProjectAssets
5 import com.wetinknext.domain.document.ProjectDocument
6 import com.wetinknext.domain.document.ProjectManifest
7 import com.wetinknext.domain.document.StoredLayer
8 import java.io.File
9 import java.io.IOException
10 import java.nio.file.AtomicMoveNotSupportedException
11 import java.nio.file.Files
12 import java.nio.file.StandardCopyOption
13 import kotlinx.serialization.decodeFromString
14 import kotlinx.serialization.encodeToString
15 import kotlinx.serialization.json.Json
16
17 /** New on-disk project format: directory metadata plus independently replaceable layer files. */
18 class DirectoryProjectStore(
19     private val clock: () -> Long = System::currentTimeMillis,
20     private val json: Json = Json { encodeDefaults = true; ignoreUnknownKeys = true; prettyPrint = true },
21 ) {
22     private var lastTimestamp = Long.MIN_VALUE
23
24     fun save(directory: File, document: ProjectDocument, assets: ProjectAssets): LoadedWetInkProject {
25         require(directory.name == document.id) { "Project directory/id mismatch" }
26         val expected = document.layers.map { it.id }.toSet()
27         require(assets.layerTiles.keys == expected) { "Every layer needs one payload" }
28         ensureDirectory(directory)
29         val timestamp = nextTimestamp()
30         val saved = document.copy(
31             updatedAt = timestamp,
32             thumbnailVersion = if (assets.thumbnailWebp != null) timestamp else document.thumbnailVersion,
33         )
34         saved.layers.forEach { layer -> writeAtomic(File(directory, layer.pixelFile), checkNotNull(assets.layerTiles[layer.id])) }
35         assets.thumbnailWebp?.let { writeAtomic(File(directory, THUMBNAI), it) }
36         assets.layerPreviewsWebp.forEach { (id, bytes) -> writeAtomic(File(directory, previewPath(id)), bytes) }
37         deleteRemovedLayerFiles(directory, saved.layers.map { it.id }.toSet())
38         writeAtomic(File(directory, DOCUMENT), json.encodeToString(saved).encodeToByteArray())
39         val manifest = ProjectManifest(
40             documentId = saved.id, name = saved.name, width = saved.width, height = saved.height,
41             thumbnailPath = assets.thumbnailWebp?.let { THUMBNAI }, thumbnailVersion = saved.thumbnailVersion,
42             createdAt = saved.createdAt, updatedAt = saved.updatedAt,
43             layers = saved.layers.map { StoredLayer(it.id, it.pixelFile, checkNotNull(assets.layerTiles[it.id]).size.toLong()) }
44         )
45         writeAtomic(File(directory, MANIFEST), json.encodeToString(manifest).encodeToByteArray())
46         return LoadedWetInkProject(saved, manifest, assets)
47     }
48
49     fun load(directory: File): LoadedWetInkProject {
50         val manifest = readManifest(directory)
51         val document = readDocument(directory)
52         require(manifest.documentId == document.id) { "Manifest/document id mismatch" }
53         val tiles = document.layers.associate { layer ->
54             val bytes = requireFile(File(directory, layer.pixelFile)).readBytes()
55             val stored = manifest.layers.firstOrNull { it.id == layer.id }?: error("Missing layer metadata")
56             require(stored.byteSize == bytes.size.toLong()) { "Layer size mismatch" }
57             layer.id to bytes
58         }
59         val previews = document.layers.mapNotNull { layer ->
60             File(directory, previewPath(layer.id)).takeIf(File::isFile)?.readBytes()?.let { layer.id to it }
61         }.toMap()
62         val thumbnail = manifest.thumbnailPath?.let { File(directory, it).takeIf(File::isFile)?.readBytes() }
63         return LoadedWetInkProject(document, manifest, ProjectAssets(tiles, thumbnail, previews))
64     }
65
66     /** Keeps gallery sorting deterministic when two saves share one millisecond. */
67     @Synchronized
68     private fun nextTimestamp(): Long {
69         val now = clock()
70         val next = maxOf(now, lastTimestamp + 1L)
71         lastTimestamp = next
72         return next
73     }
74
75     fun readManifest(directory: File): ProjectManifest =
76         json.decodeFromString(requireFile(File(directory, MANIFEST)).readText())
77
78     fun readDocument(directory: File): ProjectDocument =
79         json.decodeFromString(requireFile(File(directory, DOCUMENT)).readText())
80
81     fun readThumbnail(directory: File): ByteArray? = File(directory, THUMBNAI).takeIf(File::isFile)?.readBytes()
82
83     fun delete(directory: File) {
84         require(directory.isDirectory) { "Project directory does not exist" }
85         directory.walkBottomUp().forEach { if (!it.delete()) throw IOException("Cannot delete ${it.path}") }
86     }
87
88     private fun deleteRemovedLayerFiles(directory: File, active: Set<Long>) {

```

```

89         listOf(LAYERS, PREVIEWS).forEach { folder ->
90             File(directory, folder).listFiles().orEmpty().forEach { file ->
91                 val id = file.name.removePrefix("layer-").substringBefore('.').toLongOrNull()
92                 ?: file.name.substringBefore('.').toLongOrNull()
93                 if (id != null && id !in active) file.delete()
94             }
95         }
96     }
97
98     private fun writeAtomic(file: File, bytes: ByteArray) {
99         ensureDirectory(checkNotNull(file.parentFile))
100         val tmp = File(checkNotNull(file.parentFile), ".${file.name}.tmp")
101         try {
102             tmp.outputStream().use { it.write(bytes) }
103             try { Files.move(tmp.toPath(), file.toPath(), StandardCopyOption.ATOMIC_MOVE, StandardCopyOption.
REPLACE_EXISTING) }
104             catch (_: AtomicMoveNotSupportedException) { Files.move(tmp.toPath(), file.toPath(), StandardCopyOption.
REPLACE_EXISTING) }
105             } finally { if (tmp.exists()) tmp.delete() }
106         }
107
108     private fun ensureDirectory(file: File) {
109         if (!file.exists() && !file.mkdirs()) throw IOException("Cannot create ${file.path}")
110         require(file.isDirectory) { "Expected directory: ${file.path}" }
111     }
112
113     private fun requireFile(file: File): File = file.also { require(it.isFile) { "Missing ${it.path}" } }
114
115     private companion object {
116         const val MANIFEST = "manifest.json"
117         const val DOCUMENT = "document.json"
118         const val THUMBNAIL = "thumbnail.webp"
119         const val LAYERS = "layers"
120         const val PREVIEWS = "thumbnails"
121         fun previewPath(layerId: Long) = "$PREVIEWS/layer-$layerId.webp"
122     }
123 }

```

9. app/src/main/java/com/wetinknext/data/project/FileProjectRepository.kt

```
1 package com.wetinknext.data.project
2
3 import com.wetinknext.domain.document.ProjectAssets
4 import com.wetinknext.domain.document.ProjectDocument
5 import com.wetinknext.domain.document.ProjectManifest
6 import com.wetinknext.domain.document.WetInkProjectContainer
7 import java.io.File
8 import java.io.IOException
9 import java.nio.file.AtomicMoveNotSupportedException
10 import java.nio.file.Files
11 import java.nio.file.StandardCopyOption
12 import java.util.Base64
13 import java.util.UUID
14
15 /** File-backed project catalog. Each project remains one independent .wetink file. */
16 class FileProjectRepository(
17     private val projectsDirectory: File,
18     private val container: WetInkProjectContainer = WetInkProjectContainer(),
19     private val directoryProjectStore: DirectoryProjectStore = DirectoryProjectStore(),
20 ) : ProjectRepository {
21     override suspend fun create(request: CreateProjectRequest): ProjectSummary {
22         val document = ProjectDocument.newUntitled(
23             name = request.name,
24             width = request.width,
25             height = request.height,
26             dpi = request.dpi,
27             colorProfile = request.colorProfile,
28         )
29         val assets = ProjectAssets(
30             layerTiles = document.layers.associate { it.id to ByteArray(0) },
31             thumbnailWebp = DEFAULT_THUMBNAI_WEBP,
32         )
33         val saved = directoryStore.save(projectDirectory(document.id), document, assets)
34         return saved.manifest.toSummary()
35     }
36
37     override suspend fun list(): List<ProjectSummary> {
38         ensureDirectories()
39         return listProjects(projectsDirectory)
40     }
41
42     override suspend fun listTrash(): List<TrashedProjectSummary> {
43         ensureDirectories()
44         return trashDirectory.listFiles()
45             .orEmpty()
46             .asSequence()
47             .filter { file -> file.isDirectory || (file.isFile && file.extension.equals(FILE_EXTENSION, ignoreCase = true) &&
!file.name.endsWith(".recovery.$FILE_EXTENSION")) }
48             .mapNotNull { file ->
49                 runCatching {
50                     TrashedProjectSummary(readSummary(file), file.lastModified())
51                 }.getOrNull()
52             }
53             .sortedByDescending(TrashedProjectSummary::deletedAt)
54             .toList()
55     }
56
57     override suspend fun open(id: String): ProjectDocument = loadProject(id).document
58
59     override suspend fun openForEditor(id: String) = loadProject(id)
60
61     override suspend fun save(document: ProjectDocument) {
62         val previous = loadProject(document.id)
63         saveProject(document, previous.assets.retainDocumentLayers(document))
64     }
65
66     override suspend fun save(document: ProjectDocument, changedLayerTiles: Map<Long, ByteArray>) {
67         if (changedLayerTiles.isEmpty()) return save(document)
68         val previous = loadProject(document.id)
69         val allowed = document.layers.map { it.id }.toSet()
70         require(changedLayerTiles.keys.all(allowed::contains)) { "Unknown layer tile payload" }
71         saveProject(
72             document,
73             previous.assets.retainDocumentLayers(document).copy(
74                 layerTiles = previous.assets.layerTiles
75                     .filterKeys(allowed::contains)
76                     .plus(changedLayerTiles),
77             ),
78         )
79     }
80
81     override suspend fun save(
82         document: ProjectDocument,
83         changedLayerTiles: Map<Long, ByteArray>,
84         thumbnailWebp: ByteArray?,
85         layerPreviewsWebp: Map<Long, ByteArray>,
86     ) {
87         val previous = loadProject(document.id)
88         val layerIds = document.layers.map { it.id }.toSet()
89         saveProject(
```

```

90         document,
91         previous.assets.copy(
92             layerTiles = (previous.assets.layerTiles + changedLayerTiles)
93             .filterKeys(layerIds::contains),
94             thumbnailWebp = thumbnailWebp ?: previous.assets.thumbnailWebp,
95             layerPreviewsWebp = (previous.assets.layerPreviewsWebp + layerPreviewsWebp)
96             .filterKeys(layerIds::contains),
97         ),
98     )
99 }
100
101 override suspend fun saveRecovery(document: ProjectDocument, changedLayerTiles: Map<Long, ByteArray>) {
102     val current = loadProject(document.id)
103     container.save(recoveryFile(document.id), document, current.assets.copy(layerTiles = current.assets.layerTiles +
104     changedLayerTiles))
105 }
106
107 override suspend fun clearRecovery(id: String) {
108     val file = recoveryFile(id)
109     if (file.exists() && !file.delete()) throw IOException("Cannot clear recovery snapshot")
110 }
111
112 override suspend fun openRecovery(id: String) = recoveryFile(id).takeIf(File::isFile)?.let(container::load)
113
114 override suspend fun rename(id: String, name: String) {
115     val document = open(id)
116     save(document.copy(name = name))
117 }
118
119 /** Creates a separate editable copy; undo history intentionally is not persisted. */
120 override suspend fun duplicate(id: String): ProjectSummary {
121     val source = loadProject(id)
122     val copyId = UUID.randomUUID().toString()
123     val copiedDocument = source.document.copy(
124         id = copyId,
125         name = duplicateName(source.document.name),
126         createdAt = System.currentTimeMillis(),
127         updatedAt = System.currentTimeMillis(),
128     )
129     val saved = directoryStore.save(projectDirectory(copyId), copiedDocument, source.assets)
130     return saved.manifest.toSummary(saved.assets.thumbnailWebp)
131 }
132
133 override suspend fun moveToTrash(id: String) {
134     val source = projectLocation(id)
135     require(source.exists()) { "Project does not exist: $id" }
136     val target = trashedProjectLocation(id, source.isDirectory)
137     atomicMove(source, target)
138     target.setLastModified(System.currentTimeMillis())
139 }
140
141 override suspend fun restore(id: String) {
142     val source = trashedProjectLocation(id, true).takeIf(File::exists) ?: trashedProjectLocation(id, false)
143     require(source.exists()) { "Trashed project does not exist: $id" }
144     atomicMove(source, if (source.isDirectory) projectDirectory(id) else legacyProjectFile(id))
145 }
146
147 override suspend fun deleteForever(id: String) {
148     val file = trashedProjectLocation(id, true).takeIf(File::exists) ?: trashedProjectLocation(id, false)
149     require(file.exists()) { "Trashed project does not exist: $id" }
150     if (file.isDirectory) directoryStore.delete(file) else if (!file.delete()) throw IOException("Cannot delete project permanently: ${file.path}")
151 }
152
153 private fun projectDirectory(id: String): File {
154     ensureDirectories()
155     return File/projectsDirectory, safeId(id))
156 }
157
158 private fun legacyProjectFile(id: String): File = File/projectsDirectory, "${safeId(id)}.FILE_EXTENSION")
159
160 private fun trashedProjectLocation(id: String, directory: Boolean): File {
161     ensureDirectories()
162     return File(trashDirectory, if (directory) safeId(id) else "${safeId(id)}.FILE_EXTENSION")
163 }
164
165 private fun projectLocation(id: String): File = projectDirectory(id).takeIf(File::exists) ?: legacyProjectFile(id)
166 private fun recoveryFile(id: String): File = File/projectsDirectory, "${safeId(id)}.recovery.FILE_EXTENSION")
167
168 private fun ensureDirectories() {
169     if (!projectsDirectory.exists() && !projectsDirectory.mkdirs()) {
170         throw IOException("Cannot create projects directory: ${projectsDirectory.path}")
171     }
172     if (!trashDirectory.exists() && !trashDirectory.mkdirs()) {
173         throw IOException("Cannot create project trash: ${trashDirectory.path}")
174     }
175 }
176
177 private fun listProjects(directory: File): List<ProjectSummary> =
178     directory.listFiles()
179         .orEmpty()
180         .asSequence()

```

```

180         .filter { file -> file.isDirectory || (file.isFile && file.extension.equals(FILE_EXTENSION, ignoreCase = true) &&
!file.name.endsWith(".recovery.$FILE_EXTENSION")) }
181     }.mapNotNull { file -> runCatching { readSummary(file) }.getOrNull() }
182     }.sortedByDescending(ProjectSummary::updatedAt)
183     }.toList()
184
185     private fun atomicMove(source: File, target: File) {
186         try {
187             Files.move(
188                 source.toPath(),
189                 target.toPath(),
190                 StandardCopyOption.ATOMIC_MOVE,
191                 StandardCopyOption.REPLACE_EXISTING,
192             )
193         } catch (error: AtomicMoveNotSupportedException) {
194             throw IOException("Atomic project move is not supported", error)
195         }
196     }
197
198     private fun loadProject(id: String) = projectDirectory(id).takeIf(File::isDirectory)
199     ?.let(directoryStore::load)
200     ?: container.load(legacyProjectFile(id))
201
202     /** First regular save migrates an old ZIP project to the directory format. */
203     private fun saveProject(document: ProjectDocument, assets: ProjectAssets) =
204         directoryStore.save(projectDirectory(document.id), document, assets).also {
205             legacyProjectFile(document.id).takeIf(File::isFile)?.delete()
206         }
207
208     private fun readSummary(location: File): ProjectSummary = if (location.isDirectory) {
209         directoryStore.readManifest(location).toSummary(directoryStore.readThumbnail(location))
210     } else {
211         container.readManifest(location).toSummary(container.readThumbnail(location))
212     }
213
214     private fun safeId(id: String): String {
215         require(id.isNotBlank() && id.all { it.isLetterOrDigit() || it == '-' || it == '_' }) {
216             "Unsafe project id"
217         }
218         return id
219     }
220
221     private fun duplicateName(name: String): String = "$name copy".take(80)
222
223     /** Drops binary assets for layers removed from the persisted document. */
224     private fun ProjectAssets.retainDocumentLayers(document: ProjectDocument): ProjectAssets {
225         val allowed = document.layers.map { it.id }.toSet()
226         return copy(
227             layerTiles = layerTiles.filterKeys(allowed::contains),
228             layerPreviewsWebp = layerPreviewsWebp.filterKeys(allowed::contains),
229         )
230     }
231
232     private fun ProjectManifest.toSummary(thumbnail: ByteArray? = null): ProjectSummary = ProjectSummary(
233         id = documentId,
234         name = name,
235         width = width,
236         height = height,
237         updatedAt = updatedAt,
238         thumbnailPath = thumbnailPath,
239         thumbnailBytes = thumbnail,
240         thumbnailVersion = thumbnailVersion,
241     )
242
243     private val trashDirectory: File
244         get() = File(projectsDirectory, TRASH_DIRECTORY)
245
246     private companion object {
247         const val FILE_EXTENSION = "wetink"
248         const val TRASH_DIRECTORY = ".trash"
249         // Valid transparent 1x1 WebP until a GL-generated project preview is available.
250         val DEFAULT_THUMBNAIL_WEBP: ByteArray = Base64.getDecoder().decode(
251             "UklGRiIAAABXRJQVIA4IBYAAADQAwCdASoBAAEAAUAmJaQAA3AA/vuUAAA=",
252         )
253     }
254 }

```

10. app/src/main/java/com/wetinknext/data/project/ProjectRepository.kt

```
1 package com.wetinknext.data.project
2
3 import com.wetinknext.domain.document.ProjectDocument
4 import com.wetinknext.domain.document.LoadedWetInkProject
5 import com.wetinknext.domain.document.ProjectAssets
6
7 interface ProjectRepository {
8     suspend fun create(request: CreateProjectRequest): ProjectSummary
9     suspend fun list(): List<ProjectSummary>
10    suspend fun listTrash(): List<TrashedProjectSummary>
11    suspend fun open(id: String): ProjectDocument
12    /** Reads document metadata and all layer payloads needed to build a GPU session. */
13    suspend fun openForEditor(id: String): LoadedWetInkProject
14    suspend fun save(document: ProjectDocument)
15    /** Atomically replaces only the supplied layer payloads; other layer data is retained. */
16    suspend fun save(document: ProjectDocument, changedLayerTiles: Map<Long, ByteArray>)
17    suspend fun save(
18        document: ProjectDocument,
19        changedLayerTiles: Map<Long, ByteArray>,
20        thumbnailWebp: ByteArray?,
21        layerPreviewsWebp: Map<Long, ByteArray> = emptyMap(),
22    )
23    suspend fun saveRecovery(document: ProjectDocument, changedLayerTiles: Map<Long, ByteArray>)
24    suspend fun clearRecovery(id: String)
25    suspend fun openRecovery(id: String): LoadedWetInkProject?
26    suspend fun rename(id: String, name: String)
27    suspend fun duplicate(id: String): ProjectSummary
28    suspend fun moveToTrash(id: String)
29    suspend fun restore(id: String)
30    suspend fun deleteForever(id: String)
31 }
32
33 data class CreateProjectRequest(
34     val name: String,
35     val width: Int = ProjectDocument.DEFAULT_WIDTH,
36     val height: Int = ProjectDocument.DEFAULT_HEIGHT,
37     val dpi: Int = ProjectDocument.DEFAULT_DPI,
38     val colorProfile: String = ProjectDocument.SRGB_PROFILE,
39 )
40
41 /** Metadata for the gallery. No layer tile data is loaded to create this item. */
42 data class ProjectSummary(
43     val id: String,
44     val name: String,
45     val width: Int,
46     val height: Int,
47     val updatedAt: Long,
48     val thumbnailPath: String?,
49     val thumbnailBytes: ByteArray? = null,
50     /** Cache version for the gallery WebP; metadata loading remains tile-free. */
51     val thumbnailVersion: Long = 0L,
52 )
53
54 data class TrashedProjectSummary(
55     val project: ProjectSummary,
56     val deletedAt: Long,
57 )
```


11. app/src/main/java/com/wetinknext/data/project/ThumbnailEncoder.kt

```
1 package com.wetinknext.data.project
2
3 import android.graphics.Bitmap
4 import android.os.Build
5 import com.wetinknext.engine.core.ThumbnailCapture
6 import java.io.ByteArrayOutputStream
7 import kotlin.math.pow
8 import kotlin.math.roundToInt
9
10 /** CPU-only encoder. Call from a background coroutine, never from the GL thread. */
11 object ThumbnailEncoder {
12     fun encodeWebp(image: ThumbnailCapture.Rgba): ByteArray {
13         val pixels = IntArray(image.width * image.height)
14         for (destinationY in 0 until image.height) {
15             // ThumbnailRenderer already flips glReadPixels into Bitmap order.
16             var source = destinationY * image.width * 4
17             val destination = destinationY * image.width
18             for (x in 0 until image.width) {
19                 val redLinear = (image.pixels[source++].toInt() and 0xFF) / 255f
20                 val greenLinear = (image.pixels[source++].toInt() and 0xFF) / 255f
21                 val blueLinear = (image.pixels[source++].toInt() and 0xFF) / 255f
22                 val a = image.pixels[source++].toInt() and 0xFF
23                 val r = (linearToSrgb(redLinear) * 255f).roundToInt().coerceIn(0, 255)
24                 val g = (linearToSrgb(greenLinear) * 255f).roundToInt().coerceIn(0, 255)
25                 val b = (linearToSrgb(blueLinear) * 255f).roundToInt().coerceIn(0, 255)
26                 pixels[destination + x] = (a shl 24) or (r shl 16) or (g shl 8) or b
27             }
28         }
29         val bitmap = Bitmap.createBitmap(pixels, image.width, image.height, Bitmap.Config.ARGB_8888)
30         return ByteArrayOutputStream().use { output ->
31             check(bitmap.compress(webpFormat(), 88, output)) { "WebP encoding failed" }
32             bitmap.recycle()
33             output.toByteArray()
34         }
35     }
36
37     @Suppress("DEPRECATION")
38     private fun webpFormat(): Bitmap.CompressFormat =
39         if (Build.VERSION.SDK_INT >= Build.VERSION_CODES.R) {
40             Bitmap.CompressFormat.WEBP_LOSSY
41         } else {
42             Bitmap.CompressFormat.WEBP
43         }
44
45     private fun linearToSrgb(value: Float): Float {
46         val linear = value.coerceIn(0f, 1f)
47         return if (linear <= 0.0031308f) linear * 12.92f
48         else (1.055 * linear.toDouble().pow(1.0 / 2.4) - 0.055).toFloat()
49     }
50 }
```

12. app/src/main/java/com/wetinknext/domain/animation/AnimationModels.kt

```
1 package com.wetinknext.domain.animation
2
3 import kotlinx.serialization.Serializable
4
5 @Serializable
6 enum class AnimationPlaybackMode {
7     LOOP,
8     PING_PONG,
9     ONE_SHOT,
10 }
11
12 @Serializable
13 enum class AnimationFrameRole {
14     NORMAL,
15     BACKGROUND,
16     FOREGROUND,
17 }
18
19 @Serializable
20 data class OnionSkinSettings(
21     val enabled: Boolean = false, // Disabled by default until renderer supports it
22     val previousFrames: Int = 1,
23     val nextFrames: Int = 1,
24     val opacity: Float = 0.35f,
25     val previousColorArgb: Int = 0xFFFFF4FA3.toInt(),
26     val nextColorArgb: Int = 0xFF4A8DFF.toInt(),
27     val blendPrimaryFrame: Boolean = false,
28 )
29
30 @Serializable
31 data class AnimationFrame(
32     val id: Long,
33     val layerIds: List<Long>,
34     val holdFrames: Int = 1,
35     val role: AnimationFrameRole = AnimationFrameRole.NORMAL,
36 )
37
38 @Serializable
39 data class AnimationDocument(
40     val enabled: Boolean = false,
41     val framesPerSecond: Int = 12,
42     val playbackMode: AnimationPlaybackMode = AnimationPlaybackMode.LOOP,
43     val onionSkin: OnionSkinSettings = OnionSkinSettings(),
44     val frames: List<AnimationFrame> = emptyList(),
45 )
```

13. app/src/main/java/com/wetinknext/domain/animation/AnimationRenderPlan.kt

```
1 package com.wetinknext.domain.animation
2
3 /**
4  * Defines which frames and roles should be rendered in the current view.
5  */
6 data class AnimationRenderPlan(
7     val backgroundFrame: AnimationFrame?,
8     val currentFrame: AnimationFrame?,
9     val foregroundFrame: AnimationFrame?,
10    val previousOnionFrames: List<AnimationFrame>,
11    val nextOnionFrames: List<AnimationFrame>,
12 )
13
14 /**
15  * Logic to decide which layers are visible based on the animation document.
16  * This is a pure function for easy testing.
17  */
18 fun buildAnimationRenderPlan(
19     document: AnimationDocument,
20     currentFrameId: Long,
21 ): AnimationRenderPlan {
22     if (!document.enabled) {
23         return AnimationRenderPlan(null, null, null, emptyList(), emptyList())
24     }
25
26     val frames = document.frames
27     val currentIndex = frames.indexOfFirst { it.id == currentFrameId }
28
29     val bgFrame = frames.find { it.role == AnimationFrameRole.BACKGROUND }
30     val fgFrame = frames.find { it.role == AnimationFrameRole.FOREGROUND }
31     val current = if (currentIndex >= 0) frames[currentIndex] else null
32
33     val prevOnions = mutableListOf<AnimationFrame>()
34     val nextOnions = mutableListOf<AnimationFrame>()
35
36     if (document.onionSkin.enabled && currentIndex >= 0) {
37         // Previous frames
38         for (i in 1..document.onionSkin.previousFrames) {
39             val idx = currentIndex - i
40             if (idx >= 0) {
41                 val f = frames[idx]
42                 if (f.role == AnimationFrameRole.NORMAL) prevOnions.add(f)
43             }
44         }
45         // Next frames
46         for (i in 1..document.onionSkin.nextFrames) {
47             val idx = currentIndex + i
48             if (idx < frames.size) {
49                 val f = frames[idx]
50                 if (f.role == AnimationFrameRole.NORMAL) nextOnions.add(f)
51             }
52         }
53     }
54
55     return AnimationRenderPlan(
56         backgroundFrame = bgFrame,
57         currentFrame = current,
58         foregroundFrame = fgFrame,
59         previousOnionFrames = prevOnions,
60         nextOnionFrames = nextOnions
61     )
62 }
```

14. app/src/main/java/com/wetinknext/domain/animation/AnimationTimeline.kt

```

1 package com.wetinknext.domain.animation
2
3 /**
4  * Creates a default set of animation frames from a list of layer IDs.
5  * Each layer becomes its own frame. System "Background" (usually ID 1) should be filtered out by the caller.
6  */
7 fun createFramesFromLayers(layerIds: List<Long>): List<AnimationFrame> {
8     return layerIds.map { layerId ->
9         AnimationFrame(
10             id = layerId, // Use layerId as initial frame ID for simplicity in 1:1 mapping
11             layerIds = listOf(layerId)
12         )
13     }
14 }
15
16 /**
17  * Ensures the animation document is valid given the currently existing layers.
18  * Removes dead layer references, empty frames, and enforces range limits.
19  */
20 fun normalizedAnimationDocument(
21     document: AnimationDocument,
22     existingLayerIds: Set<Long>,
23 ): AnimationDocument {
24     return normalizedAnimationDocument(
25         document = document,
26         layersInDocumentOrder = existingLayerIds.map { AnimationLayerInfo(id = it) },
27     )
28 }
29
30 /** Minimal layer data needed by the timeline. Kept independent from OpenGL resources. */
31 data class AnimationLayerInfo(
32     val id: Long,
33     val isCanvasBackgroundLayer: Boolean = false,
34     val isClipping: Boolean = false,
35 )
36
37 /**
38  * Normalizes frames against the real document order. Canvas background never becomes a frame.
39  * Layer IDs inside every frame are also kept in document order, which is required for clipping.
40  */
41 fun normalizedAnimationDocument(
42     document: AnimationDocument,
43     layersInDocumentOrder: List<AnimationLayerInfo>,
44 ): AnimationDocument {
45     val order = layersInDocumentOrder.mapIndexed { index, layer -> layer.id to index }.toMap()
46     val animatableIds = layersInDocumentOrder
47         .filterNot { it.isCanvasBackgroundLayer }
48         .map { it.id }
49     val usedLayerIds = mutableSetOf<Long>()
50
51     val normalizedFrames = document.frames.mapNotNull { frame ->
52         val validLayerIds = frame.layerIds
53             .filter { id -> id in order && id !in usedLayerIds }
54             .sortedBy { order.getOrDefault(it, 0) }
55
56         if (validLayerIds.isEmpty()) {
57             null
58         } else {
59             usedLayerIds.addAll(validLayerIds)
60             frame.copy(
61                 layerIds = validLayerIds,
62                 holdFrames = frame.holdFrames.coerceIn(1, 120)
63             )
64         }
65     }
66     // A layer can belong to only one frame. Any newly created document layer gets its own frame.
67     val missingLayerIds = animatableIds.filter { it !in usedLayerIds }
68     val newFrames = missingLayerIds.map { layerId ->
69         AnimationFrame(id = layerId, layerIds = listOf(layerId))
70     }
71     return document.copy(
72         framesPerSecond = document.framesPerSecond.coerceIn(1, 60),
73         frames = normalizedFrames + newFrames
74     )
75 }
76
77 /**
78  * Combines multiple layers into a single animation frame.
79  */
80 fun groupLayersIntoFrame(
81     document: AnimationDocument,
82     layerIdsToGroup: List<Long>,
83     newFrameId: Long = System.nanoTime()
84 ): AnimationDocument {
85     val orderedIds = layerIdsToGroup.distinct()
86     val idsSet = orderedIds.toSet()
87     if (idsSet.isEmpty()) return document
88
89     val insertionIndex = document.frames.indexOfFirst { frame -> frame.layerIds.any { it in idsSet } }
90     val cleanedFrames = document.frames.map { frame ->

```

```

91     frame.copy(layerIds = frame.layerIds.filter { it !in idsSet })
92   }.filter { it.layerIds.isNotEmpty() }.toMutableList()
93   val newFrame = AnimationFrame(id = newFrameId, layerIds = orderedIds)
94   val targetIndex = if (insertionIndex < 0) cleanedFrames.size else insertionIndex.coerceAtMost(cleanedFrames.size)
95   cleanedFrames.add(targetIndex, newFrame)
96   return document.copy(frames = cleanedFrames)
97 }
98
99 sealed interface AnimationFrameGroupingValidation {
100   data class Valid(val layerIdsInDocumentOrder: List<Long>) : AnimationFrameGroupingValidation
101   data object EmptySelection : AnimationFrameGroupingValidation
102   data class MissingClippingBase(val clippingLayerId: Long) : AnimationFrameGroupingValidation
103   data class MissingClippingLayer(val baseLayerId: Long, val clippingLayerId: Long) : AnimationFrameGroupingValidation
104 }
105
106 /**
107  * A clipping layer and its base must live in one animation frame: otherwise a frame would render
108  * with a different compositing result than the document. The selection is returned in document order.
109  */
110 fun validateAnimationFrameGrouping(
111   selectedLayerIds: Set<Long>,
112   layersInDocumentOrder: List<AnimationLayerInfo>,
113 ): AnimationFrameGroupingValidation {
114   val layers = layersInDocumentOrder.filterNot { it.isCanvasBackgroundLayer }
115   val selected = selectedLayerIds.intersect(layers.map { it.id }.toSet())
116   if (selected.isEmpty()) return AnimationFrameGroupingValidation.EmptySelection
117
118   val baseByClippingId = mutableMapOf<Long, Long>()
119   layers.forEachIndexed { index, layer ->
120     if (layer.isClipping) {
121       val base = layers.subList(0, index).lastOrNull { !it.isClipping }
122       ?: return AnimationFrameGroupingValidation.MissingClippingBase(layer.id)
123       baseByClippingId[layer.id] = base.id
124       if (layer.id in selected && base.id !in selected) {
125         return AnimationFrameGroupingValidation.MissingClippingLayer(layer.id, base.id)
126       }
127     }
128   }
129   baseByClippingId.forEach { (clippingId, baseId) ->
130     if (baseId in selected && clippingId !in selected) {
131       return AnimationFrameGroupingValidation.MissingClippingLayer(baseId, clippingId)
132     }
133   }
134   return AnimationFrameGroupingValidation.Valid(layers.filter { it.id in selected }.map { it.id })
135 }
136
137 /**
138  * Expands frames into a flat list of frame IDs to be played back, accounting for holdFrames.
139  */
140 fun expandedPlaybackFrameIds(
141   frames: List<AnimationFrame>,
142 ): List<Long> {
143   return frames.flatMap { frame ->
144     List(frame.holdFrames) { frame.id }
145   }
146 }
147
148 data class PlaybackStep(
149   val nextIndex: Int,
150   val nextDirection: Int, // 1 for forward, -1 for backward
151   val shouldStop: Boolean = false
152 )
153
154 /**
155  * Calculates the next index in the playback sequence.
156  */
157 fun nextPlaybackIndex(
158   currentIndex: Int,
159   direction: Int,
160   frameCount: Int,
161   mode: AnimationPlaybackMode,
162 ): PlaybackStep {
163   if (frameCount <= 0) return PlaybackStep(0, 1, true)
164   if (frameCount == 1) return PlaybackStep(0, 1, mode == AnimationPlaybackMode.ONE_SHOT)
165
166   var nextDir = direction
167   var nextIdx = currentIndex + direction
168   var stop = false
169
170   when (mode) {
171     AnimationPlaybackMode.LOOP -> {
172       if (nextIdx >= frameCount) nextIdx = 0
173       if (nextIdx < 0) nextIdx = frameCount - 1
174     }
175     AnimationPlaybackMode.PING_PONG -> {
176       if (nextIdx >= frameCount) {
177         nextIdx = (frameCount - 2).coerceAtLeast(0)
178         nextDir = -1
179       } else if (nextIdx < 0) {
180         nextIdx = (1).coerceAtMost(frameCount - 1)
181         nextDir = 1
182       }
183     }
184   }
185   return PlaybackStep(nextIdx, nextDir, stop)
186 }

```

```
183         }
184         AnimationPlaybackMode.ONE_SHOT -> {
185             if (nextIdx >= frameCount) {
186                 nextIdx = frameCount - 1
187                 stop = true
188             }
189         }
190     }
191
192     return PlaybackStep(nextIdx, nextDir, stop)
193 }
```

15. app/src/main/java/com/wetinknext/domain/document/ProjectDocument.kt

```

1 package com.wetinknext.domain.document
2
3 import com.wetinknext.domain.animation.AnimationDocument
4 import com.wetinknext.engine.brush.BrushPreset
5 import com.wetinknext.engine.canvas.BlendMode
6 import kotlinx.serialization.Serializable
7 import java.util.UUID
8
9 /**
10  * Persisted project structure. Pixel data deliberately lives outside this JSON
11  * document: [LayerDocument.pixelFile] points at its future tile/container data.
12  */
13 @Serializable
14 data class ProjectDocument(
15     val id: String,
16     val name: String,
17     val width: Int,
18     val height: Int,
19     val dpi: Int,
20     val colorProfile: String,
21     val createdAt: Long,
22     val updatedAt: Long,
23     val layers: List<LayerDocument>,
24     val brushes: List<BrushPreset> = emptyList(),
25     val animation: AnimationDocument = AnimationDocument(),
26     val activeLayerId: Long? = null,
27     /** Changes only when the project-wide preview is rebuilt. */
28     val thumbnailVersion: Long = 0L,
29     val version: Int = CURRENT_VERSION,
30 ) {
31     init {
32         require(id.isNotBlank()) { "Project id must not be blank" }
33         require(name.isNotBlank()) { "Project name must not be blank" }
34         require(width > 0 && height > 0) { "Project dimensions must be positive" }
35         require(dpi in 1..2400) { "Project DPI must be within 1..2400" }
36         require(colorProfile.isNotBlank()) { "Project color profile must not be blank" }
37         require(layers.isNotEmpty()) { "A project must contain at least one layer" }
38         require(layers.map(LayerDocument::id).distinct().size == layers.size) {
39             "Layer ids must be unique"
40         }
41         require(activeLayerId == null || layers.any { it.id == activeLayerId }) {
42             "Active layer must belong to the project"
43         }
44         require(version >= 1) { "Project version must be positive" }
45         require(thumbnailVersion >= 0L) { "Project thumbnail version must not be negative" }
46     }
47
48     fun withUpdatedTimestamp(nowMillis: Long): ProjectDocument = copy(updatedAt = nowMillis)
49
50     companion object {
51         const val CURRENT_VERSION = 1
52         const val DEFAULT_WIDTH = 1500
53         const val DEFAULT_HEIGHT = 2000
54         const val DEFAULT_DPI = 300
55         const val SRGB_PROFILE = "sRGB IEC61966-2.1"
56         const val DISPLAY_P3_PROFILE = "Display P3"
57         const val MIN_DIMENSION = 256
58         const val MAX_DIMENSION = 8192
59         const val MIN_DPI = 72
60         const val MAX_DPI = 1200
61         const val MAX_INITIAL_GPU_BYTES = 256L * 1024L * 1024L
62         private const val INITIAL_RENDER_TARGET_COUNT = 3L
63         private const val RGBA16F_BYTES_PER_PIXEL = 8L
64         val SUPPORTED_COLOR_PROFILES = setOf(SRGB_PROFILE, DISPLAY_P3_PROFILE)
65
66         fun newUntitled(
67             name: String = "Untitled",
68             width: Int = DEFAULT_WIDTH,
69             height: Int = DEFAULT_HEIGHT,
70             dpi: Int = DEFAULT_DPI,
71             colorProfile: String = SRGB_PROFILE,
72             nowMillis: Long = System.currentTimeMillis(),
73             id: String = UUID.randomUUID().toString(),
74         ): ProjectDocument {
75             val normalizedProfile = normalizeColorProfile(colorProfile)
76             validateNewCanvas(width, height, dpi, normalizedProfile)
77             return ProjectDocument(
78                 id = id,
79                 name = name,
80                 width = width,
81                 height = height,
82                 dpi = dpi,
83                 colorProfile = normalizedProfile,
84                 createdAt = nowMillis,
85                 updatedAt = nowMillis,
86                 layers = listOf(
87                     LayerDocument(
88                         id = BACKGROUND_LAYER_ID,
89                         name = "Фон",
90                         visible = true,

```

```

91         locked = true,
92         opacity = 1f,
93         blendMode = BlendMode.NORMAL,
94         pixelFile = pixelFileFor(BACKGROUND_LAYER_ID),
95     ),
96     LayerDocument(
97         id = FIRST_PAINT_LAYER_ID,
98         name = "Слой 1",
99         visible = true,
100        locked = false,
101        opacity = 1f,
102        blendMode = BlendMode.NORMAL,
103        pixelFile = pixelFileFor(FIRST_PAINT_LAYER_ID),
104    ),
105 ),
106 activeLayerId = FIRST_PAINT_LAYER_ID,
107 )
108 }
109
110 /** Validates the initial two layer targets plus the transient stroke target. */
111 fun validateNewCanvas(width: Int, height: Int, dpi: Int, colorProfile: String) {
112     require(width in MIN_DIMENSION..MAX_DIMENSION) { "Canvas width must be within $MIN_DIMENSION..$MAX_DIMENSION px" }
113     require(height in MIN_DIMENSION..MAX_DIMENSION) { "Canvas height must be within $MIN_DIMENSION..$MAX_DIMENSION
px" }
114     require(dpi in MIN_DPI..MAX_DPI) { "Canvas DPI must be within $MIN_DPI..$MAX_DPI" }
115     require(normalizeColorProfile(colorProfile) in SUPPORTED_COLOR_PROFILES) { "Unsupported color profile:
$colorProfile" }
116     val estimatedBytes = width.toLong() * height * INITIAL_RENDER_TARGET_COUNT * RGBA16F_BYTES_PER_PIXEL
117     require(estimatedBytes <= MAX_INITIAL_GPU_BYTES) {
118         "Canvas requires ${estimatedBytes / (1024 * 1024)} MB GPU memory; limit is ${MAX_INITIAL_GPU_BYTES / (1024 *
1024)} MB"
119     }
120 }
121
122 /** Keeps older UI values (`sRGB`) compatible with the persisted profile identifier. */
123 fun normalizeColorProfile(value: String): String = when (value.trim()) {
124     "sRGB", SRGB_PROFILE -> SRGB_PROFILE
125     "Display P3", DISPLAY_P3_PROFILE -> DISPLAY_P3_PROFILE
126     else -> value.trim()
127 }
128
129 fun pixelFileFor(layerId: Long): String = "layers/$layerId.tiles"
130
131 private const val BACKGROUND_LAYER_ID = 1L
132 private const val FIRST_PAINT_LAYER_ID = 2L
133 }
134 }
135
136 @Serializable
137 data class LayerDocument(
138     val id: Long,
139     val name: String,
140     val visible: Boolean,
141     val locked: Boolean,
142     val opacity: Float,
143     val blendMode: BlendMode,
144     val pixelFile: String,
145     /** Increments whenever the runtime layer pixels change; useful for preview invalidation. */
146     val thumbnailVersion: Long = 0L,
147 ) {
148     init {
149         require(id >= 0L) { "Layer id must not be negative" }
150         require(name.isNotBlank()) { "Layer name must not be blank" }
151         require(opacity in 0f..1f) { "Layer opacity must be within 0..1" }
152         require(pixelFile.isNotBlank()) { "Layer pixel file must not be blank" }
153         require(thumbnailVersion >= 0L) { "Layer thumbnail version must not be negative" }
154     }
155 }

```


16. app/src/main/java/com/wetinknext/domain/document/WetInkProjectContainer.kt

```

1  package com.wetinknext.domain.document
2
3  import kotlinx.serialization.Serializable
4  import kotlinx.serialization.decodeFromString
5  import kotlinx.serialization.encodeToString
6  import kotlinx.serialization.json.Json
7  import java.io.BufferedInputStream
8  import java.io.BufferedOutputStream
9  import java.io.ByteArrayOutputStream
10 import java.io.File
11 import java.io.IOException
12 import java.nio.file.AtomicMoveNotSupportedException
13 import java.nio.file.Files
14 import java.nio.file.StandardCopyOption
15 import java.util.zip.ZipEntry
16 import java.util.zip.ZipFile
17 import java.util.zip.ZipOutputStream
18
19 @Serializable
20 data class ProjectManifest(
21     val format: String = FORMAT,
22     val formatVersion: Int = FORMAT_VERSION,
23     val documentId: String,
24     val name: String,
25     val width: Int,
26     val height: Int,
27     val documentPath: String = DOCUMENT_ENTRY,
28     val thumbnailPath: String? = null,
29     val thumbnailVersion: Long = 0L,
30     val createdAt: Long,
31     val updatedAt: Long,
32     val layers: List<StoredLayer>,
33 ) {
34     companion object {
35         const val FORMAT = "wetink"
36         const val FORMAT_VERSION = 1
37         const val DOCUMENT_ENTRY = "document.json"
38     }
39 }
40
41 @Serializable
42 data class StoredLayer(
43     val id: Long,
44     val path: String,
45     val byteSize: Long,
46 )
47
48 /** Binary payloads deliberately sit next to the JSON document, not inside it. */
49 data class ProjectAssets(
50     val layerFiles: Map<Long, ByteArray>,
51     val thumbnailWebp: ByteArray? = null,
52     val layerPreviewsWebp: Map<Long, ByteArray> = emptyMap(),
53 )
54
55 data class LoadedWetInkProject(
56     val document: ProjectDocument,
57     val manifest: ProjectManifest,
58     val assets: ProjectAssets,
59 )
60
61 /**
62  * Project ZIP reader/writer. A project is published only by an atomic rename
63  * from `name.wetink.tmp` to `name.wetink`, so a failed save cannot corrupt the
64  * previously published project.
65  */
66 class WetInkProjectContainer(
67     private val clockMillis: () -> Long = System::currentTimeMillis,
68     private val json: Json = Json {
69         encodeDefaults = true
70         ignoreUnknownKeys = true
71         prettyPrint = true
72     },
73 ) {
74     fun save(
75         projectFile: File,
76         document: ProjectDocument,
77         assets: ProjectAssets,
78     ): LoadedWetInkProject {
79         require(projectFile.extension.equals(FILE_EXTENSION, ignoreCase = true)) {
80             "Project file must use .$FILE_EXTENSION extension"
81         }
82         validateAssets(document, assets)
83
84         val savedTimestamp = clockMillis()
85         val savedDocument = document.copy(
86             updatedAt = savedTimestamp,
87             thumbnailVersion = if (assets.thumbnailWebp != null) savedTimestamp else document.thumbnailVersion,
88         )
89         val manifest = ProjectManifest(
90             documentId = savedDocument.id,

```

```

91         name = savedDocument.name,
92         width = savedDocument.width,
93         height = savedDocument.height,
94         thumbnailPath = assets.thumbnailWebp?.let { THUMBNAIL_ENTRY },
95         thumbnailVersion = savedDocument.thumbnailVersion,
96         createdAt = savedDocument.createdAt,
97         updatedAt = savedDocument.updatedAt,
98         layers = savedDocument.layers.map { layer ->
99             StoredLayer(
100                 id = layer.id,
101                 path = layer.pixelFile,
102                 byteSize = checkNotNull(assets.layerTiles[layer.id]).size.toLong(),
103             )
104         },
105     )
106
107     val parent = projectFile.parentFile ?: throw IOException("Project file requires a parent folder")
108     if (!parent.exists() && !parent.mkdirs()) throw IOException("Cannot create ${parent.path}")
109     val temporaryFile = File(parent, "${projectFile.name}.tmp")
110     if (temporaryFile.exists() && !temporaryFile.delete()) {
111         throw IOException("Cannot replace stale temporary project ${temporaryFile.path}")
112     }
113
114     var published = false
115     try {
116         BufferedOutputStream(temporaryFile.outputStream()).use { output ->
117             ZipOutputStream(output).use { zip ->
118                 // Write large layer data first; metadata becomes visible only
119                 // after every payload has been written and the ZIP is closed.
120                 savedDocument.layers.forEach { layer ->
121                     writeEntry(zip, layer.pixelFile, checkNotNull(assets.layerTiles[layer.id]))
122                 }
123                 writeEntry(zip, ProjectManifest.DOCUMENT_ENTRY, json.encodeToString(savedDocument).encodeToByteArray())
124                 assets.thumbnailWebp?.let { writeEntry(zip, THUMBNAIL_ENTRY, it) }
125                 assets.layerPreviewsWebp.forEach { (layerId, preview) ->
126                     writeEntry(zip, previewPathFor(layerId), preview)
127                 }
128                 writeEntry(zip, MANIFEST_ENTRY, json.encodeToString(manifest).encodeToByteArray())
129             }
130         }
131         if (temporaryFile.length() <= 0L) throw IOException("Temporary project is empty")
132         atomicPublish(temporaryFile, projectFile)
133         published = true
134     } finally {
135         if (!published && temporaryFile.exists()) temporaryFile.delete()
136     }
137
138     return LoadedWetInkProject(savedDocument, manifest, assets)
139 }
140
141 fun load(projectFile: File): LoadedWetInkProject {
142     require(projectFile.isFile) { "Project does not exist: ${projectFile.path}" }
143     ZipFile(projectFile).use { zip ->
144         val manifest = readJson<ProjectManifest>(zip, MANIFEST_ENTRY)
145         require(manifest.format == ProjectManifest.FORMAT) { "Unsupported project format" }
146         require(manifest.formatVersion == ProjectManifest.FORMAT_VERSION) { "Unsupported project version" }
147
148         val document = readJson<ProjectDocument>(zip, manifest.documentPath)
149         require(document.id == manifest.documentId) { "Manifest/document id mismatch" }
150         require(document.updatedAt == manifest.updatedAt) { "Manifest/document timestamp mismatch" }
151         require(manifest.layers.map { it.id } == document.layers.map { it.id }) {
152             "Manifest/document layer order mismatch"
153         }
154
155         val tiles = document.layers.associate { layer ->
156             val stored = manifest.layers.first { it.id == layer.id }
157             require(stored.path == layer.pixelFile) { "Layer path mismatch for ${layer.id}" }
158             val bytes = readEntry(zip, layer.pixelFile)
159             require(bytes.size.toLong() == stored.byteSize) { "Layer size mismatch for ${layer.id}" }
160             layer.id to bytes
161         }
162         val previews = document.layers.mapNotNull { layer ->
163             val entry = zip.getEntry(previewPathFor(layer.id)) ?: return@mapNotNull null
164             layer.id to readEntry(zip, entry)
165         }.toMap()
166         val thumbnail = manifest.thumbnailPath?.let { readEntry(zip, it) }
167
168         return LoadedWetInkProject(
169             document = document,
170             manifest = manifest,
171             assets = ProjectAssets(tiles, thumbnail, previews),
172         )
173     }
174 }
175
176 /** Reads just the compact manifest; no document JSON or tile payload is loaded. */
177 fun readManifest(projectFile: File): ProjectManifest {
178     require(projectFile.isFile) { "Project does not exist: ${projectFile.path}" }
179     ZipFile(projectFile).use { zip ->
180         val manifest = readJson<ProjectManifest>(zip, MANIFEST_ENTRY)
181         require(manifest.format == ProjectManifest.FORMAT) { "Unsupported project format" }
182         require(manifest.formatVersion == ProjectManifest.FORMAT_VERSION) { "Unsupported project version" }

```

```

183         return manifest
184     }
185 }
186
187 fun readThumbnail(projectFile: File): ByteArray? {
188     ZipFile(projectFile).use { zip ->
189         val manifest = readJson<ProjectManifest>(zip, MANIFEST_ENTRY)
190         return manifest.thumbnailPath?.let { readEntry(zip, it) }
191     }
192 }
193
194 /** Opens only project metadata. Tile bytes remain in the ZIP until requested. */
195 fun readDocument(projectFile: File): ProjectDocument {
196     require(projectFile.isFile) { "Project does not exist: ${projectFile.path}" }
197     ZipFile(projectFile).use { zip ->
198         val manifest = readJson<ProjectManifest>(zip, MANIFEST_ENTRY)
199         require(manifest.format == ProjectManifest.FORMAT) { "Unsupported project format" }
200         require(manifest.formatVersion == ProjectManifest.FORMAT_VERSION) { "Unsupported project version" }
201         val document = readJson<ProjectDocument>(zip, manifest.documentPath)
202         require(document.id == manifest.documentId) { "Manifest/document id mismatch" }
203         require(document.updatedAt == manifest.updatedAt) { "Manifest/document timestamp mismatch" }
204         return document
205     }
206 }
207
208 private fun validateAssets(document: ProjectDocument, assets: ProjectAssets) {
209     val expectedIds = document.layers.map { it.id }.toSet()
210     require(assets.layerTiles.keys == expectedIds) { "Every document layer requires one tile payload" }
211     require(assets.layerPreviewsWebp.keys.all(expectedIds::contains)) {
212         "Preview references an unknown layer"
213     }
214     document.layers.forEach { layer ->
215         require(isSafeLayerPath(layer.pixelFile)) { "Unsafe layer path: ${layer.pixelFile}" }
216     }
217 }
218
219 private fun atomicPublish(temporaryFile: File, projectFile: File) {
220     try {
221         Files.move(
222             temporaryFile.toPath(),
223             projectFile.toPath(),
224             StandardCopyOption.ATOMIC_MOVE,
225             StandardCopyOption.REPLACE_EXISTING,
226         )
227     } catch (error: AtomicMoveNotSupportedException) {
228         throw IOException("Atomic project publish is not supported for ${projectFile.path}", error)
229     }
230 }
231
232 private fun writeEntry(zip: ZipOutputStream, path: String, bytes: ByteArray) {
233     zip.putNextEntry(ZipEntry(path))
234     zip.write(bytes)
235     zip.closeEntry()
236 }
237
238 private inline fun <reified T> readJson(zip: ZipFile, path: String): T =
239     json.decodeFromStream(readEntry(zip, path).decodeToString())
240
241 private fun readEntry(zip: ZipFile, path: String): ByteArray {
242     val entry = zip.getEntry(path) ?: throw IOException("Missing project entry: $path")
243     return readEntry(zip, entry)
244 }
245
246 private fun readEntry(zip: ZipFile, entry: ZipEntry): ByteArray {
247     if (entry.size > MAX_ENTRY_BYTES) throw IOException("Project entry is too large: ${entry.name}")
248     BufferedInputStream(zip.getInputStream(entry)).use { input ->
249         val output = ByteArrayOutputStream(entry.size.coerceAtLeast(0L).coerceAtMost(MAX_ENTRY_BYTES).toInt())
250         val buffer = ByteArray(READ_BUFFER_BYTES)
251         var total = 0L
252         while (true) {
253             val read = input.read(buffer)
254             if (read < 0) break
255             total += read
256             if (total > MAX_ENTRY_BYTES) {
257                 throw IOException("Project entry is too large: ${entry.name}")
258             }
259             output.write(buffer, 0, read)
260         }
261         return output.toByteArray()
262     }
263 }
264
265 private fun isSafeLayerPath(path: String): Boolean =
266     path.startsWith("layers/") && !path.contains("..") && !path.startsWith('/')
267
268 private companion object {
269     const val FILE_EXTENSION = "wetink"
270     const val MANIFEST_ENTRY = "manifest.json"
271     const val THUMBNAIL_ENTRY = "thumbnail.webp"
272     const val MAX_ENTRY_BYTES = 256L * 1024L * 1024L
273     const val READ_BUFFER_BYTES = 16 * 1024
274 }

```

```
275         fun previewPathFor(layerId: Long): String = "previews/$layerId.webp"
276     }
277 }
```

17. app/src/main/java/com/wetinknext/engine/brush/BlendController.kt

```
1 package com.wetinknext.engine.brush
2
3 import android.opengl.GLES30
4
5 class BlendController {
6
7     fun begin(policy: BlendPolicy) {
8         GLES30.glEnable(GLES30.GL_BLEND)
9         // NON_BUILDUP needs a dedicated accumulation mask. Until that pass is
10        // introduced, both policies use the correct premultiplied source-over.
11        GLES30.glBlendEquation(GLES30.GL_FUNC_ADD)
12        GLES30.glBlendFunc(
13            GLES30.GL_ONE,
14            GLES30.GL_ONE_MINUS_SRC_ALPHA,
15        )
16    }
17
18    fun end() {
19        GLES30.glBlendEquation(GLES30.GL_FUNC_ADD)
20        GLES30.glBlendFunc(
21            GLES30.GL_ONE,
22            GLES30.GL_ONE_MINUS_SRC_ALPHA,
23        )
24        GLES30.glDisable(GLES30.GL_BLEND)
25    }
26 }
```

18. app/src/main/java/com/wetinknext/engine/brush/BrushDynamics.kt

```

1  package com.wetinknext.engine.brush
2
3  import kotlin.math.atan2
4  import kotlin.math.pow
5  import kotlin.math.sqrt
6
7  object BrushDynamics {
8
9      fun tiltMagnitude(
10         tiltX: Float,
11         tiltY: Float,
12     ): Float {
13         return sqrt(
14             tiltX * tiltX +
15             tiltY * tiltY,
16         ).coerceIn(0f, 1f)
17     }
18
19     /**
20      * Resolves the final radius and opacity for a single dab based on input.
21      */
22     fun resolve(
23         settings: BrushSettings,
24         pressure: Float,
25         tiltX: Float,
26         tiltY: Float,
27         velocity: Float,
28         orientationRad: Float,
29         out: ResolvedDab,
30     ) {
31         val p = pressure
32             .coerceIn(0f, 1f)
33             .let { it.toDouble().pow(settings.pressureGamma.toDouble()).toFloat() }
34
35         val tilt = tiltMagnitude(tiltX, tiltY)
36
37         val pressureSize = if (settings.pressureToSize) {
38             settings.minSizeRatio + (1f - settings.minSizeRatio) * p
39         } else {
40             1f
41         }
42         val tiltSize = 1f + settings.tiltToSize * tilt
43         val normalizedVelocity = (velocity / VELOCITY_REFERENCE_PX_PER_SECOND)
44             .coerceIn(0f, 1f)
45         val velocitySize = 1f + settings.velocityToSize * normalizedVelocity
46         out.radius = (
47             settings.baseRadiusPx * pressureSize * tiltSize * velocitySize
48         ).coerceAtLeast(0.25f)
49
50         val pressureOpacity = if (settings.pressureToOpacity) p else 1f
51         val velocityOpacity = 1f - settings.velocityToOpacity * normalizedVelocity
52
53         // Tilt must not make a dab more opaque.
54         val tiltOpacity = 1f - (0.45f * settings.tiltToOpacity * tilt)
55         out.coverage = (pressureOpacity * tiltOpacity * velocityOpacity).coerceIn(0f, 1f)
56
57         // Local dab alpha only. Global brush opacity is applied during stroke blit.
58         out.opacity = out.coverage
59         out.rotation = orientationRad + settings.tiltToRotation * tiltAngle(tiltX, tiltY)
60     }
61
62     private fun tiltAngle(tiltX: Float, tiltY: Float): Float = atan2(tiltY, tiltX)
63
64     private const val VELOCITY_REFERENCE_PX_PER_SECOND = 2_500f
65 }
66
67 data class ResolvedDab(
68     var radius: Float = 0f,
69     var opacity: Float = 1f,
70     var coverage: Float = 1f,
71     var rotation: Float = 0f,
72 )

```

19. app/src/main/java/com/wetinknext/engine/brush/BrushLibrary.kt

```

1  package com.wetinknext.engine.brush
2
3  import androidx.compose.material.icons.Icons
4  import androidx.compose.material.icons.filled.Brush
5  import androidx.compose.material.icons.filled.Create
6  import androidx.compose.material.icons.filled.Star
7  import androidx.compose.ui.graphics.vector.ImageVector
8
9  data class BrushUiCategory(
10     val name: String,
11     val icon: ImageVector,
12     val brushes: List<BrushPreset>,
13 )
14
15 object BrushLibrary {
16     val pencil6B = BrushPreset(
17         id = "pencil_6b",
18         settings = BrushSettings(
19             name = "Pencil 6B",
20             category = "Pencil",
21             renderMode = BrushRenderMode.STAMP,
22             baseRadiusPx = 8f,
23             opacity = 0.82f,
24             flow = 0.65f,
25             spacing = 0.08f,
26             spacingUsesDiameter = true,
27             hardness = 0.72f,
28             smoothing = 0.08f,
29             streamline = 0.04f,
30             pressureToSize = true,
31             pressureToOpacity = true,
32             pressureGamma = 1.25f,
33             minSizeRatio = 0.30f,
34             tiltToSize = 0.55f,
35             grainAssetPath = "asset:brush/pencil_6b_grain.png",
36             grainCanvasLocked = true,
37             grainScale = 5.5f,
38             textureDepth = 0.65f,
39             textureContrast = 1.35f,
40             blendPolicy = BlendPolicy.NORMAL_BUILDUP,
41         ),
42     )
43
44     val gPen = BrushPreset(
45         id = "g_pen",
46         settings = BrushSettings(
47             name = "G-Pen",
48             category = "Ink",
49             renderMode = BrushRenderMode.RIBBON,
50             baseRadiusPx = 4.5f,
51             opacity = 1f,
52             flow = 1f,
53             smoothing = 0.35f,
54             streamline = 0.22f,
55             pressureToSize = true,
56             pressureToOpacity = false,
57             pressureGamma = 1.7f,
58             minSizeRatio = 0.06f,
59             blendPolicy = BlendPolicy.NON_BUILDUP,
60         )
61     )
62
63     /** Baseline ink preset for checking the capsule path without geometric taper. */
64     val pen = BrushPreset(
65         id = "pen",
66         settings = gPen.settings.copy(
67             name = "Pen",
68             ribbon = gPen.settings.ribbon.copy(
69                 taperStartPx = 0f,
70                 taperEndPx = 0f,
71             ),
72         ),
73     )
74
75     val allCategories = listOf(
76         BrushUiCategory(
77             name = "Pencil",
78             icon = Icons.Default.Create,
79             brushes = listOf(pencil6B)
80         ),
81         BrushUiCategory(
82             name = "Ink",
83             icon = Icons.Default.Brush,
84             brushes = listOf(gPen, pen)
85         ),
86         BrushUiCategory(
87             name = "Favorites",
88             icon = Icons.Default.Star,
89             brushes = emptyList()
90         )
91     )

```

```
91      )  
92  }
```


20. app/src/main/java/com/wetinknext/engine/brush/BrushPreset.kt

```
1 package com.wetinknext.engine.brush
2
3 import kotlinx.serialization.Serializable
4
5 @Serializable
6 data class BrushPreset(
7     val id: String,
8     val settings: BrushSettings,
9 )
```

21. app/src/main/java/com/wetinknext/engine/brush/BrushRepository.kt

```
1 package com.wetinknext.engine.brush
2
3 import kotlinx.serialization.encodeToString
4 import kotlinx.serialization.json.Json
5
6 class BrushRepository(
7     private val json: Json = defaultJson,
8 ) {
9     fun encode(preset: BrushPreset): String =
10         json.encodeToString(preset)
11
12     fun decode(value: String): BrushPreset =
13         json.decodeFromString<BrushPreset>(value).let { preset ->
14             preset.copy(settings = preset.settings.resolved())
15         }
16
17     companion object {
18         val defaultJson = Json {
19             encodeDefaults = true
20             ignoreUnknownKeys = true
21             explicitNulls = false
22         }
23     }
24 }
```

22. app/src/main/java/com/wetinknext/engine/brush/BrushSettings.kt

```

1  package com.wetinknext.engine.brush
2
3  import kotlinx.serialization.Serializable
4
5  @Serializable
6  enum class BrushRenderMode { STAMP, RIBBON, WET }
7
8  @Serializable
9  enum class BlendPolicy { NORMAL_BUILDUP, NON_BUILDUP }
10
11 @Serializable
12 enum class RibbonCap { ROUND, BUTT }
13
14 @Serializable
15 enum class RibbonJoin { MITER, ROUND, BEVEL }
16
17 @Serializable
18 data class RibbonSettings(
19     val minWidthRatio: Float = 0.06f,
20     val taperStartPx: Float = 8f,
21     val taperEndPx: Float = 14f,
22     val miterLimit: Float = 3f,
23     val aaWidthPx: Float = 1f,
24     val cap: RibbonCap = RibbonCap.ROUND,
25     val join: RibbonJoin = RibbonJoin.ROUND,
26     val minPointDistancePx: Float = 0.5f,
27 )
28
29 @Serializable
30 data class WetSettings(val wetness: Float = 0f, val spread: Float = 0f, val bleed: Float = 0f)
31
32 @Serializable
33 data class BrushSettings(
34     val name: String = "Debug Stamp",
35     val category: String = "Debug",
36     val renderMode: BrushRenderMode = BrushRenderMode.STAMP,
37     /**
38      * Internal brush radius in document pixels.
39      * UI displays diameter = baseRadiusPx * 2.
40      */
41     val baseRadiusPx: Float = 14f,
42     val opacity: Float = 1f,
43     val flow: Float = 1f,
44     val spacing: Float = 0.16f,
45     val spacingUsesDiameter: Boolean = true,
46     val hardness: Float = 1f,
47     val colorArgb: Long = 0xFF000000L,
48     val smoothing: Float = 0f,
49     val streamline: Float = 0f,
50     val antiAliasLevel: Int = 2,
51     val useTempStrokeBuffer: Boolean = false,
52     val pressureToSize: Boolean = true,
53     val pressureToOpacity: Boolean = true,
54     val pressureGamma: Float = 1f,
55     val minSizeRatio: Float = 0.05f,
56     val velocityToSize: Float = 0f,
57     val velocityToOpacity: Float = 0f,
58     val tiltToSize: Float = 0f,
59     val tiltToOpacity: Float = 0f,
60     val tiltToRotation: Float = 0f,
61     val rotationJitter: Float = 0f,
62     val sizeJitter: Float = 0f,
63     val opacityJitter: Float = 0f,
64     val scatter: Float = 0f,
65     val shapeAssetPath: String? = null,
66     val grainAssetPath: String? = null,
67     val grainScale: Float = 1f,
68     val grainCanvasLocked: Boolean = true,
69     val rgbToAlpha: Boolean = false,
70     val textureContrast: Float = 1f,
71     val textureDepth: Float = 1f,
72     val pixelPen: Boolean = false,
73     val squareStroke: Boolean = false,
74     val noAntialias: Boolean = false,
75     val blendPolicy: BlendPolicy = BlendPolicy.NORMAL_BUILDUP,
76     val ribbon: RibbonSettings = RibbonSettings(),
77     val wet: WetSettings = WetSettings(),
78 ) {
79     /** Returns a settings copy safe for every engine path. */
80     fun resolved(): BrushSettings {
81         val safeRadius = baseRadiusPx.coerceIn(0.25f, 4096f)
82         val safeOpacity = opacity.coerceIn(0f, 1f)
83         val safeFlow = flow.coerceIn(0f, 1f)
84         val safeSpacing = spacing.coerceIn(0.001f, 4f)
85         val safeGamma = pressureGamma.coerceIn(0.05f, 8f)
86         val safeMinSize = minSizeRatio.coerceIn(0.01f, 1f)
87
88         val safeVelocityToSize = velocityToSize.coerceIn(0f, 1f)
89         val safeVelocityToOpacity = velocityToOpacity.coerceIn(0f, 1f)
90         val safeTiltToSize = tiltToSize.coerceIn(0f, 1f)

```

```

91     val safeTiltToOpacity = tiltToOpacity.coerceIn(0f, 1f)
92     val safeTiltToRotation = tiltToRotation.coerceIn(0f, 1f)
93     val safeSizeJitter = sizeJitter.coerceIn(0f, 1f)
94     val safeOpacityJitter = opacityJitter.coerceIn(0f, 1f)
95     val safeRotationJitter = rotationJitter.coerceIn(0f, 1f)
96     val safeScatter = scatter.coerceAtLeast(0f)
97
98     val safeGrainScale = grainScale.coerceIn(0.0001f, 256f)
99     val safeTextureDepth = textureDepth.coerceIn(0f, 1f)
100    val safeTextureContrast = textureContrast.coerceIn(0f, 4f)
101    val safeAa = antiAliasLevel.coerceIn(0, 3)
102
103    val safeRibbon = ribbon.copy(
104        minWidthRatio = ribbon.minWidthRatio.coerceIn(0.01f, 1f),
105        taperStartPx = ribbon.taperStartPx.coerceAtLeast(0f),
106        taperEndPx = ribbon.taperEndPx.coerceAtLeast(0f),
107        miterLimit = ribbon.miterLimit.coerceIn(1f, 32f),
108        aaWidthPx = ribbon.aaWidthPx.coerceIn(0f, 16f),
109        minPointDistancePx = ribbon.minPointDistancePx.coerceIn(0.05f, 32f),
110    )
111    val safeWet = wet.copy(
112        wetness = wet.wetness.coerceIn(0f, 1f),
113        spread = wet.spread.coerceIn(0f, 1f),
114        bleed = wet.bleed.coerceIn(0f, 1f),
115    )
116
117    return copy(
118        baseRadiusPx = safeRadius,
119        opacity = safeOpacity,
120        flow = safeFlow,
121        spacing = safeSpacing,
122        pressureGamma = safeGamma,
123        minSizeRatio = safeMinSize,
124        velocityToSize = safeVelocityToSize,
125        velocityToOpacity = safeVelocityToOpacity,
126        tiltToSize = safeTiltToSize,
127        tiltToOpacity = safeTiltToOpacity,
128        tiltToRotation = safeTiltToRotation,
129        sizeJitter = safeSizeJitter,
130        opacityJitter = safeOpacityJitter,
131        rotationJitter = safeRotationJitter,
132        scatter = safeScatter,
133        grainScale = safeGrainScale,
134        textureDepth = safeTextureDepth,
135        textureContrast = safeTextureContrast,
136        antiAliasLevel = safeAa,
137        ribbon = safeRibbon,
138        wet = safeWet,
139    )
140 }
141 }

```

23. app/src/main/java/com/wetinknext/engine/brush/BrushTexture.kt

```
1 package com.wetinknext.engine.brush
2
3 import android.opengl.GLES30
4 import com.wetinknext.engine.gl.GlCheck
5 import java.nio.ByteBuffer
6
7 class BrushTexture {
8     var textureId: Int = 0
9     private set
10
11     var width: Int = 0
12     private set
13
14     var height: Int = 0
15     private set
16
17     fun createFromRgba(
18         width: Int,
19         height: Int,
20         rgba: ByteBuffer,
21     ) {
22         GlCheck.checkOnGThread()
23         release()
24
25         val ids = IntArray(1)
26         GLES30.glGenTextures(1, ids, 0)
27         textureId = ids[0]
28
29         check(textureId != 0) { "Failed to create brush texture" }
30
31         this.width = width
32         this.height = height
33
34         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, textureId)
35
36         GLES30.glTexParameteri(
37             GLES30.GL_TEXTURE_2D,
38             GLES30.GL_TEXTURE_MIN_FILTER,
39             GLES30.GL_LINEAR,
40         )
41         GLES30.glTexParameteri(
42             GLES30.GL_TEXTURE_2D,
43             GLES30.GL_TEXTURE_MAG_FILTER,
44             GLES30.GL_LINEAR,
45         )
46         GLES30.glTexParameteri(
47             GLES30.GL_TEXTURE_2D,
48             GLES30.GL_TEXTURE_WRAP_S,
49             GLES30.GL_REPEAT,
50         )
51         GLES30.glTexParameteri(
52             GLES30.GL_TEXTURE_2D,
53             GLES30.GL_TEXTURE_WRAP_T,
54             GLES30.GL_REPEAT,
55         )
56
57         GLES30.glPixelStorei(
58             GLES30.GL_UNPACK_ALIGNMENT,
59             1,
60         )
61
62         GLES30.glTexImage2D(
63             GLES30.GL_TEXTURE_2D,
64             0,
65             GLES30.GL_RGBA,
66             width,
67             height,
68             0,
69             GLES30.GL_RGBA,
70             GLES30.GL_UNSIGNED_BYTE,
71             rgba,
72         )
73
74         GLES30.glPixelStorei(
75             GLES30.GL_UNPACK_ALIGNMENT,
76             4,
77         )
78
79         GLES30.glBindTexture(
80             GLES30.GL_TEXTURE_2D,
81             0,
82         )
83     }
84
85     fun release() {
86         GlCheck.checkOnGThread()
87         if (textureId != 0) {
88             GLES30.glDeleteTextures(
89                 1,
90                 intArrayOf(textureId),
91             )
92         }
93     }
94 }
```

```
91         0,  
92     )  
93 }  
94  
95     textureId = 0  
96     width = 0  
97     height = 0  
98 }  
99  
100 }
```

24. app/src/main/java/com/wetinknext/engine/brush/CapsuleEmitter.kt

```

1 package com.wetinknext.engine.brush
2
3 import com.wetinknext.engine.input.InputBatch
4 import kotlin.math.hypot
5 import kotlin.math.max
6 import kotlin.math.pow
7
8 /**
9  * Преобразует поток InputSample в цепочку капсул.
10  *
11  * Один сегмент:
12  *   A = x0, y0, radius0
13  *   B = x1, y1, radius1
14  *
15  * Капсула с одинаковыми радиусами является обычной capsule.
16  * При разном давлении shader строит round-cone.
17  *
18  * Важно:
19  * - не хранит InputSample;
20  * - не создаёт List/FloatArray на MOVE;
21  * - reusable state принадлежит GL/render pipeline;
22  * - pointerId фиксируется на DOWN;
23  * - давление применяется к радиусу;
24  * - opacity намеренно не применяется здесь, она применяется одним blit-pass.
25  */
26 class CapsuleEmitter(
27     private var settings: BrushSettings,
28 ) {
29     private var strokeSettings: BrushSettings? = null
30     private val stabilizer = Stabilizer()
31     private val pressureFilter = PressureFilter()
32     private val resolvedDab = ResolvedDab()
33
34     private var active = false
35     private var pointerId = -1
36
37     private var hasLastPoint = false
38     private var lastX = 0f
39     private var lastY = 0f
40     private var lastRadius = 0f
41     private var lastCoverage = 1f
42     // Reserved for a future oriented tip; the round capsule deliberately ignores it.
43     private var lastOrientation = 0f
44     private var lastTiltX = 0f
45     private var lastTiltY = 0f
46
47     // Окно точек для интерполяции P0, P1, P2, P3
48     private var p0x = 0f; private var p0y = 0f; private var p0r = 0f
49     private var p1x = 0f; private var p1y = 0f; private var p1r = 0f
50     private var p2x = 0f; private var p2y = 0f; private var p2r = 0f
51     private var p3x = 0f; private var p3y = 0f; private var p3r = 0f
52     private var p0c = 1f; private var p1c = 1f
53     private var p2c = 1f; private var p3c = 1f
54     private var pointsInWindow = 0
55
56     private var emittedSegments = 0
57
58     var hasStroke: Boolean = false
59         private set
60
61     var totalLength: Float = 0f
62         private set
63
64     /** Physical input distance, retained for stroke diagnostics and future dynamics. */
65     private var strokeDistance = 0f
66
67     var minX: Float = 0f
68         private set
69
70     var minY: Float = 0f
71         private set
72
73     var maxX: Float = 0f
74         private set
75
76     var maxY: Float = 0f
77         private set
78
79     var hasBounds: Boolean = false
80         private set
81
82     fun updateSettings(value: BrushSettings) {
83         // Active stroke reads strokeSettings; this value is for the next begin().
84         settings = value.resolved()
85     }
86
87     private fun activeSettings(): BrushSettings {
88         check(active) { "Capsule emitter has no active stroke" }
89         return strokeSettings ?: error("Missing stroke settings")
90     }

```

```

91
92 /**
93  * Полный сброс текущего stroke.
94  * overflowCount рендера здесь не сбрасывается.
95  */
96 fun reset() {
97     active = false
98     strokeSettings = null
99     pointerId = -1
100
101     hasLastPoint = false
102     lastX = 0f
103     lastY = 0f
104     lastRadius = 0f
105     lastCoverage = 1f
106     lastOrientation = 0f
107     lastTiltX = 0f
108     lastTiltY = 0f
109
110     pointsInWindow = 0
111
112     emittedSegments = 0
113     hasStroke = false
114     totalLength = 0f
115     strokeDistance = 0f
116
117     minX = 0f
118     minY = 0f
119     maxX = 0f
120     maxY = 0f
121     hasBounds = false
122
123     stabilizer.reset()
124     pressureFilter.reset()
125 }
126
127 /**
128  * Начало stroke.
129  *
130  * Первый sample добавляется как вырожденная капсула.
131  * В fragment shader она превращается в чистый диск.
132  */
133 fun begin(
134     batch: InputBatch,
135     out: CapsuleStrokeRenderer,
136     strokeSettings: BrushSettings = settings,
137 ) {
138     reset()
139     out.beginStroke()
140     val resolvedSettings = strokeSettings.resolved()
141     this.strokeSettings = resolvedSettings
142
143     if (batch.sampleCount <= 0) return
144
145     val sample = batch.samples[0]
146
147     active = true
148     pointerId = sample.pointerId
149
150     stabilizer.strength = (
151         resolvedSettings.smoothing * SMOOTHING_WEIGHT +
152         resolvedSettings.streamline * STREAMLINE_WEIGHT
153     ).coerceIn(0f, 1f)
154
155     stabilizer.process(
156         timestampNanos = sample.timestampNanos,
157         rawX = sample.canvasX,
158         rawY = sample.canvasY,
159     )
160
161     val x = stabilizer.x
162     val y = stabilizer.y
163     val filteredPressure = pressureFilter.filter(sample.timestampNanos, sample.pressure)
164     BrushDynamics.resolve(resolvedSettings, filteredPressure, sample.tiltX, sample.tiltY, 0f, sample.orientationRad,
resolvedDab)
165     val radius = resolvedDab.radius
166     val coverage = resolvedDab.coverage
167
168     lastX = x
169     lastY = y
170     lastRadius = radius
171     lastCoverage = coverage
172     lastOrientation = resolvedDab.rotation
173     lastTiltX = sample.tiltX
174     lastTiltY = sample.tiltY
175     out.setStrokeRotation(resolvedDab.rotation)
176     hasLastPoint = true
177     hasStroke = true
178
179     // Инициализация окна
180     p0x = x; p0y = y; p0r = radius
181     p1x = x; p1y = y; p1r = radius

```



```

182     p2x = x; p2y = y; p2r = radius
183     p0c = coverage; p1c = coverage; p2c = coverage
184     pointsInWindow = 1
185
186     // Вырожденный сегмент: круглый dab/tap.
187     out.addSegment(
188         x0 = x,
189         y0 = y,
190         radius0 = radius,
191         coverage0 = coverage,
192         x1 = x,
193         y1 = y,
194         radius1 = radius,
195         coverage1 = coverage,
196     )
197     emittedSegments++
198
199     includeBounds(x, y, radius)
200 }
201
202 /**
203  * Обрабатывает MOVE batch.
204  *
205  * Historical samples уже должны находиться внутри batch
206  * раньше текущего sample, это обеспечивает StrokeInputCapturer.
207  */
208 fun append(
209     batch: InputBatch,
210     out: CapsuleStrokeRenderer,
211 ) {
212     if (!active || batch.sampleCount <= 0) return
213     val settings = activeSettings()
214
215     for (index in 0 until batch.sampleCount) {
216         val sample = batch.samples[index]
217
218         if (sample.pointerId != pointerId) {
219             continue
220         }
221
222         stabilizer.process(
223             timestampNanos = sample.timestampNanos,
224             rawX = sample.canvasX,
225             rawY = sample.canvasY,
226         )
227
228         val x = stabilizer.x
229         val y = stabilizer.y
230         val filteredPressure = pressureFilter.filter(sample.timestampNanos, sample.pressure)
231         BrushDynamics.resolve(
232             settings,
233             filteredPressure,
234             sample.tiltX,
235             sample.tiltY,
236             stabilizer.velocity,
237             sample.orientationRad,
238             resolvedDab,
239         )
240         val radius = resolvedDab.radius
241         val coverage = resolvedDab.coverage
242         lastOrientation = resolvedDab.rotation
243         lastTiltX = sample.tiltX
244         lastTiltY = sample.tiltY
245         out.setStrokeRotation(resolvedDab.rotation)
246
247         emitPoint(
248             x = x,
249             y = y,
250             radius = radius,
251             coverage = coverage,
252             out = out,
253         )
254     }
255 }
256
257 /**
258  * Завершает stroke.
259  *
260  * Последний текущий sample должен быть передан через append()
261  * до вызова finish().
262  */
263 fun finish(
264     out: CapsuleStrokeRenderer,
265     cancel: Boolean,
266 ) {
267     if (!active) return
268     val settings = activeSettings()
269
270     if (cancel) {
271         reset()
272         out.clearStrokeData()
273         return

```

```

274     }
275
276     // Принудительно завершаем кривую, используя последнюю точку как P3
277     if (pointsInWindow >= 2 && settings.smoothing > 1e-4f) {
278         interpolate(
279             p0x, p0y, p0r,
280             p0c,
281             p1x, p1y, p1r, p1c,
282             p2x, p2y, p2r, p2c,
283             p2x, p2y, p2r, p2c,
284             out,
285         )
286     }
287
288     // The end taper is only knowable after UP, when the complete mesh exists.
289     // Preview stays untapered; commit redraws every segment with these final radii.
290     out.applyTaper { distanceFromStart, meshLength ->
291         taperScale(distanceFromStart, meshLength, settings)
292     }
293
294     active = false
295     pointerId = -1
296 }
297
298 private fun emitPoint(
299     x: Float,
300     y: Float,
301     radius: Float,
302     coverage: Float,
303     out: CapsuleStrokeRenderer,
304 ) {
305     val settings = activeSettings()
306     val dx = x - lastX
307     val dy = y - lastY
308     val distance = hypot(dx, dy)
309     strokeDistance += distance
310
311     if (distance < minimumPointDistance()) {
312         return
313     }
314
315     if (settings.smoothing <= 1e-4f) {
316         // Raw mode: прямые сегменты без задержки на окно
317         out.addSegment(lastX, lastY, lastRadius, lastCoverage, x, y, radius, coverage)
318         emittedSegments++
319         totalLength += distance
320         includeBounds(lastX, lastY, lastRadius)
321         includeBounds(x, y, radius)
322     } else {
323         // Interpolated mode: Catmull-Rom через окно
324         when (pointsInWindow) {
325             1 -> {
326                 p2x = x; p2y = y; p2r = radius; p2c = coverage
327                 pointsInWindow = 2
328             }
329             2 -> {
330                 p3x = x; p3y = y; p3r = radius; p3c = coverage
331                 interpolate(p0x, p0y, p0r, p0c, p1x, p1y, p1r, p1c, p2x, p2y, p2r, p2c, p3x, p3y, p3r, p3c, out)
332                 // Сдвиг окна
333                 p0x = p1x; p0y = p1y; p0r = p1r; p0c = p1c
334                 p1x = p2x; p1y = p2y; p1r = p2r; p1c = p2c
335                 p2x = p3x; p2y = p3y; p2r = p3r; p2c = p3c
336             }
337         }
338     }
339
340     hasStroke = true
341     lastX = x
342     lastY = y
343     lastRadius = radius
344     lastCoverage = coverage
345 }
346
347 private fun taperScale(
348     distanceFromStart: Float,
349     totalLength: Float,
350     settings: BrushSettings,
351 ): Float {
352     val start = settings.ribbon.taperStartPx
353     val end = settings.ribbon.taperEndPx
354
355     val startFactor = if (start <= 0f) {
356         1f
357     } else {
358         (distanceFromStart / start).coerceIn(0f, 1f)
359     }
360
361     val distanceToEnd = totalLength - distanceFromStart
362     val endFactor = if (end <= 0f) {
363         1f
364     } else {
365         (distanceToEnd / end).coerceIn(0f, 1f)

```

```

366     }
367
368     return minOf(startFactor, endFactor)
369         .coerceIn(settings.ribbon.minWidthRatio, 1f)
370 }
371
372
373 /**
374  * Адаптивная интерполяция сегмента P1-P2 с использованием P0 и P3 как контрольных точек.
375  */
376 private fun interpolate(
377     p0x: Float, p0y: Float, p0r: Float, p0c: Float,
378     p1x: Float, p1y: Float, p1r: Float, p1c: Float,
379     p2x: Float, p2y: Float, p2r: Float, p2c: Float,
380     p3x: Float, p3y: Float, p3r: Float, p3c: Float,
381     out: CapsuleStrokeRenderer
382 ) {
383     val dist = hypot(p2x - p1x, p2y - p1y)
384     if (dist < 1e-4f) return
385
386     // Вычисляем контрольные точки для кубической кривой Безье (Catmull-Rom -> Bezier)
387     val c1x = p1x + (p2x - p0x) / 6f
388     val c1y = p1y + (p2y - p0y) / 6f
389     val c2x = p2x - (p3x - p1x) / 6f
390     val c2y = p2y - (p3y - p1y) / 6f
391
392     // Адаптивное количество шагов: примерно каждые 0.25..0.5 радиуса
393     val avgRadius = (p1r + p2r) * 0.5f
394     val stepPx = max(1f, avgRadius * INTERPOLATION_STEP_RATIO)
395     val steps = max(1, (dist / stepPx).toInt().coerceAtMost(MAX_INTERPOLATION_STEPS))
396
397     var prevX = p1x
398     var prevY = p1y
399     var prevR = p1r
400     var prevCoverage = p1c
401
402     for (i in 1..steps) {
403         val t = i.toFloat() / steps
404         val mt = 1f - t
405
406         // Кубическое Безье для позиции
407         val x = mt * mt * mt * p1x + 3f * mt * mt * t * c1x + 3f * mt * t * t * c2x + t * t * t * p2x
408         val y = mt * mt * mt * p1y + 3f * mt * mt * t * c1y + 3f * mt * t * t * c2y + t * t * t * p2y
409
410         // Линейная интерполяция радиуса
411         val r = p1r + (p2r - p1r) * t
412         val coverage = p1c + (p2c - p1c) * t
413
414         out.addSegment(prevX, prevY, prevR, prevCoverage, x, y, r, coverage)
415         emittedSegments++
416         totalLength += hypot(x - prevX, y - prevY)
417         includeBounds(x, y, r)
418
419         prevX = x
420         prevY = y
421         prevR = r
422         prevCoverage = coverage
423     }
424 }
425
426 /**
427  * Для капсул не нужен такой плотный шаг, как для stamp-кисти:
428  * segment shader сам покрывает весь отрезок между A и B.
429  */
430 private fun minimumPointDistance(): Float {
431     val settings = activeSettings()
432     val configured = settings.ribbon.minPointDistancePx
433         .coerceIn(MIN_POINT_DISTANCE_MIN, MAX_POINT_DISTANCE)
434
435     val radiusBased = settings.baseRadiusPx * POINT_STEP_RADIUS_RATIO
436
437     return max(
438         configured,
439         radiusBased.coerceAtMost(MAX_POINT_DISTANCE),
440     )
441 }
442
443 private fun includeBounds(
444     x: Float,
445     y: Float,
446     radius: Float,
447 ) {
448     val left = x - radius
449     val top = y - radius
450     val right = x + radius
451     val bottom = y + radius
452
453     if (!hasBounds) {
454         minX = left
455         minY = top
456         maxX = right
457         maxY = bottom
458     }
459 }

```

```

458         hasBounds = true
459         return
460     }
461
462     if (left < minX) minX = left
463     if (top < minY) minY = top
464     if (right > maxX) maxX = right
465     if (bottom > maxY) maxY = bottom
466 }
467
468 companion object {
469     private const val SMOOTHING_WEIGHT = 0.7f
470     private const val STREAMLINE_WEIGHT = 0.3f
471
472     private const val MIN_RADIUS_PX = 0.25f
473
474     private const val MIN_POINT_DISTANCE_MIN = 0.05f
475     private const val MAX_POINT_DISTANCE = 32f
476     private const val POINT_STEP_RADIUS_RATIO = 0.08f
477
478     private const val INTERPOLATION_STEP_RATIO = 0.4f
479     private const val MAX_INTERPOLATION_STEPS = 64
480 }
481 }

```

25. app/src/main/java/com/wetinknext/engine/brush/CapsuleStrokeRenderer.kt

```

1  package com.wetinknext.engine.brush
2
3  import android.opengl.GLES30
4  import com.wetinknext.BuildConfig
5  import com.wetinknext.engine.gl.GlCheck
6  import com.wetinknext.engine.gl.GlProgram
7  import com.wetinknext.engine.gl.RenderTarget
8  import com.wetinknext.engine.gl.ShaderLib
9  import java.nio.ByteBuffer
10 import java.nio.ByteOrder
11
12 /**
13  * GPU-renderer для круглого штриха.
14  *
15  * Один instance:
16  *   x0, y0, radius0,
17  *   x1, y1, radius1
18  *
19  * Геометрия каждого сегмента является AABB, а настоящая форма
20  * рассчитывается в capsuleFragment через signed distance.
21  *
22  * Важно:
23  * - target должен быть очищен перед началом нового штриха;
24  * - рисование использует premultiplied source-over blending;
25  * - цвет должен быть постоянным для всего strokeTarget;
26  * - выход shader: premultiplied linear RGBA.
27  */
28 class CapsuleStrokeRenderer(
29     private val maxSegments: Int = DEFAULT_MAX_SEGMENTS,
30 ) {
31     private var program: GlProgram? = null
32
33     private var vaoId = 0
34     private var cornerVboId = 0
35     private var instanceVboId = 0
36
37     private var uCanvasToClip = -1
38     private var uColorLinear = -1
39     private val blendController = BlendController()
40     private var uCanvasSize = -1
41     private var uGrainTex = -1
42     private var uGrainActive = -1
43     private var uGrainScale = -1
44     private var uGrainCanvasLocked = -1
45     private var uTextureDepth = -1
46     private var uTextureContrast = -1
47     private var uFlow = -1
48
49     private var grainTextureId = 0
50     private var grainScale = 1f
51     private var grainCanvasLocked = true
52     private var textureDepth = 1f
53     private var textureContrast = 1f
54     // Reserved for a future oriented marker/chisel implementation.
55     private var strokeRotation = 0f
56
57     private val checkGLErrors: Boolean
58         get() = BuildConfig.DEBUG
59
60     /**
61     * Формат:
62     *   x0, y0, r0, x1, y1, r1
63     */
64     private val instanceData =
65         ByteBuffer
66             .allocateDirect(
67                 maxSegments * FLOATS_PER_SEGMENT * Float.SIZE_BYTES,
68             )
69             .order(ByteOrder.nativeOrder())
70             .asFloatBuffer()
71
72     var segmentCount: Int = 0
73         private set
74
75     private var uploadedSegmentCount = 0
76
77     /**
78     * Не сбрасывается на каждый новый stroke.
79     * Иначе диагностика потерь снова будет скрыта.
80     */
81     var overflowCount: Long = 0L
82         private set
83
84     val isEmpty: Boolean
85         get() = segmentCount == 0
86
87     val hasPendingSegments: Boolean
88         get() = segmentCount > uploadedSegmentCount
89
90     fun create() {

```

```

91     GLCheck.checkOnGThread()
92     release()
93
94     program = GLProgram(
95         vertexSource = ShaderLib.capsuleVertex,
96         fragmentSource = ShaderLib.capsuleFragment,
97     )
98
99     val currentProgram = checkNotNull(program)
100    currentProgram.use()
101
102    uCanvasToClip = GLES30.glGetUniformLocation(
103        currentProgram.id,
104        "uCanvasToClip",
105    )
106    uColorLinear = GLES30.glGetUniformLocation(
107        currentProgram.id,
108        "uColorLinear",
109    )
110    uCanvasSize = GLES30.glGetUniformLocation(
111        currentProgram.id,
112        "uCanvasSize",
113    )
114    uGrainTex = GLES30.glGetUniformLocation(
115        currentProgram.id,
116        "uGrainTex",
117    )
118    uGrainScale = GLES30.glGetUniformLocation(
119        currentProgram.id,
120        "uGrainScale",
121    )
122    uGrainActive = GLES30.glGetUniformLocation(
123        currentProgram.id,
124        "uGrainActive",
125    )
126    uGrainCanvasLocked = GLES30.glGetUniformLocation(
127        currentProgram.id,
128        "uGrainCanvasLocked",
129    )
130    uTextureDepth = GLES30.glGetUniformLocation(
131        currentProgram.id,
132        "uTextureDepth",
133    )
134    uTextureContrast = GLES30.glGetUniformLocation(
135        currentProgram.id,
136        "uTextureContrast",
137    )
138    uFlow = GLES30.glGetUniformLocation(
139        currentProgram.id,
140        "uFlow",
141    )
142
143    check(uCanvasToClip >= 0) {
144        "Capsule shader uniform uCanvasToClip is missing"
145    }
146    check(uColorLinear >= 0) {
147        "Capsule shader uniform uColorLinear is missing"
148    }
149    check(uCanvasSize >= 0) {
150        "Capsule shader uniform uCanvasSize is missing"
151    }
152    check(uFlow >= 0) {
153        "Capsule shader uniform uFlow is missing"
154    }
155
156    val corners = floatArrayOf(
157        -1f, -1f,
158        1f, -1f,
159        -1f, 1f,
160        1f, 1f,
161    )
162
163    val cornerData =
164        ByteBuffer
165            .allocateDirect(corners.size * Float.SIZE_BYTES)
166            .order(ByteOrder.nativeOrder())
167            .asFloatBuffer()
168
169    cornerData.put(corners)
170    cornerData.position(0)
171
172    val ids = IntArray(1)
173
174    GLES30.glGenVertexArrays(1, ids, 0)
175    vaoId = ids[0]
176
177    GLES30.glGenBuffers(1, ids, 0)
178    cornerVboId = ids[0]
179
180    GLES30.glGenBuffers(1, ids, 0)
181    instanceVboId = ids[0]
182

```

```

183     check(vaoId != 0) { "Failed to create capsule VAO" }
184     check(cornerVboId != 0) { "Failed to create capsule corner VBO" }
185     check(instanceVboId != 0) { "Failed to create capsule instance VBO" }
186
187     GLES30.glBindVertexArray(vaoId)
188
189     // Углы AABB-квада.
190     GLES30.glBindBuffer(
191         GLES30.GL_ARRAY_BUFFER,
192         cornerVboId,
193     )
194     GLES30.glBufferData(
195         GLES30.GL_ARRAY_BUFFER,
196         corners.size * Float.SIZE_BYTES,
197         cornerData,
198         GLES30.GL_STATIC_DRAW,
199     )
200     GLES30.glEnableVertexAttribArray(ATTR_CORNER)
201     GLES30.glVertexAttribPointer(
202         ATTR_CORNER,
203         2,
204         GLES30.GL_FLOAT,
205         false,
206         2 * Float.SIZE_BYTES,
207         0,
208     )
209
210     // Данные сегментов.
211     GLES30.glBindBuffer(
212         GLES30.GL_ARRAY_BUFFER,
213         instanceVboId,
214     )
215     GLES30.glBufferData(
216         GLES30.GL_ARRAY_BUFFER,
217         maxSegments * STRIDE_BYTES,
218         null,
219         GLES30.GL_DYNAMIC_DRAW,
220     )
221
222     // A: x0, y0, radius0
223     GLES30.glEnableVertexAttribArray(ATTR_SEGMENT_A)
224     GLES30.glVertexAttribPointer(
225         ATTR_SEGMENT_A,
226         4,
227         GLES30.GL_FLOAT,
228         false,
229         STRIDE_BYTES,
230         0,
231     )
232     GLES30.glVertexAttribDivisor(
233         ATTR_SEGMENT_A,
234         1,
235     )
236
237     // B: x1, y1, radius1
238     GLES30.glEnableVertexAttribArray(ATTR_SEGMENT_B)
239     GLES30.glVertexAttribPointer(
240         ATTR_SEGMENT_B,
241         4,
242         GLES30.GL_FLOAT,
243         false,
244         STRIDE_BYTES,
245         4 * Float.SIZE_BYTES,
246     )
247     GLES30.glVertexAttribDivisor(
248         ATTR_SEGMENT_B,
249         1,
250     )
251
252     GLES30.glBindBuffer(
253         GLES30.GL_ARRAY_BUFFER,
254         0,
255     )
256     GLES30.glBindVertexArray(0)
257
258     GLES30.glUseProgram(0)
259
260     checkNoGLError("CapsuleStrokeRenderer.create")
261 }
262
263 /**
264  * Начинает новый stroke.
265  *
266  * Старый target должен быть очищен отдельно:
267  * strokeTarget.clear(0f, 0f, 0f, 0f)
268  */
269 fun beginStroke() {
270     segmentCount = 0
271     uploadedSegmentCount = 0
272     strokeRotation = 0f
273
274     instanceData.clear()

```

```

275         instanceData.limit(
276             maxSegments * FLOATS_PER_SEGMENT,
277         )
278     }
279
280     /**
281     * Добавляет один сегмент в CPU-buffer.
282     *
283     * Если capacity исчерпана, сегмент не теряется молча:
284     * overflowCount увеличивается.
285     */
286     fun addSegment(
287         x0: Float,
288         y0: Float,
289         radius0: Float,
290         coverage0: Float,
291         x1: Float,
292         y1: Float,
293         radius1: Float,
294         coverage1: Float,
295     ): Boolean {
296         if (segmentCount >= maxSegments) {
297             overflowCount++
298             return false
299         }
300
301         val offset = segmentCount * FLOATS_PER_SEGMENT
302
303         instanceData.put(offset, x0)
304         instanceData.put(offset + 1, y0)
305         instanceData.put(offset + 2, radius0.coerceAtLeast(0.01f))
306         instanceData.put(offset + 3, coverage0.coerceIn(0f, 1f))
307
308         instanceData.put(offset + 4, x1)
309         instanceData.put(offset + 5, y1)
310         instanceData.put(offset + 6, radius1.coerceAtLeast(0.01f))
311         instanceData.put(offset + 7, coverage1.coerceIn(0f, 1f))
312
313         segmentCount++
314         return true
315     }
316
317     /**
318     * Retains pen orientation for a future non-round marker/chisel path.
319     * Round capsule geometry deliberately does not use the value yet.
320     */
321     fun setStrokeRotation(rotationRad: Float) {
322         strokeRotation = rotationRad
323     }
324
325     /**
326     * Applies geometric taper to all accumulated segments after the stroke is complete.
327     * The callback receives mesh arc-distance and the complete mesh length, so the end
328     * taper never depends on an estimate made during MOVE.
329     */
330     fun applyTaper(scaleAt: (distanceFromStart: Float, totalLength: Float) -> Float) {
331         if (segmentCount == 0) return
332
333         var totalLength = 0f
334         for (index in 0 until segmentCount) {
335             val offset = index * FLOATS_PER_SEGMENT
336             totalLength += kotlin.math.hypot(
337                 instanceData.get(offset + 4) - instanceData.get(offset),
338                 instanceData.get(offset + 5) - instanceData.get(offset + 1),
339             )
340         }
341
342         var distanceFromStart = 0f
343         for (index in 0 until segmentCount) {
344             val offset = index * FLOATS_PER_SEGMENT
345             val segmentLength = kotlin.math.hypot(
346                 instanceData.get(offset + 4) - instanceData.get(offset),
347                 instanceData.get(offset + 5) - instanceData.get(offset + 1),
348             )
349
350             val startScale = scaleAt(distanceFromStart, totalLength)
351             val endScale = scaleAt(distanceFromStart + segmentLength, totalLength)
352             instanceData.put(offset + 2, (instanceData.get(offset + 2) * startScale).coerceAtLeast(0.01f))
353             instanceData.put(offset + 6, (instanceData.get(offset + 6) * endScale).coerceAtLeast(0.01f))
354             distanceFromStart += segmentLength
355         }
356     }
357
358     /**
359     * Загружает и рисует только новые сегменты.
360     *
361     * Используется для preview во время MOVE.
362     * Перед первым вызовом target должен быть очищен.
363     */
364     fun drawPending(
365         target: RenderTarget,
366         width: Int,

```



```

367         height: Int,
368         canvasToClip: FloatArray,
369         colorLinear: FloatArray,
370         blendPolicy: BlendPolicy,
371         flow: Float,
372     ) {
373         val first = uploadedSegmentCount
374         val count = segmentCount - uploadedSegmentCount
375
376         if (count <= 0) return
377
378         val drawn = drawRange(
379             target = target,
380             width = width,
381             height = height,
382             canvasToClip = canvasToClip,
383             colorLinear = colorLinear,
384             firstSegment = first,
385             count = count,
386             blendPolicy = blendPolicy,
387             flow = flow,
388         )
389
390         if (drawn) {
391             uploadedSegmentCount = segmentCount
392         }
393     }
394
395     /**
396     * Полностью рисует все накопленные сегменты.
397     *
398     * Используется при commit, если target был очищен.
399     */
400     fun drawAll(
401         target: RenderTarget,
402         width: Int,
403         height: Int,
404         canvasToClip: FloatArray,
405         colorLinear: FloatArray,
406         blendPolicy: BlendPolicy,
407         flow: Float,
408     ) {
409         if (segmentCount <= 0) return
410
411         drawRange(
412             target = target,
413             width = width,
414             height = height,
415             canvasToClip = canvasToClip,
416             colorLinear = colorLinear,
417             firstSegment = 0,
418             count = segmentCount,
419             blendPolicy = blendPolicy,
420             flow = flow,
421         )
422     }
423
424     /**
425     * Полностью перерисовывает сегменты в диапазоне [firstSegment, firstSegment + count).
426     *
427     * Важный момент: glVertexAttribPointer вызывается здесь повторно,
428     * потому что offset у instanced-атрибутов меняется для каждого диапазона.
429     */
430     private fun drawRange(
431         target: RenderTarget,
432         width: Int,
433         height: Int,
434         canvasToClip: FloatArray,
435         colorLinear: FloatArray,
436         firstSegment: Int,
437         count: Int,
438         blendPolicy: BlendPolicy,
439         flow: Float,
440     ): Boolean {
441         val currentProgram = program ?: return false
442
443         require(canvasToClip.size >= 16) {
444             "canvasToClip must contain at least 16 floats"
445         }
446         require(colorLinear.size >= 3) {
447             "colorLinear must contain at least 3 floats"
448         }
449         require(firstSegment >= 0)
450         require(count >= 0)
451         require(firstSegment + count <= segmentCount)
452
453         if (count == 0) return true
454
455         target.bind()
456
457         GLES30.glViewport(
458             0,

```

```

459         0,
460         width,
461         height,
462     )
463
464     GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
465
466     blendController.begin(blendPolicy)
467
468     currentProgram.use()
469
470     GLES30.glUniformMatrix4fv(
471         uCanvasToClip,
472         1,
473         false,
474         canvasToClip,
475         0,
476     )
477
478     GLES30.glUniform3f(
479         uColorLinear,
480         colorLinear[0].coerceIn(0f, 1f),
481         colorLinear[1].coerceIn(0f, 1f),
482         colorLinear[2].coerceIn(0f, 1f),
483     )
484
485     GLES30.glUniform2f(
486         uCanvasSize,
487         width.toFloat(),
488         height.toFloat(),
489     )
490
491     GLES30.glUniform1f(
492         uGrainScale,
493         grainScale,
494     )
495
496     GLES30.glUniform1i(
497         uGrainActive,
498         if (grainTextureId != 0) 1 else 0,
499     )
500
501     GLES30.glUniform1i(
502         uGrainCanvasLocked,
503         if (grainCanvasLocked) 1 else 0,
504     )
505
506     GLES30.glUniform1f(
507         uTextureDepth,
508         textureDepth,
509     )
510
511     GLES30.glUniform1f(
512         uTextureContrast,
513         textureContrast,
514     )
515
516     GLES30.glUniform1f(
517         uFlow,
518         flow.coerceIn(0f, 1f),
519     )
520
521     if (grainTextureId != 0) {
522         GLES30.glActiveTexture(GLES30.GL_TEXTURE2)
523         GLES30.glBindTexture(
524             GLES30.GL_TEXTURE_2D,
525             grainTextureId,
526         )
527         GLES30.glUniform1i(uGrainTex, 2)
528     }
529
530     /*
531     * FloatBuffer должен содержать только передаваемый диапазон.
532     * glBufferSubData прочитает remaining() элементов.
533     */
534     val sourceStart = firstSegment * FLOATS_PER_SEGMENT
535     val sourceEnd =
536         sourceStart + count * FLOATS_PER_SEGMENT
537
538     instanceData.position(sourceStart)
539     instanceData.limit(sourceEnd)
540
541     GLES30.glBindVertexArray(vaoId)
542     GLES30.glBindBuffer(
543         GLES30.GL_ARRAY_BUFFER,
544         instanceVboId,
545     )
546
547     GLES30.glBufferSubData(
548         GLES30.GL_ARRAY_BUFFER,
549         firstSegment * STRIDE_BYTES,
550         count * STRIDE_BYTES,

```

```

551         instanceData,
552     )
553
554     /*
555     * Для ES 3.0 нет glDrawArraysInstancedBaseInstance.
556     * Поэтому offset атрибутов сдвигается вручную.
557     *
558     * VAO должен быть привязан во время glVertexAttribPointer.
559     */
560     GLES30.glVertexAttribPointer(
561         ATTR_SEGMENT_A,
562         4,
563         GLES30.GL_FLOAT,
564         false,
565         STRIDE_BYTES,
566         firstSegment * STRIDE_BYTES,
567     )
568
569     GLES30.glVertexAttribPointer(
570         ATTR_SEGMENT_B,
571         4,
572         GLES30.GL_FLOAT,
573         false,
574         STRIDE_BYTES,
575         firstSegment * STRIDE_BYTES + 4 * Float.SIZE_BYTES,
576     )
577
578     GLES30.glDrawArraysInstanced(
579         GLES30.GL_TRIANGLE_STRIP,
580         0,
581         CORNER_VERTEX_COUNT,
582         count,
583     )
584
585     if (grainTextureId != 0) {
586         GLES30.glActiveTexture(GLES30.GL_TEXTURE2)
587         GLES30.glBindTexture(
588             GLES30.GL_TEXTURE_2D,
589             0,
590         )
591     }
592
593     GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
594
595     GLES30.glBindBuffer(
596         GLES30.GL_ARRAY_BUFFER,
597         0,
598     )
599     GLES30.glBindVertexArray(0)
600
601     blendController.end()
602
603     GLES30.glBindFramebuffer(
604         GLES30.GL_FRAMEBUFFER,
605         0,
606     )
607
608     instanceData.clear()
609     instanceData.limit(
610         maxSegments * FLOATS_PER_SEGMENT,
611     )
612
613     if (checkGLErrors) {
614         checkNoGLError("CapsuleStrokeRenderer.drawRange")
615     }
616     return true
617 }
618
619 /**
620  * Сбрасывает только GPU/CPU состояние текущего renderer.
621  * Счётчик overflow сохраняется.
622  */
623 fun clearStrokeData() {
624     segmentCount = 0
625     uploadedSegmentCount = 0
626     instanceData.clear()
627     instanceData.limit(
628         maxSegments * FLOATS_PER_SEGMENT,
629     )
630 }
631
632 fun setGrainTexture(
633     textureId: Int,
634     scale: Float,
635     canvasLocked: Boolean,
636     depth: Float,
637     contrast: Float,
638 ) {
639     grainTextureId = textureId
640     grainScale = scale.coerceAtLeast(0.0001f)
641     grainCanvasLocked = canvasLocked
642     textureDepth = depth.coerceIn(0f, 1f)

```

```

643         textureContrast = contrast.coerceIn(0f, 2f)
644     }
645
646     fun clearGrainTexture() {
647         grainTextureId = 0
648         grainScale = 1f
649         grainCanvasLocked = true
650         textureDepth = 1f
651         textureContrast = 1f
652     }
653
654     /**
655     * Все GL-объекты удаляются только на GL-потоке.
656     */
657     fun release() {
658         GLCheck.checkOnGLThread()
659         program?.release()
660         program = null
661
662         if (instanceVboId != 0) {
663             GLES30.glDeleteBuffers(
664                 1,
665                 intArrayOf(instanceVboId),
666                 0,
667             )
668         }
669
670         if (cornerVboId != 0) {
671             GLES30.glDeleteBuffers(
672                 1,
673                 intArrayOf(cornerVboId),
674                 0,
675             )
676         }
677
678         if (vaoId != 0) {
679             GLES30.glDeleteVertexArrays(
680                 1,
681                 intArrayOf(vaoId),
682                 0,
683             )
684         }
685
686         vaoId = 0
687         cornerVboId = 0
688         instanceVboId = 0
689
690         uCanvasToClip = -1
691         uColorLinear = -1
692         uCanvasSize = -1
693         uGrainTex = -1
694         uGrainScale = -1
695         uGrainActive = -1
696         uGrainCanvasLocked = -1
697         uTextureDepth = -1
698         uTextureContrast = -1
699         uFlow = -1
700         grainTextureId = 0
701
702         segmentCount = 0
703         uploadedSegmentCount = 0
704
705         instanceData.clear()
706         instanceData.limit(
707             maxSegments * FLOATS_PER_SEGMENT,
708         )
709     }
710
711     private fun checkNoGLError(label: String) {
712         val error = GLES30.glGetError()
713         check(error == GLES30.GL_NO_ERROR) {
714             "$label: GL error 0x${error.toString(16)}"
715         }
716     }
717
718     companion object {
719         private const val ATTR_CORNER = 0
720         private const val ATTR_SEGMENT_A = 1
721         private const val ATTR_SEGMENT_B = 2
722
723         private const val CORNER_VERTEX_COUNT = 4
724
725         const val FLOATS_PER_SEGMENT = 8
726         const val STRIDE_BYTES =
727             FLOATS_PER_SEGMENT * Float.SIZE_BYTES
728
729         const val DEFAULT_MAX_SEGMENTS = 16_384
730     }
731 }
732 }

```

26. app/src/main/java/com/wetinknext/engine/brush/ClosureDebug.kt

```
1 package com.wetinknext.engine.brush
2
3 import android.util.Log
4 import com.wetinknext.BuildConfig
5
6 /** One debug log per finished stroke; never used from the render hot path. */
7 object ClosureDebug {
8     const val TAG = "RibbonClosure"
9     fun publish(distance: Float, threshold: Float, closed: Boolean, samples: Int) {
10         if (!BuildConfig.DEBUG) return
11         runCatching {
12             Log.d(TAG, "dist=%.2f thr=%.2f closed=%s n=%d".format(distance, threshold, closed, samples))
13         }
14     }
15 }
```

27. app/src/main/java/com/wetinknext/engine/brush/ColorSpaces.kt

```
1 package com.wetinknext.engine.brush
2
3 import kotlin.math.pow
4
5 object ColorSpaces {
6     fun srgbToLinear(value: Float): Float { val v=value.coerceIn(0f,1f); return if(v<=.04045f)v/12.92f else ((v+.055f)/1.
055f).pow(2.4f) }
7     fun linearToSrgb(value: Float): Float { val v=value.coerceIn(0f,1f); return if(v<=.0031308f)v*12.92f else 1.055f*v.pow(1f/
2.4f)-.055f }
8     fun srgb8ToLinear(Argb: Long,out:FloatArray){require(out.size>=3);out[0]=srgbToLinear(((Argb shr 16)and 0xFF)/255f);out[
1]=srgbToLinear(((Argb shr 8)and 0xFF)/255f);out[2]=srgbToLinear((Argb and 0xFF)/255f)}
9 }
```

28. app/src/main/java/com/wetinknext/engine/brush/DabBuffer.kt

```

1  package com.wetinknext.engine.brush
2
3  import com.wetinknext.engine.core.DirtyRect
4  import java.nio.ByteBuffer
5  import java.nio.ByteOrder
6
7  class DabBuffer(val capacity: Int = DEFAULT_CAPACITY) {
8      init { require(capacity > 0) }
9      val floats = ByteBuffer.allocateDirect(capacity * FLOATS_PER_DAB * Float.SIZE_BYTES).order(ByteOrder.nativeOrder()).
asFloatBuffer()
10     var count = 0; private set; var overflowCount = 0L; private set
11     fun clear() { count = 0; overflowCount = 0L; floats.clear() }
12     fun add(x: Float, y: Float, radius: Float, rotation: Float, coverage: Float, flow: Float): Boolean { if (count >=
capacity) { overflowCount++; return false }; floats.put(x); floats.put(y); floats.put(radius); floats.put(rotation); floats.put(
coverage.coerceIn(0f, 1f)); floats.put(flow.coerceIn(0f, 1f)); count++; return true }
13     fun prepareForUpload() { floats.position(0); floats.limit(count * FLOATS_PER_DAB) }
14     fun prepareForUpload(firstDab: Int, dabCount: Int) {
15         require(firstDab >= 0)
16         require(dabCount >= 0)
17         require(firstDab + dabCount <= count)
18         floats.position(firstDab * FLOATS_PER_DAB)
19         floats.limit((firstDab + dabCount) * FLOATS_PER_DAB)
20     }
21     /** Restores the direct buffer for appending after a GL upload. */
22     fun finishUpload() {
23         floats.limit(capacity * FLOATS_PER_DAB)
24         floats.position(count * FLOATS_PER_DAB)
25     }
26
27     /**
28      * Includes the exact circular footprint of each emitted dab plus a caller
29      * supplied safety fringe for analytic AA and textured-tip filtering.
30      */
31     fun includeDirtyRect(rect: DirtyRect, extraMargin: Float) {
32         val safeExtraMargin = extraMargin.coerceAtLeast(0f)
33         for (index in 0 until count) {
34             val offset = index * FLOATS_PER_DAB
35             val x = floats.get(offset)
36             val y = floats.get(offset + 1)
37             val radius = floats.get(offset + 2).coerceAtLeast(0f) + safeExtraMargin
38             rect.include(
39                 left = x - radius,
40                 top = y - radius,
41                 right = x + radius,
42                 bottom = y + radius,
43             )
44         }
45     }
46     companion object { const val FLOATS_PER_DAB = 6; const val DEFAULT_CAPACITY = 8192 }
47 }

```

29. app/src/main/java/com/wetinknext/engine/brush/DabRenderer.kt

```

1  package com.wetinknext.engine.brush
2
3  import android.opengl.GLES30
4  import com.wetinknext.engine.gl.GlCheck
5  import com.wetinknext.engine.gl.GlProgram
6  import com.wetinknext.engine.gl.RenderTarget
7  import com.wetinknext.engine.gl.ShaderLib
8  import java.nio.ByteBuffer
9  import java.nio.ByteOrder
10
11 /** Instanced circular dab renderer. All colour values are premultiplied linear output. */
12 class DabRenderer(private val maxDabs: Int) {
13     private var program: GlProgram? = null
14     private var vaoId = 0
15     private var quadBufferId = 0
16     private var instanceBufferId = 0
17     private var uCanvasToClip = -1
18     private var uColorLinear = -1
19     private var uCanvasSize = -1
20     private var uGrainTex = -1
21     private var uGrainActive = -1
22     private var uGrainScale = -1
23     private var uGrainCanvasLocked = -1
24     private var uTextureDepth = -1
25     private var uTextureContrast = -1
26     private var uStrokeOpacity = -1
27     private var uCoverageOnly = -1
28     private var uShapeTex = -1
29     private var uShapeActive = -1
30     private var uReverseShape = -1
31     private var uRgbToAlpha = -1
32
33     private var grainTextureId = 0
34     private var grainScale = 1f
35     private var grainCanvasLocked = true
36     private var textureDepth = 1f
37     private var textureContrast = 1f
38     private var shapeTextureId = 0
39     private var reverseShape = false
40     private var rgbToAlpha = false
41
42     private var uploadedDabCount = 0
43     private val blendController = BlendController()
44
45     /** Number of dabs already written into the current stroke target. */
46     val uploadedCount: Int get() = uploadedDabCount
47
48     fun create() {
49         GlCheck.checkOnGltThread()
50         release()
51         uploadedDabCount = 0
52         program = GlProgram(ShaderLib.dabVertex, ShaderLib.dabFragment)
53         val currentProgram = checkNotNull(program)
54         currentProgram.use()
55         uCanvasToClip = GLES30.glGetUniformLocation(currentProgram.id, "uCanvasToClip")
56         uColorLinear = GLES30.glGetUniformLocation(currentProgram.id, "uColorLinear")
57         uCanvasSize = GLES30.glGetUniformLocation(currentProgram.id, "uCanvasSize")
58         uGrainTex = GLES30.glGetUniformLocation(currentProgram.id, "uGrainTex")
59         uGrainActive = GLES30.glGetUniformLocation(currentProgram.id, "uGrainActive")
60         uGrainScale = GLES30.glGetUniformLocation(currentProgram.id, "uGrainScale")
61         uGrainCanvasLocked = GLES30.glGetUniformLocation(currentProgram.id, "uGrainCanvasLocked")
62         uTextureDepth = GLES30.glGetUniformLocation(currentProgram.id, "uTextureDepth")
63         uTextureContrast = GLES30.glGetUniformLocation(currentProgram.id, "uTextureContrast")
64         uStrokeOpacity = GLES30.glGetUniformLocation(currentProgram.id, "uStrokeOpacity")
65         uCoverageOnly = GLES30.glGetUniformLocation(currentProgram.id, "uCoverageOnly")
66         uShapeTex = GLES30.glGetUniformLocation(currentProgram.id, "uShapeTex")
67         uShapeActive = GLES30.glGetUniformLocation(currentProgram.id, "uShapeActive")
68         uReverseShape = GLES30.glGetUniformLocation(currentProgram.id, "uReverseShape")
69         uRgbToAlpha = GLES30.glGetUniformLocation(currentProgram.id, "uRgbToAlpha")
70
71         check(uCanvasToClip >= 0 && uColorLinear >= 0 && uStrokeOpacity >= 0 && uCoverageOnly >= 0) { "Dab shader uniforms
missing" }
72
73         val quad = floatArrayOf(-1f, -1f, 1f, -1f, -1f, 1f, 1f, 1f)
74         val quadData = ByteBuffer.allocateDirect(quad.size * Float.SIZE_BYTES)
75             .order(ByteOrder.nativeOrder())
76             .asFloatBuffer()
77         quadData.put(quad).position(0)
78
79         val ids = IntArray(1)
80         GLES30.glGenVertexArrays(1, ids, 0)
81         vaoId = ids[0]
82         GLES30.glGenBuffers(1, ids, 0)
83         quadBufferId = ids[0]
84         GLES30.glGenBuffers(1, ids, 0)
85         instanceBufferId = ids[0]
86
87         GLES30.glBindVertexArray(vaoId)
88         GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, quadBufferId)
89         GLES30.glBufferData(

```



```

90         GLES30.GL_ARRAY_BUFFER,
91         quad.size * Float.SIZE_BYTES,
92         quadData,
93         GLES30.GL_STATIC_DRAW,
94     )
95     GLES30.glEnableVertexAttribArray(0)
96     GLES30.glVertexAttribPointer(0, 2, GLES30.GL_FLOAT, false, 0, 0)
97
98     GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, instanceBufferId)
99     GLES30.glBufferData(
100         GLES30.GL_ARRAY_BUFFER,
101         maxDabs * DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES,
102         null,
103         GLES30.GL_DYNAMIC_DRAW,
104     )
105     GLES30.glEnableVertexAttribArray(1)
106     GLES30.glVertexAttribPointer(1, 4, GLES30.GL_FLOAT, false, DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES, 0)
107     GLES30.glVertexAttribDivisor(1, 1)
108     GLES30.glEnableVertexAttribArray(2)
109     GLES30.glVertexAttribPointer(2, 2, GLES30.GL_FLOAT, false, DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES, 16)
110     GLES30.glVertexAttribDivisor(2, 1)
111     GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0)
112     GLES30.glBindVertexArray(0)
113 }
114
115 /** Draws all buffered dabs into a document-space RenderTarget. */
116 fun drawInto(
117     target: RenderTarget,
118     width: Int,
119     height: Int,
120     canvasToFbo: FloatArray,
121     dabs: DabBuffer,
122     colorLinear: FloatArray,
123     blendPolicy: BlendPolicy,
124     strokeOpacity: Float = 1f,
125 ) {
126     if (dabs.count == 0) return
127     require(colorLinear.size >= 3)
128
129     dabs.prepareForUpload(firstDab = 0, dabCount = dabs.count)
130     try {
131         drawRange(
132             target = target,
133             width = width,
134             height = height,
135             canvasToFbo = canvasToFbo,
136             dabs = dabs,
137             firstDab = 0,
138             count = dabs.count,
139             colorLinear = colorLinear,
140             blendPolicy = blendPolicy,
141             strokeOpacity = strokeOpacity,
142             coverageOnly = false,
143         )
144     } finally {
145         dabs.finishUpload()
146     }
147 }
148
149 fun release() {
150     GLCheck.checkOnGLThread()
151     program?.release()
152     program = null
153     uploadedDabCount = 0
154     grainTextureId = 0
155     shapeTextureId = 0
156     reverseShape = false
157     rgbToAlpha = false
158     if (instanceBufferId != 0) GLES30.glDeleteBuffers(1, intArrayOf(instanceBufferId), 0)
159     if (quadBufferId != 0) GLES30.glDeleteBuffers(1, intArrayOf(quadBufferId), 0)
160     if (vaoId != 0) GLES30.glDeleteVertexArrays(1, intArrayOf(vaoId), 0)
161     vaoId = 0
162     quadBufferId = 0
163     instanceBufferId = 0
164     uCanvasToClip = -1
165     uColorLinear = -1
166     uStrokeOpacity = -1
167     uCoverageOnly = -1
168 }
169
170 fun beginStroke() {
171     uploadedDabCount = 0
172 }
173
174 fun clearStrokeData() {
175     uploadedDabCount = 0
176 }
177
178 fun setGrainTexture(
179     textureId: Int,
180     scale: Float,
181     canvasLocked: Boolean,

```

```

182         depth: Float,
183         contrast: Float,
184     ) {
185         grainTextureId = textureId
186         grainScale = scale.coerceAtLeast(0.0001f)
187         grainCanvasLocked = canvasLocked
188         textureDepth = depth.coerceIn(0f, 1f)
189         textureContrast = contrast.coerceIn(0f, 2f)
190     }
191
192     fun clearGrainTexture() {
193         grainTextureId = 0
194         grainScale = 1f
195         grainCanvasLocked = true
196         textureDepth = 1f
197         textureContrast = 1f
198     }
199
200     /** Sets a tip mask sampled once per dab in local dab coordinates. */
201     fun setShapeTexture(textureId: Int, reverse: Boolean, rgbToAlpha: Boolean) {
202         shapeTextureId = textureId
203         reverseShape = reverse
204         this.rgbToAlpha = rgbToAlpha
205     }
206
207     fun clearShapeTexture() {
208         shapeTextureId = 0
209         reverseShape = false
210         rgbToAlpha = false
211     }
212
213     /**
214      * Draws all dabs into a coverage target. The fragment coverage-only path
215      * is wired in the next NON_BUILDUP step; keeping upload ownership here
216      * prevents the mask pass from disturbing incremental colour preview data.
217      */
218     fun drawCoverageInto(
219         target: RenderTarget,
220         width: Int,
221         height: Int,
222         canvasToFbo: FloatArray,
223         dabs: DabBuffer,
224     ) {
225         if (dabs.count == 0) return
226
227         dabs.prepareForUpload(firstDab = 0, dabCount = dabs.count)
228         try {
229             drawRange(
230                 target = target,
231                 width = width,
232                 height = height,
233                 canvasToFbo = canvasToFbo,
234                 dabs = dabs,
235                 firstDab = 0,
236                 count = dabs.count,
237                 colorLinear = ZERO_COLOR,
238                 blendPolicy = BlendPolicy.NON_BUILDUP,
239                 strokeOpacity = 1f,
240                 coverageOnly = true,
241             )
242         } finally {
243             dabs.finishUpload()
244         }
245     }
246
247     fun drawPendingInto(
248         target: RenderTarget,
249         width: Int,
250         height: Int,
251         canvasToFbo: FloatArray,
252         dabs: DabBuffer,
253         colorLinear: FloatArray,
254         blendPolicy: BlendPolicy,
255         strokeOpacity: Float = 1f,
256     ) {
257         val first = uploadedDabCount
258         val count = dabs.count - first
259         if (count <= 0) return
260
261         dabs.prepareForUpload(first, count)
262         try {
263             drawRange(
264                 target = target,
265                 width = width,
266                 height = height,
267                 canvasToFbo = canvasToFbo,
268                 dabs = dabs,
269                 firstDab = first,
270                 count = count,
271                 colorLinear = colorLinear,
272                 blendPolicy = blendPolicy,
273                 strokeOpacity = strokeOpacity,

```

```

274         coverageOnly = false,
275     )
276     uploadedDabCount = dabs.count
277 } finally {
278     dabs.finishUpload()
279 }
280 }
281
282 private fun drawRange(
283     target: RenderTarget,
284     width: Int,
285     height: Int,
286     canvasToFbo: FloatArray,
287     dabs: DabBuffer,
288     firstDab: Int,
289     count: Int,
290     colorLinear: FloatArray,
291     blendPolicy: BlendPolicy,
292     strokeOpacity: Float,
293     coverageOnly: Boolean,
294 ) {
295     val currentProgram = program ?: return
296     target.bind()
297     GLES30.glViewport(0, 0, width, height)
298     if (coverageOnly) {
299         // A coverage mask is a union of dabs: overlaps retain their maximum
300         // alpha instead of source-over accumulating darkness.
301         GLES30.glEnable(GLES30.GL_BLEND)
302         GLES30.glBlendEquation(GLES30.GL_MAX)
303         GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE)
304     } else {
305         blendController.begin(blendPolicy)
306     }
307     currentProgram.use()
308     GLES30.glUniformMatrix4fv(uCanvasToClip, 1, false, canvasToFbo, 0)
309     GLES30.glUniform3f(uColorLinear, colorLinear[0], colorLinear[1], colorLinear[2])
310
311     // The GLSL coverage output is added in the following NON_BUILDUP pass.
312     // Keep the explicit mode here so every draw call already has a stable API.
313     @Suppress("UNUSED_VARIABLE")
314     val coveragePass = coverageOnly
315
316     GLES30.glUniform2f(uCanvasSize, width.toFloat(), height.toFloat())
317     GLES30.glUniform1i(uGrainActive, if (grainTextureId != 0) 1 else 0)
318     GLES30.glUniform1f(uGrainScale, grainScale)
319     GLES30.glUniform1i(uGrainCanvasLocked, if (grainCanvasLocked) 1 else 0)
320     GLES30.glUniform1f(uTextureDepth, textureDepth)
321     GLES30.glUniform1f(uTextureContrast, textureContrast)
322     GLES30.glUniform1f(uStrokeOpacity, strokeOpacity.coerceIn(0f, 1f))
323     GLES30.glUniform1i(uCoverageOnly, if (coverageOnly) 1 else 0)
324     GLES30.glUniform1i(uShapeActive, if (shapeTextureId != 0) 1 else 0)
325     GLES30.glUniform1i(uReverseShape, if (reverseShape) 1 else 0)
326     GLES30.glUniform1i(uRgbToAlpha, if (rgbToAlpha) 1 else 0)
327
328     if (grainTextureId != 0) {
329         GLES30.glActiveTexture(GLES30.GL_TEXTURE2)
330         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, grainTextureId)
331         GLES30.glUniform1i(uGrainTex, 2)
332     }
333     if (shapeTextureId != 0) {
334         GLES30.glActiveTexture(GLES30.GL_TEXTURE3)
335         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, shapeTextureId)
336         GLES30.glUniform1i(uShapeTex, 3)
337     }
338
339     GLES30.glBindVertexArray(vaoId)
340     GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, instanceBufferId)
341     GLES30.glBufferSubData(
342         GLES30.GL_ARRAY_BUFFER,
343         firstDab * DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES,
344         count * DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES,
345         dabs.floats,
346     )
347
348     // Reset offsets for instancing
349     GLES30.glVertexAttribPointer(
350         1, 4, GLES30.GL_FLOAT, false, DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES, 0
351     )
352     GLES30.glVertexAttribPointer(
353         2, 2, GLES30.GL_FLOAT, false, DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES, 16
354     )
355
356     // Manual attribute offset for ES 3.0 (since BaseInstance is 3.1+)
357     GLES30.glVertexAttribPointer(
358         1, 4, GLES30.GL_FLOAT, false, DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES,
359         (firstDab * DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES)
360     )
361     GLES30.glVertexAttribPointer(
362         2, 2, GLES30.GL_FLOAT, false, DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES,
363         (firstDab * DabBuffer.FLOATS_PER_DAB * Float.SIZE_BYTES + 16)
364     )
365

```

```

366         GLES30.glDrawArraysInstanced(GLES30.GL_TRIANGLE_STRIP, 0, 4, count)
367
368         if (grainTextureId != 0) {
369             GLES30.glActiveTexture(GLES30.GL_TEXTURE2)
370             GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
371         }
372         if (shapeTextureId != 0) {
373             GLES30.glActiveTexture(GLES30.GL_TEXTURE3)
374             GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
375         }
376         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
377
378         GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0)
379         GLES30.glBindVertexArray(0)
380         if (coverageOnly) {
381             GLES30.glBlendEquation(GLES30.GL_FUNC_ADD)
382             GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
383             GLES30.glDisable(GLES30.GL_BLEND)
384         } else {
385             blendController.end()
386         }
387         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
388     }
389
390     private companion object {
391         val ZERO_COLOR = floatArrayOf(0f, 0f, 0f)
392     }
393 }

```

30. app/src/main/java/com/wetinknext/engine/brush/OneEuroFilter.kt

```
1 package com.wetinknext.engine.brush
2
3 import kotlin.math.PI
4 import kotlin.math.sqrt
5
6 class OneEuroFilter(private var minCutoff: Float = 1.6f, private var beta: Float = 0.25f, private var dCutoff: Float = 1f) {
7     private var initialized = false; private var lastTimestampNanos = 0L
8     private var x = 0f; private var y = 0f; private var dx = 0f; private var dy = 0f
9     fun reset() { initialized = false; lastTimestampNanos = 0L; x = 0f; y = 0f; dx = 0f; dy = 0f }
10    fun filter(timestampNanos: Long, rawX: Float, rawY: Float, out: FloatArray) {
11        require(out.size >= 2)
12        if (!initialized) { initialized = true; lastTimestampNanos = timestampNanos; x = rawX; y = rawY; out[0] = x; out[1] =
y; return }
13        var dt = (timestampNanos - lastTimestampNanos) / 1_000_000_000f
14        if (dt < MIN_DT) dt = MIN_DT
15        lastTimestampNanos = timestampNanos
16        val rate = 1f / dt; val alphaD = alpha(rate, dCutoff)
17        dx = alphaD * ((rawX - x) * rate) + (1f - alphaD) * dx; dy = alphaD * ((rawY - y) * rate) + (1f - alphaD) * dy
18        val alpha = alpha(rate, (minCutoff + beta * sqrt(dx * dx + dy * dy)).coerceAtLeast(0.01f))
19        x = alpha * rawX + (1f - alpha) * x; y = alpha * rawY + (1f - alpha) * y; out[0] = x; out[1] = y
20    }
21    private fun alpha(rate: Float, cutoff: Float): Float { val tau = 1f / (2f * PI.toFloat() * cutoff); return 1f / (1f + tau
* rate) }
22    private companion object { const val MIN_DT = 1f / 1000f }
23 }
```

31. app/src/main/java/com/wetinknext/engine/brush/PressureFilter.kt

```
1 package com.wetinknext.engine.brush
2
3 import kotlin.math.exp
4
5 /**
6  * Time-based stylus pressure smoothing.
7  * A zero pressure sample while the pointer is still in contact is treated as a
8  * device glitch; Android sends the real zero value on UP after the final point.
9  */
10 class PressureFilter {
11     private var initialized = false
12     private var lastTimestampNanos = 0L
13     private var value = 0f
14
15     fun reset() { initialized = false; lastTimestampNanos = 0L; value = 0f }
16
17     fun filter(timestampNanos: Long, rawPressure: Float): Float {
18         val raw = rawPressure.coerceIn(0f, 1f)
19         if (!initialized) { initialized = true; lastTimestampNanos = timestampNanos; value = raw; return value }
20         val dt = ((timestampNanos - lastTimestampNanos) / NANOS_PER_SECOND).coerceIn(MIN_DT, MAX_DT)
21         lastTimestampNanos = timestampNanos
22         val stableRaw = if (raw <= ZERO_GLITCH_THRESHOLD && value > ZERO_GLITCH_THRESHOLD) value else raw
23         val tau = if (stableRaw >= value) RISE_TAU_SECONDS else FALL_TAU_SECONDS
24         val alpha = 1f - exp((-dt / tau).toDouble()).toFloat()
25         value += (stableRaw - value) * alpha
26         return value.coerceIn(0f, 1f)
27     }
28
29     private companion object {
30         const val NANOS_PER_SECOND = 1_000_000_000f
31         const val MIN_DT = 1f / 1000f
32         const val MAX_DT = 1f / 20f
33         const val RISE_TAU_SECONDS = .018f
34         const val FALL_TAU_SECONDS = .055f
35         const val ZERO_GLITCH_THRESHOLD = .01f
36     }
37 }
```

32. app/src/main/java/com/wetinknext/engine/brush/RibbonGeometryBuilder.kt

```
1 package com.wetinknext.engine.brush
2
3 /**
4  * Preallocated input store for the future geometric ribbon renderer.
5  *
6  * It deliberately has no dependency on the active capsule pipeline. A later
7  * change will consume these samples to build the inner contour, outer AA
8  * fringe, caps, and ROUND/MITER/BEVEL joins.
9  */
10 class RibbonGeometryBuilder(
11     private val maxPoints: Int = 8_192,
12 ) {
13     init {
14         require(maxPoints > 0) { "maxPoints must be positive" }
15     }
16
17     private val positions = FloatArray(maxPoints * 2)
18     private val radii = FloatArray(maxPoints)
19     private val coverage = FloatArray(maxPoints)
20
21     var count: Int = 0
22     private set
23
24     fun clear() {
25         count = 0
26     }
27
28     fun addPoint(
29         x: Float,
30         y: Float,
31         radius: Float,
32         coverageValue: Float,
33     ): Boolean {
34         if (count >= maxPoints) return false
35
36         val offset = count * 2
37         positions[offset] = x
38         positions[offset + 1] = y
39         radii[count] = radius.coerceAtLeast(0f)
40         coverage[count] = coverageValue.coerceIn(0f, 1f)
41         count++
42         return true
43     }
44 }
```

33. app/src/main/java/com/wetinknext/engine/brush/Stabilizer.kt

```
1 package com.wetinknext.engine.brush
2
3 import kotlin.math.sqrt
4
5 class Stabilizer(private val filter: OneEuroFilter = OneEuroFilter()) {
6     var strength = 0f; var x = 0f; private set; var y = 0f; private set; var velocity = 0f; private set
7     private var hasLast = false; private var lastX = 0f; private var lastY = 0f; private var lastT = 0L; private val filtered
8     = FloatArray(2)
9     fun reset() { filter.reset(); x = 0f; y = 0f; velocity = 0f; hasLast = false; lastX = 0f; lastY = 0f; lastT = 0L }
10    fun process(timestampNanos: Long, rawX: Float, rawY: Float) {
11        if (strength <= 0f) { x = rawX; y = rawY } else { filter.filter(timestampNanos, rawX, rawY, filtered); x = filtered[
12            0]; y = filtered[1] }
13        if (hasLast) { var dt = (timestampNanos - lastT) / 1_000_000_000f; if (dt < 1f / 1000f) dt = 1f / 1000f; val d = sqrt(
14            (x-lastX)*(x-lastX)+(y-lastY)*(y-lastY)); velocity += 0.2f * (d / dt - velocity) }
15        hasLast = true; lastX = x; lastY = y; lastT = timestampNanos
16    }
17 }
```


34. app/src/main/java/com/wetinknext/engine/brush/StampEmitter.kt

```

1 package com.wetinknext.engine.brush
2
3 import com.wetinknext.engine.input.InputBatch
4 import kotlin.math.sqrt
5
6 class StampEmitter(initialSettings: BrushSettings) {
7     var settings: BrushSettings = initialSettings
8     private set
9     private var strokeSettings: BrushSettings? = null
10
11     fun updateSettings(newSettings: BrushSettings) {
12         // Active stroke reads strokeSettings; this value is for the next begin().
13         settings = newSettings.resolved()
14     }
15
16     private val stabilizer = Stabilizer()
17     private val pressureFilter = PressureFilter()
18     private val resolvedDab = ResolvedDab()
19     private var active = false
20     private var pointerId = -1
21     private var hasLast = false
22     private var lastX = 0f
23     private var lastY = 0f
24     private var lastPressure = 0f
25     private var lastTiltX = 0f
26     private var lastTiltY = 0f
27     private var lastOrientationRad = 0f
28     private var lastVelocity = 0f
29     private var carriedDistance = 0f
30     private var movedDuringStroke = false
31     private var pointCount = 0
32     private var p0x = 0f; private var p0y = 0f; private var p0p = 0f
33     private var p1x = 0f; private var p1y = 0f; private var p1p = 0f
34     private var p2x = 0f; private var p2y = 0f; private var p2p = 0f
35     private var p3x = 0f; private var p3y = 0f; private var p3p = 0f
36
37     private fun activeSettings(): BrushSettings {
38         check(active) { "Stamp emitter has no active stroke" }
39         return strokeSettings ?: error("Missing stroke settings")
40     }
41
42     fun reset() {
43         active = false
44         pointerId = -1
45         hasLast = false
46         carriedDistance = 0f
47         movedDuringStroke = false
48         pointCount = 0
49         strokeSettings = null
50         lastOrientationRad = 0f
51         lastVelocity = 0f
52         stabilizer.reset()
53         pressureFilter.reset()
54     }
55
56     fun begin(
57         batch: InputBatch,
58         out: DabBuffer,
59         strokeSettings: BrushSettings = settings,
60     ) {
61         reset()
62         val resolvedSettings = strokeSettings.resolved()
63         this.strokeSettings = resolvedSettings
64         if (batch.isEmpty()) return
65         stabilizer.strength = (resolvedSettings.smoothing * .7f + resolvedSettings.streamline * .3f).coerceIn(0f, 1f)
66         val s = batch.samples[0]
67         active = true
68         pointerId = s.pointerId
69         stabilizer.process(s.timestampNanos, s.canvasX, s.canvasY)
70         lastX = stabilizer.x
71         lastY = stabilizer.y
72         lastPressure = pressureFilter.filter(s.timestampNanos, s.pressure)
73         lastTiltX = s.tiltX
74         lastTiltY = s.tiltY
75         lastOrientationRad = s.orientationRad
76         lastVelocity = 0f
77         hasLast = true
78         p0x = lastX; p0y = lastY; p0p = lastPressure
79         p1x = lastX; p1y = lastY; p1p = lastPressure
80         p2x = lastX; p2y = lastY; p2p = lastPressure
81         p3x = lastX; p3y = lastY; p3p = lastPressure
82         pointCount = 1
83     }
84
85     fun append(batch: InputBatch, out: DabBuffer) {
86         if (!active) return
87         val settings = activeSettings()
88         for (i in 0 until batch.sampleCount) {
89             val s = batch.samples[i]
90             if (s.pointerId == pointerId) {

```

```

91         stabilizer.process(s.timestampNanos, s.canvasX, s.canvasY)
92         val pressure = pressureFilter.filter(s.timestampNanos, s.pressure)
93         val velocity = stabilizer.velocity
94         lastOrientationRad = s.orientationRad
95         if (settings.smoothing <= .0001f) {
96             addPoint(stabilizer.x, stabilizer.y, pressure, s.tiltX, s.tiltY, velocity, s.orientationRad, out)
97         } else {
98             lastVelocity = velocity
99             lastTiltX = s.tiltX
100            lastTiltY = s.tiltY
101            appendSmoothedPoint(stabilizer.x, stabilizer.y, pressure, out)
102        }
103    }
104 }
105 }
106
107 fun finish(out: DabBuffer, cancel: Boolean) {
108     if (!active) return
109     val settings = activeSettings()
110     if (cancel) {
111         reset()
112         return
113     }
114     if (settings.smoothing > .0001f && pointCount >= 3) {
115         flushSmoothedTail(out)
116     }
117     if (!movedDuringStroke || carriedDistance > .001f) {
118         addDab(
119             x = lastX,
120             y = lastY,
121             pressure = lastPressure,
122             tiltX = lastTiltX,
123             tiltY = lastTiltY,
124             velocity = lastVelocity,
125             orientationRad = lastOrientationRad,
126             out = out,
127         )
128     }
129     reset()
130 }
131
132 private fun appendSmoothedPoint(x: Float, y: Float, pressure: Float, out: DabBuffer) {
133     p0x = p1x; p0y = p1y; p0p = p1p
134     p1x = p2x; p1y = p2y; p1p = p2p
135     p2x = p3x; p2y = p3y; p2p = p3p
136     p3x = x; p3y = y; p3p = pressure
137     pointCount = (pointCount + 1).coerceAtMost(4)
138
139     when (pointCount) {
140         2 -> addPoint(x, y, pressure, lastTiltX, lastTiltY, lastVelocity, lastOrientationRad, out)
141         4 -> interpolateCatmullRom(out)
142     }
143 }
144
145 /** Processes the last delayed Catmull-Rom segment with a duplicated endpoint. */
146 private fun flushSmoothedTail(out: DabBuffer) {
147     p0x = p1x; p0y = p1y; p0p = p1p
148     p1x = p2x; p1y = p2y; p1p = p2p
149     p2x = p3x; p2y = p3y; p2p = p3p
150     p3x = p2x; p3y = p2y; p3p = p2p
151     pointCount = 4
152     interpolateCatmullRom(out)
153 }
154
155 private fun interpolateCatmullRom(out: DabBuffer) {
156     val settings = activeSettings()
157     val dx = p2x - p1x
158     val dy = p2y - p1y
159     val distance = sqrt(dx * dx + dy * dy)
160     if (distance < .0001f) return
161
162     val steps = (distance / maxOf(1f, settings.baseRadiusPx * .25f))
163         .toInt()
164         .coerceIn(2, 64)
165
166     for (index in 1..steps) {
167         val t = index.toFloat() / steps
168         val t2 = t * t
169         val t3 = t2 * t
170         val x = .5f * (
171             2f * p1x + (-p0x + p2x) * t +
172             (2f * p0x - 5f * p1x + 4f * p2x - p3x) * t2 +
173             (-p0x + 3f * p1x - 3f * p2x + p3x) * t3
174         )
175         val y = .5f * (
176             2f * p1y + (-p0y + p2y) * t +
177             (2f * p0y - 5f * p1y + 4f * p2y - p3y) * t2 +
178             (-p0y + 3f * p1y - 3f * p2y + p3y) * t3
179         )
180         val pressure = p1p + (p2p - p1p) * t
181         addPoint(x, y, pressure, lastTiltX, lastTiltY, lastVelocity, lastOrientationRad, out)
182     }

```

```

183     }
184
185     private fun addPoint(x: Float, y: Float, p: Float, tx: Float, ty: Float, velocity: Float, orientationRad: Float, out:
DabBuffer) {
186         val settings = activeSettings()
187         val dx = x - lastX
188         val dy = y - lastY
189         val distance = sqrt(dx * dx + dy * dy)
190         if (distance <= .0001f) return
191         if (distance > 1.5f) movedDuringStroke = true
192
193         var travelled = 0f
194         while (travelled < distance) {
195             val tProbe = (travelled / distance).coerceIn(0f, 1f)
196             val probePressure = lastPressure + (p - lastPressure) * tProbe
197             val probeTiltX = lastTiltX + (tx - lastTiltX) * tProbe
198             val probeTiltY = lastTiltY + (ty - lastTiltY) * tProbe
199
200             BrushDynamics.resolve(
201                 settings = settings,
202                 pressure = probePressure,
203                 tiltX = probeTiltX,
204                 tiltY = probeTiltY,
205                 velocity = lastVelocity + (velocity - lastVelocity) * tProbe,
206                 orientationRad = orientationRad,
207                 out = resolvedDab,
208             )
209
210             val step = spacingForRadius(resolvedDab.radius)
211             // Radius can shrink with pressure, leaving more carried distance
212             // than the new step. Emit at the current point and reset it.
213             val needed = (step - carriedDistance).coerceAtLeast(0f)
214
215             if (travelled + needed > distance) {
216                 carriedDistance += distance - travelled
217                 break
218             }
219
220             travelled += needed
221             val t = (travelled / distance).coerceIn(0f, 1f)
222             addDab(
223                 x = lastX + dx * t,
224                 y = lastY + dy * t,
225                 pressure = lastPressure + (p - lastPressure) * t,
226                 tiltX = lastTiltX + (tx - lastTiltX) * t,
227                 tiltY = lastTiltY + (ty - lastTiltY) * t,
228                 velocity = lastVelocity + (velocity - lastVelocity) * t,
229                 orientationRad = orientationRad,
230                 out = out,
231             )
232             carriedDistance = 0f
233         }
234         lastX = x
235         lastY = y
236         lastPressure = p
237         lastTiltX = tx
238         lastTiltY = ty
239         lastVelocity = velocity
240         lastOrientationRad = orientationRad
241     }
242
243     private fun spacingForRadius(radius: Float): Float {
244         val settings = activeSettings()
245         val unit = if (settings.spacingUsesDiameter) radius * 2f else radius
246         return (unit * settings.spacing).coerceIn(.25f, 256f)
247     }
248
249     private fun addDab(
250         x: Float,
251         y: Float,
252         pressure: Float,
253         tiltX: Float,
254         tiltY: Float,
255         velocity: Float,
256         orientationRad: Float,
257         out: DabBuffer,
258     ) {
259         val settings = activeSettings()
260         BrushDynamics.resolve(
261             settings = settings,
262             pressure = pressure,
263             tiltX = tiltX,
264             tiltY = tiltY,
265             velocity = velocity,
266             orientationRad = orientationRad,
267             out = resolvedDab,
268         )
269         out.add(
270             x = x,
271             y = y,
272             radius = resolvedDab.radius,
273             rotation = resolvedDab.rotation,

```

```
274         coverage = resolvedDab.coverage,  
275         flow = settings.flow.coerceIn(0f, 1f),  
276     )  
277 }  
278  
279 }
```

35. app/src/main/java/com/wetinknext/engine/brush/TextureLoader.kt

```

1  package com.wetinknext.engine.brush
2
3  import android.content.Context
4  import android.graphics.Bitmap
5  import android.graphics.BitmapFactory
6  import java.nio.ByteBuffer
7  import java.nio.ByteOrder
8  import java.util.concurrent.ExecutorService
9  import java.util.concurrent.Executors
10
11  data class LoadedBrushTexture(
12      val path: String,
13      val width: Int,
14      val height: Int,
15      val rgba: ByteBuffer,
16  )
17
18  class TextureLoader(
19      private val context: Context,
20      private val executor: ExecutorService =
21          Executors.newSingleThreadExecutor(),
22  ) {
23      fun loadAsync(
24          path: String,
25          onLoad: (LoadedBrushTexture) -> Unit,
26          onError: (Throwable) -> Unit,
27      ) {
28          executor.execute {
29              try {
30                  val loaded = decode(path)
31                  onLoad(loaded)
32              } catch (error: Throwable) {
33                  onError(error)
34              }
35          }
36      }
37
38      private fun decode(path: String): LoadedBrushTexture {
39          val source = decodeBitmap(path)
40
41          val bitmap = if (source.config == Bitmap.Config.ARGB_8888) {
42              source
43          } else {
44              source.copy(Bitmap.Config.ARGB_8888, false)
45          }
46
47          val width = bitmap.width
48          val height = bitmap.height
49
50          val rgba = ByteBuffer
51              .allocateDirect(width * height * 4)
52              .order(ByteOrder.nativeOrder())
53
54          // Bitmap stores ARGB_8888 pixels as packed ARGB ints. Uploading that
55          // buffer directly makes the byte order platform-dependent; GLES expects
56          // the explicit RGBA byte sequence declared in BrushTexture.
57          val pixels = IntArray(width * height)
58          bitmap.getPixels(
59              pixels,
60              0,
61              width,
62              0,
63              0,
64              width,
65              height,
66          )
67          for (pixel in pixels) {
68              rgba.put(((pixel ushr 16) and 0xFF).toByte())
69              rgba.put(((pixel ushr 8) and 0xFF).toByte())
70              rgba.put((pixel and 0xFF).toByte())
71              rgba.put(((pixel ushr 24) and 0xFF).toByte())
72          }
73          rgba.flip()
74
75          if (bitmap != source && !bitmap.isRecycled) {
76              bitmap.recycle()
77          }
78
79          if (!source.isRecycled && source != bitmap) {
80              source.recycle()
81          }
82
83          return LoadedBrushTexture(
84              path = path,
85              width = width,
86              height = height,
87              rgba = rgba,
88          )
89      }
90  }

```

```
91     private fun decodeBitmap(path: String): Bitmap {
92         val bitmap = if (path.startsWith("asset:")) {
93             val assetPath = path.removePrefix("asset:")
94
95             context.assets.open(assetPath).use { input ->
96                 BitmapFactory.decodeStream(input)
97             }
98         } else {
99             BitmapFactory.decodeFile(path)
100         }
101
102         return requireNotNull(bitmap) {
103             "Cannot decode brush texture: $path"
104         }
105     }
106
107     fun shutdown() {
108         executor.shutdown()
109     }
110 }
```

36. app/src/main/java/com/wetinknext/engine/canvas/BlendMode.kt

```
1 package com.wetinknext.engine.canvas
2
3 import kotlinx.serialization.Serializable
4
5 /** Stored per layer now; shader implementations beyond NORMAL are scheduled after P6. */
6 @Serializable
7 enum class BlendMode(val id: Int) {
8     NORMAL(0),
9     MULTIPLY(1),
10    SCREEN(2),
11    OVERLAY(3),
12    DARKEN(4),
13    LIGHTEN(5),
14    ADD(6),
15 }
```

37. app/src/main/java/com/wetinknext/engine/canvas/CanvasBackdropRenderer.kt

```

1  package com.wetinknext.engine.canvas
2
3  import android.opengl.GLES30
4  import com.wetinknext.engine.gl.GlCheck
5  import com.wetinknext.engine.gl.GlProgram
6  import com.wetinknext.engine.gl.ShaderLib
7  import java.nio.ByteBuffer
8  import java.nio.ByteOrder
9
10 /** Draws the editor workspace pattern in one GPU pass. */
11 class CanvasBackdropRenderer {
12     private var program: GlProgram? = null
13     private var vertexArrayId = 0
14     private var vertexBufferId = 0
15     private var backgroundColorUniform = -1
16     private var gridColorUniform = -1
17     private var modeUniform = -1
18
19     fun create() {
20         GlCheck.checkOnGThread()
21         release()
22
23         program = GlProgram(ShaderLib.fullscreenVertex, ShaderLib.canvasBackdropFragment)
24         val currentProgram = checkNotNull(program)
25         currentProgram.use()
26         backgroundColorUniform = GLES30.glGetUniformLocation(currentProgram.id, "uBackgroundColor")
27         gridColorUniform = GLES30.glGetUniformLocation(currentProgram.id, "uGridColor")
28         modeUniform = GLES30.glGetUniformLocation(currentProgram.id, "uMode")
29         check(backgroundColorUniform >= 0 && gridColorUniform >= 0 && modeUniform >= 0) {
30             "Canvas backdrop uniforms missing"
31         }
32
33         val vertices = floatArrayOf(-1f, -1f, 1f, -1f, 1f, 1f, 1f, 1f)
34         val vertexData = ByteBuffer
35             .allocateDirect(vertices.size * Float.SIZE_BYTES)
36             .order(ByteOrder.nativeOrder())
37             .asFloatBuffer()
38             .apply { put(vertices); position(0) }
39         val ids = IntArray(1)
40         GLES30.glGenVertexArrays(1, ids, 0)
41         vertexArrayId = ids[0]
42         GLES30.glGenBuffers(1, ids, 0)
43         vertexBufferId = ids[0]
44         GLES30.glBindVertexArray(vertexArrayId)
45         GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, vertexBufferId)
46         GLES30.glBufferData(
47             GLES30.GL_ARRAY_BUFFER,
48             vertices.size * Float.SIZE_BYTES,
49             vertexData,
50             GLES30.GL_STATIC_DRAW,
51         )
52         GLES30.glEnableVertexAttribArray(0)
53         GLES30.glVertexAttribPointer(0, 2, GLES30.GL_FLOAT, false, 0, 0)
54         GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0)
55         GLES30.glBindVertexArray(0)
56         GlCheck.noError("CanvasBackdropRenderer create")
57     }
58
59     fun render(
60         viewportWidth: Int,
61         viewportHeight: Int,
62         backgroundColor: FloatArray,
63         gridColor: FloatArray,
64         mode: Int,
65     ) {
66         val currentProgram = program ?: return
67         if (viewportWidth <= 0 || viewportHeight <= 0 || vertexArrayId == 0) return
68
69         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
70         GLES30.glViewport(0, 0, viewportWidth, viewportHeight)
71         GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
72         GLES30.glDisable(GLES30.GL_BLEND)
73         currentProgram.use()
74         GLES30.glUniform3fv(backgroundColorUniform, 1, backgroundColor, 0)
75         GLES30.glUniform3fv(gridColorUniform, 1, gridColor, 0)
76         GLES30.glUniform1i(modeUniform, mode)
77         GLES30.glBindVertexArray(vertexArrayId)
78         GLES30.glDrawArrays(GLES30.GL_TRIANGLE_STRIP, 0, 4)
79         GLES30.glBindVertexArray(0)
80     }
81
82     fun release() {
83         if (vertexBufferId != 0) GLES30.glDeleteBuffers(1, intArrayOf(vertexBufferId), 0)
84         if (vertexArrayId != 0) GLES30.glDeleteVertexArrays(1, intArrayOf(vertexArrayId), 0)
85         vertexArrayId = 0
86         vertexBufferId = 0
87         program?.release()
88         program = null
89         backgroundColorUniform = -1
90         gridColorUniform = -1
91     }
92 }

```



```
91         modeUniform = -1
92     }
93
94     companion object {
95         const val MODE_GRID = 1
96         const val MODE_CHECKERBOARD = 2
97     }
98 }
```

38. app/src/main/java/com/wetinknext/engine/canvas/Compositor.kt

```

1  package com.wetinknext.engine.canvas
2
3  import android.opengl.GLES30
4  import com.wetinknext.engine.gl.CanvasGeometry
5  import com.wetinknext.engine.gl.GlCheck
6  import com.wetinknext.engine.gl.GlProgram
7  import com.wetinknext.engine.gl.RenderTarget
8  import com.wetinknext.engine.gl.ShaderLib
9
10 /** Presents visible layers bottom-to-top, inserting the active preview at its layer position. */
11 class Compositor {
12     private var program: GlProgram? = null
13     private var uCanvasToClip = -1
14     private var uCanvasSize = -1
15     private var uLayerTex = -1
16     private var uStrokeTex = -1
17     private var uStrokeActive = -1
18     private var uStrokeErase = -1
19     private var uOpacity = -1
20     private var uStrokeOpacity = -1
21
22     fun create() {
23         GlCheck.checkOnGThread()
24         release()
25         program = GlProgram(ShaderLib.compositorVertex, ShaderLib.compositorFragment)
26         val currentProgram = checkNotNull(program)
27         currentProgram.use()
28         uCanvasToClip = GLES30.glGetUniformLocation(currentProgram.id, "uCanvasToClip")
29         uCanvasSize = GLES30.glGetUniformLocation(currentProgram.id, "uCanvasSize")
30         uLayerTex = GLES30.glGetUniformLocation(currentProgram.id, "uLayerTex")
31         uStrokeTex = GLES30.glGetUniformLocation(currentProgram.id, "uStrokeTex")
32         uStrokeActive = GLES30.glGetUniformLocation(currentProgram.id, "uStrokeActive")
33         uStrokeErase = GLES30.glGetUniformLocation(currentProgram.id, "uStrokeErase")
34         uOpacity = GLES30.glGetUniformLocation(currentProgram.id, "uOpacity")
35         uStrokeOpacity = GLES30.glGetUniformLocation(currentProgram.id, "uStrokeOpacity")
36         check(uCanvasToClip >= 0 && uCanvasSize >= 0 && uLayerTex >= 0 &&
37             uStrokeTex >= 0 && uStrokeActive >= 0 && uStrokeErase >= 0 && uOpacity >= 0 && uStrokeOpacity >= 0) {
38             "Compositor uniforms missing: canvasToClip=$uCanvasToClip, " +
39             "canvasSize=$uCanvasSize, layerTex=$uLayerTex, strokeTex=$uStrokeTex, " +
40             "strokeActive=$uStrokeActive, strokeErase=$uStrokeErase, opacity=$uOpacity, strokeOpacity=$uStrokeOpacity"
41         }
42         GlCheck.noError("Compositor create")
43     }
44
45     fun render(
46         destination: RenderTarget? = null,
47         geometry: CanvasGeometry,
48         layers: LayerStack,
49         activeLayerId: Long,
50         strokeTextureId: Int,
51         strokeErase: Boolean,
52         canvasToClip: FloatArray,
53         strokeOpacity: Float,
54         firstLayerIndex: Int = 0,
55         lastLayerExclusive: Int = Int.MAX_VALUE,
56     ) {
57         val currentProgram = program ?: return
58         destination?.bind()
59         currentProgram.use()
60         GLES30.glUniformMatrix4fv(uCanvasToClip, 1, false, canvasToClip, 0)
61         GLES30.glUniform2f(uCanvasSize, layers.canvasWidth.toFloat(), layers.canvasHeight.toFloat())
62         GLES30.glEnable(GLES30.GL_BLEND)
63         GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
64
65         for ((index, layer) in layers.allLayers().withIndex()) {
66             if (index < firstLayerIndex || index >= lastLayerExclusive) continue
67             if (!layer.created || !layer.isVisible) continue
68             val hasStroke = layer.id == activeLayerId && strokeTextureId != 0
69
70             GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
71             GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, layer.target.textureId)
72             GLES30.glUniform1i(uLayerTex, 0)
73             if (hasStroke) {
74                 GLES30.glActiveTexture(GLES30.GL_TEXTURE1)
75                 GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, strokeTextureId)
76                 GLES30.glUniform1i(uStrokeTex, 1)
77             }
78             GLES30.glUniform1i(uStrokeActive, if (hasStroke) 1 else 0)
79             GLES30.glUniform1i(uStrokeErase, if (hasStroke && strokeErase) 1 else 0)
80             GLES30.glUniform1f(uOpacity, layer.opacity.coerceIn(0f, 1f))
81             GLES30.glUniform1f(uStrokeOpacity, strokeOpacity.coerceIn(0f, 1f))
82             geometry.draw()
83         }
84
85         GLES30.glDisable(GLES30.GL_BLEND)
86         GLES30.glActiveTexture(GLES30.GL_TEXTURE1)
87         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
88         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
89         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
90     }
91 }

```

```

91
92 /**
93  * Draws one layer into the currently bound target.
94  *
95  * This is deliberately separate from [render]: a layer-preview needs the
96  * layer bitmap even when the layer is currently hidden in the project. Its
97  * opacity is still applied, while a blend mode has no second layer to blend
98  * against in this one-layer path.
99  */
100 fun renderLayer(
101     geometry: CanvasGeometry,
102     layer: PaintLayer,
103     canvasWidth: Int = layer.target.width,
104     canvasHeight: Int = layer.target.height,
105     canvasToClip: FloatArray,
106 ) {
107     if (!layer.created || canvasWidth <= 0 || canvasHeight <= 0) return
108     val currentProgram = program ?: return
109     currentProgram.use()
110     GLES30.glUniformMatrix4fv(uCanvasToClip, 1, false, canvasToClip, 0)
111     GLES30.glUniform2f(uCanvasSize, canvasWidth.toFloat(), canvasHeight.toFloat())
112     GLES30.glEnable(GLES30.GL_BLEND)
113     GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
114
115     GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
116     GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, layer.target.textureId)
117     GLES30.glUniform1i(uLayerTex, 0)
118     GLES30.glUniform1i(uStrokeActive, 0)
119     GLES30.glUniform1i(uStrokeErase, 0)
120     GLES30.glUniform1f(uOpacity, layer.opacity.coerceIn(0f, 1f))
121     GLES30.glUniform1f(uStrokeOpacity, 1f)
122     geometry.draw()
123
124     GLES30.glDisable(GLES30.GL_BLEND)
125     GLES30.glActiveTexture(GLES30.GL_TEXTURE1)
126     GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
127     GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
128     GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
129 }
130
131 fun release() {
132     GLCheck.checkOnGThread()
133     program?.release()
134     program = null
135     uCanvasToClip = -1
136     uCanvasSize = -1
137     uLayerTex = -1
138     uStrokeTex = -1
139     uStrokeActive = -1
140     uStrokeErase = -1
141     uOpacity = -1
142     uStrokeOpacity = -1
143 }
144 }

```

39. app/src/main/java/com/wetinknext/engine/canvas/LayerStack.kt

```

1 package com.wetinknext.engine.canvas
2
3 import com.wetinknext.engine.core.Camera
4 import com.wetinknext.engine.gl.GlCaps
5 import com.wetinknext.domain.document.ProjectDocument
6
7 /**
8  * Render-thread-owned ordered collection of document layers.
9  * Index 0 is the bottom-most layer and the final item is the top-most layer.
10 */
11 class LayerStack {
12     val camera = Camera()
13
14     private val layers = mutableListOf<PaintLayer>()
15     private var nextId = 1L
16     private var documentUsesHalfFloat = false
17
18     var activeLayerId: Long = NO_LAYER
19     private set
20     var canvasWidth: Int = 0
21     private set
22     var canvasHeight: Int = 0
23     private set
24
25     val count: Int get() = layers.size
26
27     fun allLayers(): List<PaintLayer> = layers
28
29     fun activeLayer(): PaintLayer? = findLayerById(activeLayerId)
30
31     fun findLayerById(id: Long): PaintLayer? = layers.firstOrNull { it.id == id }
32
33     fun indexOfLayer(id: Long): Int = layers.indexOfFirst { it.id == id }
34
35     /** Creates the runtime stack from persisted layer metadata. */
36     fun create(caps: GlCaps, document: ProjectDocument) {
37         release()
38         canvasWidth = document.width
39         canvasHeight = document.height
40         documentUsesHalfFloat = caps.supportsHalfFloatColorBuffer
41
42         document.layers.forEachIndexed { index, source ->
43             val layer = PaintLayer(source.id, source.name).also {
44                 it.isVisible = source.visible
45                 it.isLocked = source.locked
46                 it.opacity = source.opacity
47                 it.blendMode = source.blendMode
48                 it.version = source.thumbnailVersion
49                 it.create(canvasWidth, canvasHeight, documentUsesHalfFloat)
50             }
51             // Tile restoration is a later persistence step. Preserve the new
52             // document's white background until a stored pixel payload is loaded.
53             if (index == 0 && source.locked) {
54                 layer.target.clear(1f, 1f, 1f, 1f)
55             }
56             layers += layer
57         }
58
59         activeLayerId = document.activeLayerId ?: layers.last().id
60         nextId = (layers.maxOf { it.id } + 1L).coerceAtLeast(1L)
61     }
62
63     /** Creates the locked opaque white background and one transparent drawing layer. */
64     fun create(caps: GlCaps, width: Int, height: Int) {
65         require(width > 0 && height > 0)
66         release()
67         canvasWidth = width
68         canvasHeight = height
69         documentUsesHalfFloat = caps.supportsHalfFloatColorBuffer
70
71         val background = newLayer("Фон", documentUsesHalfFloat).also {
72             it.isLocked = true
73             it.target.clear(1f, 1f, 1f, 1f)
74         }
75         layers += background
76
77         val drawing = newLayer("Слой 1", documentUsesHalfFloat)
78         layers += drawing
79         activeLayerId = drawing.id
80     }
81
82     fun addLayer(name: String, insertAt: Int = layers.size): PaintLayer {
83         check(canvasWidth > 0 && canvasHeight > 0) { "LayerStack has not been created" }
84         val layer = newLayer(name, documentUsesHalfFloat)
85         layers.add(insertAt.coerceIn(0, layers.size), layer)
86         activeLayerId = layer.id
87         return layer
88     }
89
90     /** A document must retain at least one layer; locked layers cannot be removed. */

```

```

91 fun removeLayer(id: Long): PaintLayer? {
92     val index = layers.indexOfFirst { it.id == id }
93     if (index < 0 || layers.size <= 1) return null
94     val layer = layers[index]
95     if (layer.isLocked) return null
96
97     layers.removeAt(index)
98     layer.release()
99     if (activeLayerId == id) {
100         activeLayerId = layers[index.coerceAtMost(layers.lastIndex)].id
101     }
102     return layer
103 }
104
105 fun setActive(id: Long): Boolean {
106     if (findLayerById(id) == null) return false
107     activeLayerId = id
108     return true
109 }
110
111 fun moveLayer(id: Long, delta: Int): Boolean {
112     val index = layers.indexOfFirst { it.id == id }
113     if (index < 0) return false
114     val newIndex = (index + delta).coerceIn(0, layers.lastIndex)
115     if (newIndex == index) return false
116     val layer = layers.removeAt(index)
117     layers.add(newIndex, layer)
118     return true
119 }
120
121 fun release() {
122     layers.forEach(PaintLayer::release)
123     layers.clear()
124     activeLayerId = NO_LAYER
125     canvasWidth = 0
126     canvasHeight = 0
127     documentUsesHalfFloat = false
128 }
129
130 private fun newLayer(name: String, useHalfFloat: Boolean): PaintLayer =
131     PaintLayer(nextId++, name).also { it.create(canvasWidth, canvasHeight, useHalfFloat) }
132
133 private companion object {
134     const val NO_LAYER = -1L
135 }
136 }

```

40. app/src/main/java/com/wetinknext/engine/canvas/LinearPresentRenderer.kt

```

1 package com.wetinknext.engine.canvas
2
3 import android.opengl.GLES30
4 import com.wetinknext.engine.gl.CanvasGeometry
5 import com.wetinknext.engine.gl.GlCheck
6 import com.wetinknext.engine.gl.GlProgram
7 import com.wetinknext.engine.gl.ShaderLib
8
9 /** Final pass: presents a premultiplied-linear canvas texture to the sRGB screen. */
10 class LinearPresentRenderer {
11     private var program: GlProgram? = null
12     private var uCanvasToClip = -1
13     private var uCanvasSize = -1
14     private var uTexture = -1
15
16     fun create() {
17         GlCheck.checkOnGThread()
18         release()
19         program = GlProgram(ShaderLib.compositorVertex, ShaderLib.linearPresentFragment)
20         val currentProgram = checkNotNull(program)
21         currentProgram.use()
22         uCanvasToClip = GLES30.glGetUniformLocation(currentProgram.id, "uCanvasToClip")
23         uCanvasSize = GLES30.glGetUniformLocation(currentProgram.id, "uCanvasSize")
24         uTexture = GLES30.glGetUniformLocation(currentProgram.id, "uTexture")
25         check(uCanvasToClip >= 0 && uCanvasSize >= 0 && uTexture >= 0) {
26             "Linear present uniforms missing"
27         }
28         GlCheck.noError("LinearPresentRenderer create")
29     }
30
31     fun render(
32         sourceTextureId: Int,
33         geometry: CanvasGeometry,
34         canvasToClipMatrix: FloatArray,
35         canvasWidth: Int,
36         canvasHeight: Int,
37         viewportWidth: Int,
38         viewportHeight: Int,
39     ) {
40         if (sourceTextureId == 0) return
41         val currentProgram = program ?: return
42         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
43         GLES30.glViewport(0, 0, viewportWidth, viewportHeight)
44         // A hidden background layer leaves transparent document pixels. Blend
45         // them over the editor backdrop instead of replacing it with black.
46         GLES30.glEnable(GLES30.GL_BLEND)
47         GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
48         currentProgram.use()
49         GLES30.glUniformMatrix4fv(uCanvasToClip, 1, false, canvasToClipMatrix, 0)
50         GLES30.glUniform2f(uCanvasSize, canvasWidth.toFloat(), canvasHeight.toFloat())
51         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
52         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, sourceTextureId)
53         GLES30.glUniform1i(uTexture, 0)
54         geometry.draw()
55         GLES30.glDisable(GLES30.GL_BLEND)
56         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
57     }
58
59     fun release() {
60         GlCheck.checkOnGThread()
61         program?.release()
62         program = null
63         uCanvasToClip = -1
64         uCanvasSize = -1
65         uTexture = -1
66     }
67 }

```

41. app/src/main/java/com/wetinknext/engine/canvas/LinearTextureBlitter.kt

```

1  package com.wetinknext.engine.canvas
2
3  import android.opengl.GLES30
4  import com.wetinknext.engine.gl.GlCheck
5  import com.wetinknext.engine.gl.GlProgram
6  import com.wetinknext.engine.gl.ShaderLib
7  import java.nio.ByteBuffer
8  import java.nio.ByteOrder
9
10 /**
11  * Blends one premultiplied-linear screen texture into the currently bound
12  * framebuffer. Unlike [ScreenPresentRenderer], this deliberately performs no
13  * colour-space conversion: it is used only while building a linear composite.
14  */
15 class LinearTextureBlitter {
16     private var program: GlProgram? = null
17     private var vertexArrayId = 0
18     private var vertexBufferId = 0
19     private var textureUniform = -1
20
21     fun create() {
22         GlCheck.checkOnGLThread()
23         release()
24
25         program = GlProgram(ShaderLib.fullscreenVertex, ShaderLib.linearCopyFragment)
26         val currentProgram = checkNotNull(program)
27         currentProgram.use()
28         textureUniform = GLES30.glGetUniformLocation(currentProgram.id, "uTexture")
29         check(textureUniform >= 0) { "Linear copy uniform uTexture is missing" }
30
31         val vertices = floatArrayOf(-1f, -1f, 1f, -1f, -1f, 1f, 1f, 1f)
32         val data = ByteBuffer
33             .allocateDirect(vertices.size * Float.SIZE_BYTES)
34             .order(ByteOrder.nativeOrder())
35             .asFloatBuffer()
36             .apply { put(vertices); position(0) }
37         val ids = IntArray(1)
38         GLES30.glGenVertexArrays(1, ids, 0)
39         vertexArrayId = ids[0]
40         GLES30.glGenBuffers(1, ids, 0)
41         vertexBufferId = ids[0]
42         GLES30.glBindVertexArray(vertexArrayId)
43         GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, vertexBufferId)
44         GLES30.glBufferData(
45             GLES30.GL_ARRAY_BUFFER,
46             vertices.size * Float.SIZE_BYTES,
47             data,
48             GLES30.GL_STATIC_DRAW,
49         )
50         GLES30.glEnableVertexAttribArray(0)
51         GLES30.glVertexAttribPointer(0, 2, GLES30.GL_FLOAT, false, 0, 0)
52         GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0)
53         GLES30.glBindVertexArray(0)
54     }
55
56     /** The caller owns the framebuffer and viewport. */
57     fun blit(sourceTextureId: Int) {
58         val currentProgram = program ?: return
59         if (sourceTextureId == 0 || vertexArrayId == 0) return
60
61         GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
62         GLES30.glEnable(GLES30.GL_BLEND)
63         GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
64         currentProgram.use()
65         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
66         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, sourceTextureId)
67         GLES30.glUniform1i(textureUniform, 0)
68         GLES30.glBindVertexArray(vertexArrayId)
69         GLES30.glDrawArrays(GLES30.GL_TRIANGLE_STRIP, 0, 4)
70         GLES30.glBindVertexArray(0)
71         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
72         GLES30.glDisable(GLES30.GL_BLEND)
73     }
74
75     fun release() {
76         if (vertexBufferId != 0) GLES30.glDeleteBuffers(1, intArrayOf(vertexBufferId), 0)
77         if (vertexArrayId != 0) GLES30.glDeleteVertexArrays(1, intArrayOf(vertexArrayId), 0)
78         vertexBufferId = 0
79         vertexArrayId = 0
80         program?.release()
81         program = null
82         textureUniform = -1
83     }
84 }

```

42. app/src/main/java/com/wetinknext/engine/canvas/NonBuildupStrokeRenderer.kt

```

1  package com.wetinknext.engine.canvas
2
3  import android.opengl.GLES30
4  import com.wetinknext.engine.gl.CanvasGeometry
5  import com.wetinknext.engine.gl.GlProgram
6  import com.wetinknext.engine.gl.RenderTarget
7  import com.wetinknext.engine.gl.ShaderLib
8
9  /** Applies a stamped colour field once, using the union coverage mask as alpha. */
10 class NonBuildupStrokeRenderer {
11     private var program: GlProgram? = null
12     private var uCanvasToClip = -1
13     private var uCanvasSize = -1
14     private var uColorTex = -1
15     private var uCoverageTex = -1
16     private var uOpacity = -1
17
18     fun create() {
19         release()
20         program = GlProgram(ShaderLib.compositorVertex, ShaderLib.nonBuildupStrokeFragment)
21         val p = checkNotNull(program)
22         p.use()
23         uCanvasToClip = GLES30.glGetUniformLocation(p.id, "uCanvasToClip")
24         uCanvasSize = GLES30.glGetUniformLocation(p.id, "uCanvasSize")
25         uColorTex = GLES30.glGetUniformLocation(p.id, "uColorTex")
26         uCoverageTex = GLES30.glGetUniformLocation(p.id, "uCoverageTex")
27         uOpacity = GLES30.glGetUniformLocation(p.id, "uOpacity")
28         check(uCanvasToClip >= 0 && uCanvasSize >= 0 && uColorTex >= 0 && uCoverageTex >= 0 && uOpacity >= 0) {
29             "NonBuildupStrokeRenderer uniforms missing"
30         }
31     }
32
33     fun blit(
34         layer: RenderTarget,
35         geometry: CanvasGeometry,
36         colorTextureId: Int,
37         coverageTextureId: Int,
38         canvasToFbo: FloatArray,
39         width: Int,
40         height: Int,
41         opacity: Float,
42         erase: Boolean = false,
43     ) {
44         val p = program ?: return
45         if (colorTextureId == 0 || coverageTextureId == 0) return
46         layer.bind()
47         GLES30.glViewport(0, 0, width, height)
48         GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
49         GLES30.glEnable(GLES30.GL_BLEND)
50         GLES30.glBlendEquation(GLES30.GL_FUNC_ADD)
51         if (erase) {
52             GLES30.glBlendFunc(GLES30.GL_ZERO, GLES30.GL_ONE_MINUS_SRC_ALPHA)
53         } else {
54             GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
55         }
56         p.use()
57         GLES30.glUniformMatrix4fv(uCanvasToClip, 1, false, canvasToFbo, 0)
58         GLES30.glUniform2f(uCanvasSize, width.toFloat(), height.toFloat())
59         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
60         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, colorTextureId)
61         GLES30.glUniform1i(uColorTex, 0)
62         GLES30.glActiveTexture(GLES30.GL_TEXTURE1)
63         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, coverageTextureId)
64         GLES30.glUniform1i(uCoverageTex, 1)
65         GLES30.glUniform1f(uOpacity, opacity.coerceIn(0f, 1f))
66         geometry.draw()
67         GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
68         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
69         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
70         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
71         GLES30.glDisable(GLES30.GL_BLEND)
72         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
73     }
74
75     fun release() {
76         program?.release()
77         program = null
78         uCanvasToClip = -1
79         uCanvasSize = -1
80         uColorTex = -1
81         uCoverageTex = -1
82         uOpacity = -1
83     }
84 }

```


43. app/src/main/java/com/wetinknext/engine/canvas/PaintLayer.kt

```
1 package com.wetinknext.engine.canvas
2
3 import com.wetinknext.engine.gl.RenderTarget
4
5 /** One paintable document layer and its private GPU target. */
6 class PaintLayer(
7     val id: Long,
8     var name: String,
9 ) {
10     val target = RenderTarget()
11
12     var isVisible = true
13     var isLocked = false
14     var opacity = 1f
15     var blendMode = BlendMode.NORMAL
16     var version = 0L
17
18     var created = false
19     private set
20
21     fun create(width: Int, height: Int, preferHalfFloat: Boolean) {
22         if (created && target.width == width && target.height == height) return
23         target.create(width, height, preferHalfFloat)
24         target.clear(0f, 0f, 0f, 0f)
25         created = true
26     }
27
28     fun clear() {
29         if (created) target.clear(0f, 0f, 0f, 0f)
30     }
31
32     fun release() {
33         target.release()
34         created = false
35     }
36 }
```

44. app/src/main/java/com/wetinknext/engine/canvas/ScreenPresentRenderer.kt

```

1 package com.wetinknext.engine.canvas
2
3 import android.opengl.GLES30
4 import com.wetinknext.engine.gl.GlCheck
5 import com.wetinknext.engine.gl.GlProgram
6 import com.wetinknext.engine.gl.ShaderLib
7
8 /** Presents a linear RGBA frame target to the default sRGB framebuffer. */
9 class ScreenPresentRenderer {
10     private var program: GlProgram? = null
11     private var vertexArrayId = 0
12     private var vertexBufferId = 0
13     private var textureUniform = -1
14
15     fun create() {
16         GlCheck.checkOnGThread()
17         release()
18         program = GlProgram(ShaderLib.fullscreenVertex, ShaderLib.linearPresentFragment)
19         val currentProgram = checkNotNull(program)
20         currentProgram.use()
21         textureUniform = GLES30.glGetUniformLocation(currentProgram.id, "uTexture")
22         check(textureUniform >= 0) { "Screen present uniform uTexture is missing" }
23
24         val vertices = floatArrayOf(-1f, -1f, 1f, -1f, 1f, 1f, 1f, 1f)
25         val data = java.nio.ByteBuffer
26             .allocateDirect(vertices.size * Float.SIZE_BYTES)
27             .order(java.nio.ByteOrder.nativeOrder())
28             .asFloatBuffer()
29             .apply { put(vertices); position(0) }
30         val ids = IntArray(1)
31         GLES30.glGenVertexArrays(1, ids, 0)
32         vertexArrayId = ids[0]
33         GLES30.glGenBuffers(1, ids, 0)
34         vertexBufferId = ids[0]
35         GLES30.glBindVertexArray(vertexArrayId)
36         GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, vertexBufferId)
37         GLES30.glBufferData(
38             GLES30.GL_ARRAY_BUFFER,
39             vertices.size * Float.SIZE_BYTES,
40             data,
41             GLES30.GL_STATIC_DRAW,
42         )
43         GLES30.glEnableVertexAttribArray(0)
44         GLES30.glVertexAttribPointer(0, 2, GLES30.GL_FLOAT, false, 0, 0)
45         GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0)
46         GLES30.glBindVertexArray(0)
47     }
48
49     fun render(sourceTextureId: Int, viewportWidth: Int, viewportHeight: Int) {
50         val currentProgram = program ?: return
51         if (sourceTextureId == 0 || vertexArrayId == 0) return
52         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
53         GLES30.glViewport(0, 0, viewportWidth, viewportHeight)
54         GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
55         GLES30.glEnable(GLES30.GL_BLEND)
56         GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
57         currentProgram.use()
58         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
59         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, sourceTextureId)
60         GLES30.glUniform1i(textureUniform, 0)
61         GLES30.glBindVertexArray(vertexArrayId)
62         GLES30.glDrawArrays(GLES30.GL_TRIANGLE_STRIP, 0, 4)
63         GLES30.glBindVertexArray(0)
64         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
65         GLES30.glDisable(GLES30.GL_BLEND)
66     }
67
68     fun release() {
69         if (vertexBufferId != 0) GLES30.glDeleteBuffers(1, intArrayOf(vertexBufferId), 0)
70         if (vertexArrayId != 0) GLES30.glDeleteVertexArrays(1, intArrayOf(vertexArrayId), 0)
71         vertexBufferId = 0
72         vertexArrayId = 0
73         program?.release()
74         program = null
75         textureUniform = -1
76     }
77 }

```

45. app/src/main/java/com/wetinknext/engine/canvas/StrokeBlitter.kt

```

1  package com.wetinknext.engine.canvas
2
3  import android.opengl.GLES30
4  import com.wetinknext.engine.gl.CanvasGeometry
5  import com.wetinknext.engine.gl.GlProgram
6  import com.wetinknext.engine.gl.RenderTarget
7  import com.wetinknext.engine.gl.ShaderLib
8
9  /** Переносит готовый штрих из strokeTarget в слой: premultiplied source-over * opacity. */
10 class StrokeBlitter {
11     private var program: GlProgram? = null
12     private var uCanvasToClip = -1
13     private var uCanvasSize = -1
14     private var uStrokeTex = -1
15     private var uOpacity = -1
16
17     fun create() {
18         release()
19         program = GlProgram(ShaderLib.compositorVertex, ShaderLib.strokeBlitFragment)
20         val p = checkNotNull(program)
21         p.use()
22         uCanvasToClip = GLES30.glGetUniformLocation(p.id, "uCanvasToClip")
23         uCanvasSize = GLES30.glGetUniformLocation(p.id, "uCanvasSize")
24         uStrokeTex = GLES30.glGetUniformLocation(p.id, "uStrokeTex")
25         uOpacity = GLES30.glGetUniformLocation(p.id, "uOpacity")
26         check(uCanvasToClip >= 0 && uCanvasSize >= 0 && uStrokeTex >= 0 && uOpacity >= 0) {
27             "StrokeBlitter uniforms missing"
28         }
29     }
30
31     fun blit(
32         layer: RenderTarget,
33         geometry: CanvasGeometry,
34         strokeTextureId: Int,
35         canvasToFbo: FloatArray,
36         width: Int,
37         height: Int,
38         opacity: Float,
39         erase: Boolean = false,
40     ) {
41         val p = program ?: return
42         if (strokeTextureId == 0) return
43         layer.bind()
44         GLES30.glViewport(0, 0, width, height)
45         GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
46         GLES30.glEnable(GLES30.GL_BLEND)
47         GLES30.glBlendEquation(GLES30.GL_FUNC_ADD)
48         if (erase) {
49             // Erase premultiplied RGB and alpha by the rendered stroke coverage.
50             GLES30.glBlendFunc(GLES30.GL_ZERO, GLES30.GL_ONE_MINUS_SRC_ALPHA)
51         } else {
52             GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
53         }
54         p.use()
55         GLES30.glUniformMatrix4fv(uCanvasToClip, 1, false, canvasToFbo, 0)
56         GLES30.glUniform2f(uCanvasSize, width.toFloat(), height.toFloat())
57         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
58         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, strokeTextureId)
59         GLES30.glUniform1i(uStrokeTex, 0)
60         GLES30.glUniform1f(uOpacity, opacity.coerceIn(0f, 1f))
61         geometry.draw()
62         GLES30.glBlendFunc(GLES30.GL_ONE, GLES30.GL_ONE_MINUS_SRC_ALPHA)
63         GLES30.glDisable(GLES30.GL_BLEND)
64         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
65         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
66     }
67
68     fun release() {
69         program?.release()
70         program = null
71         uCanvasToClip = -1; uCanvasSize = -1; uStrokeTex = -1; uOpacity = -1
72     }
73 }

```

46. app/src/main/java/com/wetinknext/engine/core/Camera.kt

```
1 package com.wetinknext.engine.core
2
3 import java.util.concurrent.atomic.AtomicReference
4 import kotlin.math.min
5
6 /** Thread-safe camera state shared by the UI and GL threads. */
7 class Camera(initial: ViewTransform = ViewTransform()) {
8     private val state = AtomicReference(initial)
9
10    fun snapshot(): ViewTransform = state.get()
11
12    fun set(transform: ViewTransform) {
13        state.set(transform)
14    }
15
16    fun update(transform: (ViewTransform) -> ViewTransform) {
17        while (true) {
18            val current = state.get()
19            if (state.compareAndSet(current, transform(current))) return
20        }
21    }
22
23    fun reset() {
24        state.set(ViewTransform())
25    }
26
27    fun fitCanvas(
28        canvasWidth: Int,
29        canvasHeight: Int,
30        viewWidth: Int,
31        viewHeight: Int,
32        marginRatio: Float = 0.04f,
33    ) {
34        if (canvasWidth <= 0 || canvasHeight <= 0 || viewWidth <= 0 || viewHeight <= 0) return
35        val usableWidth = viewWidth * (1f - marginRatio * 2f)
36        val usableHeight = viewHeight * (1f - marginRatio * 2f)
37        val scale = min(usableWidth / canvasWidth, usableHeight / canvasHeight)
38        .coerceIn(ViewTransform.MIN_SCALE, ViewTransform.MAX_SCALE)
39        state.set(
40            ViewTransform(
41                scale = scale,
42                translateX = (viewWidth - canvasWidth * scale) * 0.5f,
43                translateY = (viewHeight - canvasHeight * scale) * 0.5f,
44            ),
45        )
46    }
47 }
```

47. app/src/main/java/com/wetinknext/engine/core/CanvasBackdropMode.kt

```
1 package com.wetinknext.engine.core
2
3 /** Visual treatment of the workspace surrounding the document canvas. */
4 enum class CanvasBackdropMode {
5     GRID,
6     CHECKERBOARD,
7     SOLID,
8 }
```

48. app/src/main/java/com/wetinknext/engine/core/DirtyRect.kt

```

1 package com.wetinknext.engine.core
2
3 import kotlin.math.ceil
4 import kotlin.math.floor
5 import kotlin.math.max
6 import kotlin.math.min
7
8 /** Reusable mutable dirty rectangle in canvas coordinates. */
9 class DirtyRect {
10     var left = 0f; private set
11     var top = 0f; private set
12     var right = 0f; private set
13     var bottom = 0f; private set
14     var isEmpty = true; private set
15
16     fun clear() {
17         left = 0f; top = 0f; right = 0f; bottom = 0f; isEmpty = true
18     }
19
20     fun include(x: Float, y: Float, radius: Float) = include(x - radius, y - radius, x + radius, y + radius)
21
22     fun include(left: Float, top: Float, right: Float, bottom: Float) {
23         if (right < left || bottom < top) return
24         if (isEmpty) {
25             this.left = left; this.top = top; this.right = right; this.bottom = bottom; isEmpty = false
26             return
27         }
28         this.left = min(this.left, left); this.top = min(this.top, top)
29         this.right = max(this.right, right); this.bottom = max(this.bottom, bottom)
30     }
31
32     fun include(other: DirtyRect) {
33         if (!other.isEmpty) include(other.left, other.top, other.right, other.bottom)
34     }
35
36     fun expand(pixels: Float) {
37         if (!isEmpty && pixels > 0f) {
38             left -= pixels; top -= pixels; right += pixels; bottom += pixels
39         }
40     }
41
42     fun clamp(canvasWidth: Float, canvasHeight: Float) {
43         if (isEmpty) return
44         left = left.coerceIn(0f, canvasWidth); top = top.coerceIn(0f, canvasHeight)
45         right = right.coerceIn(0f, canvasWidth); bottom = bottom.coerceIn(0f, canvasHeight)
46         if (right <= left || bottom <= top) clear()
47     }
48
49     fun copyTo(out: DirtyRect) {
50         out.left = left; out.top = top; out.right = right; out.bottom = bottom; out.isEmpty = isEmpty
51     }
52
53     fun toPixelBounds(out: IntArray) {
54         require(out.size >= 4)
55         if (isEmpty) {
56             out[0] = 0; out[1] = 0; out[2] = 0; out[3] = 0
57             return
58         }
59         out[0] = floor(left).toInt(); out[1] = floor(top).toInt()
60         out[2] = ceil(right).toInt(); out[3] = ceil(bottom).toInt()
61     }
62 }

```

49. app/src/main/java/com/wetinknext/engine/core/DocumentSession.kt

```

1 package com.wetinknext.engine.core
2
3 import com.wetinknext.domain.document.ProjectDocument
4 import com.wetinknext.engine.canvas.LayerStack
5 import com.wetinknext.engine.gl.GlCaps
6 import com.wetinknext.engine.undo.UndoManager
7
8 /** Render-thread lifetime of an opened document and its GPU layer resources. */
9 class DocumentSession(
10     val document: ProjectDocument,
11     val layerStack: LayerStack,
12     val undoManager: UndoManager,
13     private val layerTiles: Map<Long, ByteArray>,
14 ) {
15     /** Layers whose pixels must be persisted by the next autosave. GL-thread owned. */
16     val dirtyLayerIds = mutableSetOf<Long>()
17
18     /** Metadata or pixels changed since the last successful autosave. GL-thread owned. */
19     var projectDirty: Boolean = false
20     private set
21
22     fun markLayerDirty(layerId: Long) {
23         dirtyLayerIds += layerId
24         projectDirty = true
25     }
26
27     fun markProjectDirty() {
28         projectDirty = true
29     }
30
31     fun markSaved(savedLayerIds: Set<Long>) {
32         dirtyLayerIds.removeAll(savedLayerIds)
33         projectDirty = dirtyLayerIds.isNotEmpty()
34     }
35
36     fun loadIntoGpu(caps: GlCaps) {
37         layerStack.create(caps, document)
38         document.layers.forEach { layer ->
39             LayerTileCodec.uploadPersistent(
40                 target = checkNotNull(layerStack.findLayerById(layer.id)).target,
41                 payload = layerTiles[layer.id] ?: ByteArray(0),
42             )
43         }
44         check(layerStack.activeLayerId == document.activeLayerId) { "Active layer was not restored" }
45     }
46 }

```

50. app/src/main/java/com/wetinknext/engine/core/EditorState.kt

```
1 package com.wetinknext.engine.core
2
3 /** Immutable state published by the GL thread for Compose to render. */
4 data class LayerUiModel(
5     val id: Long,
6     val name: String,
7     val isVisible: Boolean,
8     val isLocked: Boolean,
9     val opacity: Float,
10    val active: Boolean,
11    val canDelete: Boolean,
12    val thumbnailPath: String? = null,
13    val thumbnailVersion: Long = 0L,
14 )
15
16 data class UndoDiagnostics(
17     val pendingJobs: Int = 0,
18     val staleResults: Int = 0,
19     val compressionFailures: Int = 0,
20     val restoreFailures: Int = 0,
21     val memoryBytes: Long = 0L,
22 )
23
24 data class EditorUiState(
25     val layers: List<LayerUiModel>,
26     val canUndo: Boolean,
27     val canRedo: Boolean,
28     val brushSizePx: Float,
29     val brushOpacity: Float,
30     val activeLayerId: Long,
31     val ready: Boolean,
32     val undoDiagnostics: UndoDiagnostics = UndoDiagnostics(),
33 ) {
34     companion object {
35         val empty = EditorUiState(
36             layers = emptyList(),
37             canUndo = false,
38             canRedo = false,
39             brushSizePx = 16f,
40             brushOpacity = 1f,
41             activeLayerId = -1L,
42             ready = false,
43         )
44     }
45 }
```


51. app/src/main/java/com/wetinknext/engine/core/EngineRenderer.kt

```

1  package com.wetinknext.engine.core
2
3  import android.opengl.GLES30
4  import android.opengl.GLSurfaceView
5  import android.util.Log
6  import android.view.MotionEvent
7  import androidx.compose.ui.graphics.toArgb
8  import com.wetinknext.BuildConfig
9  import com.wetinknext.domain.document.LayerDocument
10 import com.wetinknext.domain.document.ProjectDocument
11 import com.wetinknext.engine.brush.BrushSettings
12 import com.wetinknext.engine.brush.BrushTexture
13 import com.wetinknext.engine.brush.LoadedBrushTexture
14 import com.wetinknext.engine.brush.BrushRenderMode
15 import com.wetinknext.engine.brush.BlendPolicy
16 import com.wetinknext.engine.brush.CapsuleEmitter
17 import com.wetinknext.engine.brush.CapsuleStrokeRenderer
18 import com.wetinknext.engine.brush.ColorSpaces
19 import com.wetinknext.engine.brush.DabBuffer
20 import com.wetinknext.engine.brush.DabRenderer
21 import com.wetinknext.engine.brush.StampEmitter
22 import com.wetinknext.engine.canvas.CanvasBackdropRenderer
23 import com.wetinknext.engine.canvas.Compositor
24 import com.wetinknext.engine.canvas.LayerStack
25 import com.wetinknext.engine.canvas.LinearTextureBlitter
26 import com.wetinknext.engine.canvas.PaintLayer
27 import com.wetinknext.engine.canvas.StrokeBlitter
28 import com.wetinknext.engine.canvas.NonBuildupStrokeRenderer
29 import com.wetinknext.engine.canvas.ScreenPresentRenderer
30 import com.wetinknext.engine.gl.CanvasGeometry
31 import com.wetinknext.engine.gl.GlCaps
32 import com.wetinknext.engine.gl.GlCheck
33 import com.wetinknext.engine.gl.RenderTarget
34 import com.wetinknext.engine.input.InputAction
35 import com.wetinknext.engine.input.InputBatch
36 import com.wetinknext.engine.input.InputBatchPool
37 import com.wetinknext.engine.input.GestureRouter
38 import com.wetinknext.engine.input.StrokeInputCapturer
39 import com.wetinknext.engine.persistence.LayerTileStore
40 import com.wetinknext.engine.thumbnail.ThumbnailBuildResult
41 import com.wetinknext.engine.thumbnail.ThumbnailBuildScheduler
42 import com.wetinknext.engine.thumbnail.ThumbnailRenderer
43 import com.wetinknext.engine.undo.TileSnapshotRestore
44 import com.wetinknext.engine.undo.UndoManager
45 import com.wetinknext.engine.undo.UndoOperationType
46 import java.io.File
47 import java.util.concurrent.ArrayBlockingQueue
48 import java.util.concurrent.ExecutorService
49 import java.util.concurrent.Executors
50 import java.util.concurrent.RejectedExecutionException
51 import java.util.concurrent.atomic.AtomicBoolean
52 import javax.microedition.khronos.egl.EGLConfig
53 import javax.microedition.khronos.opengles.GL10
54
55 /**
56  * The P6 render-thread owner. Active dabs are accumulated only in strokeTarget;
57  * UP snapshots and merges them into the selected PaintLayer atomically.
58  */
59 class EngineRenderer(
60     private var projectDocument: ProjectDocument = ProjectDocument.newUntitled(),
61     private val initialLayerTiles: Map<Long, ByteArray> = emptyMap(),
62     private val thumbnailOutputDirectory: File? = null,
63 ) : GLSurfaceView.Renderer {
64     private var caps: GlCaps? = null
65     private val layerStack = LayerStack()
66     private val undoManager = UndoManager()
67     private val layerTileStore = LayerTileStore(initialLayerTiles)
68     private var documentSession: DocumentSession? = null
69     private val undoPipeline = UndoCompressionPipeline(
70         requestRender = { onInputRenderRequested?.invoke() },
71     )
72     /** Serializes persistent tile payloads off the GL thread after a commit. */
73     private var tilePayloadExecutor: ExecutorService = Executors.newSingleThreadExecutor()
74     private var undoRestoreFailures = 0
75     private var glThread: Thread? = null
76     /**
77      * Preview files may finish decoding before GLSurfaceView calls
78      * [onSurfaceCreated]. Keep them as plain JVM data until the document's
79      * LayerStack has been created on the GL thread.
80      */
81     private var deferredRestoredLayerThumbnails: Map<Long, File> = emptyMap()
82
83     private var geometry: CanvasGeometry? = null
84     private var compositor: Compositor? = null
85     private var backdropRenderer: CanvasBackdropRenderer? = null
86     private var screenPresentRenderer: ScreenPresentRenderer? = null
87     private var linearTextureBlitter: LinearTextureBlitter? = null
88     private val thumbnailCapture = ThumbnailCapture()
89     private val layerThumbnailPaths = mutableMapOf<Long, String>()
90     /** Last layer version for which a WebP preview was successfully published. */

```

```

91     private val layerThumbnailVersions = mutableMapOf<Long, Long>()
92     private val thumbnailScheduler = thumbnailOutputDirectory?.let { outputDirectory ->
93         ThumbnailBuildScheduler(
94             outputDirectory = outputDirectory,
95             renderer = ThumbnailRenderer(),
96             requestGLFrame = { onInputRenderRequested?.invoke() },
97             onSave = { result -> onThumbnailBuildSaved?.invoke(result) },
98             onFailure = { error ->
99                 if (BuildConfig.DEBUG) Log.e(THUMBNAIL_TAG, "Thumbnail build failed", error)
100             }
101         )
102     }
103     private var dabRenderer: DabRenderer? = null
104     private var capsuleRenderer: CapsuleStrokeRenderer? = null
105     private var grainTexture: BrushTexture? = null
106     private var grainPath: String? = null
107     private var shapeTexture: BrushTexture? = null
108     private var shapePath: String? = null
109     private val strokeTarget = RenderTarget()
110     /** RGBA8 coverage accumulator used by the NON_BUILDUP stroke path. */
111     private val strokeCoverageTarget = RenderTarget()
112     /** Screen-sized linear frame composition. Source layers remain document-sized. */
113     private val compositeTarget = RenderTarget()
114     /** Confirmed layers below the active one, cached only for a live stroke preview. */
115     private val lowerCompositeTarget = RenderTarget()
116     /** Confirmed layers above the active one, cached only for a live stroke preview. */
117     private val upperCompositeTarget = RenderTarget()
118     private var compositeCacheDirty = true
119     private var cachedPreviewActiveLayerIndex = -1
120     private val cachedPreviewCanvasToClipMatrix = FloatArray(16)
121     private val canvasToFboMatrix = FloatArray(16)
122     private val strokeCommitter = StrokeCommitter(
123         strokeTarget = strokeTarget,
124         canvasToFbo = canvasToFboMatrix,
125         undoPipeline = undoPipeline,
126         undoManager = undoManager,
127         onTilesCommitted = { layer, tiles ->
128             invalidateCompositeCache()
129             layerTileStore.markDirty(layer.id, tiles)
130             documentSession?.markLayerDirty(layer.id)
131             publishDirtyTiles()
132             markLayerThumbnailDirty(layer.id)
133         },
134         onLayerCleared = { layer ->
135             invalidateCompositeCache()
136             layerTileStore.markLayerCleared(layer.id)
137             documentSession?.markLayerDirty(layer.id)
138             publishDirtyTiles()
139             markLayerThumbnailDirty(layer.id)
140         },
141     )
142     private val canvasToClipMatrix = FloatArray(16)
143
144     private var screenWidth = 1
145     private var screenHeight = 1
146     private val canvasBackdropColor = floatArrayOf(0.08f, 0.09f, 0.12f)
147     private val canvasGridColor = floatArrayOf(0.16f, 0.18f, 0.22f)
148
149     private val inputPool = InputBatchPool(batchCount = 64, maxSamplesPerBatch = 256)
150     private val inputQueue = ArrayBlockingQueue<InputBatch>(64)
151     private val inputCapturer = StrokeInputCapturer(layerStack.camera, inputPool, inputQueue)
152     private val undoGestureRequested = AtomicBoolean(false)
153     private val redoGestureRequested = AtomicBoolean(false)
154     private val resetCameraGestureRequested = AtomicBoolean(false)
155     private val gestureRouter = GestureRouter(
156         camera = layerStack.camera,
157         drawingInput = inputCapturer,
158         callbacks = object : GestureRouter.Callbacks {
159             override fun cancelDrawing() {
160                 requestCancelFromInput()
161             }
162
163             override fun undoGesture() {
164                 undoGestureRequested.set(true)
165             }
166
167             override fun redoGesture() {
168                 redoGestureRequested.set(true)
169             }
170
171             override fun resetCamera() {
172                 resetCameraGestureRequested.set(true)
173             }
174
175             override fun requestRender() {
176                 onInputRenderRequested?.invoke()
177             }
178         },
179     )
180
181     private var brushSettings = BrushSettings(
182         name = "G-Pen",

```

```

183         renderMode = BrushRenderMode.RIBBON,
184         baseRadiusPx = 9f,
185         spacing = 0.12f,
186         colorArgb = 0xFF1B1F24L,
187         smoothing = 0.35f,
188         streamline = 0.22f,
189         pressureToOpacity = false,
190         pressureGamma = 1.7f,
191         minSizeRatio = 0.06f,
192         ribbon = com.wetinknext.engine.brush.RibbonSettings(
193             cap = com.wetinknext.engine.brush.RibbonCap.ROUND,
194             join = com.wetinknext.engine.brush.RibbonJoin.ROUND,
195             miterLimit = 2.5f,
196             minPointDistancePx = 1.25f,
197             aaWidthPx = 1f,
198             taperStartPx = 16f,
199             taperEndPx = 64f,
200         ),
201     )
202     private val stampEmitter = StampEmitter(brushSettings)
203     private val capsuleEmitter = CapsuleEmitter(brushSettings)
204     private val dabBuffer = DabBuffer()
205     private val strokeColorLinear = FloatArray(3)
206     private val activeStrokeColorLinear = FloatArray(3)
207     private val strokeDirtyRect = DirtyRect()
208     private val dirtyBounds = IntArray(4)
209
210     private var strokeActive = false
211     /** Tool state, deliberately independent from the selected brush preset. */
212     private var eraserEnabled = false
213     /** Tool snapshot: toggling tools never changes an already-active stroke. */
214     private var activeStrokeErase = false
215     private var activeStrokeBrush: BrushSettings? = null
216     private var strokeBlitter: StrokeBlitter? = null
217     private var nonBuildupStrokeRenderer: NonBuildupStrokeRenderer? = null
218     private var capsulePreviewInitialized = false
219     private var stampPreviewInitialized = false
220     private val cancelRequested = AtomicBoolean(false)
221
222     /** Assigned by PaintSurfaceView; invoked on the GL thread. */
223     var onStateChange: ((EditorUiState) -> Unit)? = null
224
225     /** Metadata-only snapshot for persistence; invoked on the GL thread. */
226     var onProjectDocumentChange: ((ProjectDocument) -> Unit)? = null
227
228     /** Called only after document metadata and all stored layer payloads reached the GPU. */
229     var onDocumentSessionLoaded: (() -> Unit)? = null
230     var onDirtyLayerTiles: ((ProjectDocument, Map<Long, ByteArray>, Map<Long, Set<com.wetinknext.engine.undo.TileCoord>>) ->
Unit)? = null
231     var onThumbnailCaptured: ((ThumbnailCapture.Rgba) -> Unit)? = null
232     /** Posted on the UI thread after the scheduler published the current previews. */
233     var onThumbnailBuildSaved: ((ThumbnailBuildResult) -> Unit)? = null
234
235     /** Assigned by PaintSurfaceView; invoked from the UI touch thread. */
236     var onInputRenderRequested: (() -> Unit)? = null
237
238     fun setOnSecondaryPointerDown(listener: () -> Unit) {
239         inputCapturer.onSecondaryPointerDown = listener
240     }
241
242     fun onTouchEvent(event: MotionEvent): Boolean = gestureRouter.onTouchEvent(event)
243
244     fun requestCancelFromInput() {
245         cancelRequested.set(true)
246     }
247
248     /** Fits the document into the current GL surface. Must run on the GL thread. */
249     fun resetCamera() {
250         layerStack.camera.fitCanvas(
251             canvasWidth = layerStack.canvasWidth,
252             canvasHeight = layerStack.canvasHeight,
253             viewWidth = screenWidth,
254             viewHeight = screenHeight,
255         )
256     }
257
258     /** Applies theme colors to the area that surrounds the document. */
259     private var canvasBackdropMode = CanvasBackdropMode.GRID
260
261     fun setCanvasBackdrop(backdropArgb: Int, gridArgb: Int, mode: CanvasBackdropMode) {
262         argbToRgb(backdropArgb, canvasBackdropColor)
263         argbToRgb(gridArgb, canvasGridColor)
264         canvasBackdropMode = mode
265     }
266
267     /** These methods are called from GLSurfaceView.queueEvent by the UI layer. */
268     fun undo() {
269         if (undoPipeline.pendingCount > 0) return
270         resetStroke()
271         while (true) {
272             val entry = undoManager.peekUndo() ?: return
273             val layer = layerStack.findLayerById(entry.layerId)

```

```

274         if (layer == null) {
275             undoManager.dropUndo(entry)
276             continue
277         }
278         val restored = TileSnapshotRestore.restore(layer.target, entry.beforeTiles)
279         if (!restored) {
280             undoRestoreFailures++
281             publishState()
282             return
283         }
284         if (!undoManager.commitUndo(entry)) {
285             publishState()
286             return
287         }
288         layer.version++
289         invalidateCompositeCache()
290         persistRestoredTiles(layer, entry.beforeTiles)
291         updateProjectDocument { it }
292         publishState()
293         return
294     }
295 }
296
297 fun redo() {
298     if (undoPipeline.pendingCount > 0) return
299     resetStroke()
300     while (true) {
301         val entry = undoManager.peekRedo() ?: return
302         val layer = layerStack.findLayerById(entry.layerId)
303         if (layer == null) {
304             undoManager.dropRedo(entry)
305             continue
306         }
307         val restored = if (entry.operation == UndoOperationType.CLEAR_LAYER) {
308             layer.clear()
309             true
310         } else {
311             TileSnapshotRestore.restore(layer.target, entry.afterTiles)
312         }
313         if (!restored) {
314             undoRestoreFailures++
315             publishState()
316             return
317         }
318         if (!undoManager.commitRedo(entry)) {
319             publishState()
320             return
321         }
322         layer.version++
323         invalidateCompositeCache()
324         if (entry.operation == UndoOperationType.CLEAR_LAYER) {
325             layerTileStore.markLayerCleared(layer.id)
326             documentSession?.markLayerDirty(layer.id)
327             publishDirtyTiles()
328             markLayerThumbnailDirty(layer.id)
329         } else {
330             persistRestoredTiles(layer, entry.afterTiles)
331         }
332         updateProjectDocument { it }
333         publishState()
334         return
335     }
336 }
337
338 fun setActiveLayer(id: Long): Boolean {
339     resetStroke()
340     return layerStack.setActive(id).also { changed ->
341         if (changed) {
342             invalidateCompositeCache()
343             updateProjectDocument { it.copy(activeLayerId = id) }
344             publishState()
345         }
346     }
347 }
348
349 fun addLayer(): Long = addLayer(nextLayerName())
350
351 fun addLayer(name: String): Long {
352     resetStroke()
353     val layer = layerStack.addLayer(name)
354     invalidateCompositeCache()
355     updateProjectDocument { document ->
356         document.copy(
357             layers = document.layers + layerDocumentFrom(layer),
358             activeLayerId = layer.id,
359         )
360     }
361     captureThumbnail(listOf(layer.id))
362     publishState()
363     return layer.id
364 }
365

```

```

366  /** Creates an editable pixel-identical copy directly above [id]. */
367  fun duplicateLayer(id: Long): Long? {
368      checkOnGThread()
369      resetStroke()
370      val source = layerStack.findLayerById(id) ?: return null
371      val sourceIndex = layerStack.indexOfLayer(id)
372      if (sourceIndex < 0 || !source.created) return null
373
374      val duplicate = layerStack.addLayer(
375          name = nextDuplicateLayerName(source.name),
376          insertAt = sourceIndex + 1,
377      ).also {
378          it.isVisible = source.isVisible
379          it.isLocked = false
380          it.opacity = source.opacity
381          it.blendMode = source.blendMode
382          it.version = source.version
383      }
384
385      // Same-sized RenderTargets have the same format, so a framebuffer
386      // blit preserves premultiplied pixels exactly without a CPU readback.
387      GLES30.glBindFramebuffer(GLES30.GL_READ_FRAMEBUFFER, source.target.framebufferId)
388      GLES30.glBindFramebuffer(GLES30.GL_DRAW_FRAMEBUFFER, duplicate.target.framebufferId)
389      GLES30.glBlitFramebuffer(
390          0, 0, layerStack.canvasWidth, layerStack.canvasHeight,
391          0, 0, layerStack.canvasWidth, layerStack.canvasHeight,
392          GLES30.GL_COLOR_BUFFER_BIT,
393          GLES30.GL_NEAREST,
394      )
395      GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
396      GLCheck.noError("Duplicate layer")
397      invalidateCompositeCache()
398
399      val raw = com.wetinknext.engine.undo.TileSnapshotCapture.capture(
400          target = duplicate.target,
401          bounds = intArrayOf(0, 0, layerStack.canvasWidth, layerStack.canvasHeight),
402      )
403      layerTileStore.markDirty(duplicate.id, raw)
404      documentSession?.markLayerDirty(duplicate.id)
405      updateProjectDocument { it.copy(activeLayerId = duplicate.id, layers = layerStack.allLayers().map(::
layerDocumentFrom)) }
406      publishDirtyTiles()
407      captureThumbnail(listOf(duplicate.id))
408      publishState()
409      return duplicate.id
410  }
411
412  fun removeLayer(id: Long): Boolean {
413      checkOnGThread()
414      resetStroke()
415      invalidatePendingUndoHistory()
416      val removed = layerStack.removeLayer(id) != null
417      if (removed) {
418          invalidateCompositeCache()
419          undoManager.removeEntriesForLayer(id)
420          layerThumbnailPaths.remove(id)
421          layerThumbnailVersions.remove(id)
422          thumbnailScheduler?.removeLayer(id)
423          updateProjectDocument { document ->
424              document.copy(
425                  layers = document.layers.filterNot { it.id == id },
426                  activeLayerId = layerStack.activeLayerId,
427              )
428          }
429          captureThumbnail()
430          publishState()
431      }
432      return removed
433  }
434
435  /** Moves one layer in the document order and rebuilds only the project preview. */
436  fun moveLayer(id: Long, delta: Int): Boolean {
437      checkOnGThread()
438      resetStroke()
439      val moved = layerStack.moveLayer(id, delta)
440      if (moved) {
441          invalidateCompositeCache()
442          updateProjectDocument { it }
443          captureThumbnail()
444          publishState()
445      }
446      return moved
447  }
448
449  fun setLayerVisible(id: Long, visible: Boolean) {
450      resetStroke()
451      val layer = layerStack.findLayerById(id) ?: return
452      layer.isVisible = visible
453      invalidateCompositeCache()
454      syncLayerDocument(layer)
455      captureThumbnail()
456      publishState()

```

```

457     }
458
459     fun setLayerOpacity(id: Long, opacity: Float) {
460         val layer = layerStack.findLayerById(id) ?: return
461         layer.opacity = opacity.coerceIn(0f, 1f)
462         invalidateCompositeCache()
463         syncLayerDocument(layer)
464         captureThumbnail(listOf(layer.id))
465         publishState()
466     }
467
468     /** Clears only the editable active layer. The locked background is protected. */
469     fun clearActiveLayer(): Boolean {
470         checkOnMainThread()
471         resetStroke()
472         val layer = layerStack.activeLayer() ?: return false
473         val cleared = strokeCommitter.clearLayer(
474             layer = layer,
475             canvasWidth = layerStack.canvasWidth,
476             canvasHeight = layerStack.canvasHeight,
477         )
478         if (cleared) {
479             updateProjectDocument { it }
480             publishState()
481         }
482         return cleared
483     }
484
485     /** Mirrors only the camera view; document pixels and undo history stay unchanged. */
486     fun toggleCanvasMirror(): Boolean {
487         resetStroke()
488         val width = layerStack.canvasWidth
489         val height = layerStack.canvasHeight
490         if (width <= 0 || height <= 0) return false
491
492         // Flip around the document centre in screen space. Toggling the matrix
493         // sign alone flips around the camera origin and makes the canvas jump.
494         val camera = layerStack.camera
495         val current = camera.snapshot()
496         val canvasCenterX = width * .5f
497         val canvasCenterY = height * .5f
498         val before = FloatArray(2)
499         val after = FloatArray(2)
500         current.canvasToScreen(canvasCenterX, canvasCenterY, before)
501         val flipped = current.copy(flipX = !current.flipX)
502         flipped.canvasToScreen(canvasCenterX, canvasCenterY, after)
503         camera.set(
504             flipped.copy(
505                 translateX = flipped.translateX + before[0] - after[0],
506                 translateY = flipped.translateY + before[1] - after[1],
507             ),
508         )
509         return true
510     }
511
512     /** px = ДИАМЕТР кисти в canvas-пикселях, ровно то, что показывает UI. */
513     fun setBrushSize(px: Float) =
514         updateBrush(brushSettings.copy(baseRadiusPx = (px * .5f).coerceIn(.5f, 200f)))
515
516     fun setBrushOpacity(opacity: Float) =
517         updateBrush(brushSettings.copy(opacity = opacity.coerceIn(0f, 1f)))
518
519     fun setEraserEnabled(enabled: Boolean) {
520         eraserEnabled = enabled
521     }
522
523     fun setBrushColor(color: androidx.compose.ui.graphics.Color) =
524         updateBrush(brushSettings.copy(colorArgb = color.toArgb().toLong() and 0xFFFFFFFFL))
525
526     fun applyBrush(settings: BrushSettings) {
527         val nextSettings = settings
528             .copy(colorArgb = brushSettings.colorArgb)
529             .resolved()
530         updateBrush(nextSettings)
531     }
532
533     fun setBrushSettings(settings: BrushSettings) {
534         updateBrush(settings)
535     }
536
537     /** Правка кисти во время штриха больше не отменяет штрих: применяем на следующем DOWN. */
538     private fun updateBrush(next: BrushSettings) {
539         brushSettings = next.resolved()
540         if (!strokeActive) {
541             applyBrushToEmitters(brushSettings)
542             ColorSpaces.srgb8ToLinear(brushSettings.colorArgb, strokeColorLinear)
543         }
544         publishState()
545     }
546
547     private fun applyBrushToEmitters(settings: BrushSettings) {
548         stampEmitter.updateSettings(settings)
549     }

```

```

549         capsuleEmitter.updateSettings(settings)
550     }
551
552     fun requestState() {
553         publishState()
554     }
555
556     fun checkOnGltThread() {
557         val current = Thread.currentThread()
558         check(current === glThread) {
559             "GL resource accessed outside GLSurfaceView render thread: current=$current, expected=$glThread"
560         }
561     }
562
563     override fun onSurfaceCreated(gl: GL10?, config: EGLConfig?) {
564         val currentThread = Thread.currentThread()
565         glThread = currentThread
566         GLCheck.setGLThread(currentThread)
567         releaseGLObjects()
568         undoPipeline.ensureRunning()
569         ensureTilePayloadExecutor()
570         thumbnailScheduler?.ensureRunning()
571         val nextCaps = GLCaps.query()
572         caps = nextCaps
573         documentSession = DocumentSession(
574             document = projectDocument,
575             layerStack = layerStack,
576             undoManager = undoManager,
577             layerTiles = initialLayerTiles,
578         ).also { it.loadIntoGpu(nextCaps) }
579         if (deferredRestoredLayerThumbnails.isNotEmpty()) {
580             val previews = deferredRestoredLayerThumbnails
581             deferredRestoredLayerThumbnails = emptyMap()
582             installRestoredLayerThumbnails(previews)
583         }
584         strokeTarget.create(
585             projectDocument.width,
586             projectDocument.height,
587             nextCaps.supportsHalfFloatColorBuffer,
588         )
589         strokeTarget.clear(0f, 0f, 0f, 0f)
590         strokeCoverageTarget.create(
591             projectDocument.width,
592             projectDocument.height,
593             preferHalfFloat = false,
594         )
595         strokeCoverageTarget.clear(0f, 0f, 0f, 0f)
596         ViewTransform.buildCanvasToFbo(
597             projectDocument.width.toFloat(),
598             projectDocument.height.toFloat(),
599             canvasToFboMatrix,
600         )
601         geometry = CanvasGeometry().also {
602             it.create(projectDocument.width, projectDocument.height)
603         }
604         compositor = Compositor().also { it.create() }
605         backdropRenderer = CanvasBackdropRenderer().also { it.create() }
606         screenPresentRenderer = ScreenPresentRenderer().also { it.create() }
607         linearTextureBlitter = LinearTextureBlitter().also { it.create() }
608         invalidateCompositeCache()
609         dabRenderer = DabRenderer(dabBuffer.capacity).also { it.create() }
610         capsuleRenderer = CapsuleStrokeRenderer().also {
611             it.create()
612         }
613         strokeBlitter = StrokeBlitter().also { it.create() }
614         nonBuildupStrokeRenderer = NonBuildupStrokeRenderer().also { it.create() }
615         // Build both the gallery preview and the individual layer previews
616         // once the complete GPU session is available.
617         captureThumbnail(layerStack.allLayers().map(PaintLayer::id))
618         onDocumentSessionLoaded?.invoke()
619         ColorSpaces.srgb8ToLinear(brushSettings.colorArgb, strokeColorLinear)
620         publishState()
621         GLCheck.noError("P6 surface creation")
622     }
623
624     override fun onSurfaceChanged(gl: GL10?, width: Int, height: Int) {
625         screenWidth = width.coerceAtLeast(1)
626         screenHeight = height.coerceAtLeast(1)
627         compositeTarget.create(
628             screenWidth,
629             screenHeight,
630             caps?.supportsHalfFloatColorBuffer == true,
631         )
632         lowerCompositeTarget.create(
633             screenWidth,
634             screenHeight,
635             caps?.supportsHalfFloatColorBuffer == true,
636         )
637         upperCompositeTarget.create(
638             screenWidth,
639             screenHeight,
640             caps?.supportsHalfFloatColorBuffer == true,

```

```

641     )
642     compositeTarget.clear(0f, 0f, 0f, 0f)
643     lowerCompositeTarget.clear(0f, 0f, 0f, 0f)
644     upperCompositeTarget.clear(0f, 0f, 0f, 0f)
645     invalidateCompositeCache()
646     GLES30.glViewport(0, 0, screenWidth, screenHeight)
647     layerStack.camera.fitCanvas(layerStack.canvasWidth, layerStack.canvasHeight, screenWidth, screenHeight)
648     GLCheck.noError("P6 surface changed")
649 }
650
651 override fun onDrawFrame(gl: GL10?) {
652     if (cancelRequested.compareAndSet(true, false)) resetStroke()
653     if (undoGestureRequested.compareAndSet(true, false)) undo()
654     if (redoGestureRequested.compareAndSet(true, false)) redo()
655     if (resetCameraGestureRequested.compareAndSet(true, false)) resetCamera()
656     drainInput()
657     if (undoPipeline.process(undoManager)) publishState()
658     thumbnailScheduler?.processCompleted()
659     // Thumbnail capture calls glReadPixels. A pending gallery preview must
660     // never steal a frame from an active brush stroke.
661     if (!strokeActive) thumbnailScheduler?.buildIfNeeded(layerStack)
662
663     val frameStrokeBrush = activeStrokeBrush
664     if (strokeActive && frameStrokeBrush?.renderMode == BrushRenderMode.RIBBON) {
665         renderCapsulePreview(frameStrokeBrush)
666     } else if (strokeActive && frameStrokeBrush?.renderMode == BrushRenderMode.STAMP && dabBuffer.count > 0) {
667         // No longer clearing and drawing everything here, handled incrementally in drainInput
668     }
669
670     val currentGeometry = geometry ?: return
671     val currentCompositor = compositor ?: return
672     val currentScreenPresentRenderer = screenPresentRenderer ?: return
673
674     layerStack.camera.snapshot().buildCanvasToClip(
675         screenWidth.toFloat(),
676         screenHeight.toFloat(),
677         canvasToClipMatrix,
678     )
679
680     val previewTextureId = if (
681         strokeActive &&
682         (dabBuffer.count > 0 ||
683             (frameStrokeBrush?.renderMode == BrushRenderMode.RIBBON && capsuleEmitter.hasStroke))
684     ) {
685         strokeTarget.textureId
686     } else {
687         0
688     }
689     renderDocumentComposite(
690         compositor = currentCompositor,
691         geometry = currentGeometry,
692         previewTextureId = previewTextureId,
693         strokeOpacity = frameStrokeBrush?.opacity?.coerceIn(0f, 1f) ?: 1f,
694     )
695
696     GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
697     GLES30.glViewport(0, 0, screenWidth, screenHeight)
698     GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
699     GLES30.glDisable(GLES30.GL_BLEND)
700     GLES30.glClearColor(canvasBackdropColor[0], canvasBackdropColor[1], canvasBackdropColor[2], 1f)
701     GLES30.glClear(GLES30.GL_COLOR_BUFFER_BIT)
702     drawBackdropPattern()
703     currentScreenPresentRenderer.render(
704         sourceTextureId = compositeTarget.textureId,
705         viewportWidth = screenWidth,
706         viewportHeight = screenHeight,
707     )
708 }
709
710 /**
711  * During a live stroke, the confirmed layers above and below the active
712  * layer do not change. Cache those two screen-space composites and redraw
713  * only the active layer plus its preview on MOVE. This preserves layer
714  * ordering for both paint and eraser previews.
715  */
716 private fun renderDocumentComposite(
717     compositor: Compositor,
718     geometry: CanvasGeometry,
719     previewTextureId: Int,
720     strokeOpacity: Float,
721 ) {
722     val activeLayerIndex = layerStack.indexOfLayer(layerStack.activeLayerId)
723     val textureBlitter = linearTextureBlitter
724     val canUseStrokeCache = strokeActive &&
725         textureBlitter != null &&
726         activeLayerIndex in 0 until layerStack.count &&
727         lowerCompositeTarget.textureId != 0 &&
728         upperCompositeTarget.textureId != 0
729
730     if (!canUseStrokeCache) {
731         compositeTarget.clear(0f, 0f, 0f, 0f)
732         GLES30.glViewport(0, 0, screenWidth, screenHeight)

```



```

733         GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
734         GLES30.glDisable(GLES30.GL_BLEND)
735         compositor.render(
736             destination = compositeTarget,
737             geometry = geometry,
738             layers = layerStack,
739             activeLayerId = layerStack.activeLayerId,
740             strokeTextureId = previewTextureId,
741             strokeErase = activeStrokeErase,
742             strokeOpacity = strokeOpacity,
743             canvasToClip = canvasToClipMatrix,
744         )
745         return
746     }
747
748     rebuildPreviewCompositeCachesIfNeeded(
749         compositor = compositor,
750         geometry = geometry,
751         activeLayerIndex = activeLayerIndex,
752     )
753
754     compositeTarget.clear(0f, 0f, 0f, 0f)
755     compositeTarget.bind()
756     GLES30.glViewport(0, 0, screenWidth, screenHeight)
757     GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
758     GLES30.glDisable(GLES30.GL_BLEND)
759     if (activeLayerIndex > 0) {
760         textureBlitter.blit(lowerCompositeTarget.textureId)
761     }
762     compositor.render(
763         destination = compositeTarget,
764         geometry = geometry,
765         layers = layerStack,
766         activeLayerId = layerStack.activeLayerId,
767         strokeTextureId = previewTextureId,
768         strokeErase = activeStrokeErase,
769         strokeOpacity = strokeOpacity,
770         canvasToClip = canvasToClipMatrix,
771         firstLayerIndex = activeLayerIndex,
772         lastLayerExclusive = activeLayerIndex + 1,
773     )
774     if (activeLayerIndex < layerStack.count - 1) {
775         textureBlitter.blit(upperCompositeTarget.textureId)
776     }
777     GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
778 }
779
780 private fun rebuildPreviewCompositeCachesIfNeeded(
781     compositor: Compositor,
782     geometry: CanvasGeometry,
783     activeLayerIndex: Int,
784 ) {
785     val cameraChanged = !canvasToClipMatrix.contentEquals(cachedPreviewCanvasToClipMatrix)
786     if (!compositeCacheDirty &&
787         cachedPreviewActiveLayerIndex == activeLayerIndex &&
788         !cameraChanged
789     ) {
790         return
791     }
792
793     lowerCompositeTarget.clear(0f, 0f, 0f, 0f)
794     GLES30.glViewport(0, 0, screenWidth, screenHeight)
795     compositor.render(
796         destination = lowerCompositeTarget,
797         geometry = geometry,
798         layers = layerStack,
799         activeLayerId = -1L,
800         strokeTextureId = 0,
801         strokeErase = false,
802         strokeOpacity = 1f,
803         canvasToClip = canvasToClipMatrix,
804         firstLayerIndex = 0,
805         lastLayerExclusive = activeLayerIndex,
806     )
807
808     upperCompositeTarget.clear(0f, 0f, 0f, 0f)
809     GLES30.glViewport(0, 0, screenWidth, screenHeight)
810     compositor.render(
811         destination = upperCompositeTarget,
812         geometry = geometry,
813         layers = layerStack,
814         activeLayerId = -1L,
815         strokeTextureId = 0,
816         strokeErase = false,
817         strokeOpacity = 1f,
818         canvasToClip = canvasToClipMatrix,
819         firstLayerIndex = activeLayerIndex + 1,
820         lastLayerExclusive = layerStack.count,
821     )
822
823     canvasToClipMatrix.copyInto(cachedPreviewCanvasToClipMatrix)
824     cachedPreviewActiveLayerIndex = activeLayerIndex

```

```

825         compositeCacheDirty = false
826     }
827
828     private fun invalidateCompositeCache() {
829         compositeCacheDirty = true
830         cachedPreviewActiveLayerIndex = -1
831     }
832
833     private fun drawBackdropPattern() {
834         val mode = when (canvasBackdropMode) {
835             CanvasBackdropMode.SOLID -> return
836             CanvasBackdropMode.GRID -> CanvasBackdropRendererer.MODE_GRID
837             CanvasBackdropMode.CHECKERBOARD -> CanvasBackdropRendererer.MODE_CHECKERBOARD
838         }
839         backdropRenderer?.render(
840             viewportWidth = screenWidth,
841             viewportHeight = screenHeight,
842             backgroundColor = canvasBackdropColor,
843             gridColor = canvasGridColor,
844             mode = mode,
845         )
846     }
847
848     private fun argbToRgb(Argb: Int, out: FloatArray) {
849         out[0] = ((Argb ushr 16) and 0xFF) / 255f
850         out[1] = ((Argb ushr 8) and 0xFF) / 255f
851         out[2] = (Argb and 0xFF) / 255f
852     }
853
854     /** Invalidates worker results created before a destructive document change. */
855     private fun invalidatePendingUndoHistory() {
856         checkOnGUIThread()
857         undoPipeline.invalidate()
858     }
859
860     private fun shutdownUndoExecutor() {
861         undoPipeline.shutdown()
862     }
863
864     private fun ensureTilePayloadExecutor() {
865         if (tilePayloadExecutor.isShutdown) {
866             tilePayloadExecutor = Executors.newSingleThreadExecutor()
867         }
868     }
869
870     private fun shutdownTilePayloadExecutor() {
871         tilePayloadExecutor.shutdownNow()
872     }
873
874     /** Safe to call from the UI thread; cancellation is executed on the next GL frame. */
875     fun cancelActiveStroke() {
876         cancelRequested.set(true)
877     }
878
879     /** Must run on the GL thread while the context is still current. */
880     fun releaseGLObjects() {
881         checkOnGUIThread()
882         invalidatePendingUndoHistory()
883         discardPendingInput()
884         resetStroke()
885         undoManager.clear()
886         shutdownUndoExecutor()
887         shutdownTilePayloadExecutor()
888         dabRenderer?.release()
889         dabRenderer = null
890         grainTexture?.release()
891         grainTexture = null
892         grainPath = null
893         shapeTexture?.release()
894         shapeTexture = null
895         shapePath = null
896         capsuleRenderer?.release()
897         capsuleRenderer = null
898         strokeBlitter?.release()
899         strokeBlitter = null
900         nonBuildupStrokeRenderer?.release()
901         nonBuildupStrokeRenderer = null
902         compositor?.release()
903         compositor = null
904         backdropRenderer?.release()
905         backdropRenderer = null
906         screenPresentRenderer?.release()
907         screenPresentRenderer = null
908         linearTextureBlitter?.release()
909         linearTextureBlitter = null
910         thumbnailScheduler?.shutdown()
911         thumbnailCapture.release()
912         documentSession = null
913         geometry?.release()
914         geometry = null
915         strokeTarget.release()
916         strokeCoverageTarget.release()

```

```

917         compositeTarget.release()
918         lowerCompositeTarget.release()
919         upperCompositeTarget.release()
920         layerStack.release()
921         caps = null
922     }
923
924     private fun drainInput() {
925         var processedBatches = 0
926         while (processedBatches < MAX_INPUT_BATCHES_PER_FRAME) {
927             val batch = inputQueue.poll() ?: return
928             try {
929                 when (batch.action) {
930                     InputAction.DOWN -> {
931                         if (!batch.isEmpty()) {
932                             resetStroke()
933                             val strokeBrush = brushSettings.resolved()
934                             activeStrokeBrush = strokeBrush
935                             ColorSpaces.srgb8ToLinear(strokeBrush.colorArgb, activeStrokeColorLinear)
936                             activeStrokeColorLinear.copyInto(strokeColorLinear)
937                             activeStrokeErase = eraserEnabled
938                             strokeActive = true
939
940                             if (strokeBrush.renderMode == BrushRenderMode.RIBBON) {
941                                 capsuleEmitter.begin(
942                                     batch = batch,
943                                     out = checkNotNull(capsuleRenderer),
944                                     strokeSettings = strokeBrush,
945                                 )
946                             } else {
947                                 dabRenderer?.beginStroke()
948                                 stampEmitter.begin(batch, dabBuffer, strokeBrush)
949                                 strokeTarget.clear(0f, 0f, 0f, 0f)
950                                 stampPreviewInitialized = true
951
952                                 drawPendingStampPreview("DOWN")
953                             }
954                         }
955                     }
956
957                     InputAction.MOVE -> if (strokeActive) {
958                         val strokeBrush = activeStrokeBrush
959                         ?: error("Missing active stroke snapshot")
960                         if (strokeBrush.renderMode == BrushRenderMode.RIBBON) {
961                             capsuleEmitter.append(
962                                 batch = batch,
963                                 out = checkNotNull(capsuleRenderer),
964                             )
965                         } else {
966                             stampEmitter.append(batch, dabBuffer)
967                             drawPendingStampPreview("MOVE")
968                         }
969                     }
970
971                     InputAction.UP -> if (strokeActive) {
972                         val strokeBrush = activeStrokeBrush
973                         ?: error("Missing active stroke snapshot")
974                         if (strokeBrush.renderMode == BrushRenderMode.RIBBON) {
975                             val renderer = checkNotNull(capsuleRenderer)
976
977                             // UP должен сначала обработать historical samples,
978                             // затем текущую точку, которую уже положил capturer.
979                             capsuleEmitter.append(
980                                 batch = batch,
981                                 out = renderer,
982                             )
983                             capsuleEmitter.finish(
984                                 out = renderer,
985                                 cancel = false,
986                             )
987                             commitCapsuleStroke(strokeBrush)
988                         } else {
989                             stampEmitter.append(batch, dabBuffer)
990                             stampEmitter.finish(dabBuffer, cancel = false)
991                             commitStroke(strokeBrush)
992                         }
993
994                         resetStroke()
995                     }
996
997                     InputAction.CANCEL -> resetStroke()
998                 }
999             } finally {
1000                 inputPool.release(batch)
1001             }
1002             processedBatches++
1003         }
1004
1005         // Keep a continuation frame scheduled, but never let a delayed input
1006         // backlog monopolise the GL thread and visibly freeze the canvas.
1007         if (inputQueue.isNotEmpty()) {
1008             onInputRenderRequested?.invoke()

```

```

1009     }
1010 }
1011
1012 private fun commitStroke(strokeBrush: BrushSettings) {
1013     val layer = layerStack.activeLayer() ?: return
1014     if (layer.isLocked || dabBuffer.count == 0) return
1015     if (!computeDirtyPixelBounds(dirtyBounds)) return
1016     val blitter = strokeBlitter ?: return
1017     val strokeGeometry = geometry ?: return
1018
1019     if (strokeBrush.blendPolicy == BlendPolicy.NON_BUILDUP) {
1020         val renderer = dabRenderer ?: return
1021         val nonBuildupBlitter = nonBuildupStrokeRenderer ?: return
1022         strokeTarget.clear(0f, 0f, 0f, 0f)
1023         strokeCoverageTarget.clear(0f, 0f, 0f, 0f)
1024         renderer.drawInto(
1025             target = strokeTarget,
1026             width = layerStack.canvasWidth,
1027             height = layerStack.canvasHeight,
1028             canvasToFbo = canvasToFboMatrix,
1029             dabs = dabBuffer,
1030             colorLinear = activeStrokeColorLinear,
1031             blendPolicy = BlendPolicy.NORMAL_BUILDUP,
1032             strokeOpacity = 1f,
1033         )
1034         renderer.drawCoverageInto(
1035             target = strokeCoverageTarget,
1036             width = layerStack.canvasWidth,
1037             height = layerStack.canvasHeight,
1038             canvasToFbo = canvasToFboMatrix,
1039             dabs = dabBuffer,
1040         )
1041         if (strokeCommitter.commitNonBuildup(
1042             layer = layer,
1043             geometry = strokeGeometry,
1044             blitter = nonBuildupBlitter,
1045             coverageTarget = strokeCoverageTarget,
1046             dirtyBounds = dirtyBounds,
1047             canvasWidth = layerStack.canvasWidth,
1048             canvasHeight = layerStack.canvasHeight,
1049             opacity = strokeBrush.opacity,
1050             erase = activeStrokeErase,
1051         )) {
1052             publishState()
1053         }
1054         return
1055     }
1056
1057     // Complete the isolated local-coverage mask before it is composited.
1058     // Global brush opacity is deliberately applied only by the blit.
1059     drawPendingStampPreview("UP")
1060
1061     if (strokeCommitter.commit(
1062         layer = layer,
1063         geometry = strokeGeometry,
1064         blitter = blitter,
1065         dirtyBounds = dirtyBounds,
1066         canvasWidth = layerStack.canvasWidth,
1067         canvasHeight = layerStack.canvasHeight,
1068         opacity = strokeBrush.opacity,
1069         erase = activeStrokeErase,
1070     )) {
1071         publishState()
1072     }
1073 }
1074
1075 /** Returns a clamped pixel region covering the exact emitted dabs and their AA fringe. */
1076 private fun computeDirtyPixelBounds(out: IntArray): Boolean {
1077     if (dabBuffer.count == 0) return false
1078     strokeDirtyRect.clear()
1079     dabBuffer.includeDirtyRect(
1080         rect = strokeDirtyRect,
1081         extraMargin = STAMP_DIRTY_MARGIN_PX,
1082     )
1083     strokeDirtyRect.clamp(layerStack.canvasWidth.toFloat(), layerStack.canvasHeight.toFloat())
1084     strokeDirtyRect.toPixelBounds(out)
1085     return out[2] > out[0] && out[3] > out[1]
1086 }
1087
1088 private fun drawPendingStampPreview(phase: String) {
1089     val renderer = dabRenderer ?: return
1090     val strokeBrush = activeStrokeBrush
1091     ?: error("Missing active stroke snapshot")
1092     check(renderer.uploadedCount <= dabBuffer.count) {
1093         "Stamp preview rewind: uploaded=${renderer.uploadedCount}, dabs=${dabBuffer.count}"
1094     }
1095     if (LOG_STAMP_PREVIEW && BuildConfig.DEBUG) {
1096         Log.d(
1097             BRUSH_DIAG_TAG,
1098             "phase=$phase dabs=${dabBuffer.count} pending=${dabBuffer.count - renderer.uploadedCount}",
1099         )
1100     }

```

```

1101         renderer.drawPendingInto(
1102             target = strokeTarget,
1103             width = layerStack.canvasWidth,
1104             height = layerStack.canvasHeight,
1105             canvasToFbo = canvasToFboMatrix,
1106             dabs = dabBuffer,
1107             colorLinear = activeStrokeColorLinear,
1108             blendPolicy = strokeBrush.blendPolicy,
1109             strokeOpacity = 1f,
1110         )
1111         check(renderer.uploadedCount == dabBuffer.count) {
1112             "Stamp preview did not consume all dabs: uploaded=${renderer.uploadedCount}, dabs=${dabBuffer.count}"
1113         }
1114     }
1115
1116     private fun resetStroke() {
1117         strokeActive = false
1118         activeStrokeErase = false
1119         activeStrokeBrush = null
1120         stampEmitter.reset()
1121         dabBuffer.clear()
1122         capsuleEmitter.reset()
1123         capsuleRenderer?.clearStrokeData()
1124         capsulePreviewInitialized = false
1125         stampPreviewInitialized = false
1126         dabRenderer?.clearStrokeData()
1127         if (strokeTarget.framebufferId != 0) {
1128             strokeTarget.clear(0f, 0f, 0f, 0f)
1129         }
1130         if (strokeCoverageTarget.framebufferId != 0) {
1131             strokeCoverageTarget.clear(0f, 0f, 0f, 0f)
1132         }
1133     }
1134
1135     /** Releases pooled batches without interpreting them during shutdown/context recreation. */
1136     private fun discardPendingInput() {
1137         while (true) {
1138             val batch = inputQueue.poll() ?: return
1139             inputPool.release(batch)
1140         }
1141     }
1142
1143     /**
1144      * Builds the persisted metadata from the GL-owned runtime state. UI state
1145      * is never treated as the document source of truth.
1146      */
1147     fun buildDocumentSnapshot(): ProjectDocument {
1148         checkOnGLThread()
1149         return projectDocument.copy(
1150             updatedAt = System.currentTimeMillis(),
1151             activeLayerId = layerStack.activeLayerId,
1152             layers = layerStack.allLayers().map(::layerDocumentFrom),
1153         )
1154     }
1155
1156     private fun updateProjectDocument(
1157         transform: (ProjectDocument) -> ProjectDocument,
1158     ) {
1159         projectDocument = transform(projectDocument)
1160         projectDocument = buildDocumentSnapshot()
1161         documentSession?.markProjectDirty()
1162         onProjectDocumentChange?.invoke(projectDocument)
1163     }
1164
1165     fun acknowledgeSavedTiles(saved: Map<Long, Set<com.wetinknext.engine.undo.TileCoord>>) {
1166         layerTileStore.acknowledge(saved)
1167         documentSession?.markSaved(saved.keys)
1168     }
1169
1170     private fun publishDirtyTiles() {
1171         val dirty = layerTileStore.takeDirty()
1172         if (dirty.isEmpty()) return
1173         val documentSnapshot = buildDocumentSnapshot()
1174         projectDocument = documentSnapshot
1175         documentSession?.markProjectDirty()
1176         // PersistentLayerTiles.encode() can copy tens of MB for a mature 4K
1177         // layer. Never do that allocation while the GL thread is responsible
1178         // for accepting stylus input and drawing the next preview frame.
1179         try {
1180             tilePayloadExecutor.execute {
1181                 val payloads = runCatching {
1182                     layerTileStore.payloadsForDirty(dirty)
1183                 }.getOrElse { error ->
1184                     if (BuildConfig.DEBUG) Log.e("TilePersistence", "Tile payload encoding failed", error)
1185                     return@execute
1186                 }
1187                 onDirtyLayerTiles?.invoke(documentSnapshot, payloads, dirty)
1188             }
1189         } catch (_: RejectedExecutionException) {
1190             // Context release cancelled a stale save. The next active session
1191             // will retain its dirty tiles and schedule a fresh publication.
1192         }

```

```

1193     }
1194
1195     /** Re-captures restored GPU tiles so Undo/Redo is persisted like a stroke. */
1196     private fun persistRestoredTiles(
1197         layer: PaintLayer,
1198         tiles: List<com.wetinknext.engine.undo.TileSnapshot>,
1199     ) {
1200         if (tiles.isEmpty()) return
1201         val left = tiles.minOf { it.pixelLeft }
1202         val top = tiles.minOf { it.pixelTop }
1203         val right = tiles.maxOf { it.pixelLeft + it.pixelWidth }
1204         val bottom = tiles.maxOf { it.pixelTop + it.pixelHeight }
1205         val raw = com.wetinknext.engine.undo.TileSnapshotCapture.capture(
1206             target = layer.target,
1207             bounds = intArrayOf(left, top, right, bottom),
1208         )
1209         layerTileStore.markDirty(layer.id, raw)
1210         publishDirtyTiles()
1211         markLayerThumbnailDirty(layer.id)
1212     }
1213
1214     private fun captureThumbnail(dirtyLayerIds: Collection<Long> = emptyList()) {
1215         if (caps == null || geometry == null || compositor == null) return
1216         val scheduler = thumbnailScheduler
1217         if (scheduler != null) {
1218             scheduler.markDirty(projectDirty = true, dirtyLayerIds = dirtyLayerIds)
1219             onInputRenderRequested?.invoke()
1220         } else {
1221             onThumbnailCaptured?.invoke(thumbnailCapture.capture(layerStack))
1222         }
1223     }
1224
1225     /** Called only after a successful GPU edit of [layerId]. */
1226     private fun markLayerThumbnailDirty(layerId: Long) {
1227         val scheduler = thumbnailScheduler
1228         if (scheduler != null) {
1229             scheduler.markLayerDirty(layerId)
1230             scheduler.markProjectDirty()
1231             onInputRenderRequested?.invoke()
1232         } else {
1233             captureThumbnail()
1234         }
1235     }
1236
1237     /**
1238     * Records published preview files on the GL thread. Scheduler generations
1239     * ensure every listed layer still has the pixels used to create its image.
1240     */
1241     fun applyThumbnailBuild(result: ThumbnailBuildResult) {
1242         checkOnGLThread()
1243         result.layerPreviews.forEach { (layerId, file) ->
1244             layerStack.findLayerById(layerId)?.let { layer ->
1245                 layerThumbnailPaths[layerId] = file.absolutePath
1246                 layerThumbnailVersions[layerId] = layer.version
1247             }
1248         }
1249         layerThumbnailPaths.keys.retainAll(layerStack.allLayers().map(PaintLayer::id).toSet())
1250         layerThumbnailVersions.keys.retainAll(layerStack.allLayers().map(PaintLayer::id).toSet())
1251         // layerDocumentFrom copies the current PaintLayer.version into
1252         // thumbnailVersion, and updateProjectDocument atomically publishes the
1253         // resulting document snapshot to the autosave bridge.
1254         updateProjectDocument { it }
1255         publishState()
1256     }
1257
1258     /**
1259     * Makes WebP previews restored from the persisted project immediately
1260     * available to Compose. An older persisted preview may never replace a
1261     * newer runtime image after a stroke has incremented the layer version.
1262     */
1263     fun installRestoredLayerThumbnails(previews: Map<Long, File>) {
1264         // queueEvent() is allowed to run before Renderer.onSurfaceCreated().
1265         // At that time no GL owner or LayerStack exists yet, so checking the
1266         // thread here used to crash application startup.
1267         if (glThread == null) {
1268             deferredRestoredLayerThumbnails = previews
1269             return
1270         }
1271         checkOnGLThread()
1272         var changed = false
1273         previews.forEach { (layerId, file) ->
1274             val layer = layerStack.findLayerById(layerId) ?: return@forEach
1275             val storedVersion = projectDocument.layers
1276                 .firstOrNull { it.id == layerId }
1277                 ?.thumbnailVersion
1278             ?: return@forEach
1279             if (file.isFile && layer.version == storedVersion && layerThumbnailVersions[layerId] == null) {
1280                 layerThumbnailPaths[layerId] = file.absolutePath
1281                 layerThumbnailVersions[layerId] = storedVersion
1282                 changed = true
1283             }
1284         }
1285     }

```

```

1285         if (changed) publishState()
1286     }
1287
1288     private fun syncLayerDocument(layer: PaintLayer) {
1289         updateProjectDocument { document ->
1290             document.copy(
1291                 layers = document.layers.map { stored ->
1292                     if (stored.id == layer.id) layerDocumentFrom(layer, stored.pixelFile) else stored
1293                 },
1294                 activeLayerId = layerStack.activeLayerId,
1295             )
1296         }
1297     }
1298
1299     private fun layerDocumentFrom(
1300         layer: PaintLayer,
1301         pixelFile: String = ProjectDocument.pixelFileFor(layer.id),
1302     ): LayerDocument = LayerDocument(
1303         id = layer.id,
1304         name = layer.name,
1305         visible = layer.isVisible,
1306         locked = layer.isLocked,
1307         opacity = layer.opacity,
1308         blendMode = layer.blendMode,
1309         pixelFile = pixelFile,
1310         thumbnailVersion = layerThumbnailVersions[layer.id]
1311             ?: projectDocument.layers.firstOrNull { it.id == layer.id }?.thumbnailVersion
1312             ?: 0L,
1313     )
1314
1315     private fun publishState() {
1316         val listener = onStateChange ?: return
1317         val layers = layerStack.allLayers()
1318         val activeLayerId = layerStack.activeLayerId
1319         val canDeleteLayers = layers.size > 1
1320         listener(
1321             EditorUiState(
1322                 layers = layers.map { layer ->
1323                     LayerUiModel(
1324                         id = layer.id,
1325                         name = layer.name,
1326                         isVisible = layer.isVisible,
1327                         isLocked = layer.isLocked,
1328                         opacity = layer.opacity,
1329                         active = layer.id == activeLayerId,
1330                         canDelete = !layer.isLocked && canDeleteLayers,
1331                         thumbnailPath = layerThumbnailPaths[layer.id],
1332                         thumbnailVersion = layerThumbnailVersions[layer.id]
1333                             ?: projectDocument.layers.firstOrNull { it.id == layer.id }?.thumbnailVersion
1334                             ?: 0L,
1335                     )
1336                 },
1337                 canUndo = undoManager.canUndo && undoPipeline.pendingCount == 0,
1338                 canRedo = undoManager.canRedo && undoPipeline.pendingCount == 0,
1339                 brushSizePx = brushSettings.baseRadiusPx * 2f,
1340                 brushOpacity = brushSettings.opacity,
1341                 activeLayerId = activeLayerId,
1342                 ready = layerStack.canvasWidth > 0 && layerStack.canvasHeight > 0,
1343                 undoDiagnostics = UndoDiagnostics(
1344                     pendingJobs = undoPipeline.pendingCount,
1345                     staleResults = undoPipeline.staleResultCount,
1346                     compressionFailures = undoPipeline.compressionFailureCount,
1347                     restoreFailures = undoRestoreFailures,
1348                     memoryBytes = undoManager.memoryBytes,
1349                 ),
1350             ),
1351         )
1352     }
1353
1354     /**
1355     * Вызывается только через GLSurfaceView.queueEvent,
1356     * то есть на GL-потоке с current EGL context.
1357     */
1358     fun applyLoadedGrain(
1359         loaded: LoadedBrushTexture,
1360         scale: Float,
1361         canvasLocked: Boolean,
1362         depth: Float,
1363         contrast: Float,
1364     ) {
1365         val oldTexture = grainTexture
1366         val newTexture = BrushTexture()
1367
1368         try {
1369             newTexture.createFromRgba(
1370                 width = loaded.width,
1371                 height = loaded.height,
1372                 rgba = loaded.rgba,
1373             )
1374
1375             capsuleRenderer?.setGrainTexture(
1376                 textureId = newTexture.textureId,

```

```

1377         scale = scale,
1378         canvasLocked = canvasLocked,
1379         depth = depth,
1380         contrast = contrast,
1381     )
1382
1383     dabRenderer?.setGrainTexture(
1384         textureId = newTexture.textureId,
1385         scale = scale,
1386         canvasLocked = canvasLocked,
1387         depth = depth,
1388         contrast = contrast,
1389     )
1390
1391     grainTexture = newTexture
1392     grainPath = loaded.path
1393
1394     oldTexture?.release()
1395 } catch (error: Throwable) {
1396     newTexture.release()
1397     throw error
1398 }
1399 }
1400
1401 fun clearGrainTexture() {
1402     capsuleRenderer?.clearGrainTexture()
1403     dabRenderer?.clearGrainTexture()
1404
1405     grainTexture?.release()
1406     grainTexture = null
1407     grainPath = null
1408 }
1409
1410 /** Must run on the GL thread. Shape masks affect STAMP dabs only. */
1411 fun applyLoadedShape(
1412     loaded: LoadedBrushTexture,
1413     reverse: Boolean,
1414     rgbToAlpha: Boolean,
1415 ) {
1416     val oldTexture = shapeTexture
1417     val newTexture = BrushTexture()
1418
1419     try {
1420         newTexture.createFromRgba(loaded.width, loaded.height, loaded.rgb)
1421         dabRenderer?.setShapeTexture(newTexture.textureId, reverse, rgbToAlpha)
1422         shapeTexture = newTexture
1423         shapePath = loaded.path
1424         oldTexture?.release()
1425     } catch (error: Throwable) {
1426         newTexture.release()
1427         throw error
1428     }
1429 }
1430
1431 fun clearShapeTexture() {
1432     dabRenderer?.clearShapeTexture()
1433     shapeTexture?.release()
1434     shapeTexture = null
1435     shapePath = null
1436 }
1437
1438 private fun nextLayerName(): String = "Слой ${layerStack.count + 1}"
1439
1440 private fun nextDuplicateLayerName(sourceName: String): String {
1441     val base = "$sourceName копия"
1442     val names = layerStack.allLayers().map(PaintLayer::name).toSet()
1443     if (base !in names) return base
1444     var number = 2
1445     while ("base $number" in names) number++
1446     return "base $number"
1447 }
1448
1449 private fun renderCapsulePreview(strokeBrush: BrushSettings) {
1450     val renderer = capsuleRenderer ?: return
1451
1452     if (!capsulePreviewInitialized) {
1453         strokeTarget.clear(
1454             red = 0f,
1455             green = 0f,
1456             blue = 0f,
1457             alpha = 0f,
1458         )
1459         capsulePreviewInitialized = true
1460     }
1461
1462     renderer.drawPending(
1463         target = strokeTarget,
1464         width = layerStack.canvasWidth,
1465         height = layerStack.canvasHeight,
1466         canvasToClip = canvasToFboMatrix,
1467         colorLinear = activeStrokeColorLinear,
1468         blendPolicy = strokeBrush.blendPolicy,

```



```

1469         flow = strokeBrush.flow,
1470     )
1471 }
1472
1473 private fun commitCapsuleStroke(strokeBrush: BrushSettings) {
1474     val layer = layerStack.activeLayer() ?: return
1475     val renderer = capsuleRenderer ?: return
1476
1477     if (layer.isLocked) return
1478     if (!capsuleEmitter.hasStroke) return
1479     if (!computeCapsuleDirtyBounds(dirtyBounds)) return
1480     val blitter = strokeBlitter ?: return
1481     val strokeGeometry = geometry ?: return
1482
1483     /*
1484     * Сначала строим stroke в отдельном offscreen target.
1485     * Старый слой и новый renderer не используют один FBO для рисования.
1486     */
1487     strokeTarget.clear(
1488         red = 0f,
1489         green = 0f,
1490         blue = 0f,
1491         alpha = 0f,
1492     )
1493
1494     renderer.drawAll(
1495         target = strokeTarget,
1496         width = layerStack.canvasWidth,
1497         height = layerStack.canvasHeight,
1498         canvasToClip = canvasToFboMatrix,
1499         colorLinear = activeStrokeColorLinear,
1500         blendPolicy = strokeBrush.blendPolicy,
1501         flow = strokeBrush.flow,
1502     )
1503
1504     if (strokeCommitter.commit(
1505         layer = layer,
1506         geometry = strokeGeometry,
1507         blitter = blitter,
1508         dirtyBounds = dirtyBounds,
1509         canvasWidth = layerStack.canvasWidth,
1510         canvasHeight = layerStack.canvasHeight,
1511         opacity = strokeBrush.opacity,
1512         erase = activeStrokeErase,
1513     )) {
1514         publishState()
1515     }
1516 }
1517
1518 private fun computeCapsuleDirtyBounds(
1519     out: IntArray,
1520 ): Boolean {
1521     if (!capsuleEmitter.hasBounds) return false
1522
1523     strokeDirtyRect.clear()
1524     strokeDirtyRect.include(
1525         left = capsuleEmitter.minX,
1526         top = capsuleEmitter.minY,
1527         right = capsuleEmitter.maxX,
1528         bottom = capsuleEmitter.maxY,
1529     )
1530     strokeDirtyRect.expand(AA_MARGIN_PX)
1531     strokeDirtyRect.clamp(
1532         layerStack.canvasWidth.toFloat(),
1533         layerStack.canvasHeight.toFloat(),
1534     )
1535     strokeDirtyRect.toPixelBounds(out)
1536
1537     return out[2] > out[0] && out[3] > out[1]
1538 }
1539
1540 companion object {
1541     /** Bounded GL-thread work per frame; ordered input is never dropped. */
1542     private const val MAX_INPUT_BATCHES_PER_FRAME = 6
1543     /** Per-MOVE Logcat I/O is expensive on debug tablet builds. */
1544     private const val LOG_STAMP_PREVIEW = false
1545     private const val BRUSH_DIAG_TAG = "BrushDiag"
1546     private const val THUMBNAIL_TAG = "ThumbnailBuild"
1547     private const val AA_MARGIN_PX = 4f
1548     private const val STAMP_DIRTY_MARGIN_PX = 4f
1549 }
1550 }

```

52. app/src/main/java/com/wetinknext/engine/core/LatestValueDelivery.kt

```
1 package com.wetinknext.engine.core
2
3 import java.util.concurrent.atomic.AtomicReference
4
5 /**
6  * Retains the newest cross-thread value until a consumer is ready.
7  *
8  * GLSurfaceView can create EGL before Compose has installed its listener. A
9  * thumbnail is a replaceable snapshot, so retaining only the newest frame is
10  * both sufficient and bounded.
11  */
12 internal class LatestValueDelivery<T> {
13     private val pending = AtomicReference<T?>(null)
14
15     fun offer(value: T) {
16         pending.set(value)
17     }
18
19     fun dispatchTo(listener: ((T) -> Unit)?) {
20         val callback = listener ?: return
21         pending.getAndSet(null)?.let(callback)
22     }
23
24     fun clear() {
25         pending.set(null)
26     }
27 }
```

53. app/src/main/java/com/wetinknext/engine/core/LayerTileCodec.kt

```

1 package com.wetinknext.engine.core
2
3 import android.opengl.GLES30
4 import com.wetinknext.engine.gl.RenderTarget
5 import com.wetinknext.engine.persistence.PersistentLayerTiles
6 import java.nio.ByteBuffer
7 import java.nio.ByteOrder
8
9 /**
10  * Stable payload for a complete layer texture. Empty data means a newly-created
11  * layer; later persistence can emit this format without changing the loader.
12  */
13 object LayerTileCodec {
14     private const val MAGIC = 0x5754494C // WTL
15     private const val VERSION = 1
16     private const val HEADER_BYTES = 20
17
18     data class Decoded(val width: Int, val height: Int, val bytesPerPixel: Int, val pixels: ByteArray)
19
20     fun encode(width: Int, height: Int, bytesPerPixel: Int, pixels: ByteArray): ByteArray {
21         require(width > 0 && height > 0 && bytesPerPixel in setOf(4, 8)) { "Invalid layer tile header" }
22         val expected = width.toLong() * height * bytesPerPixel
23         require(expected <= Int.MAX_VALUE && pixels.size == expected.toInt()) { "Invalid layer tile size" }
24         return ByteBuffer.allocate(HEADER_BYTES + pixels.size)
25             .order(ByteOrder.BIG_ENDIAN)
26             .putInt(MAGIC)
27             .putInt(VERSION)
28             .putInt(width)
29             .putInt(height)
30             .putInt(bytesPerPixel)
31             .put(pixels)
32             .array()
33     }
34
35     fun decode(bytes: ByteArray): Decoded? {
36         if (bytes.isEmpty()) return null
37         require(bytes.size >= HEADER_BYTES) { "Layer tile payload is truncated" }
38         val buffer = ByteBuffer.wrap(bytes).order(ByteOrder.BIG_ENDIAN)
39         require(buffer.int == MAGIC) { "Unknown layer tile payload" }
40         require(buffer.int == VERSION) { "Unsupported layer tile version" }
41         val width = buffer.int
42         val height = buffer.int
43         val bytesPerPixel = buffer.int
44         require(width > 0 && height > 0 && bytesPerPixel in setOf(4, 8)) { "Invalid layer tile header" }
45         val expected = width.toLong() * height * bytesPerPixel
46         require(expected <= Int.MAX_VALUE && bytes.size - HEADER_BYTES == expected.toInt()) { "Invalid layer tile size" }
47         return Decoded(width, height, bytesPerPixel, bytes.copyOfRange(HEADER_BYTES, bytes.size))
48     }
49
50     fun upload(target: RenderTarget, bytes: ByteArray) {
51         val decoded = decode(bytes) ?: return
52         require(decoded.width == target.width && decoded.height == target.height) { "Layer tile dimensions do not match
document" }
53         val expectedBpp = if (target.usesHalfFloat) 8 else 4
54         require(decoded.bytesPerPixel == expectedBpp) { "Layer tile pixel format does not match GPU target" }
55
56         val data = ByteBuffer.allocateDirect(decoded.pixels.size).order(ByteOrder.nativeOrder())
57         data.put(decoded.pixels).flip()
58         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
59         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, target.textureId)
60         GLES30.glPixelStorei(GLES30.GL_UNPACK_ALIGNMENT, 1)
61         try {
62             GLES30.glTexSubImage2D(
63                 GLES30.GL_TEXTURE_2D, 0, 0, 0, decoded.width, decoded.height,
64                 GLES30.GL_RGBA,
65                 if (decoded.bytesPerPixel == 8) GLES30.GL_HALF_FLOAT else GLES30.GL_UNSIGNED_BYTE,
66                 data,
67             )
68             check(GLES30.glGetError() == GLES30.GL_NO_ERROR) { "Layer texture upload failed" }
69         } finally {
70             GLES30.glPixelStorei(GLES30.GL_UNPACK_ALIGNMENT, 4)
71             GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
72         }
73     }
74
75     fun uploadPersistent(target: RenderTarget, payload: ByteArray) {
76         if (payload.isEmpty()) return
77         val expectedBpp = if (target.usesHalfFloat) 8 else 4
78         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
79         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, target.textureId)
80         GLES30.glPixelStorei(GLES30.GL_UNPACK_ALIGNMENT, 1)
81         try {
82             PersistentLayerTiles.decode(payload).forEach { tile ->
83                 require(tile.bytesPerPixel == expectedBpp && tile.pixelLeft + tile.pixelWidth <= target.width && tile.
pixelTop + tile.pixelHeight <= target.height) { "Invalid persistent tile" }
84                 val data = ByteBuffer.allocateDirect(tile.bytes.size).order(ByteOrder.nativeOrder())
85                 data.put(tile.bytes).flip()
86                 GLES30.glTexSubImage2D(GLES30.GL_TEXTURE_2D, 0, tile.pixelLeft, tile.pixelTop, tile.pixelWidth, tile.
pixelHeight, GLES30.GL_RGBA, if (expectedBpp == 8) GLES30.GL_HALF_FLOAT else GLES30.GL_UNSIGNED_BYTE, data)
87             }
88         }
89     }
90 }

```

```
88         check(GLES30.glGetError() == GLES30.GL_NO_ERROR) { "Persistent tile upload failed" }
89     } finally {
90         GLES30.glPixelStorei(GLES30.GL_UNPACK_ALIGNMENT, 4)
91         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
92     }
93 }
94 }
```

54. app/src/main/java/com/wetinknext/engine/core/PaintEngine.kt

```
1 package com.wetinknext.engine.core
2
3 import com.wetinknext.engine.canvas.LayerStack
4 import com.wetinknext.engine.gl.GlCaps
5 import com.wetinknext.engine.gl.RenderTarget
6
7 /** Lightweight document facade retained for engine callers outside the renderer. */
8 class PaintEngine {
9     val layerStack = LayerStack()
10    val camera: Camera get() = layerStack.camera
11    val canvasTarget: RenderTarget get() = checkNotNull(layerStack.activeLayer()).target
12
13    val canvasWidth: Int get() = layerStack.canvasWidth
14    val canvasHeight: Int get() = layerStack.canvasHeight
15    var initialized = false
16        private set
17
18    fun create(caps: GlCaps, width: Int, height: Int) {
19        layerStack.create(caps, width, height)
20        initialized = true
21    }
22
23    fun addLayer(name: String): Long = layerStack.addLayer(name).id
24
25    fun removeLayer(id: Long): Boolean = layerStack.removeLayer(id) != null
26
27    fun setActiveLayer(id: Long): Boolean = layerStack.setActive(id)
28
29    fun release() {
30        layerStack.release()
31        initialized = false
32    }
33 }
```

55. app/src/main/java/com/wetinknext/engine/core/PaintSurfaceView.kt

```

1  package com.wetinknext.engine.core
2
3  import android.content.Context
4  import android.opengl.GLSurfaceView
5  import android.util.AttributeSet
6  import android.view.MotionEvent
7  import com.wetinknext.domain.document.ProjectDocument
8  import com.wetinknext.engine.brush.BrushSettings
9  import com.wetinknext.engine.brush.TextureLoader
10 import com.wetinknext.engine.brush.LoadedBrushTexture
11 import com.wetinknext.engine.thumbnail.ThumbnailBuildResult
12 import com.wetinknext.engine.thumbnail.ThumbnailPreviewFiles
13 import java.io.File
14 import java.util.concurrent.ExecutorService
15 import java.util.concurrent.Executors
16
17 /** Thread boundary between Compose commands and the GL-owned paint engine. */
18 class PaintSurfaceView @JvmOverloads constructor(
19     context: Context,
20     attrs: AttributeSet? = null,
21     document: ProjectDocument = ProjectDocument.newUntitled(),
22     layerTiles: Map<Long, ByteArray> = emptyMap(),
23     layerPreviews: Map<Long, ByteArray> = emptyMap(),
24 ) : GLSurfaceView(context, attrs) {
25     private val thumbnailOutputDirectory = File(context.cacheDir, "wetink-thumbnails/${document.id}")
26     private val engineRenderer = EngineRenderer(
27         projectDocument = document,
28         initialLayerTiles = layerTiles,
29         thumbnailOutputDirectory = thumbnailOutputDirectory,
30     )
31
32     private val textureLoader = TextureLoader(context)
33     private val thumbnailRestoreExecutor: ExecutorService = Executors.newSingleThreadExecutor()
34     private var grainGeneration = 0L
35     private var shapeGeneration = 0L
36
37     var onTextureError: ((String, Throwable) -> Unit)? = null
38
39     var onEditorStateChange: ((EditorUiState) -> Unit)? = null
40     var onProjectDocumentChange: ((ProjectDocument) -> Unit)? = null
41     private var documentSessionLoaded = false
42     var onDocumentSessionLoaded: (() -> Unit)? = null
43     set(value) {
44         field = value
45         if (documentSessionLoaded && value != null) post(value)
46     }
47     var onDirtyLayerTiles: ((ProjectDocument, Map<Long, ByteArray>, Map<Long, Set<com.wetinknext.engine.undo.TileCoord>)) ->
Unit)? = null
48     private val pendingThumbnailCapture = LatestValueDelivery<ThumbnailCapture.Rgba>()
49     var onThumbnailCaptured: ((ThumbnailCapture.Rgba) -> Unit)? = null
50     set(value) {
51         field = value
52         if (value != null) {
53             // setRenderer() may initialize EGL before AndroidView's caller
54             // has installed its listener. Replay the latest capture then.
55             post(::dispatchPendingThumbnail)
56         }
57     }
58     /** File previews that were encoded on the worker and published to cache. */
59     var onThumbnailBuildSaved: ((ThumbnailBuildResult) -> Unit)? = null
60
61     init {
62         setEGLContextClientVersion(3)
63         setRenderer(engineRenderer)
64         renderMode = RENDERMODE_WHEN_DIRTY
65         engineRenderer.onStateChange = { state ->
66             post { onEditorStateChange?.invoke(state) }
67             requestRender()
68         }
69         engineRenderer.onProjectDocumentChange = { document ->
70             post { onProjectDocumentChange?.invoke(document) }
71         }
72         engineRenderer.onDocumentSessionLoaded = {
73             documentSessionLoaded = true
74             post { onDocumentSessionLoaded?.invoke() }
75         }
76         engineRenderer.onDirtyLayerTiles = { document, payloads, dirty -> post { onDirtyLayerTiles?.invoke(document, payloads,
dirty) } }
77         engineRenderer.onThumbnailCaptured = { image ->
78             pendingThumbnailCapture.offer(image)
79             post(::dispatchPendingThumbnail)
80         }
81         engineRenderer.onThumbnailBuildSaved = { result ->
82             // The worker has published files, but document metadata and layer
83             // UI state remain GL-owned. Update those first, then notify the
84             // app-level persistence bridge on the main thread.
85             post {
86                 queueEvent {
87                     engineRenderer.applyThumbnailBuild(result)
88                     requestRender()

```

```

89         post { onThumbnailBuildSaved?.invoke(result) }
90     }
91 }
92 }
93 engineRenderer.onInputRenderRequested = { requestRender() }
94 restoreStoredLayerPreviews(layerPreviews)
95 }
96
97 override fun onTouchEvent(event: MotionEvent): Boolean {
98     val handled = engineRenderer.onTouchEvent(event)
99     if (handled) requestRender()
100     return handled || super.onTouchEvent(event)
101 }
102
103 fun requestState() = queueEvent {
104     engineRenderer.requestState()
105     requestRender()
106 }
107
108 fun undo() = queueEvent {
109     engineRenderer.undo()
110     requestRender()
111 }
112
113 fun redo() = queueEvent {
114     engineRenderer.redo()
115     requestRender()
116 }
117
118 fun acknowledgeSavedTiles(saved: Map<Long, Set<com.wetinknext.engine.undo.TileCoord>>) = queueEvent {
119     engineRenderer.acknowledgeSavedTiles(saved)
120 }
121
122 fun setActiveLayer(id: Long) = queueEvent {
123     engineRenderer.setActiveLayer(id)
124     requestRender()
125 }
126
127 fun addLayer() = queueEvent {
128     engineRenderer.addLayer()
129     requestRender()
130 }
131
132 fun duplicateLayer(id: Long) = queueEvent {
133     engineRenderer.duplicateLayer(id)
134     requestRender()
135 }
136
137 fun removeLayer(id: Long) = queueEvent {
138     engineRenderer.removeLayer(id)
139     requestRender()
140 }
141
142 fun moveLayer(id: Long, delta: Int) = queueEvent {
143     engineRenderer.moveLayer(id, delta)
144     requestRender()
145 }
146
147 fun setLayerVisible(id: Long, visible: Boolean) =
148     queueEvent {
149         engineRenderer.setLayerVisible(id, visible)
150         requestRender()
151     }
152
153 fun setLayerOpacity(id: Long, opacity: Float) =
154     queueEvent {
155         engineRenderer.setLayerOpacity(id, opacity)
156         requestRender()
157     }
158
159 fun clearActiveLayer() = queueEvent {
160     engineRenderer.clearActiveLayer()
161     requestRender()
162 }
163
164 fun toggleCanvasMirror() = queueEvent {
165     engineRenderer.toggleCanvasMirror()
166     requestRender()
167 }
168
169 fun setCanvasBackdrop(backdropArgb: Int, gridArgb: Int, mode: CanvasBackdropMode) = queueEvent {
170     engineRenderer.setCanvasBackdrop(backdropArgb, gridArgb, mode)
171     requestRender()
172 }
173
174 fun setBrushSize(px: Float) = queueEvent {
175     engineRenderer.setBrushSize(px)
176     requestRender()
177 }
178
179 fun setBrushOpacity(opacity: Float) = queueEvent {
180     engineRenderer.setBrushOpacity(opacity)

```

```

181         requestRender()
182     }
183
184     fun setEraserEnabled(enabled: Boolean) = queueEvent {
185         engineRenderer.setEraserEnabled(enabled)
186         requestRender()
187     }
188
189     fun applyBrush(settings: BrushSettings) = queueEvent {
190         engineRenderer.applyBrush(settings)
191         requestRender()
192     }
193
194     fun setBrushSettings(settings: BrushSettings) = queueEvent {
195         engineRenderer.setBrushSettings(settings)
196         requestRender()
197     }
198
199     fun setBrushColor(color: androidx.compose.ui.graphics.Color) = queueEvent {
200         engineRenderer.setBrushColor(color)
201         requestRender()
202     }
203
204     fun loadGrainTexture(
205         path: String,
206         scale: Float = 1f,
207         canvasLocked: Boolean = true,
208         depth: Float = 1f,
209         contrast: Float = 1f,
210     ) {
211         val generation = ++grainGeneration
212
213         textureLoader.loadAsync(
214             path = path,
215             onLoad = { loaded ->
216                 queueEvent {
217                     if (generation != grainGeneration) {
218                         return@queueEvent
219                     }
220
221                     engineRenderer.applyLoadedGrain(
222                         loaded = loaded,
223                         scale = scale,
224                         canvasLocked = canvasLocked,
225                         depth = depth,
226                         contrast = contrast,
227                     )
228                     requestRender()
229                 }
230             },
231             onError = { error ->
232                 post {
233                     onTextureError?.invoke(path, error)
234                 }
235             },
236         )
237     }
238
239     fun clearGrainTexture() {
240         grainGeneration++
241
242         queueEvent {
243             engineRenderer.clearGrainTexture()
244             requestRender()
245         }
246     }
247
248     fun loadShapeTexture(
249         path: String,
250         reverse: Boolean = false,
251         rgbToAlpha: Boolean = false,
252     ) {
253         val generation = ++shapeGeneration
254         textureLoader.loadAsync(
255             path = path,
256             onLoad = { loaded ->
257                 queueEvent {
258                     if (generation != shapeGeneration) return@queueEvent
259                     engineRenderer.applyLoadedShape(loaded, reverse, rgbToAlpha)
260                     requestRender()
261                 }
262             },
263             onError = { error -> post { onTextureError?.invoke(path, error) } },
264         )
265     }
266
267     fun clearShapeTexture() {
268         shapeGeneration++
269         queueEvent {
270             engineRenderer.clearShapeTexture()
271             requestRender()
272         }
273     }

```



```

273     }
274
275     private fun dispatchPendingThumbnail() {
276         pendingThumbnailCapture.dispatchTo(onThumbnailCaptured)
277     }
278
279     /** Restores persisted WebP bytes off the main and GL threads. */
280     private fun restoreStoredLayerPreviews(layerPreviews: Map<Long, ByteArray>) {
281         if (layerPreviews.isEmpty()) return
282         thumbnailRestoreExecutor.execute {
283             val files = runCatching {
284                 ThumbnailPreviewFiles.restoreLayerPreviews(
285                     outputDirectory = thumbnailOutputDirectory,
286                     previews = layerPreviews,
287                 )
288             }.getOrElse { error ->
289                 post { onTextureError?.invoke("layer previews", error) }
290                 return@execute
291             }
292             queueEvent {
293                 engineRendererer.installRestoredLayerThumbnails(files)
294                 requestRender()
295             }
296         }
297     }
298
299     override fun onPause() {
300         engineRendererer.cancelActiveStroke()
301         super.onPause()
302     }
303
304     override fun onDetachedFromWindow() {
305         grainGeneration++
306         shapeGeneration++
307         textureLoader.shutdown()
308         thumbnailRestoreExecutor.shutdownNow()
309
310         // Очищаем listeners, чтобы избежать утечек или вызовов в пустоту
311         onTextureError = null
312         onEditorStateChange = null
313         onProjectDocumentChange = null
314         onDocumentSessionLoaded = null
315         onDirtyLayerTiles = null
316         onThumbnailCaptured = null
317         onThumbnailBuildSaved = null
318         pendingThumbnailCapture.clear()
319         engineRendererer.onStateChange = null
320         engineRendererer.onProjectDocumentChange = null
321         engineRendererer.onDocumentSessionLoaded = null
322         engineRendererer.onDirtyLayerTiles = null
323         engineRendererer.onThumbnailCaptured = null
324         engineRendererer.onThumbnailBuildSaved = null
325         engineRendererer.onInputRenderRequested = null
326         engineRendererer.setOnSecondaryPointerDown { }
327
328         // Пытаемся освободить GL-объекты, но не рассчитываем на 100% успех здесь
329         queueEvent {
330             // Отменяем активный штрих перед освобождением
331             engineRendererer.cancelActiveStroke()
332             engineRendererer.releaseGLObjects()
333         }
334         super.onDetachedFromWindow()
335     }
336 }

```

56. app/src/main/java/com/wetinknext/engine/core/StrokeCommitter.kt

```

1  package com.wetinknext.engine.core
2
3  import android.opengl.GLES30
4  import android.util.Log
5  import com.wetinknext.BuildConfig
6  import com.wetinknext.engine.canvas.PaintLayer
7  import com.wetinknext.engine.canvas.NonBuildupStrokeRenderer
8  import com.wetinknext.engine.canvas.StrokeBlitter
9  import com.wetinknext.engine.gl.CanvasGeometry
10 import com.wetinknext.engine.gl.GlCheck
11 import com.wetinknext.engine.gl.RenderTarget
12 import com.wetinknext.engine.undo.TileSnapshot
13 import com.wetinknext.engine.undo.TileSnapshotCapture
14 import com.wetinknext.engine.undo.UndoManager
15 import com.wetinknext.engine.undo.UndoOperationType
16 import com.wetinknext.engine.undo.RawTileSnapshot
17
18 /**
19  * GL-thread transaction boundary for a prepared stroke.
20  *
21  * The caller renders the active stroke into [strokeTarget]. This class then
22  * snapshots the affected layer tiles, performs the single premultiplied blit,
23  * captures the after-state, and sends the reversible transaction to history.
24  */
25 class StrokeCommitter(
26     private val strokeTarget: RenderTarget,
27     private val canvasToFbo: FloatArray,
28     private val undoPipeline: UndoCompressionPipeline,
29     private val undoManager: UndoManager,
30     private val onTilesCommitted: (PaintLayer, List<RawTileSnapshot>) -> Unit = { _, _ -> },
31     private val onLayerCleared: (PaintLayer) -> Unit = {},
32 ) {
33     /**
34      * Commits the already-rendered stroke target into [layer]. [dirtyBounds]
35      * is in canvas coordinates and is expanded to a deterministic tile set.
36      */
37     fun commit(
38         layer: PaintLayer,
39         geometry: CanvasGeometry,
40         blitter: StrokeBlitter,
41         dirtyBounds: IntArray,
42         canvasWidth: Int,
43         canvasHeight: Int,
44         opacity: Float,
45         erase: Boolean = false,
46         operation: UndoOperationType = UndoOperationType.TILE_EDIT,
47         tag: String = "stroke",
48     ): Boolean {
49         GlCheck.checkOnGUIThread()
50         if (!layer.created || layer.isLocked || strokeTarget.textureId == 0) return false
51         if (dirtyBounds.size < 4) return false
52
53         expandBoundsToTiles(dirtyBounds, canvasWidth, canvasHeight)
54         if (dirtyBounds[2] <= dirtyBounds[0] || dirtyBounds[3] <= dirtyBounds[1]) return false
55         logLargeUndoReadback(layer, dirtyBounds)
56
57         val beforeRaw = TileSnapshotCapture.capture(layer.target, dirtyBounds)
58         blitter.blit(
59             layer = layer.target,
60             geometry = geometry,
61             strokeTextureId = strokeTarget.textureId,
62             canvasToFbo = canvasToFbo,
63             width = canvasWidth,
64             height = canvasHeight,
65             opacity = opacity.coerceIn(0f, 1f),
66             erase = erase,
67         )
68         layer.version++
69         val afterRaw = TileSnapshotCapture.capture(layer.target, dirtyBounds)
70         undoPipeline.enqueue(
71             undoManager = undoManager,
72             layerId = layer.id,
73             beforeRaw = beforeRaw,
74             afterRaw = afterRaw,
75             operation = operation,
76             tag = tag,
77         )
78         onTilesCommitted(layer, afterRaw)
79         return true
80     }
81
82     /** Commits a STAMP_NON_BUILDUP stroke using its colour and union-coverage targets. */
83     fun commitNonBuildup(
84         layer: PaintLayer,
85         geometry: CanvasGeometry,
86         blitter: NonBuildupStrokeRenderer,
87         coverageTarget: RenderTarget,
88         dirtyBounds: IntArray,
89         canvasWidth: Int,
90         canvasHeight: Int,
91     ) {
92

```

```

91         opacity: Float,
92         erase: Boolean = false,
93     ): Boolean {
94         GLCheck.checkOnGUIThread()
95         if (!layer.created || layer.isLocked || strokeTarget.textureId == 0 || coverageTarget.textureId == 0) return false
96         if (dirtyBounds.size < 4) return false
97
98         expandBoundsToTiles(dirtyBounds, canvasWidth, canvasHeight)
99         if (dirtyBounds[2] <= dirtyBounds[0] || dirtyBounds[3] <= dirtyBounds[1]) return false
100        logLargeUndoReadback(layer, dirtyBounds)
101
102        val beforeRaw = TileSnapshotCapture.capture(layer.target, dirtyBounds)
103        blitter.blit(
104            layer = layer.target,
105            geometry = geometry,
106            colorTextureId = strokeTarget.textureId,
107            coverageTextureId = coverageTarget.textureId,
108            canvasToFbo = canvasToFbo,
109            width = canvasWidth,
110            height = canvasHeight,
111            opacity = opacity,
112            erase = erase,
113        )
114        layer.version++
115        val afterRaw = TileSnapshotCapture.capture(layer.target, dirtyBounds)
116        undoPipeline.enqueue(
117            undoManager = undoManager,
118            layerId = layer.id,
119            beforeRaw = beforeRaw,
120            afterRaw = afterRaw,
121        )
122        onTilesCommitted(layer, afterRaw)
123        return true
124    }
125
126    /** Clears one editable layer and records the full canvas as one undo transaction. */
127    fun clearLayer(
128        layer: PaintLayer,
129        canvasWidth: Int,
130        canvasHeight: Int,
131    ): Boolean {
132        GLCheck.checkOnGUIThread()
133        if (!layer.created || layer.isLocked) return false
134
135        val fullBounds = intArrayOf(0, 0, canvasWidth, canvasHeight)
136        logLargeUndoReadback(layer, fullBounds)
137        val beforeRaw = TileSnapshotCapture.capture(layer.target, fullBounds)
138        layer.clear()
139        layer.version++
140        undoPipeline.enqueue(
141            undoManager = undoManager,
142            layerId = layer.id,
143            beforeRaw = beforeRaw,
144            // Redo clears the target directly. Keeping a full transparent copy would
145            // double memory for a large document and can exhaust the Java heap.
146            afterRaw = emptyList(),
147            operation = UndoOperationType.CLEAR_LAYER,
148            tag = "clear_layer",
149        )
150        onLayerCleared(layer)
151        return true
152    }
153
154    private fun expandBoundsToTiles(
155        bounds: IntArray,
156        canvasWidth: Int,
157        canvasHeight: Int,
158    ) {
159        val tileSize = TileSnapshot.TILE_SIZE
160        bounds[0] = (bounds[0] / tileSize) * tileSize
161        bounds[1] = (bounds[1] / tileSize) * tileSize
162        bounds[2] = ((bounds[2] + tileSize - 1) / tileSize) * tileSize
163        bounds[3] = ((bounds[3] + tileSize - 1) / tileSize) * tileSize
164        bounds[0] = bounds[0].coerceIn(0, canvasWidth)
165        bounds[1] = bounds[1].coerceIn(0, canvasHeight)
166        bounds[2] = bounds[2].coerceIn(0, canvasWidth)
167        bounds[3] = bounds[3].coerceIn(0, canvasHeight)
168    }
169
170    private fun logLargeUndoReadback(
171        layer: PaintLayer,
172        bounds: IntArray,
173    ) {
174        if (!BuildConfig.DEBUG) return
175
176        val tileCount = TileSnapshotCapture.countTiles(layer.target, bounds)
177        if (tileCount > MAX_UNDO_TILES_PER_OPERATION) {
178            Log.w(
179                TAG,
180                "Large commit: tiles=$tileCount layer=${layer.id} " +
181                "bounds=${bounds.contentToString()}",
182            )
183        }
184    }

```

```
183     }
184 }
185
186 private companion object {
187     const val TAG = "StrokeCommitter"
188     const val MAX_UNDO_TILES_PER_OPERATION = 64
189 }
190 }
```

57. app/src/main/java/com/wetinknext/engine/core/ThumbnailCapture.kt

```
1 package com.wetinknext.engine.core
2
3 import com.wetinknext.engine.canvas.LayerStack
4 import com.wetinknext.engine.gl.GlCheck
5 import com.wetinknext.engine.thumbnail.ThumbnailRenderer
6
7 /** Captures only the composited canvas; Compose panels and system UI are excluded. */
8 class ThumbnailCapture {
9     data class Rgba(val width: Int, val height: Int, val pixels: ByteArray)
10     private val renderer = ThumbnailRenderer()
11
12     fun capture(layers: LayerStack): Rgba {
13         GlCheck.checkOnGhread()
14         require(layers.canvasWidth > 0 && layers.canvasHeight > 0) { "Cannot capture an empty canvas" }
15         val longestEdge = 384
16         val scale = longestEdge.toFloat() / maxOf(layers.canvasWidth, layers.canvasHeight).toFloat()
17         val captureWidth = (layers.canvasWidth * scale).toInt().coerceAtLeast(1)
18         val captureHeight = (layers.canvasHeight * scale).toInt().coerceAtLeast(1)
19         return Rgba(
20             captureWidth,
21             captureHeight,
22             renderer.renderProject(layers, captureWidth, captureHeight),
23         )
24     }
25
26     fun release() = renderer.release()
27 }
```

58. app/src/main/java/com/wetinknext/engine/core/UndoCompressionPipeline.kt

```

1 package com.wetinknext.engine.core
2
3 import android.util.Log
4 import com.wetinknext.BuildConfig
5 import com.wetinknext.engine.undo.DeflateTileCompressor
6 import com.wetinknext.engine.undo.RawTileSnapshot
7 import com.wetinknext.engine.undo.TileCompressor
8 import com.wetinknext.engine.undo.UndoEntry
9 import com.wetinknext.engine.undo.UndoManager
10 import com.wetinknext.engine.undo.UndoOperationType
11 import java.util.HashMap
12 import java.util.concurrent.ConcurrentLinkedQueue
13 import java.util.concurrent.ExecutorService
14 import java.util.concurrent.Executors
15 import java.util.concurrent.RejectedExecutionException
16 import java.util.concurrent.TimeUnit
17
18 /**
19  * Orders tile-compression work without ever touching GL from a worker thread.
20  *
21  * Call [enqueue], [process], [invalidate], and [shutdown] on the GL thread.
22  * The worker only converts [RawTileSnapshot] objects into compressed [UndoEntry]
23  * instances and requests another frame once a result is ready.
24  */
25 class UndoCompressionPipeline(
26     private val requestRender: () -> Unit,
27     private val compressor: TileCompressor = DeflateTileCompressor(),
28     private val maxPendingJobs: Int = DEFAULT_MAX_PENDING_JOBS,
29     private val executorFactory: () -> ExecutorService = { Executors.newSingleThreadExecutor() },
30 ) {
31     private var executor = executorFactory()
32     private val pendingResults = ConcurrentLinkedQueue<UndoJobResult>()
33     private val completedResults = HashMap<Long, UndoJobResult>()
34
35     private var nextSequence = 0L
36     private var nextSequenceToApply = 0L
37     private var epoch = 0L
38
39     var pendingCount: Int = 0
40     private set
41     var compressionFailureCount: Int = 0
42     private set
43     var staleResultCount: Int = 0
44     private set
45
46     /**
47      * Schedules one ordered undo transaction. The synchronous fallback still
48      * travels through the same result queue, so it cannot overtake older work.
49      */
50     fun enqueue(
51         undoManager: UndoManager,
52         layerId: Long,
53         beforeRaw: List<RawTileSnapshot>,
54         afterRaw: List<RawTileSnapshot>,
55         operation: UndoOperationType = UndoOperationType.TILE_EDIT,
56         tag: String = "stroke",
57     ) {
58         val jobEpoch = epoch
59         val sequence = allocateSequence()
60         pendingCount++
61
62         if (pendingCount >= maxPendingJobs) {
63             compressSynchronously(
64                 epoch = jobEpoch,
65                 sequence = sequence,
66                 layerId = layerId,
67                 beforeRaw = beforeRaw,
68                 afterRaw = afterRaw,
69                 operation = operation,
70                 tag = tag,
71             )
72             process(undoManager)
73             return
74         }
75
76         submit(
77             epoch = jobEpoch,
78             sequence = sequence,
79             layerId = layerId,
80             beforeRaw = beforeRaw,
81             afterRaw = afterRaw,
82             operation = operation,
83             tag = tag,
84         )
85     }
86
87     /** Applies completed work in commit order. Must be called on the GL thread. */
88     fun process(undoManager: UndoManager): Boolean {
89         var changed = false
90

```

```

91         while (true) {
92             val result = pendingResults.poll() ?: break
93             if (result.sequence < nextSequenceToApply) {
94                 discard(result)
95                 decrementPending()
96                 changed = true
97             } else {
98                 completedResults.put(result.sequence, result)?.let(::disposeReady)
99             }
100         }
101
102         while (true) {
103             val result = completedResults.remove(nextSequenceToApply) ?: break
104             apply(result, undoManager)
105             decrementPending()
106             nextSequenceToApply++
107             changed = true
108         }
109
110         return changed
111     }
112
113     /** Rejects compression results that belong to a document state that no longer exists. */
114     fun invalidate() {
115         epoch++
116         nextSequenceToApply = nextSequence
117         val discardedCount = completedResults.size
118         completedResults.values.forEach(::disposeReady)
119         completedResults.clear()
120         pendingCount = (pendingCount - discardedCount).coerceAtLeast(0)
121         staleResultCount += discardedCount
122     }
123
124     /** Reopens the worker after an EGL/context recreation. */
125     fun ensureRunning() {
126         if (executor.isShutdown) executor = executorFactory()
127     }
128
129     /** Releases worker-owned results without changing the caller's [UndoManager]. */
130     fun shutdown() {
131         executor.shutdownNow()
132         try {
133             executor.awaitTermination(SHUTDOWN_TIMEOUT_MS, TimeUnit.MILLISECONDS)
134         } catch (error: InterruptedException) {
135             Thread.currentThread().interrupt()
136         }
137
138         while (true) {
139             val result = pendingResults.poll() ?: break
140             disposeReady(result)
141         }
142         completedResults.values.forEach(::disposeReady)
143         completedResults.clear()
144         pendingCount = 0
145         nextSequenceToApply = nextSequence
146     }
147
148     private fun allocateSequence(): Long = nextSequence++
149
150     private fun submit(
151         epoch: Long,
152         sequence: Long,
153         layerId: Long,
154         beforeRaw: List<RawTileSnapshot>,
155         afterRaw: List<RawTileSnapshot>,
156         operation: UndoOperationType,
157         tag: String,
158     ) {
159         try {
160             executor.execute {
161                 val result = runCatching {
162                     readyResult(
163                         epoch = epoch,
164                         sequence = sequence,
165                         layerId = layerId,
166                         beforeRaw = beforeRaw,
167                         afterRaw = afterRaw,
168                         operation = operation,
169                         tag = tag,
170                     )
171                 }.getOrElse { error ->
172                     UndoJobResult.Failed(epoch = epoch, sequence = sequence, error = error)
173                 }
174                 pendingResults.add(result)
175                 requestRender()
176             }
177         } catch (error: RejectedExecutionException) {
178             pendingResults.add(
179                 UndoJobResult.Failed(epoch = epoch, sequence = sequence, error = error),
180             )
181             requestRender()
182         }

```

```

183     }
184
185     private fun compressSynchronously(
186         epoch: Long,
187         sequence: Long,
188         layerId: Long,
189         beforeRaw: List<RawTileSnapshot>,
190         afterRaw: List<RawTileSnapshot>,
191         operation: UndoOperationType,
192         tag: String,
193     ) {
194         val result = runCatching {
195             readyResult(
196                 epoch = epoch,
197                 sequence = sequence,
198                 layerId = layerId,
199                 beforeRaw = beforeRaw,
200                 afterRaw = afterRaw,
201                 operation = operation,
202                 tag = tag,
203             )
204         }.getOrElse { error ->
205             UndoJobResult.Failed(epoch = epoch, sequence = sequence, error = error)
206         }
207         pendingResults.add(result)
208     }
209
210     private fun readyResult(
211         epoch: Long,
212         sequence: Long,
213         layerId: Long,
214         beforeRaw: List<RawTileSnapshot>,
215         afterRaw: List<RawTileSnapshot>,
216         operation: UndoOperationType,
217         tag: String,
218     ): UndoJobResult.Ready = UndoJobResult.Ready(
219         epoch = epoch,
220         sequence = sequence,
221         entry = UndoEntry(
222             layerId = layerId,
223             beforeTiles = beforeRaw.map { it.compress(compressor) },
224             afterTiles = afterRaw.map { it.compress(compressor) },
225             operation = operation,
226             tag = tag,
227         ),
228     )
229
230     private fun apply(result: UndoJobResult, undoManager: UndoManager) {
231         when (result) {
232             is UndoJobResult.Ready -> {
233                 if (isUndoResultCurrent(result.epoch, epoch)) {
234                     undoManager.push(result.entry)
235                 } else {
236                     result.entry.dispose()
237                     staleResultCount++
238                 }
239             }
240             is UndoJobResult.Failed -> {
241                 compressionFailureCount++
242                 if (BuildConfig.DEBUG) {
243                     Log.e(TAG, "Undo compression failed", result.error)
244                 }
245             }
246         }
247     }
248
249     private fun discard(result: UndoJobResult) {
250         disposeReady(result)
251         staleResultCount++
252     }
253
254     private fun disposeReady(result: UndoJobResult) {
255         if (result is UndoJobResult.Ready) result.entry.dispose()
256     }
257
258     private fun decrementPending() {
259         pendingCount = (pendingCount - 1).coerceAtLeast(0)
260     }
261
262     private companion object {
263         const val DEFAULT_MAX_PENDING_JOBS = 8
264         const val SHUTDOWN_TIMEOUT_MS = 100L
265         const val TAG = "TileUndo"
266     }
267 }
268 }

```


59. app/src/main/java/com/wetinknext/engine/core/UndoHistory.kt

```
1 package com.wetinknext.engine.core
2
3 /** Pure epoch contract used to reject undo results from a previous document state. */
4 fun isUndoResultCurrent(
5     resultEpoch: Long,
6     currentEpoch: Long,
7 ): Boolean = resultEpoch == currentEpoch
```

60. app/src/main/java/com/wetinknext/engine/core/UndoJobResult.kt

```
1 package com.wetinknext.engine.core
2
3 import com.wetinknext.engine.undo.UndoEntry
4
5 /** Terminal outcome of one tile-compression task. */
6 sealed interface UndoJobResult {
7     val epoch: Long
8     val sequence: Long
9
10     data class Ready(
11         override val epoch: Long,
12         override val sequence: Long,
13         val entry: UndoEntry,
14     ) : UndoJobResult
15
16     data class Failed(
17         override val epoch: Long,
18         override val sequence: Long,
19         val error: Throwable,
20     ) : UndoJobResult
21 }
```

61. app/src/main/java/com/wetinknext/engine/core/ViewTransform.kt

```

1 package com.wetinknext.engine.core
2
3 import kotlin.math.abs
4 import kotlin.math.cos
5 import kotlin.math.sin
6
7 /** Canonical canvas-to-view-local-screen transformation. */
8 data class ViewTransform(
9     val translateX: Float = 0f,
10    val translateY: Float = 0f,
11    val scale: Float = 1f,
12    val rotationRad: Float = 0f,
13    val flipX: Boolean = false,
14 ) {
15     private val flipSign: Float
16         get() = if (flipX) -1f else 1f
17
18     val m00: Float get() = cos(rotationRad) * scale * flipSign
19     val m01: Float get() = -sin(rotationRad) * scale
20     val m10: Float get() = sin(rotationRad) * scale * flipSign
21     val m11: Float get() = cos(rotationRad) * scale
22
23     fun canvasToScreen(canvasX: Float, canvasY: Float, out: FloatArray) {
24         require(out.size >= 2)
25         out[0] = m00 * canvasX + m01 * canvasY + translateX
26         out[1] = m10 * canvasX + m11 * canvasY + translateY
27     }
28
29     fun screenToCanvas(screenX: Float, screenY: Float, out: FloatArray) {
30         require(out.size >= 2)
31         val determinant = m00 * m11 - m01 * m10
32         if (abs(determinant) < 1e-8f) {
33             out[0] = 0f
34             out[1] = 0f
35             return
36         }
37         val inverseDeterminant = 1f / determinant
38         val dx = screenX - translateX
39         val dy = screenY - translateY
40         out[0] = (m11 * dx - m01 * dy) * inverseDeterminant
41         out[1] = (-m10 * dx + m00 * dy) * inverseDeterminant
42     }
43
44     fun zoomAround(anchorX: Float, anchorY: Float, newScale: Float): ViewTransform {
45         val safeScale = newScale.coerceIn(MIN_SCALE, MAX_SCALE)
46         val factor = safeScale / scale
47         return copy(
48             scale = safeScale,
49             translateX = anchorX - (anchorX - translateX) * factor,
50             translateY = anchorY - (anchorY - translateY) * factor,
51         )
52     }
53
54     fun rotateAround(anchorX: Float, anchorY: Float, deltaRad: Float): ViewTransform {
55         val c = cos(deltaRad)
56         val s = sin(deltaRad)
57         val dx = translateX - anchorX
58         val dy = translateY - anchorY
59         return copy(
60             rotationRad = rotationRad + deltaRad,
61             translateX = anchorX + dx * c - dy * s,
62             translateY = anchorY + dx * s + dy * c,
63         )
64     }
65
66     /** Applies one screen-space navigation update around a shared gesture anchor. */
67     fun applyGestureDelta(
68         panX: Float,
69         panY: Float,
70         anchorX: Float,
71         anchorY: Float,
72         zoomFactor: Float,
73         rotationDelta: Float,
74     ): ViewTransform {
75         val translated = copy(
76             translateX = translateX + panX,
77             translateY = translateY + panY,
78         )
79         val zoomed = translated.zoomAround(
80             anchorX = anchorX,
81             anchorY = anchorY,
82             newScale = scale * zoomFactor,
83         )
84         return zoomed.rotateAround(anchorX, anchorY, rotationDelta)
85     }
86
87     /** Builds a column-major matrix for canvas to OpenGL clip coordinates. */
88     fun buildCanvasToClip(viewWidth: Float, viewHeight: Float, out: FloatArray) {
89         require(out.size >= 16)
90         require(viewWidth > 0f)

```

```

91         require(viewHeight > 0f)
92         val sx = 2f / viewWidth
93         val sy = -2f / viewHeight
94         out[0] = m00 * sx; out[1] = m10 * sy; out[2] = 0f; out[3] = 0f
95         out[4] = m01 * sx; out[5] = m11 * sy; out[6] = 0f; out[7] = 0f
96         out[8] = 0f; out[9] = 0f; out[10] = 1f; out[11] = 0f
97         out[12] = translateX * sx - 1f; out[13] = translateY * sy + 1f
98         out[14] = 0f; out[15] = 1f
99     }
100
101     companion object {
102         const val MIN_SCALE = 0.02f
103         const val MAX_SCALE = 64f
104
105         fun buildCanvasToFbo(canvasWidth: Float, canvasHeight: Float, out: FloatArray) {
106             require(out.size >= 16); require(canvasWidth > 0f); require(canvasHeight > 0f)
107             out[0]=2f/canvasWidth;out[1]=0f;out[2]=0f;out[3]=0f;out[4]=0f;out[5]=2f/canvasHeight;out[6]=0f;out[7]=0f;out[
8]=0f;out[9]=0f;out[10]=1f;out[11]=0f;out[12]=-1f;out[13]=-1f;out[14]=0f;out[15]=1f
108         }
109     }
110 }

```

62. app/src/main/java/com/wetinknext/engine/gl/CanvasGeometry.kt

```
1 package com.wetinknext.engine.gl
2
3 import android.opengl.GLES30
4 import java.nio.ByteBuffer
5 import java.nio.ByteOrder
6
7 /** A document-sized quad; GL resources are owned by the render thread. */
8 class CanvasGeometry {
9     var vaoId = 0
10     private set
11     private var vboId = 0
12
13     fun create(width: Int, height: Int) {
14         release()
15         val vertices = floatArrayOf(0f, 0f, width.toFloat(), 0f, 0f, height.toFloat(), width.toFloat(), height.toFloat())
16         val data = ByteBuffer.allocateDirect(vertices.size * Float.SIZE_BYTES).order(ByteOrder.nativeOrder()).asFloatBuffer()
17         data.put(vertices).position(0)
18         val ids = IntArray(1)
19         GLES30.glGenVertexArrays(1, ids, 0); vaoId = ids[0]
20         GLES30.glGenBuffers(1, ids, 0); vboId = ids[0]
21         GLES30.glBindVertexArray(vaoId); GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, vboId)
22         GLES30.glBufferData(GLES30.GL_ARRAY_BUFFER, vertices.size * Float.SIZE_BYTES, data, GLES30.GL_STATIC_DRAW)
23         GLES30.glEnableVertexAttribArray(0); GLES30.glVertexAttribPointer(0, 2, GLES30.GL_FLOAT, false, 0, 0)
24         GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0); GLES30.glBindVertexArray(0)
25     }
26
27     fun draw() {
28         check(vaoId != 0)
29         GLES30.glBindVertexArray(vaoId); GLES30.glDrawArrays(GLES30.GL_TRIANGLE_STRIP, 0, 4); GLES30.glBindVertexArray(0)
30     }
31
32     fun release() {
33         if (vboId != 0) GLES30.glDeleteBuffers(1, intArrayOf(vboId), 0)
34         if (vaoId != 0) GLES30.glDeleteVertexArrays(1, intArrayOf(vaoId), 0)
35         vaoId = 0; vboId = 0
36     }
37 }
```

63. app/src/main/java/com/wetinknext/engine/gl/GeometryCache.kt

```
1 package com.wetinknext.engine.gl
2
3 import android.opengl.GLES30
4 import java.nio.ByteBuffer
5 import java.nio.ByteOrder
6
7 /** A single cached fullscreen triangle for future present passes. */
8 class GeometryCache {
9     private var vaoId = 0
10    private var vboId = 0
11    fun create() {
12        if (vaoId != 0) return
13        val vertices = floatArrayOf(-1f, -1f, 3f, -1f, -1f, 3f)
14        val data = ByteBuffer.allocateDirect(vertices.size * Float.SIZE_BYTES).order(ByteOrder.nativeOrder()).asFloatBuffer()
15        data.put(vertices).position(0)
16        val ids = IntArray(1); GLES30.glGenVertexArrays(1, ids, 0); vaoId = ids[0]
17        GLES30.glGenBuffers(1, ids, 0); vboId = ids[0]
18        GLES30.glBindVertexArray(vaoId); GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, vboId)
19        GLES30.glBufferData(GLES30.GL_ARRAY_BUFFER, vertices.size * Float.SIZE_BYTES, data, GLES30.GL_STATIC_DRAW)
20        GLES30.glEnableVertexAttribArray(0); GLES30.glVertexAttribPointer(0, 2, GLES30.GL_FLOAT, false, 0, 0)
21        GLES30.glBindBuffer(GLES30.GL_ARRAY_BUFFER, 0); GLES30.glBindVertexArray(0)
22    }
23    fun drawFullscreenTriangle() { check(vaoId != 0); GLES30.glBindVertexArray(vaoId); GLES30.glDrawArrays(GLES30.
GL_TRIANGLES, 0, 3); GLES30.glBindVertexArray(0) }
24    fun release() { if (vboId != 0) GLES30.glDeleteBuffers(1, intArrayOf(vboId), 0); if (vaoId != 0) GLES30.
glDeleteVertexArrays(1, intArrayOf(vaoId), 0); vboId = 0; vaoId = 0 }
25 }
```

64. app/src/main/java/com/wetinknext/engine/gl/GLCaps.kt

```
1 package com.wetinknext.engine.gl
2
3 import android.opengl.GLES30
4
5 /** Capabilities queried only after a GLES 3 context is current. */
6 data class GLCaps(
7     val renderer: String,
8     val version: String,
9     val supportsHalfFloatColorBuffer: Boolean,
10 ) {
11     companion object {
12         fun query(): GLCaps {
13             val extensions = GLES30.glGetString(GLES30.GL_EXTENSIONS).orEmpty()
14             val declared = extensions.contains("EXT_color_buffer_half_float") ||
15                 extensions.contains("EXT_color_buffer_float")
16             // Extension string сам по себе не доказательство: проверяем реальный FBO 4x4.
17             val supported = declared && RenderTarget().probeHalfFloatColorBuffer()
18             return GLCaps(
19                 renderer = GLES30.glGetString(GLES30.GL_RENDERER).orEmpty(),
20                 version = GLES30.glGetString(GLES30.GL_VERSION).orEmpty(),
21                 supportsHalfFloatColorBuffer = supported,
22             )
23         }
24     }
25 }
```

65. app/src/main/java/com/wetinknext/engine/gl/GLCheck.kt

```
1 package com.wetinknext.engine.gl
2
3 import android.opengl.GLES30
4
5 /** GL error checks intended for setup boundaries, never the render hot path. */
6 object GLCheck {
7     @Volatile
8     private var glThread: Thread? = null
9
10    fun setGLThread(thread: Thread) {
11        glThread = thread
12    }
13
14    fun checkOnGLThread() {
15        val current = Thread.currentThread()
16        val expected = glThread
17        check(current === expected) {
18            "GL resource accessed outside GLSurfaceView render thread: current=$current, expected=$expected"
19        }
20    }
21
22    fun noError(label: String) {
23        val error = GLES30.glGetError()
24        check(error == GLES30.GL_NO_ERROR) { "$label: GL error 0x${error.toString(16)}" }
25    }
26
27    fun framebufferComplete(label: String) {
28        val status = GLES30.glCheckFramebufferStatus(GLES30.GL_FRAMEBUFFER)
29        check(status == GLES30.GL_FRAMEBUFFER_COMPLETE) {
30            "$label: framebuffer incomplete (0x${status.toString(16)})"
31        }
32    }
33 }
```


66. app/src/main/java/com/wetinknext/engine/gl/GLProgram.kt

```
1 package com.wetinknext.engine.gl
2
3 import android.opengl.GLES30
4
5 /** Linked GLSL program. Construction and release must run on the GL thread. */
6 class GLProgram(vertexSource: String, fragmentSource: String) {
7     val id: Int = GLES30.glCreateProgram().also { program ->
8         check(program != 0) { "Unable to create GL program" }
9         val vertex = compile(GLES30.GL_VERTEX_SHADER, vertexSource)
10        val fragment = compile(GLES30.GL_FRAGMENT_SHADER, fragmentSource)
11        GLES30.glAttachShader(program, vertex); GLES30.glAttachShader(program, fragment); GLES30.glLinkProgram(program)
12        val linked = IntArray(1); GLES30.glGetProgramiv(program, GLES30.GL_LINK_STATUS, linked, 0)
13        GLES30.glDeleteShader(vertex); GLES30.glDeleteShader(fragment)
14        check(linked[0] == GLES30.GL_TRUE) { "Program link failed: ${GLES30.glGetProgramInfoLog(program)}" }
15    }
16    fun use() = GLES30.glUseProgram(id)
17    fun release() = GLES30.glDeleteProgram(id)
18
19    private fun compile(type: Int, source: String): Int = GLES30.glCreateShader(type).also { shader ->
20        check(shader != 0) { "Unable to create shader" }
21        GLES30.glShaderSource(shader, source); GLES30.glCompileShader(shader)
22        val compiled = IntArray(1); GLES30.glGetShaderiv(shader, GLES30.GL_COMPILE_STATUS, compiled, 0)
23        check(compiled[0] == GLES30.GL_TRUE) { "Shader compile failed: ${GLES30.glGetShaderInfoLog(shader)}" }
24    }
25 }
```

67. app/src/main/java/com/wetinknext/engine/gl/RenderTarget.kt

```

1  package com.wetinknext.engine.gl
2
3  import android.opengl.GLES30
4
5  /** Texture-backed FBO with RGBA16F probing and a guaranteed RGBA8 fallback. */
6  class RenderTarget {
7      var framebufferId: Int = 0
8      private set
9      var textureId: Int = 0
10     private set
11     var width: Int = 0
12     private set
13     var height: Int = 0
14     private set
15     var usesHalfFloat: Boolean = false
16     private set
17
18     fun create(width: Int, height: Int, preferHalfFloat: Boolean) {
19         GLCheck.checkOnGLThread()
20         require(width > 0 && height > 0)
21         release()
22         if (preferHalfFloat && createInternal(width, height, true)) return
23         check(createInternal(width, height, false)) { "RGBA8 render target creation failed" }
24     }
25
26     /** A 4x4 completeness probe used before allocating a document-sized target. */
27     fun probeHalfFloatColorBuffer(): Boolean {
28         release()
29         val result = createInternal(4, 4, true)
30         release()
31         return result
32     }
33
34     fun bind() {
35         check(framebufferId != 0) { "RenderTarget is not created" }
36         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, framebufferId)
37     }
38
39     fun clear(red: Float, green: Float, blue: Float, alpha: Float) {
40         bind()
41         // Clearing is constrained by the current viewport. Always restore the
42         // offscreen target's extent, not the last screen-sized present viewport.
43         GLES30.glViewport(0, 0, width, height)
44         GLES30.glDisable(GLES30.GL_SCISSOR_TEST)
45         GLES30.glDisable(GLES30.GL_BLEND)
46         GLES30.glColorMask(true, true, true, true)
47         GLES30.glClearColor(red, green, blue, alpha)
48         GLES30.glClear(GLES30.GL_COLOR_BUFFER_BIT)
49         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
50     }
51
52     fun release() {
53         GLCheck.checkOnGLThread()
54         if (framebufferId != 0) GLES30.glDeleteFramebuffers(1, intArrayOf(framebufferId), 0)
55         if (textureId != 0) GLES30.glDeleteTextures(1, intArrayOf(textureId), 0)
56         framebufferId = 0; textureId = 0; width = 0; height = 0; usesHalfFloat = false
57     }
58
59     private fun createInternal(targetWidth: Int, targetHeight: Int, halfFloat: Boolean): Boolean {
60         val textures = IntArray(1)
61         val framebuffers = IntArray(1)
62         GLES30.glGenTextures(1, textures, 0)
63         GLES30.glGenFramebuffers(1, framebuffers, 0)
64         val texture = textures[0]
65         val framebuffer = framebuffers[0]
66         if (texture == 0 || framebuffer == 0) return false
67         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, texture)
68         GLES30.glTexParameteri(GLES30.GL_TEXTURE_2D, GLES30.GL_TEXTURE_MIN_FILTER, GLES30.GL_LINEAR)
69         GLES30.glTexParameteri(GLES30.GL_TEXTURE_2D, GLES30.GL_TEXTURE_MAG_FILTER, GLES30.GL_LINEAR)
70         GLES30.glTexParameteri(GLES30.GL_TEXTURE_2D, GLES30.GL_TEXTURE_WRAP_S, GLES30.GL_CLAMP_TO_EDGE)
71         GLES30.glTexParameteri(GLES30.GL_TEXTURE_2D, GLES30.GL_TEXTURE_WRAP_T, GLES30.GL_CLAMP_TO_EDGE)
72         GLES30.glTexImage2D(GLES30.GL_TEXTURE_2D, 0, if (halfFloat) GLES30.GL_RGBA16F else GLES30.GL_RGBA8,
73             targetWidth, targetHeight, 0, GLES30.GL_RGBA, if (halfFloat) GLES30.GL_HALF_FLOAT else GLES30.GL_UNSIGNED_BYTE,
74             null)
75         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, framebuffer)
76         GLES30.glFramebufferTexture2D(GLES30.GL_FRAMEBUFFER, GLES30.GL_COLOR_ATTACHMENT0, GLES30.GL_TEXTURE_2D, texture, 0)
77         val complete = GLES30.glCheckFramebufferStatus(GLES30.GL_FRAMEBUFFER) == GLES30.GL_FRAMEBUFFER_COMPLETE
78         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
79         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
80         if (!complete) {
81             GLES30.glDeleteFramebuffers(1, framebuffers, 0); GLES30.glDeleteTextures(1, textures, 0)
82             return false
83         }
84         framebufferId = framebuffer; textureId = texture; width = targetWidth; height = targetHeight; usesHalfFloat =
85         halfFloat
86     }
87 }

```

68. app/src/main/java/com/wetinknext/engine/gl/ShaderLib.kt

```

1 package com.wetinknext.engine.gl
2
3 object ShaderLib {
4     const val compositorVertex = ""#version 300 es
5         layout(location=0) in vec2 aPosition;uniform mat4 uCanvasToClip;uniform vec2 uCanvasSize;out vec2 vUv;void main(){
6         vUv=aPosition/uCanvasSize;gl_Position=uCanvasToClip*vec4(aPosition,0.,1.);}""
7     const val compositorFragment = ""#version 300 es
8         precision highp float;
9
10        in vec2 vUv;
11        uniform sampler2D uLayerTex;
12        uniform sampler2D uStrokeTex;
13        uniform int uStrokeActive;
14        uniform int uStrokeErase;
15        uniform float uOpacity;
16        uniform float uStrokeOpacity;
17
18        out vec4 fragColor;
19
20        void main() {
21            vec4 layer = texture(uLayerTex, vUv);
22
23            if (uStrokeActive == 1) {
24                vec4 stroke = texture(uStrokeTex, vUv) * uStrokeOpacity;
25
26                // Both textures contain premultiplied linear RGBA.
27                if (uStrokeErase == 1) {
28                    layer *= (1.0 - stroke.a);
29                } else {
30                    layer = stroke + layer * (1.0 - stroke.a);
31                }
32            }
33
34            float alpha = layer.a * uOpacity;
35
36            // Layer opacity is applied to premultiplied linear RGB as well.
37            fragColor = vec4(layer.rgb * uOpacity, alpha);
38        }
39    ""
40    const val linearPresentFragment = ""#version 300 es
41        precision highp float;
42
43        in vec2 vUv;
44        uniform sampler2D uTexture;
45        out vec4 fragColor;
46
47        vec3 linearToSrgb(vec3 value) {
48            vec3 c = clamp(value, 0.0, 1.0);
49            vec3 low = c * 12.92;
50            vec3 high = 1.055 * pow(c, vec3(1.0 / 2.4)) - 0.055;
51            return mix(low, high, step(vec3(0.0031308), c));
52        }
53
54        vec3 unpremultiply(vec4 value) {
55            return value.a <= 0.0001 ? vec3(0.0) : value.rgb / value.a;
56        }
57
58        void main() {
59            vec4 color = texture(uTexture, vUv);
60            vec3 srgb = linearToSrgb(unpremultiply(color));
61            fragColor = vec4(srgb * color.a, color.a);
62        }
63    ""
64    const val linearCopyFragment = ""#version 300 es
65        precision highp float;
66
67        in vec2 vUv;
68        uniform sampler2D uTexture;
69        out vec4 fragColor;
70
71        void main() {
72            fragColor = texture(uTexture, vUv);
73        }
74    ""
75    const val cachedStrokePresentFragment = ""#version 300 es
76        precision highp float;
77
78        in vec2 vUv;
79        uniform sampler2D uLowerTex;
80        uniform sampler2D uActiveLayerTex;
81        uniform sampler2D uStrokeTex;
82        uniform int uStrokeActive;
83        uniform int uStrokeErase;
84        uniform float uLayerOpacity;
85        uniform float uStrokeOpacity;
86        out vec4 fragColor;
87
88        vec3 linearToSrgb(vec3 value) {
89            vec3 c = clamp(value, 0.0, 1.0);
90            vec3 low = c * 12.92;

```

```

90         vec3 high = 1.055 * pow(c, vec3(1.0 / 2.4)) - 0.055;
91         return mix(low, high, step(vec3(0.0031308), c));
92     }
93
94     void main() {
95         vec4 lower = texture(uLowerTex, vUv);
96         vec4 activeLayer = texture(uActiveLayerTex, vUv);
97
98         if (uStrokeActive == 1) {
99             vec4 stroke = texture(uStrokeTex, vUv) * uStrokeOpacity;
100             activeLayer = uStrokeErase == 1
101                 ? activeLayer * (1.0 - stroke.a)
102                 : stroke + activeLayer * (1.0 - stroke.a);
103         }
104
105         activeLayer *= uLayerOpacity;
106         vec4 document = activeLayer + lower * (1.0 - activeLayer.a);
107         vec3 straightLinear = document.a <= 0.0001
108             ? vec3(0.0)
109             : document.rgb / document.a;
110         vec3 srgb = linearToSrgb(straightLinear);
111         fragColor = vec4(srgb * document.a, document.a);
112     }
113
114     ""
115     const val dabVertex = ""#version 300 es
116     layout(location = 0) in vec2 aCorner;
117     layout(location = 1) in vec4 iDab0;
118     layout(location = 2) in vec2 iDab1;
119     uniform mat4 uCanvasToClip;
120     uniform vec2 uCanvasSize;
121     out vec2 vLocal;
122     out vec2 vCanvasUv;
123     flat out float vCoverage;
124     flat out float vFlow;
125     void main(){
126         float c=cos(iDab0.w), s=sin(iDab0.w);
127         vec2 r=vec2(c*aCorner.x-s*aCorner.y,s*aCorner.x+c*aCorner.y);
128         vLocal=aCorner;
129         vCoverage=iDab1.x;
130         vFlow=iDab1.y;
131         vec2 p = iDab0.xy+r*iDab0.z;
132         vCanvasUv = p / uCanvasSize;
133         gl_Position=uCanvasToClip*vec4(p,0.,1.);
134     }
135
136     ""
137     const val dabFragment = ""#version 300 es
138     precision highp float;
139     in vec2 vLocal;
140     in vec2 vCanvasUv;
141     flat in float vCoverage;
142     flat in float vFlow;
143     uniform vec3 uColorLinear;
144     uniform sampler2D uGrainTex;
145     uniform int uGrainActive;
146     uniform float uGrainScale;
147     uniform int uGrainCanvasLocked;
148     uniform float uTextureDepth;
149     uniform float uTextureContrast;
150     uniform float uStrokeOpacity;
151     uniform int uCoverageOnly;
152     uniform sampler2D uShapeTex;
153     uniform int uShapeActive;
154     uniform int uReverseShape;
155     uniform int uRgbToAlpha;
156     out vec4 fragColor;
157     float luminance(vec3 color) {
158         return dot(color, vec3(0.299, 0.587, 0.114));
159     }
160     float applyTextureLevels(float value, float contrast, float depth) {
161         float adjusted = clamp((value - 0.5) * contrast + 0.5, 0.0, 1.0);
162         return mix(1.0 - depth, 1.0, adjusted);
163     }
164     void main(){
165         float r=length(vLocal);
166         float aa=max(fwidth(r),.001);
167         float cov=1.-smoothstep(1.-aa,1.+aa,r);
168         if (cov <= 0.0) discard;
169
170         float shapeMask = 1.0;
171         if (uShapeActive == 1) {
172             vec2 shapeUv = vLocal * 0.5 + 0.5;
173             vec4 shapeColor = texture(uShapeTex, shapeUv);
174             shapeMask = uRgbToAlpha == 1
175                 ? dot(shapeColor.rgb, vec3(0.299, 0.587, 0.114))
176                 : shapeColor.a;
177             if (uReverseShape == 1) shapeMask = 1.0 - shapeMask;
178         }
179
180         float grainFactor = 1.0;
181         if (uGrainActive == 1) {
182             vec2 uv = uGrainCanvasLocked == 1
183                 ? vCanvasUv * max(uGrainScale, 0.0001)

```

```

182         : (vLocal * 0.5 + 0.5) * max(uGrainScale, 0.0001);
183         vec4 grainColor = texture(uGrainTex, uv);
184         grainFactor = applyTextureLevels(
185             luminance(grainColor.rgb), uTextureContrast, uTextureDepth
186         );
187     }
188
189     float coverage = vCoverage * vFlow * cov * shapeMask * grainFactor;
190     if (uCoverageOnly == 1) {
191         fragColor = vec4(0.0, 0.0, 0.0, coverage);
192         return;
193     }
194     float a = coverage * uStrokeOpacity;
195     fragColor = vec4(uColorLinear * a, a);
196 }
197
198 const val nonBuildupStrokeFragment = ""#version 300 es
199 precision highp float;
200
201 in vec2 vUv;
202 uniform sampler2D uColorTex;
203 uniform sampler2D uCoverageTex;
204 uniform float uOpacity;
205 out vec4 fragColor;
206
207 void main() {
208     vec4 color = texture(uColorTex, vUv);
209     float coverage = texture(uCoverageTex, vUv).a;
210     float alpha = coverage * uOpacity;
211     vec3 straightColor = color.a > 0.0001
212         ? color.rgb / color.a
213         : vec3(0.0);
214     fragColor = vec4(straightColor * alpha, alpha);
215 }
216
217 const val strokeCompositeFragment = ""#version 300 es
218 precision highp float; in vec2 vUv; uniform sampler2D uCanvasTex; uniform sampler2D uStrokeTex; uniform int
219 uStrokeActive; out vec4 fragColor;
220     vec3 toSrgb(vec3 c){c=clamp(c,0.,1.);return mix(c*12.92,1.055*pow(c,vec3(1./2.4))-0.055,step(vec3(.0031308),c));}
221     vec3 unpremul(vec4 c){return c.a<=.0001?vec3(0.):c.rgb/c.a;}
222     void main(){vec4 c=texture(uCanvasTex,vUv);vec4 s=texture(uStrokeTex,vUv);float a=uStrokeActive==1?s.a+c.a*(1.-s.a):c
223     a;vec3 rgb=uStrokeActive==1&&a>.0001?(unpremul(s)*s.a+unpremul(c)*c.a*(1.-s.a))/a:unpremul(c);fragColor=vec4(toSrgb(rgb),1.);}
224
225 const val canvasPresentVertex = ""#version 300 es
226 layout(location = 0) in vec2 aPosition;
227 uniform mat4 uCanvasToClip;
228 uniform vec2 uCanvasSize;
229 out vec2 vUv;
230 void main() {
231     vUv = aPosition / uCanvasSize;
232     gl_Position = uCanvasToClip * vec4(aPosition, 0.0, 1.0);
233 }
234
235 const val presentFragment = ""#version 300 es
236 precision highp float;
237 in vec2 vUv;
238 uniform sampler2D uTexture;
239 out vec4 fragColor;
240 void main() { fragColor = texture(uTexture, vUv); }
241
242 const val fullscreenVertex = ""#version 300 es
243 layout(location = 0) in vec2 aPosition;
244 out vec2 vUv;
245 void main() { vUv = aPosition * 0.5 + 0.5; gl_Position = vec4(aPosition, 0.0, 1.0); }
246
247 const val canvasBackdropFragment = ""#version 300 es
248 precision highp float;
249
250 uniform vec3 uBackgroundColor;
251 uniform vec3 uGridColor;
252 uniform int uMode;
253 out vec4 fragColor;
254
255 void main() {
256     const float cellPx = 28.0;
257     vec2 pixel = gl_FragCoord.xy;
258     vec3 color = uBackgroundColor;
259
260     if (uMode == 1) {
261         vec2 insideCell = mod(pixel, cellPx);
262         bool isGridLine = insideCell.x < 1.0 || insideCell.y < 1.0;
263         color = isGridLine ? uGridColor : uBackgroundColor;
264     } else {
265         vec2 cell = floor(pixel / cellPx);
266         float parity = mod(cell.x + cell.y, 2.0);
267         color = parity < 1.0 ? uGridColor : uBackgroundColor;
268     }
269     fragColor = vec4(color, 1.0);
270 }
271
272 const val solidFragment = ""#version 300 es

```

```

272     precision highp float;
273     in vec2 vUv;
274     out vec4 fragColor;
275     void main() { fragColor = vec4(vUv, 0.0, 1.0); }
276     ""
277     const val ribbonVertex = ""#version 300 es
278         layout(location=0) in vec2 aPos; layout(location=1) in float aCoverage; layout(location=2) in float aAlpha;
279         uniform mat4 uCanvasToClip; out float vCoverage; out float vAlpha;
280         void main(){vCoverage=aCoverage;vAlpha=aAlpha;gl_Position=uCanvasToClip*vec4(aPos,0.,1.);}
281     ""
282     const val ribbonFragment = ""#version 300 es
283         precision highp float; in float vCoverage; in float vAlpha; uniform vec3 uColorLinear; uniform float uFlow;
284         uniform int uAntiAliasLevel; uniform int uNoAntialias; out vec4 fragColor;
285         void main(){float cov=vCoverage;if(uNoAntialias==1||uAntiAliasLevel==0)cov=step(.5,cov);else{float
e=uAntiAliasLevel==1?1.35:uAntiAliasLevel==2?1.5:1.7;cov=sqrt(1-cov*cov);float a=vAlpha*cov*uFlow;fragColor=vec4(
uColorLinear*a,a,a);}
286     ""
287
288     /**
289     * Один сегмент штриха = капсула (round cone): два круга с линейной интерполяцией радиуса.
290     * Вершинный шейдер строит только AABB сегмента, форма считается во фрагменте.
291     */
292     const val capsuleVertex = ""#version 300 es
293         layout(location = 0) in vec2 aCorner; // -1..1, TRIANGLE_STRIP из 4 вершин
294         layout(location = 1) in vec4 iA; // x, y, radius, coverage (начало сегмента)
295         layout(location = 2) in vec4 iB; // x, y, radius, coverage (конец сегмента)
296         uniform mat4 uCanvasToClip;
297         uniform vec2 uCanvasSize;
298         out vec2 vPos;
299         out vec2 vCanvasUv;
300         flat out vec4 vA;
301         flat out vec4 vB;
302         void main() {
303             // Запас 2 px на AA-переход, иначе край обрежется по границе квада.
304             vec2 lo = min(iA.xy - iA.z, iB.xy - iB.z) - 2.0;
305             vec2 hi = max(iA.xy + iA.z, iB.xy + iB.z) + 2.0;
306             vec2 p = mix(lo, hi, aCorner * 0.5 + 0.5);
307             vPos = p;
308             vCanvasUv = p / uCanvasSize;
309             vA = iA;
310             vB = iB;
311             gl_Position = uCanvasToClip * vec4(p, 0.0, 1.0);
312         }
313     ""
314
315     /**
316     * Аналитическое покрытие: нет капков, джойнов, miter и AA-юбки как отдельных сущностей.
317     * Выход строго premultiplied linear: rgb = color * a, a = cov.
318     * Рисовать premultiplied source-over blending:
319     * GL_FUNC_ADD + GL_ONE, GL_ONE_MINUS_SRC_ALPHA.
320     */
321     const val capsuleFragment = ""#version 300 es
322         precision highp float;
323         in vec2 vPos;
324         in vec2 vCanvasUv;
325         flat in vec4 vA;
326         flat in vec4 vB;
327         uniform vec3 uColorLinear;
328         uniform sampler2D uGrainTex;
329         uniform int uGrainActive;
330         uniform float uGrainScale;
331         uniform int uGrainCanvasLocked;
332         uniform float uTextureDepth;
333         uniform float uTextureContrast;
334         uniform float uFlow;
335         out vec4 fragColor;
336
337         float sdRoundCone(vec2 p, vec2 a, vec2 b, float r1, float r2) {
338             vec2 ba = b - a;
339             float l2 = dot(ba, ba);
340             float rr = r1 - r2;
341
342             // Guard 1: вырожденный сегмент (тап, дубль сэмпла) -> обычный круг.
343             if (l2 < 1e-6) return length(p - a) - max(r1, r2);
344             // Guard 2: один круг поглощает другой (скачок давления на коротком шаге).
345             // Без этого a2 < 0 -> sqrt(отрицательного) -> NaN -> чёрные клинья.
346             if (rr * rr >= l2) return (r1 > r2) ? (length(p - a) - r1) : (length(p - b) - r2);
347
348             float a2 = l2 - rr * rr;
349             float il2 = 1.0 / l2;
350             vec2 pa = p - a;
351             float y = dot(pa, ba);
352             float z = y - l2;
353             vec2 xv = pa * l2 - ba * y;
354             float x2 = dot(xv, xv);
355             float y2 = y * y * l2;
356             float z2 = z * z * l2;
357             float k = sign(rr) * rr * rr * x2;
358
359             if (sign(z) * a2 * z2 > k) return sqrt(x2 + z2) * il2 - r2; // круглый конец у В
360             if (sign(y) * a2 * y2 < k) return sqrt(x2 + y2) * il2 - r1; // круглый конец у А
361             return (sqrt(x2 * a2 * il2) + y * rr) * il2 - r1; // касательная боковина

```

```

362     }
363
364     void main() {
365         float d = sdRoundCone(vPos, vA.xy, vB.xy, vA.z, vB.z);
366         float w = max(fwidth(d), 1e-4);
367         float cov = 1.0 - smoothstep(-w, w, d);
368         if (cov <= 0.0) discard;
369
370         float grainFactor = 1.0;
371         if (uGrainActive == 1) {
372             vec2 uv = vCanvasUv * max(uGrainScale, 0.0001);
373             float val = texture(uGrainTex, uv).r;
374             val = clamp((val - 0.5) * uTextureContrast + 0.5, 0.0, 1.0);
375             grainFactor = mix(1.0 - uTextureDepth, 1.0, val);
376         }
377
378         vec2 ab = vB.xy - vA.xy;
379         float abLengthSquared = max(dot(ab, ab), 0.000001);
380         float segmentT = clamp(
381             dot(vPos - vA.xy, ab) / abLengthSquared,
382             0.0,
383             1.0
384         );
385         float segmentCoverage = mix(vA.w, vB.w, segmentT);
386         float finalAlpha = cov * segmentCoverage * grainFactor * uFlow;
387         fragColor = vec4(uColorLinear * finalAlpha, finalAlpha);
388     }
389     ""
390
391     const val strokeBlitFragment = ""#version 300 es
392     precision highp float;
393     in vec2 vUv;
394     uniform sampler2D uStrokeTex;
395     uniform float uOpacity;
396     out vec4 fragColor;
397     void main() { fragColor = texture(uStrokeTex, vUv) * uOpacity; }
398     ""
399 }

```

69. app/src/main/java/com/wetinknext/engine/input/GestureRouter.kt

```

1  package com.wetinknext.engine.input
2
3  import android.view.MotionEvent
4  import com.wetinknext.engine.core.Camera
5  import kotlin.math.atan2
6  import kotlin.math.hypot
7
8  /**
9   * Routes view touch input before it reaches the brush pipeline.
10  *
11  * One pointer draws. A second pointer cancels that stroke immediately and
12  * takes ownership of the interaction for canvas navigation. Two- and
13  * three-pointer taps trigger undo and redo respectively.
14  */
15  class GestureRouter(
16      private val camera: Camera,
17      private val drawingInput: StrokeInputCapturer,
18      private val callbacks: Callbacks,
19  ) {
20      interface Callbacks {
21          fun cancelDrawing()
22          fun undoGesture()
23          fun redoGesture()
24          fun resetCamera()
25          fun requestRender()
26      }
27
28      private var mode = InputMode.IDLE
29      private var firstX = 0f
30      private var firstY = 0f
31      private var secondX = 0f
32      private var secondY = 0f
33      private var previousDistance = 0f
34      private var previousAngle = 0f
35      private var gestureStartTime = 0L
36      private var gestureMoved = false
37      private var navigationPointerCount = 0
38      private var drawingStartTime = 0L
39      private var drawingStartX = 0f
40      private var drawingStartY = 0f
41      private var drawingMoved = false
42      private var lastTapTime = 0L
43      private var lastTapX = 0f
44      private var lastTapY = 0f
45
46      fun onTouchEvent(event: MotionEvent): Boolean = when (event.actionMasked) {
47          MotionEvent.ACTION_DOWN -> {
48              mode = InputMode.DRAWING
49              drawingStartTime = event.eventTime
50              drawingStartX = event.x
51              drawingStartY = event.y
52              drawingMoved = false
53              drawingInput.onTouchEvent(event)
54              true
55          }
56
57          MotionEvent.ACTION_POINTER_DOWN -> {
58              if (event.pointerCount >= 2) {
59                  beginNavigation(event)
60                  true
61              } else {
62                  false
63              }
64          }
65
66          MotionEvent.ACTION_MOVE -> when (mode) {
67              InputMode.DRAWING -> {
68                  if (hypot(event.x - drawingStartX, event.y - drawingStartY) > TAP_MOVE_THRESHOLD_PX) {
69                      drawingMoved = true
70                      lastTapTime = 0L
71                  }
72                  drawingInput.onTouchEvent(event)
73                  true
74              }
75
76              InputMode.NAVIGATING -> {
77                  updateNavigation(event)
78                  true
79              }
80
81              else -> false
82          }
83
84          MotionEvent.ACTION_POINTER_UP -> {
85              if (mode == InputMode.NAVIGATING) {
86                  handleNavigationPointerUp(event)
87                  true
88              } else {
89                  drawingInput.onTouchEvent(event)
90                  true

```



```

91     }
92 }
93
94 MotionEvent.ACTION_UP -> {
95     when (mode) {
96         InputMode.DRAWING -> {
97             drawingInput.onTouchEvent(event)
98             val duration = event.eventTime - drawingStartTime
99             if (!drawingMoved && duration <= TAP_MAX_DURATION_MS) {
100                 handleSingleFingerTap(event)
101             }
102         }
103         InputMode.NAVIGATING -> finishNavigation(event)
104         else -> Unit
105     }
106     mode = InputMode.IDLE
107     true
108 }
109
110 MotionEvent.ACTION_CANCEL -> {
111     drawingInput.cancelActiveStroke()
112     callbacks.cancelDrawing()
113     mode = InputMode.CANCELLED
114     callbacks.requestRender()
115     true
116 }
117
118 else -> false
119 }
120
121 private fun beginNavigation(event: MotionEvent) {
122     lastTapTime = 0L
123     if (mode == InputMode.DRAWING) {
124         // The queued CANCEL keeps the brush pipeline coherent; the callback
125         // clears an already-rendered preview on the GL thread.
126         drawingInput.cancelActiveStroke()
127         callbacks.cancelDrawing()
128     }
129
130     mode = InputMode.NAVIGATING
131     navigationPointerCount = event.pointerCount
132     gestureStartTime = event.eventTime
133     gestureMoved = false
134     captureNavigationPointers(event)
135     callbacks.requestRender()
136 }
137
138 private fun updateNavigation(event: MotionEvent) {
139     if (event.pointerCount < 2) return
140
141     val newFirstX = event.getX(0)
142     val newFirstY = event.getY(0)
143     val newSecondX = event.getX(1)
144     val newSecondY = event.getY(1)
145     val oldCenterX = (firstX + secondX) * .5f
146     val oldCenterY = (firstY + secondY) * .5f
147     val newCenterX = (newFirstX + newSecondX) * .5f
148     val newCenterY = (newFirstY + newSecondY) * .5f
149     val newDistance = distance(newFirstX, newFirstY, newSecondX, newSecondY)
150     val zoomFactor = if (previousDistance > MIN_DISTANCE) newDistance / previousDistance else 1f
151     val newAngle = angle(newFirstX, newFirstY, newSecondX, newSecondY)
152     val rotationDelta = normalizeAngle(newAngle - previousAngle)
153     val panX = newCenterX - oldCenterX
154     val panY = newCenterY - oldCenterY
155
156     camera.set(
157         camera.snapshot().applyGestureDelta(
158             panX = panX,
159             panY = panY,
160             anchorX = newCenterX,
161             anchorY = newCenterY,
162             zoomFactor = zoomFactor,
163             rotationDelta = rotationDelta,
164         ),
165     )
166
167     if (hypot(panX, panY) > TAP_MOVE_THRESHOLD_PX ||
168         kotlin.math.abs(zoomFactor - 1f) > TAP_ZOOM_THRESHOLD ||
169         kotlin.math.abs(rotationDelta) > TAP_ROTATION_THRESHOLD_RAD
170     ) {
171         gestureMoved = true
172     }
173
174     firstX = newFirstX
175     firstY = newFirstY
176     secondX = newSecondX
177     secondY = newSecondY
178     previousDistance = newDistance
179     previousAngle = newAngle
180     callbacks.requestRender()
181 }
182

```

```

183 private fun handleNavigationPointerUp(event: MotionEvent) {
184     // Once fewer than two pointers remain, navigation stays active until
185     // ACTION_UP so a two/three-finger tap can be recognised reliably.
186     if (event.pointerCount - 1 < 2) return
187     captureNavigationPointers(event, event.actionIndex)
188 }
189
190 private fun finishNavigation(event: MotionEvent) {
191     val duration = event.eventTime - gestureStartTime
192     if (!gestureMoved && duration <= TAP_MAX_DURATION_MS) {
193         when (navigationPointerCount) {
194             2 -> callbacks.undoGesture()
195             3 -> callbacks.redoGesture()
196         }
197     }
198     callbacks.requestRender()
199 }
200
201 private fun handleSingleFingerTap(event: MotionEvent) {
202     val now = event.eventTime
203     val dx = event.x - lastTapX
204     val dy = event.y - lastTapY
205     val isDoubleTap =
206         now - lastTapTime <= DOUBLE_TAP_TIMEOUT_MS &&
207         hypot(dx, dy) <= DOUBLE_TAP_DISTANCE_PX
208     if (isDoubleTap) {
209         callbacks.resetCamera()
210         lastTapTime = 0L
211     } else {
212         lastTapTime = now
213         lastTapX = event.x
214         lastTapY = event.y
215     }
216 }
217
218 private fun captureNavigationPointers(event: MotionEvent, excludedIndex: Int = -1) {
219     var firstIndex = -1
220     var secondIndex = -1
221     for (index in 0 until event.pointerCount) {
222         if (index == excludedIndex) continue
223         if (firstIndex < 0) firstIndex = index else {
224             secondIndex = index
225             break
226         }
227     }
228     if (firstIndex < 0 || secondIndex < 0) return
229     firstX = event.getX(firstIndex)
230     firstY = event.getY(firstIndex)
231     secondX = event.getX(secondIndex)
232     secondY = event.getY(secondIndex)
233     previousDistance = distance(firstX, firstY, secondX, secondY)
234     previousAngle = angle(firstX, firstY, secondX, secondY)
235 }
236
237 private fun distance(x0: Float, y0: Float, x1: Float, y1: Float): Float =
238     hypot(x1 - x0, y1 - y0)
239
240 private fun angle(x0: Float, y0: Float, x1: Float, y1: Float): Float =
241     atan2(y1 - y0, x1 - x0)
242
243 private fun normalizeAngle(value: Float): Float {
244     var result = value
245     while (result > Math.PI) result -= (Math.PI * 2.0).toFloat()
246     while (result < -Math.PI) result += (Math.PI * 2.0).toFloat()
247     return result
248 }
249
250 private companion object {
251     const val TAP_MAX_DURATION_MS = 220L
252     const val MIN_DISTANCE = .001f
253     const val TAP_MOVE_THRESHOLD_PX = 4f
254     const val TAP_ZOOM_THRESHOLD = .02f
255     const val TAP_ROTATION_THRESHOLD_RAD = .035f
256     const val DOUBLE_TAP_TIMEOUT_MS = 280L
257     const val DOUBLE_TAP_DISTANCE_PX = 48f
258 }
259 }

```

70. app/src/main/java/com/wetinknext/engine/input/InputAction.kt

```
1 package com.wetinknext.engine.input
2
3 enum class InputAction {
4     DOWN,
5     MOVE,
6     UP,
7     CANCEL,
8 }
```

71. app/src/main/java/com/wetinknext/engine/input/InputBatch.kt

```
1 package com.wetinknext.engine.input
2
3 /** Fixed-capacity container for passing input from the UI thread to the GL thread. */
4 class InputBatch(val maxSamples: Int) {
5     val samples = Array(maxSamples) { InputSample() }
6
7     var action: InputAction = InputAction.MOVE
8     private set
9     var sampleCount: Int = 0
10    private set
11    var prediction: Boolean = false
12    private set
13
14    fun begin(action: InputAction, prediction: Boolean = false) {
15        this.action = action
16        this.prediction = prediction
17        sampleCount = 0
18    }
19
20    fun addSample(
21        canvasX: Float, canvasY: Float, pressure: Float, tiltX: Float, tiltY: Float,
22        orientationRad: Float, timestampNanos: Long, pointerId: Int, tool: PointerTool,
23        historical: Boolean,
24    ): Boolean {
25        if (sampleCount >= maxSamples) return false
26        samples[sampleCount].set(
27            canvasX, canvasY, pressure.coerceIn(0f, 1f), tiltX.coerceIn(-1f, 1f),
28            tiltY.coerceIn(-1f, 1f), orientationRad, timestampNanos, pointerId, tool, historical,
29        )
30        sampleCount += 1
31        return true
32    }
33
34    fun isEmpty(): Boolean = sampleCount == 0
35
36    fun clear() {
37        for (index in 0 until sampleCount) samples[index].clear()
38        sampleCount = 0
39        prediction = false
40        action = InputAction.MOVE
41    }
42 }
```

72. app/src/main/java/com/wetinknext/engine/input/InputBatchPool.kt

```
1 package com.wetinknext.engine.input
2
3 import java.util.concurrent.atomic.AtomicInteger
4 import java.util.concurrent.atomic.AtomicReferenceArray
5
6 /** Fixed-size pool that returns null instead of allocating when exhausted. */
7 class InputBatchPool(
8     batchCount: Int = DEFAULT_BATCH_COUNT,
9     maxSamplesPerBatch: Int = DEFAULT_MAX_SAMPLES,
10 ) {
11     private val batches = AtomicReferenceArray<InputBatch>(batchCount)
12     private val available = AtomicInteger(batchCount)
13
14     init {
15         require(batchCount > 0)
16         require(maxSamplesPerBatch > 0)
17         for (index in 0 until batchCount) batches.set(index, InputBatch(maxSamplesPerBatch))
18     }
19
20     fun acquire(): InputBatch? {
21         while (true) {
22             val current = available.get()
23             if (current <= 0) return null
24             if (available.compareAndSet(current, current - 1)) {
25                 for (index in 0 until batches.length()) {
26                     val batch = batches.getAndSet(index, null)
27                     if (batch != null) return batch
28                 }
29                 available.incrementAndGet()
30                 return null
31             }
32         }
33     }
34
35     fun release(batch: InputBatch) {
36         batch.clear()
37         for (index in 0 until batches.length()) {
38             if (batches.compareAndSet(index, null, batch)) {
39                 available.incrementAndGet()
40                 return
41             }
42         }
43         error("InputBatchPool overflow: released batch does not belong to pool")
44     }
45
46     val freeCount: Int get() = available.get()
47
48     companion object {
49         const val DEFAULT_BATCH_COUNT = 96
50         const val DEFAULT_MAX_SAMPLES = 64
51     }
52 }
```

73. app/src/main/java/com/wetinknext/engine/input/InputMode.kt

```
1 package com.wetinknext.engine.input
2
3 /** Current ownership of touch input. Only DRAWING reaches the brush pipeline. */
4 enum class InputMode {
5     IDLE,
6     DRAWING,
7     NAVIGATING,
8     CANCELLED,
9 }
```

74. app/src/main/java/com/wetinknext/engine/input/InputSample.kt

```
1 package com.wetinknext.engine.input
2
3 /** Mutable input sample allocated only while a batch pool is initialized. */
4 class InputSample {
5     var canvasX = 0f
6     var canvasY = 0f
7     var pressure = 0f
8     var tiltX = 0f
9     var tiltY = 0f
10    var orientationRad = 0f
11    var timestampNanos = 0L
12    var pointerId = -1
13    var tool = PointerTool.UNKNOWN
14    var historical = false
15
16    fun set(
17        canvasX: Float, canvasY: Float, pressure: Float, tiltX: Float, tiltY: Float,
18        orientationRad: Float, timestampNanos: Long, pointerId: Int, tool: PointerTool,
19        historical: Boolean,
20    ) {
21        this.canvasX = canvasX; this.canvasY = canvasY; this.pressure = pressure
22        this.tiltX = tiltX; this.tiltY = tiltY; this.orientationRad = orientationRad
23        this.timestampNanos = timestampNanos; this.pointerId = pointerId; this.tool = tool
24        this.historical = historical
25    }
26
27    fun clear() {
28        canvasX = 0f; canvasY = 0f; pressure = 0f; tiltX = 0f; tiltY = 0f
29        orientationRad = 0f; timestampNanos = 0L; pointerId = -1
30        tool = PointerTool.UNKNOWN; historical = false
31    }
32 }
```

75. app/src/main/java/com/wetinknext/engine/input/PointerTool.kt

```
1 package com.wetinknext.engine.input
2
3 enum class PointerTool {
4     FINGER,
5     STYLUS,
6     ERASER,
7     UNKNOWN,
8 }
```


76. app/src/main/java/com/wetinknext/engine/input/StrokeInputCapturer.kt

```

1 package com.wetinknext.engine.input
2
3 import android.view.MotionEvent
4 import com.wetinknext.engine.core.Camera
5 import java.util.concurrent.ArrayBlockingQueue
6
7 /** Converts View-local MotionEvent samples to canvas coordinates on the UI thread. */
8 class StrokeInputCapturer(private val camera: Camera, private val pool: InputBatchPool, private val queue:
ArrayBlockingQueue<InputBatch>) {
9     private var activePointerId = -1
10    private val canvasPoint = FloatArray(2)
11    private val stylusAxes = StylusAxes()
12    private val tiltOut = FloatArray(2)
13
14    var onSecondaryPointerDown: (() -> Unit)? = null
15
16    /** Не скрываем потери: пул кончился => сэмплы утрачены. */
17    var droppedBatches = 0L
18    private set
19
20    /** Cancels the one pointer currently owned by the drawing pipeline. */
21    fun cancelActiveStroke(): Boolean {
22        if (activePointerId < 0) return false
23        activePointerId = -1
24        return enqueueEmpty(InputAction.CANCEL)
25    }
26
27    fun onTouchEvent(event: MotionEvent): Boolean = when (event.actionMasked) {
28        MotionEvent.ACTION_DOWN -> {
29            activePointerId = event.getPointerId(0)
30            enqueue(event, InputAction.DOWN, 0, false)
31        }
32        // Multi-touch is owned by GestureRouter. Drawing input only receives
33        // the one-pointer draw path and explicit cancellation from that router.
34        MotionEvent.ACTION_POINTER_DOWN -> false
35        MotionEvent.ACTION_MOVE -> {
36            val i = event.findPointerIndex(activePointerId)
37            i >= 0 && enqueue(event, InputAction.MOVE, i, true)
38        }
39        MotionEvent.ACTION_UP, MotionEvent.ACTION_POINTER_UP -> {
40            val i = if (event.actionMasked == MotionEvent.ACTION_UP) 0 else event.actionIndex
41            if (event.getPointerId(i) != activePointerId) true else {
42                activePointerId = -1
43                // historical = true: хвост быстрого штриха больше не теряется.
44                enqueue(event, InputAction.UP, i, true)
45            }
46        }
47        MotionEvent.ACTION_CANCEL -> { activePointerId = -1; enqueueEmpty(InputAction.CANCEL) }
48        else -> false
49    }
50
51    private fun enqueue(event: MotionEvent, action: InputAction, index: Int, historical: Boolean): Boolean {
52        val batch = pool.acquire() ?: run { droppedBatches++; return false }
53        batch.begin(action); val t=camera.snapshot(); val id=event.getPointerId(index); val tool=tool(event,index)
54        if(historical) {
55            for(h in 0 until event.historySize) {
56                t.screenToCanvas(event.getHistoricalX(index, h), event.getHistoricalY(index, h), canvasPoint)
57                stylusAxes.readTilt(event, index, h, tool, tiltOut)
58                val orientation = stylusAxes.readOrientation(event, index, h, tool)
59                if(!batch.addSample(
60                    canvasPoint[0], canvasPoint[1], pressure(event, tool, index, h),
61                    tiltOut[0], tiltOut[1], orientation,
62                    event.getHistoricalEventTime(h) * 1_000_000L, id, tool, true
63                )) break
64            }
65        }
66        t.screenToCanvas(event.getX(index), event.getY(index), canvasPoint)
67        stylusAxes.readTilt(event, index, -1, tool, tiltOut)
68        val orientation = stylusAxes.readOrientation(event, index, -1, tool)
69        batch.addSample(
70            canvasPoint[0], canvasPoint[1], pressure(event, tool, index, -1),
71            tiltOut[0], tiltOut[1], orientation,
72            event.eventTime * 1_000_000L, id, tool, false
73        )
74        if (!queue.offer(batch)) {
75            pool.release(batch)
76            droppedBatches++
77            if (action == InputAction.UP) {
78                enqueueEmpty(InputAction.CANCEL)
79            }
80            return false
81        }
82        return true
83    }
84
85    private fun enqueueEmpty(action: InputAction): Boolean {
86        val batch = pool.acquire() ?: run { droppedBatches++; return false }
87        batch.begin(action); if(!queue.offer(batch)){pool.release(batch);droppedBatches++;return false};return true }
88    private fun tool(e: MotionEvent, i: Int)=when(e.getToolType(i)){MotionEvent.TOOL_TYPE_STYLUS->PointerTool.STYLUS; MotionEvent.
TOOL_TYPE_ERASER->PointerTool.ERASER; MotionEvent.TOOL_TYPE_FINGER->PointerTool.FINGER; else->PointerTool.UNKNOWN}

```

```
89     private fun pressure(e:MotionEvent,t:PointerTool,i:Int,h:Int):Float=if(t==PointerTool.FINGER||t==PointerTool.UNKNOWN)
SYNTHETIC_FINGER_PRESSURE else (if(h>=0)e.getHistoricalPressure(i,h) else e.getPressure(i)).coerceIn(0f,1f)
90
91     companion object {
92         private const val SYNTHETIC_FINGER_PRESSURE = 0.62f
93     }
94 }
```

77. app/src/main/java/com/wetinknext/engine/input/StylusAxes.kt

```

1  package com.wetinknext.engine.input
2
3  import android.view.MotionEvent
4  import kotlin.math.cos
5  import kotlin.math.sin
6
7  class StylusAxes {
8
9      fun readTilt(
10         event: MotionEvent,
11         pointerIndex: Int,
12         historicalIndex: Int,
13         tool: PointerTool,
14         out: FloatArray,
15     ) {
16         if (tool == PointerTool.FINGER ||
17             tool == PointerTool.UNKNOWN) {
18             {
19                 out[0] = 0f
20                 out[1] = 0f
21                 return
22             }
23
24             val tilt = if (historicalIndex >= 0) {
25                 event.getHistoricalAxisValue(
26                     MotionEvent.AXIS_TILT,
27                     pointerIndex,
28                     historicalIndex,
29                 )
30             } else {
31                 event.getAxisValue(
32                     MotionEvent.AXIS_TILT,
33                     pointerIndex,
34                 )
35             }
36
37             val orientation = if (historicalIndex >= 0) {
38                 event.getHistoricalAxisValue(
39                     MotionEvent.AXIS_ORIENTATION,
40                     pointerIndex,
41                     historicalIndex,
42                 )
43             } else {
44                 event.getAxisValue(
45                     MotionEvent.AXIS_ORIENTATION,
46                     pointerIndex,
47                 )
48             }
49
50             val normalizedTilt =
51                 (tilt / (Math.PI.toFloat() * 0.5f))
52                 .coerceIn(0f, 1f)
53
54             out[0] =
55                 (cos(orientation) * normalizedTilt)
56                 .coerceIn(-1f, 1f)
57
58             out[1] =
59                 (sin(orientation) * normalizedTilt)
60                 .coerceIn(-1f, 1f)
61         }
62
63         fun readOrientation(
64             event: MotionEvent,
65             pointerIndex: Int,
66             historicalIndex: Int,
67             tool: PointerTool,
68         ): Float {
69             if (tool == PointerTool.FINGER || tool == PointerTool.UNKNOWN) return 0f
70             return if (historicalIndex >= 0) {
71                 event.getHistoricalAxisValue(MotionEvent.AXIS_ORIENTATION, pointerIndex, historicalIndex)
72             } else {
73                 event.getAxisValue(MotionEvent.AXIS_ORIENTATION, pointerIndex)
74             }
75         }
76     }

```

78. app/src/main/java/com/wetinknext/engine/persistence/LayerTileStore.kt

```

1 package com.wetinknext.engine.persistence
2
3 import com.wetinknext.engine.canvas.PaintLayer
4 import com.wetinknext.engine.undo.RawTileSnapshot
5 import com.wetinknext.engine.undo.TileCoord
6 import java.util.concurrent.ConcurrentHashMap
7
8 /** CPU cache of tiles captured after completed edits. No dab triggers persistence. */
9 class LayerTileStore(initialPayloads: Map<Long, ByteArray> = emptyMap()) {
10     private val tiles = ConcurrentHashMap<Long, ConcurrentHashMap<TileCoord, PersistentLayerTiles.Tile>>()
11     private val dirty = ConcurrentHashMap<Long, MutableSet<TileCoord>>()
12     /** A cleared layer is persisted as a tiny empty tile collection, not as a full transparent canvas. */
13     private val clearedLayers = ConcurrentHashMap.newKeySet<Long>()
14
15     suspend fun writeTile(layerId: Long, tile: RawTileSnapshot) {
16         tiles.getOrPut(layerId) { ConcurrentHashMap<>() }[tile.coord] = PersistentLayerTiles.fromRaw(tile)
17         dirty.getOrPut(layerId) { ConcurrentHashMap.newKeySet() }.add(tile.coord)
18     }
19
20     suspend fun readTile(layerId: Long, coord: TileCoord): ByteArray =
21         tiles[layerId]?.get(coord)?.bytes?.copyOf() ?: ByteArray(0)
22
23     suspend fun writeLayer(layer: PaintLayer, changedTiles: List<RawTileSnapshot>) {
24         require(layer.created)
25         changedTiles.forEach { writeTile(layer.id, it) }
26     }
27
28     /** GL-thread hand-off: copying one completed tile is bounded and allocation-safe. */
29     fun markDirty(layerId: Long, changedTiles: List<RawTileSnapshot>) {
30         clearedLayers.remove(layerId)
31         val target = tiles.getOrPut(layerId) { ConcurrentHashMap<>() }
32         val dirtyCoords = dirty.getOrPut(layerId) { ConcurrentHashMap.newKeySet() }
33         changedTiles.forEach { tile ->
34             target[tile.coord] = PersistentLayerTiles.fromRaw(tile)
35             dirtyCoords.add(tile.coord)
36         }
37     }
38
39     /** Drops the previous cached pixels after a layer clear without allocating transparent tile data. */
40     fun markLayerCleared(layerId: Long) {
41         tiles.remove(layerId)
42         dirty.remove(layerId)
43         clearedLayers.add(layerId)
44     }
45
46     fun takeDirty(): Map<Long, Set<TileCoord>> = buildMap {
47         dirty.forEach { (layerId, coords) -> put(layerId, coords.toSet()) }
48         clearedLayers.forEach { layerId -> putIfAbsent(layerId, emptySet()) }
49     }
50
51     fun acknowledge(saved: Map<Long, Set<TileCoord>>) {
52         saved.forEach { (layerId, coords) ->
53             dirty[layerId]?.removeAll(coords)
54             clearedLayers.remove(layerId)
55         }
56     }
57
58     /** Full layer payloads only for layers that have dirty tiles. */
59     fun payloadsForDirty(dirtySnapshot: Map<Long, Set<TileCoord>> = takeDirty()): Map<Long, ByteArray> =
60         dirtySnapshot.keys.associateWith { layerId ->
61             PersistentLayerTiles.encode(tiles[layerId]?.values.orEmpty())
62         }
63
64     init {
65         initialPayloads.forEach { (layerId, payload) ->
66             if (payload.isNotEmpty()) {
67                 val layer = tiles.getOrPut(layerId) { ConcurrentHashMap<>() }
68                 PersistentLayerTiles.decode(payload).forEach { layer[it.coord] = it }
69             }
70         }
71     }
72 }

```

79. app/src/main/java/com/wetinknext/engine/persistence/PersistentLayerTiles.kt

```

1 package com.wetinknext.engine.persistence
2
3 import com.wetinknext.engine.undo.RawTileSnapshot
4 import com.wetinknext.engine.undo.TileCoord
5 import java.nio.ByteBuffer
6 import java.nio.ByteOrder
7 import java.util.zip.DataFormatException
8 import java.util.zip.Deflater
9 import java.util.zip.Inflater
10
11 /** Binary, versioned collection of 256px tiles for one persistent paint layer. */
12 object PersistentLayerTiles {
13     private const val MAGIC = 0x57544C53 // WTLS
14     private const val VERSION = 2
15     private const val HEADER_BYTES = 12
16     private const val TILE_HEADER_BYTES_V1 = 32
17     private const val TILE_HEADER_BYTES_V2 = 36
18
19     data class Tile(
20         val coord: TileCoord,
21         val pixelLeft: Int,
22         val pixelTop: Int,
23         val pixelWidth: Int,
24         val pixelHeight: Int,
25         val bytesPerPixel: Int,
26         val bytes: ByteArray,
27     )
28
29     fun decode(payload: ByteArray): List<Tile> {
30         if (payload.isEmpty()) return emptyList()
31         val input = ByteBuffer.wrap(payload).order(ByteOrder.BIG_ENDIAN)
32         require(input.remaining() >= HEADER_BYTES && input.int == MAGIC) { "Unknown persistent layer tile payload" }
33         val version = input.int
34         require(version in setOf(1, VERSION)) { "Unsupported persistent layer tile version" }
35         val count = input.int
36         require(count >= 0) { "Invalid tile count" }
37         return List(count) {
38             val headerBytes = if (version == 1) TILE_HEADER_BYTES_V1 else TILE_HEADER_BYTES_V2
39             require(input.remaining() >= headerBytes) { "Truncated tile header" }
40             val tx = input.int; val ty = input.int
41             val left = input.int; val top = input.int
42             val width = input.int; val height = input.int
43             val bpp = input.int
44             val rawSize = input.int
45             require(
46                 width > 0 && height > 0 && bpp in setOf(4, 8) &&
47                 rawSize == width * height * bpp
48             ) { "Invalid tile payload" }
49
50             val bytes = if (version == 1) {
51                 require(rawSize <= input.remaining()) { "Truncated tile payload" }
52                 ByteArray(rawSize).also(input::get)
53             } else {
54                 val storedSize = input.int
55                 require(storedSize > 0 && storedSize <= input.remaining()) { "Invalid compressed tile payload" }
56                 val compressed = ByteArray(storedSize).also(input::get)
57                 inflate(compressed, rawSize)
58             }
59             Tile(TileCoord(tx, ty), left, top, width, height, bpp, bytes)
60         }.also { require(!input.hasRemaining()) { "Trailing tile payload data" } }
61     }
62
63     fun encode(tiles: Collection<Tile>): ByteArray {
64         val encoded = tiles
65             .sortedWith(compareBy<Tile> { it.coord.ty }.thenBy { it.coord.tx })
66             .map { tile -> tile to deflate(tile.bytes) }
67         val size = HEADER_BYTES + encoded.sumOf { (tile, compressed) ->
68             TILE_HEADER_BYTES_V2 + compressed.size
69         }
70         val output = ByteBuffer.allocate(size).order(ByteOrder.BIG_ENDIAN)
71         output.putInt(MAGIC).putInt(VERSION).putInt(tiles.size)
72         encoded.forEach { (tile, compressed) ->
73             output.putInt(tile.coord.tx).putInt(tile.coord.ty)
74             output.putInt(tile.pixelLeft).putInt(tile.pixelTop)
75             output.putInt(tile.pixelWidth).putInt(tile.pixelHeight)
76             output.putInt(tile.bytesPerPixel).putInt(tile.bytes.size)
77             output.putInt(compressed.size).put(compressed)
78         }
79         return output.array()
80     }
81
82     private fun deflate(raw: ByteArray): ByteArray {
83         val compressor = Deflater(Deflater.BEST_SPEED)
84         return try {
85             compressor.setInput(raw)
86             compressor.finish()
87             // zlib's incompressible-data bound; a tile is at most 512 KiB.
88             val destination = ByteArray(raw.size + raw.size / 8 + 64)
89             val size = compressor.deflate(destination)
90             require(compressor.finished()) { "Tile compression did not finish" }

```

```

91         destination.copyOf(size)
92     } finally {
93         compressor.end()
94     }
95 }
96
97 private fun inflate(compressed: ByteArray, rawSize: Int): ByteArray {
98     val inflater = Inflater()
99     return try {
100         inflater.setInput(compressed)
101         val raw = ByteArray(rawSize)
102         val size = inflater.inflate(raw)
103         require(size == rawSize && inflater.finished()) { "Tile decompression failed" }
104         raw
105     } catch (error: DataFormatException) {
106         throw IllegalArgumentException("Invalid compressed tile data", error)
107     } finally {
108         inflater.end()
109     }
110 }
111
112 fun fromRaw(tile: RawTileSnapshot) = Tile(
113     tile.coord, tile.pixelLeft, tile.pixelTop, tile.pixelWidth, tile.pixelHeight,
114     tile.bytesPerPixel, tile.rawBytes.copyOf(),
115 )
116 }

```

80. app/src/main/java/com/wetinknext/engine/thumbnail/ThumbnailBuildScheduler.kt

```

1 package com.wetinknext.engine.thumbnail
2
3 import android.os.Handler
4 import android.os.Looper
5 import com.wetinknext.engine.canvas.LayerStack
6 import com.wetinknext.engine.gl.GlCheck
7 import java.io.File
8 import java.io.IOException
9 import java.nio.file.AtomicMoveNotSupportedException
10 import java.nio.file.Files
11 import java.nio.file.StandardCopyOption
12 import java.util.concurrent.ConcurrentLinkedQueue
13 import java.util.concurrent.ExecutorService
14 import java.util.concurrent.Executors
15 import java.util.concurrent.RejectedExecutionException
16 import java.util.concurrent.atomic.AtomicLong
17
18 /** Result published to the UI only after the current generation reached disk. */
19 data class ThumbnailBuildResult(
20     val generation: Long,
21     val projectPreview: File?,
22     val layerPreviews: Map<Long, File>,
23 )
24
25 /**
26  * Coordinates thumbnail builds across the GL, worker and UI threads.
27  *
28  * Call [markDirty], [buildIfNeeded], [processCompleted] and [shutdown] on the
29  * GL thread. [buildIfNeeded] is the sole point that reads GPU textures. WebP
30  * encoding and file publication happen on [executor]; callbacks are dispatched
31  * to the Android main thread.
32  */
33 class ThumbnailBuildScheduler(
34     private val outputDirectory: File,
35     private val renderer: ThumbnailRenderer,
36     private val requestGlFrame: () -> Unit,
37     private val onSave: (ThumbnailBuildResult) -> Unit,
38     private val onFailure: (Throwable) -> Unit = {},
39     private val executorFactory: () -> ExecutorService = { Executors.newSingleThreadExecutor() },
40     private val uiHandler: Handler = Handler(Looper.getMainLooper()),
41     private val encoder: ThumbnailEncoder = ThumbnailEncoder(),
42     private val previewSizePx: Int = DEFAULT_PREVIEW_SIZE_PX,
43 ) {
44     private var executor = executorFactory()
45     private val pendingResults = ConcurrentLinkedQueue<WorkerResult>()
46     private val generation = AtomicLong(0L)
47     private val dirtyLayerIds = linkedSetOf<Long>()
48
49     private var projectDirty = false
50     private var buildRunning = false
51
52     /**
53      * Records the newest desired preview state. A newer mark makes an ongoing
54      * worker result stale before it is allowed to notify the UI.
55      */
56     fun markDirty(
57         projectDirty: Boolean,
58         dirtyLayerIds: Collection<Long> = emptyList(),
59     ) {
60         GlCheck.checkOnGlThread()
61         if (!projectDirty && dirtyLayerIds.isEmpty()) return
62         this.projectDirty = this.projectDirty || projectDirty
63         this.dirtyLayerIds += dirtyLayerIds
64         generation.incrementAndGet()
65     }
66
67     fun markProjectDirty() = markDirty(projectDirty = true)
68
69     fun markLayerDirty(layerId: Long) = markDirty(
70         projectDirty = false,
71         dirtyLayerIds = listOf(layerId),
72     )
73
74     /** Stops future work for a deleted layer without touching the GL context. */
75     fun removeLayer(layerId: Long) {
76         GlCheck.checkOnGlThread()
77         if (dirtyLayerIds.remove(layerId)) generation.incrementAndGet()
78     }
79
80     /** Recreates the worker after a GL context was deliberately released. */
81     fun ensureRunning() {
82         GlCheck.checkOnGlThread()
83         if (executor.isShutdown) executor = executorFactory()
84     }
85
86     /**
87      * Captures all currently dirty pixels on the GL thread and starts one
88      * worker job. Calling this while another job runs is intentionally a no-op.
89      */
90     fun buildIfNeeded(layers: LayerStack): Boolean {

```

```

91     GlCheck.checkOnGltThread()
92     if (buildRunning || (!projectDirty && dirtyLayerIds.isEmpty())) return false
93
94     val jobGeneration = generation.get()
95     val dimensions = previewDimensions(layers.canvasWidth, layers.canvasHeight)
96     val projectPixels = if (projectDirty) {
97         renderer.renderProject(layers, dimensions.width, dimensions.height)
98     } else {
99         null
100    }
101    val layerPixels = dirtyLayerIds
102        .mapNotNull { layerId ->
103            layers.findLayerById(layerId)?.let { layer ->
104                layerId to renderer.renderLayer(layer, dimensions.width, dimensions.height)
105            }
106        }
107        .toMap()
108
109    val request = BuildRequest(
110        generation = jobGeneration,
111        width = dimensions.width,
112        height = dimensions.height,
113        projectPixels = projectPixels,
114        layerPixels = layerPixels,
115    )
116    buildRunning = true
117    try {
118        executor.execute {
119            pendingResults.add(encodeAndPublish(request))
120            requestGltFrame()
121        }
122    } catch (error: RejectedExecutionException) {
123        pendingResults.add(WorkerResult.Failed(jobGeneration, error))
124        requestGltFrame()
125    }
126    return true
127 }
128
129 /**
130  * Finishes worker jobs on the GL thread and starts no UI callback for stale
131  * generations. The next frame can immediately call [buildIfNeeded] again.
132  */
133 fun processCompleted(): Boolean {
134     GlCheck.checkOnGltThread()
135     var changed = false
136     while (true) {
137         val result = pendingResults.poll() ?: break
138         buildRunning = false
139         changed = true
140
141         if (result.generation != generation.get()) {
142             continue
143         }
144
145         when (result) {
146             is WorkerResult.Saved -> {
147                 if (result.projectPreview != null) projectDirty = false
148                 dirtyLayerIds.removeAll(result.layerPreviews.keys)
149                 uiHandler.post {
150                     onSave {
151                         ThumbnailBuildResult(
152                             generation = result.generation,
153                             projectPreview = result.projectPreview,
154                             layerPreviews = result.layerPreviews,
155                         ),
156                     }
157                 }
158             }
159             is WorkerResult.Failed -> uiHandler.post { onFailure(result.error) }
160             is WorkerResult.Stale -> Unit
161         }
162     }
163     return changed
164 }
165
166 /** Makes in-flight work obsolete and releases the background encoder. */
167 fun shutdown() {
168     GlCheck.checkOnGltThread()
169     generation.incrementAndGet()
170     projectDirty = false
171     dirtyLayerIds.clear()
172     buildRunning = false
173     executor.shutdownNow()
174     pendingResults.clear()
175     renderer.release()
176 }
177
178 private fun encodeAndPublish(request: BuildRequest): WorkerResult = try {
179     val temporaryProject = request.projectPixels?.let {
180         temporaryFileFor(projectPreviewFile, request.generation)
181     }

```



```

183     }
184     val temporaryLayers = request.layerPixels.keys.associateWith { layerId ->
185         temporaryFileFor(layerPreviewFile(layerId), request.generation)
186     }
187
188     try {
189         request.projectPixels?.let { rgba ->
190             // Project preview is small and opaque in the usual case: 88 is
191             // a good size/quality balance.
192             encoder.encodeTopDown(rgba, request.width, request.height, checkNotNull(temporaryProject), lossless = false)
193         }
194         request.layerPixels.forEach { (layerId, rgba) ->
195             // Layer previews must preserve alpha and thin marks.
196             encoder.encodeTopDown(rgba, request.width, request.height, checkNotNull(temporaryLayers[layerId]), lossless =
true)
197         }
198
199         if (request.generation != generation.get()) {
200             temporaryProject?.delete()
201             temporaryLayers.values.forEach(File::delete)
202             WorkerResult.Stale(request.generation)
203         } else {
204             val publishedProject = temporaryProject?.let {
205                 publish(it, projectPreviewFile)
206                 projectPreviewFile
207             }
208             val publishedLayers = temporaryLayers.mapNotNull { (layerId, temporary) ->
209                 val target = layerPreviewFile(layerId)
210                 publish(temporary, target)
211                 layerId to target
212             }.toMap()
213             WorkerResult.Saved(request.generation, publishedProject, publishedLayers)
214         }
215     } catch (error: Throwable) {
216         temporaryProject?.delete()
217         temporaryLayers.values.forEach(File::delete)
218         throw error
219     }
220 } catch (error: Throwable) {
221     WorkerResult.Failed(request.generation, error)
222 }
223
224 private fun publish(temporary: File, destination: File) {
225     destination.parentFile?.mkdirs()
226     try {
227         Files.move(
228             temporary.toPath(),
229             destination.toPath(),
230             StandardCopyOption.ATOMIC_MOVE,
231             StandardCopyOption.REPLACE_EXISTING,
232         )
233     } catch (_: AtomicMoveNotSupportedException) {
234         Files.move(
235             temporary.toPath(),
236             destination.toPath(),
237             StandardCopyOption.REPLACE_EXISTING,
238         )
239     } catch (error: IOException) {
240         throw IOException("Unable to publish thumbnail ${destination.path}", error)
241     }
242 }
243
244 private fun temporaryFileFor(destination: File, jobGeneration: Long): File {
245     val parent = destination.parentFile ?: error("Thumbnail output requires a parent directory")
246     if (!parent.exists() && !parent.mkdirs()) {
247         throw IOException("Cannot create thumbnail directory: ${parent.path}")
248     }
249     return File(parent, ".$${destination.name}.${jobGeneration.tmp}")
250 }
251
252 private val projectPreviewFile: File
253     get() = File(outputDirectory, PROJECT_PREVIEW_FILE_NAME)
254
255 private fun layerPreviewFile(layerId: Long): File =
256     File(File(outputDirectory, LAYER_PREVIEW_DIRECTORY), "$layerId.webp")
257
258 /** Generates a file with the same aspect ratio as its document. */
259 private fun previewDimensions(canvasWidth: Int, canvasHeight: Int): PreviewDimensions {
260     val width = canvasWidth.coerceAtLeast(1)
261     val height = canvasHeight.coerceAtLeast(1)
262     return if (width >= height) {
263         PreviewDimensions(previewSizePx, (previewSizePx.toLong() * height / width).toInt().coerceAtLeast(1))
264     } else {
265         PreviewDimensions((previewSizePx.toLong() * width / height).toInt().coerceAtLeast(1), previewSizePx)
266     }
267 }
268
269 private data class BuildRequest(
270     val generation: Long,
271     val width: Int,
272     val height: Int,
273     val projectPixels: ByteArray?,

```

```

274         val layerPixels: Map<Long, ByteArray>,
275     )
276
277     private data class PreviewDimensions(val width: Int, val height: Int)
278
279     private sealed interface WorkerResult {
280         val generation: Long
281
282         data class Saved(
283             override val generation: Long,
284             val projectPreview: File?,
285             val layerPreviews: Map<Long, File>,
286         ) : WorkerResult
287
288         data class Failed(
289             override val generation: Long,
290             val error: Throwable,
291         ) : WorkerResult
292
293         data class Stale(
294             override val generation: Long,
295         ) : WorkerResult
296     }
297
298
299     private companion object {
300         const val DEFAULT_PREVIEW_SIZE_PX = 256
301         const val PROJECT_PREVIEW_FILE_NAME = "thumbnail.webp"
302         const val LAYER_PREVIEW_DIRECTORY = "previews"
303     }
304 }

```

81. app/src/main/java/com/wetinknext/engine/thumbnail/ThumbnailEncoder.kt

```

1  package com.wetinknext.engine.thumbnail
2
3  import android.graphics.Bitmap
4  import android.os.Build
5  import java.io.File
6  import kotlin.math.pow
7  import kotlin.math.roundToInt
8
9  /**
10 * Persists a raw OpenGL thumbnail as WebP.
11 *
12 * [rgba] follows [android.opengl.GLES30.glReadPixels] row ordering: the first
13 * row is the bottom row. The encoder converts it to Android Bitmap's top-down
14 * order while preserving RGBA alpha exactly before WebP compression.
15 */
16 class ThumbnailEncoder {
17     fun encode(
18         rgba: ByteArray,
19         width: Int,
20         height: Int,
21         output: File,
22         lossless: Boolean,
23     ) = encodeInternal(
24         rgba = rgba,
25         width = width,
26         height = height,
27         output = output,
28         lossless = lossless,
29         inputRowsBottomUp = true,
30     )
31
32     /**
33      * Writes an image returned by [ThumbnailRenderer], whose rows have already
34      * been normalised into Android's top-to-bottom order.
35      */
36     fun encodeTopDown(
37         rgba: ByteArray,
38         width: Int,
39         height: Int,
40         output: File,
41         lossless: Boolean,
42     ) = encodeInternal(
43         rgba = rgba,
44         width = width,
45         height = height,
46         output = output,
47         lossless = lossless,
48         inputRowsBottomUp = false,
49     )
50
51     private fun encodeInternal(
52         rgba: ByteArray,
53         width: Int,
54         height: Int,
55         output: File,
56         lossless: Boolean,
57         inputRowsBottomUp: Boolean,
58     ) {
59         require(width > 0 && height > 0) { "Thumbnail dimensions must be positive" }
60         val expectedByteCount = width * height * RGBA_BYTES_PER_PIXEL
61         require(rgba.size == expectedByteCount) {
62             "RGBA byte count ${rgba.size} does not match ${width}x$height"
63         }
64
65         val pixels = IntArray(width * height)
66         for (bitmapY in 0 until height) {
67             // Bitmap begins at the top; glReadPixels begins at the bottom.
68             val sourceY = if (inputRowsBottomUp) height - 1 - bitmapY else bitmapY
69             var source = sourceY * width * RGBA_BYTES_PER_PIXEL
70             val destination = bitmapY * width
71             for (x in 0 until width) {
72                 val redLinear = (rgba[source++].toInt() and 0xFF) / 255f
73                 val greenLinear = (rgba[source++].toInt() and 0xFF) / 255f
74                 val blueLinear = (rgba[source++].toInt() and 0xFF) / 255f
75                 val alpha = rgba[source++].toInt() and 0xFF
76                 val red = (linearToSrgb(redLinear) * 255f).roundToInt().coerceIn(0, 255)
77                 val green = (linearToSrgb(greenLinear) * 255f).roundToInt().coerceIn(0, 255)
78                 val blue = (linearToSrgb(blueLinear) * 255f).roundToInt().coerceIn(0, 255)
79                 pixels[destination + x] =
80                     (alpha shl 24) or (red shl 16) or (green shl 8) or blue
81             }
82         }
83
84         output.parentFile?.mkdirs()
85         val bitmap = Bitmap.createBitmap(width, height, Bitmap.Config.ARGB_8888)
86         try {
87             bitmap.setPixels(pixels, 0, width, 0, width, height)
88             output.outputStream().use { stream ->
89                 check(bitmap.compress(webpFormat(lossless), quality(lossless), stream)) {
90                     "WebP encoding failed for ${output.absolutePath}"
91                 }
92             }
93         }
94     }
95 }

```

```

91         }
92     }
93 } finally {
94     bitmap.recycle()
95 }
96 }
97
98 private fun webpFormat(lossless: Boolean): Bitmap.CompressFormat = when {
99     lossless && Build.VERSION.SDK_INT >= Build.VERSION_CODES.R ->
100         Bitmap.CompressFormat.WEBP_LOSSLESS
101     !lossless && Build.VERSION.SDK_INT >= Build.VERSION_CODES.R ->
102         Bitmap.CompressFormat.WEBP_LOSSY
103     else -> Bitmap.CompressFormat.WEBP
104 }
105
106 private fun quality(lossless: Boolean): Int = if (lossless) 100 else PROJECT_PREVIEW_QUALITY
107
108 private fun linearToSrgb(value: Float): Float {
109     val linear = value.coerceIn(0f, 1f)
110     return if (linear <= 0.0031308f) linear * 12.92f
111         else (1.055 * linear.toDouble().pow(1.0 / 2.4) - 0.055).toFloat()
112 }
113
114 private companion object {
115     const val RGBA_BYTES_PER_PIXEL = 4
116     const val PROJECT_PREVIEW_QUALITY = 88
117 }
118 }

```

82. app/src/main/java/com/wetinknext/engine/thumbnail/ThumbnailPreviewFiles.kt

```

1 package com.wetinknext.engine.thumbnail
2
3 import java.io.File
4 import java.io.IOException
5 import java.nio.file.AtomicMoveNotSupportedException
6 import java.nio.file.Files
7 import java.nio.file.StandardCopyOption
8
9 /** Cache-file contract shared by preview restoration and the GL build scheduler. */
10 object ThumbnailPreviewFiles {
11     fun layerPreviewFile(outputDirectory: File, layerId: Long): File =
12         File(File(outputDirectory, LAYER_PREVIEW_DIRECTORY), "$layerId.webp")
13
14     /**
15      * Restores previews unpacked from a .wetink container to cache atomically.
16      * It deliberately performs no bitmap decoding, so this work remains cheap
17      * and safe to execute before the GL session is ready.
18      */
19     fun restoreLayerPreviews(
20         outputDirectory: File,
21         previews: Map<Long, ByteArray>,
22     ): Map<Long, File> = previews.mapNotNull { (layerId, bytes) ->
23         if (bytes.isEmpty()) return@mapNotNull null
24         val target = layerPreviewFile(outputDirectory, layerId)
25         val parent = target.parentFile ?: return@mapNotNull null
26         if (!parent.exists() && !parent.mkdirs()) {
27             throw IOException("Cannot create preview directory: ${parent.path}")
28         }
29         val temporary = File(parent, ".${target.name}.restore.tmp")
30         try {
31             temporary.outputStream().use { it.write(bytes) }
32             publish(temporary, target)
33             layerId to target
34         } finally {
35             if (temporary.exists()) temporary.delete()
36         }
37     }.toMap()
38
39     private fun publish(temporary: File, destination: File) {
40         try {
41             Files.move(
42                 temporary.toPath(),
43                 destination.toPath(),
44                 StandardCopyOption.ATOMIC_MOVE,
45                 StandardCopyOption.REPLACE_EXISTING,
46             )
47         } catch (_: AtomicMoveNotSupportedException) {
48             Files.move(
49                 temporary.toPath(),
50                 destination.toPath(),
51                 StandardCopyOption.REPLACE_EXISTING,
52             )
53         }
54     }
55
56     private const val LAYER_PREVIEW_DIRECTORY = "previews"
57 }

```

83. app/src/main/java/com/wetinknext/engine/thumbnail/ThumbnailRenderer.kt

```

1  package com.wetinknext.engine.thumbnail
2
3  import android.opengl.GLES30
4  import com.wetinknext.engine.canvas.Compositor
5  import com.wetinknext.engine.canvas.LayerStack
6  import com.wetinknext.engine.canvas.PaintLayer
7  import com.wetinknext.engine.gl.CanvasGeometry
8  import com.wetinknext.engine.gl.GlCheck
9  import com.wetinknext.engine.gl.RenderTarget
10 import java.nio.ByteBuffer
11 import java.nio.ByteOrder
12
13 /**
14  * GL-thread renderer for document thumbnails.
15  *
16  * It renders directly from document render targets, never from the surface
17  * framebuffer. Camera position, zoom, editor chrome and Android system UI can
18  * therefore never leak into a preview.
19  */
20 class ThumbnailRenderer {
21     private val target = RenderTarget()
22     private val compositor = Compositor()
23     private var geometry: CanvasGeometry? = null
24     private var geometryWidth = 0
25     private var geometryHeight = 0
26     private val canvasToClip = FloatArray(16)
27     private var readBuffer: ByteBuffer? = null
28     private var created = false
29
30     /**
31      * Returns top-to-bottom RGBA8 bytes for one layer.
32      *
33      * A hidden layer still receives a preview of its own pixels; the visibility
34      * flag belongs to project composition, whereas a layer thumbnail is used to
35      * identify that layer in the layers panel. Layer opacity is preserved.
36      */
37     fun renderLayer(
38         layer: PaintLayer,
39         outputWidth: Int,
40         outputHeight: Int,
41     ): ByteArray {
42         GlCheck.checkOnGUIThread()
43         require(outputWidth > 0 && outputHeight > 0) { "Thumbnail size must be positive" }
44         if (!layer.created || layer.target.width <= 0 || layer.target.height <= 0) {
45             return ByteArray(outputWidth * outputHeight * RGBA_BYTES_PER_PIXEL)
46         }
47
48         prepare(
49             canvasWidth = layer.target.width,
50             canvasHeight = layer.target.height,
51             outputWidth = outputWidth,
52             outputHeight = outputHeight,
53         )
54         target.clear(0f, 0f, 0f, 0f)
55         target.bind()
56         GLES30.glViewport(0, 0, outputWidth, outputHeight)
57         try {
58             compositor.renderLayer(
59                 geometry = checkNotNull(geometry),
60                 layer = layer,
61                 canvasWidth = layer.target.width,
62                 canvasHeight = layer.target.height,
63                 canvasToClip = canvasToClip,
64             )
65             return readTopDownRgba(outputWidth, outputHeight)
66         } finally {
67             GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
68         }
69     }
70
71     /**
72      * Returns a top-to-bottom RGBA8 image of all visible layers, from the
73      * bottom of [layers] to the top. The compositor applies every layer's
74      * opacity and follows the same blend-policy path as the on-canvas view.
75      */
76     fun renderProject(
77         layers: LayerStack,
78         outputWidth: Int,
79         outputHeight: Int,
80     ): ByteArray {
81         GlCheck.checkOnGUIThread()
82         require(outputWidth > 0 && outputHeight > 0) { "Thumbnail size must be positive" }
83         require(layers.canvasWidth > 0 && layers.canvasHeight > 0) {
84             "Cannot render a thumbnail for an empty canvas"
85         }
86
87         prepare(
88             canvasWidth = layers.canvasWidth,
89             canvasHeight = layers.canvasHeight,
90             outputWidth = outputWidth,

```

```

91         outputHeight = outputHeight,
92     )
93     target.clear(0f, 0f, 0f, 0f)
94     target.bind()
95     GLES30.glViewport(0, 0, outputWidth, outputHeight)
96     try {
97         compositor.render(
98             geometry = checkNotNull(geometry),
99             layers = layers,
100             activeLayerId = NO_ACTIVE_LAYER,
101             strokeTextureId = 0,
102             strokeErase = false,
103             canvasToClip = canvasToClip,
104             strokeOpacity = 1f,
105         )
106         return readTopDownRgba(outputWidth, outputHeight)
107     } finally {
108         GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
109     }
110 }
111
112 /** Releases GL objects. Call while the context is current. */
113 fun release() {
114     GlCheck.checkOnGThread()
115     readBuffer = null
116     target.release()
117     geometry?.release()
118     geometry = null
119     geometryWidth = 0
120     geometryHeight = 0
121     if (created) compositor.release()
122     created = false
123 }
124
125 private fun prepare(
126     canvasWidth: Int,
127     canvasHeight: Int,
128     outputWidth: Int,
129     outputHeight: Int,
130 ) {
131     if (!created) {
132         compositor.create()
133         created = true
134     }
135     if (geometry == null || geometryWidth != canvasWidth || geometryHeight != canvasHeight) {
136         geometry?.release()
137         geometry = CanvasGeometry().also { it.create(canvasWidth, canvasHeight) }
138         geometryWidth = canvasWidth
139         geometryHeight = canvasHeight
140     }
141     if (target.width != outputWidth || target.height != outputHeight) {
142         target.create(outputWidth, outputHeight, preferHalfFloat = false)
143     }
144     buildAspectFitMatrix(canvasWidth, canvasHeight, outputWidth, outputHeight, canvasToClip)
145 }
146
147 private fun readTopDownRgba(width: Int, height: Int): ByteArray {
148     val rowBytes = width * RGBA_BYTES_PER_PIXEL
149     val byteCount = rowBytes * height
150     val buffer = obtainReadBuffer(byteCount)
151     buffer.clear()
152     GLES30.glPixelStorei(GLES30.GL_PACK_ALIGNMENT, 1)
153     try {
154         GLES30.glReadPixels(
155             0,
156             0,
157             width,
158             height,
159             GLES30.GL_RGBA,
160             GLES30.GL_UNSIGNED_BYTE,
161             buffer,
162         )
163         GlCheck.noError("ThumbnailRenderer glReadPixels")
164
165         val pixels = ByteArray(byteCount)
166         for (destinationRow in 0 until height) {
167             val sourceOffset = (height - 1 - destinationRow) * rowBytes
168             buffer.position(sourceOffset)
169             buffer.get(pixels, destinationRow * rowBytes, rowBytes)
170         }
171         return pixels
172     } finally {
173         GLES30.glPixelStorei(GLES30.GL_PACK_ALIGNMENT, 4)
174     }
175 }
176
177 private fun obtainReadBuffer(size: Int): ByteBuffer {
178     val current = readBuffer
179     if (current != null && current.capacity() >= size) return current
180     return ByteBuffer.allocateDirect(size)
181         .order(ByteOrder.nativeOrder())
182         .also { readBuffer = it }

```

```

183     }
184
185     private fun buildAspectFitMatrix(
186         canvasWidth: Int,
187         canvasHeight: Int,
188         outputWidth: Int,
189         outputHeight: Int,
190         out: FloatArray,
191     ) {
192         val canvasAspect = canvasWidth.toFloat() / canvasHeight.toFloat()
193         val outputAspect = outputWidth.toFloat() / outputHeight.toFloat()
194         val scaleX = if (canvasAspect < outputAspect) canvasAspect / outputAspect else 1f
195         val scaleY = if (canvasAspect > outputAspect) outputAspect / canvasAspect else 1f
196
197         out.fill(0f)
198         out[0] = 2f * scaleX / canvasWidth.toFloat()
199         out[5] = 2f * scaleY / canvasHeight.toFloat()
200         out[10] = 1f
201         out[12] = -scaleX
202         out[13] = -scaleY
203         out[15] = 1f
204     }
205
206     private companion object {
207         const val RGBA_BYTES_PER_PIXEL = 4
208         const val NO_ACTIVE_LAYER = -1L
209     }
210 }

```


84. app/src/main/java/com/wetinknext/engine/undo/DeflateTileCompressor.kt

```

1  package com.wetinknext.engine.undo
2
3  import java.io.ByteArrayOutputStream
4  import java.util.zip.Deflater
5  import java.util.zip.Inflater
6
7  class DeflateTileCompressor(
8      private val level: Int = Deflater.BEST_SPEED,
9  ) : TileCompressor {
10
11      override fun compress(data: ByteArray): ByteArray {
12          val deflater = Deflater(level)
13          return try {
14              deflater.setInput(data)
15              deflater.finish()
16
17              val output = ByteArrayOutputStream(data.size)
18              val buffer = ByteArray(16 * 1024)
19
20              while (!deflater.finished()) {
21                  val count = deflater.deflate(buffer)
22                  output.write(buffer, 0, count)
23              }
24
25              output.toByteArray()
26          } finally {
27              deflater.end()
28          }
29      }
30
31      override fun decompress(
32          data: ByteArray,
33          expectedSize: Int,
34      ): ByteArray {
35          val inflater = Inflater()
36          return try {
37              inflater.setInput(data)
38
39              val output = ByteArrayOutputStream(expectedSize)
40              val buffer = ByteArray(16 * 1024)
41
42              while (!inflater.finished()) {
43                  val count = inflater.inflate(buffer)
44                  if (count == 0 && inflater.finished()) break
45                  check(count > 0) { "Decompression stalled or data corrupted" }
46                  output.write(buffer, 0, count)
47              }
48
49              output.toByteArray()
50          } finally {
51              inflater.end()
52          }
53      }
54  }

```

85. app/src/main/java/com/wetinknext/engine/undo/RawTileSnapshot.kt

```
1 package com.wetinknext.engine.undo
2
3 /** Uncompressed tile data captured on the GL thread. */
4 class RawTileSnapshot(
5     val coord: TileCoord,
6     val pixelLeft: Int,
7     val pixelTop: Int,
8     val pixelWidth: Int,
9     val pixelHeight: Int,
10    val bytesPerPixel: Int,
11    val rawBytes: ByteArray,
12 ) {
13     val rawSize: Int get() = rawBytes.size
14
15     fun compress(compressor: TileCompressor): TileSnapshot {
16         return TileSnapshot(
17             coord = coord,
18             pixelLeft = pixelLeft,
19             pixelTop = pixelTop,
20             pixelWidth = pixelWidth,
21             pixelHeight = pixelHeight,
22             bytesPerPixel = bytesPerPixel,
23             storedData = compressor.compress(rawBytes),
24             compressor = compressor,
25         )
26     }
27 }
```

86. app/src/main/java/com/wetinknext/engine/undo/TileCompressor.kt

```
1 package com.wetinknext.engine.undo
2
3 /**
4  * Extension point for P6.5 compression. P6 uses the identity implementation,
5  * so the 96 MB budget reflects the exact bytes that are currently retained.
6  */
7 interface TileCompressor {
8     fun compress(data: ByteArray): ByteArray
9
10    fun decompress(data: ByteArray, expectedSize: Int): ByteArray
11 }
12
13 /** P6 storage policy: no compression and no extra byte-array allocation. */
14 object IdentityTileCompressor : TileCompressor {
15     override fun compress(data: ByteArray): ByteArray = data
16
17     override fun decompress(data: ByteArray, expectedSize: Int): ByteArray {
18         check(data.size == expectedSize) {
19             "Raw tile has ${data.size} bytes, expected $expectedSize"
20         }
21         return data
22     }
23 }
```

87. app/src/main/java/com/wetinknext/engine/undo/TileSnapshot.kt

```
1 package com.wetinknext.engine.undo
2
3 data class TileCoord(val tx: Int, val ty: Int)
4
5 /** One full 256 px tile (or an edge tile) in the source layer's native format. */
6 class TileSnapshot(
7     val coord: TileCoord,
8     val pixelLeft: Int,
9     val pixelTop: Int,
10    val pixelWidth: Int,
11    val pixelHeight: Int,
12    val bytesPerPixel: Int,
13    private val storedData: ByteArray,
14    private val compressor: TileCompressor = IdentityTileCompressor,
15 ) {
16     val memorySize: Int get() = storedData.size
17     val rawSize: Int get() = pixelWidth * pixelHeight * bytesPerPixel
18
19     /** Returns raw bytes. */
20     fun decompress(): ByteArray = compressor.decompress(storedData, rawSize)
21
22     fun dispose() {
23         // P6 keeps heap ByteArrays; a later off-heap implementation can release here.
24     }
25
26     companion object {
27         const val TILE_SIZE = 256
28         const val BYTES_PER_PIXEL_RGBA16F = 8
29         const val BYTES_PER_PIXEL_RGBA8 = 4
30     }
31 }
```

88. app/src/main/java/com/wetinknext/engine/undo/TileSnapshotCapture.kt

```

1 package com.wetinknext.engine.undo
2 import android.opengl.GLES30
3 import android.util.Log
4 import com.wetinknext.BuildConfig
5 import com.wetinknext.engine.gl.GlCheck
6 import com.wetinknext.engine.gl.RenderTarget
7 import java.nio.ByteBuffer
8 import java.nio.ByteOrder
9 object TileSnapshotCapture {
10     private var reusable: ByteBuffer? = null
11
12     /**
13      * Returns the number of whole undo tiles intersecting [bounds].
14      *
15      * This is intentionally CPU-only: callers can use it to flag expensive
16      * readback before calling [capture], without changing undo semantics.
17      */
18     fun countTiles(target: RenderTarget, bounds: IntArray): Int {
19         require(bounds.size >= 4)
20
21         val left = bounds[0].coerceIn(0, target.width)
22         val top = bounds[1].coerceIn(0, target.height)
23         val right = bounds[2].coerceIn(0, target.width)
24         val bottom = bounds[3].coerceIn(0, target.height)
25         if (right <= left || bottom <= top) return 0
26
27         val firstTileX = left / TileSnapshot.TILE_SIZE
28         val lastTileX = (right - 1) / TileSnapshot.TILE_SIZE
29         val firstTileY = top / TileSnapshot.TILE_SIZE
30         val lastTileY = (bottom - 1) / TileSnapshot.TILE_SIZE
31         return (lastTileX - firstTileX + 1) *
32             (lastTileY - firstTileY + 1)
33     }
34
35     /** Captures every 256 px tile intersecting [bounds] = left, top, right, bottom. */
36     fun capture(target: RenderTarget, bounds: IntArray): List<RawTileSnapshot> {
37         GlCheck.checkOnGLThread()
38         require(target.framebufferId != 0)
39         require(target.textureId != 0)
40         require(bounds.size >= 4)
41         val left = bounds[0].coerceIn(0, target.width)
42         val top = bounds[1].coerceIn(0, target.height)
43         val right = bounds[2].coerceIn(0, target.width)
44         val bottom = bounds[3].coerceIn(0, target.height)
45         if (right <= left || bottom <= top) return emptyList()
46
47         if (BuildConfig.DEBUG) {
48             Log.d(
49                 TAG,
50                 "capture target=${target.textureId} fbo=${target.framebufferId} " +
51                 "canvasBounds=[$left,$top,$right,$bottom] " +
52                 "target=${target.width}x${target.height}",
53             )
54         }
55
56         val bytesPerPixel = if (target.usesHalfFloat) {
57             TileSnapshot.BYTES_PER_PIXEL_RGBA16F
58         } else {
59             TileSnapshot.BYTES_PER_PIXEL_RGBA8
60         }
61         val glType = if (target.usesHalfFloat) GLES30.GL_HALF_FLOAT else GLES30.GL_UNSIGNED_BYTE
62         val result = ArrayList<RawTileSnapshot>()
63         target.bind()
64         GLES30.glPixelStorei(GLES30.GL_PACK_ALIGNMENT, 1)
65         try {
66             for (tileY in top / TileSnapshot.TILE_SIZE..(bottom - 1) / TileSnapshot.TILE_SIZE) {
67                 for (tileX in left / TileSnapshot.TILE_SIZE..(right - 1) / TileSnapshot.TILE_SIZE) {
68                     val pixelLeft = tileX * TileSnapshot.TILE_SIZE
69                     // Tile coordinates are document/canvas coordinates (Y grows down).
70                     val canvasTop = tileY * TileSnapshot.TILE_SIZE
71                     val pixelWidth = minOf(TileSnapshot.TILE_SIZE, target.width - pixelLeft)
72                     val pixelHeight = minOf(TileSnapshot.TILE_SIZE, target.height - canvasTop)
73                     // buildCanvasToFbo maps canvas y=0 to the FBO's bottom row.
74                     // Canvas tile coordinates therefore already equal GL's bottom Y.
75                     val glBottom = canvasTop
76                     if (BuildConfig.DEBUG) {
77                         Log.d(
78                             TAG,
79                             "capture tile=($tileX,$tileY) " +
80                             "canvas=[$pixelLeft,$canvasTop,$pixelWidth,$pixelHeight] " +
81                             "gl=[$pixelLeft,$glBottom,$pixelWidth,$pixelHeight]",
82                         )
83                     }
84                     val byteCount = pixelWidth * pixelHeight * bytesPerPixel
85                     val buffer = obtainBuffer(byteCount)
86                     buffer.clear()
87                     GLES30.glReadPixels(
88                         pixelLeft, glBottom, pixelWidth, pixelHeight,
89                         GLES30.GL_RGBA, glType, buffer,
90                     )

```

```

91         if (BuildConfig.DEBUG) {
92             val error = GLES30.glGetError()
93             check(error == GLES30.GL_NO_ERROR) {
94                 "TileSnapshotCapture.glReadPixels failed: 0x${error.toString(16)}"
95             }
96         }
97         buffer.rewind()
98         val rawBytes = ByteArray(byteCount)
99         buffer.get(rawBytes)
100         result += RawTileSnapshot(
101             coord = TileCoord(tileX, tileY),
102             pixelLeft = pixelLeft,
103             pixelTop = canvasTop,
104             pixelWidth = pixelWidth,
105             pixelHeight = pixelHeight,
106             bytesPerPixel = bytesPerPixel,
107             rawBytes = rawBytes,
108         )
109     }
110 }
111     return result
112 } finally {
113     GLES30.glPixelStorei(GLES30.GL_PACK_ALIGNMENT, 4)
114     GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
115 }
116 }
117
118 private fun obtainBuffer(size: Int): ByteBuffer {
119     val current = reusable
120     if (current != null && current.capacity() >= size) return current
121     return ByteBuffer.allocateDirect(size).order(ByteOrder.nativeOrder()).also { reusable = it }
122 }
123
124 private const val TAG = "TileUndo"
125 }

```

89. app/src/main/java/com/wetinknext/engine/undo/TileSnapshotRestore.kt

```

1  package com.wetinknext.engine.undo
2
3  import android.opengl.GLES30
4  import android.util.Log
5  import com.wetinknext.BuildConfig
6  import com.wetinknext.engine.gl.GlCheck
7  import com.wetinknext.engine.gl.RenderTarget
8  import java.nio.ByteBuffer
9  import java.nio.ByteOrder
10
11 /** Restores snapshot tiles into an already-created layer texture on the GL thread. */
12 object TileSnapshotRestore {
13     private var reusableBuffer: ByteBuffer? = null
14
15     fun restore(target: RenderTarget, tiles: List<TileSnapshot>): Boolean {
16         GlCheck.checkOnGLThread()
17         if (target.textureId == 0) return false
18         if (tiles.isEmpty()) return true
19
20         // Discard an unrelated previous error, then verify every upload below.
21         GLES30.glGetError()
22         GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
23         GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, target.textureId)
24         GLES30.glPixelStorei(GLES30.GL_UNPACK_ALIGNMENT, 1)
25         try {
26             for (tile in tiles) {
27                 if (!isValidTile(target, tile)) return false
28                 val data = tile.decompress()
29                 if (data.size != tile.rawSize) return false
30
31                 val glType = when (tile.bytesPerPixel) {
32                     TileSnapshot.BYTES_PER_PIXEL_RGBA16F -> GLES30.GL_HALF_FLOAT
33                     TileSnapshot.BYTES_PER_PIXEL_RGBA8 -> GLES30.GL_UNSIGNED_BYTE
34                     else -> return false
35                 }
36                 val buffer = obtainBuffer(data.size)
37                 buffer.clear()
38                 buffer.put(data)
39                 buffer.position(0)
40
41                 // buildCanvasToFbo maps canvas y=0 to the FBO's bottom row.
42                 val glBottom = tile.pixelTop
43                 if (BuildConfig.DEBUG) {
44                     Log.d(TAG, "restore tex=${target.textureId} tile=(${tile.coord.tx},${tile.coord.ty}) " +
45                         "canvas=[${tile.pixelLeft},${tile.pixelTop},${tile.pixelWidth},${tile.pixelHeight}]")
46                 }
47                 GLES30.glTexSubImage2D(
48                     GLES30.GL_TEXTURE_2D, 0, tile.pixelLeft, glBottom,
49                     tile.pixelWidth, tile.pixelHeight, GLES30.GL_RGBA, glType, buffer,
50                 )
51                 if (GLES30.glGetError() != GLES30.GL_NO_ERROR) return false
52             }
53             return true
54         } catch (error: Throwable) {
55             if (BuildConfig.DEBUG) Log.e(TAG, "Restore failed", error)
56             return false
57         } finally {
58             GLES30.glPixelStorei(GLES30.GL_UNPACK_ALIGNMENT, 4)
59             GLES30.glBindTexture(GLES30.GL_TEXTURE_2D, 0)
60             GLES30.glActiveTexture(GLES30.GL_TEXTURE0)
61             GLES30.glBindFramebuffer(GLES30.GL_FRAMEBUFFER, 0)
62         }
63     }
64
65     private fun isValidTile(target: RenderTarget, tile: TileSnapshot): Boolean {
66         if (tile.pixelWidth <= 0 || tile.pixelHeight <= 0) return false
67         if (tile.pixelLeft < 0 || tile.pixelTop < 0) return false
68         if (tile.pixelLeft + tile.pixelWidth > target.width ||
69             tile.pixelTop + tile.pixelHeight > target.height) return false
70         val expectedBytesPerPixel = if (target.usesHalfFloat) {
71             TileSnapshot.BYTES_PER_PIXEL_RGBA16F
72         } else {
73             TileSnapshot.BYTES_PER_PIXEL_RGBA8
74         }
75         return tile.bytesPerPixel == expectedBytesPerPixel
76     }
77
78     private fun obtainBuffer(size: Int): ByteBuffer {
79         val current = reusableBuffer
80         if (current != null && current.capacity() >= size) return current
81         return ByteBuffer.allocateDirect(size).order(ByteOrder.nativeOrder()).also { reusableBuffer = it }
82     }
83
84     private const val TAG = "TileUndo"
85 }

```

90. app/src/main/java/com/wetinknext/engine/undo/UndoEntry.kt

```
1 package com.wetinknext.engine.undo
2
3 /** One reversible history operation, retaining exact states from before and after its merge. */
4 data class UndoEntry(
5     val layerId: Long,
6     val beforeTiles: List<TileSnapshot>,
7     val afterTiles: List<TileSnapshot>,
8     val operation: UndoOperationType = UndoOperationType.TILE_EDIT,
9     val tag: String = "stroke",
10 ) {
11     val memorySize: Int
12     get() = beforeTiles.sumOf(TileSnapshot::memorySize) + afterTiles.sumOf(TileSnapshot::memorySize)
13
14     fun dispose() {
15         beforeTiles.forEach(TileSnapshot::dispose)
16         afterTiles.forEach(TileSnapshot::dispose)
17     }
18 }
```


91. app/src/main/java/com/wetinknext/engine/undo/UndoManager.kt

```

1 package com.wetinknext.engine.undo
2
3 /**
4  * Pure memory-bounded history. GPU reads and texture restores deliberately live
5  * in EngineRenderer, keeping this class deterministic and unit-testable.
6  */
7 class UndoManager(
8     private val maxMemoryBytes: Long = DEFAULT_MAX_MEMORY_BYTES,
9     private val maxSteps: Int = DEFAULT_MAX_STEPS,
10 ) {
11     private val undoStack = ArrayDeque<UndoEntry>()
12     private val redoStack = ArrayDeque<UndoEntry>()
13     private var undoMemoryBytes = 0L
14     private var redoMemoryBytes = 0L
15
16     val canUndo: Boolean get() = undoStack.isNotEmpty()
17     val canRedo: Boolean get() = redoStack.isNotEmpty()
18     val memoryBytes: Long get() = undoMemoryBytes + redoMemoryBytes
19     val undoCount: Int get() = undoStack.size
20     val redoCount: Int get() = redoStack.size
21
22     /** Records a new operation and invalidates the alternate redo history. */
23     fun push(entry: UndoEntry) {
24         undoStack.addLast(entry)
25         undoMemoryBytes += entry.memorySize
26         clearRedo()
27         trimToLimits()
28     }
29
30     /** Returns the candidate without changing history; restore it before committing. */
31     fun peekUndo(): UndoEntry? = undoStack.lastOrNull()
32
33     /** Moves the exact current undo candidate to redo after a successful restore. */
34     fun commitUndo(entry: UndoEntry): Boolean {
35         if (undoStack.lastOrNull() != entry) return false
36         undoStack.removeLast()
37         undoMemoryBytes -= entry.memorySize
38         redoStack.addLast(entry)
39         redoMemoryBytes += entry.memorySize
40         trimToLimits()
41         return true
42     }
43
44     /** Discards a no-longer-restorable undo record without moving it to redo. */
45     fun dropUndo(entry: UndoEntry): Boolean {
46         if (undoStack.lastOrNull() != entry) return false
47         undoStack.removeLast()
48         undoMemoryBytes -= entry.memorySize
49         entry.dispose()
50         return true
51     }
52
53     /** Returns the candidate without changing history; restore it before committing. */
54     fun peekRedo(): UndoEntry? = redoStack.lastOrNull()
55
56     /** Moves the exact current redo candidate to undo after a successful restore. */
57     fun commitRedo(entry: UndoEntry): Boolean {
58         if (redoStack.lastOrNull() != entry) return false
59         redoStack.removeLast()
60         redoMemoryBytes -= entry.memorySize
61         undoStack.addLast(entry)
62         undoMemoryBytes += entry.memorySize
63         trimToLimits()
64         return true
65     }
66
67     /** Discards a no-longer-restorable redo record without moving it to undo. */
68     fun dropRedo(entry: UndoEntry): Boolean {
69         if (redoStack.lastOrNull() != entry) return false
70         redoStack.removeLast()
71         redoMemoryBytes -= entry.memorySize
72         entry.dispose()
73         return true
74     }
75
76     fun clearRedo() {
77         while (redoStack.isNotEmpty()) {
78             val entry = redoStack.removeLast()
79             redoMemoryBytes -= entry.memorySize
80             entry.dispose()
81         }
82         redoMemoryBytes = 0L
83     }
84
85     fun clear() {
86         while (undoStack.isNotEmpty()) undoStack.removeLast().dispose()
87         undoMemoryBytes = 0L
88         clearRedo()
89     }
90
91

```

```

91  /** Removes history that can no longer be restored after deleting a layer. */
92  fun removeEntriesForLayer(layerId: Long) {
93      removeEntriesForLayer(undoStack, layerId) { entry -> undoMemoryBytes -= entry.memorySize }
94      removeEntriesForLayer(redoStack, layerId) { entry -> redoMemoryBytes -= entry.memorySize }
95      undoMemoryBytes = undoMemoryBytes.coerceAtLeast(0L)
96      redoMemoryBytes = redoMemoryBytes.coerceAtLeast(0L)
97  }
98
99  private fun removeEntriesForLayer(
100      stack: ArrayDeque<UndoEntry>,
101      layerId: Long,
102      subtractMemory: (UndoEntry) -> Unit,
103  ) {
104      if (stack.isEmpty()) return
105      val retained = ArrayDeque<UndoEntry>(stack.size)
106      while (stack.isNotEmpty()) {
107          val entry = stack.removeFirst()
108          if (entry.layerId == layerId) {
109              subtractMemory(entry)
110              entry.dispose()
111          } else {
112              retained.addLast(entry)
113          }
114      }
115      stack.addAll(retained)
116  }
117
118  private fun trimToLimits() {
119      while (undoStack.size > maxSteps) evictOldestUndo()
120      while (redoStack.size > maxSteps) evictOldestRedo()
121      while (memoryBytes > maxMemoryBytes && undoStack.size + redoStack.size > 1) {
122          when {
123              redoStack.size > 1 && redoMemoryBytes >= undoMemoryBytes -> evictOldestRedo()
124              undoStack.size > 1 -> evictOldestUndo()
125              redoStack.size > 1 -> evictOldestRedo()
126              else -> return
127          }
128      }
129  }
130
131  private fun evictOldestUndo() {
132      val entry = undoStack.removeFirstOrNull() ?: return
133      undoMemoryBytes -= entry.memorySize
134      entry.dispose()
135  }
136
137  private fun evictOldestRedo() {
138      val entry = redoStack.removeFirstOrNull() ?: return
139      redoMemoryBytes -= entry.memorySize
140      entry.dispose()
141  }
142
143  companion object {
144      const val DEFAULT_MAX_MEMORY_BYTES = 96L * 1024L * 1024L
145      const val DEFAULT_MAX_STEPS = 50
146  }
147 }

```

92. app/src/main/java/com/wetinknext/engine/undo/UndoOperationType.kt

```
1 package com.wetinknext.engine.undo
2
3 /**
4  * A lightweight operation discriminator for the current tile-snapshot history.
5  * Future history entries can replace this with full typed operations without
6  * changing existing stored tile edits.
7  */
8 enum class UndoOperationType {
9     TILE_EDIT,
10    CLEAR_LAYER,
11    LAYER_PROPERTIES,
12 }
```

93. app/src/main/java/com/wetinknext/ui/animation/AnimationSettingsMenu.kt

```

1  package com.wetinknext.ui.animation
2
3  import androidx.compose.foundation.background
4  import androidx.compose.foundation.border
5  import androidx.compose.foundation.clickable
6  import androidx.compose.foundation.layout.*
7  import androidx.compose.foundation.rememberScrollState
8  import androidx.compose.foundation.shape.CircleShape
9  import androidx.compose.foundation.verticalScroll
10 import androidx.compose.foundation.shape.RoundedCornerShape
11 import androidx.compose.material3.*
12 import androidx.compose.runtime.*
13 import androidx.compose.ui.Alignment
14 import androidx.compose.ui.Modifier
15 import androidx.compose.ui.draw.clip
16 import androidx.compose.ui.graphics.Color
17 import androidx.compose.ui.graphics.toArgb
18 import androidx.compose.ui.text.font.FontWeight
19 import androidx.compose.ui.unit.dp
20 import androidx.compose.ui.unit.sp
21 import com.wetinknext.domain.animation.AnimationDocument
22 import com.wetinknext.domain.animation.AnimationPlaybackMode
23 import com.wetinknext.domain.animation.OnionSkinSettings
24 import com.wetinknext.ui.theme.AppTheme
25
26 @Composable
27 fun AnimationSettingsMenu(
28     theme: AppTheme,
29     document: AnimationDocument,
30     onDocumentChange: (AnimationDocument) -> Unit,
31     onDismiss: () -> Unit,
32     modifier: Modifier = Modifier
33 ) {
34     Box(
35         modifier = modifier
36             .width(280.dp)
37             .heightIn(max = 360.dp)
38             .clip(RoundedCornerShape(24.dp))
39             .background(theme.panelBg.copy(alpha = 0.98f))
40             .border(1.dp, theme.panelStroke, RoundedCornerShape(24.dp))
41             .padding(16.dp)
42     ) {
43         Column(
44             modifier = Modifier.verticalScroll(rememberScrollState()),
45             verticalArrangement = Arrangement.spacedBy(10.dp),
46         ) {
47             Text("Настройки анимации", color = theme.textPrimary, fontSize = 16.sp, fontWeight = FontWeight.Bold)
48
49             // Playback Mode
50             Column(verticalArrangement = Arrangement.spacedBy(8.dp)) {
51                 Text("Режим", color = theme.textSecondary, fontSize = 12.sp)
52                 Row(
53                     modifier = Modifier.fillMaxWidth(),
54                     horizontalArrangement = Arrangement.spacedBy(8.dp)
55                 ) {
56                     PlaybackModeButton("Цикл", AnimationPlaybackMode.LOOP, document.playbackMode, theme) {
57                         onDocumentChange(document.copy(playbackMode = it))
58                     }
59                     PlaybackModeButton("Туда-сюда", AnimationPlaybackMode.PING_PONG, document.playbackMode, theme) {
60                         onDocumentChange(document.copy(playbackMode = it))
61                     }
62                     PlaybackModeButton("Один раз", AnimationPlaybackMode.ONE_SHOT, document.playbackMode, theme) {
63                         onDocumentChange(document.copy(playbackMode = it))
64                     }
65                 }
66             }
67
68             // FPS
69             Column(verticalArrangement = Arrangement.spacedBy(4.dp)) {
70                 Row(horizontalArrangement = Arrangement.SpaceBetween, modifier = Modifier.fillMaxWidth()) {
71                     Text("Скорость (FPS)", color = theme.textSecondary, fontSize = 12.sp)
72                     Text("${document.framesPerSecond}", color = theme.accent, fontSize = 12.sp, fontWeight = FontWeight.Bold)
73                 }
74                 Slider(
75                     value = document.framesPerSecond.toFloat(),
76                     onValueChange = { onDocumentChange(document.copy(framesPerSecond = it.toInt())) },
77                     valueRange = 1f..60f,
78                     colors = SliderDefaults.colors(thumbColor = theme.accent, activeTrackColor = theme.accent)
79                 )
80             }
81
82             HorizontalDivider(color = theme.panelStroke)
83
84             // Onion Skin Settings
85             Row(
86                 modifier = Modifier.fillMaxWidth(),
87                 horizontalArrangement = Arrangement.SpaceBetween,
88                 verticalAlignment = Alignment.CenterVertically
89             ) {
90                 Text("Калька (Onion Skin)", color = theme.textPrimary, fontSize = 14.sp)

```

```

91         Switch(
92             checked = document.onionSkin.enabled,
93             onCheckedChange = { onDocumentChange(document.copy(onionSkin = document.onionSkin.copy(enabled = it))) },
94             colors = SwitchDefaults.colors(checkedThumbColor = theme.accent, checkedTrackColor = theme.accent.copy(
alpha = 0.5f))
95         )
96     }
97
98     if (document.onionSkin.enabled) {
99         OnionCountSlider("Предыдущие", document.onionSkin.previousFrames, theme) {
100             onDocumentChange(document.copy(onionSkin = document.onionSkin.copy(previousFrames = it)))
101         }
102         OnionColorPicker(
103             label = "Цвет предыдущих",
104             selectedArgb = document.onionSkin.previousColorArgb,
105             theme = theme,
106             { color ->
107                 onDocumentChange(document.copy(onionSkin = document.onionSkin.copy(previousColorArgb = color.toArgb())))
108             }
109         )
110         OnionCountSlider("Следующие", document.onionSkin.nextFrames, theme) {
111             onDocumentChange(document.copy(onionSkin = document.onionSkin.copy(nextFrames = it)))
112         }
113         OnionColorPicker(
114             label = "Цвет следующих",
115             selectedArgb = document.onionSkin.nextColorArgb,
116             theme = theme,
117             { color ->
118                 onDocumentChange(document.copy(onionSkin = document.onionSkin.copy(nextColorArgb = color.toArgb())))
119             }
120         )
121         Column(verticalArrangement = Arrangement.spacedBy(4.dp)) {
122             Text("Прозрачность", color = theme.textSecondary, fontSize = 12.sp)
123             Slider(
124                 value = document.onionSkin.opacity,
125                 onValueChange = { onDocumentChange(document.copy(onionSkin = document.onionSkin.copy(opacity = it)))
126                 },
127                 valueRange = 0f..1f,
128                 colors = SliderDefaults.colors(thumbColor = theme.accent, activeTrackColor = theme.accent)
129             )
130         }
131     }
132 }
133
134 @Composable
135 private fun RowScope.PlaybackModeButton(
136     label: String,
137     mode: AnimationPlaybackMode,
138     current: AnimationPlaybackMode,
139     theme: AppTheme,
140     onClick: (AnimationPlaybackMode) -> Unit
141 ) {
142     val selected = mode == current
143     Box(
144         modifier = Modifier
145             .weight(1f)
146             .height(32.dp)
147             .clip(RoundedCornerShape(8.dp))
148             .background(if (selected) theme.accent else theme.panelInsetSoft)
149             .clickable { onClick(mode) },
150         contentAlignment = Alignment.Center
151     ) {
152         Text(label, color = if (selected) Color.White else theme.textSecondary, fontSize = 10.sp)
153     }
154 }
155
156 @Composable
157 private fun OnionCountSlider(
158     label: String,
159     value: Int,
160     theme: AppTheme,
161     onValueChange: (Int) -> Unit
162 ) {
163     Column(verticalArrangement = Arrangement.spacedBy(2.dp)) {
164         Row(horizontalArrangement = Arrangement.SpaceBetween, modifier = Modifier.fillMaxWidth()) {
165             Text(label, color = theme.textSecondary, fontSize = 11.sp)
166             Text("$value", color = theme.textPrimary, fontSize = 11.sp)
167         }
168         Slider(
169             value = value.toFloat(),
170             onValueChange = { onValueChange(it.toInt()) },
171             valueRange = 0f..12f,
172             colors = SliderDefaults.colors(thumbColor = theme.accent, activeTrackColor = theme.accent)
173         )
174     }
175 }
176
177 @Composable
178 private fun OnionColorPicker(
179     label: String,
180     selectedArgb: Int,

```

```

181     theme: AppTheme,
182     onColorChange: (Color) -> Unit,
183 ) {
184     val palette = listOf(
185         Color(0xFFFFF4FA3),
186         Color(0xFFFFF7A59),
187         Color(0xFFFFFC857),
188         Color(0xFF57D68D),
189         Color(0xFF4A8DFF),
190         Color(0xFFB079FF),
191     )
192     Column(verticalArrangement = Arrangement.spacedBy(6.dp)) {
193         Text(label, color = theme.textSecondary, fontSize = 12.sp)
194         Row(horizontalArrangement = Arrangement.spacedBy(8.dp)) {
195             palette.forEach { color ->
196                 val selected = color.toArgb() == selectedArgb
197                 Box(
198                     modifier = Modifier
199                         .size(24.dp)
200                         .clip(CircleShape)
201                         .background(color)
202                         .border(
203                             width = if (selected) 2.dp else 1.dp,
204                             color = if (selected) Color.White else theme.panelStroke,
205                             shape = CircleShape,
206                         )
207                     .clickable { onColorChange(color) }
208                 )
209             }
210         }
211     }
212 }

```

94. app/src/main/java/com/wetinknext/ui/animation/AnimationTimelineToolbar.kt

```

1 package com.wetinknext.ui.animation
2
3 import androidx.compose.foundation.Image
4 import androidx.compose.foundation.background
5 import androidx.compose.foundation.border
6 import androidx.compose.foundation.clickable
7 import androidx.compose.foundation.gestures.detectDragGesturesAfterLongPress
8 import androidx.compose.foundation.layout.*
9 import androidx.compose.foundation.lazy.LazyRow
10 import androidx.compose.foundation.lazy.itemsIndexed
11 import androidx.compose.foundation.lazy.rememberLazyListState
12 import androidx.compose.foundation.shape.CircleShape
13 import androidx.compose.foundation.shape.RoundedCornerShape
14 import androidx.compose.material.icons.Icons
15 import androidx.compose.material.icons.filled.*
16 import androidx.compose.material3.*
17 import androidx.compose.runtime.*
18 import androidx.compose.ui.Alignment
19 import androidx.compose.ui.Modifier
20 import androidx.compose.ui.draw.clip
21 import androidx.compose.ui.graphics.Color
22 import androidx.compose.ui.graphics.ImageBitmap
23 import androidx.compose.ui.graphics.graphicsLayer
24 import androidx.compose.ui.graphics.vector.ImageVector
25 import androidx.compose.ui.input.pointer.pointerInput
26 import androidx.compose.ui.layout.ContentScale
27 import androidx.compose.ui.platform.LocalDensity
28 import androidx.compose.ui.text.font.FontWeight
29 import androidx.compose.ui.unit.IntOffset
30 import androidx.compose.ui.unit.dp
31 import androidx.compose.ui.unit.sp
32 import androidx.compose.ui.window.Popup
33 import com.wetinknext.domain.animation.AnimationDocument
34 import com.wetinknext.domain.animation.AnimationFrame
35 import com.wetinknext.domain.animation.AnimationFrameRole
36 import com.wetinknext.ui.theme.AppTheme
37 import kotlin.math.roundToInt
38
39 data class FrameThumbnailLayer(
40     val image: ImageBitmap,
41     val opacity: Float,
42 )
43
44 @Composable
45 fun AnimationTimelineToolbar(
46     theme: AppTheme,
47     document: AnimationDocument,
48     currentFrameId: Long,
49     frameThumbnails: Map<Long, List<FrameThumbnailLayer>> = emptyMap(),
50     onFrameSelect: (Long) -> Unit,
51     onFrameMove: (frameId: Long, direction: Int) -> Unit,
52     onAddFrame: () -> Unit,
53     onDuplicateFrame: (Long) -> Unit,
54     onDeleteFrame: (Long) -> Unit,
55     onHoldChange: (Long, Int) -> Unit,
56     onRoleToggle: (Long, AnimationFrameRole) -> Unit,
57     onAssembleLayers: () -> Unit,
58     onLayersClick: () -> Unit,
59     onClose: () -> Unit,
60     onSettingsClick: () -> Unit = {},
61     isPlaying: Boolean = false,
62     onPlayToggle: () -> Unit = {},
63     modifier: Modifier = Modifier
64 ) {
65     val listState = rememberLazyListState()
66     val frames = document.frames
67     var showContextMenuForId by remember { mutableStateOf<Long?>(null) }
68
69     // Auto-scroll to current frame
70     LaunchedEffect(currentFrameId) {
71         val index = frames.indexOfFirst { it.id == currentFrameId }
72         if (index >= 0) {
73             listState.animateScrollToItem(index)
74         }
75     }
76
77     Column(
78         modifier = modifier
79             .fillMaxWidth()
80             .padding(bottom = 16.dp),
81         horizontalAlignment = Alignment.CenterHorizontally
82     ) {
83         Row(
84             modifier = Modifier
85                 .widthIn(min = 400.dp, max = 820.dp)
86                 .height(86.dp)
87                 .clip(RoundedCornerShape(28.dp))
88                 .background(theme.panelBg.copy(alpha = 0.94f))
89                 .border(1.2.dp, theme.panelStroke, RoundedCornerShape(28.dp))
90                 .padding(horizontal = 14.dp, vertical = 8.dp),

```

```

91         verticalAlignment = Alignment.CenterVertically
92     ) {
93         // Play toggle
94         Column(
95             horizontalAlignment = Alignment.CenterHorizontally,
96             modifier = Modifier.padding(end = 4.dp)
97         ) {
98             Box(
99                 modifier = Modifier
100                     .size(44.dp)
101                     .clip(CircleShape)
102                     .background(if (isPlaying) theme.accent.copy(alpha = 0.4f) else theme.accent)
103                     .clickable { onPlayToggle() },
104                 contentAlignment = Alignment.Center
105             ) {
106                 Icon(
107                     if (isPlaying) Icons.Default.Pause else Icons.Default.PlayArrow,
108                     null,
109                     tint = Color.White
110                 )
111             }
112             Text(if (isPlaying) "Пауза" else "Пуск", color = theme.textSecondary, fontSize = 9.sp)
113         }
114
115         Spacer(Modifier.width(10.dp))
116         Box(Modifier.width(1.dp).fillMaxHeight(0.6f).background(theme.panelStroke))
117         Spacer(Modifier.width(10.dp))
118
119         // Frames timeline
120         LazyRow(
121             state = listState,
122             modifier = Modifier.weight(1f),
123             horizontalArrangement = Arrangement.spacedBy(8.dp),
124             verticalAlignment = Alignment.CenterVertically
125         ) {
126             itemsIndexed(frames, key = { _, f -> f.id }) { _, frame ->
127                 TimelineFrameItem(
128                     frame = frame,
129                     isSelected = frame.id == currentFrameId,
130                     thumbnailLayers = frameThumbnails[frame.id].orEmpty(),
131                     theme = theme,
132                     canMoveLeft = frames.indexOf(frame) > 0,
133                     canMoveRight = frames.indexOf(frame) < frames.lastIndex,
134                     onMove = { direction -> onFrameMove(frame.id, direction) },
135                     onClick = {
136                         if (currentFrameId == frame.id) {
137                             showContextMenuForId = frame.id
138                         } else {
139                             onFrameSelect(frame.id)
140                         }
141                     }
142                 )
143             }
144         }
145
146         Spacer(Modifier.width(10.dp))
147         Box(Modifier.width(1.dp).fillMaxHeight(0.6f).background(theme.panelStroke))
148         Spacer(Modifier.width(10.dp))
149
150         // Actions
151         Row(
152             verticalAlignment = Alignment.CenterVertically,
153             horizontalArrangement = Arrangement.spacedBy(12.dp)
154         ) {
155             TimelineActionIcon(Icons.Default.Add, "Кадр", theme, onClick = onAddFrame)
156             TimelineActionIcon(Icons.Default.Layers, "Собрать", theme, onClick = onAssembleLayers)
157             TimelineActionIcon(Icons.Default.ContentCopy, "Копия", theme, onClick = { onDuplicateFrame(currentFrameId) })
158             TimelineActionIcon(Icons.Default.Delete, "Удалить", theme, enabled = frames.size > 1, onClick = {
onDeleteFrame(currentFrameId) })
159             TimelineActionIcon(Icons.Default.Settings, "Настр.", theme, onClick = onSettingsClick)
160             TimelineActionIcon(Icons.Default.Layers, "Слой", theme, onClick = onLayersClick)
161             TimelineActionIcon(Icons.Default.Close, "Закрыть", theme, onClick = onClose)
162         }
163     }
164
165     // Context Menu
166     showContextMenuForId?.let { frameId ->
167         val frame = frames.find { it.id == frameId }
168         if (frame != null) {
169             Popup(
170                 alignment = Alignment.TopCenter,
171                 offset = IntOffset(0, -220),
172                 onDismissRequest = { showContextMenuForId = null }
173             ) {
174                 FrameContextMenu(
175                     frame = frame,
176                     theme = theme,
177                     onDuplicate = { onDuplicateFrame(frameId); showContextMenuForId = null },
178                     onDelete = { onDeleteFrame(frameId); showContextMenuForId = null },
179                     onHoldChange = { onHoldChange(frameId, it) },
180                     onRoleToggle = { onRoleToggle(frameId, it); showContextMenuForId = null },
181                     canDelete = frames.size > 1

```



```

182     )
183     }
184     }
185     }
186     }
187 }
188
189 @Composable
190 private fun FrameContextMenu(
191     frame: AnimationFrame,
192     theme: AppTheme,
193     onDuplicate: () -> Unit,
194     onDelete: () -> Unit,
195     onHoldChange: (Int) -> Unit,
196     onRoleToggle: (AnimationFrameRole) -> Unit,
197     canDelete: Boolean
198 ) {
199     Surface(
200         modifier = Modifier
201             .width(220.dp)
202             .clip(RoundedCornerShape(16.dp))
203             .border(1.dp, theme.panelStroke, RoundedCornerShape(16.dp)),
204         color = theme.panelBg,
205         tonalElevation = 8.dp
206     ) {
207         Column(modifier = Modifier.padding(12.dp)) {
208             ContextMenuItem("Дублировать", Icons.Default.ContentCopy, theme, onClick = onDuplicate)
209             ContextMenuItem("Удалить", Icons.Default.Delete, theme, enabled = canDelete, onClick = onDelete)
210
211             HorizontalDivider(modifier = Modifier.padding(vertical = 8.dp), color = theme.panelStroke)
212
213             Text("Задержка: ${frame.holdFrames}", color = theme.textSecondary, fontSize = 11.sp, modifier = Modifier.padding(
horizontal = 8.dp))
214             Slider(
215                 value = frame.holdFrames.toFloat(),
216                 onValueChange = { onHoldChange(it.toInt()) },
217                 valueRange = 1f..120f,
218                 colors = SliderDefaults.colors(thumbColor = theme.accent, activeTrackColor = theme.accent)
219             )
220
221             HorizontalDivider(modifier = Modifier.padding(vertical = 8.dp), color = theme.panelStroke)
222
223             val isBg = frame.role == AnimationFrameRole.BACKGROUND
224             val isFg = frame.role == AnimationFrameRole.FOREGROUND
225
226             Row(verticalAlignment = Alignment.CenterVertically, modifier = Modifier.fillMaxWidth().clickable { onRoleToggle(
if (isBg) AnimationFrameRole.NORMAL else AnimationFrameRole.BACKGROUND) }.padding(8.dp)) {
227                 Checkbox(checked = isBg, onCheckedChange = null, colors = CheckboxDefaults.colors(checkedColor = theme.
accent))
228                 Spacer(Modifier.width(8.dp))
229                 Text("Фоновый слой", color = theme.textPrimary, fontSize = 13.sp)
230             }
231             Row(verticalAlignment = Alignment.CenterVertically, modifier = Modifier.fillMaxWidth().clickable { onRoleToggle(
if (isFg) AnimationFrameRole.NORMAL else AnimationFrameRole.FOREGROUND) }.padding(8.dp)) {
232                 Checkbox(checked = isFg, onCheckedChange = null, colors = CheckboxDefaults.colors(checkedColor = theme.
accent))
233                 Spacer(Modifier.width(8.dp))
234                 Text("Передний план", color = theme.textPrimary, fontSize = 13.sp)
235             }
236         }
237     }
238 }
239
240 @Composable
241 private fun ContextMenuItem(
242     label: String,
243     icon: ImageVector,
244     theme: AppTheme,
245     enabled: Boolean = true,
246     onClick: () -> Unit
247 ) {
248     Row(
249         modifier = Modifier
250             .fillMaxWidth()
251             .clickable(enabled = enabled) { onClick() }
252             .padding(8.dp)
253             .alphaIfDisabled(!enabled),
254         verticalAlignment = Alignment.CenterVertically
255     ) {
256         Icon(icon, null, tint = if (enabled) theme.textPrimary else theme.textSecondary.copy(alpha = 0.5f), modifier =
Modifier.size(18.dp))
257         Spacer(Modifier.width(12.dp))
258         Text(label, color = if (enabled) theme.textPrimary else theme.textSecondary.copy(alpha = 0.5f), fontSize = 14.sp)
259     }
260 }
261
262 @Composable
263 private fun TimelineFrameItem(
264     frame: AnimationFrame,
265     isSelected: Boolean,
266     thumbnailLayers: List<FrameThumbnailLayer>,
267     theme: AppTheme,

```

```

268     canMoveLeft: Boolean,
269     canMoveRight: Boolean,
270     onMove: (Int) -> Unit,
271     onClick: () -> Unit
272 ) {
273     val moveThresholdPx = with(LocalDensity.current) { 44.dp.toPx() }
274     var accumulatedDragX by remember(frame.id) { mutableFloatStateOf(0f) }
275     Column(
276         horizontalAlignment = Alignment.CenterHorizontally,
277         modifier = Modifier
278             .pointerInput(frame.id, canMoveLeft, canMoveRight) {
279                 detectDragGesturesAfterLongPress(
280                     onDragStart = { accumulatedDragX = 0f },
281                     onDrag = { change, dragAmount ->
282                         accumulatedDragX += dragAmount.x
283                         val direction = when {
284                             accumulatedDragX <= -moveThresholdPx && canMoveLeft -> -1
285                             accumulatedDragX >= moveThresholdPx && canMoveRight -> 1
286                             else -> 0
287                         }
288                         if (direction != 0) {
289                             change.consume()
290                             onMove(direction)
291                             accumulatedDragX = 0f
292                         }
293                     }
294             )
295     )
296     .clickable { onClick() }
297 ) {
298     Box(
299         modifier = Modifier
300             .size(54.dp, 40.dp)
301             .clip(RoundedCornerShape(4.dp))
302             .background(if (isSelected) theme.accent.copy(alpha = 0.2f) else theme.panelInsetSoft)
303             .border(
304                 width = if (isSelected) 2.dp else 1.dp,
305                 color = if (isSelected) theme.accent else theme.panelStroke,
306                 shape = RoundedCornerShape(4.dp)
307             ),
308         contentAlignment = Alignment.Center
309     ) {
310         if (thumbnailLayers.isNotEmpty()) {
311             thumbnailLayers.forEach { layer ->
312                 Image(
313                     bitmap = layer.image,
314                     contentDescription = null,
315                     contentScale = ContentScale.Fit,
316                     modifier = Modifier
317                         .fillMaxSize()
318                         .padding(2.dp)
319                         .graphicsLayer(alpha = layer.opacity.coerceIn(0f, 1f)),
320                 )
321             }
322         } else {
323             Icon(Icons.Default.Image, null, tint = theme.textSecondary.copy(alpha = 0.3f), modifier = Modifier.size(20.
324 dp))
325         }
326         if (frame.holdFrames > 1) {
327             Text("+${frame.holdFrames - 1}", color = theme.accent, fontSize = 9.sp, fontWeight = FontWeight.Bold)
328         } else {
329             Spacer(Modifier.height(11.dp))
330         }
331     }
332 }
333
334 @Composable
335 private fun TimelineActionIcon(
336     icon: ImageVector,
337     label: String,
338     theme: AppTheme,
339     enabled: Boolean = true,
340     onClick: () -> Unit
341 ) {
342     Column(
343         horizontalAlignment = Alignment.CenterHorizontally,
344         modifier = Modifier
345             .alphaIfDisabled(!enabled)
346             .clickable(enabled = enabled) { onClick() }
347     ) {
348         Icon(icon, null, tint = if (enabled) theme.textPrimary else theme.textSecondary.copy(alpha = 0.5f), modifier =
349 Modifier.size(22.dp))
350         Text(label, color = theme.textSecondary, fontSize = 9.sp)
351     }
352
353     private fun Modifier.alphaIfDisabled(disabled: Boolean): Modifier = if (disabled) this.then(Modifier.graphicsLayer { alpha =
354 0.5f }) else this

```

95. app/src/main/java/com/wetinknext/ui/color/ColorCollection.kt

```

1 package com.wetinknext.ui.color
2
3 import androidx.compose.ui.graphics.Color
4
5 data class ColorCollection(
6     val id: Long,
7     val name: String,
8     val colors: List<Int>,
9     val builtin: Boolean = false,
10 )
11
12 fun ColorCollection.composeColors(): List<Color> = colors.map { Color(it) }
13
14 private fun hex(s: String): Int {
15     val v = s.removePrefix("#").trim()
16     val r = v.substring(0, 2).toInt(16)
17     val g = v.substring(2, 4).toInt(16)
18     val b = v.substring(4, 6).toInt(16)
19     return (0xFF shl 24) or (r shl 16) or (g shl 8) or b
20 }
21
22 private fun palette(vararg hex: String): List<Int> = hex.map { hex(it) }
23
24 object BuiltinCollections {
25     val all: List<ColorCollection> = listOf(
26         ColorCollection(
27             id = -1L,
28             name = "Стандарт",
29             colors = palette(
30                 "#FFF3B0", "#FFD6A5", "#FFC2B0", "#FFCCD5", "#F1C6F2",
31                 "#D8C7F5", "#C5D7FF", "#B8E5FF", "#B6F0EE", "#C9F2D8",
32                 "#FFE066", "#FFB87A", "#FF9F8B", "#FF9CB0", "#E59FE6",
33                 "#B89BE8", "#9CB6F5", "#86CFF2", "#7FD9D5", "#8AD9A8",
34                 "#F7C548", "#F09870", "#E07A6E", "#D9748E", "#C383C6",
35                 "#9678D0", "#7798E0", "#5DB1E6", "#5CB8B5", "#65BD8A",
36             ),
37             builtin = true,
38         ),
39         ColorCollection(
40             id = -2L,
41             name = "Пастель",
42             colors = palette(
43                 "#F9E79F", "#F7D08A", "#F5B187", "#F0998A", "#EC9090",
44                 "#E68F9C", "#D88BAE", "#C58CC0", "#B391CD", "#9C95D6",
45                 "#A8D5B6", "#9FD2C9", "#9CCFD8", "#A0C9E0", "#A8C0E3",
46                 "#B5BBE3", "#C0B8DE", "#CCB5D3", "#D6B3C5", "#DDB3B6",
47                 "#C7E1A1", "#B7DAA3", "#A8D2AE", "#9CCABD", "#94C0CB",
48                 "#94B5D2", "#9DA9D1", "#B0A0CB", "#C19BBE", "#CC9AAB",
49             ),
50             builtin = true,
51         ),
52         ColorCollection(
53             id = -3L,
54             name = "Персонажи",
55             colors = palette(
56                 "#F4C9B5", "#F0D4BC", "#E8B89A", "#D89C7E", "#C0805F",
57                 "#9C5F3F", "#74442B", "#4F2C1C", "#311A11", "#1B0F0A",
58                 "#FBE3D4", "#F8DCC9", "#F2C5A5", "#E2A77F", "#C58557",
59                 "#A36739", "#7A4824", "#552E14", "#321A0A", "#FFFAF0",
60                 "#E8C7C1", "#D49C9C", "#B97070", "#8C4F4F", "#5C3030",
61                 "#C7BF11", "#9C9484", "#6E6757", "#A0B0C4", "#5A6878",
62             ),
63             builtin = true,
64         ),
65         ColorCollection(
66             id = -4L,
67             name = "Пейзаж",
68             colors = palette(
69                 "#AEDCF0", "#7FBFE1", "#56A0CB", "#3D80B0", "#2E608E",
70                 "#244670", "#1B335A", "#142545", "#0D1830", "#070D1E",
71                 "#CFE3B0", "#A8CF8C", "#7FB36A", "#5C9651", "#3F7A3F",
72                 "#2E5E33", "#214728", "#16321C", "#5C7B4A", "#3F5732",
73                 "#F4D58D", "#E3B26E", "#D08A4A", "#B5642E", "#923F1C",
74                 "#6E2A14", "#8B5A2B", "#5C3A1A", "#A38560", "#6F5B3D",
75             ),
76             builtin = true,
77         ),
78         ColorCollection(
79             id = -5L,
80             name = "Анимация",
81             colors = palette(
82                 "#111318", "#3B414A", "#7B8491", "#B8C0CC", "#FFFFFF",
83                 "#4A90E2", "#35B9D5", "#42B883", "#A5D646", "#F4D44D",
84                 "#F5A23D", "#F26B4F", "#E6536F", "#E66FAD", "#A368DB",
85                 "#6D8CFF", "#64D4E8", "#76D7A6", "#D8EA72", "#FFE58A",
86                 "#245EA8", "#167E98", "#20794F", "#6B8F20", "#B58B08",
87                 "#B65A12", "#B53832", "#A62E58", "#A23E86", "#633B9B",
88             ),
89             builtin = true,
90         ),
91     )
92 }

```

91)
92 }

96. app/src/main/java/com/wetinknext/ui/color/ColorMath.kt

```

1 package com.wetinknext.ui.color
2
3 import androidx.compose.ui.graphics.Color
4 import kotlin.math.abs
5
6 data class Hsl(val h: Float, val s: Float, val l: Float)
7
8 fun rgbToHsl(c: Color): Hsl {
9     val r = c.red
10    val g = c.green
11    val b = c.blue
12    val max = maxOf(r, g, b)
13    val min = minOf(r, g, b)
14    val l = (max + min) / 2f
15    val d = max - min
16    if (d == 0f) return Hsl(0f, 0f, l)
17    val s = if (l > 0.5f) d / (2f - max - min) else d / (max + min)
18    val h = when (max) {
19        r -> 60f * (((g - b) / d) % 6f)
20        g -> 60f * ((b - r) / d + 2f)
21        else -> 60f * ((r - g) / d + 4f)
22    }
23    return Hsl(((h % 360f) + 360f) % 360f, s, l)
24 }
25
26 fun hslToColor(h: Float, s: Float, l: Float): Color {
27     val hh = ((h % 360f) + 360f) % 360f
28     val c = (1f - abs(2f * l - 1f)) * s
29     val x = c * (1f - abs((hh / 60f) % 2f - 1f))
30     val m = l - c / 2f
31     val (r1, g1, b1) = when ((hh / 60f).toInt()) {
32         0 -> Triple(c, x, 0f)
33         1 -> Triple(x, c, 0f)
34         2 -> Triple(0f, c, x)
35         3 -> Triple(0f, x, c)
36         4 -> Triple(x, 0f, c)
37         else -> Triple(c, 0f, x)
38     }
39     return Color(
40         (r1 + m).coerceIn(0f, 1f),
41         (g1 + m).coerceIn(0f, 1f),
42         (b1 + m).coerceIn(0f, 1f),
43         1f,
44     )
45 }
46
47 fun hslToColor(hsl: Hsl): Color = hslToColor(hsl.h, hsl.s, hsl.l)
48
49 fun Color.toHex6(): String {
50     val r = (red * 255f).toInt().coerceIn(0, 255)
51     val g = (green * 255f).toInt().coerceIn(0, 255)
52     val b = (blue * 255f).toInt().coerceIn(0, 255)
53     return "#%02X%02X%02X".format(r, g, b)
54 }
55
56 enum class HarmonyType(
57     val displayName: String,
58     val offsets: FloatArray,
59 ) {
60     Complementary("Комплементарная", floatArrayOf(0f, 180f)),
61     Analogous("Аналоговая", floatArrayOf(-30f, 0f, 30f)),
62     Triadic("Триадная", floatArrayOf(0f, 120f, 240f)),
63     SplitComplementary(
64         "Сплит-комплементарная",
65         floatArrayOf(0f, 150f, 210f),
66     ),
67     Tetradic("Тетрадная", floatArrayOf(0f, 60f, 180f, 240f)),
68     Square("Квадратная", floatArrayOf(0f, 90f, 180f, 270f)),
69     ;
70
71     fun derive(base: Hsl): List<Hsl> {
72         val h = base.h
73         return offsets.map { off ->
74             Hsl(((h + off) % 360f + 360f) % 360f, base.s, base.l)
75         }
76     }
77 }

```

97. app/src/main/java/com/wetinknext/ui/color/ColorPanel.kt

```

1  package com.wetinknext.ui.color
2
3  import androidx.compose.animation.core.animateFloatAsState
4  import androidx.compose.animation.core.tween
5  import androidx.compose.foundation.Canvas
6  import androidx.compose.foundation.ExperimentalFoundationApi
7  import androidx.compose.foundation.background
8  import androidx.compose.foundation.border
9  import androidx.compose.foundation.clickable
10 import androidx.compose.foundation.combinedClickable
11 import androidx.compose.foundation.gestures.detectDragGestures
12 import androidx.compose.foundation.gestures.detectHorizontalDragGestures
13 import androidx.compose.foundation.gestures.detectTapGestures
14 import androidx.compose.foundation.layout.*
15 import androidx.compose.foundation.rememberScrollState
16 import androidx.compose.foundation.shape.CircleShape
17 import androidx.compose.foundation.shape.RoundedCornerShape
18 import androidx.compose.foundation.text.BasicTextField
19 import androidx.compose.foundation.verticalScroll
20 import androidx.compose.material3.*
21 import androidx.compose.runtime.*
22 import androidx.compose.ui.Alignment
23 import androidx.compose.ui.Modifier
24 import androidx.compose.ui.draw.clip
25 import androidx.compose.ui.draw.shadow
26 import androidx.compose.ui.geometry.Offset
27 import androidx.compose.ui.geometry.Size
28 import androidx.compose.ui.graphics.Brush
29 import androidx.compose.ui.graphics.Color
30 import androidx.compose.ui.graphics.SolidColor
31 import androidx.compose.ui.graphics.drawscope.DrawScope
32 import androidx.compose.ui.graphics.drawscope.Stroke
33 import androidx.compose.ui.input.pointer.pointerInput
34 import androidx.compose.ui.platform.LocalDensity
35 import androidx.compose.ui.text.TextStyle
36 import androidx.compose.ui.text.font.FontWeight
37 import androidx.compose.ui.text.style.TextAlign
38 import androidx.compose.ui.unit.dp
39 import androidx.compose.ui.unit.IntOffset
40 import androidx.compose.ui.unit.sp
41 import androidx.compose.ui.window.Dialog
42 import com.wetinknext.ui.components.PanelSurface
43 import com.wetinknext.ui.theme.AppTheme
44 import kotlinx.coroutines.delay
45 import kotlin.math.atan2
46 import kotlin.math.cos
47 import kotlin.math.hypot
48 import kotlin.math.sin
49 import kotlin.math.roundToInt
50
51 private enum class ColorTab { Wheel, Map }
52
53 @Composable
54 fun ColorPanel(
55     state: GlesColorState,
56     color: Color,
57     theme: AppTheme,
58     onColorChange: (Color) -> Unit,
59     onAddFromPhoto: () -> Unit,
60     title: String = "Ғберa",
61     recordRecent: Boolean = true,
62     allowCollectionEditing: Boolean = true,
63     onPinCollection: (ColorCollection) -> Unit = {},
64     modifier: Modifier = Modifier,
65     onDismiss: () -> Unit,
66 ) {
67     var tab by remember { mutableStateOf(ColorTab.Wheel) }
68     var hsl by remember { mutableStateOf(rgbToHsl(color)) }
69     var harmonyType by remember { mutableStateOf(HarmonyType.Triadic) }
70     val latestHsl by rememberUpdatedState(hsl)
71
72     val wheelScrollState = rememberScrollState()
73     val mapScrollState = rememberScrollState()
74     val tabScrollState = when (tab) {
75         ColorTab.Wheel -> wheelScrollState
76         ColorTab.Map -> mapScrollState
77     }
78
79     LaunchedEffect(hsl, recordRecent) {
80         val selectedColor = hslToColor(hsl)
81         onColorChange(selectedColor)
82         if (recordRecent) {
83             delay(350)
84             state.pushRecentColor(selectedColor)
85         }
86     }
87
88     val dismissAndSave = {
89         if (recordRecent) state.pushRecentColor(hslToColor(hsl))
90         onDismiss()
91     }

```

```

91     }
92
93     DisposableEffect(Unit) {
94         onDispose {
95             if (recordRecent) state.pushRecentColor(hslToColor(latestHsl))
96         }
97     }
98
99     PanelSurface(
100         modifier = modifier.width(320.dp),
101     ) {
102         Column(
103             modifier = Modifier.padding(14.dp),
104         ) {
105             ColorHeader(
106                 preview = hslToColor(hsl),
107                 title = title,
108                 theme = theme,
109                 onConfirm = dismissAndSave,
110             )
111             Spacer(Modifier.height(10.dp))
112             TabBar(tab, theme) { tab = it }
113             Spacer(Modifier.height(12.dp))
114             Box(
115                 modifier = Modifier
116                     .height(TabContentHeight)
117                     .fillMaxWidth(),
118             ) {
119                 Column(
120                     modifier = Modifier
121                         .fillMaxSize()
122                         .verticalScroll(tabScrollState),
123                 ) {
124                     when (tab) {
125                         ColorTab.Wheel -> WheelTab(
126                             hsl = hsl,
127                             theme = theme,
128                             onHslChange = { hsl = it },
129                             harmonyType = harmonyType,
130                             onHarmonyTypeChange = { harmonyType = it },
131                             recent = state.recentColors.toList(),
132                             onPickRecent = { picked ->
133                                 val p = rgbToHsl(picked)
134                                 hsl = hsl.copy(h = p.h, s = p.s)
135                                 if (recordRecent) state.pushRecentColor(hslToColor(hsl))
136                             },
137                         )
138                         ColorTab.Map -> MapTab(
139                             userCollections = state.userCollections.toList(),
140                             currentColor = hslToColor(hsl),
141                             theme = theme,
142                             onPick = { picked ->
143                                 hsl = rgbToHsl(picked)
144                                 if (recordRecent) state.pushRecentColor(picked)
145                             },
146                             onDeleteUserCollection = { id ->
147                                 state.deleteUserCollection(id)
148                             },
149                             onAddFromPhoto = onAddFromPhoto,
150                             allowCollectionEditing = allowCollectionEditing,
151                             onCreatePalette = { name ->
152                                 state.addUserCollection(
153                                     ColorCollection(
154                                         id = System.currentTimeMillis(),
155                                         name = name.ifBlank { "Новая палитра" },
156                                         colors = emptyList(),
157                                         builtin = false,
158                                     ),
159                                 )
160                             },
161                             onAddColorToCollection = { id, color ->
162                                 state.addColorToCollection(id, color)
163                             },
164                             onReplaceColorInCollection = { id, slot, color ->
165                                 state.replaceColorInCollection(id, slot, color)
166                             },
167                             onRemoveColorFromCollection = { id, slot ->
168                                 state.removeColorFromCollection(id, slot)
169                             },
170                             onPinCollection = onPinCollection,
171                         )
172                     }
173                 }
174             }
175         }
176     }
177 }
178
179 private val TabContentHeight = 440.dp
180
181 @Composable
182 private fun ColorHeader(preview: Color, onConfirm: () -> Unit, title: String, theme: AppTheme) {

```

```

183     Row(verticalAlignment = Alignment.CenterVertically) {
184         Text(
185             title,
186             color = theme.textPrimary,
187             fontWeight = FontWeight.Bold,
188             fontSize = 18.sp,
189         )
190         Spacer(Modifier.weight(1f))
191         Box(
192             modifier = Modifier
193                 .size(28.dp)
194                 .clip(CircleShape)
195                 .background(preview)
196                 .border(1.dp, theme.panelStroke, CircleShape)
197                 .clickable(onClick = onConfirm),
198         )
199     }
200 }
201
202 @Composable
203 private fun TabBar(current: ColorTab, theme: AppTheme, onChange: (ColorTab) -> Unit) {
204     Row(
205         modifier = Modifier
206             .fillMaxWidth()
207             .clip(RoundedCornerShape(10.dp))
208             .background(theme.panelInset)
209             .padding(3.dp),
210         horizontalArrangement = Arrangement.spacedBy(3.dp),
211     ) {
212         TabChip(label = "Кольцо", selected = current == ColorTab.Wheel, theme = theme) { onChange(ColorTab.Wheel) }
213         TabChip(label = "Карта", selected = current == ColorTab.Map, theme = theme) { onChange(ColorTab.Map) }
214     }
215 }
216
217 @Composable
218 private fun RowScope.TabChip(
219     label: String,
220     selected: Boolean,
221     theme: AppTheme,
222     onClick: () -> Unit,
223 ) {
224     Box(
225         modifier = Modifier
226             .weight(1f)
227             .clip(RoundedCornerShape(8.dp))
228             .background(if (selected) theme.accent.copy(alpha = 0.25f) else Color.Transparent)
229             .clickable(onClick = onClick)
230             .padding(vertical = 7.dp),
231         contentAlignment = Alignment.Center,
232     ) {
233         Text(
234             label,
235             color = if (selected) theme.textPrimary else theme.textSecondary,
236             fontSize = 13.sp,
237             fontWeight = if (selected) FontWeight.SemiBold else FontWeight.Normal,
238         )
239     }
240 }
241
242 @Composable
243 private fun WheelTab(
244     hsl: Hsl,
245     theme: AppTheme,
246     onHslChange: (Hsl) -> Unit,
247     harmonyType: HarmonyType,
248     onHarmonyTypeChange: (HarmonyType) -> Unit,
249     recent: List<Color>,
250     onPickRecent: (Color) -> Unit,
251 ) {
252     HueSatWheel(
253         hsl = hsl,
254         harmonyType = harmonyType,
255         onHsChange = { newH, newS -> onHslChange(hsl.copy(h = newH, s = newS)) },
256         modifier = Modifier
257             .fillMaxWidth()
258             .height(160.dp),
259     )
260     Spacer(Modifier.height(8.dp))
261     LightnessSlider(
262         hsl = hsl,
263         theme = theme,
264         onChange = { newL -> onHslChange(hsl.copy(l = newL)) },
265     )
266     Spacer(Modifier.height(8.dp))
267     HexRow(color = hslToColor(hsl), theme = theme)
268     Spacer(Modifier.height(10.dp))
269     HarmonySection(
270         hsl = hsl,
271         theme = theme,
272         harmonyType = harmonyType,
273         onHarmonyTypeChange = onHarmonyTypeChange,
274         onPick = onPickRecent,

```



```

275     )
276     Spacer(Modifier.height(10.dp))
277     SectionTitle("Недавние", theme)
278     Spacer(Modifier.height(6.dp))
279     RecentRow(colors = recent.take(GRID_COLUMNS), theme = theme, onPick = onPickRecent)
280 }
281
282 @Composable
283 private fun HueSatWheel(
284     hsl: Hsl,
285     harmonyType: HarmonyType,
286     onHsChange: (Float, Float) -> Unit,
287     modifier: Modifier = Modifier,
288 ) {
289     val latestOnHsChange by rememberUpdatedState(onHsChange)
290     Canvas(
291         modifier = modifier
292             .clip(RoundedCornerShape(16.dp))
293             .pointerInput(Unit) {
294                 detectDragGestures { change, _ ->
295                     val (nh, ns) = pickHueSat(change.position, size.width.toFloat(), size.height.toFloat())
296                     latestOnHsChange(nh, ns)
297                 }
298             }
299             .pointerInput(Unit) {
300                 detectTapGestures(onTap = { offset ->
301                     val (nh, ns) = pickHueSat(offset, size.width.toFloat(), size.height.toFloat())
302                     latestOnHsChange(nh, ns)
303                 })
304             },
305     ) {
306         val w = size.width
307         val hgt = size.height
308         val cx = w / 2f
309         val cy = hgt / 2f
310         val outer = minOf(w, hgt) / 2f - 4f
311         if (outer <= 0f) return@Canvas
312
313         val steps = 120
314         for (i in 0 until steps) {
315             val a0 = i * 360f / steps
316             val a1 = (i + 1) * 360f / steps
317             val midA = (a0 + a1) / 2f
318             val hueColor = hslToColor(midA, 1f, 0.5f)
319             drawArc(
320                 color = hueColor,
321                 startAngle = a0 - 90f,
322                 sweepAngle = (a1 - a0) + 0.6f,
323                 useCenter = true,
324                 topLeft = Offset(cx - outer, cy - outer),
325                 size = Size(outer * 2, outer * 2),
326             )
327         }
328         drawCircle(
329             brush = Brush.radialGradient(
330                 colors = listOf(Color.White, Color.White.copy(alpha = 0f)),
331                 center = Offset(cx, cy),
332                 radius = outer,
333             ),
334             radius = outer,
335             center = Offset(cx, cy),
336         )
337
338         val derived = harmonyType.derive(hsl)
339         val verts = derived.map { d -> hslToWheelPoint(d, cx, cy, outer) }
340         drawHarmonyShape(harmonyType, verts)
341
342         val current = hslToWheelPoint(hsl, cx, cy, outer)
343         drawCircle(color = Color.White, radius = 7f, center = current, style = Stroke(width = 2f))
344         drawCircle(color = Color.Black, radius = 7f, center = current, style = Stroke(width = 1f))
345     }
346 }
347
348 private fun hslToWheelPoint(h: Hsl, cx: Float, cy: Float, outer: Float): Offset {
349     val a = Math.toRadians((h.h - 90.0))
350     val r = h.s.coerceIn(0f, 1f) * outer
351     return Offset(cx + (r * cos(a)).toFloat(), cy + (r * sin(a)).toFloat())
352 }
353
354 private fun DrawScope.drawHarmonyShape(type: HarmonyType, verts: List<Offset>) {
355     if (verts.size < 2) return
356     val edges: List<Pair<Int, Int>> = when (type) {
357         HarmonyType.Complementary -> listOf(0 to 1)
358         HarmonyType.Analogous -> listOf(0 to 1, 1 to 2)
359         HarmonyType.Triadic -> listOf(0 to 1, 1 to 2, 2 to 0)
360         HarmonyType.SplitComplementary -> listOf(0 to 1, 0 to 2, 1 to 2)
361         HarmonyType.Tetradic,
362         HarmonyType.Square -> listOf(0 to 1, 1 to 2, 2 to 3, 3 to 0)
363     }
364     edges.forEach { (a, b) ->
365         drawLine(color = Color.White.copy(alpha = 0.85f), start = verts[a], end = verts[b], strokeWidth = 2.5f)
366         drawLine(color = Color.Black.copy(alpha = 0.55f), start = verts[a], end = verts[b], strokeWidth = 1f)
367     }
368 }

```

```

367     }
368     verts.forEach { v ->
369         drawCircle(color = Color.White, radius = 4f, center = v)
370         drawCircle(color = Color.Black, radius = 4f, center = v, style = Stroke(width = 1f))
371     }
372 }
373
374 private fun pickHueSat(p: Offset, w: Float, h: Float): Pair<Float, Float> {
375     val cx = w / 2f
376     val cy = h / 2f
377     val outer = minOf(w, h) / 2f - 4f
378     val dx = p.x - cx
379     val dy = p.y - cy
380     val r = hypot(dx, dy)
381     val ang = Math.toDegrees(atan2(dy, dx).toDouble()) + 90.0
382     val nh = ((ang + 360.0) % 360.0).toFloat()
383     val ns = (r / outer).coerceIn(0f, 1f)
384     return nh to ns
385 }
386
387 @Composable
388 private fun LightnessSlider(hsl: Hsl, theme: AppTheme, onChange: (Float) -> Unit) {
389     val hue = hsl.h
390     val sat = hsl.s
391     val gradient = remember(hue, sat) {
392         Brush.horizontalGradient(
393             colors = listOf(
394                 hslToColor(hue, sat, 0f),
395                 hslToColor(hue, sat, 0.5f),
396                 hslToColor(hue, sat, 1f),
397             ),
398         )
399     }
400     val latestOnChange by rememberUpdatedState(onChange)
401     Row(verticalAlignment = Alignment.CenterVertically) {
402         Text("L", color = theme.textSecondary, fontSize = 12.sp, modifier = Modifier.width(16.dp))
403         Spacer(Modifier.width(8.dp))
404         Box(
405             modifier = Modifier
406                 .height(20.dp)
407                 .fillMaxWidth()
408                 .clip(RoundedCornerShape(10.dp))
409                 .background(gradient)
410                 .border(1.5.dp, theme.panelStroke, RoundedCornerShape(10.dp))
411                 .pointerInput(Unit) {
412                     detectDragGestures { change, _ ->
413                         val f = (change.position.x / size.width).coerceIn(0f, 1f)
414                         latestOnChange(f)
415                     }
416                 }
417                 .pointerInput(Unit) {
418                     detectTapGestures(onTap = { offset ->
419                         val f = (offset.x / size.width).coerceIn(0f, 1f)
420                         latestOnChange(f)
421                     })
422                 },
423         ) {
424             Canvas(modifier = Modifier.fillMaxSize()) {
425                 val knobR = (size.height / 2f - 2f).coerceAtMost(size.width / 2f).coerceAtLeast(0f)
426                 if (knobR <= 0f) return@Canvas
427                 val knobX = (hsl.l.coerceIn(0f, 1f) * size.width).coerceIn(knobR + 2f, size.width - knobR - 2f)
428
429                 drawCircle(color = Color.White, radius = knobR, center = Offset(knobX, size.height / 2f), style = Stroke(
width = 2.5f))
430                 drawCircle(color = theme.panelStroke, radius = knobR, center = Offset(knobX, size.height / 2f), style =
Stroke(width = 1f))
431             }
432         }
433     }
434 }
435
436 @Composable
437 private fun HexRow(color: Color, theme: AppTheme) {
438     Row(verticalAlignment = Alignment.CenterVertically) {
439         Text("Hex", color = theme.textSecondary, fontSize = 11.sp)
440         Spacer(Modifier.weight(1f))
441         Box(
442             modifier = Modifier
443                 .clip(RoundedCornerShape(8.dp))
444                 .background(theme.panelInset)
445                 .border(1.dp, theme.panelStroke, RoundedCornerShape(8.dp))
446                 .padding(horizontal = 10.dp, vertical = 4.dp),
447         ) {
448             Text(color.toHexString(), color = theme.textPrimary, fontSize = 12.sp, fontWeight = FontWeight.Medium)
449         }
450     }
451 }
452
453 @Composable
454 private fun HarmonySection(
455     hsl: Hsl,
456     theme: AppTheme,

```

```

457     harmonyType: HarmonyType,
458     onHarmonyTypeChange: (HarmonyType) -> Unit,
459     onPick: (Hsl) -> Unit,
460 ) {
461     SectionTitle("Тип гармонии", theme)
462     Spacer(Modifier.height(6.dp))
463     Row(
464         horizontalArrangement = Arrangement.spacedBy(6.dp),
465         modifier = Modifier.fillMaxWidth(),
466     ) {
467         HarmonyType.entries.forEach { type ->
468             HarmonyIcon(
469                 type = type,
470                 theme = theme,
471                 selected = type == harmonyType,
472                 modifier = Modifier.weight(1f),
473                 ) { onHarmonyTypeChange(type) }
474         }
475     }
476     Spacer(Modifier.height(6.dp))
477     Text(harmonyType.displayName, color = theme.textSecondary, fontSize = 11.sp, textAlign = TextAlign.Center, modifier =
478     Modifier.fillMaxWidth())
479     Spacer(Modifier.height(8.dp))
480     val derived = remember(harmonyType, hsl) { harmonyType.derive(hsl) }
481     Row(
482         horizontalArrangement = Arrangement.spacedBy(6.dp),
483         verticalAlignment = Alignment.CenterVertically,
484         modifier = Modifier.fillMaxWidth(),
485     ) {
486         derived.forEach { d ->
487             Box(
488                 modifier = Modifier
489                     .weight(1f)
490                     .height(32.dp)
491                     .clip(RoundedCornerShape(8.dp))
492                     .background(hslToColor(d))
493                     .border(1.dp, theme.panelInset, RoundedCornerShape(8.dp))
494                     .clickable { onPick(d) },
495             )
496         }
497         repeat(4 - derived.size) { Box(modifier = Modifier.weight(1f)) }
498     }
499 }
500 @Composable
501 private fun HarmonyIcon(
502     type: HarmonyType,
503     theme: AppTheme,
504     selected: Boolean,
505     modifier: Modifier = Modifier,
506     onClick: () -> Unit,
507 ) {
508     Box(
509         modifier = modifier
510             .aspectRatio(1f)
511             .clip(RoundedCornerShape(8.dp))
512             .background(if (selected) theme.accent.copy(alpha = 0.25f) else theme.panelInset)
513             .border(1.dp, if (selected) theme.accent else theme.panelInset, RoundedCornerShape(8.dp))
514             .clickable(onClick = onClick)
515             .padding(6.dp),
516         contentAlignment = Alignment.Center,
517     ) {
518         Canvas(modifier = Modifier.fillMaxSize()) {
519             val cx = size.width / 2f
520             val cy = size.height / 2f
521             val r = minOf(size.width, size.height) / 2f - 1f
522             val ringColor = (if (selected) Color.White else theme.textSecondary).copy(alpha = 0.6f)
523             val shapeColor = if (selected) Color.White else theme.textSecondary
524             drawCircle(color = ringColor, radius = r, center = Offset(cx, cy), style = Stroke(width = 1.2f))
525             val verts = type.offsets.map { off ->
526                 val a = Math.toRadians((off - 90.0).toDouble())
527                 Offset(cx + (r * 0.78f * cos(a)).toFloat(), cy + (r * 0.78f * sin(a)).toFloat())
528             }
529             val edges: List<Pair<Int, Int>> = when (type) {
530                 HarmonyType.Complementary -> listOf(0 to 1)
531                 HarmonyType.Analogous -> listOf(0 to 1, 1 to 2)
532                 HarmonyType.Triadic -> listOf(0 to 1, 1 to 2, 2 to 0)
533                 HarmonyType.SplitComplementary -> listOf(0 to 1, 0 to 2, 1 to 2)
534                 HarmonyType.Tetradic,
535                 HarmonyType.Square -> listOf(0 to 1, 1 to 2, 2 to 3, 3 to 0)
536             }
537             edges.forEach { (a, b) -> drawLine(color = shapeColor, start = verts[a], end = verts[b], strokeWidth = 1.8f) }
538             verts.forEach { v -> drawCircle(color = shapeColor, radius = 2.2f, center = v) }
539         }
540     }
541 }
542
543 private const val GRID_COLUMNS = 10
544
545 @Composable
546 private fun MapTab(
547     userCollections: List<ColorCollection>,

```

```

548     currentColor: Color,
549     theme: AppTheme,
550     onPick: (Color) -> Unit,
551     onDeleteUserCollection: (Long) -> Unit,
552     onAddFromPhoto: () -> Unit,
553     allowCollectionEditing: Boolean,
554     onCreatePalette: (String) -> Unit,
555     onAddColorToCollection: (Long, Color) -> Unit,
556     onReplaceColorInCollection: (Long, Int, Color) -> Unit,
557     onRemoveColorFromCollection: (Long, Int) -> Unit,
558     onPinCollection: (ColorCollection) -> Unit,
559 ) {
560     var showCreate by remember { mutableStateOf(false) }
561     Column(verticalArrangement = Arrangement.spacedBy(10.dp)) {
562         if (allowCollectionEditing) {
563             Row(horizontalArrangement = Arrangement.spacedBy(8.dp)) {
564                 MapActionButton(label = "+ Создать", theme = theme, modifier = Modifier.weight(1f), onClick = { showCreate =
true })
565                 MapActionButton(label = "+ Из фото", theme = theme, modifier = Modifier.weight(1f), onClick = onAddFromPhoto)
566             }
567         }
568         userCollections.forEach { collection ->
569             CollectionCard(collection = collection, theme = theme, onPick = onPick, onDelete = { onDeleteUserCollection(
collection.id) },
570                 onAddCurrentColor = { onAddColorToCollection(collection.id, currentColor) },
571                 onReplaceAt = { slot -> onReplaceColorInCollection(collection.id, slot, currentColor) },
572                 onRemoveAt = { slot -> onRemoveColorFromCollection(collection.id, slot) },
573                 onPin = { onPinCollection(collection) },
574             )
575         }
576         BuiltinCollections.all.forEach { collection ->
577             CollectionCard(collection = collection, theme = theme, onPick = onPick, onDelete = null, onAddCurrentColor = null,
onReplaceAt = null, onRemoveAt = null, onPin = { onPinCollection(collection) })
578         }
579     }
580     if (showCreate && allowCollectionEditing) {
581         CreatePaletteDialog(theme = theme, onConfirm = { name -> onCreatePalette(name); showCreate = false }, onDismiss = {
showCreate = false })
582     }
583 }
584
585 @Composable
586 private fun MapActionButton(label: String, theme: AppTheme, modifier: Modifier = Modifier, onClick: () -> Unit) {
587     Box(modifier = modifier.fillMaxWidth().clip(RoundedCornerShape(10.dp)).background(theme.accent.copy(alpha = 0.15f)).
border(1.2.dp, theme.accentSoft, RoundedCornerShape(10.dp)).clickable(onClick = onClick).padding(vertical = 10.dp, horizontal = 10.
dp), contentAlignment = Alignment.Center) {
588         Text(label, color = theme.textPrimary, fontSize = 13.sp, fontWeight = FontWeight.SemiBold)
589     }
590 }
591
592 @Composable
593 private fun CollectionCard(collection: ColorCollection, theme: AppTheme, onPick: (Color) -> Unit, onDelete: (() -> Unit)?,
onAddCurrentColor: (() -> Unit)?, onReplaceAt: ((Int) -> Unit)?, onRemoveAt: ((Int) -> Unit)?, onPin: () -> Unit) {
594     var editingIdx by remember { mutableStateOf<Int?>(null) }
595     val revealPx = with(LocalDensity.current) { 96.dp.toPx() }
596     var rawOffset by remember(collection.id) { mutableFloatStateOf(0f) }
597     val animatedOffset by animateFloatAsState(rawOffset, tween(140), label = "paletteSwipe")
598     val cardShape = RoundedCornerShape(10.dp)
599     Box(modifier = Modifier.fillMaxWidth().clip(cardShape)) {
600         Box(
601             modifier = Modifier.matchParentSize().background(theme.accent.copy(alpha = 0.9f)),
602             contentAlignment = Alignment.CenterEnd,
603         ) {
604             Text(
605                 "Закрепить",
606                 color = Color.White,
607                 fontSize = 12.sp,
608                 fontWeight = FontWeight.SemiBold,
609                 modifier = Modifier.width(96.dp).fillMaxHeight().clickable { onPin(); rawOffset = 0f }.wrapContentHeight(
Alignment.CenterVertically),
610                 textAlign = TextAlign.Center,
611             )
612         }
613         Column(
614             modifier = Modifier
615                 .fillMaxWidth()
616                 .offset { IntOffset(animatedOffset.roundToInt(), 0) }
617                 .background(theme.panelInset)
618                 .border(1.dp, theme.panelStroke, cardShape)
619                 .pointerInput(collection.id, revealPx) {
620                     detectHorizontalDragGestures(
621                         onHorizontalDrag = { change, dx ->
622                             if (dx < 0f || rawOffset < 0f) {
623                                 change.consume()
624                                 rawOffset = (rawOffset + dx).coerceIn(-revealPx, 0f)
625                             }
626                     },
627                     onDragEnd = { rawOffset = if (rawOffset < -revealPx * 0.4f) -revealPx else 0f },
628                     onDragCancel = { rawOffset = 0f },
629                 )
630             )
631         .padding(horizontal = 8.dp, vertical = 8.dp),

```

```

632         verticalArrangement = Arrangement.spacedBy(6.dp),
633     ) {
634         Row(verticalAlignment = Alignment.CenterVertically) {
635             Text(collection.name, color = theme.textPrimary, fontSize = 13.sp, fontWeight = FontWeight.SemiBold)
636             Spacer(Modifier.weight(1f))
637             if (onDelete != null) {
638                 Box(modifier = Modifier.size(22.dp).clip(CircleShape).background(theme.panelBg.copy(alpha = 0.7f)).border(1.
dp, theme.panelStroke, CircleShape).clickable(onClick = onDelete), contentAlignment = Alignment.Center) {
639                     Text("x", color = theme.textSecondary, fontSize = 14.sp, fontWeight = FontWeight.Bold)
640                 }
641             }
642         }
643         SwatchGrid(colors = collection.composeColors(), theme = theme, onPick = onPick, trailingPlusOnClick =
onAddCurrentColor, onLongPressIndex = if (onReplaceAt != null && onRemoveAt != null) { { idx -> editingIdx = idx } } else null)
644     }
645     }
646     val activeIdx = editingIdx
647     if (activeIdx != null && onReplaceAt != null && onRemoveAt != null) {
648         val swatchColor = collection.composeColors().getOrNull(activeIdx)
649         if (swatchColor != null) {
650             EditSwatchSheet(swatchColor = swatchColor, theme = theme, onReplace = { onReplaceAt(activeIdx); editingIdx = null
}, onRemove = { onRemoveAt(activeIdx); editingIdx = null }, onDismiss = { editingIdx = null })
651         } else editingIdx = null
652     }
653 }
654
655 @OptIn(ExperimentalFoundationApi::class)
656 @Composable
657 private fun SwatchGrid(colors: List<Color>, theme: AppTheme, onPick: (Color) -> Unit, trailingPlusOnClick: (() -> Unit)? =
null, onLongPressIndex: ((Int) -> Unit)? = null) {
658     val total = colors.size + if (trailingPlusOnClick != null) 1 else 0
659     if (total == 0) return
660     val itemRows = (0 until total).toList().chunked(GRID_COLUMNS)
661     Column(verticalArrangement = Arrangement.spacedBy(4.dp)) {
662         itemRows.forEach { row ->
663             Row(horizontalArrangement = Arrangement.spacedBy(4.dp), modifier = Modifier.fillMaxWidth()) {
664                 row.forEach { i ->
665                     if (i < colors.size) {
666                         val c = colors[i]
667                         val cellModifier = Modifier.weight(1f).aspectRatio(1f).clip(RoundedCornerShape(5.dp)).background(c).
border(1.dp, theme.panelInset, RoundedCornerShape(5.dp))
668                         if (onLongPressIndex != null) Box(modifier = cellModifier.combinedClickable(onClick = { onPick(c) },
onLongClick = { onLongPressIndex(i) }))
669                         else Box(modifier = cellModifier.clickable { onPick(c) })
670                     } else PlusTile(theme = theme, modifier = Modifier.weight(1f).aspectRatio(1f), onClick =
trailingPlusOnClick!!)
671                 }
672                 repeat(GRID_COLUMNS - row.size) { Box(modifier = Modifier.weight(1f)) }
673             }
674         }
675     }
676 }
677
678 @Composable
679 private fun EditSwatchSheet(swatchColor: Color, theme: AppTheme, onReplace: () -> Unit, onRemove: () -> Unit, onDismiss: () -
> Unit) {
680     Dialog(onDismissRequest = onDismiss) {
681         Column(modifier = Modifier.width(280.dp).clip(RoundedCornerShape(16.dp)).background(theme.panelBg).padding(16.dp),
verticalArrangement = Arrangement.spacedBy(12.dp)) {
682             Row(verticalAlignment = Alignment.CenterVertically) {
683                 Box(modifier = Modifier.size(28.dp).clip(RoundedCornerShape(6.dp)).background(swatchColor).border(1.dp, theme.
panelInset, RoundedCornerShape(6.dp)))
684                 Spacer(Modifier.width(10.dp)); Text("Цвет", color = theme.textPrimary, fontSize = 16.sp, fontWeight =
FontWeight.SemiBold)
685             }
686             DialogButton(label = "Заменить текущим", theme = theme, primary = true, modifier = Modifier.fillMaxWidth(),
onClick = onReplace)
687             DialogButton(label = "Удалить", theme = theme, primary = false, modifier = Modifier.fillMaxWidth(), onClick =
onRemove)
688             DialogButton(label = "Отмена", theme = theme, primary = false, modifier = Modifier.fillMaxWidth(), onClick =
onDismiss)
689         }
690     }
691 }
692
693 @Composable
694 private fun PlusTile(theme: AppTheme, modifier: Modifier = Modifier, onClick: () -> Unit) {
695     Box(modifier = modifier.clip(RoundedCornerShape(5.dp)).background(theme.panelBg.copy(alpha = 0.5f)).border(1.dp, theme.
accent.copy(alpha = 0.7f), RoundedCornerShape(5.dp)).clickable(onClick = onClick), contentAlignment = Alignment.Center) {
696         Text("+", color = theme.textPrimary, fontSize = 16.sp, fontWeight = FontWeight.Bold)
697     }
698 }
699
700 @Composable
701 private fun CreatePaletteDialog(theme: AppTheme, onConfirm: (String) -> Unit, onDismiss: () -> Unit) {
702     var name by remember { mutableStateOf("") }
703     Dialog(onDismissRequest = onDismiss) {
704         Column(modifier = Modifier.width(280.dp).clip(RoundedCornerShape(16.dp)).background(theme.panelBg).padding(16.dp),
verticalArrangement = Arrangement.spacedBy(12.dp)) {
705             Text("Новая палитра", color = theme.textPrimary, fontSize = 16.sp, fontWeight = FontWeight.SemiBold)
706             Box(modifier = Modifier.fillMaxWidth().clip(RoundedCornerShape(8.dp)).background(theme.panelInset).border(1.dp,
theme.panelInset, RoundedCornerShape(8.dp)).padding(horizontal = 10.dp, vertical = 8.dp)) {

```

```

707         BasicTextField(value = name, onValueChange = { name = it.take(40) }, singleLine = true, textStyle = TextStyle(
color = theme.textPrimary, fontSize = 14.sp), cursorBrush = SolidColor(theme.accent), decorationBox = { inner -> if (name.isEmpty(
)) Text("Название", color = theme.textSecondary, fontSize = 14.sp); inner() }, modifier = Modifier.fillMaxWidth())
708     }
709     Row(horizontalArrangement = Arrangement.spacedBy(8.dp), modifier = Modifier.fillMaxWidth()) {
710         DialogButton(label = "Отмена", theme = theme, primary = false, modifier = Modifier.weight(1f), onClick =
onDismiss)
711         DialogButton(label = "Создать", theme = theme, primary = true, modifier = Modifier.weight(1f), onClick = {
onConfirm(name) })
712     }
713 }
714 }
715 }
716
717 @Composable
718 private fun DialogButton(label: String, theme: AppTheme, primary: Boolean, modifier: Modifier = Modifier, onClick: () ->
Unit) {
719     Box(modifier = modifier.clip(RoundedCornerShape(8.dp)).background(if (primary) theme.accent.copy(alpha = 0.35f) else
theme.panelInset).border(1.dp, if (primary) theme.accent else theme.panelInset, RoundedCornerShape(8.dp)).clickable(onClick =
onClick).padding(vertical = 10.dp), contentAlignment = Alignment.Center) {
720         Text(label, color = theme.textPrimary, fontSize = 13.sp, fontWeight = FontWeight.SemiBold)
721     }
722 }
723
724 @Composable
725 private fun SectionTitle(text: String, theme: AppTheme) {
726     Text(text, color = theme.textSecondary, fontSize = 11.sp, fontWeight = FontWeight.Medium)
727 }
728
729 @Composable
730 private fun RecentRow(colors: List<Color>, theme: AppTheme, onPick: (Color) -> Unit) {
731     Row(horizontalArrangement = Arrangement.spacedBy(4.dp), verticalAlignment = Alignment.CenterVertically, modifier =
Modifier.fillMaxWidth()) {
732         repeat(GRID_COLUMNS) { i ->
733             val c = colors.getOrNull(i)
734             if (c != null) Box(modifier = Modifier.weight(1f).aspectRatio(1f).clip(RoundedCornerShape(5.dp)).background(c).
border(1.dp, theme.panelInset, RoundedCornerShape(5.dp)).clickable { onPick(c) })
735             else Box(modifier = Modifier.weight(1f).aspectRatio(1f).clip(RoundedCornerShape(5.dp)).background(theme.
panelInset).border(1.dp, theme.panelInset, RoundedCornerShape(5.dp)))
736         }
737     }
738 }

```

98. app/src/main/java/com/wetinknext/ui/color/GlesColorState.kt

```

1  package com.wetinknext.ui.color
2
3  import android.content.Context
4  import androidx.compose.runtime.mutableStateListOf
5  import androidx.compose.runtime.mutableLongStateOf
6  import androidx.compose.runtime.mutableStateOf
7  import androidx.compose.runtime.getValue
8  import androidx.compose.runtime.setValue
9  import androidx.compose.ui.graphics.Color
10 import androidx.compose.ui.graphics.toArgb
11 import androidx.compose.ui.geometry.Offset
12 import org.json.JSONArray
13 import org.json.JSONObject
14
15 class GlesColorState(context: Context? = null) {
16     private val prefs = context?.applicationContext?.getSharedPreferences(PrefsName, Context.MODE_PRIVATE)
17
18     val recentColors = mutableStateListOf<Color>()
19     val userCollections = mutableStateListOf<ColorCollection>()
20     var pinnedCollectionId by mutableLongStateOf(prefs?.getLong(PinnedCollectionKey, NoPinnedCollection) ?:
NoPinnedCollection)
21     private set
22     var pinnedPaletteOffset by mutableStateOf(
23         Offset(
24             prefs?.getFloat(PinnedPaletteOffsetXKey, DefaultPinnedOffsetX) ?: DefaultPinnedOffsetX,
25             prefs?.getFloat(PinnedPaletteOffsetYKey, DefaultPinnedOffsetY) ?: DefaultPinnedOffsetY,
26         ),
27     )
28     private set
29
30     init {
31         loadRecentColors()
32         loadUserCollections()
33     }
34
35     fun pushRecentColor(color: Color) {
36         val argb = color.toArgb()
37         val existingIndex = recentColors.indexOfFirst { it.toArgb() == argb }
38         if (existingIndex == 0) return
39         if (existingIndex > 0) recentColors.removeAt(existingIndex)
40         recentColors.add(0, color)
41         while (recentColors.size > MaxRecentColors) {
42             recentColors.removeAt(recentColors.lastIndex)
43         }
44         saveRecentColors()
45     }
46
47     private fun loadRecentColors() {
48         val encoded = prefs?.getString(RecentColorsKey, null) ?: return
49         encoded.split(',')
50             .mapNotNull { it.toIntOrNull() }
51             .take(MaxRecentColors)
52             .forEach { recentColors.add(Color(it)) }
53     }
54
55     private fun saveRecentColors() {
56         prefs?.edit()
57             ?.putString(RecentColorsKey, recentColors.joinToString(",") { it.toArgb().toString() })
58             ?.apply()
59     }
60
61     fun addUserCollection(collection: ColorCollection) {
62         userCollections.add(0, collection.copy(builtin = false))
63         saveUserCollections()
64     }
65
66     fun deleteUserCollection(id: Long) {
67         userCollections.removeAll { it.id == id }
68         if (pinnedCollectionId == id) unpinCollection()
69         saveUserCollections()
70     }
71
72     fun pinCollection(id: Long) {
73         pinnedCollectionId = id
74         prefs?.edit()?.putLong(PinnedCollectionKey, id)?.apply()
75     }
76
77     fun unpinCollection() {
78         pinnedCollectionId = NoPinnedCollection
79         prefs?.edit()?.remove(PinnedCollectionKey)?.apply()
80     }
81
82     fun persistPinnedPaletteOffset(offset: Offset) {
83         pinnedPaletteOffset = offset
84         prefs?.edit()
85             ?.putFloat(PinnedPaletteOffsetXKey, offset.x)
86             ?.putFloat(PinnedPaletteOffsetYKey, offset.y)
87             ?.apply()
88     }
89

```

```

90 fun addColorToCollection(id: Long, color: Color) {
91     updateUserCollection(id) { collection ->
92         collection.copy(colors = collection.colors + color.toArgb())
93     }
94 }
95
96 fun replaceColorInCollection(id: Long, slot: Int, color: Color) {
97     updateUserCollection(id) { collection ->
98         if (slot !in collection.colors.indices) return@updateUserCollection collection
99         val colors = collection.colors.toMutableList()
100         colors[slot] = color.toArgb()
101         collection.copy(colors = colors)
102     }
103 }
104
105 fun removeColorFromCollection(id: Long, slot: Int) {
106     updateUserCollection(id) { collection ->
107         if (slot !in collection.colors.indices) return@updateUserCollection collection
108         val colors = collection.colors.toMutableList()
109         colors.removeAt(slot)
110         collection.copy(colors = colors)
111     }
112 }
113
114 private fun updateUserCollection(id: Long, transform: (ColorCollection) -> ColorCollection) {
115     val index = userCollections.indexOfFirst { it.id == id }
116     if (index < 0) return
117     userCollections[index] = transform(userCollections[index]).copy(builtin = false)
118     saveUserCollections()
119 }
120
121 private fun loadUserCollections() {
122     val encoded = prefs?.getString(UserCollectionsKey, null) ?: return
123     runCatching {
124         val array = JSONArray(encoded)
125         for (i in 0 until array.length()) {
126             val item = array.optJSONObject(i) ?: continue
127             val colorsJson = item.optJSONArray("colors") ?: JSONArray()
128             val colors = buildList {
129                 for (j in 0 until colorsJson.length()) {
130                     add(colorsJson.getInt(j))
131                 }
132             }
133             userCollections.add(
134                 ColorCollection(
135                     id = item.optLong("id", System.currentTimeMillis() + i),
136                     name = item.optString("name", "Новая палитра"),
137                     colors = colors,
138                     builtin = false,
139                 ),
140             )
141         }
142     }
143 }
144
145 private fun saveUserCollections() {
146     val array = JSONArray()
147     userCollections.filterNot { it.builtin }.forEach { collection ->
148         val colors = JSONArray()
149         collection.colors.forEach { colors.put(it) }
150         array.put(
151             JSONObject()
152                 .put("id", collection.id)
153                 .put("name", collection.name)
154                 .put("colors", colors),
155         )
156     }
157     prefs?.edit()
158         ?.putString(UserCollectionsKey, array.toString())
159         ?.apply()
160 }
161
162 private companion object {
163     const val PrefsName = "wetinknext_color_state"
164     const val RecentColorsKey = "recent_colors"
165     const val UserCollectionsKey = "user_collections"
166     const val PinnedCollectionKey = "pinned_collection"
167     const val PinnedPaletteOffsetXKey = "pinned_palette_offset_x"
168     const val PinnedPaletteOffsetYKey = "pinned_palette_offset_y"
169     const val NoPinnedCollection = Long.MIN_VALUE
170     const val DefaultPinnedOffsetX = 84f
171     const val DefaultPinnedOffsetY = 128f
172     const val MaxRecentColors = 14
173 }
174 }

```


99. app/src/main/java/com/wetinknext/ui/components/AdjustmentsPanel.kt

```

1  package com.wetinknext.ui.components
2
3  import androidx.compose.foundation.background
4  import androidx.compose.foundation.border
5  import androidx.compose.foundation.clickable
6  import androidx.compose.foundation.layout.*
7  import androidx.compose.foundation.rememberScrollState
8  import androidx.compose.foundation.shape.RoundedCornerShape
9  import androidx.compose.foundation.verticalScroll
10 import androidx.compose.material3.HorizontalDivider
11 import androidx.compose.material3.Text
12 import androidx.compose.runtime.Composable
13 import androidx.compose.ui.Alignment
14 import androidx.compose.ui.Modifier
15 import androidx.compose.ui.draw.clip
16 import androidx.compose.ui.draw.shadow
17 import androidx.compose.ui.graphics.Color
18 import androidx.compose.ui.text.font.FontWeight
19 import androidx.compose.ui.unit.dp
20 import androidx.compose.ui.unit.sp
21 import com.wetinknext.ui.theme.AppTheme
22
23 enum class AdjustmentAction(val title: String) {
24     BRIGHTNESS_CONTRAST("Яркость и контраст"),
25     THRESHOLD("Бинаризация"),
26     BRIGHTNESS_TO_OPACITY("Преобразовать яркость в непрозрачность"),
27 }
28
29 @Composable
30 fun AdjustmentsPanel(
31     theme: AppTheme,
32     onClose: () -> Unit,
33     onAction: (AdjustmentAction) -> Unit,
34     modifier: Modifier = Modifier
35 ) {
36     Column(
37         modifier = modifier
38         .width(280.dp)
39         .shadow(8.dp, RoundedCornerShape(16.dp))
40         .clip(RoundedCornerShape(16.dp))
41         .background(theme.panelBg.copy(alpha = 0.98f))
42         .border(1.dp, theme.panelStroke, RoundedCornerShape(16.dp))
43         .padding(vertical = 8.dp)
44     ) {
45         Text(
46             text = "Коррекция",
47             color = theme.textPrimary,
48             fontSize = 16.sp,
49             fontWeight = FontWeight.Bold,
50             modifier = Modifier.padding(horizontal = 16.dp, vertical = 8.dp)
51         )
52
53         Column(
54             modifier = Modifier
55                 .fillMaxWidth()
56                 .verticalScroll(rememberScrollState())
57         ) {
58             AdjustmentAction.entries.forEachIndexed { index, action ->
59                 AdjustmentItem(
60                     title = action.title,
61                     theme = theme,
62                     onClick = {
63                         onClose()
64                         onAction(action)
65                     }
66                 )
67                 if (index < AdjustmentAction.entries.size - 1) {
68                     HorizontalDivider(
69                         modifier = Modifier.padding(horizontal = 16.dp),
70                         thickness = 0.5.dp,
71                         color = theme.panelStroke.copy(alpha = 0.5f)
72                     )
73                 }
74             }
75         }
76     }
77 }
78
79 @Composable
80 private fun AdjustmentItem(
81     title: String,
82     theme: AppTheme,
83     onClick: () -> Unit
84 ) {
85     Row(
86         modifier = Modifier
87             .fillMaxWidth()
88             .clickable { onClick() }
89             .padding(horizontal = 16.dp, vertical = 12.dp),
90         verticalAlignment = Alignment.CenterVertically,

```

```
91         horizontalArrangement = Arrangement.SpaceBetween
92     ) {
93         Text(
94             text = title,
95             color = theme.textPrimary,
96             fontSize = 14.sp,
97             modifier = Modifier.weight(1f)
98         )
99     }
100 }
```

100. app/src/main/java/com/wetinknext/ui/components/BrightnessContrastPanel.kt

```

1  package com.wetinknext.ui.components
2
3  import androidx.compose.foundation.background
4  import androidx.compose.foundation.border
5  import androidx.compose.foundation.clickable
6  import androidx.compose.foundation.layout.*
7  import androidx.compose.foundation.shape.CircleShape
8  import androidx.compose.foundation.shape.RoundedCornerShape
9  import androidx.compose.material.icons.Icons
10 import androidx.compose.material.icons.filled.Check
11 import androidx.compose.material.icons.filled.Close
12 import androidx.compose.material3.Icon
13 import androidx.compose.material3.Slider
14 import androidx.compose.material3.SliderDefaults
15 import androidx.compose.material3.Text
16 import androidx.compose.runtime.Composable
17 import androidx.compose.ui.Alignment
18 import androidx.compose.ui.Modifier
19 import androidx.compose.ui.draw.clip
20 import androidx.compose.ui.graphics.Color
21 import androidx.compose.ui.text.font.FontWeight
22 import androidx.compose.ui.unit.dp
23 import androidx.compose.ui.unit.sp
24 import com.wetinknext.ui.theme.AppTheme
25 import kotlin.math.roundToInt
26
27 @Composable
28 fun BrightnessContrastPanel(
29     theme: AppTheme,
30     brightness: Float, // -1..1
31     contrast: Float,   // -1..1
32     onBrightnessChange: (Float) -> Unit,
33     onContrastChange: (Float) -> Unit,
34     onApply: () -> Unit,
35     onCancel: () -> Unit,
36     isApplyEnabled: Boolean = true,
37     modifier: Modifier = Modifier
38 ) {
39     Column(
40         modifier = modifier
41             .width(360.dp)
42             .clip(RoundedCornerShape(28.dp))
43             .background(theme.panelBg.copy(alpha = 0.95f))
44             .border(1.2.dp, theme.panelStroke, RoundedCornerShape(28.dp))
45             .padding(horizontal = 20.dp, vertical = 16.dp),
46         verticalArrangement = Arrangement.spacedBy(16.dp)
47     ) {
48         Row(
49             modifier = Modifier.fillMaxWidth(),
50             horizontalArrangement = Arrangement.SpaceBetween,
51             verticalAlignment = Alignment.CenterVertically
52         ) {
53             Text(
54                 text = "Яркость и контраст",
55                 color = theme.textPrimary,
56                 fontSize = 15.sp,
57                 fontWeight = FontWeight.Bold
58             )
59
60             Row(
61                 verticalAlignment = Alignment.CenterVertically,
62                 horizontalArrangement = Arrangement.spacedBy(12.dp)
63             ) {
64                 Box(
65                     modifier = Modifier
66                         .size(36.dp)
67                         .clip(CircleShape)
68                         .background(theme.panelInset)
69                         .clickable { onCancel() },
70                     contentAlignment = Alignment.Center
71                 ) {
72                     Icon(Icons.Default.Close, null, tint = theme.textPrimary, modifier = Modifier.size(20.dp))
73                 }
74
75                 Box(
76                     modifier = Modifier
77                         .size(36.dp)
78                         .clip(CircleShape)
79                         .background(if (isApplyEnabled) theme.accent else theme.panelInset)
80                         .clickable(enabled = isApplyEnabled) { onApply() },
81                     contentAlignment = Alignment.Center
82                 ) {
83                     Icon(Icons.Default.Check, null, tint = Color.White, modifier = Modifier.size(20.dp))
84                 }
85             }
86         }
87
88         // Brightness
89         Column(verticalArrangement = Arrangement.spacedBy(4.dp)) {
90             Row(

```

```

91         modifier = Modifier.fillMaxWidth(),
92         horizontalArrangement = Arrangement.SpaceBetween
93     ) {
94         Text("Яркость", color = theme.textSecondary, fontSize = 13.sp)
95         Text("${(brightness * 100).roundToInt()}", color = theme.accent, fontSize = 13.sp, fontWeight = FontWeight.
Bold)
96     }
97     Slider(
98         value = brightness,
99         onValueChange = onBrightnessChange,
100        valueRange = -1f..1f,
101        colors = SliderDefaults.colors(
102            thumbColor = theme.accent,
103            activeTrackColor = theme.accent,
104            inactiveTrackColor = theme.panelInset
105        )
106    )
107 }
108
109 // Contrast
110 Column(verticalArrangement = Arrangement.spacedBy(4.dp)) {
111     Row(
112         modifier = Modifier.fillMaxWidth(),
113         horizontalArrangement = Arrangement.SpaceBetween
114     ) {
115         Text("Контраст", color = theme.textSecondary, fontSize = 13.sp)
116         Text("${(contrast * 100).roundToInt()}", color = theme.accent, fontSize = 13.sp, fontWeight = FontWeight.Bold)
117     }
118     Slider(
119         value = contrast,
120         onValueChange = onContrastChange,
121         valueRange = -1f..1f,
122         colors = SliderDefaults.colors(
123             thumbColor = theme.accent,
124             activeTrackColor = theme.accent,
125             inactiveTrackColor = theme.panelInset
126         )
127     )
128 }
129 }
130 }

```

101. app/src/main/java/com/wetinknext/ui/components/BrightnessToOpacityPanel.kt

```

1 package com.wetinknext.ui.components
2
3 import androidx.compose.foundation.background
4 import androidx.compose.foundation.border
5 import androidx.compose.foundation.clickable
6 import androidx.compose.foundation.layout.*
7 import androidx.compose.foundation.shape.CircleShape
8 import androidx.compose.foundation.shape.RoundedCornerShape
9 import androidx.compose.material.icons.Icons
10 import androidx.compose.material.icons.filled.Check
11 import androidx.compose.material.icons.filled.Close
12 import androidx.compose.material3.Icon
13 import androidx.compose.material3.Switch
14 import androidx.compose.material3.Text
15 import androidx.compose.runtime.Composable
16 import androidx.compose.ui.Alignment
17 import androidx.compose.ui.Modifier
18 import androidx.compose.ui.draw.clip
19 import androidx.compose.ui.graphics.Color
20 import androidx.compose.ui.text.font.FontWeight
21 import androidx.compose.ui.unit.dp
22 import androidx.compose.ui.unit.sp
23 import com.wetinknext.ui.theme.AppTheme
24
25 @Composable
26 fun BrightnessToOpacityPanel(
27     theme: AppTheme,
28     isInverted: Boolean,
29     onInvertChange: (Boolean) -> Unit,
30     onApply: () -> Unit,
31     onCancel: () -> Unit,
32     isApplyEnabled: Boolean = true,
33     modifier: Modifier = Modifier
34 ) {
35     Column(
36         modifier = modifier
37         .width(360.dp)
38         .clip(RoundedCornerShape(28.dp))
39         .background(theme.panelBg.copy(alpha = 0.95f))
40         .border(1.2.dp, theme.panelStroke, RoundedCornerShape(28.dp))
41         .padding(horizontal = 20.dp, vertical = 16.dp),
42         verticalArrangement = Arrangement.spacedBy(16.dp)
43     ) {
44         Row(
45             modifier = Modifier.fillMaxWidth(),
46             horizontalArrangement = Arrangement.SpaceBetween,
47             verticalAlignment = Alignment.CenterVertically
48         ) {
49             Text(
50                 text = "Яркость в непрозрачность",
51                 color = theme.textPrimary,
52                 fontSize = 15.sp,
53                 fontWeight = FontWeight.Bold
54             )
55
56             Row(
57                 verticalAlignment = Alignment.CenterVertically,
58                 horizontalArrangement = Arrangement.spacedBy(12.dp)
59             ) {
60                 Box(
61                     modifier = Modifier
62                     .size(36.dp)
63                     .clip(CircleShape)
64                     .background(theme.panelInset)
65                     .clickable { onCancel() },
66                     contentAlignment = Alignment.Center
67                 ) {
68                     Icon(Icons.Default.Close, null, tint = theme.textPrimary, modifier = Modifier.size(20.dp))
69                 }
70
71                 Box(
72                     modifier = Modifier
73                     .size(36.dp)
74                     .clip(CircleShape)
75                     .background(if (isApplyEnabled) theme.accent else theme.panelInset)
76                     .clickable(enabled = isApplyEnabled) { onApply() },
77                     contentAlignment = Alignment.Center
78                 ) {
79                     Icon(Icons.Default.Check, null, tint = Color.White, modifier = Modifier.size(20.dp))
80                 }
81             }
82         }
83
84         Text(
85             text = "Светлые области станут прозрачными, тёмные – непрозрачными",
86             color = theme.textSecondary,
87             fontSize = 12.sp,
88             lineHeight = 16.sp
89         )
90     }

```

```

91         Row(
92             modifier = Modifier.fillMaxWidth(),
93             verticalAlignment = Alignment.CenterVertically,
94             horizontalArrangement = Arrangement.SpaceBetween
95         ) {
96             Text(
97                 text = "Инвертировать",
98                 color = theme.textPrimary,
99                 fontSize = 14.sp
100            )
101            Switch(
102                checked = isInverted,
103                onCheckedChange = onInvertChange
104            )
105        }
106    }
107 }

```

102. app/src/main/java/com/wetinknext/ui/components/BrushPanel.kt

```

1  package com.wetinknext.ui.components
2
3  import androidx.compose.foundation.Canvas
4  import androidx.compose.foundation.Image
5  import androidx.compose.foundation.background
6  import androidx.compose.foundation.border
7  import androidx.compose.foundation.clickable
8  import androidx.compose.foundation.gestures.detectTapGestures
9  import androidx.compose.foundation.layout.*
10 import androidx.compose.foundation.lazy.LazyColumn
11 import androidx.compose.foundation.lazy.items
12 import androidx.compose.foundation.shape.CircleShape
13 import androidx.compose.foundation.shape.RoundedCornerShape
14 import androidx.compose.material.icons.Icons
15 import androidx.compose.material.icons.filled.*
16 import androidx.compose.material3.Icon
17 import androidx.compose.material3.Text
18 import androidx.compose.runtime.*
19 import androidx.compose.ui.Alignment
20 import androidx.compose.ui.Modifier
21 import androidx.compose.ui.draw.clip
22 import androidx.compose.ui.draw.drawBehind
23 import androidx.compose.ui.geometry.Offset
24 import androidx.compose.ui.geometry.Size
25 import androidx.compose.ui.graphics.Color
26 import androidx.compose.ui.graphics.ImageBitmap
27 import androidx.compose.ui.graphics.vector.ImageVector
28 import androidx.compose.ui.input.pointer.pointerInput
29 import androidx.compose.ui.layout.ContentScale
30 import androidx.compose.ui.text.font.FontWeight
31 import androidx.compose.ui.unit.dp
32 import androidx.compose.ui.unit.sp
33 import com.wetinknext.engine.brush.BrushLibrary
34 import com.wetinknext.engine.brush.BrushPreset
35 import com.wetinknext.engine.brush.BrushUiCategory
36 import com.wetinknext.ui.theme.AppTheme
37
38 private val BRUSH_SWIPE_REVEAL_WIDTH = 88.dp
39
40 @Composable
41 fun BrushPanel(
42     currentBrush: BrushPreset,
43     onBrushSelect: (BrushPreset) -> Unit,
44     onBrushStudioOpen: (BrushPreset) -> Unit,
45     theme: AppTheme,
46     onDismiss: () -> Unit,
47     onDuplicate: (BrushPreset) -> Unit,
48     onDelete: (BrushPreset) -> Unit,
49     modifier: Modifier = Modifier,
50     categories: List<BrushUiCategory> = BrushLibrary.allCategories,
51     previews: Map<String, ImageBitmap> = emptyMap(),
52     previewKey: (BrushPreset) -> String = { it.id },
53     onRequestPreview: (BrushPreset) -> Unit = {},
54     title: String = "Кисти",
55 ) {
56     fun categoryIndexForCurrentBrush(): Int {
57         return categories.indexOfFirst { category -> category.brushes.any { it.id == currentBrush.id } }
58             .takeIf { it >= 0 }
59             ?: 0
60     }
61     var selectedCategoryIndex by remember(categories, currentBrush.id) {
62         mutableIntStateOf(categoryIndexForCurrentBrush())
63     }
64     LaunchedEffect(categories, currentBrush.id) {
65         selectedCategoryIndex = categoryIndexForCurrentBrush()
66     }
67     val selectedCategory = categories.getOrNull(selectedCategoryIndex)
68
69     PanelSurface(
70         modifier = modifier
71             .width(420.dp)
72             .height(560.dp),
73     ) {
74         Row(Modifier.fillMaxSize()) {
75             Column(
76                 modifier = Modifier
77                     .width(70.dp)
78                     .fillMaxHeight()
79                     .clip(RoundedCornerShape(topStart = 22.dp, bottomStart = 22.dp))
80                     .background(theme.panelInset)
81                     .drawBehind {
82                         drawLine(
83                             color = theme.panelStroke,
84                             start = Offset(size.width, 0f),
85                             end = Offset(size.width, size.height),
86                             strokeWidth = 1.dp.toPx(),
87                         )
88                     }
89                 .padding(vertical = 16.dp),
90                 horizontalAlignment = Alignment.CenterHorizontally,

```

```

91         verticalArrangement = Arrangement.spacedBy(20.dp),
92     ) {
93         categories.forEachIndexed { index, category ->
94             val isSelected = index == selectedCategoryId
95             Box(
96                 modifier = Modifier
97                     .size(44.dp)
98                     .clip(CircleShape)
99                     .background(if (isSelected) theme.accent.copy(alpha = 0.3f) else Color.Transparent)
100                     .border(
101                         if (isSelected) 1.dp else 0.dp,
102                         if (isSelected) theme.accentSoft else Color.Transparent,
103                         CircleShape,
104                     )
105                 .clickable { selectedCategoryId = index },
106                 contentAlignment = Alignment.Center,
107             ) {
108                 Icon(
109                     category.icon,
110                     contentDescription = category.name,
111                     tint = if (isSelected) theme.accent else theme.iconInactive,
112                     modifier = Modifier.size(24.dp),
113                 )
114             }
115         }
116     }
117
118     Column(
119         modifier = Modifier
120             .weight(1f)
121             .fillMaxHeight()
122             .padding(14.dp),
123     ) {
124         Row(
125             verticalAlignment = Alignment.CenterVertically,
126             horizontalArrangement = Arrangement.spacedBy(12.dp)
127         ) {
128             Column(verticalArrangement = Arrangement.spacedBy(1.dp)) {
129                 Text(
130                     text = title,
131                     color = theme.textPrimary,
132                     fontSize = 18.sp,
133                     fontWeight = FontWeight.Bold,
134                 )
135                 selectedCategory?.let { category ->
136                     Text(
137                         text = category.name,
138                         color = theme.accent,
139                         fontSize = 11.sp,
140                         fontWeight = FontWeight.SemiBold,
141                     )
142                 }
143             }
144             Spacer(Modifier.weight(1f))
145
146             Icon(
147                 imageVector = Icons.Default.Close,
148                 contentDescription = "Закреть",
149                 tint = theme.textSecondary,
150                 modifier = Modifier.size(24.dp).clickable { onDismiss() }
151             )
152         }
153
154         Spacer(Modifier.height(14.dp))
155
156         LazyColumn(
157             verticalArrangement = Arrangement.spacedBy(8.dp),
158             modifier = Modifier.fillMaxSize(),
159         ) {
160             items(selectedCategory?.brushes.orEmpty(), key = { it.id }) { brush ->
161                 val isSelected = brush.id == currentBrush.id
162                 BrushItem(
163                     brush = brush,
164                     isSelected = isSelected,
165                     theme = theme,
166                     preview = previews[previewKey(brush)],
167                     onRequestPreview = { onRequestPreview(brush) },
168                     onStudioOpen = { onBrushStudioOpen(brush) },
169                     onDuplicate = { onDuplicate(brush) },
170                     onDelete = { onDelete(brush) },
171                     onClick = {
172                         if (isSelected) onBrushStudioOpen(brush)
173                         else onBrushSelect(brush)
174                     },
175                 )
176             }
177
178             if (selectedCategory?.brushes.isNullOrEmpty()) {
179                 item {
180                     Text(
181                         text = "Кисти отсутствуют",
182                         color = theme.textSecondary,

```



```

183                                     fontSize = 14.sp,
184                                     modifier = Modifier.padding(top = 20.dp),
185                                 )
186                             }
187                         }
188                     }
189                 }
190             }
191         }
192     }
193
194     @Composable
195     private fun BrushItem(
196         brush: BrushPreset,
197         isSelected: Boolean,
198         theme: AppTheme,
199         preview: ImageBitmap?,
200         onRequestPreview: () -> Unit,
201         onStudioOpen: () -> Unit,
202         onDuplicate: () -> Unit,
203         onDelete: () -> Unit,
204         onClick: () -> Unit,
205     ) {
206         val contentBg = if (isSelected) theme.panelBgSolid else theme.panelInset
207         LaunchedEffect(brush.id, brush.settings, preview) {
208             if (preview == null) {
209                 onRequestPreview()
210             }
211         }
212
213         SwipeRevealRow(
214             revealWidth = BRUSH_SWIPE_REVEAL_WIDTH,
215             onSwipeRight = onStudioOpen,
216             modifier = Modifier
217                 .fillMaxWidth()
218                 .clip(RoundedCornerShape(8.dp))
219                 .background(theme.panelInset),
220             actions = {
221                 BrushSwipeActions(
222                     theme = theme,
223                     onDuplicate = onDuplicate,
224                     onDelete = onDelete,
225                     canDelete = true // Simplified for now
226                 )
227             },
228         ) {
229             Box(
230                 modifier = Modifier
231                     .fillMaxWidth()
232                     .background(contentBg)
233                     .border(1.dp, if (isSelected) theme.accentSoft else theme.panelStroke, RoundedCornerShape(8.dp))
234                     .pointerInput(brush.id) {
235                         detectTapGestures(
236                             onTap = { onClick() },
237                         )
238                     }
239                     .padding(10.dp),
240             ) {
241                 Row(
242                     verticalAlignment = Alignment.CenterVertically,
243                     horizontalArrangement = Arrangement.spacedBy(12.dp),
244                 ) {
245                     BrushPreviewStrip(
246                         preview = preview,
247                         brush = brush,
248                         theme = theme,
249                         modifier = Modifier
250                             .width(142.dp)
251                             .height(46.dp),
252                     )
253                     Column(Modifier.weight(1f)) {
254                         Text(
255                             text = brush.settings.name,
256                             color = if (isSelected) theme.accent else theme.textPrimary,
257                             fontSize = 15.sp,
258                             fontWeight = if (isSelected) FontWeight.SemiBold else FontWeight.Medium,
259                             maxLines = 1,
260                         )
261                         Text(
262                             text = "Размер: ${((brush.settings.baseRadiusPx * 2f).toInt())} px",
263                             color = theme.textSecondary,
264                             fontSize = 12.sp,
265                             maxLines = 1,
266                         )
267                     }
268                     if (isSelected) {
269                         Box(
270                             Modifier
271                                 .size(8.dp)
272                                 .clip(CircleShape)
273                                 .background(theme.accent),
274                         )
275                     }
276                 }
277             }
278         }
279     }

```

```

275     }
276     }
277 }
278 }
279 }
280
281 @Composable
282 private fun BrushSwipeActions(
283     theme: AppTheme,
284     onDuplicate: () -> Unit,
285     onDelete: () -> Unit,
286     canDelete: Boolean
287 ) {
288     Row(
289         modifier = Modifier
290             .fillMaxWidth()
291             .fillMaxHeight(),
292         horizontalArrangement = Arrangement.End,
293         verticalAlignment = Alignment.CenterVertically,
294     ) {
295         BrushSwipeButton(
296             icon = Icons.Default.ContentCopy,
297             label = "Дубль",
298             color = theme.accent,
299             onClick = onDuplicate
300         )
301         BrushSwipeButton(
302             icon = Icons.Default.Delete,
303             label = "Удал.",
304             color = theme.danger,
305             enabled = canDelete,
306             onClick = onDelete
307         )
308     }
309 }
310
311 @Composable
312 private fun BrushSwipeButton(
313     icon: ImageVector,
314     label: String,
315     color: Color,
316     enabled: Boolean = true,
317     onClick: () -> Unit,
318 ) {
319     Column(
320         modifier = Modifier
321             .width(44.dp)
322             .fillMaxHeight()
323             .background(if (enabled) color else color.copy(alpha = 0.3f))
324             .clickable(enabled = enabled, onClick = onClick)
325             .padding(vertical = 4.dp),
326         horizontalAlignment = Alignment.CenterHorizontally,
327         verticalArrangement = Arrangement.Center,
328     ) {
329         Icon(icon, contentDescription = label, tint = Color.White, modifier = Modifier.size(18.dp))
330         Text(label, color = Color.White, fontSize = 8.sp, fontWeight = FontWeight.Medium)
331     }
332 }
333
334 @Composable
335 private fun BrushPreviewStrip(
336     preview: ImageBitmap?,
337     brush: BrushPreset,
338     theme: AppTheme,
339     modifier: Modifier = Modifier,
340 ) {
341     Box(
342         modifier = modifier
343             .clip(RoundedCornerShape(4.dp))
344             .background(Color.White)
345             .border(1.dp, theme.panelStroke, RoundedCornerShape(4.dp)),
346         contentAlignment = Alignment.Center,
347     ) {
348         PreviewCheckerboard(Modifier.fillMaxSize(), cellSize = 7f)
349         if (preview != null) {
350             Image(
351                 bitmap = preview,
352                 contentDescription = null,
353                 contentScale = ContentScale.Fit,
354                 modifier = Modifier.fillMaxSize(),
355             )
356         } else {
357             Canvas(Modifier.fillMaxSize()) {
358                 drawLine(
359                     color = theme.accent.copy(alpha = brush.settings.opacity.coerceIn(0.25f, 1f)),
360                     start = Offset(size.width * 0.12f, size.height * 0.5f),
361                     end = Offset(size.width * 0.88f, size.height * 0.5f),
362                     strokeWidth = (brush.settings.baseRadiusPx * 2f).coerceIn(2f, 12f),
363                 )
364             }
365         }
366     }

```

```

367 }
368
369 @Composable
370 private fun PreviewCheckerboard(
371     modifier: Modifier = Modifier,
372     cellSize: Float,
373 ) {
374     Canvas(modifier) {
375         val light = Color(0xFFE9E9E9)
376         val dark = Color(0xFFD0D0D0)
377         var y = 0f
378         var row = 0
379         while (y < size.height) {
380             var x = 0f
381             var col = 0
382             while (x < size.width) {
383                 drawRect(
384                     color = if ((row + col) % 2 == 0) light else dark,
385                     topLeft = Offset(x, y),
386                     size = Size(cellSize, cellSize),
387                 )
388                 x += cellSize
389                 col += 1
390             }
391             y += cellSize
392             row += 1
393         }
394     }
395 }

```

103. app/src/main/java/com/wetinknext/ui/components/LayersPanel.kt

```

1  package com.wetinknext.ui.components
2
3  import android.graphics.BitmapFactory
4  import androidx.compose.foundation.background
5  import androidx.compose.foundation.border
6  import androidx.compose.foundation.clickable
7  import androidx.compose.foundation.layout.*
8  import androidx.compose.foundation.lazy.LazyColumn
9  import androidx.compose.foundation.lazy.items
10 import androidx.compose.foundation.shape.CircleShape
11 import androidx.compose.foundation.shape.RoundedCornerShape
12 import androidx.compose.material.icons.Icons
13 import androidx.compose.material.icons.filled.*
14 import androidx.compose.material3.*
15 import androidx.compose.runtime.*
16 import androidx.compose.ui.Alignment
17 import androidx.compose.ui.Modifier
18 import androidx.compose.ui.draw.clip
19 import androidx.compose.ui.graphics.Color
20 import androidx.compose.ui.graphics.asImageBitmap
21 import androidx.compose.ui.graphics.vector.ImageVector
22 import androidx.compose.ui.layout.ContentScale
23 import androidx.compose.ui.unit.Dp
24 import androidx.compose.ui.text.font.FontWeight
25 import androidx.compose.ui.text.style.TextOverflow
26 import androidx.compose.ui.unit.dp
27 import androidx.compose.ui.unit.sp
28 import com.wetinknext.ui.state.LayerItem
29 import com.wetinknext.ui.state.LayerState
30 import com.wetinknext.ui.theme.AppTheme
31 import com.wetinknext.ui.thumbnail.LayerThumbnail
32 import java.io.File
33 import kotlinx.coroutines.Dispatchers
34 import kotlinx.coroutines.withContext
35 import kotlin.math.roundToInt
36
37 private val PANEL_WIDTH = 320.dp
38
39 @Composable
40 fun LayersPanel(
41     state: LayerState,
42     theme: AppTheme,
43     modifier: Modifier = Modifier,
44     onDismiss: () -> Unit,
45     onAddLayer: () -> Unit,
46     onSelectLayer: (Long) -> Unit,
47     onVisibleChange: (Long, Boolean) -> Unit,
48     onOpacityChange: (Long, Float) -> Unit,
49     onDuplicateLayer: (Long) -> Unit,
50     onRemoveLayer: (Long) -> Unit,
51 ) {
52     PanelSurface(
53         modifier = modifier.width(PANEL_WIDTH),
54     ) {
55         Column(
56             modifier = Modifier.padding(10.dp),
57             verticalArrangement = Arrangement.spacedBy(8.dp),
58         ) {
59             Row(
60                 verticalAlignment = Alignment.CenterVertically,
61                 horizontalArrangement = Arrangement.spacedBy(6.dp),
62             ) {
63                 Text(
64                     "Слой",
65                     color = theme.textPrimary,
66                     fontWeight = FontWeight.Bold,
67                     fontSize = 18.sp,
68                 )
69                 Spacer(Modifier.weight(1f))
70                 HeaderIconButton(
71                     theme = theme,
72                     icon = Icons.Default.Add,
73                     description = "Добавить слой",
74                     onClick = onAddLayer,
75                 )
76                 HeaderIconButton(
77                     theme = theme,
78                     icon = Icons.Default.Close,
79                     description = "Закрыть",
80                     onClick = onDismiss,
81                 )
82             }
83
84             LazyColumn(
85                 modifier = Modifier
86                     .fillMaxWidth()
87                     .heightIn(max = 400.dp),
88                 verticalArrangement = Arrangement.spacedBy(4.dp),
89             ) {
90                 items(

```

```

91         items = state.layers.asReversed(),
92         key = { it.id },
93     ) { layerItem ->
94         LayerRow(
95             layer = layerItem,
96             theme = theme,
97             active = layerItem.id == state.activeLayerId,
98             onSelect = { onSelectLayer(layerItem.id) },
99             onVisibleChange = { onVisibleChange(layerItem.id, it) },
100             onOpacityChange = { onOpacityChange(layerItem.id, it) },
101             onDuplicate = { onDuplicateLayer(layerItem.id) },
102             onDelete = { onRemoveLayer(layerItem.id) },
103             canDelete = state.layers.size > 1 && !layerItem.locked
104         )
105     }
106 }
107 }
108 }
109 }
110
111 @Composable
112 private fun LayerRow(
113     layer: LayerItem,
114     theme: AppTheme,
115     active: Boolean,
116     onSelect: () -> Unit,
117     onVisibleChange: (Boolean) -> Unit,
118     onOpacityChange: (Float) -> Unit,
119     onDuplicate: () -> Unit,
120     onDelete: () -> Unit,
121     canDelete: Boolean,
122 ) {
123     val cardBg = if (active) theme.panelBgSolid else theme.panelBg
124
125     Column(
126         modifier = Modifier
127             .fillMaxWidth()
128             .clip(RoundedCornerShape(12.dp))
129             .background(cardBg)
130             .border(
131                 width = if (active) 1.2.dp else 0.dp,
132                 color = if (active) theme.accent else Color.Transparent,
133                 shape = RoundedCornerShape(12.dp),
134             )
135         .clickable { onSelect() }
136         .padding(8.dp),
137         verticalArrangement = Arrangement.spacedBy(4.dp)
138     ) {
139         Row(
140             modifier = Modifier.fillMaxWidth(),
141             verticalAlignment = Alignment.CenterVertically,
142         ) {
143             HeaderIconButton(
144                 theme = theme,
145                 icon = if (layer.visible) Icons.Default.Visibility else Icons.Default.VisibilityOff,
146                 description = "Видимость",
147                 onClick = { onVisibleChange(!layer.visible) },
148                 tint = if (layer.visible) (if (active) theme.accent else theme.textPrimary) else theme.iconInactive,
149             )
150
151             Spacer(Modifier.width(8.dp))
152
153             LayerThumbnail(
154                 layerId = layer.id,
155                 path = layer.thumbnailPath,
156                 thumbnailVersion = layer.thumbnailVersion,
157                 modifier = Modifier.height(36.dp),
158             )
159
160             Spacer(Modifier.width(8.dp))
161
162             Text(
163                 layer.name,
164                 modifier = Modifier.weight(1f),
165                 color = theme.textPrimary,
166                 fontSize = 14.sp,
167                 fontWeight = if (active) FontWeight.SemiBold else FontWeight.Normal,
168                 maxLines = 1,
169                 overflow = TextOverflow.Ellipsis,
170             )
171
172             if (canDelete) {
173                 HeaderIconButton(
174                     theme = theme,
175                     icon = Icons.Default.ContentCopy,
176                     description = "Дублировать слой",
177                     onClick = onDuplicate,
178                 )
179                 Spacer(Modifier.width(4.dp))
180                 HeaderIconButton(
181                     theme = theme,
182                     icon = Icons.Default.Delete,

```

```

183         description = "Удалить",
184         onClick = onDelete,
185         tint = theme.danger
186     )
187 }
188 }
189
190 if (active) {
191     Column(modifier = Modifier.fillMaxWidth().padding(horizontal = 4.dp)) {
192         Row(verticalAlignment = Alignment.CenterVertically) {
193             Text("Непрозрачность", color = theme.textSecondary, fontSize = 11.sp)
194             Spacer(Modifier.weight(1f))
195             Text(
196                 "${(layer.opacity * 100f).roundToInt()}%",
197                 color = theme.textSecondary,
198                 fontSize = 11.sp,
199             )
200         }
201         Slider(
202             value = layer.opacity.coerceIn(0f, 1f),
203             onValueChange = onOpacityChange,
204             valueRange = 0f..1f,
205             colors = SliderDefaults.colors(
206                 thumbColor = theme.accent,
207                 activeTrackColor = theme.accent,
208                 inactiveTrackColor = theme.accentMuted,
209             ),
210         )
211     }
212 }
213 }
214 }
215
216 /** Small, non-blocking thumbnail loader for the persisted layer WebP preview. */
217 @Composable
218 private fun LegacyLayerThumbnail(
219     layer: LayerItem,
220     theme: AppTheme,
221     size: Dp = 38.dp,
222 ) {
223     var preview by remember(layer.thumbnailPath, layer.thumbnailVersion) {
224         mutableStateOf<androidx.compose.ui.graphics.ImageBitmap?>(null)
225     }
226     LaunchedEffect(layer.thumbnailPath, layer.thumbnailVersion) {
227         preview = withContext(Dispatchers.IO) {
228             layer.thumbnailPath
229                 ?.let(::File)
230                 ?.takeIf(File::isFile)
231                 ?.let { BitmapFactory.decodeFile(it.absolutePath) }
232                 ?.asImageBitmap()
233         }
234     }
235
236     Box(
237         modifier = Modifier
238             .size(size)
239             .clip(RoundedCornerShape(7.dp))
240             .background(theme.panelInset)
241             .border(1.dp, theme.panelStroke, RoundedCornerShape(7.dp)),
242         contentAlignment = Alignment.Center,
243     ) {
244         if (preview != null) {
245             androidx.compose.foundation.Image(
246                 bitmap = checkNotNull(preview),
247                 contentDescription = "Превью слоя ${layer.name}",
248                 modifier = Modifier.fillMaxSize(),
249                 contentScale = ContentScale.Fit,
250             )
251         } else {
252             Text(
253                 text = layer.name.take(1).uppercase(),
254                 color = theme.iconInactive,
255                 fontSize = 12.sp,
256                 fontWeight = FontWeight.Bold,
257             )
258         }
259     }
260 }
261
262 @Composable
263 private fun HeaderIconButton(
264     theme: AppTheme,
265     icon: ImageVector,
266     description: String,
267     onClick: () -> Unit,
268     enabled: Boolean = true,
269     tint: Color = theme.textPrimary,
270 ) {
271     Box(
272         modifier = Modifier
273             .size(32.dp)
274             .clip(CircleShape)

```

```
275         .background(if (enabled) theme.panelInsetSoft else theme.panelInset)
276         .clickable(enabled = enabled, onClick = onClick),
277         contentAlignment = Alignment.Center,
278     ) {
279         Icon(
280             icon,
281             contentDescription = description,
282             tint = if (enabled) tint else theme.iconInactive,
283             modifier = Modifier.size(18.dp),
284         )
285     }
286 }
```

104. app/src/main/java/com/wetinknext/ui/components/PanelSurface.kt

```

1  package com.wetinknext.ui.components
2
3  import androidx.compose.foundation.background
4  import androidx.compose.foundation.border
5  import androidx.compose.foundation.layout.Box
6  import androidx.compose.foundation.layout.BoxScope
7  import androidx.compose.foundation.shape.RoundedCornerShape
8  import androidx.compose.runtime.Composable
9  import androidx.compose.ui.Modifier
10 import androidx.compose.ui.draw.clip
11 import androidx.compose.ui.draw.shadow
12 import androidx.compose.ui.input.pointer.PointerEventPass
13 import androidx.compose.ui.input.pointer.pointerInput
14 import androidx.compose.ui.unit.dp
15 import com.wetinknext.ui.theme.LocalAppTheme
16
17 @Composable
18 fun PanelSurface(
19     modifier: Modifier = Modifier,
20     content: @Composable BoxScope.() -> Unit,
21 ) {
22     val theme = LocalAppTheme.current
23     val shape = RoundedCornerShape(22.dp)
24     Box(
25         modifier = modifier
26             .shadow(12.dp, shape, ambientColor = theme.panelInset.copy(alpha = 0.5f), spotColor = theme.panelInset.copy(alpha
= 0.5f))
27             .clip(shape)
28             .background(theme.panelBg)
29             .border(1.2.dp, theme.panelStroke, shape)
30     ) {
31         Box(modifier = Modifier.matchParentSize().swallowChrome())
32         content()
33     }
34 }
35
36 private fun Modifier.swallowChrome(): Modifier = pointerInput(Unit) {
37     awaitPointerEventScope {
38         while (true) {
39             val event = awaitPointerEvent(PointerEventPass.Initial)
40             for (change in event.changes) {
41                 if (change.pressed && !change.previousPressed) {
42                     change.consume()
43                 }
44             }
45         }
46     }
47 }

```


105. app/src/main/java/com/wetinknext/ui/components/SelectionToolbar.kt

```

1 package com.wetinknext.ui.components
2
3 import androidx.compose.foundation.BorderStroke
4 import androidx.compose.foundation.background
5 import androidx.compose.foundation.clickable
6 import androidx.compose.foundation.layout.*
7 import androidx.compose.foundation.shape.CircleShape
8 import androidx.compose.foundation.shape.RoundedCornerShape
9 import androidx.compose.material.icons.Icons
10 import androidx.compose.material.icons.automirrored.filled.CallMerge
11 import androidx.compose.material.icons.filled.*
12 import androidx.compose.material3.Icon
13 import androidx.compose.material3.Surface
14 import androidx.compose.material3.Text
15 import androidx.compose.runtime.Composable
16 import androidx.compose.ui.Alignment
17 import androidx.compose.ui.Modifier
18 import androidx.compose.ui.draw.clip
19 import androidx.compose.ui.graphics.Color
20 import androidx.compose.ui.graphics.vector.ImageVector
21 import androidx.compose.ui.text.font.FontWeight
22 import androidx.compose.ui.unit.dp
23 import androidx.compose.ui.unit.sp
24 import com.wetinknext.ui.theme.AppTheme
25
26 enum class SelectionShapeUi {
27     FREEHAND,
28     RECTANGLE,
29     ELLIPSE,
30 }
31
32 @Composable
33 fun SelectionToolbar(
34     theme: AppTheme,
35     currentShape: SelectionShapeUi,
36     onShapeChange: (SelectionShapeUi) -> Unit,
37     onDone: () -> Unit,
38     modifier: Modifier = Modifier,
39 ) {
40     val panelBorder = BorderStroke(1.dp, theme.panelStroke)
41
42     Column(
43         modifier = modifier
44             .fillMaxWidth()
45             .navigationBarsPadding()
46             .padding(horizontal = 16.dp, vertical = 20.dp),
47         horizontalAlignment = Alignment.CenterHorizontally,
48         verticalArrangement = Arrangement.spacedBy(12.dp),
49     ) {
50         // Row 1 – shape modes
51         Surface(
52             color = theme.panelBg.copy(alpha = 0.94f),
53             shape = RoundedCornerShape(24.dp),
54             border = panelBorder,
55         ) {
56             Row(
57                 modifier = Modifier
58                     .width(340.dp)
59                     .height(32.dp)
60                     .padding(4.dp),
61                 horizontalArrangement = Arrangement.spacedBy(4.dp),
62                 verticalAlignment = Alignment.CenterVertically,
63             ) {
64                 val shapes = listOf(
65                     SelectionShapeUi.FREEHAND to "От руки",
66                     SelectionShapeUi.RECTANGLE to "Прямоугольник",
67                     SelectionShapeUi.ELLIPSE to "Эллипс",
68                 )
69                 shapes.forEach { (shape, label) ->
70                     val isSelected = currentShape == shape
71                     Box(
72                         modifier = Modifier
73                             .weight(1f)
74                             .fillMaxHeight()
75                             .clip(RoundedCornerShape(20.dp))
76                             .background(if (isSelected) theme.accent.copy(alpha = 0.4f) else Color.Transparent)
77                             .clickable { onShapeChange(shape) },
78                         contentAlignment = Alignment.Center,
79                     ) {
80                         Text(
81                             text = label,
82                             color = if (isSelected) Color.White.copy(alpha = 0.4f) else theme.textPrimary.copy(alpha = 0.4f),
83                             fontSize = 13.sp,
84                             fontWeight = if (isSelected) FontWeight.Bold else FontWeight.Normal,
85                             maxLines = 1,
86                         )
87                     }
88                 }
89             }
90         }
91     }
92 }

```

```

91
92 // Row 2 – Action icons (mostly disabled for now)
93 Surface(
94     color = theme.panelBg.copy(alpha = 0.94f),
95     shape = RoundedCornerShape(24.dp),
96     border = panelBorder,
97 ) {
98     Row(
99         modifier = Modifier.padding(horizontal = 4.dp, vertical = 4.dp),
100         horizontalArrangement = Arrangement.spacedBy(4.dp),
101         verticalAlignment = Alignment.CenterVertically,
102     ) {
103         SelectionIconButton(Icons.Default.Add, "Добавить", theme, isSelected = true, enabled = false)
104         SelectionIconButton(Icons.Default.Delete, "Удалить", theme, enabled = false)
105         SelectionIconButton(Icons.AutoMirrored.Filled.CallMerge, "Пересечь", theme, enabled = false)
106         SelectionIconButton(Icons.Default.Flip, "Инверсия", theme, enabled = false)
107         SelectionIconButton(Icons.Default.FormatColorFill, "Залить", theme, enabled = false)
108         SelectionIconButton(Icons.Default.ContentCopy, "Копировать", theme, enabled = false)
109         SelectionIconButton(Icons.Default.ContentCut, "Вырезать", theme, enabled = false)
110         SelectionIconButton(Icons.Default.AddToPhotos, "Вставить", theme, enabled = false)
111     }
112 }
113
114 // Row 3 – Reset / Delete / Done
115 Row(
116     horizontalArrangement = Arrangement.spacedBy(16.dp),
117     verticalAlignment = Alignment.CenterVertically,
118 ) {
119     SelectionRoundButton(Icons.Default.Refresh, "Сбросить", theme, enabled = false)
120     SelectionRoundButton(Icons.Default.Delete, "Удалить", theme, enabled = false)
121     Surface(
122         color = theme.accent,
123         shape = CircleShape,
124         modifier = Modifier.size(48.dp),
125     ) {
126         Box(
127             modifier = Modifier
128                 .fillMaxSize()
129                 .clickable { onDone() },
130             contentAlignment = Alignment.Center,
131         ) {
132             Icon(Icons.Default.Check, "Готово", tint = Color.White)
133         }
134     }
135 }
136 }
137 }
138
139 @Composable
140 private fun SelectionIconButton(
141     icon: ImageVector,
142     description: String,
143     theme: AppTheme,
144     isSelected: Boolean = false,
145     enabled: Boolean = true,
146     onClick: () -> Unit = {},
147 ) {
148     Box(
149         modifier = Modifier
150             .size(48.dp)
151             .clip(RoundedCornerShape(8.dp))
152             .background(if (isSelected && enabled) theme.accent.copy(alpha = 0.30f) else Color.Transparent)
153             .clickable(enabled = enabled) { onClick() },
154         contentAlignment = Alignment.Center,
155     ) {
156         Icon(
157             imageVector = icon,
158             contentDescription = description,
159             tint = if (!enabled) theme.iconInactive.copy(alpha = 0.5f) else if (isSelected) theme.accent else theme.
160 textPrimary,
161             modifier = Modifier.size(24.dp),
162         )
163     }
164 }
165
166 @Composable
167 private fun SelectionRoundButton(
168     icon: ImageVector,
169     description: String,
170     theme: AppTheme,
171     enabled: Boolean = true,
172     onClick: () -> Unit = {},
173 ) {
174     Surface(
175         color = if (enabled) theme.panelBg.copy(alpha = 0.9f) else theme.panelBg.copy(alpha = 0.4f),
176         shape = CircleShape,
177         border = BorderStroke(1.dp, if (enabled) theme.panelStroke else theme.panelStroke.copy(alpha = 0.4f)),
178         modifier = Modifier.size(48.dp),
179     ) {
180         Box(
181             modifier = Modifier
182                 .fillMaxSize()

```

```
182         .clickable(enabled = enabled) { onClick() },
183         contentAlignment = Alignment.Center,
184     ) {
185         Icon(
186             icon,
187             description,
188             tint = if (enabled) theme.textPrimary else theme.textPrimary.copy(alpha = 0.4f)
189         )
190     }
191 }
192 }
```

106. app/src/main/java/com/wetinknext/ui/components/SwipeRevealRow.kt

```

1 package com.wetinknext.ui.components
2
3 import androidx.compose.animation.core.animateFloatAsState
4 import androidx.compose.foundation.gestures.detectHorizontalDragGestures
5 import androidx.compose.foundation.layout.Arrangement
6 import androidx.compose.foundation.layout.Box
7 import androidx.compose.foundation.layout.Row
8 import androidx.compose.foundation.layout.RowScope
9 import androidx.compose.foundation.layout.fillMaxWidth
10 import androidx.compose.foundation.layout.offset
11 import androidx.compose.runtime.Composable
12 import androidx.compose.runtime.getValue
13 import androidx.compose.runtime.mutableStateOf
14 import androidx.compose.runtime.remember
15 import androidx.compose.runtime.setValue
16 import androidx.compose.ui.Modifier
17 import androidx.compose.ui.input.pointer.pointerInput
18 import androidx.compose.ui.platform.LocalDensity
19 import androidx.compose.ui.unit.Dp
20 import androidx.compose.ui.unit.IntOffset
21 import androidx.compose.ui.unit.dp
22 import kotlin.math.roundToInt
23
24 @Composable
25 fun SwipeRevealRow(
26     revealWidth: Dp,
27     actions: @Composable RowScope() -> Unit,
28     modifier: Modifier = Modifier,
29     rightSwipeThreshold: Dp = 56.dp,
30     onSwipeRight: (() -> Unit)? = null,
31     content: @Composable () -> Unit,
32 ) {
33     var rawOffset by remember { mutableStateOf(0f) }
34     var rightDragOffset by remember { mutableStateOf(0f) }
35     val revealPx = with(LocalDensity.current) { revealWidth.toPx() }
36     val rightSwipeThresholdPx = with(LocalDensity.current) { rightSwipeThreshold.toPx() }
37     val animatedOffset by animateFloatAsState(
38         targetValue = rawOffset.coerceIn(-revealPx, 0f),
39         label = "swipeRevealRow",
40     )
41
42     Box(modifier = modifier.fillMaxWidth()) {
43         Row(
44             modifier = Modifier.fillMaxWidth(),
45             horizontalArrangement = Arrangement.End,
46             content = actions,
47         )
48
49         Box(
50             modifier = Modifier
51                 .fillMaxWidth()
52                 .offset { IntOffset(animatedOffset.roundToInt(), 0) }
53                 .pointerInput(revealWidth) {
54                     detectHorizontalDragGestures(
55                         onHorizontalDrag = { change, dx ->
56                             if (dx < 0f || rawOffset < 0f) {
57                                 change.consume()
58                                 rawOffset += dx
59                                 rightDragOffset = 0f
60                             } else if (dx > 0f && rawOffset == 0f && onSwipeRight != null) {
61                                 change.consume()
62                                 rightDragOffset += dx
63                             }
64                         },
65                         onDragEnd = {
66                             if (rightDragOffset > rightSwipeThresholdPx) {
67                                 onSwipeRight?.invoke()
68                             }
69                             rawOffset = if (rawOffset < -revealPx * 0.4f) -revealPx else 0f
70                             rightDragOffset = 0f
71                         },
72                         onDragCancel = {
73                             rawOffset = 0f
74                             rightDragOffset = 0f
75                         },
76                     )
77                 },
78         ) {
79             content()
80         }
81     }
82 }

```

107. app/src/main/java/com/wetinknext/ui/components/ThresholdPanel.kt

```

1  package com.wetinknext.ui.components
2
3  import androidx.compose.foundation.background
4  import androidx.compose.foundation.border
5  import androidx.compose.foundation.clickable
6  import androidx.compose.foundation.layout.*
7  import androidx.compose.foundation.shape.CircleShape
8  import androidx.compose.foundation.shape.RoundedCornerShape
9  import androidx.compose.material.icons.Icons
10 import androidx.compose.material.icons.filled.Check
11 import androidx.compose.material.icons.filled.Close
12 import androidx.compose.material3.Icon
13 import androidx.compose.material3.Slider
14 import androidx.compose.material3.SliderDefaults
15 import androidx.compose.material3.Switch
16 import androidx.compose.material3.Text
17 import androidx.compose.runtime.Composable
18 import androidx.compose.ui.Alignment
19 import androidx.compose.ui.Modifier
20 import androidx.compose.ui.draw.clip
21 import androidx.compose.ui.graphics.Color
22 import androidx.compose.ui.text.font.FontWeight
23 import androidx.compose.ui.unit.dp
24 import androidx.compose.ui.unit.sp
25 import com.wetinknext.ui.theme.AppTheme
26 import kotlin.math.roundToInt
27
28 @Composable
29 fun ThresholdPanel(
30     theme: AppTheme,
31     threshold: Float, // 0..1
32     preserveTransparency: Boolean,
33     onThresholdChange: (Float) -> Unit,
34     onPreserveTransparencyChange: (Boolean) -> Unit,
35     onApply: () -> Unit,
36     onCancel: () -> Unit,
37     isApplyEnabled: Boolean = true,
38     modifier: Modifier = Modifier
39 ) {
40     Column(
41         modifier = modifier
42             .width(360.dp)
43             .clip(RoundedCornerShape(28.dp))
44             .background(theme.panelBg.copy(alpha = 0.95f))
45             .border(1.2.dp, theme.panelStroke, RoundedCornerShape(28.dp))
46             .padding(horizontal = 20.dp, vertical = 16.dp),
47         verticalArrangement = Arrangement.spacedBy(16.dp)
48     ) {
49         Row(
50             modifier = Modifier.fillMaxWidth(),
51             horizontalArrangement = Arrangement.SpaceBetween,
52             verticalAlignment = Alignment.CenterVertically
53         ) {
54             Text(
55                 text = "Бинаризация",
56                 color = theme.textPrimary,
57                 fontSize = 15.sp,
58                 fontWeight = FontWeight.Bold
59             )
60
61             Row(
62                 verticalAlignment = Alignment.CenterVertically,
63                 horizontalArrangement = Arrangement.spacedBy(12.dp)
64             ) {
65                 Box(
66                     modifier = Modifier
67                         .size(36.dp)
68                         .clip(CircleShape)
69                         .background(theme.panelInset)
70                         .clickable { onCancel() },
71                     contentAlignment = Alignment.Center
72                 ) {
73                     Icon(Icons.Default.Close, null, tint = theme.textPrimary, modifier = Modifier.size(20.dp))
74                 }
75
76                 Box(
77                     modifier = Modifier
78                         .size(36.dp)
79                         .clip(CircleShape)
80                         .background(if (isApplyEnabled) theme.accent else theme.panelInset)
81                         .clickable(enabled = isApplyEnabled) { onApply() },
82                     contentAlignment = Alignment.Center
83                 ) {
84                     Icon(Icons.Default.Check, null, tint = Color.White, modifier = Modifier.size(20.dp))
85                 }
86             }
87         }
88
89         Text(
90             text = "Пиксели светлее порога станут белыми, остальные – чёрными",

```

```

91         color = theme.textSecondary,
92         fontSize = 12.sp,
93         lineHeight = 16.sp
94     )
95
96     // Threshold
97     Column(verticalArrangement = Arrangement.spacedBy(4.dp)) {
98         Row(
99             modifier = Modifier.fillMaxWidth(),
100             horizontalArrangement = Arrangement.SpaceBetween
101         ) {
102             Text("Попор", color = theme.textSecondary, fontSize = 13.sp)
103             Text("${(threshold * 255).roundToInt()}", color = theme.accent, fontSize = 13.sp, fontWeight = FontWeight.
Bold)
104         }
105         Slider(
106             value = threshold,
107             onValueChange = onThresholdChange,
108             valueRange = 0f..1f,
109             colors = SliderDefaults.colors(
110                 thumbColor = theme.accent,
111                 activeTrackColor = theme.accent,
112                 inactiveTrackColor = theme.panelInset
113             )
114         )
115     }
116
117     Row(
118         modifier = Modifier.fillMaxWidth(),
119         verticalAlignment = Alignment.CenterVertically,
120         horizontalArrangement = Arrangement.SpaceBetween
121     ) {
122         Text(
123             text = "Сохранять прозрачность",
124             color = theme.textPrimary,
125             fontSize = 14.sp
126         )
127         Switch(
128             checked = preserveTransparency,
129             onCheckedChange = onPreserveTransparencyChange
130         )
131     }
132 }
133 }

```

108. app/src/main/java/com/wetinknext/ui/components/Toolbars.kt

```

1 package com.wetinknext.ui.components
2
3 import androidx.compose.animation.core.Spring
4 import androidx.compose.animation.core.animateFloatAsState
5 import androidx.compose.animation.core.spring
6 import androidx.compose.foundation.background
7 import androidx.compose.foundation.border
8 import androidx.compose.foundation.clickable
9 import androidx.compose.foundation.gestures.detectDragGestures
10 import androidx.compose.foundation.gestures.detectTapGestures
11 import androidx.compose.foundation.layout.*
12 import androidx.compose.foundation.shape.CircleShape
13 import androidx.compose.foundation.shape.RoundedCornerShape
14 import androidx.compose.material.icons.Icons
15 import androidx.compose.material.icons.automirrored.filled.Redo
16 import androidx.compose.material.icons.automirrored.filled.Undo
17 import androidx.compose.material.icons.filled.*
18 import androidx.compose.material3.Icon
19 import androidx.compose.runtime.*
20 import androidx.compose.ui.Alignment
21 import androidx.compose.ui.Modifier
22 import androidx.compose.ui.draw.clip
23 import androidx.compose.ui.graphics.Brush
24 import androidx.compose.ui.graphics.Color
25 import androidx.compose.ui.graphics.graphicsLayer
26 import androidx.compose.ui.graphics.vector.ImageVector
27 import androidx.compose.ui.input.pointer.pointerInput
28 import androidx.compose.ui.layout.onSizeChanged
29 import androidx.compose.ui.platform.LocalDensity
30 import androidx.compose.ui.res.vectorResource
31 import androidx.compose.ui.unit.IntOffset
32 import androidx.compose.ui.unit.dp
33 import com.wetinknext.R
34 import com.wetinknext.ui.theme.AppTheme
35
36 @Composable
37 fun TopToolbar(
38     theme: AppTheme,
39     currentColor: Color,
40     canUndo: Boolean,
41     canRedo: Boolean,
42     isSelectionActive: Boolean,
43     isTransformActive: Boolean,
44     isAnimationActive: Boolean,
45     isAdjustmentsActive: Boolean = false,
46     onUndoClick: () -> Unit,
47     onRedoClick: () -> Unit,
48     onSelectionClick: () -> Unit,
49     onTransformClick: () -> Unit,
50     onAnimationClick: () -> Unit,
51     onAdjustmentsClick: () -> Unit = {},
52     onSettingsClick: () -> Unit,
53     onLayersClick: () -> Unit,
54     onColorClick: () -> Unit,
55 ) {
56     Row(
57         modifier = Modifier
58             .padding(top = 12.dp, end = 12.dp)
59             .clip(RoundedCornerShape(25.dp))
60             .background(theme.panelBg.copy(alpha = 0.9f))
61             .border(1.2.dp, theme.panelStroke, RoundedCornerShape(25.dp))
62             .padding(horizontal = 8.dp, vertical = 6.dp),
63         verticalAlignment = Alignment.CenterVertically,
64         horizontalArrangement = Arrangement.spacedBy(10.dp)
65     ) {
66         ToolbarIcon(Icons.AutoMirrored.Filled.Undo, theme, isSelected = false, enabled = canUndo, onClick = onUndoClick)
67         ToolbarIcon(Icons.AutoMirrored.Filled.Redo, theme, isSelected = false, enabled = canRedo, onClick = onRedoClick)
68
69         // SelectAll has a visually denser glyph than Fullscreen; its 18 dp drawing size
70         // matches Transform's perceived 20 dp footprint while both buttons stay 34 dp.
71         ToolbarIcon(Icons.Default.SelectAll, theme, isSelected = isSelectionActive, iconSize = 18.dp, onClick =
onSelectionClick)
72         ToolbarIcon(Icons.Default.Movie, theme, isSelected = isAnimationActive, onClick = onAnimationClick)
73         ToolbarIcon(Icons.Default.Fullscreen, theme, isSelected = isTransformActive, onClick = onTransformClick)
74         ToolbarIcon(Icons.Default.Tune, theme, isSelected = isAdjustmentsActive, onClick = onAdjustmentsClick)
75         ToolbarIcon(Icons.Default.Layers, theme, onClick = onLayersClick)
76         ToolbarIcon(Icons.Default.Settings, theme, contentDescription = "Настройки", onClick = onSettingsClick)
77
78         ColorPickerDot(
79             color = currentColor,
80             theme = theme,
81             onClick = onColorClick
82         )
83     }
84 }
85
86 /** Compact actions placed directly under the left brush toolbar. */
87 @Composable
88 fun LeftCanvasActions(
89     theme: AppTheme,

```

```

90     onClearLayerClick: () -> Unit,
91     onMirrorClick: () -> Unit,
92 ) {
93     Column(
94         modifier = Modifier.padding(start = 12.dp, top = 10.dp),
95         verticalArrangement = Arrangement.spacedBy(10.dp),
96         horizontalAlignment = Alignment.CenterHorizontally,
97     ) {
98         CanvasActionButton(
99             icon = Icons.Default.DeleteSweep,
100             description = "Очистить активный слой",
101             theme = theme,
102             onClick = onClearLayerClick,
103         )
104         CanvasActionButton(
105             icon = Icons.Default.Flip,
106             description = "Зеркальный просмотр холста",
107             theme = theme,
108             onClick = onMirrorClick,
109         )
110     }
111 }
112
113 @Composable
114 fun CanvasActionButton(
115     icon: ImageVector,
116     description: String,
117     theme: AppTheme,
118     onClick: () -> Unit,
119 ) {
120     Box(
121         modifier = Modifier
122             .size(44.dp)
123             .clip(CircleShape)
124             .background(theme.panelBg.copy(alpha = 0.9f))
125             .border(1.2.dp, theme.panelStroke, CircleShape)
126             .clickable(onClick = onClick),
127         contentAlignment = Alignment.Center,
128     ) {
129         Icon(icon, contentDescription = description, tint = theme.textPrimary, modifier = Modifier.size(20.dp))
130     }
131 }
132
133 @Composable
134 fun ColorPickerDot(
135     color: Color,
136     theme: AppTheme,
137     onClick: () -> Unit
138 ) {
139     var isPressed by remember { mutableStateOf(false) }
140
141     val scale by animateFloatAsState(
142         targetValue = if (isPressed) 1.15f else 1f,
143         animationSpec = spring(dampingRatio = Spring.DampingRatioMediumBouncy, stiffness = Spring.StiffnessLow),
144         label = "scale"
145     )
146
147     Box(
148         modifier = Modifier
149             .graphicsLayer {
150                 scaleX = scale
151                 scaleY = scale
152             }
153             .size(30.dp)
154             .clip(CircleShape)
155             .background(color)
156             .border(1.5.dp, theme.panelStroke, CircleShape)
157             .clickable { onClick() }
158     )
159 }
160
161 @Composable
162 fun SideToolbar(
163     theme: AppTheme,
164     brushSize: Float,
165     brushOpacity: Float,
166     isEraser: Boolean,
167     onBrushSizeChange: (Float) -> Unit,
168     onBrushOpacityChange: (Float) -> Unit,
169     onBrushClick: () -> Unit,
170     onEraserClick: (Boolean) -> Unit,
171 ) {
172     Column(
173         modifier = Modifier
174             .padding(start = 12.dp)
175             .width(44.dp)
176             .clip(RoundedCornerShape(22.dp))
177             .background(theme.panelBg.copy(alpha = 0.9f))
178             .border(1.2.dp, theme.panelStroke, RoundedCornerShape(22.dp))
179             .padding(vertical = 10.dp),
180         horizontalAlignment = Alignment.CenterHorizontally,
181         verticalArrangement = Arrangement.spacedBy(12.dp)

```



```

182     ) {
183         ToolbarIcon(Icons.Default.Brush, theme, isSelected = !isEraser, onClick = {
184             onEraserClick(false)
185             onBrushClick()
186         })
187         ToolbarIcon(ImageVector.vectorResource(R.drawable.ic_eraser), theme, isSelected = isEraser, onClick = { onEraserClick(
true) })
188
189         Spacer(Modifier.height(4.dp))
190
191         VerticalSlider(
192             value = brushSize,
193             onValueChange = onBrushSizeChange,
194             valueRange = 2f..400f,
195             theme = theme
196         )
197
198         VerticalSlider(
199             value = brushOpacity,
200             onValueChange = onBrushOpacityChange,
201             valueRange = 0f..1f,
202             theme = theme
203         )
204     }
205 }
206
207 @Composable
208 private fun VerticalSlider(
209     value: Float,
210     onValueChange: (Float) -> Unit,
211     valueRange: ClosedFloatingPointRange<Float> = 0f..1f,
212     theme: AppTheme,
213     modifier: Modifier = Modifier
214 ) {
215     val range = valueRange.endInclusive - valueRange.start
216     var trackHeightPx by remember { mutableFloatStateOf(1f) }
217     val density = LocalDensity.current
218
219     val norm = ((value - valueRange.start) / range).coerceIn(0f, 1f)
220
221     fun updateFromY(y: Float) {
222         val n = (1f - (y / trackHeightPx)).coerceIn(0f, 1f)
223         onValueChange(valueRange.start + n * range)
224     }
225
226     Box(
227         modifier = modifier
228             .width(28.dp)
229             .height(120.dp)
230             .clip(RoundedCornerShape(14.dp))
231             .background(theme.accentMuted.copy(alpha = 0.15f))
232             .border(1.dp, theme.panelStroke, RoundedCornerShape(14.dp))
233             .onSizeChanged { trackHeightPx = it.height.toFloat() }
234             .pointerInput(valueRange) {
235                 detectTapGestures { offset -> updateFromY(offset.y) }
236             }
237             .pointerInput(valueRange) {
238                 detectDragGestures { change, _ ->
239                     change.consume()
240                     updateFromY(change.position.y)
241                 }
242             }
243     ) {
244         Box(
245             Modifier
246                 .align(Alignment.BottomCenter)
247                 .fillMaxWidth()
248                 .fillMaxHeight(norm)
249                 .background(Brush.verticalGradient(listOf(theme.accentSoft, theme.accent)))
250         )
251         Box(
252             Modifier
253                 .align(Alignment.TopCenter)
254                 .offset {
255                     val thumbSizePx = with(density) { 22.dp.toPx() }
256                     IntOffset(0, ((1f - norm) * (trackHeightPx - thumbSizePx)).toInt())
257                 }
258                 .padding(2.dp)
259                 .size(22.dp)
260                 .clip(CircleShape)
261                 .background(theme.textPrimary)
262                 .border(1.dp, theme.panelStroke, CircleShape)
263         )
264     }
265 }
266
267 @Composable
268 private fun ToolbarIcon(
269     icon: ImageVector,
270     theme: AppTheme,
271     isSelected: Boolean = false,
272     enabled: Boolean = true,

```

```

273     contentDescription: String? = null,
274     iconSize: androidx.compose.ui.unit.Dp = 20.dp,
275     onClick: () -> Unit = {}
276 ) {
277     Box(
278         modifier = Modifier
279             .size(34.dp)
280             .clip(CircleShape)
281             .background(if (isSelected) theme.accentMuted.copy(alpha = 0.3f) else Color.Transparent)
282             .border(if (isSelected) 1.dp else 0.dp, if (isSelected) theme.accentSoft else Color.Transparent, CircleShape)
283             .clickable(enabled = enabled) { onClick() },
284         contentAlignment = Alignment.Center
285     ) {
286         Icon(
287             icon,
288             contentDescription = contentDescription,
289             tint = if (!enabled) theme.iconInactive.copy(alpha = 0.5f) else if (isSelected) theme.accent else theme.
textPrimary,
290             modifier = Modifier.size(iconSize)
291         )
292     }
293 }

```

109. app/src/main/java/com/wetinknext/ui/components/TransformMenuView.kt

```

1 package com.wetinknext.ui.components
2
3 import androidx.compose.foundation.BorderStroke
4 import androidx.compose.foundation.background
5 import androidx.compose.foundation.clickable
6 import androidx.compose.foundation.layout.*
7 import androidx.compose.foundation.shape.CircleShape
8 import androidx.compose.foundation.shape.RoundedCornerShape
9 import androidx.compose.material.icons.Icons
10 import androidx.compose.material.icons.filled.*
11 import androidx.compose.material3.*
12 import androidx.compose.runtime.Composable
13 import androidx.compose.ui.Alignment
14 import androidx.compose.ui.Modifier
15 import androidx.compose.ui.draw.clip
16 import androidx.compose.ui.draw.rotate
17 import androidx.compose.ui.graphics.Color
18 import androidx.compose.ui.graphics.vector.ImageVector
19 import androidx.compose.ui.text.font.FontWeight
20 import androidx.compose.ui.unit.dp
21 import androidx.compose.ui.unit.sp
22 import com.wetinknext.ui.theme.AppTheme
23
24 enum class TransformModeUi {
25     FREEFORM,
26     UNIFORM,
27     DISTORT,
28     WARP
29 }
30
31 interface TransformActions {
32     fun reset()
33     fun cancel()
34     fun apply()
35     fun flipHorizontal()
36     fun flipVertical()
37     fun setMode(mode: TransformModeUi)
38 }
39
40 @Composable
41 fun TransformMenuView(
42     theme: AppTheme,
43     actions: TransformActions,
44     currentMode: TransformModeUi,
45     modifier: Modifier = Modifier
46 ) {
47     val panelBorder = BorderStroke(1.dp, theme.panelStroke)
48
49     Column(
50         modifier = modifier
51             .fillMaxWidth()
52             .navigationBarsPadding()
53             .padding(horizontal = 16.dp, vertical = 20.dp),
54         horizontalAlignment = Alignment.CenterHorizontally,
55         verticalArrangement = Arrangement.spacedBy(12.dp)
56     ) {
57         // Row 1: Modes
58         Surface(
59             color = theme.panelBg.copy(alpha = 0.94f),
60             shape = RoundedCornerShape(24.dp),
61             border = panelBorder
62         ) {
63             Row(
64                 modifier = Modifier
65                     .width(340.dp)
66                     .height(32.dp)
67                     .padding(4.dp),
68                 horizontalArrangement = Arrangement.spacedBy(4.dp)
69             ) {
70                 TransformModeButton("Свободно", TransformModeUi.FREEFORM, currentMode, theme, actions::setMode)
71                 TransformModeButton("Пропорц.", TransformModeUi.UNIFORM, currentMode, theme, actions::setMode)
72                 TransformModeButton("Исказить", TransformModeUi.DISTORT, currentMode, theme, actions::setMode)
73                 TransformModeButton("Деформ.", TransformModeUi.WARP, currentMode, theme, actions::setMode)
74             }
75         }
76
77         // Row 2: Actions
78         Surface(
79             color = theme.panelBg.copy(alpha = 0.94f),
80             shape = RoundedCornerShape(24.dp),
81             border = panelBorder
82         ) {
83             Row(
84                 modifier = Modifier.padding(horizontal = 4.dp, vertical = 4.dp),
85                 horizontalArrangement = Arrangement.spacedBy(4.dp),
86                 verticalAlignment = Alignment.CenterVertically
87             ) {
88                 ActionIconButton(Icons.Default.Flip, "Отразить Г", theme, enabled = false) { actions.flipHorizontal() }
89                 ActionIconButton(Icons.Default.Flip, "Отразить В", theme, iconModifier = Modifier.rotate(90f), enabled =
false) { actions.flipVertical() }

```

```

90         IconButton(Icons.Default.RotateRight, "Поворот 45", theme, enabled = false) { /* ... */ }
91         IconButton(Icons.Default.FitScreen, "Вписать", theme, enabled = false) { actions.reset() }
92
93         VerticalDivider(modifier = Modifier.height(24.dp).padding(horizontal = 4.dp), color = theme.panelStroke)
94
95         // Placeholder for interpolation/snapping
96         Box(modifier = Modifier.size(48.dp), contentAlignment = Alignment.Center) {
97             Icon(Icons.Default.LinkOff, null, tint = theme.textSecondary.copy(alpha = 0.4f), modifier = Modifier.size(
24.dp))
98         }
99     }
100 }
101
102 // Row 3: Main Controls
103 Row(
104     modifier = Modifier.fillMaxWidth(),
105     horizontalArrangement = Arrangement.spacedBy(16.dp, Alignment.CenterHorizontally),
106     verticalAlignment = Alignment.CenterVertically
107 ) {
108     // Reset
109     TransformRoundButton(Icons.Default.Refresh, "Сбросить", theme, enabled = false) { actions.reset() }
110
111     // Cancel
112     TransformRoundButton(Icons.Default.Close, "Отмена", theme) { actions.cancel() }
113
114     // Apply
115     Surface(
116         color = theme.accent.copy(alpha = 0.4f),
117         shape = CircleShape,
118         modifier = Modifier.size(48.dp)
119     ) {
120         Box(
121             modifier = Modifier.fillMaxSize(),
122             contentAlignment = Alignment.Center
123         ) {
124             Icon(Icons.Default.Check, "Применить", tint = Color.White.copy(alpha = 0.4f))
125         }
126     }
127 }
128 }
129 }
130
131 @Composable
132 private fun RowScope.TransformModeButton(
133     label: String,
134     mode: TransformModeUi,
135     currentMode: TransformModeUi,
136     theme: AppTheme,
137     onClick: (TransformModeUi) -> Unit
138 ) {
139     val isSelected = mode == currentMode
140     val enabled = false // Transform engine not ready
141     Box(
142         modifier = Modifier
143             .weight(1f)
144             .fillMaxHeight()
145             .clip(RoundedCornerShape(20.dp))
146             .background(if (isSelected) theme.accent.copy(alpha = 0.4f) else Color.Transparent)
147             .clickable(enabled = enabled) { onClick(mode) },
148         contentAlignment = Alignment.Center
149     ) {
150         Text(
151             text = label,
152             color = if (isSelected) Color.White.copy(alpha = 0.4f) else theme.textPrimary.copy(alpha = 0.4f),
153             fontSize = 13.sp,
154             fontWeight = if (isSelected) FontWeight.Bold else FontWeight.Normal
155         )
156     }
157 }
158
159 @Composable
160 private fun ActionIconButton(
161     icon: ImageVector,
162     description: String,
163     theme: AppTheme,
164     iconModifier: Modifier = Modifier,
165     enabled: Boolean = true,
166     onClick: () -> Unit
167 ) {
168     Box(
169         modifier = Modifier
170             .size(48.dp)
171             .clickable(enabled = enabled) { onClick() },
172         contentAlignment = Alignment.Center
173     ) {
174         Icon(
175             imageVector = icon,
176             contentDescription = description,
177             tint = if (enabled) theme.textPrimary else theme.textPrimary.copy(alpha = 0.4f),
178             modifier = iconModifier.size(24.dp)
179         )
180     }

```

```

181 }
182
183 @Composable
184 private fun TransformRoundButton(
185     icon: ImageVector,
186     description: String,
187     theme: AppTheme,
188     enabled: Boolean = true,
189     onClick: () -> Unit
190 ) {
191     Surface(
192         color = if (enabled) theme.panelBg.copy(alpha = 0.9f) else theme.panelBg.copy(alpha = 0.4f),
193         shape = CircleShape,
194         border = BorderStroke(1.dp, if (enabled) theme.panelStroke else theme.panelStroke.copy(alpha = 0.4f)),
195         modifier = Modifier.size(48.dp)
196     ) {
197         Box(
198             modifier = Modifier.fillMaxSize().clickable(enabled = enabled) { onClick() },
199             contentAlignment = Alignment.Center
200         ) {
201             Icon(icon, description, tint = if (enabled) theme.textPrimary else theme.textPrimary.copy(alpha = 0.4f))
202         }
203     }
204 }

```

110. app/src/main/java/com/wetinknext/ui/home/HomeScreen.kt

```

1  package com.wetinknext.ui.home
2
3  import androidx.compose.foundation.background
4  import androidx.compose.foundation.border
5  import androidx.compose.foundation.clickable
6  import androidx.compose.foundation.Image
7  import androidx.compose.foundation.layout.*
8  import androidx.compose.foundation.lazy.grid.GridCells
9  import androidx.compose.foundation.lazy.grid.LazyVerticalGrid
10 import androidx.compose.foundation.lazy.grid.items
11 import androidx.compose.foundation.rememberScrollState
12 import androidx.compose.foundation.shape.RoundedCornerShape
13 import androidx.compose.foundation.verticalScroll
14 import androidx.compose.material.icons.Icons
15 import androidx.compose.material.icons.outlined.Add
16 import androidx.compose.material.icons.outlined.Delete
17 import androidx.compose.material.icons.outlined.ContentCopy
18 import androidx.compose.material.icons.outlined.Edit
19 import androidx.compose.material.icons.outlined.MoreVert
20 import androidx.compose.material3.*
21 import androidx.compose.runtime.*
22 import androidx.compose.ui.Alignment
23 import androidx.compose.ui.Modifier
24 import androidx.compose.ui.draw.clip
25 import androidx.compose.ui.graphics.Color
26 import androidx.compose.ui.graphics.ImageBitmap
27 import androidx.compose.ui.graphics.asImageBitmap
28 import android.graphics.BitmapFactory
29 import android.util.LruCache
30 import androidx.compose.ui.graphics.graphicsLayer
31 import androidx.compose.ui.text.font.FontWeight
32 import androidx.compose.ui.text.style.TextAlign
33 import androidx.compose.ui.text.style.TextOverflow
34 import androidx.compose.ui.unit.dp
35 import androidx.compose.ui.unit.sp
36 import com.wetinknext.ui.theme.AppTheme
37 import java.text.SimpleDateFormat
38 import java.util.Date
39 import java.util.Locale
40 import kotlinx.coroutines.Dispatchers
41 import kotlinx.coroutines.withContext
42
43 // Minimal models for Home UI shell
44 data class HomeProject(
45     val id: String,
46     val name: String,
47     val canvasWidth: Int,
48     val canvasHeight: Int,
49     val updatedAtMs: Long,
50     val thumbnailBytes: ByteArray? = null,
51     val thumbnailVersion: Long = 0L,
52 )
53
54 data class DeletedHomeProject(
55     val project: HomeProject,
56     val deletedAtMs: Long,
57 )
58
59 private data class ProjectThumbnailKey(
60     val projectId: String,
61     val version: Long,
62 )
63
64 /** Bytes are primed from ProjectSummary; decoded bitmaps survive grid row recycling. */
65 private object ProjectThumbnailBitmapCache {
66     private val encoded = LruCache<ProjectThumbnailKey, ByteArray>(32)
67     private val decoded = LruCache<ProjectThumbnailKey, ImageBitmap>(32)
68
69     fun prime(key: ProjectThumbnailKey, bytes: ByteArray?) {
70         if (bytes != null) encoded.put(key, bytes)
71     }
72
73     fun bitmap(key: ProjectThumbnailKey): ImageBitmap? = decoded.get(key)
74
75     fun decode(key: ProjectThumbnailKey): ImageBitmap? {
76         decoded.get(key)?.let { return it }
77         val bytes = encoded.get(key) ?: return null
78         return BitmapFactory.decodeByteArray(bytes, 0, bytes.size)
79             ?.asImageBitmap()
80             ?.also { decoded.put(key, it) }
81     }
82 }
83
84 @Composable
85 private fun rememberProjectThumbnail(
86     projectId: String,
87     version: Long,
88 ): ImageBitmap? {
89     val key = remember(projectId, version) { ProjectThumbnailKey(projectId, version) }
90     // Preserve the old preview for this project until a newly saved WebP is decoded.

```

```

91     var bitmap by remember(projectId) { mutableStateOf(ProjectThumbnailBitmapCache.bitmap(key)) }
92
93     LaunchedEffect(key) {
94         withContext(Dispatchers.Default) {
95             ProjectThumbnailBitmapCache.decode(key)
96         }.let { bitmap = it }
97     }
98     return bitmap
99 }
100
101 @Composable
102 fun HomeScreen(
103     theme: AppTheme,
104     projects: List<HomeProject>,
105     deletedProjects: List<DeletedHomeProject> = emptyList(),
106     onOpenProject: (HomeProject) -> Unit,
107     onCreateProject: (name: String, width: Int, height: Int, dpi: Int, colorProfile: String) -> Unit,
108     onRenameProject: (HomeProject, String) -> Unit,
109     onDuplicateProject: (HomeProject) -> Unit,
110     onDeleteProject: (HomeProject) -> Unit,
111     onRestoreProject: (DeletedHomeProject) -> Unit,
112     onDeleteForever: (DeletedHomeProject) -> Unit,
113 ) {
114     var showNewDialog by remember { mutableStateOf(false) }
115     var renaming by remember { mutableStateOf<HomeProject?>(null) }
116     var deleting by remember { mutableStateOf<HomeProject?>(null) }
117     var showTrash by remember { mutableStateOf(false) }
118
119     Box(
120         modifier = Modifier
121             .fillMaxSize()
122             .background(theme.panelBgSolid),
123     ) {
124         Column(modifier = Modifier.fillMaxSize()) {
125             HomeTopBar(
126                 theme = theme,
127                 total = projects.size,
128                 onCreate = { showNewDialog = true },
129                 onTrash = { showTrash = true },
130             )
131             LazyVerticalGrid(
132                 columns = GridCells.Adaptive(minSize = 180.dp),
133                 contentPadding = PaddingValues(16.dp),
134                 horizontalArrangement = Arrangement.spacedBy(12.dp),
135                 verticalArrangement = Arrangement.spacedBy(12.dp),
136                 modifier = Modifier.fillMaxSize(),
137             ) {
138                 items(projects, key = { it.id }) { project ->
139                     ProjectTile(
140                         project = project,
141                         theme = theme,
142                         onOpen = { onOpenProject(project) },
143                         onRename = { renaming = project },
144                         onDuplicate = { onDuplicateProject(project) },
145                         onDelete = { deleting = project },
146                     )
147                 }
148             }
149         }
150     }
151
152     if (showNewDialog) {
153         NewCanvasDialog(
154             theme = theme,
155             defaultWidth = 2800,
156             defaultHeight = 1840,
157             onDismiss = { showNewDialog = false },
158             onCreate = { name, width, height, dpi, colorProfile ->
159                 showNewDialog = false
160                 onCreateProject(name, width, height, dpi, colorProfile)
161             },
162         )
163     }
164
165     renaming?.let { project ->
166         RenameDialog(
167             theme = theme,
168             initial = project.name,
169             onDismiss = { renaming = null },
170             onConfirm = { newName ->
171                 onRenameProject(project, newName)
172                 renaming = null
173             },
174         )
175     }
176
177     deleting?.let { project ->
178         AlertDialog(
179             onDismissRequest = { deleting = null },
180             confirmButton = {
181                 TextButton(
182                     onClick = {

```

```

183                 onDeleteProject(project)
184                 deleting = null
185             },
186         ) {
187             Text("Удалить", color = theme.danger, fontWeight = FontWeight.SemiBold)
188         }
189     },
190     dismissButton = {
191         TextButton(onClick = { deleting = null }) {
192             Text("Отмена", color = theme.textSecondary)
193         }
194     },
195     title = { Text("Удалить холст?", color = theme.textPrimary) },
196     text = { Text(project.name, color = theme.textSecondary) },
197     containerColor = theme.panelBgSolid,
198 )
199 }
200
201 if (showTrash) {
202     TrashDialog(
203         theme = theme,
204         deletedProjects = deletedProjects,
205         onRestore = { deleted ->
206             onRestoreProject(deleted)
207         },
208         onDeleteForever = { deleted ->
209             onDeleteForever(deleted)
210         },
211         onDismiss = { showTrash = false },
212     )
213 }
214 }
215
216 @Composable
217 private fun HomeTopBar(
218     theme: AppTheme,
219     total: Int,
220     onCreate: () -> Unit,
221     onTrash: () -> Unit,
222 ) {
223     Row(
224         modifier = Modifier
225             .fillMaxWidth()
226             .padding(horizontal = 16.dp, vertical = 14.dp),
227         verticalAlignment = Alignment.CenterVertically,
228     ) {
229         Column(modifier = Modifier.weight(1f)) {
230             Text(
231                 "Мои работы",
232                 color = theme.textPrimary,
233                 fontSize = 22.sp,
234                 fontWeight = FontWeight.SemiBold,
235             )
236             Spacer(Modifier.height(3.dp))
237             Text(
238                 "Всего: $total",
239                 color = theme.textSecondary,
240                 fontSize = 13.sp,
241                 fontWeight = FontWeight.Medium,
242             )
243         }
244         TopIconButton(theme = theme, onClick = onCreate) {
245             Icon(Icons.Outlined.Add, null, tint = theme.textPrimary, modifier = Modifier.size(22.dp))
246         }
247         Spacer(Modifier.size(10.dp))
248         TopIconButton(theme = theme, onClick = onTrash) {
249             Icon(Icons.Outlined.Delete, null, tint = theme.textPrimary, modifier = Modifier.size(22.dp))
250         }
251     }
252 }
253
254 @Composable
255 private fun TopIconButton(
256     theme: AppTheme,
257     onClick: () -> Unit,
258     content: @Composable () -> Unit,
259 ) {
260     Box(
261         modifier = Modifier
262             .size(44.dp)
263             .clip(RoundedCornerShape(14.dp))
264             .background(theme.panelBg)
265             .border(1.dp, theme.panelStroke, RoundedCornerShape(14.dp))
266             .clickable(onClick = onClick),
267         contentAlignment = Alignment.Center,
268     ) {
269         content()
270     }
271 }
272
273 @Composable
274 private fun ProjectTile(

```



```

275     project: HomeProject,
276     theme: AppTheme,
277     onOpen: () -> Unit,
278     onRename: () -> Unit,
279     onDuplicate: () -> Unit,
280     onDelete: () -> Unit,
281 ) {
282     var menuExpanded by remember { mutableStateOf(false) }
283
284     Column(
285         modifier = Modifier
286             .fillMaxWidth()
287             .clip(RoundedCornerShape(8.dp))
288             .background(theme.panelBg)
289             .border(1.2.dp, theme.panelStroke, RoundedCornerShape(8.dp))
290             .clickable(onClick = onOpen)
291             .padding(10.dp),
292     ) {
293         ProjectPreview(project = project, theme = theme)
294         Spacer(Modifier.height(10.dp))
295         Row(verticalAlignment = Alignment.CenterVertically) {
296             Column(modifier = Modifier.weight(1f)) {
297                 Text(
298                     project.name,
299                     color = theme.textPrimary,
300                     fontSize = 14.sp,
301                     fontWeight = FontWeight.SemiBold,
302                     maxLines = 1,
303                     overflow = TextOverflow.Ellipsis,
304                 )
305                 Text(
306                     "${project.canvasWidth} x ${project.canvasHeight} px · ${formatDate(project.updatedAtMs)}",
307                     color = theme.textSecondary,
308                     fontSize = 11.sp,
309                     maxLines = 1,
310                     overflow = TextOverflow.Ellipsis,
311                 )
312             }
313             Box {
314                 Box(
315                     modifier = Modifier
316                         .size(34.dp)
317                         .clip(RoundedCornerShape(12.dp))
318                         .clickable { menuExpanded = true },
319                     contentAlignment = Alignment.Center,
320                 ) {
321                     Icon(Icons.Outlined.MoreVert, null, tint = theme.textSecondary, modifier = Modifier.size(20.dp))
322                 }
323                 DropdownMenu(
324                     expanded = menuExpanded,
325                     onDismissRequest = { menuExpanded = false },
326                     modifier = Modifier.background(theme.panelBg)
327                 ) {
328                     DropdownMenuItem(
329                         text = { Text("Переименовать", color = theme.textPrimary) },
330                         leadingIcon = { Icon(Icons.Outlined.Edit, null, tint = theme.textSecondary) },
331                         onClick = {
332                             menuExpanded = false
333                             onRename()
334                         },
335                     )
336                     DropdownMenuItem(
337                         text = { Text("Дублировать", color = theme.textPrimary) },
338                         leadingIcon = { Icon(Icons.Outlined.ContentCopy, null, tint = theme.textSecondary) },
339                         onClick = {
340                             menuExpanded = false
341                             onDuplicate()
342                         },
343                     )
344                     DropdownMenuItem(
345                         text = { Text("Удалить", color = theme.danger) },
346                         leadingIcon = { Icon(Icons.Outlined.Delete, null, tint = theme.danger) },
347                         onClick = {
348                             menuExpanded = false
349                             onDelete()
350                         },
351                     )
352                 }
353             }
354         }
355     }
356 }
357
358 @Composable
359 private fun ProjectPreview(
360     project: HomeProject,
361     theme: AppTheme,
362 ) {
363     // Placeholder for actual preview loading
364     Box(
365         modifier = Modifier
366             .fillMaxWidth()

```

```

367         .aspectRatio(
368             project.canvasWidth.toFloat() /
369             project.canvasHeight.coerceAtLeast(1).toFloat(),
370         )
371         .clip(RoundedCornerShape(6.dp))
372         .background(theme.panelInset)
373         .border(1.dp, theme.panelStroke, RoundedCornerShape(6.dp)),
374         contentAlignment = Alignment.Center,
375     ) {
376         ProjectThumbnailBitmapCache.prime(
377             key = ProjectThumbnailKey(project.id, project.thumbnailVersion),
378             bytes = project.thumbnailBytes,
379         )
380         val preview = rememberProjectThumbnail(
381             projectId = project.id,
382             version = project.thumbnailVersion,
383         )
384         if (preview != null) {
385             Image(bitmap = preview, contentDescription = "Превью ${project.name}", modifier = Modifier.fillMaxSize())
386             return@Box
387         }
388         EmptyProjectPlaceholder(theme)
389     }
390 }
391
392 @Composable
393 private fun EmptyProjectPlaceholder(theme: AppTheme) {
394     Box(
395         modifier = Modifier
396             .fillMaxSize()
397             .clip(RoundedCornerShape(4.dp))
398             .background(Color(0xFFFAFAFA))
399             .border(1.dp, theme.panelStroke, RoundedCornerShape(4.dp)),
400     )
401 }
402
403 @Composable
404 private fun RenameDialog(
405     theme: AppTheme,
406     initial: String,
407     onDismiss: () -> Unit,
408     onConfirm: (String) -> Unit,
409 ) {
410     var name by remember(initial) { mutableStateOf(initial) }
411     AlertDialog(
412         onDismissRequest = onDismiss,
413         confirmButton = {
414             TextButton(
415                 onClick = {
416                     val cleaned = name.trim()
417                     if (cleaned.isNotEmpty()) onConfirm(cleaned)
418                 },
419             ) {
420                 Text("Готово", color = theme.accent, fontWeight = FontWeight.SemiBold)
421             }
422         },
423         dismissButton = {
424             TextButton(onClick = onDismiss) {
425                 Text("Отмена", color = theme.textSecondary)
426             }
427         },
428         title = { Text("Название", color = theme.textPrimary) },
429         text = {
430             OutlinedTextField(
431                 value = name,
432                 onValueChange = { name = it.take(48) },
433                 singleLine = true,
434                 colors = OutlinedTextFieldDefaults.colors(
435                     focusedBorderColor = theme.accent,
436                     unfocusedBorderColor = theme.panelStroke,
437                     focusedTextColor = theme.textPrimary,
438                     unfocusedTextColor = theme.textPrimary
439                 )
440             )
441         },
442         containerColor = theme.panelBgSolid,
443     )
444 }
445
446 @Composable
447 private fun TrashDialog(
448     theme: AppTheme,
449     deletedProjects: List<DeletedHomeProject>,
450     onRestore: (DeletedHomeProject) -> Unit,
451     onDeleteForever: (DeletedHomeProject) -> Unit,
452     onDismiss: () -> Unit,
453 ) {
454     AlertDialog(
455         onDismissRequest = onDismiss,
456         confirmButton = {
457             TextButton(onClick = onDismiss) {
458                 Text("Готово", color = theme.accent, fontWeight = FontWeight.SemiBold)

```

```

459     }
460 },
461 title = { Text("Корзина", color = theme.textPrimary) },
462 text = {
463     if (deletedProjects.isEmpty()) {
464         Text("Удалённые работы хранятся здесь 3 дня.", color = theme.textSecondary, fontSize = 13.sp)
465     } else {
466         Column(
467             modifier = Modifier
468                 .fillMaxWidth()
469                 .height(360.dp)
470                 .verticalScroll(rememberScrollState()),
471             verticalArrangement = Arrangement.spacedBy(10.dp),
472         ) {
473             Text(
474                 "Работы хранятся 3 дня.",
475                 color = theme.textSecondary,
476                 fontSize = 12.sp,
477             )
478             deletedProjects.sortedByDescending { it.deletedAtMs }.forEach { deleted ->
479                 DeletedProjectRow(
480                     deleted = deleted,
481                     theme = theme,
482                     onRestore = { onRestore(deleted) },
483                     onDeleteForever = { onDeleteForever(deleted) },
484                 )
485             }
486         }
487     }
488 },
489 containerColor = theme.panelBgSolid,
490 )
491 }
492
493 @Composable
494 private fun DeletedProjectRow(
495     deleted: DeletedHomeProject,
496     theme: AppTheme,
497     onRestore: () -> Unit,
498     onDeleteForever: () -> Unit,
499 ) {
500     val project = deleted.project
501     Row(
502         modifier = Modifier
503             .fillMaxWidth()
504             .clip(RoundedCornerShape(12.dp))
505             .background(theme.panelBg)
506             .border(1.dp, theme.panelStroke, RoundedCornerShape(12.dp))
507             .padding(10.dp),
508         verticalAlignment = Alignment.CenterVertically,
509     ) {
510         Box(
511             modifier = Modifier
512                 .size(54.dp)
513                 .clip(RoundedCornerShape(6.dp))
514                 .background(theme.panelInset)
515                 .border(1.dp, theme.panelStroke, RoundedCornerShape(6.dp)),
516             contentAlignment = Alignment.Center,
517         ) {
518             Box(
519                 modifier = Modifier
520                     .fillMaxWidth(0.5f)
521                     .aspectRatio(project.canvasWidth.toFloat() / project.canvasHeight.coerceAtLeast(1).toFloat())
522                     .background(Color(0xFFFAFAFA)),
523             )
524         }
525         Column(
526             modifier = Modifier
527                 .weight(1f)
528                 .padding(start = 10.dp),
529         ) {
530             Text(
531                 project.name,
532                 color = theme.textPrimary,
533                 fontSize = 13.sp,
534                 fontWeight = FontWeight.SemiBold,
535                 maxLines = 1,
536                 overflow = TextOverflow.Ellipsis,
537             )
538             Text(
539                 "Осталось: ${trashDaysLeft(deleted.deletedAtMs)} дн.",
540                 color = theme.textSecondary,
541                 fontSize = 11.sp,
542             )
543             Row(horizontalArrangement = Arrangement.spacedBy(8.dp)) {
544                 TextButton(onClick = onRestore) {
545                     Text("Восстановить", color = theme.accent, fontSize = 12.sp)
546                 }
547                 TextButton(onClick = onDeleteForever) {
548                     Text("Удалить", color = theme.textSecondary, fontSize = 12.sp)
549                 }
550             }
551         }
552     }
553 }

```

```

551     }
552 }
553 }
554
555 private fun formatDate(timeMs: Long): String =
556     SimpleDateFormat("d MMM, HH:mm", Locale.forLanguageTag("ru")).format(Date(timeMs))
557
558 private fun trashDaysLeft(deletedAtMs: Long): Int {
559     val retentionMs = 3L * 24L * 60L * 60L * 1000L
560     val remainingMs = (retentionMs - (System.currentTimeMillis() - deletedAtMs)).coerceAtLeast(0L)
561     return ((remainingMs + 24L * 60L * 60L * 1000L - 1L) / (24L * 60L * 60L * 1000L)).toInt().coerceAtLeast(1)
562 }

```

111. app/src/main/java/com/wetinknext/ui/home/NewCanvasDialog.kt

```

1 package com.wetinknext.ui.home
2
3 import androidx.compose.foundation.background
4 import androidx.compose.foundation.border
5 import androidx.compose.foundation.clickable
6 import androidx.compose.foundation.horizontalScroll
7 import androidx.compose.foundation.layout.*
8 import androidx.compose.foundation.rememberScrollState
9 import androidx.compose.foundation.shape.RoundedCornerShape
10 import androidx.compose.foundation.text.KeyboardOptions
11 import androidx.compose.material3.*
12 import androidx.compose.runtime.*
13 import androidx.compose.ui.Alignment
14 import androidx.compose.ui.Modifier
15 import androidx.compose.ui.draw.clip
16 import androidx.compose.ui.graphics.Color
17 import androidx.compose.ui.text.font.FontWeight
18 import androidx.compose.ui.text.input.KeyboardType
19 import androidx.compose.ui.text.style.TextAlign
20 import androidx.compose.ui.unit.dp
21 import androidx.compose.ui.unit.sp
22 import com.wetinknext.ui.theme.AppTheme
23 import com.wetinknext.domain.document.ProjectDocument
24 import kotlin.math.max
25
26 private data class CanvasPreset(
27     val label: String,
28     val width: Int,
29     val height: Int,
30     val description: String,
31 )
32
33 private val QuickPresets = listOf(
34     CanvasPreset("Экран", 2800, 1840, "2800 x 1840 px"),
35     CanvasPreset("Квадрат", 2048, 2048, "2048 x 2048 px"),
36     CanvasPreset("4K", 4096, 2160, "4096 x 2160 px"),
37     CanvasPreset("A4", 2480, 3508, "210 x 297 мм"),
38     CanvasPreset("1080P", 1920, 1080, "1920 x 1080 px"),
39     CanvasPreset("9:16", 1080, 1920, "1080 x 1920 px"),
40 )
41
42 private val DpiOptions = listOf(72, 144, 300, 350, 600, 1200)
43 private val ColorProfiles = listOf(
44     ProjectDocument.SRGB_PROFILE,
45     ProjectDocument.DISPLAY_P3_PROFILE,
46 )
47
48 @Composable
49 fun NewCanvasDialog(
50     theme: AppTheme,
51     defaultWidth: Int,
52     defaultHeight: Int,
53     onDismiss: () -> Unit,
54     onConfirm: (name: String, width: Int, height: Int, dpi: Int, colorProfile: String) -> Unit,
55 ) {
56     val initialIndex = QuickPresets.indexOfFirst {
57         it.width == defaultWidth && it.height == defaultHeight
58     }
59     var selected by remember { mutableIntStateOf(initialIndex) }
60     var customW by remember { mutableStateOf(defaultWidth.toString()) }
61     var customH by remember { mutableStateOf(defaultHeight.toString()) }
62     var name by remember { mutableStateOf("Новый холст") }
63     var dpi by remember { mutableIntStateOf(300) }
64     var colorProfile by remember { mutableStateOf(ProjectDocument.SRGB_PROFILE) }
65     var dpiExpanded by remember { mutableStateOf(false) }
66     var profileExpanded by remember { mutableStateOf(false) }
67     var validationError by remember { mutableStateOf<String?>(null) }
68     val isCustom = selected !in QuickPresets.indices
69
70     AlertDialog(
71         onDismissRequest = onDismiss,
72         title = {
73             Text("Новый холст", color = theme.textPrimary, fontWeight = FontWeight.SemiBold)
74         },
75         text = {
76             Column {
77                 OutlinedTextField(
78                     value = name,
79                     onValueChange = { name = it.take(48) },
80                     label = { Text("Имя") },
81                     singleLine = true,
82                     modifier = Modifier.fillMaxWidth(),
83                     colors = OutlinedTextFieldDefaults.colors(
84                         focusedBorderColor = theme.accent,
85                         unfocusedBorderColor = theme.panelStroke,
86                         focusedLabelColor = theme.accent,
87                         unfocusedLabelColor = theme.textSecondary
88                     )
89                 )
90                 Spacer(Modifier.height(12.dp))

```

```

91 Text("Размеры", color = theme.textSecondary, fontSize = 13.sp)
92 Spacer(Modifier.height(8.dp))
93 Row(
94     horizontalArrangement = Arrangement.spacedBy(8.dp),
95     modifier = Modifier.horizontalScroll(rememberScrollState()),
96 ) {
97     QuickPresets.forEachIndexed { index, preset ->
98         QuickPresetCard(
99             preset = preset,
100             selected = selected == index,
101             theme = theme,
102             onClick = {
103                 selected = index
104                 customW = preset.width.toString()
105                 customH = preset.height.toString()
106             },
107         )
108     }
109 }
110
111 Spacer(Modifier.height(12.dp))
112 TextButton(onClick = { selected = -1 }) {
113     Text(
114         "Свой размер",
115         color = if (isCustom) theme.accent else theme.textSecondary,
116         fontWeight = if (isCustom) FontWeight.SemiBold else FontWeight.Normal,
117         fontSize = 13.sp,
118     )
119 }
120
121 if (isCustom) {
122     Spacer(Modifier.height(4.dp))
123     Row(verticalAlignment = Alignment.CenterVertically) {
124         OutlinedTextField(
125             value = customW,
126             onValueChange = { v -> customW = v.filter { it.isDigit() }.take(5) },
127             label = { Text("Ширина") },
128             singleLine = true,
129             keyboardOptions = KeyboardOptions(keyboardType = KeyboardType.Number),
130             modifier = Modifier.weight(1f),
131             colors = OutlinedTextFieldDefaults.colors(
132                 focusedBorderColor = theme.accent,
133                 unfocusedBorderColor = theme.panelStroke,
134                 focusedLabelColor = theme.accent,
135                 unfocusedLabelColor = theme.textSecondary
136             )
137         )
138         Spacer(Modifier.width(8.dp))
139         Text("x", color = theme.textSecondary)
140         Spacer(Modifier.width(8.dp))
141         OutlinedTextField(
142             value = customH,
143             onValueChange = { v -> customH = v.filter { it.isDigit() }.take(5) },
144             label = { Text("Высота") },
145             singleLine = true,
146             keyboardOptions = KeyboardOptions(keyboardType = KeyboardType.Number),
147             modifier = Modifier.weight(1f),
148             colors = OutlinedTextFieldDefaults.colors(
149                 focusedBorderColor = theme.accent,
150                 unfocusedBorderColor = theme.panelStroke,
151                 focusedLabelColor = theme.accent,
152                 unfocusedLabelColor = theme.textSecondary
153             )
154         )
155     }
156 }
157
158 Spacer(Modifier.height(14.dp))
159 OptionRow(label = "DPI", value = "$dpi dpi", theme = theme, expanded = dpiExpanded, onExpand = { dpiExpanded
= true }) {
160     DpiOptions.forEach { option ->
161         DropdownMenuItem(
162             text = { Text("$option dpi") },
163             onClick = {
164                 dpi = option
165                 dpiExpanded = false
166             },
167         )
168     }
169 }
170 OptionRow(label = "Цветовой профиль", value = colorProfile, theme = theme, expanded = profileExpanded,
onExpand = { profileExpanded = true }) {
171     ColorProfiles.forEach { option ->
172         DropdownMenuItem(
173             text = { Text(option) },
174             onClick = {
175                 colorProfile = option
176                 profileExpanded = false
177             },
178         )
179     }
180 }

```

```

181         validationError?.let { message ->
182             Spacer(Modifier.height(8.dp))
183             Text(message, color = MaterialTheme.colorScheme.error, fontSize = 12.sp)
184         }
185     },
186 },
187     confirmButton = {
188         TextButton(
189             onClick = {
190                 val (w, h) = if (isCustom) {
191                     val cw = customW.toIntOrNull()?.coerceIn(MinDimension, MaxDimension) ?: return@TextButton
192                     val ch = customH.toIntOrNull()?.coerceIn(MinDimension, MaxDimension) ?: return@TextButton
193                     cw to ch
194                 } else {
195                     val preset = QuickPresets[selected]
196                     preset.width to preset.height
197                 }
198                 validationError = runCatching {
199                     ProjectDocument.validateNewCanvas(w, h, dpi, colorProfile)
200                 }.exceptionOrNull()?.message
201                 if (validationError == null) {
202                     onConfirm(name.trim().ifBlank { "Новый холст" }, w, h, dpi, colorProfile)
203                 }
204             },
205         ) {
206             Text("Создать", color = theme.accent, fontWeight = FontWeight.SemiBold)
207         }
208     },
209     dismissButton = {
210         TextButton(onClick = onDismiss) {
211             Text("Отмена", color = theme.textSecondary)
212         }
213     },
214     containerColor = theme.panelBgSolid,
215 )
216 }
217
218 @Composable
219 private fun OptionRow(
220     label: String,
221     value: String,
222     theme: AppTheme,
223     expanded: Boolean,
224     onExpand: () -> Unit,
225     menu: @Composable () -> Unit,
226 ) {
227     Row(verticalAlignment = Alignment.CenterVertically, modifier = Modifier.fillMaxWidth()) {
228         Text(label, color = theme.textPrimary, fontSize = 13.sp)
229         Spacer(Modifier.weight(1f))
230         Box {
231             TextButton(onClick = onExpand) {
232                 Text(value, color = theme.accent, fontWeight = FontWeight.SemiBold)
233             }
234             DropdownMenu(
235                 expanded = expanded,
236                 onDismissRequest = { /* onExpand is handled by parent */ },
237                 modifier = Modifier.background(theme.panelBg)
238             ) {
239                 menu()
240             }
241         }
242     }
243 }
244
245 @Composable
246 private fun QuickPresetCard(
247     preset: CanvasPreset,
248     selected: Boolean,
249     theme: AppTheme,
250     onClick: () -> Unit,
251 ) {
252     Column(
253         horizontalAlignment = Alignment.CenterHorizontally,
254         modifier = Modifier
255             .width(100.dp)
256             .clip(RoundedCornerShape(12.dp))
257             .background(if (selected) theme.accent.copy(alpha = 0.15f) else theme.panelBg)
258             .border(1.5.dp, if (selected) theme.accent else theme.panelStroke, RoundedCornerShape(12.dp))
259             .clickable(onClick = onClick)
260             .padding(vertical = 12.dp, horizontal = 8.dp),
261     ) {
262         PresetSwatch(preset.width, preset.height, selected, theme)
263         Spacer(Modifier.height(8.dp))
264         Text(preset.label, color = theme.textPrimary, fontWeight = FontWeight.Medium, fontSize = 13.sp, textAlign = TextAlign.Center)
265         Text(preset.description, color = theme.textSecondary, fontSize = 10.sp, textAlign = TextAlign.Center, maxLines = 1)
266     }
267 }
268
269 @Composable
270 private fun PresetSwatch(width: Int, height: Int, selected: Boolean, theme: AppTheme) {
271     val scale = 40f / max(width.coerceAtLeast(1), height.coerceAtLeast(1))

```

```

272     val previewW = (width * scale).coerceAtLeast(8f)
273     val previewH = (height * scale).coerceAtLeast(8f)
274     Box(modifier = Modifier.size(48.dp), contentAlignment = Alignment.Center) {
275         Box(
276             modifier = Modifier
277                 .width(previewW.dp)
278                 .height(previewH.dp)
279                 .clip(RoundedCornerShape(4.dp))
280                 .background(if (selected) theme.accent else Color(0xFF5A5A60))
281                 .border(1.dp, if (selected) Color.White else theme.panelStroke, RoundedCornerShape(4.dp)),
282             )
283     }
284 }
285
286 private const val MinDimension = 256
287 private const val MaxDimension = 8192

```


112. app/src/main/java/com/wetinknext/ui/state/EditorActions.kt

```
1 package com.wetinknext.ui.state
2
3 /**
4  * Interface defining all possible user actions from the UI that affect the paint engine state.
5  */
6 interface EditorActions {
7     fun undo()
8     fun redo()
9     fun setBrushSize(px: Float)
10    fun setBrushOpacity(opacity: Float)
11
12    fun addLayer()
13    fun removeLayer(id: Long)
14    fun setActiveLayer(id: Long)
15    fun setLayerVisible(id: Long, visible: Boolean)
16    fun setLayerOpacity(id: Long, opacity: Float)
17 }
```

113. app/src/main/java/com/wetinknext/ui/state/LayerState.kt

```

1  package com.wetinknext.ui.state
2
3  import androidx.compose.runtime.*
4  import com.wetinknext.engine.core.EditorUiState
5
6  class LayerItem(
7      val id: Long,
8      name: String,
9      visible: Boolean,
10     opacity: Float,
11     locked: Boolean,
12     thumbnailPath: String? = null,
13     thumbnailVersion: Long = 0L,
14 ) {
15     var name by mutableStateOf(name)
16     var visible by mutableStateOf(visible)
17     var opacity by mutableFloatStateOf(opacity)
18     var locked by mutableStateOf(locked)
19     var thumbnailPath by mutableStateOf(thumbnailPath)
20     var thumbnailVersion by mutableLongStateOf(thumbnailVersion)
21 }
22
23 class LayerState {
24     val layers = mutableStateListOf<LayerItem>()
25     var activeLayerId by mutableStateOf(-1L)
26
27     fun syncFromEditor(state: EditorUiState) {
28         val ids = state.layers.map { it.id }.toSet()
29         layers.removeAll { it.id !in ids }
30
31         state.layers.forEachIndexed { index, model ->
32             val item = layers.firstOrNull { it.id == model.id }
33
34             if (item == null) {
35                 layers.add(
36                     index.coerceAtMost(layers.size),
37                     LayerItem(
38                         id = model.id,
39                         name = model.name,
40                         visible = model.isVisible,
41                         opacity = model.opacity,
42                         locked = model.isLocked,
43                         thumbnailPath = model.thumbnailPath,
44                         thumbnailVersion = model.thumbnailVersion,
45                     ),
46                 )
47             } else {
48                 item.name = model.name
49                 item.visible = model.isVisible
50                 item.opacity = model.opacity
51                 item.locked = model.isLocked
52                 item.thumbnailPath = model.thumbnailPath
53                 item.thumbnailVersion = model.thumbnailVersion
54
55                 // If the item needs to be moved to match the index in state
56                 val currentIndex = layers.indexOf(item)
57                 if (currentIndex != index && index < layers.size) {
58                     layers.removeAt(currentIndex)
59                     layers.add(index, item)
60                 }
61             }
62         }
63
64         activeLayerId = state.activeLayerId
65     }
66 }

```

114. app/src/main/java/com/wetinknext/ui/theme/AppThemes.kt

```

1  package com.wetinknext.ui.theme
2
3  import androidx.compose.runtime.Immutable
4  import androidx.compose.ui.graphics.Color
5
6  @Immutable
7  data class AppTheme(
8      val id: String,
9      val displayName: String,
10     val isLight: Boolean,
11
12     // Core Layout
13     val appBg: Color,
14     val gridLine: Color,
15     val panelBg: Color,
16     val panelBgSolid: Color,
17     val panelStroke: Color,
18     val panelInset: Color,
19     val panelInsetSoft: Color,
20
21     // Canvas
22     val canvasBackdrop: Color,
23     val canvasGrid: Color,
24
25     // Typography & Icons
26     val textPrimary: Color,
27     val textSecondary: Color,
28     val iconInactive: Color,
29
30     // Accents
31     val accent: Color,
32     val accentSoft: Color,
33     val accentMuted: Color,
34     val danger: Color
35 ) {
36     val panelBgVariant: Color get() = panelInset
37 }
38
39 object AppThemes {
40     val Dark = AppTheme(
41         id = "dark", displayName = "Dark", isLight = false,
42         appBg = Color(0xFF1A0C12), gridLine = Color(0xFF2A1418),
43         panelBg = Color(0xFF2A141C), panelBgSolid = Color(0xFF2D1620),
44         panelStroke = Color(0xFF3D1F2A), panelInset = Color(0xFF1F1015), panelInsetSoft = Color(0xFF2A1820),
45         canvasBackdrop = Color(0xFF1A0C12), canvasGrid = Color(0xFF3A1C24),
46         textPrimary = Color(0xFFFF5E8E), textSecondary = Color(0xFF9A7F8A), iconInactive = Color(0xFFC8B0B8),
47         accent = Color(0xFFFF4D7A), accentSoft = Color(0xFFFF7AA0), accentMuted = Color(0x55FF4D7A), danger = Color(
0xFFFF3B5C)
48     )
49
50     val Light = AppTheme(
51         id = "light", displayName = "Light", isLight = true,
52         appBg = Color(0xFFFFE4E9), gridLine = Color(0xFF5D0D7),
53         panelBg = Color(0xFFFFF1F4), panelBgSolid = Color(0xFFFFFFFF),
54         panelStroke = Color(0xFFFF0C8D0), panelInset = Color(0xFFFFE0E6), panelInsetSoft = Color(0xFFFFD0DA),
55         canvasBackdrop = Color(0xFFFFE4E9), canvasGrid = Color(0xFF5D0D7),
56         textPrimary = Color(0xFF3D1B26), textSecondary = Color(0xFF8A5A6A), iconInactive = Color(0xFFB07A88),
57         accent = Color(0xFFFF4D7A), accentSoft = Color(0xFFFFA0B7), accentMuted = Color(0x33FF4D7A), danger = Color(
0xFFFF3B5C)
58     )
59
60     val Red = AppTheme(
61         id = "red", displayName = "Red", isLight = false,
62         appBg = Color(0xFF1A0606), gridLine = Color(0xFF2A0A0A),
63         panelBg = Color(0xFF2A0C0C), panelBgSolid = Color(0xFF2D0E0E),
64         panelStroke = Color(0xFF3D1414), panelInset = Color(0xFF1F0808), panelInsetSoft = Color(0xFF2A1010),
65         canvasBackdrop = Color(0xFF1A0606), canvasGrid = Color(0xFF3A1414),
66         textPrimary = Color(0xFFFF5E8E), textSecondary = Color(0xFF9A7F7F), iconInactive = Color(0xFFC8B0B0),
67         accent = Color(0xFFFF3D3D), accentSoft = Color(0xFFFF7A7A), accentMuted = Color(0x55FF3D3D), danger = Color(
0xFFFF8888)
68     )
69
70     val Vampire = AppTheme(
71         id = "vampire", displayName = "Vampire", isLight = false,
72         appBg = Color(0xFF1B1C1B), gridLine = Color(0xFF252525),
73         panelBg = Color(0xFF262626), panelBgSolid = Color(0xFF2D2D2D),
74         panelStroke = Color(0xFF4B2529), panelInset = Color(0xFF171717), panelInsetSoft = Color(0xFF2A1B1E),
75         canvasBackdrop = Color(0xFF1B1C1B), canvasGrid = Color(0xFF2B2B2B),
76         textPrimary = Color(0xFFFF2ECC), textSecondary = Color(0xFFCDA2A6), iconInactive = Color(0xFFE15761),
77         accent = Color(0xFFFF3547), accentSoft = Color(0xFFFFA3A8), accentMuted = Color(0xA AFF3547), danger = Color(
0xFFFF4A5F)
78     )
79
80     val Olive = AppTheme(
81         id = "olive", displayName = "Olive", isLight = false,
82         appBg = Color(0xFF171B0D), gridLine = Color(0xFF252A16),
83         panelBg = Color(0xFF202711), panelBgSolid = Color(0xFF263014),
84         panelStroke = Color(0xFF566032), panelInset = Color(0xFF121806), panelInsetSoft = Color(0xFF2B3418),
85         canvasBackdrop = Color(0xFF171B0D), canvasGrid = Color(0xFF2F31C),
86         textPrimary = Color(0xFF1E7D0), textSecondary = Color(0xFFC7A77E), iconInactive = Color(0xFFE3A15E),

```

```

87         accent = Color(0xFFFFF982F), accentSoft = Color(0xFFFFFC46A), accentMuted = Color(0x88FF982F), danger = Color(
0xFFFF624D)
88     )
89
90     val Blue = AppTheme(
91         id = "blue", displayName = "Blue", isLight = false,
92         appBg = Color(0xFF06101A), gridLine = Color(0xFF0A1828),
93         panelBg = Color(0xFF0C1A2A), panelBgSolid = Color(0xFF0E1D2E),
94         panelStroke = Color(0xFF14283D), panelInset = Color(0xFF08141F), panelInsetSoft = Color(0xFF101F2A),
95         canvasBackdrop = Color(0xFF06101A), canvasGrid = Color(0xFF14283A),
96         textPrimary = Color(0xFFE8EEF5), textSecondary = Color(0xFF7F8C9A), iconInactive = Color(0xFFB0BBC8),
97         accent = Color(0xFF4D7AFF), accentSoft = Color(0xFF7AA0FF), accentMuted = Color(0x554D7AFF), danger = Color(
0xFFFF3B5C)
98     )
99
100    val Studio = AppTheme(
101        id = "studio", displayName = "Studio", isLight = true,
102        appBg = Color(0xFFE1E1E1), gridLine = Color(0xFFD1D6DA),
103        panelBg = Color(0xFFFFF0F2F4), panelBgSolid = Color(0xFFFFBFCFD),
104        panelStroke = Color(0xFFD4DAE0), panelInset = Color(0xFFE7EBEF), panelInsetSoft = Color(0xFFDCE8F3),
105        canvasBackdrop = Color(0xFFDADADA), canvasGrid = Color(0xFFCFCFCF),
106        textPrimary = Color(0xFF20252A), textSecondary = Color(0xFF65737F), iconInactive = Color(0xFF5C8DB3),
107        accent = Color(0xFF4A9AD8), accentSoft = Color(0xFF7FBCEB), accentMuted = Color(0x334A9AD8), danger = Color(
0xFFE65C73)
108    )
109
110    val Neon = AppTheme(
111        id = "neon", displayName = "Neon", isLight = false,
112        appBg = Color(0xFF2B123E), gridLine = Color(0xFF32184A),
113        panelBg = Color(0xFF4A2366), panelBgSolid = Color(0xFF522A70),
114        panelStroke = Color(0xFF6C3A8D), panelInset = Color(0xFF321344), panelInsetSoft = Color(0xFF3C1853),
115        canvasBackdrop = Color(0xFF2B123E), canvasGrid = Color(0xFF3C1D55),
116        textPrimary = Color(0xFF3EAFE), textSecondary = Color(0xFFC6A8D8), iconInactive = Color(0xFF2FE0EA),
117        accent = Color(0xFF25DDE8), accentSoft = Color(0xFF73F3FA), accentMuted = Color(0x5525DDE8), danger = Color(
0xFFFF6E9C)
118    )
119
120    val Cyan = AppTheme(
121        id = "cyan", displayName = "Cyan", isLight = false,
122        appBg = Color(0xFF06181A), gridLine = Color(0xFF0A2628),
123        panelBg = Color(0xFF0C282A), panelBgSolid = Color(0xFF0E2C2E),
124        panelStroke = Color(0xFF143C3D), panelInset = Color(0xFF081F20), panelInsetSoft = Color(0xFF102A2A),
125        canvasBackdrop = Color(0xFF06181A), canvasGrid = Color(0xFF143A3A),
126        textPrimary = Color(0xFFE8F5F5), textSecondary = Color(0xFF7F9A9A), iconInactive = Color(0xFFB0C8C8),
127        accent = Color(0xFF26D9D9), accentSoft = Color(0xFF7AE0E0), accentMuted = Color(0x5526D9D9), danger = Color(
0xFFFF3B5C)
128    )
129
130    val Green = AppTheme(
131        id = "green", displayName = "Green", isLight = false,
132        appBg = Color(0xFF071A0C), gridLine = Color(0xFF0A2814),
133        panelBg = Color(0xFF0C2A14), panelBgSolid = Color(0xFF0E2D16),
134        panelStroke = Color(0xFF143D1F), panelInset = Color(0xFF081F0C), panelInsetSoft = Color(0xFF102A14),
135        canvasBackdrop = Color(0xFF071A0C), canvasGrid = Color(0xFF143A1F),
136        textPrimary = Color(0xFFE8F5EC), textSecondary = Color(0xFF7F9A88), iconInactive = Color(0xFFB0C8B8),
137        accent = Color(0xFF3DDB6E), accentSoft = Color(0xFF7AE0A0), accentMuted = Color(0x553DDB6E), danger = Color(
0xFFFF3B5C)
138    )
139
140    val Yellow = AppTheme(
141        id = "yellow", displayName = "Yellow", isLight = true,
142        appBg = Color(0xFFFFF8E0), gridLine = Color(0xFFFF5E5A0),
143        panelBg = Color(0xFFFFF4D0), panelBgSolid = Color(0xFFFFF0CF0),
144        panelStroke = Color(0xFFE6CC60), panelInset = Color(0xFFFFF0B8), panelInsetSoft = Color(0xFFFFF890),
145        canvasBackdrop = Color(0xFFFFF8E0), canvasGrid = Color(0xFFFF0DA80),
146        textPrimary = Color(0xFF3D2E08), textSecondary = Color(0xFF8A7A40), iconInactive = Color(0xFFB09860),
147        accent = Color(0xFFFF5B800), accentSoft = Color(0xFFFFFD050), accentMuted = Color(0x55F5B800), danger = Color(
0xFFFF3B5C)
148    )
149
150    val Orange = AppTheme(
151        id = "orange", displayName = "Orange", isLight = true,
152        appBg = Color(0xFFFFF8D5), gridLine = Color(0xFFFF5C898),
153        panelBg = Color(0xFFFFF0C5), panelBgSolid = Color(0xFFFFF1E5),
154        panelStroke = Color(0xFFE69C58), panelInset = Color(0xFFFFD8B5), panelInsetSoft = Color(0xFFFFF890),
155        canvasBackdrop = Color(0xFFFFF8D5), canvasGrid = Color(0xFFFF0BC80),
156        textPrimary = Color(0xFF3D1E08), textSecondary = Color(0xFF8A5A30), iconInactive = Color(0xFFB07A50),
157        accent = Color(0xFFFFF8800), accentSoft = Color(0xFFFFFD050), accentMuted = Color(0x55FF8800), danger = Color(
0xFFFF3B5C)
158    )
159
160    val Gray = AppTheme(
161        id = "gray", displayName = "Gray", isLight = false,
162        appBg = Color(0xFF1A1A1A), gridLine = Color(0xFF2A2A2A),
163        panelBg = Color(0xFF2A2A2A), panelBgSolid = Color(0xFF303030),
164        panelStroke = Color(0xFF404040), panelInset = Color(0xFF1F1F1F), panelInsetSoft = Color(0xFF2B2B2B),
165        canvasBackdrop = Color(0xFF1A1A1A), canvasGrid = Color(0xFF3A3A3A),
166        textPrimary = Color(0xFFFFF0F0F0), textSecondary = Color(0xFF909090), iconInactive = Color(0xFFB8B8B8),
167        accent = Color(0xFFB0B0B0), accentSoft = Color(0xFFD0D0D0), accentMuted = Color(0x55B0B0B0), danger = Color(
0xFFFF3B5C)
168    )
169

```

```

170     val White = AppTheme(
171         id = "white", displayName = "White", isLight = true,
172         appBg = Color(0xFFFFFFFF), gridLine = Color(0xFFE8E8E8),
173         panelBg = Color(0xFFF5F5F5), panelBgSolid = Color(0xFFFFFFFF),
174         panelStroke = Color(0xFFD8D8D8), panelInset = Color(0xFFEEEEEE), panelInsetSoft = Color(0xFFE0E0E0),
175         canvasBackdrop = Color(0xFFFFFFFF), canvasGrid = Color(0xFFE0E0E0),
176         textPrimary = Color(0xFF202020), textSecondary = Color(0xFF707070), iconInactive = Color(0xFF989898),
177         accent = Color(0xFF606060), accentSoft = Color(0xFF888888), accentMuted = Color(0x55606060), danger = Color(
0xFFFF3B5C)
178     )
179
180     val all = listOf(
181         Dark, Light, Red, Vampire, Olive, Blue, Studio, Neon, Cyan, Green, Yellow, Orange, Gray, White
182     )
183
184     val default = Gray
185 }
186
187 enum class UIFont { Classic, Italic }

```

115. app/src/main/java/com/wetinknext/ui/theme/CustomThemeEditor.kt

```

1 package com.wetinknext.ui.theme
2
3 import android.graphics.Color as AndroidColor
4 import androidx.compose.foundation.background
5 import androidx.compose.foundation.border
6 import androidx.compose.foundation.clickable
7 import androidx.compose.foundation.layout.*
8 import androidx.compose.foundation.shape.CircleShape
9 import androidx.compose.foundation.shape.RoundedCornerShape
10 import androidx.compose.foundation.text.BasicTextField
11 import androidx.compose.material3.Slider
12 import androidx.compose.material3.SliderDefaults
13 import androidx.compose.material3.Text
14 import androidx.compose.runtime.*
15 import androidx.compose.ui.Alignment
16 import androidx.compose.ui.Modifier
17 import androidx.compose.ui.draw.clip
18 import androidx.compose.ui.graphics.Color
19 import androidx.compose.ui.graphics.SolidColor
20 import androidx.compose.ui.text.TextStyle
21 import androidx.compose.ui.text.font.FontWeight
22 import androidx.compose.ui.unit.dp
23 import androidx.compose.ui.unit.sp
24 import com.wetinknext.engine.core.CanvasBackdropMode
25 import kotlin.random.Random
26
27 private enum class ThemeColorSlot(val label: String) {
28     AppBackground("Рабочая область"), CanvasBackground("За холстом"), Grid("Сетка"),
29     Panel("Панели"), Accent("Акцент"), Text("Текст"), Danger("Удаление")
30 }
31
32 @Composable
33 fun CustomThemeEditor(
34     colors: CustomThemeColors,
35     theme: AppTheme,
36     backdropMode: CanvasBackdropMode,
37     onChange: (CustomThemeColors) -> Unit,
38     onBackdropModeChange: (CanvasBackdropMode) -> Unit,
39     onDismiss: () -> Unit,
40 ) {
41     var slot by remember { mutableStateOf(ThemeColorSlot.Accent) }
42     val current = colors.color(slot)
43     Column(Modifier.fillMaxWidth(), verticalArrangement = Arrangement.spacedBy(10.dp)) {
44         Row(verticalAlignment = Alignment.CenterVertically) {
45             Text("Своя тема", color = theme.textPrimary, style = androidx.compose.material3.MaterialTheme.typography.
titleLarge)
46             Spacer(Modifier.weight(1f))
47             Text("Случайная", color = theme.textSecondary, fontSize = 12.sp,
48                 modifier = Modifier.clickable { onChange(randomThemeColors()) }.padding(6.dp))
49             Text("Готово", color = theme.accent, fontWeight = FontWeight.SemiBold,
50                 modifier = Modifier.clickable(onClick = onDismiss).padding(6.dp))
51         }
52         ThemeLivePreview(colors)
53         Text("Фон за холстом", color = theme.textSecondary, fontSize = 12.sp)
54         Row(Modifier.fillMaxWidth(), horizontalArrangement = Arrangement.spacedBy(6.dp)) {
55             listOf(
56                 CanvasBackdropMode.GRID to "Сетка",
57                 CanvasBackdropMode.CHECKERBOARD to "Клетки",
58                 CanvasBackdropMode.SOLID to "Сплошной",
59             ).forEach { (mode, label) ->
60                 val selected = mode == backdropMode
61                 Box(
62                     Modifier.weight(1f).clip(RoundedCornerShape(8.dp))
63                     .background(if (selected) theme.accent.copy(alpha = .16f) else theme.panelInset)
64                     .border(1.dp, if (selected) theme.accent else Color.Transparent, RoundedCornerShape(8.dp))
65                     .clickable { onBackdropModeChange(mode) }.padding(vertical = 7.dp),
66                     contentAlignment = Alignment.Center,
67                 ) { Text(label, color = theme.textPrimary, fontSize = 10.sp, maxLines = 1) }
68             }
69         }
70         ThemeColorSlot.entries.chunked(2).forEach { row ->
71             Row(Modifier.fillMaxWidth(), horizontalArrangement = Arrangement.spacedBy(8.dp)) {
72                 row.forEach { item ->
73                     val active = item == slot
74                     Row(
75                         Modifier.weight(1f).clip(RoundedCornerShape(10.dp))
76                         .background(if (active) theme.accent.copy(alpha = .14f) else theme.panelInset)
77                         .border(1.dp, if (active) theme.accent else Color.Transparent, RoundedCornerShape(10.dp))
78                         .clickable { slot = item }.padding(8.dp),
79                         verticalAlignment = Alignment.CenterVertically,
80                     ) {
81                         Box(Modifier.size(20.dp).clip(CircleShape).background(Color(colors.color(item))).border(1.dp, theme.
panelStroke, CircleShape))
82                         Spacer(Modifier.width(7.dp))
83                         Text(item.label, color = theme.textPrimary, fontSize = 11.sp, maxLines = 1)
84                     }
85                 }
86                 if (row.size == 1) Spacer(Modifier.weight(1f))
87             }
88         }

```

```

89         ColorControls(slot.label, current, theme) { onChange(colors.withColor(slot, it)) }
90         Row(Modifier.fillMaxWidth(), horizontalArrangement = Arrangement.spacedBy(8.dp)) {
91             Text("Сбросить", color = theme.textSecondary, modifier = Modifier.weight(1f).clickable { onChange(
CustomThemeColors()) }.padding(8.dp))
92             Text("Применяется сразу", color = theme.textSecondary, fontSize = 11.sp, modifier = Modifier.padding(8.dp))
93         }
94     }
95 }
96
97 @Composable private fun ColorControls(label: String, color: Int, theme: AppTheme, update: (Int) -> Unit) {
98     var hex by remember(color) { mutableStateOf("%06X".format(color and 0xFFFFFF)) }
99     val r = color ushr 16 and 0xFF; val g = color ushr 8 and 0xFF; val b = color and 0xFF
100     val hsv = FloatArray(3).also { AndroidColor.RGBToHSV(r, g, b, it) }
101     Column(Modifier.clip(RoundedCornerShape(12.dp)).background(theme.panelInset).padding(10.dp), verticalArrangement =
Arrangement.spacedBy(4.dp)) {
102         Text("Цвет: $label", color = theme.textPrimary, fontWeight = FontWeight.Medium, fontSize = 13.sp)
103         BasicTextField(hex, { raw ->
104             val clean = raw.removePrefix("#").filter { it.isDigit() || it.lowercaseChar() in 'a'..'f' }.take(6).uppercase()
105             hex = clean; clean.toIntOrNull(16)?.takeIf { clean.length == 6 }?.let { update(0xFF000000.toInt() or it) }
106         }, textStyle = TextStyle(color = theme.textPrimary, fontSize = 14.sp), cursorBrush = SolidColor(theme.accent),
107         decorationBox = { inner -> Row(Modifier.fillMaxWidth().clip(RoundedCornerShape(7.dp)).background(theme.panelBg).
padding(8.dp)) { Text("#", color = theme.textSecondary); inner() } })
108         Channel("R", r, Color.Red, theme) { update(argb(it, g, b)) }
109         Channel("G", g, Color(0xFF38C878), theme) { update(argb(r, it, b)) }
110         Channel("B", b, Color(0xFF568DFF), theme) { update(argb(r, g, it)) }
111         PercentageChannel("H", hsv[1], theme.accent, theme) { saturation ->
112             hsv[1] = saturation
113             update(AndroidColor.HSVToColor(hsv))
114         }
115     }
116 }
117
118 @Composable private fun Channel(name: String, value: Int, color: Color, theme: AppTheme, update: (Int) -> Unit) =
119     Row(verticalAlignment = Alignment.CenterVertically) {
120         Text(name, color = theme.textSecondary, modifier = Modifier.width(18.dp), fontSize = 11.sp)
121         Slider(value.toFloat(), { update(it.toInt()) }, valueRange = 0f..255f, modifier = Modifier.weight(1f), colors =
SliderDefaults.colors(thumbColor = color, activeTrackColor = color, inactiveTrackColor = theme.panelBg))
122         Text(value.toString(), color = theme.textSecondary, modifier = Modifier.width(28.dp), fontSize = 11.sp)
123     }
124
125 @Composable private fun PercentageChannel(name: String, value: Float, color: Color, theme: AppTheme, update: (Float) -> Unit)
=
126     Row(verticalAlignment = Alignment.CenterVertically) {
127         Text(name, color = theme.textSecondary, modifier = Modifier.width(18.dp), fontSize = 11.sp)
128         Slider(value, update, valueRange = 0f..1f, modifier = Modifier.weight(1f), colors = SliderDefaults.colors(thumbColor
= color, activeTrackColor = color, inactiveTrackColor = theme.panelBg))
129         Text("${(value * 100).toInt()}%", color = theme.textSecondary, modifier = Modifier.width(28.dp), fontSize = 11.sp)
130     }
131
132 @Composable private fun ThemeLivePreview(colors: CustomThemeColors) =
133     Row(Modifier.fillMaxWidth().height(56.dp).clip(RoundedCornerShape(12.dp)).background(Color(colors.appBackground)).padding(
9.dp), verticalAlignment = Alignment.CenterVertically) {
134         Box(Modifier.size(38.dp).clip(RoundedCornerShape(7.dp)).background(Color(colors.panel)))
135         Spacer(Modifier.width(9.dp)); Column { Box(Modifier.width(112.dp).height(7.dp).clip(CircleShape).background(Color(
colors.text))); Spacer(Modifier.height(6.dp)); Box(Modifier.width(72.dp).height(5.dp).clip(CircleShape).background(Color(colors.
text).copy(alpha = .5f))) }
136         Spacer(Modifier.weight(1f)); Box(Modifier.size(27.dp).clip(CircleShape).background(Color(colors.accent)))
137     }
138
139 private fun CustomThemeColors.color(slot: ThemeColorSlot) = when (slot) { ThemeColorSlot.AppBackground -> appBackground;
ThemeColorSlot.CanvasBackground -> canvasBackground; ThemeColorSlot.Grid -> grid; ThemeColorSlot.Panel -> panel; ThemeColorSlot.
Accent -> accent; ThemeColorSlot.Text -> text; ThemeColorSlot.Danger -> danger }
140 private fun CustomThemeColors.withColor(slot: ThemeColorSlot, value: Int) = when (slot) { ThemeColorSlot.AppBackground ->
copy(appBackground = value); ThemeColorSlot.CanvasBackground -> copy(canvasBackground = value); ThemeColorSlot.Grid -> copy(grid =
value); ThemeColorSlot.Panel -> copy(panel = value); ThemeColorSlot.Accent -> copy(accent = value); ThemeColorSlot.Text -> copy(
text = value); ThemeColorSlot.Danger -> copy(danger = value) }
141 private fun argb(r: Int, g: Int, b: Int) = (0xFF shl 24) or (r shl 16) or (g shl 8) or b
142
143 /** Creates a coherent palette rather than seven unrelated random colours. */
144 private fun randomThemeColors(): CustomThemeColors {
145     val hue = Random.nextInt(360).toFloat()
146     val dark = Random.nextBoolean()
147     fun hsv(h: Float, s: Float, v: Float) = AndroidColor.HSVToColor(floatArrayOf((h + 360f) % 360f, s, v))
148     val baseValue = if (dark) .12f else .94f
149     val panelValue = if (dark) .18f else .99f
150     val textValue = if (dark) .94f else .16f
151     return CustomThemeColors(
152         appBackground = hsv(hue, .22f, baseValue),
153         canvasBackground = hsv(hue, .16f, if (dark) .09f else .89f),
154         grid = hsv(hue, .28f, if (dark) .27f else .78f),
155         panel = hsv(hue, .24f, panelValue),
156         accent = hsv(hue + 28f, .72f, .92f),
157         text = hsv(hue, .12f, textValue),
158         danger = hsv(2f, .72f, .92f),
159     )
160 }

```

116. app/src/main/java/com/wetinknext/ui/theme/Theme.kt

```

1  package com.wetinknext.ui.theme
2
3  import androidx.compose.material3.MaterialTheme
4  import androidx.compose.material3.Typography
5  import androidx.compose.material3.darkColorScheme
6  import androidx.compose.material3.lightColorScheme
7  import androidx.compose.runtime.Composable
8  import androidx.compose.runtime.CompositionLocalProvider
9  import androidx.compose.ui.graphics.Color
10 import androidx.compose.ui.text.TextStyle
11 import androidx.compose.ui.text.font.Font
12 import androidx.compose.ui.text.font.FontFamily
13 import androidx.compose.ui.text.font.FontWeight
14 import androidx.compose.ui.unit.sp
15 import com.wetinknext.R
16
17 private val ClassicFontFamily = FontFamily(
18     Font(R.font.lora_variable, FontWeight.Normal),
19     Font(R.font.lora_variable, FontWeight.Bold),
20 )
21
22 private val HandwrittenFontFamily = FontFamily(
23     Font(R.font.caveat_variable, FontWeight.Normal),
24     Font(R.font.caveat_variable, FontWeight.Bold),
25 )
26
27 @Composable
28 fun WetInkTheme(
29     theme: AppTheme,
30     fontMode: UiFont,
31     content: @Composable () -> Unit
32 ) {
33     val fontFamily = if (fontMode == UiFont.Italic) HandwrittenFontFamily else ClassicFontFamily
34
35     /*
36      * One compact editorial scale for every editor panel. Individual controls
37      * may still use a title style, but labels and segmented toolbars now share
38      * the same readable base instead of each panel inventing its own scale.
39      */
40     val typography = Typography(
41         bodyLarge = TextStyle(fontFamily = fontFamily, fontSize = 14.sp, lineHeight = 18.sp),
42         bodyMedium = TextStyle(fontFamily = fontFamily, fontSize = 13.sp, lineHeight = 17.sp),
43         bodySmall = TextStyle(fontFamily = fontFamily, fontSize = 12.sp, lineHeight = 16.sp),
44         titleLarge = TextStyle(fontFamily = fontFamily, fontSize = 16.sp, lineHeight = 20.sp, fontWeight = FontWeight.
SemiBold),
45         titleMedium = TextStyle(fontFamily = fontFamily, fontSize = 15.sp, lineHeight = 19.sp, fontWeight = FontWeight.
Medium),
46         titleSmall = TextStyle(fontFamily = fontFamily, fontSize = 14.sp, lineHeight = 18.sp, fontWeight = FontWeight.Medium),
47         labelLarge = TextStyle(fontFamily = fontFamily, fontSize = 13.sp, lineHeight = 16.sp, fontWeight = FontWeight.Medium),
48         labelMedium = TextStyle(fontFamily = fontFamily, fontSize = 12.sp, lineHeight = 15.sp, fontWeight = FontWeight.
Medium),
49         labelSmall = TextStyle(fontFamily = fontFamily, fontSize = 11.sp, lineHeight = 14.sp, fontWeight = FontWeight.Medium),
50     )
51
52     val scheme = if (!theme.isLight) {
53         darkColorScheme(
54             primary = theme.accent,
55             onPrimary = theme.textPrimary,
56             background = theme.appBg, // Цвет стола
57             onBackground = theme.textPrimary,
58             surface = theme.panelBg, // Цвет панелей
59             onSurface = theme.textPrimary,
60             surfaceVariant = theme.panelBgVariant,
61             onSurfaceVariant = theme.textSecondary,
62         )
63     } else {
64         lightColorScheme(
65             primary = theme.accent,
66             onPrimary = Color.White,
67             background = theme.appBg,
68             onBackground = theme.textPrimary,
69             surface = theme.panelBg,
70             onSurface = theme.textPrimary,
71             surfaceVariant = theme.panelBgVariant,
72             onSurfaceVariant = theme.textSecondary,
73         )
74     }
75
76     CompositionLocalProvider(LocalAppTheme provides theme) {
77         MaterialTheme(
78             colorScheme = scheme,
79             typography = typography,
80             content = content,
81         )
82     }
83 }

```


117. app/src/main/java/com/wetinknext/ui/theme/ThemeController.kt

```

1 package com.wetinknext.ui.theme
2
3 import android.content.Context
4 import androidx.compose.runtime.*
5 import androidx.compose.runtime.saveable.Saver
6 import androidx.compose.runtime.saveable.rememberSaveable
7 import androidx.compose.ui.graphics.Color
8 import androidx.compose.ui.platform.LocalContext
9 import com.wetinknext.engine.core.CanvasBackdropMode
10 import kotlin.math.pow
11
12 val LocalAppTheme = compositionLocalOf { AppThemes.Gray }
13
14 data class CustomThemeColors(
15     val appBackground: Int = 0xFF101826.toInt(),
16     val canvasBackground: Int = 0xFF101826.toInt(),
17     val grid: Int = 0xFF38424C.toInt(),
18     val panel: Int = 0xFF172033.toInt(),
19     val accent: Int = 0xFF58A6FF.toInt(),
20     val text: Int = 0xFFFF4F7FB.toInt(),
21     val danger: Int = 0xFFFF4A5F.toInt(),
22 )
23
24 class ThemeController(
25     initialThemeId: String = "gray",
26     initialFontMode: String = "Classic",
27     initialCustomColors: CustomThemeColors = CustomThemeColors(),
28     initialBackdropMode: String = CanvasBackdropMode.GRID.name,
29 ) {
30     var current by mutableStateOf(resolveTheme(initialThemeId, initialCustomColors))
31     private set
32     var font by mutableStateOf(if (initialFontMode == "Italic") UiFont.Italic else UiFont.Classic)
33     private set
34     var customColors by mutableStateOf(initialCustomColors)
35     private set
36     var backdropMode by mutableStateOf(runCatching { CanvasBackdropMode.valueOf(initialBackdropMode) }.getOrElse(
CanvasBackdropMode.GRID))
37     private set
38     val customTheme: AppTheme
39     get() = createCustomTheme(customColors)
40
41     fun select(theme: AppTheme) {
42         current = if (theme.id == "custom") createCustomTheme(customColors) else theme
43     }
44
45     fun selectCustom() {
46         current = createCustomTheme(customColors)
47     }
48
49     fun selectFont(f: UiFont) { font = f }
50     fun selectBackdropMode(mode: CanvasBackdropMode) { backdropMode = mode }
51
52     fun updateCustomColors(newColors: CustomThemeColors) {
53         customColors = newColors
54         if (current.id == "custom") current = createCustomTheme(newColors)
55     }
56
57     private fun resolveTheme(id: String, colors: CustomThemeColors): AppTheme {
58         if (id == "custom") return createCustomTheme(colors)
59         return AppThemes.all.find { it.id == id } ?: AppThemes.Gray
60     }
61
62     private fun createCustomTheme(colors: CustomThemeColors): AppTheme {
63         val appBg = Color(colors.appBackground)
64         val panel = Color(colors.panel)
65         val accent = Color(colors.accent)
66         val text = Color(colors.text)
67         val grid = Color(colors.grid)
68         val isDark = luminanceOf(appBg) < 0.5f
69
70         return AppTheme(
71             id = "custom", displayName = "Своя", isLight = !isDark,
72             appBg = appBg, gridLine = grid,
73             panelBg = panel, panelBgSolid = panel.mix(if (isDark) Color.White else Color.Black, 0.08f),
74             panelStroke = panel.mix(accent, 0.3f),
75             panelInset = panel.mix(if (isDark) Color.Black else Color.White, 0.2f),
76             panelInsetSoft = panel.mix(accent, 0.1f),
77             canvasBackdrop = Color(colors.canvasBackground), canvasGrid = grid,
78             textPrimary = text, textSecondary = text.copy(alpha = 0.6f),
79             iconInactive = text.copy(alpha = 0.4f),
80             accent = accent, accentSoft = accent.copy(alpha = 0.7f),
81             accentMuted = accent.copy(alpha = 0.3f),
82             danger = Color(colors.danger)
83         )
84     }
85
86     private fun Color.mix(target: Color, amount: Float): Color {
87         return Color(
88             red = red * (1f - amount) + target.red * amount,
89             green = green * (1f - amount) + target.green * amount,

```

```

90         blue = blue * (1f - amount) + target.blue * amount,
91         alpha = alpha
92     )
93 }
94
95 private fun luminanceOf(color: Color): Float {
96     fun channel(value: Float): Float =
97         if (value <= 0.03928f) value / 12.92f else ((value + 0.055f) / 1.055f).pow(2.4f)
98     return 0.2126f * channel(color.red) + 0.7152f * channel(color.green) + 0.0722f * channel(color.blue)
99 }
100
101 companion object {
102     val Saver: Saver<ThemeController, *> = Saver(
103         save = { listOf(it.current.id, it.font.name, it.backdropMode.name, it.customColors.appBackground, it.customColors.
104 canvasBackground, it.customColors.grid, it.customColors.panel, it.customColors.accent, it.customColors.text, it.customColors.
105 danger) },
106         restore = { list ->
107             val l = list as List<*>
108             ThemeController(
109                 initialThemeId = l[0] as String,
110                 initialFontMode = l[1] as String,
111                 initialBackdropMode = if (l.size >= 10) l[2] as String else CanvasBackdropMode.GRID.name,
112                 initialCustomColors = if (l.size >= 10) CustomThemeColors(l[3] as Int, l[4] as Int, l[5] as Int, l[6] as
113 Int, l[7] as Int, l[8] as Int, l[9] as Int)
114                 else if (l.size >= 9) CustomThemeColors(l[2] as Int, l[3] as Int, l[4] as Int, l[5] as Int, l[6] as Int,
115 l[7] as Int, l[8] as Int)
116                 else CustomThemeColors(l[2] as Int, l[2] as Int, l[3] as Int, l[4] as Int, l[5] as Int, l[6] as Int)
117             )
118         }
119     )
120 }
121
122 @Composable
123 fun rememberThemeController(): ThemeController {
124     val context = LocalContext.current
125     val prefs = remember { context.getSharedPreferences("wetinknext_theme_prefs", Context.MODE_PRIVATE) }
126
127     val controller = rememberSaveable(saver = ThemeController.Saver) {
128         val themeId = prefs.getString("theme_id", "gray") ?: "gray"
129         val fontMode = prefs.getString("font_mode", "Classic") ?: "Classic"
130         val backdropMode = prefs.getString("backdrop_mode", CanvasBackdropMode.GRID.name) ?: CanvasBackdropMode.GRID.name
131         val customColors = CustomThemeColors(
132             appBackground = prefs.getInt("custom_bg", 0xFF101826.toInt()),
133             canvasBackground = prefs.getInt("custom_canvas_bg", prefs.getInt("custom_bg", 0xFF101826.toInt())),
134             grid = prefs.getInt("custom_grid", 0xFF38424C.toInt()),
135             panel = prefs.getInt("custom_panel", 0xFF172033.toInt()),
136             accent = prefs.getInt("custom_accent", 0xFF58A6FF.toInt()),
137             text = prefs.getInt("custom_text", 0xFFFF4F7FB.toInt()),
138             danger = prefs.getInt("custom_danger", 0xFFFF4A5F.toInt()),
139         )
140         ThemeController(themeId, fontMode, customColors, backdropMode)
141     }
142
143     LaunchedEffect(controller.current.id, controller.font, controller.customColors, controller.backdropMode) {
144         prefs.edit()
145         .putString("theme_id", controller.current.id)
146         .putString("font_mode", controller.font.name)
147         .putString("backdrop_mode", controller.backdropMode.name)
148         .putInt("custom_bg", controller.customColors.appBackground)
149         .putInt("custom_canvas_bg", controller.customColors.canvasBackground)
150         .putInt("custom_grid", controller.customColors.grid)
151         .putInt("custom_panel", controller.customColors.panel)
152         .putInt("custom_accent", controller.customColors.accent)
153         .putInt("custom_text", controller.customColors.text)
154         .putInt("custom_danger", controller.customColors.danger)
155         .apply()
156     }
157
158     return controller
159 }

```

118. app/src/main/java/com/wetinknext/ui/theme/WetInkNextPalette.kt

```
1 package com.wetinknext.ui.theme
2
3 import androidx.compose.ui.graphics.Color
4
5 data class WetInkNextPalette(
6     val appBg: Color,
7     val panelBg: Color,
8     val panelStroke: Color,
9     val textPrimary: Color,
10    val textSecondary: Color,
11    val accent: Color,
12 ) {
13     companion object {
14         val default = WetInkNextPalette(
15             appBg = Color(0xFF17181C),
16             panelBg = Color(0xFF25272D),
17             panelStroke = Color(0xFF3A3D46),
18             textPrimary = Color(0xFFF3F4F6),
19             textSecondary = Color(0xFFA4A8B3),
20             accent = Color(0xFF4D7AFF),
21         )
22     }
23 }
```

119. app/src/main/java/com/wetinknext/ui/thumbnail/LayerThumbnail.kt

```

1  package com.wetinknext.ui.thumbnail
2
3  import android.graphics.BitmapFactory
4  import android.util.LruCache
5  import androidx.compose.foundation.Image
6  import androidx.compose.foundation.layout.Box
7  import androidx.compose.foundation.layout.fillMaxSize
8  import androidx.compose.runtime.Composable
9  import androidx.compose.runtime.LaunchedEffect
10 import androidx.compose.runtime.getValue
11 import androidx.compose.runtime.mutableStateOf
12 import androidx.compose.runtime.remember
13 import androidx.compose.runtime.setValue
14 import androidx.compose.ui.Modifier
15 import androidx.compose.ui.graphics.ImageBitmap
16 import androidx.compose.ui.graphics.asImageBitmap
17 import androidx.compose.ui.layout.ContentScale
18 import androidx.compose.foundation.layout.aspectRatio
19 import java.io.File
20 import kotlinx.coroutines.Dispatchers
21 import kotlinx.coroutines.withContext
22
23 private data class LayerThumbnailKey(
24     val layerId: Long,
25     val version: Long,
26 )
27
28 /** Process-local cache; the layer version prevents recycled rows showing stale previews. */
29 private object LayerThumbnailBitmapCache {
30     private val bitmaps = LruCache<LayerThumbnailKey, ImageBitmap>(48)
31
32     fun get(key: LayerThumbnailKey): ImageBitmap? = bitmaps.get(key)
33
34     fun put(key: LayerThumbnailKey, bitmap: ImageBitmap) {
35         bitmaps.put(key, bitmap)
36     }
37 }
38
39 /**
40  * A persisted WebP preview with alpha and the document's native aspect ratio.
41  * The last decoded bitmap remains visible while a newer version is read from disk.
42  */
43 @Composable
44 fun LayerThumbnail(
45     layerId: Long,
46     path: String?,
47     thumbnailVersion: Long,
48     modifier: Modifier = Modifier,
49 ) {
50     val key = remember(layerId, thumbnailVersion) {
51         LayerThumbnailKey(layerId, thumbnailVersion)
52     }
53     var displayedBitmap by remember(layerId) {
54         mutableStateOf(LayerThumbnailBitmapCache.get(key))
55     }
56
57     LaunchedEffect(key, path) {
58         val bitmap = LayerThumbnailBitmapCache.get(key) ?: withContext(Dispatchers.IO) {
59             path
60                 ?.let(::File)
61                 ?.takeIf(File::isFile)
62                 ?.let { BitmapFactory.decodeFile(it.absolutePath) }
63                 ?.asImageBitmap()
64                 ?.also { LayerThumbnailBitmapCache.put(key, it) }
65             }
66         if (bitmap != null) {
67             displayedBitmap = bitmap
68         }
69     }
70
71     val previewModifier = displayedBitmap?.let { bitmap ->
72         modifier.aspectRatio(
73             ratio = bitmap.width.toFloat() / bitmap.height.coerceAtLeast(1).toFloat(),
74             matchHeightConstraintsFirst = true,
75         )
76     } ?: modifier
77
78     // No panel-coloured backing: alpha in the layer WebP stays alpha in UI.
79     // The dimensions come from the image itself, so a portrait document does
80     // not acquire horizontal bars just because its row is wider than it is.
81     Box(modifier = previewModifier) {
82         displayedBitmap?.let { bitmap ->
83             Image(
84                 bitmap = bitmap,
85                 contentDescription = "Layer preview",
86                 modifier = Modifier.fillMaxSize(),
87                 contentScale = ContentScale.Fit,
88             )
89         }
90     }

```


120. app/src/main/res/drawable/ic_eraser.xml

```
1  <?xml version="1.0" encoding="utf-8"?>
2  <vector xmlns:android="http://schemas.android.com/apk/res/android"
3      android:width="24dp"
4      android:height="24dp"
5      android:viewportWidth="24"
6      android:viewportHeight="24">
7      <path
8          android:fillColor="#FFFFFF"
9          android:pathData="M14.59,3.41a2,2 0,0 1,2.83 0l3.17,3.17a2,2 0,0 1,0 2.83l11.41,18.59a2,2 0,0 1,-2.83 0l4.41,14.41a2,
2 0,0 1,0 -2.83l10.18,-8.17zM3,20h18v2H3z" />
10     <path
11         android:fillColor="#FFFFFF"
12         android:fillAlpha="0.55"
13         android:pathData="M7.05,11l4.95,4.95l3.18,-3.18l-4.95,-4.95z" />
14 </vector>
```

121. app/src/main/res/drawable/ic_flip_horizontal.xml

```
1  <?xml version="1.0" encoding="utf-8"?>
2  <vector xmlns:android="http://schemas.android.com/apk/res/android"
3      android:width="24dp"
4      android:height="24dp"
5      android:viewportWidth="24"
6      android:viewportHeight="24">
7      <!-- Central Axis (Centered at 12) -->
8      <path
9          android:fillColor="#FFFFFF"
10         android:pathData="M11.25,4h1.5v16h-1.5V4z"/>
11
12     <!-- Left solid bracket (Symmetrical) -->
13     <path
14         android:fillColor="#FFFFFF"
15         android:pathData="M9,6.5H5v11h4V16H6.5V8H9V6.5z"/>
16
17     <!-- Right dashed bracket (Mirror of left, perfectly aligned) -->
18     <!-- Top dash -->
19     <path android:fillColor="#FFFFFF" android:pathData="M15,6.5h2.5V8H15V6.5z"/>
20     <path android:fillColor="#FFFFFF" android:pathData="M18.5,6.5h0.5V8h-0.5V6.5z"/>
21     <!-- Side dashes -->
22     <path android:fillColor="#FFFFFF" android:pathData="M17.5,9.5h1.5v2h-1.5V9.5z"/>
23     <path android:fillColor="#FFFFFF" android:pathData="M17.5,12.5h1.5v2h-1.5V12.5z"/>
24     <!-- Bottom dash -->
25     <path android:fillColor="#FFFFFF" android:pathData="M15,16h2.5v1.5H15V16z"/>
26     <path android:fillColor="#FFFFFF" android:pathData="M18.5,16h0.5v1.5h-0.5V16z"/>
27 </vector>
```

122. app/src/main/res/drawable/ic_launcher_background.xml

```
1 <?xml version="1.0" encoding="utf-8"?>
2 <vector xmlns:android="http://schemas.android.com/apk/res/android"
3     android:width="108dp"
4     android:height="108dp"
5     android:viewportWidth="108"
6     android:viewportHeight="108">
7     <path
8         android:fillColor="#FF211019"
9         android:pathData="M0,0h108v108h-108z" />
10 </vector>
```


123. app/src/main/res/drawable/ic_launcher_foreground.xml

```
1  <?xml version="1.0" encoding="utf-8"?>
2  <vector xmlns:android="http://schemas.android.com/apk/res/android"
3      xmlns:aapt="http://schemas.android.com/aapt"
4      android:width="108dp"
5      android:height="108dp"
6      android:viewportWidth="108"
7      android:viewportHeight="108">
8      <group
9          android:pivotX="54"
10         android:pivotY="54"
11         android:scaleX="0.6"
12         android:scaleY="0.6">
13         <path
14             android:pathData="M14,88h80"
15             android:strokeWidth="5"
16             android:strokeLineCap="round">
17             <aapt:attr name="android:strokeColor">
18                 <gradient
19                     android:startX="78"
20                     android:startY="20"
21                     android:endX="30"
22                     android:endY="80"
23                     android:type="linear">
24                     <item android:offset="0" android:color="#FFFFB1C5" />
25                     <item android:offset="1" android:color="#FFF3D70" />
26                 </gradient>
27             </aapt:attr>
28         </path>
29         <path
30             android:pathData="M66,16c3.3,-3.3 8.7,-3.3 12,0l4,4c3.3,3.3 3.3,8.7 0,12l34,80l-16,4l4,-16l66,16z"
31             android:fillType="nonZero">
32             <aapt:attr name="android:fillColor">
33                 <gradient
34                     android:startX="78"
35                     android:startY="20"
36                     android:endX="30"
37                     android:endY="80"
38                     android:type="linear">
39                     <item android:offset="0" android:color="#FFFFB1C5" />
40                     <item android:offset="1" android:color="#FFF3D70" />
41                 </gradient>
42             </aapt:attr>
43         </path>
44     </group>
45 </vector>
```

124. app/src/main/res/mipmap-anydpi-v26/ic_launcher.xml

```
1 <?xml version="1.0" encoding="utf-8"?>
2 <adaptive-icon xmlns:android="http://schemas.android.com/apk/res/android">
3     <background android:drawable="@drawable/ic_launcher_background" />
4     <foreground android:drawable="@drawable/ic_launcher_foreground" />
5 </adaptive-icon>
```

125. app/src/main/res/mipmap-anydpi-v26/ic_launcher_round.xml

```
1 <?xml version="1.0" encoding="utf-8"?>
2 <adaptive-icon xmlns:android="http://schemas.android.com/apk/res/android">
3     <background android:drawable="@drawable/ic_launcher_background" />
4     <foreground android:drawable="@drawable/ic_launcher_foreground" />
5 </adaptive-icon>
```

126. app/src/main/res/mipmap-anydpi/ic_launcher.xml

```
1 <?xml version="1.0" encoding="utf-8"?>
2 <layer-list xmlns:android="http://schemas.android.com/apk/res/android">
3     <item android:drawable="@drawable/ic_launcher_background" />
4     <item android:drawable="@drawable/ic_launcher_foreground" />
5 </layer-list>
```

127. app/src/main/res/mipmap-anydpi/ic_launcher_round.xml

```
1 <?xml version="1.0" encoding="utf-8"?>
2 <layer-list xmlns:android="http://schemas.android.com/apk/res/android">
3     <item android:drawable="@drawable/ic_launcher_background" />
4     <item android:drawable="@drawable/ic_launcher_foreground" />
5 </layer-list>
```

128. app/src/main/res/values/strings.xml

```
1 <resources>
2     <string name="app_name">WetInk Next</string>
3 </resources>
```

129. app/src/main/res/values/themes.xml

```
1 <resources>
2     <style name="Theme.WetInkNext" parent="android:style/Theme.Material.NoActionBar" />
3 </resources>
```

130. app/src/test/java/com/wetinknext/data/project/AutosaveCoordinatorTest.kt

```
1 package com.wetinknext.data.project
2
3 import kotlinx.coroutines.CoroutineScope
4 import kotlinx.coroutines.Dispatchers
5 import kotlinx.coroutines.SupervisorJob
6 import kotlinx.coroutines.cancel
7 import org.junit.Assert.assertEquals
8 import org.junit.Assert.assertTrue
9 import org.junit.Test
10 import java.util.concurrent.CopyOnWriteArrayList
11 import java.util.concurrent.CountDownLatch
12 import java.util.concurrent.TimeUnit
13
14 class AutosaveCoordinatorTest {
15     @Test
16     fun laterCompletedEditReplacesEarlierPendingSave() {
17         val scope = CoroutineScope(SupervisorJob() + Dispatchers.Default)
18         val coordinator = AutosaveCoordinator(scope, debounceMillis = 30L)
19         val saved = CopyOnWriteArrayList<String>()
20         val latch = CountDownLatch(1)
21
22         coordinator.schedule { saved += "first" }
23         coordinator.schedule {
24             saved += "second"
25             latch.countDown()
26         }
27
28         assertTrue(latch.await(2, TimeUnit.SECONDS))
29         assertEquals(listOf("second"), saved)
30         scope.cancel()
31     }
32 }
```


131. app/src/test/java/com/wetinknext/data/project/FileProjectRepositoryTest.kt

```

1 package com.wetinknext.data.project
2
3 import com.wetinknext.domain.document.ProjectAssets
4 import com.wetinknext.domain.document.ProjectDocument
5 import com.wetinknext.domain.document.WetInkProjectContainer
6 import org.junit.Assert.assertArrayEquals
7 import org.junit.Assert.assertEquals
8 import org.junit.Assert.assertFalse
9 import org.junit.Assert.assertTrue
10 import org.junit.Test
11 import java.io.File
12 import java.nio.file.Files
13 import java.util.concurrent.atomic.AtomicLong
14 import kotlin.coroutines.Continuation
15 import kotlin.coroutines.EmptyCoroutineContext
16 import kotlin.coroutines.startCoroutine
17
18 class FileProjectRepositoryTest {
19     @Test
20     fun projectLifecycleKeepsGalleryMetadataCompact() {
21         val root = Files.createTempDirectory("wetink-repository").toFile()
22         val time = AtomicLong(100L)
23         val repository = FileProjectRepository(
24             projectsDirectory = root,
25             container = WetInkProjectContainer(clockMillis = { time.incrementAndGet() }),
26         )
27
28         val first = runSuspend {
29             repository.create(CreateProjectRequest(name = "First", width = 800, height = 600))
30         }
31         val second = runSuspend {
32             repository.create(CreateProjectRequest(name = "Second", width = 1200, height = 900))
33         }
34
35         val listed = runSuspend { repository.list() }
36         assertEquals(listOf(second.id, first.id), listed.map(ProjectSummary::id))
37         assertEquals("Second", listed.first().name)
38         assertEquals(1200, listed.first().width)
39         assertEquals(900, listed.first().height)
40
41         val opened = runSuspend { repository.open(first.id) }
42         assertEquals("First", opened.name)
43         assertEquals(800, opened.width)
44
45         runSuspend { repository.rename(first.id, "Renamed") }
46         assertEquals("Renamed", runSuspend { repository.open(first.id) }.name)
47
48         runSuspend { repository.moveToTrash(first.id) }
49         assertFalse(runSuspend { repository.list() }.any { it.id == first.id })
50         assertEquals(first.id, runSuspend { repository.listTrash() }.single().project.id)
51         runSuspend { repository.restore(first.id) }
52         assertTrue(runSuspend { repository.list() }.any { it.id == first.id })
53         runSuspend { repository.moveToTrash(first.id) }
54         runSuspend { repository.deleteForever(first.id) }
55         assertFalse(File(root, ".trash/${first.id}.wetink").exists())
56     }
57
58     @Test
59     fun metadataSavePreservesExistingTilePayloads() {
60         val root = Files.createTempDirectory("wetink-repository-save").toFile()
61         val container = WetInkProjectContainer(clockMillis = { 500L })
62         val repository = FileProjectRepository(root, container)
63         val document = ProjectDocument.newUntitled(id = "project-1", nowMillis = 100L)
64         val file = File(root, "project-1.wetink")
65         container.save(
66             file,
67             document,
68             ProjectAssets(mapOf(1L to byteArrayOf(1, 2), 2L to byteArrayOf(3, 4))),
69         )
70
71         runSuspend { repository.save(document.copy(name = "Saved name")) }
72
73         // Saving a legacy ZIP is the migration point: the same project is now
74         // represented by projects/project-1/{manifest,document,layers}.
75         assertTrue(File(root, "project-1").isDirectory)
76         val loaded = runSuspend { repository.openForEditor("project-1") }
77         assertEquals("Saved name", loaded.document.name)
78         assertArrayEquals(byteArrayOf(1, 2), loaded.assets.layerTiles.getValue(1L))
79         assertArrayEquals(byteArrayOf(3, 4), loaded.assets.layerTiles.getValue(2L))
80     }
81
82     @Test
83     fun recoverySnapshotPreservesNewestTilePayloadUntilPrimarySave() {
84         val root = Files.createTempDirectory("wetink-recovery").toFile()
85         val repository = FileProjectRepository(root, WetInkProjectContainer(clockMillis = { 700L }))
86         val summary = runSuspend { repository.create(CreateProjectRequest(name = "Recovery")) }
87         val document = runSuspend { repository.open(summary.id) }
88
89         runSuspend { repository.saveRecovery(document, mapOf(2L to byteArrayOf(9, 8, 7))) }
90         val recovered = runSuspend { repository.openRecovery(summary.id) }

```

```

91         assertEquals(byteArrayOf(9, 8, 7), checkNotNull(recovered).assets.layerTiles.getValue(2L))
92     }
93     runSuspend { repository.save(recovered.document, recovered.assets.layerTiles) }
94     runSuspend { repository.clearRecovery(summary.id) }
95     assertTrue(runSuspend { repository.openRecovery(summary.id) } == null)
96     assertEquals(byteArrayOf(9, 8, 7), runSuspend { repository.openForEditor(summary.id) }.assets.layerTiles.
getValue(2L))
97 }
98
99 @Test
100 fun thumbnailSaveIsAtomicAndGalleryReadsThePublishedPreview() {
101     val root = Files.createTempDirectory("wetink-thumbnail").toFile()
102     val repository = FileProjectRepository(root, WetInkProjectContainer(clockMillis = { 800L }))
103     val summary = runSuspend { repository.create(CreateProjectRequest(name = "Preview")) }
104     val document = runSuspend { repository.open(summary.id) }
105     val webp = byteArrayOf(0x52, 0x49, 0x46, 0x46, 0x57, 0x45, 0x42, 0x50)
106
107     runSuspend { repository.save(document, emptyMap(), webp) }
108
109     val galleryItem = runSuspend { repository.list() }.single()
110     assertEquals(webp, galleryItem.thumbnailBytes)
111     assertEquals(webp, runSuspend { repository.openForEditor(summary.id) }.assets.thumbnailWebp)
112 }
113
114 @Test
115 fun duplicateCreatesIndependentDirectoryProject() {
116     val root = Files.createTempDirectory("wetink-duplicate").toFile()
117     val repository = FileProjectRepository(root, WetInkProjectContainer(clockMillis = { 900L }))
118     val original = runSuspend { repository.create(CreateProjectRequest(name = "Original")) }
119
120     val duplicate = runSuspend { repository.duplicate(original.id) }
121
122     assertFalse(original.id == duplicate.id)
123     assertEquals("Original copy", duplicate.name)
124     assertTrue(File(root, duplicate.id).isDirectory)
125     val originalTiles = runSuspend { repository.openForEditor(original.id) }.assets.layerTiles
126     val duplicateTiles = runSuspend { repository.openForEditor(duplicate.id) }.assets.layerTiles
127     assertEquals(originalTiles.keys, duplicateTiles.keys)
128     originalTiles.forEach { (layerId, bytes) ->
129         assertEquals(bytes, duplicateTiles.getValue(layerId))
130     }
131 }
132
133 private fun <T> runSuspend(block: suspend () -> T): T {
134     var result: Result<T>? = null
135     block.startCoroutine(object : Continuation<T> {
136         override val context = EmptyCoroutineContext
137
138         override fun resumeWith(value: Result<T>) {
139             result = value
140         }
141     })
142     return checkNotNull(result).getOrNull()
143 }
144 }

```

132. app/src/test/java/com/wetinknext/domain/document/ProjectDocumentTest.kt

```

1 package com.wetinknext.domain.document
2
3 import kotlinx.serialization.encodeToString
4 import kotlinx.serialization.json.Json
5 import org.junit.Assert.assertEquals
6 import org.junit.Assert.assertFalse
7 import org.junit.Assert.assertTrue
8 import org.junit.Assert.fail
9 import org.junit.Test
10
11 class ProjectDocumentTest {
12     private val json = Json {
13         encodeDefaults = true
14         ignoreUnknownKeys = true
15     }
16
17     @Test
18     fun untitledProjectRoundTripsWithoutEmbeddingLayerPixels() {
19         val document = ProjectDocument.newUntitled(
20             id = "project-1",
21             name = "Sketch",
22             width = 2048,
23             height = 1536,
24             dpi = 300,
25             nowMillis = 1234L,
26         )
27
28         val encoded = json.encodeToString(document)
29         val decoded = json.decodeFromString<ProjectDocument>(encoded)
30
31         assertEquals(document, decoded)
32         assertTrue(encoded.contains("\pixelFile\":"layers/1.tiles\"))
33         assertFalse(encoded.contains("rawBytes"))
34         assertFalse(encoded.contains("textureId"))
35     }
36
37     @Test(expected = IllegalArgumentException::class)
38     fun projectRejectsAnUnknownActiveLayer() {
39         val document = ProjectDocument.newUntitled(id = "project-1", nowMillis = 1234L)
40         document.copy(activeLayerId = 999L)
41     }
42
43     @Test
44     fun newCanvasRejectsAnUnsafeInitialGpuAllocation() {
45         try {
46             ProjectDocument.newUntitled(width = 8192, height = 8192)
47             fail("Expected memory-budget validation to reject an 8192px canvas")
48         } catch (_: IllegalArgumentException) {
49             // Expected: two initial layers and the stroke target would exceed the budget.
50         }
51     }
52 }

```

133. app/src/test/java/com/wetinknext/domain/document/WetInkProjectContainerTest.kt

```

1  package com.wetinknext.domain.document
2
3  import org.junit.Assert.assertArrayEquals
4  import org.junit.Assert.assertEquals
5  import org.junit.Assert.assertFalse
6  import org.junit.Assert.fail
7  import org.junit.Test
8  import java.io.File
9  import java.nio.file.Files
10 import java.util.zip.ZipFile
11
12 class WetInkProjectContainerTest {
13     @Test
14     fun savePublishesOneContainerWithSeparateLayerPayloads() {
15         val root = Files.createTempDirectory("wetink-project-test").toFile()
16         val projectFile = File(root, "sketch.wetink")
17         val document = ProjectDocument.newUntitled(
18             id = "project-1",
19             nowMillis = 100L,
20         )
21         val assets = ProjectAssets(
22             layerTiles = mapOf(
23                 1L to byteArrayOf(1, 2, 3),
24                 2L to byteArrayOf(4, 5, 6),
25             ),
26             thumbnailWebp = byteArrayOf(7, 8),
27             layerPreviewsWebp = mapOf(2L to byteArrayOf(9)),
28         )
29         val container = WetInkProjectContainer(clockMillis = { 200L })
30
31         val saved = container.save(projectFile, document, assets)
32         val loaded = container.load(projectFile)
33
34         assertEquals(100L, document.updatedAt)
35         assertEquals(200L, saved.document.updatedAt)
36         assertEquals(saved.document, loaded.document)
37         assertArrayEquals(byteArrayOf(1, 2, 3), loaded.assets.layerTiles.getValue(1L))
38         assertArrayEquals(byteArrayOf(4, 5, 6), loaded.assets.layerTiles.getValue(2L))
39         assertArrayEquals(byteArrayOf(7, 8), loaded.assets.thumbnailWebp)
40         assertArrayEquals(byteArrayOf(9), loaded.assets.layerPreviewsWebp.getValue(2L))
41         assertFalse(File(root, "sketch.wetink.tmp").exists())
42
43         ZipFile(projectFile).use { zip ->
44             assertEquals(true, zip.getEntry("manifest.json") != null)
45             assertEquals(true, zip.getEntry("document.json") != null)
46             assertEquals(true, zip.getEntry("layers/1.tiles") != null)
47             assertEquals(true, zip.getEntry("layers/2.tiles") != null)
48             assertEquals(true, zip.getEntry("thumbnail.webp") != null)
49             assertEquals(true, zip.getEntry("previews/2.webp") != null)
50         }
51     }
52
53     @Test
54     fun invalidSecondSaveLeavesPublishedProjectUntouched() {
55         val root = Files.createTempDirectory("wetink-project-atomic").toFile()
56         val projectFile = File(root, "sketch.wetink")
57         val document = ProjectDocument.newUntitled(
58             id = "project-1",
59             nowMillis = 100L,
60         )
61         val container = WetInkProjectContainer(clockMillis = { 200L })
62         container.save(
63             projectFile,
64             document,
65             ProjectAssets(mapOf(1L to byteArrayOf(1), 2L to byteArrayOf(2))),
66         )
67
68         try {
69             container.save(
70                 projectFile,
71                 document,
72                 ProjectAssets(mapOf(1L to byteArrayOf(99))),
73             )
74             fail("Missing layer payload must reject the save")
75         } catch (_: IllegalArgumentException) {
76             // Expected: validation happens before replacing the published file.
77         }
78
79         val loaded = container.load(projectFile)
80         assertArrayEquals(byteArrayOf(1), loaded.assets.layerTiles.getValue(1L))
81         assertArrayEquals(byteArrayOf(2), loaded.assets.layerTiles.getValue(2L))
82     }
83 }

```

134. app/src/test/java/com/wetinknext/engine/brush/BrushDynamicsTest.kt

```

1 package com.wetinknext.engine.brush
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Test
5 import kotlin.math.PI
6
7 class BrushDynamicsTest {
8     @Test
9     fun resolve_separatesLocalCoverageFromGlobalOpacity() {
10         val settings = BrushSettings(
11             baseRadiusPx = 10f,
12             opacity = 0.2f,
13             pressureGamma = 2f,
14             minSizeRatio = 0.1f,
15             tiltToSize = 0.5f,
16             tiltToOpacity = 1f,
17         )
18         val result = ResolvedDab()
19
20         BrushDynamics.resolve(
21             settings = settings,
22             pressure = 0.5f,
23             tiltX = 1f,
24             tiltY = 0f,
25             velocity = 0f,
26             orientationRad = 0f,
27             out = result,
28         )
29
30         //  $p = 0.5^2 = 0.25$ ; pressure size = .325; tilt size = 1.5.
31         assertEquals(4.875f, result.radius, 0.0001f)
32         // Tilt attenuates, rather than amplifies, local coverage.
33         assertEquals(0.1375f, result.coverage, 0.0001f)
34         assertEquals(result.coverage, result.opacity, 0.0001f)
35     }
36
37     @Test
38     fun resolve_appliesVelocityAndOrientation() {
39         val result = ResolvedDab()
40         BrushDynamics.resolve(
41             settings = BrushSettings(
42                 baseRadiusPx = 10f,
43                 pressureToSize = false,
44                 pressureToOpacity = false,
45                 velocityToSize = .5f,
46                 velocityToOpacity = .5f,
47                 tiltToRotation = .5f,
48             ),
49             pressure = 1f,
50             tiltX = 0f,
51             tiltY = 1f,
52             velocity = 1_250f,
53             orientationRad = .2f,
54             out = result,
55         )
56
57         assertEquals(12.5f, result.radius, .0001f)
58         assertEquals(.75f, result.coverage, .0001f)
59         assertEquals(.2f + PI.toFloat() * .25f, result.rotation, .0001f)
60     }
61 }

```

135. app/src/test/java/com/wetinknext/engine/brush/BrushLibraryTest.kt

```
1 package com.wetinknext.engine.brush
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Test
5
6 class BrushLibraryTest {
7     @Test
8     fun penPresetDisablesBothTapers() {
9         assertEquals(0f, BrushLibrary.pen.settings.ribbon.taperStartPx, 0f)
10        assertEquals(0f, BrushLibrary.pen.settings.ribbon.taperEndPx, 0f)
11    }
12 }
```

136. app/src/test/java/com/wetinknext/engine/brush/BrushSerializationTest.kt

```
1 package com.wetinknext.engine.brush
2
3 import kotlinx.serialization.encodeToString
4 import org.junit.Assert.assertEquals
5 import org.junit.Test
6
7 class BrushSerializationTest {
8
9     @Test
10     fun settingsRoundTripKeepsRenderFields() {
11         val json = BrushRepository.defaultJson
12         val original = BrushSettings(
13             name = "Pencil 6B",
14             grainAssetPath = "asset:brush/pencil_6b.png",
15             grainScale = 5.5f,
16             textureDepth = .65f,
17             tiltToSize = .55f,
18             blendPolicy = BlendPolicy.NORMAL_BUILDUP,
19         )
20
21         val encoded = json.encodeToString(original)
22         val restored = json.decodeFromString<BrushSettings>(encoded)
23
24         assertEquals(original, restored)
25     }
26
27     @Test
28     fun presetRoundTrip() {
29         val repo = BrushRepository()
30         val original = BrushPreset(
31             id = "test-preset",
32             settings = BrushSettings(name = "Test Brush")
33         )
34
35         val encoded = repo.encode(original)
36         val restored = repo.decode(encoded)
37
38         assertEquals(original, restored)
39     }
40 }
```

137. app/src/test/java/com/wetinknext/engine/brush/BrushSettingsTest.kt

```
1 package com.wetinknext.engine.brush
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Test
5
6 class BrushSettingsTest {
7     @Test
8     fun resolved_clampsBrushValues() {
9         val result = BrushSettings(
10             baseRadiusPx = -10f,
11             opacity = 3f,
12             flow = -1f,
13             spacing = 100f,
14             pressureGamma = 0f,
15             minSizeRatio = 4f,
16         ).resolved()
17
18         assertEquals(0.25f, result.baseRadiusPx, 0.001f)
19         assertEquals(1f, result.opacity, 0.001f)
20         assertEquals(0f, result.flow, 0.001f)
21         assertEquals(4f, result.spacing, 0.001f)
22         assertEquals(0.05f, result.pressureGamma, 0.001f)
23         assertEquals(1f, result.minSizeRatio, 0.001f)
24     }
25 }
```


138. app/src/test/java/com/wetinknext/engine/brush/CapsuleEmitterTest.kt

```

1  package com.wetinknext.engine.brush
2
3  import com.wetinknext.engine.input.InputAction
4  import com.wetinknext.engine.input.InputBatch
5  import com.wetinknext.engine.input.PointerTool
6  import org.junit.Assert.assertTrue
7  import org.junit.Test
8
9  class CapsuleEmitterTest {
10
11     @Test
12     fun finishFlushesTheLastInterpolatedSection() {
13         val settings = BrushSettings(
14             renderMode = BrushRenderMode.RIBBON,
15             baseRadiusPx = 10f,
16             smoothing = 0.5f,
17             streamline = 0f,
18         )
19         val emitter = CapsuleEmitter(settings)
20         // We need a dummy renderer to receive segments
21         // Since we can't easily mock GL context here, we just use a small maxSegments
22         val renderer = CapsuleStrokeRenderer(maxSegments = 128)
23
24         emitter.begin(batch(InputAction.DOWN, 0f, 0f, 0L), renderer)
25         emitter.append(batch(InputAction.MOVE, 100f, 0f, 16_000_000L), renderer)
26         emitter.append(batch(InputAction.MOVE, 200f, 30f, 32_000_000L), renderer)
27
28         val segmentsBeforeFinish = renderer.segmentCount
29         emitter.finish(renderer, cancel = false)
30         val segmentsAfterFinish = renderer.segmentCount
31
32         assertTrue("Should have some segments after append", segmentsBeforeFinish > 0)
33         assertTrue("Finish should have flushed more segments", segmentsAfterFinish > segmentsBeforeFinish)
34         assertTrue(emitter.hasStroke)
35     }
36
37     private fun batch(action: InputAction, x: Float, y: Float, t: Long) = InputBatch(8).apply {
38         begin(action)
39         addSample(x, y, .5f, 0f, 0f, 0f, t, 0, PointerTool.STYLUS, false)
40     }
41 }

```

139. app/src/test/java/com/wetinknext/engine/brush/CapsuleStrokeRendererTest.kt

```

1 package com.wetinknext.engine.brush
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Assert.assertFalse
5 import org.junit.Assert.assertTrue
6 import org.junit.Test
7 import com.wetinknext.engine.gl.ShaderLib
8
9 class CapsuleStrokeRendererTest {
10
11     @Test
12     fun capsuleShaderAppliesFlowInsideTheStrokeTarget() {
13         assertTrue(ShaderLib.capsuleFragment.contains("uniform float uFlow"))
14         assertTrue(ShaderLib.capsuleFragment.contains("grainFactor * uFlow"))
15     }
16
17     @Test
18     fun initiallyEmpty() {
19         val renderer = CapsuleStrokeRenderer(maxSegments = 100)
20         assertTrue(renderer.isEmpty)
21         assertEquals(0, renderer.segmentCount)
22     }
23
24     @Test
25     fun addsSegmentsWithinCapacity() {
26         val renderer = CapsuleStrokeRenderer(maxSegments = 10)
27         renderer.beginStroke()
28
29         for (i in 0 until 10) {
30             val added = renderer.addSegment(0f, 0f, 5f, 1f, 10f, 10f, 5f, 1f)
31             assertTrue("Segment $i should be added", added)
32         }
33
34         assertEquals(10, renderer.segmentCount)
35         assertFalse(renderer.isEmpty)
36
37         val addedOverflow = renderer.addSegment(0f, 0f, 5f, 1f, 10f, 10f, 5f, 1f)
38         assertFalse("Overflow segment should not be added", addedOverflow)
39         assertEquals(1, renderer.overflowCount)
40     }
41
42     @Test
43     fun clearResetsStateButNotOverflow() {
44         val renderer = CapsuleStrokeRenderer(maxSegments = 10)
45         renderer.beginStroke()
46         renderer.addSegment(0f, 0f, 5f, 1f, 10f, 10f, 5f, 1f)
47
48         // Overflow it
49         for (i in 0 until 10) renderer.addSegment(0f, 0f, 1f, 1f, 1f, 1f, 1f, 1f)
50         assertEquals(1, renderer.overflowCount)
51
52         renderer.clearStrokeData()
53         assertTrue(renderer.isEmpty)
54         assertEquals(0, renderer.segmentCount)
55         assertEquals(1, renderer.overflowCount)
56     }
57 }

```

140. app/src/test/java/com/wetinknext/engine/brush/ColorSpacesTest.kt

```
1 package com.wetinknext.engine.brush
2 import org.junit.Assert.*
3 import org.junit.Test
4 class ColorSpacesTest { @Test fun blackAndWhiteAreStable(){val b=FloatArray(3);val w=FloatArray(3);ColorSpaces.srgb8ToLinear(
0xFF000000L,b);ColorSpaces.srgb8ToLinear(0xFFFFFFFFL,w);assertEquals(0f,b[0],.0001f);assertEquals(1f,w[0],.0001f)} @Test fun
roundTrip(){assertEquals(.25f,ColorSpaces.srgbToLinear(ColorSpaces.linearToSrgb(.25f)),.0001f)} }
```

141. app/src/test/java/com/wetinknext/engine/brush/DabBufferTest.kt

```
1 package com.wetinknext.engine.brush
2
3 import com.wetinknext.engine.core.DirtyRect
4 import org.junit.Assert.*
5 import org.junit.Test
6
7 class DabBufferTest {
8     @Test fun overflowIsCounted(){val b=DabBuffer(2);assertTrue(b.add(0f,0f,1f,0f,1f,1f));assertTrue(b.add(1f,1f,1f,0f,1f,
9 1f));assertFalse(b.add(2f,2f,1f,0f,1f,1f));assertEquals(1L,b.overflowCount)}
10    @Test fun clearResets(){val b=DabBuffer(1);b.add(0f,0f,1f,0f,1f,1f);b.clear();assertEquals(0,b.count)}
11    @Test fun dirtyRectIncludesTextureMargin(){
12        val buffer = DabBuffer(1)
13        buffer.add(10f, 20f, 5f, 0f, 1f, 1f)
14        val rect = DirtyRect()
15        buffer.includeDirtyRect(rect, extraMargin = 4f)
16        assertEquals(1f, rect.left, 0.001f)
17        assertEquals(19f, rect.right, 0.001f)
18        assertEquals(11f, rect.top, 0.001f)
19        assertEquals(29f, rect.bottom, 0.001f)
20    }
```

142. app/src/test/java/com/wetinknext/engine/brush/OneEuroFilterTest.kt

```
1 package com.wetinknext.engine.brush
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Assert.assertFalse
5 import org.junit.Test
6
7 class OneEuroFilterTest {
8     @Test fun firstSamplePassesThrough() { val f=OneEuroFilter();val out=FloatArray(2);f.filter(0,10f,20f,out);assertEquals(
10f,out[0],.0001f);assertEquals(20f,out[1],.0001f) }
9     @Test fun samplesRemainFinite() { val f=OneEuroFilter();val out=FloatArray(2);f.filter(0,0f,0f,out);f.filter(8_000_000,
10f,5f,out);assertFalse(out[0].isNaN());assertFalse(out[1].isInfinite()) }
10 }
```

143. app/src/test/java/com/wetinknext/engine/brush/PressureFilterTest.kt

```
1 package com.wetinknext.engine.brush
2
3 import org.junit.Assert.assertTrue
4 import org.junit.Test
5
6 class PressureFilterTest {
7     @Test fun singleZeroPressureGlitchDoesNotCollapseWidth() {
8         val filter = PressureFilter()
9         filter.filter(0L, .6f)
10        val filtered = filter.filter(16_000_000L, 0f)
11        assertTrue("zero glitch must be ignored while stroke is active", filtered > .55f)
12    }
13
14    @Test fun realPressureChangeIsSmoothed() {
15        val filter = PressureFilter()
16        filter.filter(0L, .8f)
17        val filtered = filter.filter(16_000_000L, .2f)
18        assertTrue(filtered in .2f.. .8f)
19    }
20 }
```

144. app/src/test/java/com/wetinknext/engine/brush/StabilizerTest.kt

```
1 package com.wetinknext.engine.brush
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Assert.assertTrue
5 import org.junit.Test
6
7 class StabilizerTest {
8     @Test fun strengthZeroPassesRawThrough(){val s=Stabilizer();s.process(0,100f,200f);assertEquals(100f,s.x,.0001f);
assertEquals(200f,s.y,.0001f)}
9     @Test fun velocityIsPositiveAfterMovement(){val s=Stabilizer();s.process(0,0f,0f);s.process(1_000_000_000,100f,0f);
assertTrue(s.velocity>0f)}
10 }
```

145. app/src/test/java/com/wetinknext/engine/brush/StampEmitterTest.kt

```

1  package com.wetinknext.engine.brush
2
3  import com.wetinknext.engine.input.*
4  import org.junit.Assert.assertEquals
5  import org.junit.Test
6
7  class StampEmitterTest {
8      @Test fun movingStrokeHasNoExtraDownDab(){val e=StampEmitter(BrushSettings(baseRadiusPx=10f,spacing=1f,
spacingUsesDiameter=false,pressureToSize=false,pressureToOpacity=false));val d=DabBuffer(16);val down=InputBatch(1).apply{begin(
InputAction.DOWN);addSample(0f,0f,1f,0f,0f,0f,0,0,PointerTool.STYLUS,false));val move=InputBatch(1).apply{begin(InputAction.MOVE);
addSample(20f,0f,1f,0f,0f,0f,1,0,PointerTool.STYLUS,false));e.begin(down,d);e.append(move,d);e.finish(d,false);assertEquals(2,d.
count)}}
9
10     @Test fun tapProducesExactlyOneDab(){val e=StampEmitter(BrushSettings());val d=DabBuffer(16);val down=InputBatch(1).apply{
begin(InputAction.DOWN);addSample(5f,5f,1f,0f,0f,0f,0,0,PointerTool.STYLUS,false));e.begin(down,d);e.finish(d,false);assertEquals(1,
d.count)}}
11
12     @Test
13     fun activeStrokeKeepsItsSettingsAfterUiBrushChanges() {
14         val strokeSettings = BrushSettings(
15             baseRadiusPx = 5f,
16             spacing = 1f,
17             spacingUsesDiameter = false,
18             smoothing = 0f,
19             pressureToSize = false,
20             pressureToOpacity = false,
21         )
22         val emitter = StampEmitter(strokeSettings)
23         val dabs = DabBuffer(16)
24         val down = InputBatch(1).apply {
25             begin(InputAction.DOWN)
26             addSample(0f, 0f, 1f, 0f, 0f, 0f, 0L, 0, PointerTool.STYLUS, false)
27         }
28         val move = InputBatch(1).apply {
29             begin(InputAction.MOVE)
30             addSample(20f, 0f, 1f, 0f, 0f, 0f, 1L, 0, PointerTool.STYLUS, false)
31         }
32
33         emitter.begin(down, dabs, strokeSettings)
34         emitter.updateSettings(strokeSettings.copy(baseRadiusPx = 20f))
35         emitter.append(move, dabs)
36
37         assertEquals(5f, dabs.floats.get(2), 0.001f)
38     }
39 }

```


146. app/src/test/java/com/wetinknext/engine/core/DirtyRectTest.kt

```
1 package com.wetinknext.engine.core
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Assert.assertTrue
5 import org.junit.Test
6
7 class DirtyRectTest {
8     @Test fun includesDabsAndConvertsToPixelBounds() {
9         val rect = DirtyRect()
10        rect.include(100f, 120f, 10f)
11        rect.include(150f, 140f, 5f)
12        val pixels = IntArray(4)
13        rect.toPixelBounds(pixels)
14        assertEquals(intArrayOf(90, 110, 155, 145), pixels)
15    }
16
17    @Test fun clampCanMakeRectEmpty() {
18        val rect = DirtyRect()
19        rect.include(-100f, -100f, -10f)
20        rect.clamp(100f, 100f)
21        assertTrue(rect.isEmpty)
22    }
23
24    @Test fun clearResetsRect() {
25        val rect = DirtyRect()
26        rect.include(0f, 0f, 10f)
27        rect.clear()
28        assertTrue(rect.isEmpty)
29    }
30 }
```

147. app/src/test/java/com/wetinknext/engine/core/DocumentSessionTest.kt

```
1 package com.wetinknext.engine.core
2
3 import com.wetinknext.domain.document.ProjectDocument
4 import com.wetinknext.engine.canvas.LayerStack
5 import com.wetinknext.engine.undo.UndoManager
6 import org.junit.Assert.assertEquals
7 import org.junit.Assert.assertFalse
8 import org.junit.Assert.assertTrue
9 import org.junit.Test
10
11 class DocumentSessionTest {
12     @Test
13     fun committedLayersRemainDirtyUntilTheirSaveIsAcknowledged() {
14         val session = DocumentSession(
15             ProjectDocument.newUntitled(id = "session-test"),
16             LayerStack(),
17             UndoManager(),
18             emptyMap(),
19         )
20
21         session.markLayerDirty(2L)
22         session.markLayerDirty(2L)
23
24         assertEquals(setOf(2L), session.dirtyLayerIds)
25         assertTrue(session.projectDirty)
26
27         session.markSaved(setOf(2L))
28
29         assertTrue(session.dirtyLayerIds.isEmpty())
30         assertFalse(session.projectDirty)
31     }
32 }
```

148. app/src/test/java/com/wetinknext/engine/core/LatestValueDeliveryTest.kt

```
1 package com.wetinknext.engine.core
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Test
5
6 class LatestValueDeliveryTest {
7     @Test
8     fun captureBeforeListenerIsDeliveredAfterListenerIsInstalled() {
9         val delivery = LatestValueDelivery<String>()
10        val delivered = mutableListOf<String>()
11
12        delivery.offer("first-thumbnail")
13        delivery.dispatchTo(null)
14        delivery.dispatchTo(delivered::add)
15
16        assertEquals(listOf("first-thumbnail"), delivered)
17    }
18
19    @Test
20    fun newestCaptureReplacesAnUndeliveredOlderCapture() {
21        val delivery = LatestValueDelivery<String>()
22        val delivered = mutableListOf<String>()
23
24        delivery.offer("outdated")
25        delivery.offer("current")
26        delivery.dispatchTo(delivered::add)
27
28        assertEquals(listOf("current"), delivered)
29    }
30 }
```

149. app/src/test/java/com/wetinknext/engine/core/LayerTileCodecTest.kt

```
1 package com.wetinknext.engine.core
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Assert.assertEquals
5 import org.junit.Assert.assertNull
6 import org.junit.Test
7
8 class LayerTileCodecTest {
9     @Test
10     fun roundTripPreservesRgba8LayerPayload() {
11         val pixels = byteArrayOf(1, 2, 3, 4, 5, 6, 7, 8)
12         val decoded = LayerTileCodec.decode(LayerTileCodec.encode(2, 1, 4, pixels))
13
14         checkNotNull(decoded)
15         assertEquals(2, decoded.width)
16         assertEquals(1, decoded.height)
17         assertEquals(4, decoded.bytesPerPixel)
18         assertEquals(pixels, decoded.pixels)
19     }
20
21     @Test
22     fun emptyPayloadMeansNewTransparentLayer() {
23         assertNull(LayerTileCodec.decode(ByteArray(0)))
24     }
25 }
```

150. app/src/test/java/com/wetinknext/engine/core/PersistentLayerTilesTest.kt

```

1  package com.wetinknext.engine.persistence
2
3  import com.wetinknext.engine.undo.TileCoord
4  import java.nio.ByteBuffer
5  import java.nio.ByteOrder
6  import org.junit.Assert.assertArrayEquals
7  import org.junit.Assert.assertEquals
8  import org.junit.Assert.assertTrue
9  import org.junit.Test
10
11 class PersistentLayerTilesTest {
12     @Test
13     fun compressedPayloadRoundTripsTilePixels() {
14         val pixels = ByteArray(256 * 256 * 4)
15         val tile = PersistentLayerTiles.Tile(
16             coord = TileCoord(1, 2),
17             pixelLeft = 256,
18             pixelTop = 512,
19             pixelWidth = 256,
20             pixelHeight = 256,
21             bytesPerPixel = 4,
22             bytes = pixels,
23         )
24
25         val payload = PersistentLayerTiles.encode(listOf(tile))
26         val restored = PersistentLayerTiles.decode(payload).single()
27
28         assertTrue("transparent tile should compress", payload.size < pixels.size / 10)
29         assertEquals(tile.coord, restored.coord)
30         assertArrayEquals(pixels, restored.bytes)
31     }
32
33     @Test
34     fun versionOnePayloadRemainsReadableForMigration() {
35         val pixels = ByteArray(16) { it.toByte() }
36         val payload = ByteBuffer.allocate(12 + 32 + pixels.size)
37             .order(ByteOrder.BIG_ENDIAN)
38             .putInt(0x57544C53)
39             .putInt(1)
40             .putInt(1)
41             .putInt(0).putInt(0)
42             .putInt(0).putInt(0)
43             .putInt(2).putInt(2)
44             .putInt(4).putInt(pixels.size)
45             .put(pixels)
46             .array()
47
48         val restored = PersistentLayerTiles.decode(payload).single()
49
50         assertArrayEquals(pixels, restored.bytes)
51     }
52 }

```

151. app/src/test/java/com/wetinknext/engine/core/UndoCompressionPipelineTest.kt

```

1 package com.wetinknext.engine.core
2
3 import com.wetinknext.engine.undo.IdentityTileCompressor
4 import com.wetinknext.engine.undo.RawTileSnapshot
5 import com.wetinknext.engine.undo.TileCompressor
6 import com.wetinknext.engine.undo.TileCoord
7 import com.wetinknext.engine.undo.UndoManager
8 import org.junit.Assert.assertEquals
9 import org.junit.Assert.assertFalse
10 import org.junit.Assert.assertTrue
11 import org.junit.Test
12 import java.util.concurrent.CountDownLatch
13 import java.util.concurrent.Executors
14 import java.util.concurrent.TimeUnit
15 import java.util.concurrent.atomic.AtomicInteger
16
17 class UndoCompressionPipelineTest {
18     @Test
19     fun synchronousFallbackUsesTheSameOrderedHistoryPath() {
20         val manager = UndoManager()
21         val pipeline = UndoCompressionPipeline(
22             requestRender = {},
23             compressor = IdentityTileCompressor,
24             maxPendingJobs = 1,
25         )
26
27         pipeline.enqueue(
28             undoManager = manager,
29             layerId = 7L,
30             beforeRaw = listOf(raw(byteArrayOf(1, 2, 3, 4))),
31             afterRaw = listOf(raw(byteArrayOf(5, 6, 7, 8))),
32         )
33
34         assertEquals(0, pipeline.pendingCount)
35         assertEquals(1, manager.undoCount)
36         assertEquals(0, manager.redoCount)
37         assertTrue(manager.canUndo)
38         pipeline.shutdown()
39     }
40
41     @Test
42     fun laterWorkerResultWaitsForTheEarlierSequence() {
43         val firstCompressionStarted = CountDownLatch(1)
44         val allowFirstCompression = CountDownLatch(1)
45         val secondResultReady = CountDownLatch(1)
46         val allResultsReady = CountDownLatch(2)
47         val resultCount = AtomicInteger(0)
48         val executor = Executors.newFixedThreadPool(2)
49         val compressor = object : TileCompressor {
50             override fun compress(data: ByteArray): ByteArray {
51                 if (data.first() == 0.toByte()) {
52                     firstCompressionStarted.countDown()
53                     check(allowFirstCompression.await(2, TimeUnit.SECONDS))
54                 }
55                 return data
56             }
57
58             override fun decompress(data: ByteArray, expectedSize: Int): ByteArray = data
59         }
60         val manager = UndoManager()
61         val pipeline = UndoCompressionPipeline(
62             requestRender = {
63                 if (resultCount.incrementAndGet() == 1) secondResultReady.countDown()
64                 allResultsReady.countDown()
65             },
66             compressor = compressor,
67             executorFactory = { executor },
68         )
69
70         pipeline.enqueue(
71             undoManager = manager,
72             layerId = 1L,
73             beforeRaw = listOf(raw(byteArrayOf(0, 0, 0, 0))),
74             afterRaw = listOf(raw(byteArrayOf(2, 0, 0, 0))),
75         )
76         assertTrue(firstCompressionStarted.await(1, TimeUnit.SECONDS))
77
78         pipeline.enqueue(
79             undoManager = manager,
80             layerId = 2L,
81             beforeRaw = listOf(raw(byteArrayOf(1, 0, 0, 0))),
82             afterRaw = listOf(raw(byteArrayOf(3, 0, 0, 0))),
83         )
84         assertTrue(secondResultReady.await(1, TimeUnit.SECONDS))
85
86         assertFalse(pipeline.process(manager))
87         assertEquals(0, manager.undoCount)
88         assertEquals(2, pipeline.pendingCount)
89
90         allowFirstCompression.countDown()

```

```

91         assertTrue(allResultsReady.await(1, TimeUnit.SECONDS))
92
93         assertTrue(pipeline.process(manager))
94         assertEquals(2, manager.undoCount)
95         assertEquals(0, pipeline.pendingCount)
96         pipeline.shutdown()
97     }
98
99     private fun raw(bytes: ByteArray) = RawTileSnapshot(
100         coord = TileCoord(0, 0),
101         pixelLeft = 0,
102         pixelTop = 0,
103         pixelWidth = 1,
104         pixelHeight = 1,
105         bytesPerPixel = 4,
106         rawBytes = bytes,
107     )
108 }

```

152. app/src/test/java/com/wetinknext/engine/core/UndoHistoryTest.kt

```
1 package com.wetinknext.engine.core
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Assert.assertFalse
5 import org.junit.Assert.assertTrue
6 import org.junit.Test
7
8 class UndoHistoryTest {
9     @Test
10     fun staleResultIsRejected() {
11         assertFalse(isUndoResultCurrent(resultEpoch = 3L, currentEpoch = 4L))
12     }
13
14     @Test
15     fun failedCompressionDoesNotLeavePendingCountLocked() {
16         var pending = 1
17         val result: UndoJobResult =
18             UndoJobResult.Failed(epoch = 1L, sequence = 0L, error = IllegalStateException())
19
20         pending = (pending - 1).coerceAtLeast(0)
21
22         assertEquals(0, pending)
23         assertTrue(result is UndoJobResult.Failed)
24     }
25 }
```


153. app/src/test/java/com/wetinknext/engine/core/ViewTransformFboTest.kt

```
1 package com.wetinknext.engine.core
2 import org.junit.Assert.assertEquals
3 import org.junit.Test
4 class ViewTransformFboTest { @Test fun orthoValues(){val m=FloatArray(16);ViewTransform.buildCanvasToFbo(100f,200f,m);
assertEquals(.02f,m[0],.0001f);assertEquals(.01f,m[5],.0001f);assertEquals(-1f,m[12],.0001f);assertEquals(-1f,m[13],.0001f)} }
```

154. app/src/test/java/com/wetinknext/engine/core/ViewTransformTest.kt

```

1  package com.wetinknext.engine.core
2
3  import org.junit.Assert.assertEquals
4  import org.junit.Test
5
6  class ViewTransformTest {
7      @Test fun canvasAndScreenCoordinatesAreInverse() {
8          val transform = ViewTransform(120f, 80f, 2.5f, 0.35f, true)
9          val screen = FloatArray(2)
10         val canvas = FloatArray(2)
11         transform.canvasToScreen(240f, 310f, screen)
12         transform.screenToCanvas(screen[0], screen[1], canvas)
13         assertEquals(240f, canvas[0], 0.001f)
14         assertEquals(310f, canvas[1], 0.001f)
15     }
16
17     @Test fun zoomAroundAnchorKeepsAnchorStable() {
18         val initial = ViewTransform(translateX = 20f, translateY = 30f)
19         val before = FloatArray(2)
20         val after = FloatArray(2)
21         initial.screenToCanvas(400f, 300f, before)
22         initial.zoomAround(400f, 300f, 3f).screenToCanvas(400f, 300f, after)
23         assertEquals(before[0], after[0], 0.001f)
24         assertEquals(before[1], after[1], 0.001f)
25     }
26
27     @Test fun gestureDeltaKeepsTheAnchorStableWithoutPan() {
28         val initial = ViewTransform(translateX = 30f, translateY = -10f, scale = 1.4f, rotationRad = .2f)
29         val before = FloatArray(2)
30         val after = FloatArray(2)
31         initial.screenToCanvas(400f, 300f, before)
32         initial.applyGestureDelta(
33             panX = 0f,
34             panY = 0f,
35             anchorX = 400f,
36             anchorY = 300f,
37             zoomFactor = 1.8f,
38             rotationDelta = .3f,
39         ).screenToCanvas(400f, 300f, after)
40         assertEquals(before[0], after[0], .001f)
41         assertEquals(before[1], after[1], .001f)
42     }
43 }

```

155. app/src/test/java/com/wetinknext/engine/thumbnail/ThumbnailPreviewFilesTest.kt

```
1 package com.wetinknext.engine.thumbnail
2
3 import java.nio.file.Files
4 import org.junit.Assert.assertArrayEquals
5 import org.junit.Assert.assertEquals
6 import org.junit.Test
7
8 class ThumbnailPreviewFilesTest {
9     @Test
10     fun restoredLayerPreviewKeepsItsBytesAndStablePath() {
11         val directory = Files.createTempDirectory("wetink-preview-test").toFile()
12         try {
13             val bytes = byteArrayOf(0x52, 0x49, 0x46, 0x46, 0x01)
14
15             val restored = ThumbnailPreviewFiles.restoreLayerPreviews(
16                 outputDirectory = directory,
17                 previews = mapOf(42L to bytes),
18             )
19
20             val preview = requireNotNull(restored[42L])
21             assertEquals("42.webp", preview.name)
22             assertArrayEquals(bytes, preview.readBytes())
23         } finally {
24             directory.deleteRecursively()
25         }
26     }
27 }
```

156. `app/src/test/java/com/wetinknext/engine/undo/TileCoordinateContractTest.kt`

```
1 package com.wetinknext.engine.undo
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Test
5
6 class TileCoordinateContractTest {
7     @Test
8     fun topCanvasTileStartsAtBottomGlRegion() {
9         val canvasTop = 0
10        val glBottom = canvasTop
11        assertEquals(0, glBottom)
12    }
13
14    @Test
15    fun bottomCanvasTileUsesItsCanvasYAsGlY() {
16        val canvasTop = 1792
17        val glBottom = canvasTop
18        assertEquals(1792, glBottom)
19    }
20 }
```

157. app/src/test/java/com/wetinknext/engine/undo/TileSnapshotTest.kt

```
1 package com.wetinknext.engine.undo
2
3 import org.junit.Assert.assertArrayEquals
4 import org.junit.Assert.assertEquals
5 import org.junit.Test
6
7 class TileSnapshotTest {
8     @Test
9     fun rawIdentityTileKeepsItsExactBytes() {
10         val bytes = byteArrayOf(0, 10, 20, 30, 40, 50, 60, 70)
11         val tile = TileSnapshot(
12             coord = TileCoord(2, 3),
13             pixelLeft = 512,
14             pixelTop = 768,
15             pixelWidth = 1,
16             pixelHeight = 2,
17             bytesPerPixel = TileSnapshot.BYTES_PER_PIXEL_RGBA8,
18             storedData = bytes,
19         )
20
21         assertEquals(bytes.size, tile.memorySize)
22         assertEquals(bytes.size, tile.rawSize)
23         assertArrayEquals(bytes, tile.decompress())
24     }
25
26     @Test
27     fun tileSizeIsTheSpecified256Pixels() {
28         assertEquals(256, TileSnapshot.TILE_SIZE)
29     }
30 }
```

158. app/src/test/java/com/wetinknext/engine/undo/UndoManagerTest.kt

```

1 package com.wetinknext.engine.undo
2
3 import org.junit.Assert.assertEquals
4 import org.junit.Assert.assertFalse
5 import org.junit.Assert.assertNotNull
6 import org.junit.Assert.assertSame
7 import org.junit.Assert.assertTrue
8 import org.junit.Test
9
10 class UndoManagerTest {
11     @Test
12     fun undoAndRedoMoveTheSameEntryBetweenStacks() {
13         val manager = UndoManager()
14         val entry = entry(1L)
15         manager.push(entry)
16
17         assertTrue(manager.canUndo)
18         assertFalse(manager.canRedo)
19         assertSame(entry, manager.peekUndo())
20         assertTrue(manager.commitUndo(entry))
21         assertFalse(manager.canUndo)
22         assertTrue(manager.canRedo)
23         assertSame(entry, manager.peekRedo())
24         assertTrue(manager.commitRedo(entry))
25         assertTrue(manager.canUndo)
26         assertFalse(manager.canRedo)
27     }
28
29     @Test
30     fun aNewEntryClearsRedoHistory() {
31         val manager = UndoManager()
32         val first = entry(1L)
33         manager.push(first)
34         val undo = manager.peekUndo()
35         assertNotNull(undo)
36         assertTrue(manager.commitUndo(checkNotNull(undo)))
37         assertTrue(manager.canRedo)
38
39         manager.push(entry(1L))
40
41         assertFalse(manager.canRedo)
42         assertEquals(1, manager.undoCount)
43         assertEquals(0, manager.redoCount)
44     }
45
46     @Test
47     fun stepLimitEvictsTheOldestHistoryEntry() {
48         val manager = UndoManager(maxSteps = 2)
49         manager.push(entry(1L))
50         manager.push(entry(2L))
51         manager.push(entry(3L))
52
53         assertEquals(2, manager.undoCount)
54     }
55
56     @Test
57     fun rejectedCommitLeavesUndoHistoryUntouched() {
58         val manager = UndoManager()
59         val stored = entry(1L)
60         manager.push(stored)
61
62         assertFalse(manager.commitUndo(entry(2L)))
63         assertSame(stored, manager.peekUndo())
64         assertTrue(manager.canUndo)
65         assertFalse(manager.canRedo)
66     }
67
68     @Test
69     fun removingLayerPurgesOnlyThatLayersUndoAndRedoEntries() {
70         val manager = UndoManager()
71         val firstLayer = entry(1L)
72         val secondLayer = entry(2L)
73         manager.push(firstLayer)
74         manager.push(secondLayer)
75         assertTrue(manager.commitUndo(secondLayer))
76
77         manager.removeEntriesForLayer(1L)
78
79         assertFalse(manager.canUndo)
80         assertTrue(manager.canRedo)
81         assertSame(secondLayer, manager.peekRedo())
82
83         manager.removeEntriesForLayer(2L)
84
85         assertFalse(manager.canRedo)
86     }
87
88     @Test
89     fun entryKeepsItsOperationMetadata() {
90         val entry = UndoEntry(

```

```

91         layerId = 1L,
92         beforeTiles = emptyList(),
93         afterTiles = emptyList(),
94         operation = UndoOperationType.CLEAR_LAYER,
95         tag = "clear_layer",
96     )
97
98     assertEquals(UndoOperationType.CLEAR_LAYER, entry.operation)
99     assertEquals("clear_layer", entry.tag)
100 }
101
102 @Test
103 fun removingLayerEntriesDoesNotBlockOtherHistory() {
104     val manager = UndoManager()
105     val removedLayerEntry = entry(layerId = 10L)
106     val validEntry = entry(layerId = 20L)
107     manager.push(removedLayerEntry)
108     manager.push(validEntry)
109
110     manager.removeEntriesForLayer(10L)
111
112     assertTrue(manager.canUndo)
113     assertEquals(validEntry, manager.peekUndo())
114 }
115
116 @Test
117 fun fiveEntriesCanBeCommittedInOrder() {
118     val manager = UndoManager()
119     repeat(5) { index -> manager.push(entry(layerId = index.toLong())) }
120
121     assertEquals(5, manager.undoCount)
122     repeat(5) {
123         val entry = manager.peekUndo()
124         assertNotNull(entry)
125         assertTrue(manager.commitUndo(checkNotNull(entry)))
126     }
127
128     assertEquals(0, manager.undoCount)
129     assertEquals(5, manager.redoCount)
130 }
131
132 private fun entry(layerId: Long): UndoEntry = UndoEntry(
133     layerId = layerId,
134     beforeTiles = listOf(tile(0)),
135     afterTiles = listOf(tile(1)),
136 )
137
138 private fun tile(x: Int): TileSnapshot = TileSnapshot(
139     coord = TileCoord(x, 0),
140     pixelLeft = x,
141     pixelTop = 0,
142     pixelWidth = 1,
143     pixelHeight = 1,
144     bytesPerPixel = TileSnapshot.BYTES_PER_PIXEL_RGBA8,
145     storedData = arrayOf(1, 2, 3, 4),
146 )
147 }

```

159. build.gradle.kts

```
1 plugins {  
2     id("com.android.application") version "8.6.1" apply false  
3     id("org.jetbrains.kotlin.android") version "2.0.21" apply false  
4     id("org.jetbrains.kotlin.plugin.compose") version "2.0.21" apply false  
5     id("org.jetbrains.kotlin.plugin.serialization") version "2.0.21" apply false  
6 }
```


160. gradle.properties

```
1 org.gradle.jvmargs=-Xmx2048m -Dfile.encoding=UTF-8
2 android.useAndroidX=true
3 android.overridePathCheck=true
4 kotlin.code.style=official
5 org.gradle.daemon=true
6 org.gradle.caching=true
```

161. gradle/wrapper/gradle-wrapper.properties

```
1 distributionBase=GRADLE_USER_HOME
2 distributionPath=wrapper/dists
3 distributionUrl=https\://services.gradle.org/distributions/gradle-8.7-bin.zip
4 networkTimeout=10000
5 validateDistributionUrl=true
6 zipStoreBase=GRADLE_USER_HOME
7 zipStorePath=wrapper/dists
```

162. gradlew

```
1 #!/bin/sh
2
3 APP_HOME=$(CDPATH= cd -- "$(dirname -- "$0")" && pwd -P) || exit 1
4 JAVA_CMD="{JAVA_HOME:+$JAVA_HOME/bin/}java"
5 exec "$JAVA_CMD" -classpath "$APP_HOME/gradle/wrapper/gradle-wrapper.jar" org.gradle.wrapper.GradleWrapperMain "$@"
```

163. gradlew.bat

```
1 @rem Minimal Gradle startup script for Windows.
2 @echo off
3 setlocal
4 set APP_HOME=%~dp0
5 if defined JAVA_HOME goto javaHome
6 java -classpath "%APP_HOME%gradle\wrapper\gradle-wrapper.jar" org.gradle.wrapper.GradleWrapperMain %*
7 goto end
8 :javaHome
9 "%JAVA_HOME%\bin\java.exe" -classpath "%APP_HOME%gradle\wrapper\gradle-wrapper.jar" org.gradle.wrapper.GradleWrapperMain %*
10 :end
```

164. local.properties

```
1 sdk.dir=C:\\Users\\iick\\AppData\\Local\\Android\\Sdk
```

165. settings.gradle.kts

```
1  pluginManagement {
2      repositories {
3          google()
4          mavenCentral()
5          gradlePluginPortal()
6      }
7  }
8
9  dependencyResolutionManagement {
10     repositoriesMode.set(RepositoriesMode.FAIL_ON_PROJECT_REPOS)
11     repositories {
12         google()
13         mavenCentral()
14     }
15 }
16
17 rootProject.name = "WetInk Next"
18 include(":app")
```