

Introduction to Programming

Week – 8, Lecture – 3

Stacks and Queues

SAURABH SRIVASTAVA

DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING


IIT KANPUR



Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```

Memory for the Program




Assume that we are trying to execute this simple C program

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```

Memory for the Program




Assume that we are trying to execute this simple C program

It has four functions – `main()`, `f1()`, `f2()` and `f3()`

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```

Memory for the Program




Assume that we are trying to execute this simple C program

It has four functions – `main()`, `f1()`, `f2()` and `f3()`

The execution starts from the first statement in `main()`

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



A variable called `v1` is allocated in some "designated" space in the Main Memory

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




A variable called `v1` is allocated in some “designated” space in the Main Memory

This memory block is reserved for executing the `main()` function only

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



The next statement in `main()` is a call to the function `f1()`

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



At this point, some space in the memory is allocated for executing `f1()`

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




At this point, some space in the memory is allocated for executing `f1()`

The memory block for `main()` is also in the memory, but it is separated from this block

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




At this point, some space in the memory is allocated for executing `f1()`

The memory block for `main()` is also in the memory, but it is separated from this block

Some information is saved in the block, for resumption of `main()` on return of `f1()`

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



At this point, some space in the memory is allocated for executing `f1()`


The memory block for `main()` is also in the memory, but it is separated from this block

Some information is saved in the block, for resumption of `main()` on return of `f1()`

Local variable `v2`, which is a formal parameter for `f1()`, gets allocated in this block

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



At this point, some space in the memory is allocated for executing `f1()`

The memory block for `main()` is also in the memory, but it is separated from this block


Some information is saved in the block, for resumption of `main()` on return of `f1()`

Local variable `v2`, which is a formal parameter for `f1()`, gets allocated in this block

The first statement in `f1()` is a call to the function `f2()`

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



Again, another memory block is allocated, for executing `f2 ()` ...

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




Again, another memory block is allocated, for executing `f2 ()` ...

... and some information to return the control back to `f1 ()` is also stored

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




Again, another memory block is allocated, for executing `f2()` ...

... and some information to return the control back to `f1()` is also stored

The blocks for `f1()` and `main()` remain intact

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



Again, another memory block is allocated,
for executing `f2 ()` ...


... and some information to return the control
back to `f1 ()` is also stored

The blocks for `f1 ()` and `main ()` remain
intact

The `printf ()` statement executes, and since
there are no other statements, `f2 ()` returns

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



As soon as the return statement executes,
the block for f2 () gets freed

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




As soon as the return statement executes, the block for `f2()` gets freed

The return information is used at this point, to go back to the correct position in code

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



The control now returns to `f1 ()`

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




The control now returns to f1 ()

The next statement now, is a call to f3 ()

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



Another memory block gets allocated, this time for executing `f3()`

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




Another memory block gets allocated, this time for executing `f3()`

The formal parameter `v3`, is allocated in that block

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




Another memory block gets allocated, this time for executing `f3()`

The formal parameter `v3`, is allocated in that block

The return address information is also stored

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



Another memory block gets allocated, this time for executing f3 ()


The formal parameter v3, is allocated in that block

The return address information is also stored

The blocks for f1 () and main () still remain intact

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



Another memory block gets allocated, this time for executing `f3()`

The formal parameter `v3`, is allocated in that block


The return address information is also stored

The blocks for `f1()` and `main()` still remain intact

The `printf()` statement executes, and since there are no other statements, `f3()` returns

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



The memory block for `f3()`, too, is freed when the return statement is executed

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




The memory block for `f3()`, too, is freed when the return statement is executed

Again, the return information helps in taking the control back to `f1()`

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



Now, `f1 ()` too, has completed execution,
and can now return

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




Now, `f1()` too, has completed execution,
and can now return

Its memory block, too, is now freed

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```




Now, `f1()` too, has completed execution, and can now return

Its memory block, too, is now freed

With the help of the return information, control can now go back to `main()`

Example: How does a program execute?


```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



Finally, the `main()` too, completes and returns

Example: How does a program execute?

```
1  #include<stdio.h>
2  int main()
3  {
4      int v1 = 5;
5      f1(v1);
6      return 0;
7  }
8  void f1(int v2)
9  {
10     f2();
11     f3(v2);
12     return;
13 }
14 void f2()
15 {
16     printf("Hey !!");
17     return;
18 }
19 void f3(int v3)
20 {
21     printf("%d", v3);
22     return;
23 }
```



Finally, the `main()` too, completes and returns

At this point, the execution of the program ends, and the memory allocated to the respective process is freed in totality

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

This type of organisation of the memory is called a *stack*

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

This type of organisation of the memory is called a *stack*

A stack is a type of *data structure*

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

This type of organisation of the memory is called a *stack*

A stack is a type of *data structure*

- A data structure is just a way to organise data, so that it is useful for some purpose

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

This type of organisation of the memory is called a *stack*

A stack is a type of *data structure*

- A data structure is just a way to organise data, so that it is useful for some purpose

In a stack, the data that is stored last, is taken out first, and vice versa

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

This type of organisation of the memory is called a *stack*

A stack is a type of *data structure*

- A data structure is just a way to organise data, so that it is useful for some purpose

In a stack, the data that is stored last, is taken out first, and vice versa

One way to implement a stack, is by using restricted insertions and deletions over an array

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

This type of organisation of the memory is called a *stack*

A stack is a type of *data structure*

- A data structure is just a way to organise data, so that it is useful for some purpose

In a stack, the data that is stored last, is taken out first, and vice versa

One way to implement a stack, is by using restricted insertions and deletions over an array

- The restriction is that the values can only be added or removed from the higher end of the array

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

This type of organisation of the memory is called a *stack*

A stack is a type of *data structure*

- A data structure is just a way to organise data, so that it is useful for some purpose

In a stack, the data that is stored last, is taken out first, and vice versa

One way to implement a stack, is by using restricted insertions and deletions over an array

- The restriction is that the values can only be added or removed from the higher end of the array
- We call the currently highest index of the array, where some element is present, as the *top* of the stack

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

This type of organisation of the memory is called a *stack*

A stack is a type of *data structure*

- A data structure is just a way to organise data, so that it is useful for some purpose

In a stack, the data that is stored last, is taken out first, and vice versa

One way to implement a stack, is by using restricted insertions and deletions over an array

- The restriction is that the values can only be added or removed from the higher end of the array
- We call the currently highest index of the array, where some element is present, as the *top* of the stack

The operation to add an element to a stack is called *push()* and it takes the element as argument

The concept of a Stack

One aspect of the memory blocks that we saw, is that they follow a *last in first out* pattern...

- ... i.e. the block for the function which was called most recently in the function call chain, is freed first

This type of organisation of the memory is called a *stack*

A stack is a type of *data structure*

- A data structure is just a way to organise data, so that it is useful for some purpose

In a stack, the data that is stored last, is taken out first, and vice versa

One way to implement a stack, is by using restricted insertions and deletions over an array

- The restriction is that the values can only be added or removed from the higher end of the array
- We call the currently highest index of the array, where some element is present, as the *top* of the stack

The operation to add an element to a stack is called *push()* and it takes the element as argument

The operation to delete an element from a stack is called *pop()* and it returns the deleted element

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

Assume that we have a single element in the stack right now

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

`top = 0`

Assume that we have a single element in the stack right now

The `top` right now points to index 0

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

If we push an element, 21, it is inserted at position 1

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

If we push an element, 21, it is inserted at position 1

The top now points to index 1

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

push(39)

0	1	2	3	4
12	21	39	x	x

top = 2

If we push another element, 39, it is inserted at position 2

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

push(39)

0	1	2	3	4
12	21	39	x	x

top = 2

If we push another element, 39, it is inserted at position 2

The top now points to index 2

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

push(39)

0	1	2	3	4
12	21	39	x	x

top = 2

pop() [returns 39]

0	1	2	3	4
12	21	x	x	x

top = 1

If we pop an element, the element at index `top` is removed

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

push(39)

0	1	2	3	4
12	21	39	x	x

top = 2

pop() [returns 39]

0	1	2	3	4
12	21	x	x	x

top = 1

If we pop an element, the element at index `top` is removed

The removed element, i.e., 39, is returned, and `top` now points to 1

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

push(39)

0	1	2	3	4
12	21	39	x	x

top = 2

pop() [returns 39]

0	1	2	3	4
12	21	x	x	x

top = 1

pop() [returns 21]

0	1	2	3	4
12	x	x	x	x

top = 0

Another pop will remove 12 from the stack

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

push(39)

0	1	2	3	4
12	21	39	x	x

top = 2

pop() [returns 39]

0	1	2	3	4
12	21	x	x	x

top = 1

pop() [returns 21]

0	1	2	3	4
12	x	x	x	x

top = 0

Another pop will remove 12 from the stack

The top now points to index 0

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

push(39)

0	1	2	3	4
12	21	39	x	x

top = 2

pop() [returns 39]

0	1	2	3	4
12	21	x	x	x

top = 1

pop() [returns 21]

0	1	2	3	4
12	x	x	x	x

top = 0

push(43)

0	1	2	3	4
12	43	x	x	x

top = 1

Another push operation, say with element 43, adds it to index 1

Example: Stack using an array

0	1	2	3	4
12	x	x	x	x

top = 0

push(21)

0	1	2	3	4
12	21	x	x	x

top = 1

push(39)

0	1	2	3	4
12	21	39	x	x

top = 2

pop() [returns 39]

0	1	2	3	4
12	21	x	x	x

top = 1

pop() [returns 21]

0	1	2	3	4
12	x	x	x	x

top = 0

push(43)

0	1	2	3	4
12	43	x	x	x

top = 1

Another push operation, say with element 43, adds it to index 1

The top again increases to index 1

A counterpart of Stack – Queue

With stack, the insertions and deletions are restricted at just one end

A counterpart of Stack – Queue

With stack, the insertions and deletions are restricted at just one end

Another data structure with a lot of utility is called *queue*

A counterpart of Stack – Queue

With stack, the insertions and deletions are restricted at just one end

Another data structure with a lot of utility is called *queue*

In a queue, insertions and deletions are still restricted to ends, but they occur at different ends

- Instead of last in first out, a queue is a *first in first out* data structure

A counterpart of Stack – Queue

With stack, the insertions and deletions are restricted at just one end

Another data structure with a lot of utility is called *queue*

In a queue, insertions and deletions are still restricted to ends, but they occur at different ends

- Instead of last in first out, a queue is a *first in first out* data structure

The end where insertions are done, is called the rear end...

- ... and a variable that points to the index of the last inserted element is called *rear*

A counterpart of Stack – Queue

With stack, the insertions and deletions are restricted at just one end

Another data structure with a lot of utility is called *queue*

In a queue, insertions and deletions are still restricted to ends, but they occur at different ends

- Instead of last in first out, a queue is a *first in first out* data structure

The end where insertions are done, is called the rear end...

- ... and a variable that points to the index of the last inserted element is called *rear*

Similarly, the other end, where deletions occur, is called the front end...

- ... and a variable that points to the element which will go out next is called *front*

A counterpart of Stack – Queue

With stack, the insertions and deletions are restricted at just one end

Another data structure with a lot of utility is called *queue*

In a queue, insertions and deletions are still restricted to ends, but they occur at different ends

- Instead of last in first out, a queue is a *first in first out* data structure

The end where insertions are done, is called the rear end...

- ... and a variable that points to the index of the last inserted element is called *rear*

Similarly, the other end, where deletions occur, is called the front end...

- ... and a variable that points to the element which will go out next is called *front*

The counterparts of push() and pop() are called *enqueue()* and *dequeue()* respectively

A counterpart of Stack – Queue

With stack, the insertions and deletions are restricted at just one end

Another data structure with a lot of utility is called *queue*

In a queue, insertions and deletions are still restricted to ends, but they occur at different ends

- Instead of last in first out, a queue is a *first in first out* data structure

The end where insertions are done, is called the rear end...

- ... and a variable that points to the index of the last inserted element is called *rear*


Similarly, the other end, where deletions occur, is called the front end...

- ... and a variable that points to the element which will go out next is called *front*


The counterparts of push() and pop() are called *enqueue()* and *dequeue()* respectively

Queues are often used in holding details for processes, so that they can be scheduled judiciously

Example: Scheduling Processes



Example: Scheduling Processes



Example: Queue using an array

0	1	2	3	4
12	x	x	x	x

```
rear = 0  
front = 0
```

Assume that we have a single element in the queue right now

Example: Queue using an array

0	1	2	3	4
12	x	x	x	x

```
rear = 0  
front = 0
```

Assume that we have a single element in the queue right now

Both `rear` and `front` point to index 0

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

If we enqueue an element, 21, in the queue, it is added at index 1

0	1	2	3	4
12	21	X	X	X

enqueue (21)

```
rear = 1  
front = 0
```

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

enqueue (21)

0	1	2	3	4
12	21	X	X	X

```
rear = 1  
front = 0
```

If we enqueue an element, 21, in the queue, it is added at index 1

While `rear` now points to index 1, `front` remains unchanged

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

Another enqueue request, for element 39, is then executed

0	1	2	3	4
12	21	X	X	X

enqueue (21)

```
rear = 1  
front = 0
```

0	1	2	3	4
12	21	39	X	X

enqueue (39)

```
rear = 2  
front = 0
```

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

enqueue (21)

0	1	2	3	4
12	21	X	X	X

```
rear = 1  
front = 0
```

enqueue (39)

0	1	2	3	4
12	21	39	X	X

```
rear = 2  
front = 0
```

Another enqueue request, for element 39, is then executed

The element is added at index 2

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

enqueue (21)

0	1	2	3	4
12	21	X	X	X

```
rear = 1  
front = 0
```

enqueue (39)

0	1	2	3	4
12	21	39	X	X

```
rear = 2  
front = 0
```

Another enqueue request, for element 39, is then executed

The element is added at index 2

It means `rear` now points to 2; `front` remains at 0

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

0	1	2	3	4
12	21	X	X	X

enqueue (21)

```
rear = 1  
front = 0
```

0	1	2	3	4
12	21	39	X	X

enqueue (39)

```
rear = 2  
front = 0
```

0	1	2	3	4
X	21	39	X	X

dequeue () [returns 12]

```
rear = 2  
front = 1
```

On receiving a dequeue request, element 12 is removed from the queue and returned

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

enqueue (21)

0	1	2	3	4
12	21	X	X	X

```
rear = 1  
front = 0
```

enqueue (39)

0	1	2	3	4
12	21	39	X	X

```
rear = 2  
front = 0
```

dequeue () [returns 12]

0	1	2	3	4
X	21	39	X	X

```
rear = 2  
front = 1
```

On receiving a dequeue request, element 12 is removed from the queue and returned

The `front` now moves to index 1, while `rear` points to the same index as before

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

0	1	2	3	4
12	21	X	X	X

enqueue (21)

```
rear = 1  
front = 0
```

0	1	2	3	4
12	21	39	X	X

enqueue (39)

```
rear = 2  
front = 0
```

dequeue () [returns 12]

0	1	2	3	4
X	21	39	X	X

```
rear = 2  
front = 1
```

dequeue () [returns 21]

0	1	2	3	4
X	X	39	X	X

```
rear = 2  
front = 2
```

One more dequeue request removes 21 this time the queue, and the same is returned

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

enqueue (21)

0	1	2	3	4
12	21	X	X	X

```
rear = 1  
front = 0
```

enqueue (39)

0	1	2	3	4
12	21	39	X	X

```
rear = 2  
front = 0
```

dequeue () [returns 12]

0	1	2	3	4
X	21	39	X	X

```
rear = 2  
front = 1
```

dequeue () [returns 21]

0	1	2	3	4
X	X	39	X	X

```
rear = 2  
front = 2
```

One more dequeue request removes 21 this time the queue, and the same is returned

The `front` moves further to index 2, joining `rear`

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

0	1	2	3	4
12	21	X	X	X

enqueue (21)

```
rear = 1  
front = 0
```

0	1	2	3	4
12	21	39	X	X

enqueue (39)

```
rear = 2  
front = 0
```

0	1	2	3	4
X	21	39	X	X

dequeue () [returns 12]

```
rear = 2  
front = 1
```

0	1	2	3	4
X	X	39	X	X

dequeue () [returns 21]

```
rear = 2  
front = 2
```

0	1	2	3	4
X	X	39	43	X

enqueue (43)

```
rear = 3  
front = 2
```

And again, another enqueue operation, this time for element 43, results in its addition in the queue at index 3

Example: Queue using an array

0	1	2	3	4
12	X	X	X	X

```
rear = 0  
front = 0
```

enqueue (21)

0	1	2	3	4
12	21	X	X	X

```
rear = 1  
front = 0
```

enqueue (39)

0	1	2	3	4
12	21	39	X	X

```
rear = 2  
front = 0
```

dequeue () [returns 12]

0	1	2	3	4
X	21	39	X	X

```
rear = 2  
front = 1
```

dequeue () [returns 21]

0	1	2	3	4
X	X	39	X	X

```
rear = 2  
front = 2
```

enqueue (43)

0	1	2	3	4
X	X	39	43	X

```
rear = 3  
front = 2
```

And again, another enqueue operation, this time for element 43, results in its addition in the queue at index 3

This results in advancement of `rear` to index 3, leaving `front` at index 2

Uses of Stacks and Queues

We saw how stacks are used to implement a system for chains of function calls

Uses of Stacks and Queues

We saw how stacks are used to implement a system for chains of function calls

In fact, if you have a recursive solution to a difficult problem...

- ... and for performance reasons, you want to convert it to an iterative solution...
- ... using a stack can provide a straightforward conversion

Uses of Stacks and Queues

We saw how stacks are used to implement a system for chains of function calls

In fact, if you have a recursive solution to a difficult problem...

- ... and for performance reasons, you want to convert it to an iterative solution...
- ... using a stack can provide a straightforward conversion

Queues are used for many purposes in Computer Science

- Protocols that requires a “first-come-first-serve” model usually use queues in background
- A common example is usage in any type of message delivery system

Uses of Stacks and Queues

We saw how stacks are used to implement a system for chains of function calls

In fact, if you have a recursive solution to a difficult problem...

- ... and for performance reasons, you want to convert it to an iterative solution...
- ... using a stack can provide a straightforward conversion

Queues are used for many purposes in Computer Science

- Protocols that requires a “first-come-first-serve” model usually use queues in background
- A common example is usage in any type of message delivery system

However, the formulation of queues that we saw in this lecture is seldom used

- It is because we will not be able to enqueue any new element, when `rear` reaches the end of the array
- Usually, the queues that are used more practically, are *circular* in nature (see **Additional Reading** slide)

Uses of Stacks and Queues

We saw how stacks are used to implement a system for chains of function calls

In fact, if you have a recursive solution to a difficult problem...

- ... and for performance reasons, you want to convert it to an iterative solution...
- ... using a stack can provide a straightforward conversion

Queues are used for many purposes in Computer Science

- Protocols that requires a “first-come-first-serve” model usually use queues in background
- A common example is usage in any type of message delivery system

However, the formulation of queues that we saw in this lecture is seldom used

- It is because we will not be able to enqueue any new element, when `rear` reaches the end of the array
- Usually, the queues that are used more practically, are *circular* in nature (see **Additional Reading** slide)

This was just an introduction to two most common data structures

- We will have a look at one more important data structure – *linked lists* – in the next week

Homework !!

Revisit the program called `BasicArrayOperations.c` from Week 5

- Change it to create two programs – `StackOperations.c` and `QueueOperations.c`
- Modify the code to emulate the working of a stack and a queue respectively
- See if you can handle the problem with formulation of a queue that we discussed

Hint: May be shifting elements of the array could lead to a solution

Additional Reading

A more practical version of queue is called *circular queue*

- A circular queue allows the rear and the front variables to “wrap-around”...
- ... i.e., they can go from 0 to size-1 and vice versa, if applicable

Read more about circular queues

- You may start here:
<https://www.geeksforgeeks.org/circular-queue-set-1-introduction-array-implementation/>