CHAKRABORTY OVERSEAS

Fastener Export Catalogue

Mild steel · Stainless steel · High tension & precision · Miscellaneous · Construction & machinery

Sourced from verified Indian manufacturing partners, checked against your specification, export packed and shipped with complete documentation. Sizes M3 to M72 subject to range and item.

MERCHANT EXPORTER · HOWRAH (KOLKATA), WEST BENGAL, INDIA

IEC Available
GSTIN Available
EEPC RCMC - Available
exports@chakrabortyoverseas.com
+91 98316 47114

RANGE 01

Stainless Steel Fasteners

SPECIFICATION

GRADES	SS 202 · SS 304 (A2) · SS 316 (A4) · SS 304L · SS 316L · SS Super Duplex - the same set across every type
STANDARDS	BIS, IS, DIN, ASTM, BSW, UNC
SIZES	M2.5 - M72 bolts, nuts, screws, washers and studs · ST2.9 - ST6.3 self-tapping and self-drilling
FINISH	Self colour, passivated, electropolished, PTFE coated
TYPICAL USE	Marine and offshore, food and chemical plant, façades, water treatment

Shown in bright and passivated stainless - electropolished and PTFE coated to order

BOLTS & SCREWS



Hex bolts

GRADE A2-70 (SS 304) · A4-80 (SS 316)

STANDARD ISO 4014 / 4017, DIN 931 / 933



Flange bolts

GRADE A2 / A4 · serrated or plain flange

STANDARD DIN 6921, IS 1364



Carriage bolts

HEAD Cup head, square neck

STANDARD DIN 603, IS 2609



Eye bolts

TYPE Collared lifting and plain eye

STANDARD DIN 580, IS 4190



U-bolts

TYPE Round and square bend, with nuts

STANDARD To drawing or pipe schedule



J-bolts

TYPE Hook bolt, threaded one end

STANDARD To drawing



Machine screws

HEAD Pan, cheese, CSK, raised CSK

STANDARD DIN 84, DIN 963, ISO 7045



Self-tapping & self-drilling screws

POINT Type A, AB, B and self-drilling

STANDARD DIN 7981 / 7982, DIN 7504, ISO 1479

NUTS



Hex nuts

GRADE A2 / A4 (SS 304 / SS 316)

STANDARD ISO 4032 / 4033, DIN 934



Heavy hex nuts

GRADE A4 · Super Duplex on request

STANDARD ASTM A194, DIN 6915



Nylock nuts

INSERT Nylon ring, prevailing torque

STANDARD DIN 985, ISO 7040



Dome nuts

TYPE Closed cap, high and low crown

STANDARD DIN 1587, DIN 917



Wing nuts & wing bolts

TYPE Cold forged and cast pattern

STANDARD DIN 315, IS 2687



Flange nuts

TYPE Serrated and plain flange

STANDARD DIN 6923, BSW / UNC to order

WASHERS, ROD & ANCHORS



Washers

TYPE Plain, spring, star, taper, heavy duty

STANDARD DIN 125, DIN 127, ISO 7089



Threaded rod & studs

LENGTH 1 m / 3 m bar and cut studs

STANDARD DIN 975 / 976, ASTM A193 B8



Anchor & wedge bolts

TYPE Wedge, sleeve and drop-in

STANDARD To manufacturer specification



Specials to drawing

BASIS Made to buyer drawing or sample

STANDARD As specified on the drawing

RANGE 02

Mild Steel Fasteners

SPECIFICATION

GRADES	Bolts, nuts, studs and threaded rod: class 4.6, 4.8, 5.6, 5.8 · washers and screws are size-rated, not property-class rated
STANDARDS	DIN 933 / 931 (bolts) · DIN 934 (nuts) · DIN 125 (washers) · IS 1363 / 1367
SIZES	M3 - M48 for bolts · nuts to M60
FINISH	Black, bright zinc, yellow zinc, hot dip galvanised, geomet
TYPICAL USE	General fabrication, construction, furniture, sheet metal

Shown in bright and yellow zinc - black, hot dip galvanised and geomet to order

BOLTS



Hex bolts

GRADE 4.6 / 4.8 / 5.6 / 5.8

STANDARD IS 1363, DIN 931 / 933, ANSI B18.2.1



Hex flange bolts

GRADE 4.6 - 5.8 · serrated or plain flange

STANDARD DIN 6921, IS 1364



Carriage bolts

HEAD Cup head, square neck

STANDARD DIN 603, IS 2609



Eye bolts

TYPE Collared lifting and plain eye

STANDARD DIN 580, IS 4190



Threaded rod, tie rod & studs

TYPE Male full thread rod and cut studs

STANDARD DIN 975 / 976

SCREWS



Self-tapping screws

POINT Type A, AB, B and self-drilling

STANDARD DIN 7981, DIN 7504



Drywall screws

THREAD Coarse and fine, bugle head

FINISH Phosphated black, zinc



Chipboard screws

DRIVE Pozi, Torx, Phillips

FINISH Yellow zinc, bright zinc



Machine screws

HEAD Pan, cheese, CSK, raised CSK

STANDARD DIN 84, DIN 963, ISO 7045

NUTS



Hex & square nuts

GRADE Class 5, 6 · thin and thick

STANDARD IS 1363, DIN 934, DIN 557



Nylock nuts

INSERT Nylon ring, prevailing torque

STANDARD DIN 985, DIN 982, ISO 7040



Dome nuts

TYPE Closed cap, high and low crown

STANDARD DIN 1587, DIN 917



Wing nuts

TYPE Cold forged and cast pattern

STANDARD DIN 315, IS 2687



Flange nuts

TYPE Serrated and plain, MS & HT

STANDARD DIN 6923

INDIVIDUAL NUT TYPES



T slot nut

USE Machine tables and profile slots

STANDARD DIN 508, to drawing



Spring channel nut

TYPE Long and short spring, plain

USE Strut channel support systems



Long hex nut / bar nut

TYPE Coupling nut, hex bar

STANDARD DIN 6334



DF nut / hex bar nut

TYPE Deformed thread, prevailing torque

STANDARD DIN 980



Thin hex / lock nuts

TYPE Jam nut, half thickness

STANDARD DIN 439, ISO 4035

WASHERS



Plain washer

TYPE Form A and heavy pattern

STANDARD DIN 125, IS 2016



Spring washer

MATERIAL MS and spring steel (En 42)

STANDARD DIN 127, IS 3063



Star washer - internal

TYPE Internal tooth serrated

STANDARD DIN 6797 J



Star washer - external & overlap

TYPE External tooth and overlap star

STANDARD DIN 6797 A



Taper washer

USE Channel and joist flanges

STANDARD IS 5372 / 5374



Square washer

USE Timber and structural packing

STANDARD To drawing

ANCHOR FASTENERS



Wedge anchor

FIXING Through fixing into concrete

FINISH Bright zinc, yellow zinc, HDG



Drop-in anchor

FIXING Flush internally threaded

SETTING Setting tool required



Nylon frame fixing anchor

FIXING Frame and façade fixing

BODY Nylon sleeve with screw



Rawl bolt anchor

TYPE Bolt projecting, loose bolt

FINISH Yellow zinc



Rawl hook anchor

TYPE Eye and hook pattern

USE Suspended services



Pin type anchor

TYPE Hammer-set pin anchor

FINISH Yellow zinc



Sleeve anchor

HEAD Hex, flange, CSK

USE Concrete, brick, block



Anchor shell & anchor nut

TYPE Shell with internal thread

USE Ceiling and soffit fixing



Rawl goli

TYPE Expansion ball anchor

USE Light duty concrete fixing

INSERT & RIVET NUTS



Rivet / insert nuts

BODY Knurled, round and hex body

HEAD Flat, reduced, CSK



Tee nut - prong

TYPE Four prong, hammer in

USE Timber and board



Wooden D insert nut

TYPE Screw-in threaded insert

FINISH Yellow zinc, bright zinc



Clinch nut

TYPE Self-clinching for sheet metal

USE Panels and enclosures



Socket rivet / bush nut

TYPE Bush and barrel socket rivet

FINISH Nickel, zinc


CAGE, PROFILE & CHANNEL HARDWARE



Cage nut

TYPE Spring cage, square hole

USE Racks and enclosures



Slotted profile T-nut

TYPE Slide-in and drop-in T nut

USE Aluminium profile systems



T-hammer bolt

TYPE Quarter turn hammer head

USE Profile and channel systems



T-hammer nut

TYPE Hammer head nut

USE Profile and channel systems



Flange nylock nut

TYPE Serrated flange, nylon insert

STANDARD DIN 6926

FURNITURE FITTINGS



Minifix items

SET Cam, bolt, dowel and cap

USE Knock-down furniture



Barrel nut

TYPE Cross dowel, slotted drive

FINISH Zinc, nickel



Cabinet screw connector

TYPE Male - female connector screw

USE Cabinet and panel joining

CONSTRUCTION & MACHINERY BOLTS



Foundation bolt

TYPE L, J and plate type anchors

STANDARD To drawing, IS 5624



U-bolt

TYPE Round and square bend with nuts

USE Pipe and axle clamping



J-bolt

TYPE Hook bolt, threaded one end

USE Concrete anchoring, tie down



Belt fasteners

TYPE Bolted plate belt joiners

USE Conveyor belt splicing



Elevator bucket bolt

HEAD Flat countersunk, square neck

USE Bucket elevators, grain handling



JCB furniture bolt

HEAD Dome head, square neck

USE Earth-moving attachments



Fala bolt

TYPE Shuttering and scaffold bolt

FINISH Black, bright zinc

RANGE 03

High Tension & Precision

SPECIFICATION

PROPERTY CLASS	Bolts 8.8, 10.9, 12.9 · 14.9 (non-ISO, to buyer spec) · nuts class 8, 10, 12 · studs and threaded rod 8.8, 10.9, 12.9 · socket screws 12.9
HSFG CLASS	Bolts 8.8S, 10.9S, 12.9S · nuts 8S, 10S, 12S
STANDARDS	DIN 931 / 933 (bolts) · DIN 934 (nuts) · DIN 912 / ISO 4762 (socket cap) · DIN 913 / 914 / 915 / 916 (set screws) · ISO 4014 / 4017 · ISO 898-1 · BS 1768 · ANSI B18.2.1 / 18.2.2
MATERIAL	Alloy and carbon steel, heat treated
FINISH	Dacro, Geomet, hot dip galvanised, zinc-aluminium flake, Delta-Seal, Delta-Tone, zinc-iron plating, chrome-passivated zinc, thermal & chemical blackening, electroless nickel
SIZES	M3 - M48 for bolts and socket screws · nuts to M60
TYPICAL USE	Structural steelwork, automotive, plant and machinery

Shown in black oxide - Dacro, Geomet, zinc flake and HDG to order

HIGH TENSILE BOLTS & NUTS



High tensile hex bolts

CLASS 8.8 / 10.9 / 12.9 · 14.9 (non-ISO, to buyer spec)

STANDARD ISO 4014, DIN 931, ASTM F3125 (Gr. A325 / A490)



High tensile nuts

CLASS 8 / 10 / 12 to match bolt class

STANDARD ISO 4032, DIN 934, ASTM A194 2H



Structural stud bolts

TYPE Full thread stud with two heavy nuts

STANDARD ASTM A193 B7 / A194 2H

HSFG STRUCTURAL ASSEMBLIES



HSFG bolts

GRADE 8.8S / 10.9S / 12.9S

STANDARD IS 3757, BS 4395, ASTM F3125



HSFG nuts

GRADE Matched to bolt grade

STANDARD IS 6623, BS 4395



HSFG washers

TYPE Hardened flat, square taper

STANDARD IS 6649, BS 4395



DTI washers

TYPE Direct tension indicator

STANDARD ASTM F959, BS 7644

SOCKET SERIES



Socket head cap screws

CLASS 12.9 black or plated

STANDARD DIN 912, ISO 4762, ANSI B18.3



Socket button head screws

CLASS 10.9 / 12.9

STANDARD ISO 7380, DIN 7380



CLASS 10.9 / 12.9

STANDARD DIN 7991, ISO 10642



Socket set / grub screws

POINT Cup, cone, flat, dog point

STANDARD DIN 913 - 916, ISO 4026 - 4029

PRECISION & SPECIALS



Precision turned parts

BASIS CNC turned to buyer drawing

TOLERANCE As per drawing · ISO 2768



Special high tension items

BASIS Non-standard heads, lengths, coatings

STANDARD ISO / DIN / ANSI / BS as required