iiode Re27

Datasheet

Lighting made conscious

iiode Re27 delivers tunable white light in the standard E27 form factor, pairing true-to-life colours and comfort with environmental and social responsibility. Designed for serviceability and compatibility with existing lighting solutions and new fixtures, iiode Re27 unites past and present while charting a brighter future for us all.

PHYSICAL

Dimensions:	Ø 60 × 110 mm
Base:	nickel-plated E27
Heatsink:	Recycled aluminium
Lens:	Recycled polycarbonate
Weight:	~150 g

ELECTRICAL

Input:	220–240 V~ 50/60 Hz
Current	(typ.): 0.07 A
Power:	15 W
LED efficacy:	115 lm/W (package, typ.)
Lifetime:	50,000 h

ILLUMINATION

CCT:	2200–5700 K
Lumens:	1000 lm
Flicker:	< 1 % @ 1 200 Hz (typ.)
Clip-in lense:	±135° isotropic
Light source:	Bridgelux CSP array
CRI (Ra):	≥95

Certification pending

REMOTE CONTROL
Bluetooth mesh by default, with dual-channel tunable white and global dimming. Firmware swappable at assembly to third-party stacks.

CONSTRUCTION & ORIGIN
Recycled-aluminium heatsink and recycled poly-carbonate lens allow disassembly for field-serviceable PCBs and recycling at end-of-life. Mechanical components primarily sourced in the EU under fair working conditions. Developed & assembled by iiode in Switzerland.

iiode

Av. des Alpes 9 CH - 1006 Lausanne

iiode.com | info@iiode.com | @iiode

Specifications subject to change without notice. Please refer to our website for the most recent product documentation.

iiode Re27 is an EU-registered, patent-pending design by iiode.