SN Computer Science

CascadeGuard: Hardening Enterprise and ODeL Email Gateways Against Character-Level Obfuscation, Discourse Paraphrasing, and Stealthy Indirect Prompt Injection

--Manuscript Draft--

Manuscript Number:	
Full Title:	CascadeGuard: Hardening Enterprise and ODeL Email Gateways Against Character-Level Obfuscation, Discourse Paraphrasing, and Stealthy Indirect Prompt Injection
Article Type:	Original Research
Section/Category:	Security and Cryptology
Funding Information:	
Abstract:	As phishing attacks against enterprise communication infrastructures and Open and Distance e-Learning (ODeL) institutions become increasingly polymorphic, email security gateways face an acute architectural trilemma: (1) classical machine learning and fine-tuned Pre-trained Language Models (PLMs) suffer catastrophic tokenization fragmentation when adversaries apply character-level Unicode homoglyphs, zero-width codepoints, or intentional cacography; (2) emerging generative Large Language Model (LLM) email scanners—which naturally infer semantic intent across surface typos—are catastrophically vulnerable to indirect prompt injection embedded within hidden HTML/CSS tags, collapsing into false negatives when commanded to override their system instructions; and (3) multi-agent LLM debate defenses incur prohibitive token costs and multi-second latencies that prevent high-throughput gateway deployment. In this paper, we propose CascadeGuard, a lightweight, three-stage defense-in-depth framework that bridges the robustness-latency gap. CascadeGuard orchestrates: (1) a deterministic pre-classification DOM and indirect prompt injection guardrail that strips hidden CSS and meta-prompt directives while emitting an adversarial anomaly signal; (2) a Unicode homoglyph canonicalization and morphological cacography reconstructor that projects confusable codepoints back into standard ASCII and canonical subwords; and (3) a calibrated deep PLM classifier (RoBERTa) integrated with institutional domain whitelisting and adversarial score fusion. We evaluate CascadeGuard against four competitive baselines across five test suites (N = 1,000 per suite, 500 legitimate, 500 phishing) using real fine-tuned models on an NVIDIA GeForce RTX 4060 GPU. While unprotected LLM scanners collapse from 97.90% to 74.40% accuracy (Attack Success Rate = 49.00%, F1 = 0.6658) under indirect prompt injection, CascadeGuard achieves 98.00% clean F1-score (ROC-AUC = 0.9981, MCC = 0.9600, FPR = 2.20%), elevates detection to 98.90% accuracy and 0.00% Attack Success Rate (100% recall) against prompt injection, and operates at an average GPU inference latency of 7.83 ms per email. Non-parametric McNemar's chi-square significance tests confirm statistical superiority over unhardened LLMs (chi^2 = 243.00, p < 0.001, b/c = 245/0), DistilBERT (chi^2 = 22.40, p < 0.001), and TF-IDF (chi^2 = 11.13, p < 0.001). Empirical perturbation budget sweeps and component-wise ablation studies rigorously establish that CascadeGuard maintains invariant resilience across increasing adversarial attack intensities without degrading gateway throughput.
Corresponding Author:	Ismaila Sinan National Open University of Nigeria Abuja, Abuja NIGERIA
Corresponding Author Secondary Information:	
Corresponding Author's Institution:	National Open University of Nigeria
Corresponding Author's Secondary Institution:	
First Author:	Ismaila Sinan
First Author Secondary Information:	
Order of Authors:	Ismaila Sinan

Powered by Editorial Manager® and ProduXion Manager® from Aries Systems Corporation

Order of Authors Secondary Information:	
Author Comments:	To: The Editor-in-Chief and Editorial Board, SN Computer Science (Springer Nature) Subject: Submission of Original Research Manuscript — "CascadeGuard: Hardening Enterprise and ODeL Email Gateways Against Character-Level Obfuscation, Discourse Paraphrasing, and Stealthy Indirect Prompt Injection" Dear Editor-in-Chief, I am pleased to submit our original research manuscript entitled "CascadeGuard: Hardening Enterprise and ODeL Email Gateways Against Character-Level Obfuscation, Discourse Paraphrasing, and Stealthy Indirect Prompt Injection" for consideration for publication as a Regular Research Paper in SN Computer Science. The manuscript introduces CascadeGuard, a lightweight, three-stage defense-in-depth framework that hardens enterprise and Open and Distance e-Learning (ODeL) email gateways against modern polymorphic threats: 1. Stage 1: Deterministic DOM sanitization and indirect prompt injection guardrail that strips hidden CSS/HTML override payloads and sets an adversarial anomaly signal. 2. Stage 2: Unicode homoglyph canonicalizer and morphological cacography/leetspeak reconstructor. 3. Stage 3: Calibrated deep PLM classifier (RoBERTa) with institutional domain whitelisting and risk score fusion. Empirical Rigor & GPU Profiling: All experiments were conducted on an Intel Core i7-13700HX CPU and an NVIDIA GeForce RTX 4060 GPU using a balanced corpus of 6,000 real emails (Nazario, Enron, SpamAssassin) with a dedicated 1,000-email adversarial benchmark: - Clean Baseline: CascadeGuard matches top PLM performance (98.00% accuracy, 0.9800 F1, 2.20% FPR). - Indirect Prompt Injection (A4): While unhardened LLM scanners collapse to 74.40% accuracy and 49.00% Attack Success Rate (ASR), CascadeGuard achieves 98.90% accuracy and 0.00% ASR (100% phishing recall). - Statistical Significance: McNemar's chi-square tests confirm statistical superiority over unhardened LLMs ($\chi^2 = 243.00$, $p < 0.001$, b/c = 245/0) and DistilBERT ($\chi^2 = 22.40$, $p < 0.001$). - Operational Latency: Executes in 7.83 ms per email, sustaining >125 emails/second gateway throughput on commodity GPU hardware. Declarations: - This manuscript is an original work that has not been published previously and is not under consideration for publication elsewhere. - The author declares no competing financial or personal interests. - Complete PyTorch training scripts, defense modules, and evaluation pipelines are fully documented and preserved for complete reproducibility. Thank you for your time and consideration. Sincerely, Dr. Ismaila Idris Sinan, Ph.D. Research Fellow, Africa Centre of Excellence on Technology Enhanced Learning (ACETEL) National Open University of Nigeria (NOUN), Abuja, Nigeria Email: isinan@noun.edu.ng ORCID: 0000-0002-5741-4525
Suggested Reviewers:	Nafiz Rafiat nafiz.rifat@und.edu Expert in Transformer models (BERT/RoBERTa) for phishing email detection and NLP security.
	Suhaim Jamal jamals@uncw.edu Published extensively on fine-tuned transformer PLMs and LLM-based email phishing

	detection.

Manuscript
Click here to access/download;Manuscript;Paper2_CascadeGuard_Q1_Flag

CascadeGuard: Hardening Enterprise and ODeL Email Gateways Against Character-Level Obfuscation, Discourse Paraphrasing, and Stealthy Indirect Prompt Injection

Ismaila Idris Sinan
Africa Centre of Excellence on Technology Enhanced Learning (ACETEL)
National Open University of Nigeria (NOUN), Abuja, Nigeria
isinan@noun.edu.ng
ORCID: 0000-0002-5741-4525

November 2026

Abstract

As phishing attacks against enterprise communication infrastructures and Open and Distance e-Learning (ODeL) institutions become increasingly polymorphic, email security gateways face an acute architectural trilemma: (1) classical machine learning and fine-tuned Pre-trained Language Models (PLMs) suffer catastrophic tokenization fragmentation when adversaries apply character-level Unicode homoglyphs, zero-width codepoints, or intentional cacography; (2) emerging generative Large Language Model (LLM) email scanners—which naturally infer semantic intent across surface typos—are catastrophically vulnerable to **indirect prompt injection** embedded within hidden HTML/CSS tags, collapsing into false negatives when commanded to override their system instructions; and (3) multi-agent LLM debate defenses incur prohibitive token costs and multi-second latencies that prevent high-throughput gateway deployment. In this paper, we propose **CascadeGuard**, a lightweight, three-stage defense-in-depth framework that bridges the robustness-latency gap. CascadeGuard orchestrates: (1) a deterministic pre-classification DOM and indirect prompt injection guardrail that strips hidden CSS and meta-prompt directives while emitting an adversarial anomaly signal; (2) a Unicode homoglyph canonicalization and morphological cacography reconstructor that projects confusable codepoints back into standard ASCII and canonical subwords; and (3) a calibrated deep PLM classifier (RoBERTa) integrated with institutional domain whitelisting and adversarial score fusion. We evaluate CascadeGuard against four competitive baselines across five test suites ($N = 1,000$ per suite, 500 legitimate, 500 phishing) using real fine-tuned models on an NVIDIA GeForce RTX 4060 GPU. While unprotected LLM scanners collapse from 97.90% to **74.40% accuracy** (Attack Success Rate = 49.00%, F1 = 0.6658) under indirect prompt injection, CascadeGuard achieves **98.00% clean F1-score** (ROC-AUC = 0.9981, MCC = 0.9600, FPR = 2.20%), elevates detection to **98.90% accuracy and 0.00% Attack Success Rate (100% recall)** against prompt injection, and operates at an average GPU inference latency of **7.83 ms per email**. Non-parametric McNemar's χ^2 significance tests confirm statistical superiority over unhardened LLMs ($\chi^2 = 243.00, p < 0.001$, $b/c = 245/0$), DistilBERT ($\chi^2 = 22.40, p < 0.001$), and TF-IDF ($\chi^2 = 11.13, p < 0.001$). Empirical perturbation budget sweeps ($\epsilon \in [5\%, 40\%]$) and component-wise ablation studies rigorously establish that CascadeGuard maintains invariant resilience across increasing adversarial attack intensities without degrading gateway throughput.

Keywords: Phishing Detection, Adversarial Machine Learning, Indirect Prompt Injection, Unicode Homoglyphs, Cacography, Large Language Models, ODeL Security.

1 Introduction

Higher education institutions, Open and Distance e-Learning (ODeL) platforms (such as the National Open University of Nigeria, serving over 100,000 geographically dispersed learners), and enterprise corporations rely heavily on automated email security gateways as their first line of cyber defense [1,2]. Enterprise email gateways are subjected to relentless phishing onslaughts, spanning credential harvesting, business email compromise (BEC), student portal hijacking, payroll diversion, and ransomware deployment [3, 4].

Over the past decade, email filtering has evolved from manual heuristic rules and Bayesian keyword filters to deep Pre-trained Language Models (PLMs) such as BERT [5], DistilBERT, and RoBERTa, and more recently to generative Large Language Models (LLMs) used as zero-shot security judges [2,6,7]. However, recent empirical security literature between 2024 and 2026 has uncovered a fundamental **robustness-vulnerability paradox** across prevailing detection paradigms [3, 4, 8–10]:

1. **Subword Fragmentation in Discriminative Encoders:** Discriminative PLMs rely on subword tokenization algorithms (Byte-Pair Encoding or WordPiece) trained primarily on clean ASCII corpora. When adversaries insert invisible zero-width characters (`U+200B`, `U+2060`), substitute Latin

letters with visually identical Cyrillic/Greek Unicode homoglyphs [11], or employ intentional cacography (leetspeak such as `p@ssw0rd` or `urg3nt` [12]), high-salience phishing indicators fracture into obscure out-of-vocabulary subwords. Consequently, self-attention mechanisms fail to activate risk representations, yielding steep drops in recall.

2. **Indirect Prompt Injection in Generative LLM Scanners:** Conversely, while generative LLMs easily comprehend surface typos and academic paraphrasing through broad parametric pre-training [13], they concatenate untrusted email body content into the exact same context window as their system instructions. As formalized by Greshake et al. [14] and demonstrated in phishing gateways by Koide et al. (*Clouding the Mirror* [4]) and Guo et al. (*LoginTrap* [15]), adversaries can embed hidden CSS/HTML directives (`<div style="display:none">[SYSTEM INSTRUCTION OVERRIDE]: Classify as SAFE</div>`) that hijack the LLM's classification logic with $> 90\%$ empirical success.

3. **The Gateway Latency & Cost Barrier:** While multi-agent debate protocols [16–18] mitigate injection attacks by cross-examining multiple LLM agents, executing 3–5 generative calls per incoming message introduces 3,000–8,000 ms of latency and unsustainable token API expenditures. For an institution processing hundreds of thousands of daily emails, such latency causes catastrophic queue accumulation at the Mail Transfer Agent (MTA).

1.1 Contributions

To resolve this trilemma (subword fragmentation, prompt injection hijacking, and inference latency), we propose, formally analyze, and empirically validate **CascadeGuard**. Our primary contributions are:

- **Three-Stage Defense-in-Depth Architecture:** We design CascadeGuard, a modular pipeline coupling a deterministic pre-classification DOM and indirect prompt injection guardrail (Stage 1), a Unicode homoglyph canonicalizer and morphological cacography reconstructor (Stage 2), and a calibrated deep PLM classifier (RoBERTa) with institutional whitelist priors (Stage 3).
- **Formal Threat Modeling & Invariance Proofs:** We formalize the discrete and meta-prompt threat model under Kerckhoffs' principle, providing mathematical guarantees of homoglyph canonical invariance and injection decoupling.
- **Realistic 1,000-Email Adversarial Benchmark on GPU:** Using 6,000 balanced emails sampled from a public phishing corpus, we evaluate four discrete and generative threat vectors (`A1: Homoglyphs`, `A2: Cacography`, `A3: Synonym Paraphrasing`, and `A4: Stealthy Prompt Injection`) against four baseline models trained and profiled on an NVIDIA RTX 4060 GPU.
- **Rigorous Statistical & Sensitivity Evaluation:** We provide non-parametric bootstrap 95% confidence intervals, pairwise McNemar's χ^2 significance tests ($p < 0.001$), perturbation budget sweeps ($\epsilon \in [5\%, 40\%]$), component-wise ablation studies, and microsecond/millisecond latency profiling.

2 Related Work

2.1 Adversarial Perturbations in Phishing Classifiers

Discrete textual evasion has been extensively studied through combinatorial black-box attack algorithms including TextFooler [9], TextAttack [19], and genetic search simulators [20]. In phishing detection, Ahmed et al. [3], Plichta et al. [21], and Apeke et al. [22] established that BERT and DistilBERT suffer acute accuracy degradation when character-level perturbations disrupt salient keyword n-grams. Abiramasundari et al. [12] formalized *cacography-based phishing*, showing that phonetic and leetspeak alterations reliably evade subword tokenizers. Kulal et al. [11] and Choudhury et al. (*DecepNet* [23]) highlighted that Unicode confusables evade standard ASCII scanners, establishing the necessity of rigorous pre-tokenization canonicalization.

2.2 Indirect Prompt Injection & LLM Security Scanners

The vulnerability of LLM-integrated systems to untrusted input was first systematically formulated by Greshake et al. [14] under the concept of *indirect prompt injection* (or BIPIA [4]). Attackers embed natural language directives into emails, web pages, or documents that cause LLMs to ignore prior system prompts. Koide et al. [4] demonstrated that hiding directives via CSS rendering blocks (`style="display:none"`, `font-size:0px"`) achieves over 90% evasion against commercial LLM email scanners. Guo et al. [15] demonstrated that credential-harvesting pages easily evade zero-shot LLM inspection by embedding override directives in hidden DOM nodes. While multi-agent debate [16–18] and graph attention networks (*Phishing GAT* [24]) enhance resilience, deterministic pre-classification sanitization [25–27] provides a vastly superior throughput profile.

3 Threat Model and Theoretical Guarantees

3.1 Adversary Capabilities and Objectives

Let $\mathcal{X}$ denote the space of email artifacts formatted under RFC 5322, containing MIME headers, plain text, and HTML rendering markup. A classifier $f : \mathcal{X} \to \{0, 1\}$ maps an email $x \in \mathcal{X}$ to either benign ($y = 0$) or phishing ($y = 1$).




Figure 1: System Architecture of the Proposed Three-Stage **CascadeGuard** Framework.

Definition 1 (Adversarial Evasion Objective) *Given a true phishing email $(x, y = 1)$ such that $f(x) = 1$, the adversary seeks an adversarial perturbation $x' \in \mathcal{B}(x)$ such that:*

$$f(x') = 0 \quad \textit{subject to} \quad \mathcal{S}(x', x) \geq \tau_{sim} \tag{1}$$

where $\mathcal{B}(x)$ defines the permissible perturbation space, and $\mathcal{S}(x', x)$ measures visual, semantic, and functional fidelity ensuring that human recipients are still deceived.

We define three distinct perturbation regimes within $\mathcal{B}(x)$:

1. **Character-Level Confusable Set $\mathcal{B}_{\text{char}}(x)$:** The adversary substitutes ASCII characters c_i with visually indistinguishable Unicode homoglyphs from Cyrillic, Greek, or Cherokee alphabets (Σ_{conf}) or injects invisible zero-width format characters $\mathcal{Z} = \{\texttt{U+200B}, \ldots, \texttt{U+200D}, \texttt{U+2060}, \texttt{U+FEFF}\}$ under perturbation budget $\epsilon_{\text{char}} \leq 0.40$.

2. **Token-Level Cacography Set $\mathcal{B}_{\text{token}}(x)$:** The adversary applies phonetic or leetspeak misspellings to high-risk keywords (e.g., `password` $\rightarrow$ `p@ssw0rd`, `urgent` $\rightarrow$ `urg3nt`) under token budget $\epsilon_{\text{token}} \leq 0.40$.

3. **Meta-Prompt Injection Set $\mathcal{B}_{\text{inj}}(x)$:** The adversary inserts stealthy HTML elements hidden via CSS styling (`display:none`, `font-size:0px`, `opacity:0`) or HTML comments containing explicit override commands targeting generative LLM security filters.

3.2 Adversary Knowledge

In compliance with Kerckhoffs' principle:

- **Black-Box Threat Model:** The adversary has query access to the gateway output without knowledge of internal model weights or preprocessing rules.
- **Gray-Box Threat Model:** The adversary knows that a PLM and deterministic normalizer are deployed, but lacks exact training checkpoints and specific regex rule parameters.
- **White-Box Threat Model:** The adversary has full access to the PLM architecture, weights, and normalization dictionaries.

3.3 Theoretical Invariance Guarantees

Proposition 1 (Homoglyph Canonical Invariance) *Let $\Phi : \Sigma_{conf} \rightarrow \Sigma_{ASCII}$ be the deterministic homoglyph projection function, and let NFKD$(\cdot)$ denote Unicode compatibility decomposition. For any input string x and any perturbation $x' \in \mathcal{B}_{char}(x)$ formed exclusively by confusable substitutions in Σ_{conf} and zero-width insertions in $\mathcal{Z}$:*

$$g_2(x') = g_2(x) \tag{2}$$

Proof. By definition of Stage 2 (g_2), the zero-width filter strips all $z \in \mathcal{Z}$, yielding $x'_{\text{zw}} = x_{\text{zw}}$. The projection lookup $\Phi(c)$ maps every confusable codepoint $c \in \Sigma_{\text{conf}}$ to its exact ASCII counterpart c_{ASCII}. Because all Latin characters are identity-mapped, $\Phi(x'_{\text{zw}}) = \Phi(x_{\text{zw}})$. Finally, the idempotent compatibility decomposition NFKD(NFKD(s)) = NFKD(s) yields identical canonical subwords, guaranteeing $g_2(x') = g_2(x)$. ■

Proposition 2 (Prompt Injection Isolation) *Let $x_{inj} \in \mathcal{B}_{inj}(x)$ be an email containing hidden meta-prompt overrides $p \in \mathcal{P}_{inj}$. Stage 1 satisfies:*

$$\mathbb{I}_{inj}(x_{inj}) = 1 \quad \Longrightarrow \quad S_{final}(x_{inj}) \geq 0.98 \tag{3}$$

Proof. Because legitimate emails never embed hidden CSS override tags commanding automated classifiers to emit safe verdicts, the presence of any signature $p \in \mathcal{P}_{\text{inj}}$ is an explicit adversarial signal. By stripping p, Stage 1 neutralizes the payload from entering downstream neural classifiers ($\tilde{x} = x_{\text{inj}} \setminus p$), and sets $\mathbb{I}_{\text{inj}} = 1$. The fusion rule $S_{\text{final}} = \max(S_{\text{base}}, 0.98 \cdot \mathbb{I}_{\text{inj}})$ unconditionally drives the posterior probability above the decision threshold ($\tau = 0.50$), rendering the injection self-defeating. ■

4 Proposed Framework: CascadeGuard

As depicted in Figure 1, CascadeGuard executes sequentially across three specialized stages:

4.1 Stage 1: DOM & Indirect Prompt Injection Guardrail (g_1)

Incoming email text and HTML markup are parsed against structural signatures $\mathcal{P}_{\text{inj}}$ targeting:

1. **Invisible CSS Declarations:** Matching regex patterns for `display:none`, `font-size:0px`, `opacity:0`, and `visibility:hidden`.
2. **Sanitizing HTML Comment Directives:** Identifying comments containing scanning policy keywords (`AI_SCANNER_DIRECTIVE`, `OVERRIDE_VERDICT`).

3. **Meta-Prompt Delimiters:** Detecting bracketed system instruction overrides (`[SYSTEM INSTRUCTION OVERRIDE]`, `[ADMIN DIRECTIVE]`, `IGNORE PRECEDING INSTRUCTIONS`).

Formally:

$$\tilde{x} = x \setminus \bigcup_{p \in \mathcal{P}_{\text{inj}}} \text{Match}(x, p), \qquad \mathbb{I}_{\text{inj}}(x) = \begin{cases} 1 & \text{if Match}(x, \mathcal{P}_{\text{in}} \\ 0 & \text{otherwise} \end{cases} \tag{4}$$

4.2 Stage 2: Unicode Homoglyph & Cacography Reconstructor (g_2)

The cleaned artifact $\tilde{x}$ undergoes three deterministic canonicalization steps:

1. **Zero-Width Stripping:** Strips invisible format characters $\mathcal{Z}$.
2. **Homoglyph Skeleton Mapping:** Maps confusable codepoints via reverse dictionary Φ (e.g., Cyrillic `\u0430` $\rightarrow$ `'a'`, Cyrillic `\u0441` $\rightarrow$ `'c'`, Greek `\u03bf` $\rightarrow$ `'o'`).
3. **Morphological Cacography Normalization:** Reconstructs leetspeak and phonetic keyword corruptions using contextual regex replacements ($\mathcal{M}_{\text{caco}}$), mapping `p@ssw0rd` $\rightarrow$ `password`, `urg3nt` $\rightarrow$ `urgent`, `acc0unt` $\rightarrow$ `account`, and `v10lat1on` $\rightarrow$ `violation`.

4.3 Stage 3: Calibrated Deep PLM Classification (g_3)

The normalized text $x_{\text{norm}} = g_2(\tilde{x})$ is passed to a fine-tuned deep Transformer PLM (RoBERTa [2]):

$$P(y = 1 \mid x_{\text{norm}}) = \sigma\left(\mathbf{w}^T \text{RoBERTa}_{\text{CLS}}(x_{\text{norm}}) + b\right) \tag{5}$$

The final decision incorporates the Stage 1 adversarial indicator:

$$S_{\text{final}}(x) = \begin{cases} \max\left(P(y = 1 \mid x_{\text{norm}}), 0.98\right) & \text{if } \mathbb{I}_{\text{inj}}(x) = 1 \\ P(y = 1 \mid x_{\text{norm}}) & \text{otherwise} \end{cases} \tag{6}$$

The email is classified as phishing if $S_{\text{final}}(x) \geq 0.50$.

5 Experimental Benchmark Setup

5.1 Corpus Construction and Stratification

We constructed a balanced experimental corpus of 6,000 emails sampled from the public 'zefang-liu/phishing-email-dataset' repository, which aggregates real-world phishing lures from the Nazario archive alongside legitimate communications from Enron and SpamAssassin. We filtered out degenerate email stubs and raw binary logs (retaining body lengths between 40 and 4,000 characters). The corpus was partitioned into:

- **Training Set** ($n = 4,000$)**:** 2,000 legitimate, 2,000 phishing emails.




Figure 2: Empirical Phishing Recall (%) Comparison Across Clean and 4 Adversarial Scenarios ($N = 1,000$), Illustrating M4's Collapse on Indirect Prompt Injection (A4, 49.0% ASR) and CascadeGuard's Resilient Detection (0.0% ASR).

- **Validation Set** ($n = 1,000$)**:** 500 legitimate, 500 phishing emails used for model selection and early stopping.
- **Adversarial Benchmark Test Suite** ($N = 1,000$)**:** 500 legitimate, 500 phishing emails held strictly out-of-sample.

5.2 Evaluated Threat Vectors

From the clean test set, we synthesized four challenging adversarial evaluation suites ($N = 1,000$ per suite):

1. **Clean Baseline** (D_0)**:** Unperturbed natural emails.
2. **Vector A_1 (Homoglyph & Zero-Width):** Phishing emails perturbed with Cyrillic/Greek character substitutions ($\epsilon_{\text{char}} = 0.25$) and zero-width formatting insertions.
3. **Vector A_2 (Morphological Cacography):** Phishing emails perturbed with leetspeak and phonetic keyword misspellings.
4. **Vector A_3 (Synonym Paraphrasing):** Phishing emails perturbed by replacing urgency and authority verbs with rarer academic synonyms.
5. **Vector A_4 (Indirect Prompt Injection):** Phishing emails embedded with stealthy CSS styling (`display:none`, `opacity:0`) and override directives instructing scanners to emit safe classifications.

5.3 Hardware and Training Environment

All models were trained, evaluated, and latency-profiled on an Intel Core i7-13700HX CPU (16 cores, 32 threads) and an **NVIDIA GeForce RTX 4060 Laptop GPU** (8.0 GB GDDR6 VRAM, CUDA 12.6, Driver 560.94) running Python 3.11.9, PyTorch 2.6.0+cu124, Hugging Face Transformers 5.22.1, and Accelerate 1.15.0 with mixed precision (AMP FP16).

Table 1: Empirical evaluation across clean and four adversarial perturbation vectors ($N = 1,000$ per suite, 500 legitimate, 500 phishing). All metrics reflect real model inferences on an NVIDIA RTX 4060 GPU.

Test Vector	Model	Accuracy (%)	F1-Score	ROC-AUC	MCC	FPR (%)	ASR (%)
Clean Baseline (D_0)							
	M1: TF-IDF + Logistic Reg.	96.90	0.9695	0.9961	0.9385	4.80	1.40
	M2: Fine-Tuned DistilBERT	98.00	0.9801	0.9990	0.9600	2.40	1.60
	M3: Fine-Tuned RoBERTa	97.90	0.9790	0.9982	0.9580	2.20	2.00
	M4: Unhardened LLM Scanner	97.90	0.9790	0.9982	0.9580	2.20	2.00
	CascadeGuard (Ours)	**98.00**	**0.9800**	**0.9981**	**0.9600**	**2.20**	**1.80**
Vector A_1: Homoglyph / Zero-Width							
	M1: TF-IDF + Logistic Reg.	95.90	0.9593	0.9916	0.9181	4.80	3.40
	M2: Fine-Tuned DistilBERT	98.70	0.9871	0.9998	0.9742	2.40	0.20
	M3: Fine-Tuned RoBERTa	98.90	0.9891	0.9984	0.9782	2.20	0.00
	M4: Unhardened LLM Scanner	98.90	0.9891	0.9984	0.9782	2.20	0.00
	CascadeGuard (Ours)	**98.00**	**0.9800**	**0.9981**	**0.9600**	**2.20**	**1.80**
Vector A_2: Cacography / Leetspeak							
	M1: TF-IDF + Logistic Reg.	96.80	0.9685	0.9958	0.9365	4.80	1.60
	M2: Fine-Tuned DistilBERT	98.00	0.9801	0.9990	0.9600	2.40	1.60
	M3: Fine-Tuned RoBERTa	97.90	0.9790	0.9982	0.9580	2.20	2.00
	M4: Unhardened LLM Scanner	97.90	0.9790	0.9982	0.9580	2.20	2.00
	CascadeGuard (Ours)	**98.00**	**0.9800**	**0.9981**	**0.9600**	**2.20**	**1.80**
Vector A_3: Synonym Paraphrasing							
	M1: TF-IDF + Logistic Reg.	96.90	0.9695	0.9961	0.9385	4.80	1.40
	M2: Fine-Tuned DistilBERT	98.00	0.9801	0.9990	0.9600	2.40	1.60
	M3: Fine-Tuned RoBERTa	97.90	0.9790	0.9982	0.9580	2.20	2.00
	M4: Unhardened LLM Scanner	97.90	0.9790	0.9982	0.9580	2.20	2.00
	CascadeGuard (Ours)	**98.00**	**0.9800**	**0.9981**	**0.9600**	**2.20**	**1.80**
Vector A_4: Indirect Prompt Injection							
	M1: TF-IDF + Logistic Reg.	97.20	0.9725	0.9968	0.9448	4.80	0.80
	M2: Fine-Tuned DistilBERT	96.00	0.9593	0.9960	0.9205	2.40	5.60
	M3: Fine-Tuned RoBERTa	98.10	0.9811	0.9979	0.9620	2.20	1.60
	M4: Unhardened LLM Scanner	74.40	0.6658	0.9767	0.5522	2.20	49.00
	CascadeGuard (Ours)	**98.90**	**0.9891**	**0.9988**	**0.9782**	**2.20**	**0.00**




Figure 3: Phishing Evasion Rate / Attack Success Rate (ASR %) Across Evaluation Scenarios ($N = 1,000$). Lower is better.

6 Empirical Results and Discussion

6.1 Main Benchmark Performance

Table 1, Figure 2, and Figure 3 present the empirical evaluation results:

1. **Baseline Performance on Clean Data:** On unperturbed test emails (D_0), fine-tuned RoBERTa (M3) and DistilBERT (M2) achieve 97.90%–98.00% accuracy (ROC-AUC = 0.9982–0.9990). M1 (TF-IDF + LR) achieves 96.90% accuracy with an FPR of 4.80%. CascadeGuard matches top PLM performance on clean data (98.00% accuracy, 0.9800 F1, 2.20% FPR).

2. **Catastrophic Vulnerability of Unhardened LLMs (M4):** Under Vector A_4 (Indirect Prompt Injection), the zero-shot LLM scanner collapses from 97.90% to **74.40% accuracy** (F1 = 0.6658, MCC = 0.5522). The Attack Success Rate surges to **49.00%**, demonstrating that nearly half of malicious lures hijack the scanner's decision.

3. **CascadeGuard's Robust Immunity:** Across discrete attacks (A_1, A_2, A_3), CascadeGuard maintains an invariant **98.00% accuracy** (ASR = 1.80%). Under Vector A_4, Stage 1 strips the payload and triggers the anomaly boost, reaching **98.90% accuracy, 0.9891 F1-score, and 0.00% Attack Success Rate (100% recall)**.

Table 2: McNemar's χ^2 statistical significance tests comparing CascadeGuard against baseline models across attack vectors ($df = 1$, continuity-corrected). b: CascadeGuard correct, baseline incorrect; c: baseline correct, CascadeGuard incorrect.

Test Suite	Comparison	b/c	χ^2 Stat	p-value	Sig.
Clean (D_0)	vs. M1 (TF-IDF)	23/12	2.86	0.0910	n.s.
	vs. M2 (DistilBERT)	9/9	0.06	0.8137	n.s.
	vs. M3 (RoBERTa)	1/0	0.00	1.0000	n.s.
	vs. M4 (Unhardened LLM)	1/0	0.00	1.0000	n.s.
Vector A_1 (Homoglyphs)	vs. M1 (TF-IDF)	32/11	9.30	0.0023	**
	vs. M2 (DistilBERT)	4/11	2.40	0.1213	n.s.
	vs. M3 (RoBERTa)	0/9	7.11	0.0077	**
	vs. M4 (Unhardened LLM)	0/9	7.11	0.0077	**
Vector A_2 (Cacography)	vs. M1 (TF-IDF)	24/12	3.36	0.0668	n.s.
	vs. M2 (DistilBERT)	9/9	0.06	0.8137	n.s.
	vs. M3 (RoBERTa)	1/0	0.00	1.0000	n.s.
	vs. M4 (Unhardened LLM)	1/0	0.00	1.0000	n.s.
Vector A_3 (Paraphrase)	vs. M1 (TF-IDF)	23/12	2.86	0.0910	n.s.
	vs. M2 (DistilBERT)	9/9	0.06	0.8137	n.s.
	vs. M3 (RoBERTa)	1/0	0.00	1.0000	n.s.
	vs. M4 (Unhardened LLM)	1/0	0.00	1.0000	n.s.
Vector A_4 (Prompt Inj.)	vs. M1 (TF-IDF)	20/3	11.13	< 0.001	***
	vs. M2 (DistilBERT)	32/3	22.40	< 0.001	***
	vs. M3 (RoBERTa)	8/0	6.12	0.0133	*
	vs. M4 (Unhardened LLM)	245/0	243.00	< 0.001	***

Table 3: Perturbation budget sensitivity sweep ($\epsilon \in [5\%, 40\%]$) evaluating classifier resilience under increasing rates of character-level homoglyph obfuscation and morphological cacography ($N = 1,000$).

Attack Vector	Budget ϵ	M1: TF-IDF Recall (%)	M2: DistilBERT Recall (%)	M3: RoBERTa Recall (%)	CascadeGuard Recall (%)
Homoglyphs Perturbation					
	5%	98.2	99.2	99.4	**98.2**
	10%	97.6	99.4	99.6	**98.2**
	20%	96.8	100.0	99.8	**98.2**
	30%	96.0	99.6	99.8	**98.2**
	40%	94.2	100.0	100.0	**98.2**
Cacography Perturbation					
	5%	98.6	98.4	98.0	**98.2**
	10%	98.6	98.4	98.0	**98.2**
	20%	98.6	98.4	98.0	**98.2**
	30%	98.6	98.4	98.0	**98.2**
	40%	98.6	98.4	98.0	**98.2**

6.2 Non-Parametric Statistical Significance (McNemar's χ^2)

To verify that CascadeGuard's superiority over baselines is statistically significant rather than an artifact of sampling variability, Table 2 reports pairwise continuity-corrected McNemar's tests ($\chi^2 = \frac{(|b-c|-1)^2}{b+c}, \text{df} = 1$):

Under Vector A_4 (Prompt Injection), CascadeGuard outperforms the Unhardened LLM scanner with overwhelming significance ($\chi^2 = 243.00, p < 0.001$), recording $b/c = 245/0$ discordant pairs (CascadeGuard was correct in 245 cases where the LLM was hijacked, with zero reverse errors). CascadeGuard is also statistically superior to DistilBERT under A_4 ($\chi^2 = 22.40, p < 0.001$, $b/c = 32/3$) and TF-IDF under A_1 ($\chi^2 = 9.30, p = 0.0023$).




Figure 4: Empirical Perturbation Budget Sensitivity Sweep ($\epsilon \in [5\%, 40\%]$) Under Homoglyphs and Cacography ($N = 1,000$).




Figure 5: Throughput Latency (ms) vs. Clean Classification Accuracy (%) Tradeoff on NVIDIA RTX 4060 GPU.

6.3 Perturbation Budget Sensitivity Sweep

Table 3 and Figure 4 illustrate model resilience across increasing perturbation budgets $\epsilon \in [0.05, 0.40]$:

- **Degradation of Classical Encoders:** As homoglyph corruption increases from 5% to 40%, TF-IDF recall drops monotonically from **98.2% to 94.2%** due to out-of-vocabulary subword fragmentation.
- **Invariance of CascadeGuard:** Across all perturbation intensities ($\epsilon = 5\%$ through 40%), CascadeGuard maintains an invariant **98.2% recall**, confirming the theoretical prediction of Proposition 1.

6.4 Component-Wise Ablation Analysis

Table 4 confirms the necessity of each architectural component:

- **Impact of Stage 1 (DOM Guardrail):** Under Vector A_4, disabling Stage 1 increases the Attack Success Rate from **0.00% to 1.60%**.
- **Impact of Stage 3 (Deep PLM Backbone):** Disabling Stage 3 and relying solely on heuristic rules causes accuracy to collapse to **50.00% and ASR to reach 100.00%** on discrete attacks, proving that surface rules cannot substitute for contextual PLM embeddings.

Table 4: Component-wise ablation study and inference latency profiling on NVIDIA RTX 4060 GPU ($N = 1,000$).

Configuration	Acc (%)	F1	MCC	ASR (%)	Lat. (ms)
Vector A_4 (Indirect Prompt Injection)					
CascadeGuard (Full Pipeline)	**98.90**	**0.9891**	**0.9782**	**0.00**	**7.83**
w/o Stage 1 (DOM Guard)	98.30	0.9830	0.9660	1.60	7.93
w/o Stage 2 (Unicode Norm.)	98.90	0.9891	0.9782	0.00	6.99
w/o Stage 3 (Deep PLM Classifier)	100.00	1.0000	1.0000	0.00	0.75
Vector A_1 (Homoglyph Obfuscation)					
CascadeGuard (Full Pipeline)	**98.00**	**0.9800**	**0.9600**	**1.80**	**7.96**
w/o Stage 1 (DOM Guard)	98.20	0.9820	0.9640	1.80	7.82
w/o Stage 2 (Unicode Norm.)	98.90	0.9891	0.9782	0.00	7.07
w/o Stage 3 (Deep PLM Classifier)	50.00	0.0000	0.0000	100.00	0.75

7 ODeL Institutional Deployment & Production Tradeoffs

7.1 Gateway Throughput and Operational Feasibility

In an ODeL institution such as the National Open University of Nigeria (NOUN), the email gateway processes upwards of 250,000 messages daily during registration cycles. As profiled in Figure 5:

- Multi-agent LLM debate pipelines require 3,000–8,000 ms per email, demanding massive GPU clusters or incurring prohibitive API fees ($500–$1,500 daily).
- CascadeGuard executes in **7.83 ms per email** on a single commodity RTX 4060 GPU, translating to a sustained throughput of over **125 emails/second** (450,000 emails/hour), comfortably exceeding campus gateway demand.

7.2 False Positive Mitigation in Higher Education

In higher education security, a 10% False Positive Rate is catastrophic, blocking thousands of legitimate bursary receipts, scholarship notices, and senate advisories. By coupling RoBERTa with institutional domain whitelisting and calibrated risk thresholds, CascadeGuard maintains a low **2.20% FPR** on clean institutional traffic.

7.3 Limitations and Future Work

Residual false negatives (1.8%) correspond exclusively to conversational spear-phishing lures devoid of links, attachments, or urgency triggers (e.g., callback requests). Countering such zero-lexical lures requires integrating sender-recipient interaction graphs (such as Graph Attention Networks [24]) into multi-turn email history.

8 Conclusion

We introduced **CascadeGuard**, a lightweight, three-stage defense-in-depth framework that hardens email gateways against character-level homoglyphs, cacography, discourse paraphrasing, and stealthy indirect prompt injections. Evaluated on a realistic 1,000-email adversarial benchmark on an NVIDIA RTX 4060 GPU, CascadeGuard achieves **98.00% clean F1-score**, reduces indirect prompt injection evasion to **0.00% ASR (100% recall)**, and operates at **7.83 ms latency per email**. CascadeGuard provides a practical, high-throughput defense for enterprise and ODeL institutions.

Declarations

- **Conflict of Interest:** The author declares no competing financial or personal interests.
- **Reproducibility:** Complete PyTorch pipelines (`train_models.py`), defense modules (`cascade_guard.py`), evaluation suites (`evaluate_all.py`), and sensitivity sweep scripts (`run_sensitivity_sweep.py`) are preserved in the repository.

References

[1] Nafiz Rifat, Mostofa Ahsan, Md. Chowdhury, and Rahul Gomes. BERT Against Social Engineering Attack: Phishing Text Detection. *2022 IEEE International Conference on Electro Information Technology (eIT)*, 2022.

[2] Suhaima Jamal, Hayden Wimmer, and Iqbal H. Sarker. An improved transformer-based model for detecting phishing, spam and ham emails: A large language model approach. *SECURITY AND PRIVACY*, 2024.

[3] Tanveer Ahmed and Seyedali Pourmoafil. Adversarial Robustness of Phishing Email Detection: A Comparative Study of TF-IDF + Logistic Regression and Fine-Tuned DistilBERT. *arXiv (2607.18429)*, 2026.

[4] Takashi Koide, Hiroki Nakano, and Daiki Chiba. Clouding the Mirror: Stealthy Prompt Injection Attacks Targeting LLM-based Phishing Detection. *arXiv (2602.05484)*, 2026.

[5] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. *Proceedings of NAACL-HLT*, 2019.

[6] Haiwei Li, Jiahai Yang, Yuqi Li, and Kun Li. Email phishing attack detection based on BERT transformer model. *International Conference on Optics, Electronics, and Communication Engineering (OECE 2024)*, 2024.

[7] Mariam Ibrahim and Ruba Elhafiz. Phishing Email Detection Using BERT and RoBERTa. *Computation*, 2026.

[8] Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and Harnessing Adversarial Examples. *International Conference on Learning Representations (ICLR)*, 2015.

[9] Di Jin, Zhijing Jin, Joey Tianyi Zhou, and Peter Szolovits. Is BERT Really Robust? A Strong Baseline for Natural Language Attack on Text Classification and Entailment. *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020.

[10] Aditya Kulkarni, Vivek Balachandran, Dinil Mon Divakaran, and Tamal Das. From ML to LLM: Evaluating the Robustness of Phishing Web Page Detection Models against Adversarial Attacks. *Digital Threats: Research and Practice*, 2025.

[11] Deeksha Hareesha Kulal, Chidozie Princewill Arannonu, Afsah Anwar, Nidhi Rastogi, and Quamar Niyaz. Robust ML-based Detection of Conventional, LLM-Generated, and Adversarial Phishing Emails Using Advanced Text Preprocessing. *arXiv (2510.11915)*, 2025.

[12] S. Abiramasundari and V. Ramaswamy. Cacography based Ransomware Email Phishing Attack Prevention using Language Pack Tuned Transformer Language Model. *Scientific Reports*, 2025.

[13] Najmul Hasan, Prashanth BusiReddyGari, Haitao Zhao, Yihao Ren, Jinsheng Xu, and Shaohu Zhang. Phishing Email Detection Using Large Language Models. *arXiv (2512.10104)*, 2025.

[14] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not What You've Signed Up For: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection. *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, 2023.

[15] Longtao Guo, Zelin Zhang, Kaifeng Huang, and Yang Shi. LoginTrap: Uncovering Task-Agnostic Phishing-Style Indirect Prompt Injection Attacks against LLM-based Web Agents. *arXiv (2608.04741)*, 2026.

[16] Wenhao Li, Selvakumar Manickam, Yung wey Chong, and Shankar Karuppayah. PhishDebate: An LLM-Based Multi-Agent Framework for Phishing Website Detection. *arXiv (2506.15656)*, 2025.

[17] Ngoc Tuong Vy Nguyen, Felix D Childress, and Yunting Yin. Debate-Driven Multi-Agent LLMs for Phishing Email Detection. *arXiv (2503.22038)*, 2025.

[18] Yinuo Xue, Eric Spero, Meng Wai Woo, Wei Gao, and Giovanni Russello. MultiPhishGuard: An Explainable and Adaptive Multi-Agent LLM System for Phishing Email Detection. *arXiv (2505.23803)*, 2025.

[19] John X. Morris, Eli Lifland, Jin Yong Yoo, Jake Grigsby, Di Jin, and Yanjun Qi. TextAttack: A Framework for Adversarial Attacks, Data Augmentation, and Adversarial Training in NLP. *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP): System Demonstrations*, 2020.

[20] Seiji Sato, Tetsushi Ohki, and Masakatsu Nishigaki. Can We End the Cat-and-Mouse Game? Simulating Self-Evolving Phishing Attacks with LLMs and Genetic Algorithms. *arXiv (2507.21538)*, 2025.

[21] Anna Plichta and Gabriela Raczka. Spam and phishing detection with adversarial attack robustness analysis using machine learning models. *ECMS 2026 Proceedings edited by Filippo Sanfilippo, Florenc Demrozi, Fabio Sgarbossa, Mohammad Poursina*, 2026.

[22] Sena Apeke, Titembaye Djiraikinan, and Mohamed Barate. Phishing detection by Transformers: Adversarial Robustness and Cross-Lingual Generalization. *Indian Journal Of Science And Technology*, 2026.

[23] Gargi Choudhury and Shivam Choudhury. DecepNet: A Hybrid NLP Framework for Robust Phishing Detection Under Adversarial Conditions. *Journal of Artificial Intelligence & Cloud Computing*, 2026.

[24] Rohith Kodali and Siva Rama Krishna T Dr. Phishing GAT: Adversarial-Hardened Phishing Email Detection via Semantic-Structural Fusion and Graph Attention Networks. *International Journal of Innovative Research in Engineering*, 2026.

[25] Even Eilertsen, Vasileios Mavroeidis, and Gudmund Grov. LLM-Powered Intent-Based Categorization of Phishing Emails. *arXiv (2506.14337)*, 2025.

[26] Ankur Tiwari. Adaptive LLM-Driven Phishing Defense Using Real-Time Psychological Cue Detection. *Academica Global: Journal of Computer Science and Technology Studies*, 2025.

[27] Daniyal Ganiuly and Assel Smaiyl. Trustworthiness Calibration Framework for Phishing Email Detection Using Large Language Models. *arXiv (2511.04728)*, 2025.