

PersonalAIz REST API

[Admin API](#)

[Personal API](#)

[Stereotype API](#)

[Community API](#)

[Recommendation Engine API](#)

[Security API](#)

Admin API

Add Client

Description:

Add a client in PersonalAlz platform.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/admin/client/{clientName}

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: clientName | The new client username

fp: password | The new client password

fp: info | A JSON with client information. e.g. {"mail":"info@mail.org","infoName":"infovalue"}

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/admin/client/panagiotis>

postParams("password", "123456789")

postParams("info", "{ 'mail': 'info@mail.com' }")

Example response:

{"outputMessage": "Add Client Complete"}

Delete Client

Description:

Delete a client from PersonalAlz platform.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/admin/client/delete/{clientName}

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: clientName | The client name that we want to delete.

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/admin/client/delete/panagiotis>

Example response:

```
{"outputMessage":"Delete Client Complete"}
```

Get Clients

Description:

Get a list with all clients in the PersonalAlz platform.

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuthe}/admin/clients

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/admin/clients>

Example response:

```
{"outputMessage":"Complete Get Clients", "output":["user1","user2",...]}
```

Set Settings

Description:

Set the settings in PersonalAlz platform

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/admin/settings

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

fp: settings | the settings to set in the platform. e.g. {'LogLevel':'info'}

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/admin/settings>

postParams("settings", '{"LogLevel":"info"}')

Example response:

```
{"outputMessage":"Set PServer settings complete"}
```

Set Setting

Description:

Set the setting in PersonalAlz platform

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/admin/setting

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

fp: name | the setting name e.g. LogLevel

fp: value | the settings value e.g. info

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/admin/setting>

postParams("name", "LogLevel")

postParams("value", "info")

Example response:

{"outputMessage": "Set PServer setting complete"}

Get Settings

Description:

Get platforms settings.

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuthe}/admin/settings

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/admin/settings>

Example response:

{"outputMessage": "Get PServer settings complete", "output": {"settingName": "value", ...}}

Personal API

Add User

Description:

Add user on PServer.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/personal/users

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

fp: JSONUsers | A json with a user object. e.g. {"panagiotis": {"features": {"category.sport": "3" }, "attributes": {"gender": "male", "age": "18"}}}

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/personal/users>

postParams("JSONUsers", {"panagiotis": {"features": {"category.sport": "3" }, "attributes": {"gender": "male", "age": "18"}}})

Example response:

{"outputMessage": "Add Users Complete"}

Delete User

Description:

Delete users from pserver based on given pattern. If pattern is null then delete all users.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/personal/users/delete

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

fp: pattern | The username pattern.

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/personal/users/delete>

postParams("pattern", null)

Example response:

```
{"outputMessage":"Delete Users Complete"}
```

Get Users

Description:

Get PServer users.

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuthe}/personal/users

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

fp: pattern | The username pattern. If null return all users.

fp: page | The number of the page. If null return all users in one page.

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/personal/users>

Example response:

```
{"outputMessage":"Get Users Complete","output":["username1",...]}
```

Get User Attributes

Description:

Get the user attributes for given username.

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuthe}/personal/users/{user}/attributes

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: user | The username.

fp: pattern | The attribute name pattern. If null return all user attributes.

fp: page | The number of the page. If null return all attributes in one page.

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/personal/users/panagiotis/attributes>

Example response:

```
{"outputMessage":"Complete Get User Attributes","output":[{"attrname":"attrValue",...}]}
```

Get User Profile

Description:

Get the user profile. User profile is a list of features with their values.

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuth}/personal/users/{user}/features

Parameters:

pp: userAuth | The system user authentication. With api key or username|password

pp: user | The username.

fp: pattern | The feature name pattern. If null return all user features.

fp: page | The number of the page. If null return all features in one page.

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/personal/users/panagiotis/features>

Example response:

```
{"outputMessage":"Complete Get User Profile","output":[{"ftrname":"ftralue",...}]}
```

Modify User Features

Description:

Modify user Features.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuth}/personal/users/{user}/features/modify

Parameters:

pp: userAuth | The system user authentication. With api key or username|password

pp: user | The username.

fp: JSONUserFeatures | A json with pairs of feature name - value. e.g. {"category.sport": "7"}
}

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/personal/users/panagiotis/features/modify>

putParams("JSONUserFeatures", "{ \"category.sport\": \"7\" }")

Example response:

{"outputMessage": "Modify User Features Complete"}

Set User Attributes

Description:

Set new value on user attributes.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/personal/users/{user}/attributes

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: user | The username.

fp: JSONUserAttributes | A json with pairs of attribute name - value. e.g. {"age": "17" }

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/personal/users/panagiotis/attributes>

putParams("JSONUserAttributes", "{ \"age\": \"17\" }")

Example response:

{"outputMessage": "Set User Attributes Complete"}

Set User Features

Description:

Set new value on user features.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/personal/users/{user}/features

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: user | The username.

fp: JSONUserFeatures | A json with pairs of feature name - value. e.g. {"category.sport": "7" }

Example:

<http://localhost:8080/PersonalAlz/pserver/root%7Croot/personal/users/panagiotis/features>
putParams("JSONUserFeatures", "{ \"category.sport\": \"7\" }")

Example response:

{"outputMessage": "Set User Features Complete"}

Stereotype API

Add Stereotype

Description:

Add new stereotype on PServer based on given rule.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuth}/stereotype/{stereotypeName}

Parameters:

pp: userAuth | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

fp: rule | The stereotype rule based on attributes. e.g. age<0|AND|gender:male

Example:

Example response:

Add User On Stereotype

Description:

Add a user manually on a existed stereotype.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuth}/stereotype/{stereotypeName}/user/add/{username}

Parameters:

pp: userAuth | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

pp: username | The username.

Example:

Example response:

Check Stereotype Users

Description:

Check all stereotype users and remove the users who not satisfies the stereotype rule.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/{stereotypeName}/users/check

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

Example:

Example response:

Delete Stereotype Features

Description:

Delete features from stereotype profile.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/{stereotypeName}/features/delete

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

fp: pattern | The stereotype feature pattern.

Example:

Example response:

Delete Stereotypes

Description:

Delete stereotypes based on given pattern. If no pattern den delete all stereotypes.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/delete

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

fp: pattern | The stereotype name pattern.

Example:

Example response:

Delete User From Stereotype

Description:

Remove manually a user from stereotype.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/{stereotypeName}/user/delete/{username}

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

pp: username | The username.

Example:

Example response:

Find Stereotype Users

Description:

Find and add new users in stereotype who satisfies the rule.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/{stereotypeName}/users/find

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

Example:

Example response:

Get Stereotype Features

Description:

Get stereotype profile. A list with pairs of feature name - value

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

fp: pattern | The feature name pattern. If null return all stereotype features.

fp: page | The number of the page. If null return all features in one page.

Example:

Example response:

Get Stereotype Users

Description:

Get a list with users that belongs to Stereotype.

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/{stereotypeName}/users

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.
fp: pattern | The username pattern. If null return all stereotype users.
fp: page | The number of the page. If null return all users in one page.

Example:

Example response:

Get Stereotypes

Description:

Get a list with stereotype names in PServer.

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password
fp: pattern | The stereotype name pattern. If null return all stereotype names.
fp: page | The number of the page. If null return all stereotype names in one page.

Example:

Example response:

Get System Attributes

Description:

Get the unique attribute names that exist in PServer.

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/attributes

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

Example:

Example response:

Get User Stereotypes

Description:

Get a list with stereotypes that a user belong.

Method:

GET

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/user/{usernameName}/stereotypes

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: usernameName | The username.

fp: pattern | The stereotype name pattern. If null return all stereotype names.

fp: page | The number of the page. If null return all stereotype names in one page.

Example:

Example response:

Modify Stereotype Features

Description:

Modify the values of stereotype features.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/{stereotypeName}/features/modify

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

fp: JSONStereotypeFeatures | The json of stereotype name - values. e.g.

{ "category.sport": "10" }

Example:

Example response:

Remake Stereotype

Description:

Remake the stereotype based on stored rule.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/{stereotypeName}/remake

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

Example:

Example response:

Set Stereotype Features

Description:

Set new values on stereotype features.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/{stereotypeName}/features/set

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

fp: JSONStereotypeFeatures | The json of stereotype name - values. e.g.

{ "category.sport": "10" }

Example:

Example response:

Update Stereotype Features

Description:

Re calculate all stereotype features based on users profile.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/{stereotypeName}/features/update

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

Example:

Example response:

Update Stereotype Users

Description:

Check and find users for the given stereotype name.

Method:

POST

URL:

PersonalAlz/api/pserver/{userAuthe}/stereotype/

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: stereotypeName | The stereotype name.

Example:

Example response:

Community API

Recommendation Engine API

Add User

Description:

Add a user in Recommendation Engine.

Method:

POST

URL:

PersonalAlz/api/recengine/{userAuthe}/user/{username}

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password.

pp: username | The application user username.

fp: JSONUser | The user attributes or information. e.g. {"attributes": {"gender": "male", "age": "25"}, "info": {"mail": "info@test.org"} }

Example:

<http://localhost:8080/PersonalAlz/api/recengine/root%7Croot/user/panagiotis>

postParams("JSONUser", {"attributes": {"gender": "male", "age": "25"} })

Example response:

{"outputMessage": "Add Users Complete"}

Delete User

Description:

Delete a user from Recommendation Engine.

Method:

POST

URL:

PersonalAlz/api/recengine/{userAuthe}/user/delete/{username}

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: username | The application user username.

Example:

<http://localhost:8080/PersonalAlz/api/recengine/root%7Croot/user/delete/panagiotis>

Example response:

```
{"outputMessage":"Delete Users Complete"}
```

Feed

Description:

Feed Recommendation Engine with user's preferences.

Method:

POST

URL:

PersonalAlz/api/recengine/{userAuthe}/feed/{username}

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: username | The application user username.

fp: JSONObject | The feed object that user click on it. e.g.

```
{
  "id": "1",
  "language": "en",
  "recommended": "true",
  "timestamp": "125455226",
  "text": [
    "text sample 1",
    "text sample 2"
  ],
  "category": [
    "category1"
  ],
  "tag": [
    "tag1",
    "tag2",
    "tag3"
  ],
  "boolean": [
    "boolean1name:value",
    "boolean2name:value",
    "boolean3name:value"
  ],
  "alphanumerics": [
    "alpha1name:value",
    "alpha2name:value",
    "alpha3name:value"
  ]
}
```

```

    ],
    "numeric": [
        "numeric1name:value",
        "numeric2name:value",
        "numeric3name:value"
    ]
}

```

Example:

<http://localhost:8080/PersonalAlz/api/recengine/root%7Croot/feed/panagiotis>

postParams("JSONObject", "{...}")

Example response:

Get Recommendation

Description:

Get a ranked list based on users profile.

Method:

POST

URL:

PersonalAlz/api/recengine/{userAuthe}/getRecommendation/{username}

Parameters:

pp: userAuthe | The system user authentication. With api key or username|password

pp: username | The application user username.

fp: JSONObjectList | The object list that we want to rank based on user. e.g.

```

[
{
    "id": "1",
    "language": "en",
    "text": [
        "text sample 1",
        "text sample 2"
    ],
    "category": [
        "category1"
    ],
    "tag": [
        "tag1",
        "tag2",
        "tag3"
    ],
    "boolean": [

```

```
        "boolean1name:value",
        "boolean2name:value",
        "boolean3name:value"
    ],
    "alphanumerics": [
        "alpha1name:value",
        "alpha2name:value",
        "alpha3name:value"
    ],
    "numeric": [
        "numeric1name:value",
        "numeric2name:value",
        "numeric3name:value"
    ]
},
{
    "id": "2",
    "language": "en",
    "text": [
        "text sample 1",
        "text sample 2"
    ],
    "category": [
        "category1"
    ],
    "tag": [
        "tag1",
        "tag2",
        "tag3"
    ],
    "boolean": [
        "boolean1name:value",
        "boolean2name:value",
        "boolean3name:value"
    ],
    "alphanumerics": [
        "alpha1name:value",
        "alpha2name:value",
        "alpha3name:value"
    ],
    "numeric": [
        "numeric1name:value",
        "numeric2name:value",
        "numeric3name:value"
    ]
}
```

]

Example:

<http://localhost:8080/PersonalAIz/api/recengine/root%7Croot/getRecommendation/panagioti>
[s](#)

postParams("JSONObjectList", "[{...},..., {...}]")

Example response:

{"outputMessage": "Get recommendation Complete", "output": {"objId": "score", ...}}

Security API

Check Credentials

Description:

Check the credentials username and password for a client.

Method:

POST

URL:

PersonalAlz/api/security/check/credentials

Parameters:

fp: username | The client username

fp: password | The client password

Example:

<http://localhost:8080/PersonalAlz/api/security/check/credentials>

```
postParams("username","root");
```

```
postParams("password","roeot");
```

Example response:

```
{"output":false}
```