

Quantum Variational Algorithms on Adiabatic Quantum Computing Devices

Philipp Hanussek

June 11, 2026

1 Motivation

Since the development of the quantum computers, many claims regarding quantum advantage have been made. Often, these advantage claims did not last long. In this work, we focus exclusively on the D-Wave Quantum Annealer, which leverages quantum technology to solve quadratically unconstrained binary optimization (QUBO) problems. D-Wave is among the first companies to commercially sell quantum computers. In 2025, researcher from D-Wave claimed to have solved a scientifically relevant problem fast using quantum technology, than it would have been possible on classical devices. However, it is currently an open question whether the D-Wave Quantum Annealer is able to solve other problems well, and possible faster than conventional computers. In this work, we assess the D-Wave's ability to sample from a probability distribution, to approximate the ground state of different statistical mechanical models using variational algorithms.

1.1 Previous Work

The D-Wave's Quantum Annealers performance scaling for finding the ground state (corresponding to the minimum of the quadratic binary cost function) has been extensively studied, with classical methods exhibiting better scaling and solution times. This has been done on a wide range of problems, ranging from cryptographic instances to physics inspired models.

2 Sampling Methods

In this section we briefly outline the main computational and algorithmic methods used in this work.

2.1 Adiabatic Quantum Computing

Adiabatic Quantum Computing is based on the adiabatic theorem, which states: *A physical system remains in its instantaneous eigenstate if a given perturbation is acting on it slowly enough and if there is a gap between the eigenvalue and the rest of the Hamiltonian's spectrum.* In this work we focus on the D-Wave Quantum Annealer, which acts according to the adiabatic theorem in the following way: In the beginning of the annealing process, the device is initiated in the ground state of a initial driver Hamiltonian H_D that can be easily constructed:

$$H_D = - \sum_{i=1}^N \sigma_x^{(i)} \text{ with ground state } |+\rangle^{\otimes N} \quad (1)$$

where σ_x , σ_y , and σ_z are the Pauli matrices acting on qubit i . The problem Hamiltonian is defined as

$$H_P = \sum_{i=1}^N h_i \sigma_z^{(i)} + \sum_{i,j=1}^N J_{ij} \sigma_z^i \otimes \sigma_z^j. \quad (2)$$

During the annealing process, the system is slowly brought from H_D to H_P according to the so-called annealing schedules $A(s)$ and $B(s)$:

$$H(s) = A(s)H_D + B(s)H_P = -A(s) \sum_{i=1}^N \sigma_x^{(i)} + B(s) \sum_{i=1}^N h_i \sigma_z^{(i)} + B(s) \sum_{i=1}^N \sum_{j=1}^{i-1} J_{ij} \sigma_z^{(i)} \otimes \sigma_z^{(j)}, \quad (3)$$

where $s \in [0, 1]$ is the normalized time. $A(s)$ decreases the driving terms in H_D as s increases, and $B(s)$ activates the terms of the problem Hamiltonian H_P . At the end of the evolution, if the process happens slow enough, and assuming a noiseless environment, the system will be in the ground state of the problem Hamiltonian according to the adiabatic theorem.

2.2 Simulated Annealing

Simulated Annealing is the classical analogue and predecessor of quantum annealing. It works by exploring the neighborhood of a given configuration, accepting the neighborhood with a temperature dependent probability, or if the new configuration has a lower energy than the current one.

2.3 Metropolis Algorithm

3 Variational Algorithms

Variational algorithms are a class of hybrid quantum-classical optimization methods. We focus on the Variational Quantum Eigensolver (VQE) which is designed to find the ground state of a given Hamiltonian. It consists of three parts: the *cost function* to be minimized, the *ansatz*, which in our case is a Boltzman machine, and an *expectation value estimation*. Additionally, a classical optimizer is needed to improve the ansatz at each iteration. Depending on the quantum architecture, two approaches for estimating the expectation value are possible:

- On gate-based quantum computers, measuring can be used to gather expectation values of the modified ansatz and improve it further
- In adiabatic quantum computing, the quantum device is used to generate representative samples of the modified ansatz. These samples are then used to approximate the expectation value.

Mathematically, the problem can be described as follows: The goal is to approximate the ground state, that is, the eigenstate corresponding to the lowest eigenvalue of a Hamiltonian H . In physics, a Hamiltonian is defined to be an operator that describes the energy of a system. Efficient methods exist to encode many classical problems, such as scheduling or integer factoring, into Hamiltonians. The ground state of this Hamiltonian is often used to represent the problem's solution. Calculating this solution analytically using for example exact diagonalisation is computationally difficult, as the Hilbert space grows exponentially with the size of the quantum state. In the adiabatic case, the ansatz can be written as

$$|\Phi\rangle = \sum_v \Phi(v) |v\rangle, \text{ with } \Phi(v) = \sum e^{-\Phi(v,h)} \quad (4)$$

The network is specified by the weights $\mathbf{a}, \mathbf{b}, \mathbf{W}$, which are respectively applied to the vector of visible units $\mathbf{v} = (v_1, \dots, v_N)$ and hidden units $\mathbf{h} = (h_1, \dots, h_N)$.