

Question 1. [6 MARKS]

Consider the following client code which produces the memory model shown below.


On the next page, write code for the three classes required by the client code. Do not write any docstrings, but you must include type annotations. There must be an inheritance relationship in your code, and the parent class does not have to be abstract.

```
if __name__ == '__main__':
```

```
    p = Plant(20, True)
```

```
    t = Tree(30, 10)
```


```
    f = Flower(5, 'pink', True)
```



In the space below, write your classes. You do not need to include docstrings.

Question 2. [7 MARKS]

Part (a) [5 MARKS] Consider the following code. Draw the contents of the call stack **immediately before** have_fun returns. Draw any objects as needed in the space below to complete the memory model. If any stack frames were popped before have_fun returns, cross them out to indicate that they were popped. We have executed the first line of code in the stack frame for __main__ to get you started, but you will have to draw the object with id148.








```
def d_fun(lst: list[int], v: int) -> None:
    z = v + 1
    lst.append(z)
```

```
def z_fun(d: list[int]) -> int:
    d_fun(d, 3)
    return d[-1]
```

```
def have_fun(lst: list[int]) -> int:
    rslt = z_fun(lst)
    return rslt
```

```
if __name__ == "__main__":
    a = [1, 2, 3]
    c = a[:]
    print(have_fun(a))
    print(c)
```



Part (b) [2 MARKS] In the space below, write what is printed when the code is executed.

Question 3. [6 MARKS]

Part (a) [1 MARK] Consider the `MyList` class below.

What is the name of the relationship between the `MyList` class and the `Queue` class? _____

Part (b) [5 MARKS] Implement the `remove` method according to its docstring. Do not make any assumptions about the behaviour of the `Queue` class other than that it has the API specified on the aid sheet. You may not define any other methods or functions. You may not use any builtin python lists, sets, tuples, or dictionaries — use `Stack` or `Queue` objects instead. Comments are not required but are encouraged.

```
class MyList:
    """A list implemented using a Queue.
       The item at index 0 in this MyList is stored at the front of _queue"""
    _queue: Queue

    def __init__(self) -> None:
        """ Initialize <self> to represent an empty list. """
        self._queue = Queue()

    def remove(self, item: Any) -> None:
        """Remove the first occurrence of <item> from this list.
        Raise a ValueError if <item> is not in this list."""
```

Question 4. [7 MARKS]


Consider the following docstring description of a new `LinkedList` method:

```
def expand_all_tuples(self) -> None:
    """Mutate <self> so that every tuple has been "expanded".
    Expanding a tuple of length n results in n-1 new nodes, each containing
    one item from the original tuple, in the original order. The original node
    contains the first item from the original tuple.

    Preconditions:
    - each tuple in self has length > 0

    >>> lst = LinkedList([('hi', 'there'), 42])
    >>> print(lst) # the original list
    ('hi', 'there') -> 42
    >>> lst.expand_all_tuples()
    >>> print(lst) # the mutated list after calling the method
    hi -> there -> 42
    """
```

Part (a) [2 MARKS] Modify the simplified `LinkedList` object diagram below to show how this `LinkedList` object will look after `expand_all_tuples` is executed. Hint: `self._first.item` will be mutated.



Part (b) [5 MARKS] Implement this method by filling in the blanks in the partially complete code below. You must not call any other `LinkedList` methods. Do not add any additional lines of code or remove any.

```
def expand_all_tuples(self) -> None:
    """Mutate <self> so that every tuple has been "expanded".
    Expanding a tuple of length n results in n-1 new nodes, each containing
    one item from the original tuple, in the original order. The original node
    contains the first item from the original tuple.

    Preconditions:
    - each tuple in self has length > 0"""

    cur = _____

    while _____: # traverse one node at a time

        if isinstance(_____, tuple): # check if we are at a tuple

            part = cur.item

            cur.item = part[0]

            part = part[1:]

            while len(part) > 0: # while the tuple still has items to expand

                node = _____ # create a new node object

                node.next, cur.next = _____ # link new node in

                cur = _____ # advance cur

                part = _____ # the rest of the tuple to expand

            _____
```

Use this page for rough work.

If you want the work on this page to be marked, indicate this clearly at the location of the original question.

Use this page for rough work.
If you want the work on this page to be marked, indicate this clearly at the location of the original question.