



SILESIA UNIVERSITY OF TECHNOLOGY
FACULTY OF ELECTRICAL ENGINEERING

Department of Power Electronics, Electrical Drives and Robotics

Master's thesis

To be determined

Student:	Igor Aleksander JANKIEWICZ
Transcript no.:	285947
Type of studies:	Extramural studies (MSc programme)
Field of study:	Electrical Engineering
Programme:	To be determined
Supervisor:	PhD. EEng. Andrzej Latko

Gliwice 2020

CONTENTS

1	Introduction	4
1.1	Motivation	4
1.2	Objective of a Master's thesis	4
2	Concept of Energy Harvesting	5
2.1	Piezoelectric material utilized in harvesters	5
2.2	Efficiency and power density	5
3	Measurement setup design	6
3.1	Design requirements	7
3.2	Accelerometer board	9
3.2.1	Most important parameters of the accelerometer	10
3.2.2	Selection of the integrated circuit	10
3.2.3	Accelerometer board design	11
3.3	Data acquisition board design	13
3.3.1	AC input section	13
	References	15

1 INTRODUCTION

This Master's thesis is focused on Piezoelectric Energy Harvesting in general. Apart from the explanation of the actual energy scavenging process, it also covers a design of a proper data acquisition system used for evaluation and development of piezoelectric-based generators.

1.1 Motivation

Nowadays, electrical energy itself is taken for granted by most of the people. It may be a result of the fact that most of household appliances and daily use items require that energy to operate. Moreover, almost any of our tasks require a proper illumination, Internet access or simply the outlet to live any tool we might need at the moment. To conclude, it is almost impossible to imagine our life without an access to the power grid.

On the other hand, it is important to keep in mind that most of electricity we utilize comes from non-renewable fuels such as coal, liquid gas or crude oil. At some point, humankind is to face a problem of insufficient deposits of these materials, therefore it tremendously important to look for alternatives. Of course, people have already taken advantage of water, wind or solar radiation, what is proven by the existence of many green power plants around the world. Unfortunately, one of the major problems faced by all of these plans is the intermittent access to the energy source. Moreover, there are many places that does not allow to use any of these well explored solutions, forcing engineers to look for new ones. This could be a reason why vibrational energy is getting more awareness over last years.

Energy harvesting from vibration gives many new possibilities, especially in IoT (Internet of Things) applications, as well as in industrial environment. The second application seems particularly tempting, as in many industrial applications, there is a lot of vibration involved, what gives a wide scope for custom sensor development. Piezoelectric harvesters are relatively compact, therefore it is possible to install them in inaccessible places. Moreover, they are robust, providing that a proper enclosure is used for mechanical protection.

All of mentioned factors gained author's interest, and in the event prompted to work on this subject within the confines of this thesis.

1.2 Objective of a Master's thesis

The main goal stated by the author is to examine a potential of vibration-based energy scavenging. In order to do so, number of different aspects need a thorough investigation. Undeniably, much of the focus would be put on the energy harvester itself. Nevertheless, a proper measurement and data acquisition system is also an important aspect throughout the entire work, since it will allow confirm or deny thesis statements posed during the research. In addition, the design process of the mentioned device would allow a more in-depth analysis of the piezoelectric generator itself, since the understanding of its operation is the only way to come up with a suitable measurement system.

Returning to the piezoelectric generator, the first thing to look at is the theory behind the piezoelectric effect. Then, there would be a description of the piezoelectric cantilever and its properties. Subsequently, the complete mechanical and electrical model would be studied.

Once the required theory is introduced, it is possible to focus exactly on the topic.

2 CONCEPT OF ENERGY HARVESTING

Energy Harvesting is a process of using ambient energy by converting it into a usable form, i.e. electricity or heat. It is important to point out that energy harvesting has been around for quite a long time, since solar panels, wind turbines and water turbines are in constant use for a few decades, providing people with environmentally clean energy [1].

There are some important issues related to any energy source that could be potentially used for harvesting. First of all, it is crucial to evaluate intensity and availability of that source. Subsequently, one should find out a cost-effectiveness of the solution as well as the influence of the harvesting process on the primary energy source [1].

Vibration-based Energy Harvesting incorporates a number of different fields of study, i.e. material science, mechanics or electrical engineering, just to name a few. Last sentence implies that the analysis of a piezoelectric generator itself is not a straightforward process. The electromechanical response of this device relies thoroughly on the source of ambient energy [2].

The concept of piezoelectric energy harvesting is strongly related to the improvement of electronics manufacturing technologies. Due to fact that most of devices are becoming more energy efficient, it allows to seek for potentially useful energy in solutions that have been neglected before. This perfectly applies to vibrational energy [3].

2.1 Piezoelectric material utilized in harvesters

Currently, the most popular material utilized in harvesters is so called PZT (lead zirconate titanate). It was developed at the Tokyo Institute of Technology in the 1950s [2]. Nowadays, it can be found in a few different flavours, what would be described more precisely later. This material is a polymer composite, which is very brittle and prone to crack when overstressed[4].

As described in the previous paragraph, PZT has a number of different types that vary with electrical and electromechanical properties. The simplest division includes hard and soft types - PZH-5H and PZH-5A, respectively. Soft piezoceramics are more susceptible to changes caused by the stress. This is one of the aspects why PZH-5H is the most common choice for piezoelectric equipment. On the other hand, one of the biggest manufacturers of harvesters [5] is mentioning that PZH-5A is more temperature stable. Nevertheless, PZH-5H remains the best choice in terms of performance versus price.

Properties of piezoelectric materials strongly depend on the direction of the stress and orientation of the polarization [1]. It is characterized by the constants listed in the Table

2.2 Efficiency and power density

Piezoelectric generator is truly a non-linear device. It produces maximum output power at its resonance frequency, which depends on a number of factors.

Power density of the harvesters is expressed as the output power divided by the device volume for the given input [2]. In case of vibrational energy, the input is the acceleration level and the frequency. An output of the piezoelectric generator provides voltage levels suitable for many electronics systems, therefore it is often unnecessary to add additional power electronics, what has an influence on efficiency.





Figure 2.1: Operation modes of the piezoelectric element



3 MEASUREMENT SETUP DESIGN

A proper measurement process is a crucial part of this project. Having said that, a custom data acquisition board is to be designed.

First of all, it is vital to highlight most important features required to achieve desired performance. There are four major aspects that have to be taken into account, namely, the ADC resolution as well as the input voltage range, the bandwidth and high input impedance of the analog front-end. Apart from that, one should take care of easy interfacing to personal computer, thus compact size and USB interface would be considered as huge assets.

The previous paragraph introduced briefly main functionalities of the target device. It is quite easy to notice that there would be a lot of trade-offs to consider through the design process. Compact size and the complex analog circuitry usually do not mix, especially when planning to get a device of USB mass storage size. These facts are forcing the designer to look for a microcontroller that provides decent ADCs, also in terms of the sampling rate. Since the project is dealing with piezoelectric generators, there is always a risk of relatively high voltages at the input terminals, especially when harvesters are not connected to any load. To face this problem, the data acquisition board would be equipped with two different means of protection. The first one takes care of the input stage of the device. The second one is a classic galvanic isolation between the microcontroller (as well as the analog front end) and the personal computer. This way, there is no risk of damaging host devices utilizing the data acquisition system. The summary of the above-mentioned description is presented in the Figure 3.1.

3 Measurement setup design

Table 2.1: Common data for some of Energy Harvesting Sources [1]

Type	Conditions	Power Density	Area or Volume	Energy/Day
Vibration	$1m/s^2$	$100\mu W/cm^3$	$1cm^2$	$8.64J$ (continuous vibration)
Solar	Outdoors	$7500\mu W/cm^2$	$1cm^2$	$324J$ (sunny half a day)
Solar	Indoors	$100\mu W/cm^2$	$1cm^2$	$4.32J$ (sunny half a day)
Thermal	$\Delta T = 5^\circ C$	$60\mu W/cm^2$	$1cm^2$	$2.59J$ (heat available for half a day)




Figure 3.1: Measurement setup overview

3.1 Design requirements

The first step of the design process is to determine desired input ratings as well as data acquisition capabilities. The piezoelectric device used in this project would be the major signal source during all experiments. Its datasheet [5] does not state any fixed maximum ratings. Instead, it provides exemplary results obtained by varying acceleration amplitude, frequency, tip mass and load resistance - see Table 3.1.

Table 3.1: Exemplary piezoelectric harvester response. Data from PPA-1001 datasheet [5]

Acceler. ampl. (g)	Freq. (Hz)	Tip mass ($gram$)	RMS power (mW)	RMS voltage (V)	RMS current (mA)	Load ($k\Omega$)
0.25	132	0.0	0.1	1.1	0.1	17.9
0.50	131	0.0	0.2	1.9	0.1	18.3
1.00	131	0.0	0.7	3.4	0.2	15.7
2.00	129	0.0	2.2	5.4	0.4	13.0
0.25	60	1.9	0.1	2.9	0.0	61.0
0.50	60	1.8	0.5	3.3	0.2	20.8
1.00	60	1.7	1.8	7.1	0.3	28.6
0.25	22	22.8	1.4	9.0	0.1	60.4
0.50	22	22.8	4.4	17.3	0.3	67.6

As mentioned in the previous paragraph, there is no constrained area in terms of vibration frequency and level stated by the manufacturer. Based on the data presented in the Table 3.1, the designer is relatively free to determine the operating frequency range as well as input signal range recorded at the harvester's output. When considering bandwidth and sampling rate, it is important to take into account the Nyquist criterion. It states that the sampling rate has to

be twice the highest frequency in the signal [6]. Assuming maximum vibration frequency of 500Hz, more than 1000 samples per second need to be captured.

Of course, this sampling rate only allows to reproduce an incoming signal (sinusoidal wave) as a corrupted triangle, since there is not enough data points to accurately reflect the sine shape. To solve this problem, the sampling rate should be increased by factor of 5 or so, what ultimately yields at least 5000 samples per second (sps). To illustrate the problem, Figure 3.2 is introduced. It can be easily seen that sampling rate as high as twice the input signal frequency is definitely not enough. Having said that, the minimum expected sampling rate is to be at least 5000 sps.




Figure 3.2: Captured waveform versus sampling rate

It is likely that the microcontroller used in the data logger would use some kind of a serial communication protocol. Assuming that more than one signal is recorded at the time and the baud rate is fixed at the same level, the maximum input signal frequency would be divided by the number of active channels. For example, for 2 channel measurement, the maximum input signal frequency is 250Hz and so on.

One of the previous paragraphs mentioned the piezoelectric harvester as the main input signal source. Knowing that the device produces a sinusoidal output, the analog front-end has to be able to capture AC signals, preferably of a relatively high amplitude. This requirements force the designer to develop symmetrical power supply for the input section as well as the circuitry allowing to add offset to the signal before it reaches the ADC input. A reason is that the ADC of the microcontroller is likely to accept only unipolar signals within tightly specified range. Remaining channels would be able to interface DC signals only, what makes them suitable for external sensors such as the accelerometer.

When considering the maximum input signal level, one has to note that it should not exceed supply voltage of operational amplifier used in the input section. In case of the designed device,

the power supply would be industrial $\pm 15VDC$, as it helps to maintain compatibility with wide range of available operational amplifiers. Based on the last sentence, the maximum input voltage is specified to $\pm 15V$ for the AC input and $+15V$ for DC inputs. In order to assure proper operating conditions for the analog-front end, an additional input protection is to be provided.

There are two last aspect that need some care. The first one is the resolution of the ADC that would be used to capture the incoming signal. The second one is the input impedance of input channels.

As to the first point, it is useful to have a look at technical details of commonly available oscilloscopes, since they can be treated as a nice reference. Most of them utilize 8 or 10-bit ADCs, mostly because of bandwidth requirements as well as the sampling time. In case of this design, the bandwidth is significantly reduced, what allows to look for a bit more resolution, of course still bearing in mind that all the processes are handled by one modest microcontroller. Putting it all together, an 14-bit ADC is going to be a desired data converter.

The last point relates to the impedance of analog inputs. Piezoelectric harvesters are high output impedance devices [1], therefore it is desirable to maintain as high input impedance of the analog front-end as possible, in order not to disturb the incoming signal. There are two potential problems that may occur when designing the input stage. As it can be guessed, the input signal has to be divided before it gets to the analog-to-digital converter. The easiest way to go is to put a voltage divider directly at the output of the harvester. Unfortunately, this circuit would have a significant influence on the impedance seen from piezo generator's output terminals, thus posing a risk of changing its operating conditions. To deal with this problem, the incoming signal is to be buffered before any further processing. This is where low input bias current operational amplifiers would come in handy. The second risk is related to the protection circuitry attached to input terminals. Once the input signal gets to high, it would be clamped in order to protect the data acquisition board. Unhappily, it would also disturb the measured object due to rapid change of the impedance seen at mentioned harvester's output terminals. The only way to deal with this issue is to provide relatively high supply voltage for buffering amplifiers and adjust the load as to meet the input voltage requirements.

As a summary of design considerations included in this subsection, Table 3.2 has been created.

Table 3.2: Summary of requirements for the data acquisition board

Requirement	Value
Max. input signal frequency (Sine)	500Hz
Min. sampling rate	5000sps
Min. ADC resolution	14-bit
Max. input voltage range (p-p)	15V
Input impeadnce	TBD

3.2 Accelerometer board

As it has been previously mentioned, is is necessary to constantly monitor vibration level during all the experiments. These measurements will be a reference for the results obtained using the piezoelectric harvester, as they easily allow to correlate generated power and current vibration level.

The piezoelectric beam used throughout the research is mounted in a 3D-printed holder provided by the device manufacturer. Apart from a proper fit, it allows to attach some external electronics by means using nice mounting holes. It is worth to take advantage of this feature, therefore designed electronics would be compatible with the handler.

3.2.1 *Most important parameters of the accelerometer*

As to the electrical and electromechanical properties of the accelerometer, there are a few aspects that should be highlighted. The first one is the measurement range. By checking the maximum acceleration of the beam, it is possible to estimate required range for the sought integrated circuit. Next, the frequency response and output signal type need to be determined. Frequency response describes the measurement resolution that could be understood as the smallest detectable acceleration [7]. By mentioning the type of the output signal, it was intended to distinguish between analog and digital output types. It is planned to synchronize the accelerometer output with the piezoelectric cantilever response, so the analog output is more suitable and easier to use.

Harvester's datasheet [5] does not mention the exact upper limit of allowed vibration level. According to the Table 3.1, the maximum acceleration amplitude mentioned by the manufacturer is 2g. Without any additional information, it is reasonable to treat this value as the upper acceleration limit. The same applies to the frequency response, which is also not described precisely. Again, Table 3.1 states the maximum operation frequency at the level of 132Hz. In this case, the minimum acceptable bandwidth of the accelerometer would be roughly 200Hz. As it was mentioned in the previous paragraph, it is intended to use the analog output accelerometer. A summary of the above-mentioned choices is presented in the Table 3.3.

Table 3.3: Summary of requirements for the accelerometer

Requirement	Value
Max. acceleration value	$\pm 2g$
Max. operating frequency	300Hz
Output type	Analog

3.2.2 *Selection of the integrated circuit*

After a thorough market research, a proper device has been found - see Table 3.4. Apart from parameters listed in the table, the selected accelerometer has the following features: small SMD package, 3.3V supply operation, low power consumption and tunable bandwidth filters for every axis. Moreover, it exhibits non-linearity at a level of 0.3% [8].

Table 3.4: Parameters of the selected parameter - taken from the datasheet [8]

Parameter	Value
Model	ADXL335
Manufacturer	Analog devices
Output type	Analog
Max. acceleration value	$\pm 3g$
Bandwidth	up to 1600Hz

As it can be seen, the above-mentioned device fulfils the requirements presented in the previous subsection. At this point, it is necessary to think about additional circuitry allowing to take advantage of the selected integrated circuit. In order to do so, a small PCB is to be designed.

3.2.3 Accelerometer board design

The accelerometer board should be a battery powered device, as it is going to be used throughout tests in different types of environment, many times without an access to any power supply. Moreover, battery operation allows for a better performance in terms of noise generated on supply rails. Additionally, the board is ought to be equipped with a temperature sensor, in case some tests are to be performed in extreme temperatures and the exact temperature value is needed to know.

Figure 3.3 presents the diagram of designed board. It can be divided into two main parts, namely a power supply with a battery charger and a sensing part including the accelerometer and the temperature sensor.




Figure 3.3: Accelerometer board diagram

As to the power supply part, for the convenience, the entire board is powered using a micro USB port, which is fused for safety purposes. Right after the input, there is a single cell battery charger (BRCL4054CME by Blue Rocket Electronics [9]). Charging current is set using just one resistor. Moreover, it incorporates such functions as C/10 charge termination, a soft-start feature as well as an open-drain output used for signalling purposes.

Power storage is maintained by means of a 110mAh lithium-polymer battery (LIPO511422 by MAXPOWER). It is equipped with a complete protection circuitry, so it is unnecessary to include additional protection on the accelerometer board. The battery manufacturer claims the cycle life of 1000 cycles.

Right after the ON/OFF switch, there is a low dropout linear regulator supplying the rest of the circuits (AP2112K-3.3TRG1 by Diodes Incorporated [10]). It is a 600mA output, low noise regulator with $\pm 1\%$ output voltage accuracy.




Figure 3.4: Accelerometer board top side view




Figure 3.5: Accelerometer board bottom side view

One of the sensors placed on this board is the accelerometer mentioned in the previous section. The second one is a low-power linear temperature sensor (MCP9700T-E/TT by Microchip [11]). Since the linear output is one of the requirements for all sensors used in this project, this kind of device was an easy choice. MCP9700 includes circuitry converting temperature to voltage and provides accuracy of $\pm 2^\circ\text{C}$, which is by all means acceptable for this application.

Figures 3.4 and 3.5 present the final design. As it can be seen, a relatively compact and intuitive device has been developed. A standard connector with 2.54mm pitch is used to allow easy access to the board. There are two reinforced holes for mounting screws. The bottom side of the PCB includes large pads allowing to solder cables connected to piezoelectric beam terminals in order to make the construction more robust.

This board is going to be an inherent part of most experiments performed throughout this thesis.

3.3 Data acquisition board design

3.3.1 AC input section

The data acquisition board is going to be equipped with one AC-tolerant input channel. This feature will be helpful in cases when piezoelectric beam is loaded only with a resistive load, hence there is no rectification action present. In order not to damage the microprocessor and other circuitry that is powered from a single supply, some signal conditioning is required.

Input protection

An important aspect (often overlooked though) is proper input protection for analog circuitry. At this point it is important to highlight that signal conditioning would be based on a variety of different operational amplifiers. Having said that, one should consider problems related to these devices as well as the influence of protection circuit on measurement results.

One of most popular means of protection for op-amps are clamping diodes along with current limiting resistors. Nowadays, popular operational amplifiers incorporate ESD protection diodes into their input circuitry, which is surely very helpful in most cases, nevertheless it can be a source of potential problems. These diodes are clamped to supply rails in order to provide return path for currents generated by ESD-related events. These happen once the input voltage gets higher than supply rail voltage plus voltage drop (usually around 0.7V) or lower than negative rail voltage minus the diode voltage drop, respectively [12]. In normal conditions these diodes remain transparent.

It is important to remember that the clamping circuit is going to have an influence on measurement results if designed improperly. Now, it is time to recall a very important parameter related to inputs of the operational amplifier, namely the input bias current, which is inherently related to any "real" (and non-ideal) Op Amp. It's value is going to have a direct influence on the clamping circuit design, what would be explained in a more detailed manner soon.




Figure 3.6: Clamping overvoltage protection scheme

The input bias current is a DC current required by the Op Amp's inputs to establish proper biasing of input stage transistors [13]. It ranges from a few microamps to a few picoamps. This current is going to flow through the input protection resistor, generating a voltage drop proportional to mentioned current value multiplied by the series resistance.

Another unwanted, but also unavoidable error source is reverse leakage current of clamping diodes. This voltage drop is going to generate the output error as in the Equation 3.1.

$$V_{error} = (R_{ser} \times (I_{bias} + 2 \times I_{leak})) \times Gain \quad (3.1)$$

The outline of the AC channel is presented in the Figure 3.6.

REFERENCES

- [1] N. W. Stephen Beeby, *Energy Harvesting for Autonomous Systems*. Artech House, 2010. ISBN: 978-1-59693-718-5.
- [2] D. J. I. Alper Erturk, *Piezoelectric Energy Harvesting*. John Wiley & Sons, Ltd, 2011. ISBN: 978-0-470-68254-8.
- [3] C. Tian, “Energy harvesting from low frequency applications using piezoelectric, materials,” 01 2019.
- [4] Y. M. Thorsten Hehn, *CMOS Circuits for Piezoelectric Energy Harvesters*. Springer Science+Business Media Dordrecht, 2015. ISBN: 978-94-017-9288-2.
- [5] Midé Technology, *PPA Products. Datasheet and User Manual*, 2016. Revision No. 002.
- [6] J. Louis E. Frenzel, *Electronics Explained*. Newnes (Elsevier Inc.), 2010. ISBN: 978-1-85617-700-9.
- [7] STMicroelectronics group, *AN4508 Application note. Parameters and calibration of a low-g 3-axis accelerometer.*, 2014. Revision No. 001.
- [8] Analog Devices Inc., *ADXL335 datasheet*, 2009. Revision No. 000.
- [9] Foshan Blue Rocket Electronics, *BRCL4054CME datasheet*, 2018. Revision B.
- [10] Diodes Incorporated, *AP2112 datasheet. Documnet number: DS39724*, June 2017. Revision no.2-2.
- [11] Microchip Technology Inc., *MCP9700 datasheet*, July 2017. Revision F.
- [12] D. Burton, “Op amp input overvoltage protection: Clamping vs. integrated,” 05 2016.
- [13] T. Willams, *Circuit Designer’S Companion*. Newnes (An imprint of Butterworth-Heinemann), 1993. ISBN: 978-0750617567.