

Package ‘fitAutoReg’

September 4, 2023

Title Fit Autoregressive Models

Version 0.9.1

Description Fit autoregressive models using 'RcppArmadillo'.

URL <https://github.com/ijapesigan/fitAutoReg>,
<https://ijapesigan.github.io/fitAutoReg/>

BugReports <https://github.com/ijapesigan/fitAutoReg/issues>

License GPL (>= 3)

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Depends R (>= 3.5.0)

LinkingTo Rcpp, RcppArmadillo

Imports Rcpp

Suggests knitr, rmarkdown, testthat, MASS

RoxygenNote 7.2.3

NeedsCompilation yes

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<https://orcid.org/0000-0003-4818-8420>)

Maintainer Ivan Jacob Agaloos Pesigan <r.ijapesigan@gmail.com>

R topics documented:

BootCI	2
BootSE	4
dat_ml_p1	5
dat_ml_p2	6
dat_p1	7
dat_p1_yx	8

dat_p2	8
dat_p2_exo	9
dat_p2_exo_yx	9
dat_p2_yx	10
FitVARLasso	10
FitVARLassoSearch	12
FitVAROLS	13
LambdaSeq	14
OrigScale	15
PBootVARExoLasso	16
PBootVARExoOLS	17
PBootVARLasso	18
PBootVAROLS	20
RBootVARExoLasso	21
RBootVARExoOLS	22
RBootVARLasso	23
RBootVAROLS	24
SearchVARLasso	25
SelectVARLasso	27
SimVAR	28
SimVARExo	30
StdMat	31
YX	32
YXExo	34
Index	37

BootCI	<i>Bootstrap Percentile Confidence Intervals</i>
--------	--

Description

Bootstrap Percentile Confidence Intervals

Usage

BootCI(x, alpha = 0.05)

Arguments

x	Numeric matrix. Output of <code>PBootVAROLS()</code> , <code>PBootVARLasso()</code> , <code>RBootVAROLS()</code> , or <code>RBootVARLasso()</code> .
alpha	Numeric. Significance level.

Value

A list with two elements, namely `ll` for the lower limit and `ul` for the upper limit.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Simulation of Autoregressive Data Functions: [BootSE\(\)](#), [SelectVARLasso\(\)](#), [SimVARExo\(\)](#), [SimVAR\(\)](#), [YXExo\(\)](#), [YX\(\)](#)

Examples

```
set.seed(42)
# Parametric bootstrap
system.time(
  pb <- PBootVAROLS(
    data = dat_p2,
    p = 2,
    B = 5,
    burn_in = 20
  )
)
pb$est
BootCI(pb)
system.time(
  pb <- PBootVARLasso(
    data = dat_p2,
    p = 2,
    B = 5,
    burn_in = 20,
    n_lambdas = 50,
    crit = "ebic",
    max_iter = 1000,
    tol = 1e-5
  )
)
pb$est
BootCI(pb)

# Residual bootstrap
system.time(
  rb <- RBootVAROLS(
    data = dat_p2,
    p = 2,
    B = 5
  )
)
rb$est
BootCI(rb)
system.time(
  rb <- RBootVARLasso(
    data = dat_p2,
    p = 2,
    B = 5,
```

```

      n_lambdas = 50,
      crit = "ebic",
      max_iter = 1000,
      tol = 1e-5
    )
  )
  rb$est
  BootCI(rb)

```

 BootSE

Bootstrap Standard Errors

Description

Bootstrap Standard Errors

Usage

BootSE(x)

Arguments

x Numeric matrix. Output of [PBootVAROLS\(\)](#), [PBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), or [RBootVARLasso\(\)](#).

Value

A matrix of standard errors.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Simulation of Autoregressive Data Functions: [BootCI\(\)](#), [SelectVARLasso\(\)](#), [SimVARExo\(\)](#), [SimVAR\(\)](#), [YXExo\(\)](#), [YX\(\)](#)

Examples

```

set.seed(42)
# Parametric bootstrap
system.time(
  pb <- PBootVAROLS(
    data = dat_p2,
    p = 2,
    B = 5,
    burn_in = 20
  )
)

```

```

    )
  )
  pb$est
  BootSE(pb)
  system.time(
    pb <- PBootVARLasso(
      data = dat_p2,
      p = 2,
      B = 5,
      burn_in = 20,
      n_lambdas = 50,
      crit = "ebic",
      max_iter = 1000,
      tol = 1e-5
    )
  )
  pb$est
  BootSE(pb)

# Residual bootstrap
system.time(
  rb <- RBootVAROLS(
    data = dat_p2,
    p = 2,
    B = 5
  )
)
rb$est
BootSE(rb)
system.time(
  rb <- RBootVARLasso(
    data = dat_p2,
    p = 2,
    B = 5,
    n_lambdas = 50,
    crit = "ebic",
    max_iter = 1000,
    tol = 1e-5
  )
)
rb$est
BootSE(rb)

```

dat_ml_p1

Data from the Multilevel Vector Autoregressive Model ($p = 1$)

Description

Data from the Multilevel Vector Autoregressive Model ($p = 1$)

Usage

dat_ml_p1

Format

A list of length $n = 100$ consisting of matrices with 1000 rows (time points) and $k = 3$ columns (variables) generated from the $p = 1$ multilevel vector autoregressive model given by

$$Y_{1_t} = 1 + \mathcal{N}(\mu = 0.4, \sigma^2 = 0.01) Y_{1_{t-1}} + 0.0Y_{2_{t-1}} + 0.0Y_{3_{t-1}} + \varepsilon_{1_t},$$

$$Y_{2_t} = 1 + 0.0Y_{1_{t-1}} + \mathcal{N}(\mu = 0.5, \sigma^2 = 0.01) Y_{2_{t-1}} + 0.0Y_{3_{t-1}} + \varepsilon_{2_t},$$

and

$$Y_{3_t} = 1 + 0.0Y_{1_{t-1}} + 0.0Y_{2_{t-1}} + \mathcal{N}(\mu = 0.6, \sigma^2 = 0.01) Y_{3_{t-1}} + \varepsilon_{3_t}$$

which simplifies to

$$Y_{1_t} = 1 + \mathcal{N}(\mu = 0.4, \sigma^2 = 0.01) Y_{1_{t-1}} + \varepsilon_{1_t},$$

$$Y_{2_t} = 1 + \mathcal{N}(\mu = 0.5, \sigma^2 = 0.01) Y_{2_{t-1}} + \varepsilon_{2_t},$$

and

$$Y_{3_t} = 1 + \mathcal{N}(\mu = 0.6, \sigma^2 = 0.01) Y_{3_{t-1}} + \varepsilon_{3_t}.$$

The covariance matrix of process noise is an identity matrix.

dat_ml_p2

Data from the Multilevel Vector Autoregressive Model ($p = 2$)

Description

Data from the Multilevel Vector Autoregressive Model ($p = 2$)

Usage

dat_ml_p2

Format

A list of length $n = 100$ consisting of matrices with 1000 rows (time points) and $k = 3$ columns (variables) generated from the $p = 2$ multilevel vector autoregressive model given by

$$Y_{1_t} = 1 + \mathcal{N}(\mu = 0.4, \sigma^2 = 0.01) Y_{1_{t-1}} + 0.0Y_{2_{t-1}} + 0.0Y_{3_{t-1}} + \mathcal{N}(\mu = 0.1, \sigma^2 = 0.01) Y_{1_{t-2}} + 0.0Y_{2_{t-2}} + 0.0Y_{3_{t-2}} + \varepsilon_{1_t},$$

$$Y_{2_t} = 1 + 0.0Y_{1_{t-1}} + \mathcal{N}(\mu = 0.5, \sigma^2 = 0.01) Y_{2_{t-1}} + 0.0Y_{3_{t-1}} + 0.0Y_{1_{t-2}} + \mathcal{N}(\mu = 0.2, \sigma^2 = 0.01) Y_{2_{t-2}} + 0.0Y_{3_{t-2}} + \varepsilon_{2_t},$$

and

$$Y_{3_t} = 1 + 0.0Y_{1_{t-1}} + 0.0Y_{2_{t-1}} + \mathcal{N}(\mu = 0.6, \sigma^2 = 0.01) Y_{3_{t-1}} + 0.0Y_{1_{t-2}} + 0.0Y_{2_{t-2}} + \mathcal{N}(\mu = 0.3, \sigma^2 = 0.01) Y_{3_{t-2}} + \varepsilon_{3_t}$$

which simplifies to

$$Y_{1_t} = 1 + \mathcal{N}(\mu = 0.4, \sigma^2 = 0.01) Y_{1_{t-1}} + \mathcal{N}(\mu = 0.1, \sigma^2 = 0.01) Y_{1_{t-2}} + \varepsilon_{1_t},$$

$$Y_{2_t} = 1 + \mathcal{N}(\mu = 0.5, \sigma^2 = 0.01) Y_{2_{t-1}} + \mathcal{N}(\mu = 0.2, \sigma^2 = 0.01) Y_{2_{t-2}} + \varepsilon_{2_t},$$

and

$$Y_{3_t} = 1 + \mathcal{N}(\mu = 0.6, \sigma^2 = 0.01) Y_{3_{t-1}} + \mathcal{N}(\mu = 0.3, \sigma^2 = 0.01) Y_{3_{t-2}} + \varepsilon_{3_t}.$$

The covariance matrix of process noise is an identity matrix.

dat_p1

Data from the Vector Autoregressive Model (p = 1)

Description

Data from the Vector Autoregressive Model (p = 1)

Usage

dat_p1

Format

A matrix with 1000 rows (time points) and k = 3 columns (variables) generated from the p = 1 vector autoregressive model given by

$$Y_{1_t} = 1 + 0.4Y_{1_{t-1}} + 0.0Y_{2_{t-1}} + 0.0Y_{3_{t-1}} + \varepsilon_{1_t},$$

$$Y_{2_t} = 1 + 0.0Y_{1_{t-1}} + 0.5Y_{2_{t-1}} + 0.0Y_{3_{t-1}} + \varepsilon_{2_t},$$

and

$$Y_{3_t} = 1 + 0.0Y_{1_{t-1}} + 0.0Y_{2_{t-1}} + 0.6Y_{3_{t-1}} + \varepsilon_{3_t}$$

which simplifies to

$$Y_{1_t} = 1 + 0.4Y_{1_{t-1}} + \varepsilon_{1_t},$$

$$Y_{2_t} = 1 + 0.5Y_{2_{t-1}} + \varepsilon_{2_t},$$

and

$$Y_{3_t} = 1 + 0.6Y_{3_{t-1}} + \varepsilon_{3_t}.$$

The covariance matrix of process noise is an identity matrix.

dat_p1_yx	<i>Data from the Vector Autoregressive Model (Y) and Lagged Predictors (X) (p = 1)</i>
-----------	--

Description

Data from the Vector Autoregressive Model (Y) and Lagged Predictors (X) (p = 1)

Usage

dat_p1_yx

Format

A list with elements Y and X where Y is equal to the dat_p1 data set minus p = 1 terminal rows and X is a matrix of ones for the first column and lagged values of Y for the rest of the columns.

dat_p2	<i>Data from the Vector Autoregressive Model (p = 2)</i>
--------	--

Description

Data from the Vector Autoregressive Model (p = 2)

Usage

dat_p2

Format

A matrix with 1000 rows (time points) and k = 3 columns (variables) generated from the p = 2 vector autoregressive model given by

$$Y_{1t} = 1 + 0.4Y_{1t-1} + 0.0Y_{2t-1} + 0.0Y_{3t-1} + 0.1Y_{1t-2} + 0.0Y_{2t-2} + 0.0Y_{3t-2} + \varepsilon_{1t},$$

$$Y_{2t} = 1 + 0.0Y_{1t-1} + 0.5Y_{2t-1} + 0.0Y_{3t-1} + 0.0Y_{1t-2} + 0.2Y_{2t-2} + 0.0Y_{3t-2} + \varepsilon_{2t},$$

and

$$Y_{3t} = 1 + 0.0Y_{1t-1} + 0.0Y_{2t-1} + 0.6Y_{3t-1} + 0.0Y_{1t-2} + 0.0Y_{2t-2} + 0.3Y_{3t-2} + \varepsilon_{3t}$$

which simplifies to

$$Y_{1t} = 1 + 0.4Y_{1t-1} + 0.1Y_{1t-2} + \varepsilon_{1t},$$

$$Y_{2t} = 1 + 0.5Y_{2t-1} + 0.2Y_{2t-2} + \varepsilon_{2t},$$

and

$$Y_{3t} = 1 + 0.6Y_{3t-1} + 0.3Y_{3t-2} + \varepsilon_{3t}.$$

The covariance matrix of process noise is an identity matrix.

dat_p2_exo	<i>Data from the Vector Autoregressive Model with Exogenous Variables (p = 2)</i>
------------	---

Description

Data from the Vector Autoregressive Model with Exogenous Variables (p = 2)

Usage

dat_p2_exo

Format

A matrix with 1000 rows (time points) and k = 3 (autoregressive variables) plus m = 3 columns (exogenous variables) generated from the p = 2 vector autoregressive model given by

$$Y_{1t} = 1 + 0.4Y_{1t-1} + 0.0Y_{2t-1} + 0.0Y_{3t-1} + 0.1Y_{1t-2} + 0.0Y_{2t-2} + 0.0Y_{3t-2} + 0.5X_1 + 0.0X_2 + 0.0X_3\varepsilon_{1t},$$

$$Y_{2t} = 1 + 0.0Y_{1t-1} + 0.5Y_{2t-1} + 0.0Y_{3t-1} + 0.0Y_{1t-2} + 0.2Y_{2t-2} + 0.0Y_{3t-2} + 0.0X_1 + 0.5X_2 + 0.0X_3\varepsilon_{2t},$$

and

$$Y_{3t} = 1 + 0.0Y_{1t-1} + 0.0Y_{2t-1} + 0.6Y_{3t-1} + 0.0Y_{1t-2} + 0.0Y_{2t-2} + 0.3Y_{3t-2} + 0.0X_1 + 0.0X_2 + 0.5X_3\varepsilon_{3t}$$

which simplifies to

$$Y_{1t} = 1 + 0.4Y_{1t-1} + 0.1Y_{1t-2} + 0.5X_1\varepsilon_{1t},$$

$$Y_{2t} = 1 + 0.5Y_{2t-1} + 0.2Y_{2t-2} + 0.5X_2\varepsilon_{2t},$$

and

$$Y_{3t} = 1 + 0.6Y_{3t-1} + 0.3Y_{3t-2} + 0.5X_3\varepsilon_{3t}.$$

The covariance matrix of process noise is an identity matrix.

dat_p2_exo_yx	<i>Data from the Vector Autoregressive Model (Y) and Lagged Predictors and Exogenous Variables (X) (p = 2)</i>
---------------	--

Description

Data from the Vector Autoregressive Model (Y) and Lagged Predictors and Exogenous Variables (X) (p = 2)

Usage

dat_p2_exo_yx

Format

A list with elements Y and X where Y is equal to the $k = 3$ autoregressive variables of the `dat_p2_exo` data set minus $p = 2$ terminal rows and X is a matrix of ones for the first column, lagged values of Y, and $m = 3$ exogenous variables.

<code>dat_p2_yx</code>	<i>Data from the Vector Autoregressive Model (Y) and Lagged Predictors (X) ($p = 2$)</i>
------------------------	---

Description

Data from the Vector Autoregressive Model (Y) and Lagged Predictors (X) ($p = 2$)

Usage

`dat_p2_yx`

Format

A list with elements Y and X where Y is equal to the `dat_p2` data set minus $p = 2$ terminal rows and X is a matrix of ones for the first column and lagged values of Y for the rest of the columns.

<code>FitVARLasso</code>	<i>Fit Vector Autoregressive (VAR) Model Parameters using Lasso Regularization</i>
--------------------------	--

Description

This function estimates the parameters of a VAR model using the Lasso regularization method with cyclical coordinate descent. The Lasso method is used to estimate the autoregressive and cross-regression coefficients with sparsity.

Usage

`FitVARLasso(YStd, XStd, lambda, max_iter, tol)`

Arguments

<code>YStd</code>	Numeric matrix. Matrix of standardized dependent variables (Y).
<code>XStd</code>	Numeric matrix. Matrix of standardized predictors (X). <code>XStd</code> should not include a vector of ones in column one.
<code>lambda</code>	Numeric. Lasso hyperparameter. The regularization strength controlling the sparsity.
<code>max_iter</code>	Integer. The maximum number of iterations for the coordinate descent algorithm (e.g., <code>max_iter = 10000</code>).
<code>tol</code>	Numeric. Convergence tolerance. The algorithm stops when the change in coefficients between iterations is below this tolerance (e.g., <code>tol = 1e-5</code>).

Details

The `FitVARLasso()` function estimates the parameters of a Vector Autoregressive (VAR) model using the Lasso regularization method. Given the input matrices `YStd` and `XStd`, where `YStd` is the matrix of standardized dependent variables, and `XStd` is the matrix of standardized predictors, the function computes the autoregressive and cross-regression coefficients of the VAR model with sparsity induced by the Lasso regularization.

The steps involved in estimating the VAR model parameters using Lasso are as follows:

- **Initialization:** The function initializes the coefficient matrix `beta` with OLS estimates. The `beta` matrix will store the estimated autoregressive and cross-regression coefficients.
- **Coordinate Descent Loop:** The function performs the cyclical coordinate descent algorithm to estimate the coefficients iteratively. The loop iterates `max_iter` times, or until convergence is achieved. The outer loop iterates over the predictor variables (columns of `XStd`), while the inner loop iterates over the outcome variables (columns of `YStd`).
- **Coefficient Update:** For each predictor variable (column of `XStd`), the function iteratively updates the corresponding column of `beta` using the coordinate descent algorithm with L1 norm regularization (Lasso). The update involves calculating the soft-thresholded value `c`, which encourages sparsity in the coefficients. The algorithm continues until the change in coefficients between iterations is below the specified tolerance `tol` or when the maximum number of iterations is reached.
- **Convergence Check:** The function checks for convergence by comparing the current `beta` matrix with the previous iteration's `beta_old`. If the maximum absolute difference between `beta` and `beta_old` is below the tolerance `tol`, the algorithm is considered converged, and the loop exits.

Value

Matrix of estimated autoregressive and cross-regression coefficients.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: `FitVARLassoSearch()`, `FitVAROLS()`, `LambdaSeq()`, `OrigScale()`, `PBootVARExoLasso()`, `PBootVARExoOLS()`, `PBootVARLasso()`, `PBootVAROLS()`, `RBootVARExoLasso()`, `RBootVARExoOLS()`, `RBootVARLasso()`, `RBootVAROLS()`, `SearchVARLasso()`, `StdMat()`

Examples

```
YStd <- StdMat(dat_p2_yx$Y)
XStd <- StdMat(dat_p2_yx$X[, -1]) # remove the constant column
lambda <- 73.90722
FitVARLasso(
  YStd = YStd,
  XStd = XStd,
  lambda = lambda,
```

```
max_iter = 10000,  
tol = 1e-5  
)
```

FitVARLassoSearch	<i>Fit Vector Autoregressive (VAR) Model Parameters using Lasso Regularization with Lambda Search</i>
-------------------	---

Description

Fit Vector Autoregressive (VAR) Model Parameters using Lasso Regularization with Lambda Search

Usage

```
FitVARLassoSearch(YStd, XStd, lambdas, crit, max_iter, tol)
```

Arguments

YStd	Numeric matrix. Matrix of standardized dependent variables (Y).
XStd	Numeric matrix. Matrix of standardized predictors (X). XStd should not include a vector of ones in column one.
lambdas	Numeric vector. Lasso hyperparameter. The regularization strength controlling the sparsity.
crit	Character string. Information criteria to use. Valid values include "aic", "bic", and "ebic".
max_iter	Integer. The maximum number of iterations for the coordinate descent algorithm (e.g., max_iter = 10000).
tol	Numeric. Convergence tolerance. The algorithm stops when the change in coefficients between iterations is below this tolerance (e.g., tol = 1e-5).

Value

Matrix of estimated autoregressive and cross-regression coefficients.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```

YStd <- StdMat(dat_p2_yx$Y)
XStd <- StdMat(dat_p2_yx$X[, -1]) # remove the constant column
lambdas <- LambdaSeq(
  YStd = YStd,
  XStd = XStd,
  n_lambdas = 100
)
FitVARLassoSearch(
  YStd = YStd,
  XStd = XStd,
  lambdas = lambdas,
  crit = "ebic",
  max_iter = 1000,
  tol = 1e-5
)

```

FitVAROLS

Fit Vector Autoregressive (VAR) Model Parameters using Ordinary Least Squares (OLS)

Description

This function estimates the parameters of a VAR model using the Ordinary Least Squares (OLS) method. The OLS method is used to estimate the autoregressive and cross-regression coefficients.

Usage

```
FitVAROLS(Y, X)
```

Arguments

Y	Numeric matrix. Matrix of dependent variables (Y).
X	Numeric matrix. Matrix of predictors (X).

Details

The `FitVAROLS()` function estimates the parameters of a Vector Autoregressive (VAR) model using the Ordinary Least Squares (OLS) method. Given the input matrices Y and X, where Y is the matrix of dependent variables, and X is the matrix of predictors, the function computes the autoregressive and cross-regression coefficients of the VAR model. Note that if the first column of X is a vector of ones, the constant vector is also estimated.

The steps involved in estimating the VAR model parameters using OLS are as follows:

- Compute the QR decomposition of the lagged predictor matrix X using the `qr_econ` function from the Armadillo library.
- Extract the Q and R matrices from the QR decomposition.

- Solve the linear system $R * \text{coef} = Q.t() * Y$ to estimate the VAR model coefficients `coef`.
- The function returns a matrix containing the estimated autoregressive and cross-regression coefficients of the VAR model.

Value

Matrix of estimated autoregressive and cross-regression coefficients.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
Y <- dat_p2_yx$Y
X <- dat_p2_yx$X
FitVAROLS(Y = Y, X = X)
```

LambdaSeq

Function to generate the sequence of lambdas

Description

Function to generate the sequence of lambdas

Usage

```
LambdaSeq(YStd, XStd, n_lambdas)
```

Arguments

YStd	Numeric matrix. Matrix of standardized dependent variables (Y).
XStd	Numeric matrix. Matrix of standardized predictors (X). XStd should not include a vector of ones in column one.
n_lambdas	Integer. Number of lambdas to generate.

Value

Returns a vector of lambdas.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
YStd <- StdMat(dat_p2_yx$Y)
XStd <- StdMat(dat_p2_yx$X[, -1]) # remove the constant column
LambdaSeq(YStd = YStd, XStd = XStd, n_lambdas = 100)
```

OrigScale	<i>Return Standardized Estimates to the Original Scale</i>
-----------	--

Description

Return Standardized Estimates to the Original Scale

Usage

```
OrigScale(coef_std, Y, X)
```

Arguments

- coef_std Numeric matrix. Standardized estimates of the autoregression and cross regression coefficients.
- Y Numeric matrix. Matrix of dependent variables (Y).
- X Numeric matrix. Matrix of predictors (X).

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
Y <- dat_p2_yx$Y
X <- dat_p2_yx$X[, -1] # remove the constant column
YStd <- StdMat(Y)
XStd <- StdMat(X)
coef_std <- FitVAROLS(Y = YStd, X = XStd)
FitVAROLS(Y = Y, X = X)
OrigScale(coef_std = coef_std, Y = Y, X = X)
```

PBootVARExoLasso	<i>Parametric Bootstrap for the Vector Autoregressive Model with Exogenous Variables Using Lasso Regularization</i>
------------------	---

Description

Parametric Bootstrap for the Vector Autoregressive Model with Exogenous Variables Using Lasso Regularization

Usage

```
PBootVARExoLasso(data, exo_mat, p, B, burn_in, n_lambdas, crit, max_iter, tol)
```

Arguments

<code>data</code>	Numeric matrix. The time series data with dimensions <code>t</code> by <code>k</code> , where <code>t</code> is the number of observations and <code>k</code> is the number of variables.
<code>exo_mat</code>	Numeric matrix. Matrix of exogenous variables with dimensions <code>t + burn_in</code> by <code>m</code> . If the number of rows is equal to <code>t</code> , set <code>burn_in = 0</code> .
<code>p</code>	Integer. The order of the VAR model (number of lags).
<code>B</code>	Integer. Number of bootstrap samples to generate.
<code>burn_in</code>	Integer. Number of burn-in observations to exclude before returning the results in the simulation step.
<code>n_lambdas</code>	Integer. Number of lambdas to generate.
<code>crit</code>	Character string. Information criteria to use. Valid values include "aic", "bic", and "ebic".
<code>max_iter</code>	Integer. The maximum number of iterations for the coordinate descent algorithm (e.g., <code>max_iter = 10000</code>).
<code>tol</code>	Numeric. Convergence tolerance. The algorithm stops when the change in coefficients between iterations is below this tolerance (e.g., <code>tol = 1e-5</code>).

Value

List with the following elements:

- **est**: Numeric matrix. Original OLS estimate of the coefficient matrix.
- **boot**: Numeric matrix. Matrix of vectorized bootstrap estimates of the coefficient matrix.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
data <- dat_p2_exo$data
exo_mat <- dat_p2_exo$exo_mat
pb <- PBootVARExoLasso(
  data = data,
  exo_mat = exo_mat,
  p = 2,
  B = 5,
  burn_in = 0,
  n_lambdas = 10,
  crit = "ebic",
  max_iter = 1000,
  tol = 1e-5
)
str(pb)
```

PBootVARExoOLS

Parametric Bootstrap for the Vector Autoregressive Model with Exogenous Variables Using Ordinary Least Squares

Description

Parametric Bootstrap for the Vector Autoregressive Model with Exogenous Variables Using Ordinary Least Squares

Usage

```
PBootVARExoOLS(data, exo_mat, p, B, burn_in)
```

Arguments

data	Numeric matrix. The time series data with dimensions t by k , where t is the number of observations and k is the number of variables.
exo_mat	Numeric matrix. Matrix of exogenous variables with dimensions $t + \text{burn_in}$ by m . If the number of rows is equal to t , set $\text{burn_in} = 0$.
p	Integer. The order of the VAR model (number of lags).

B	Integer. Number of bootstrap samples to generate.
burn_in	Integer. Number of burn-in observations to exclude before returning the results in the simulation step.

Value

List with the following elements:

- **est**: Numeric matrix. Original OLS estimate of the coefficient matrix.
- **boot**: Numeric matrix. Matrix of vectorized bootstrap estimates of the coefficient matrix.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
data <- dat_p2_exo$data
exo_mat <- dat_p2_exo$exo_mat
pb <- PBootVARExoOLS(
  data = data,
  exo_mat = exo_mat,
  p = 2,
  B = 5,
  burn_in = 0
)
str(pb)
```

PBootVARLasso	<i>Parametric Bootstrap for the Vector Autoregressive Model Using Lasso Regularization</i>
---------------	--

Description

Parametric Bootstrap for the Vector Autoregressive Model Using Lasso Regularization

Usage

```
PBootVARLasso(data, p, B, burn_in, n_lambdas, crit, max_iter, tol)
```

Arguments

<code>data</code>	Numeric matrix. The time series data with dimensions <code>t</code> by <code>k</code> , where <code>t</code> is the number of observations and <code>k</code> is the number of variables.
<code>p</code>	Integer. The order of the VAR model (number of lags).
<code>B</code>	Integer. Number of bootstrap samples to generate.
<code>burn_in</code>	Integer. Number of burn-in observations to exclude before returning the results in the simulation step.
<code>n_lambdas</code>	Integer. Number of lambdas to generate.
<code>crit</code>	Character string. Information criteria to use. Valid values include "aic", "bic", and "ebic".
<code>max_iter</code>	Integer. The maximum number of iterations for the coordinate descent algorithm (e.g., <code>max_iter = 10000</code>).
<code>tol</code>	Numeric. Convergence tolerance. The algorithm stops when the change in coefficients between iterations is below this tolerance (e.g., <code>tol = 1e-5</code>).

Value

List with the following elements:

- **est**: Numeric matrix. Original Lasso estimate of the coefficient matrix.
- **boot**: Numeric matrix. Matrix of vectorized bootstrap estimates of the coefficient matrix.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
pb <- PBootVARLasso(
  data = dat_p2,
  p = 2,
  B = 5,
  burn_in = 20,
  n_lambdas = 10,
  crit = "ebic",
  max_iter = 1000,
  tol = 1e-5
)
str(pb)
```

PBootVAROLS

Parametric Bootstrap for the Vector Autoregressive Model Using Ordinary Least Squares

Description

Parametric Bootstrap for the Vector Autoregressive Model Using Ordinary Least Squares

Usage

```
PBootVAROLS(data, p, B, burn_in)
```

Arguments

data	Numeric matrix. The time series data with dimensions t by k , where t is the number of observations and k is the number of variables.
p	Integer. The order of the VAR model (number of lags).
B	Integer. Number of bootstrap samples to generate.
burn_in	Integer. Number of burn-in observations to exclude before returning the results in the simulation step.

Value

List with the following elements:

- **est**: Numeric matrix. Original OLS estimate of the coefficient matrix.
- **boot**: Numeric matrix. Matrix of vectorized bootstrap estimates of the coefficient matrix.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
pb <- PBootVAROLS(data = dat_p2, p = 2, B = 5, burn_in = 20)
str(pb)
```

RBootVARExoLasso	<i>Residual Bootstrap for the Vector Autoregressive Model with Exogenous Variables Using Lasso Regularization</i>
------------------	---

Description

Residual Bootstrap for the Vector Autoregressive Model with Exogenous Variables Using Lasso Regularization

Usage

```
RBootVARExoLasso(data, exo_mat, p, B, n_lambdas, crit, max_iter, tol)
```

Arguments

<code>data</code>	Numeric matrix. The time series data with dimensions <code>t</code> by <code>k</code> , where <code>t</code> is the number of observations and <code>k</code> is the number of variables.
<code>exo_mat</code>	Numeric matrix. Matrix of exogenous variables with dimensions <code>t</code> by <code>m</code> .
<code>p</code>	Integer. The order of the VAR model (number of lags).
<code>B</code>	Integer. Number of bootstrap samples to generate.
<code>n_lambdas</code>	Integer. Number of lambdas to generate.
<code>crit</code>	Character string. Information criteria to use. Valid values include "aic", "bic", and "ebic".
<code>max_iter</code>	Integer. The maximum number of iterations for the coordinate descent algorithm (e.g., <code>max_iter = 10000</code>).
<code>tol</code>	Numeric. Convergence tolerance. The algorithm stops when the change in coefficients between iterations is below this tolerance (e.g., <code>tol = 1e-5</code>).

Value

List with the following elements:

- **est**: Numeric matrix. Original Lasso estimate of the coefficient matrix.
- **boot**: Numeric matrix. Matrix of vectorized bootstrap estimates of the coefficient matrix.
- **X**: Numeric matrix. Original X
- **Y**: List of numeric matrices. Bootstrapped Y

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
data <- dat_p2_exo$data
exo_mat <- dat_p2_exo$exo_mat
rb <- RBootVARExoLasso(
  data = data,
  exo_mat = exo_mat,
  p = 2,
  B = 5,
  n_lambdas = 10,
  crit = "ebic",
  max_iter = 1000,
  tol = 1e-5
)
str(rb)
```

RBootVARExoOLS

Residual Bootstrap for the Vector Autoregressive Model with Exogenous Variables Using Ordinary Least Squares

Description

Residual Bootstrap for the Vector Autoregressive Model with Exogenous Variables Using Ordinary Least Squares

Usage

```
RBootVARExoOLS(data, exo_mat, p, B)
```

Arguments

data	Numeric matrix. The time series data with dimensions t by k , where t is the number of observations and k is the number of variables.
exo_mat	Numeric matrix. Matrix of exogenous variables with dimensions t by m .
p	Integer. The order of the VAR model (number of lags).
B	Integer. Number of bootstrap samples to generate.

Value

List with the following elements:

- **est**: Numeric matrix. Original OLS estimate of the coefficient matrix.
- **boot**: Numeric matrix. Matrix of vectorized bootstrap estimates of the coefficient matrix.
- **X**: Numeric matrix. Original X
- **Y**: List of numeric matrices. Bootstrapped Y

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
data <- dat_p2_exo$data
exo_mat <- dat_p2_exo$exo_mat
rb <- RBootVARExoOLS(data = data, exo_mat = exo_mat, p = 2, B = 5)
str(rb)
```

RBootVARLasso

Residual Bootstrap for the Vector Autoregressive Model Using Lasso Regularization

Description

Residual Bootstrap for the Vector Autoregressive Model Using Lasso Regularization

Usage

```
RBootVARLasso(data, p, B, n_lambdas, crit, max_iter, tol)
```

Arguments

data	Numeric matrix. The time series data with dimensions t by k , where t is the number of observations and k is the number of variables.
p	Integer. The order of the VAR model (number of lags).
B	Integer. Number of bootstrap samples to generate.
n_lambdas	Integer. Number of lambdas to generate.
crit	Character string. Information criteria to use. Valid values include "aic", "bic", and "ebic".
max_iter	Integer. The maximum number of iterations for the coordinate descent algorithm (e.g., <code>max_iter = 10000</code>).
tol	Numeric. Convergence tolerance. The algorithm stops when the change in coefficients between iterations is below this tolerance (e.g., <code>tol = 1e-5</code>).

Value

List with the following elements:

- **est**: Numeric matrix. Original Lasso estimate of the coefficient matrix.
- **boot**: Numeric matrix. Matrix of vectorized bootstrap estimates of the coefficient matrix.
- **X**: Numeric matrix. Original X
- **Y**: List of numeric matrices. Bootstrapped Y

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
rb <- RBootVARLasso(
  data = dat_p2,
  p = 2,
  B = 5,
  n_lambdas = 10,
  crit = "ebic",
  max_iter = 1000,
  tol = 1e-5
)
str(rb)
```

RBootVAROLS

Residual Bootstrap for the Vector Autoregressive Model Using Ordinary Least Squares

Description

Residual Bootstrap for the Vector Autoregressive Model Using Ordinary Least Squares

Usage

```
RBootVAROLS(data, p, B)
```


Arguments

<code>data</code>	Numeric matrix. The time series data with dimensions <code>t</code> by <code>k</code> , where <code>t</code> is the number of observations and <code>k</code> is the number of variables.
<code>p</code>	Integer. The order of the VAR model (number of lags).
<code>B</code>	Integer. Number of bootstrap samples to generate.

Value

List with the following elements:

- **est**: Numeric matrix. Original OLS estimate of the coefficient matrix.
- **boot**: Numeric matrix. Matrix of vectorized bootstrap estimates of the coefficient matrix.
- **X**: Numeric matrix. Original X
- **Y**: List of numeric matrices. Bootstrapped Y

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [SearchVARLasso\(\)](#), [StdMat\(\)](#)

Examples

```
rb <- RBootVAROLS(data = dat_p2, p = 2, B = 5)
str(rb)
```

SearchVARLasso

Compute AIC, BIC, and EBIC for Lasso Regularization

Description

This function computes the Akaike Information Criterion (AIC), Bayesian Information Criterion (BIC), and Extended Bayesian Information Criterion (EBIC) for a given matrix of predictors X , a matrix of outcomes Y , and a vector of lambda hyperparameters for Lasso regularization.

Usage

```
SearchVARLasso(YStd, XStd, lambdas, max_iter, tol)
```

Arguments

<code>YStd</code>	Numeric matrix. Matrix of standardized dependent variables (Y).
<code>XStd</code>	Numeric matrix. Matrix of standardized predictors (X). <code>XStd</code> should not include a vector of ones in column one.
<code>lambdas</code>	Numeric vector. Lasso hyperparameter. The regularization strength controlling the sparsity.
<code>max_iter</code>	Integer. The maximum number of iterations for the coordinate descent algorithm (e.g., <code>max_iter = 10000</code>).
<code>tol</code>	Numeric. Convergence tolerance. The algorithm stops when the change in coefficients between iterations is below this tolerance (e.g., <code>tol = 1e-5</code>).

Value

List with the following elements:

- **criteria:** Matrix with columns for lambda, AIC, BIC, and EBIC values.
- **fit:** List of matrices containing the estimated autoregressive and cross-regression coefficients for each lambda.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [StdMat\(\)](#)

Examples

```
YStd <- StdMat(dat_p2_yx$Y)
XStd <- StdMat(dat_p2_yx$X[, -1])
lambdas <- 10^seq(-5, 5, length.out = 100)
search <- SearchVARLasso(YStd = YStd, XStd = XStd, lambdas = lambdas,
  max_iter = 10000, tol = 1e-5)
plot(x = 1:nrow(search$criteria), y = search$criteria[, 4],
  type = "b", xlab = "lambda", ylab = "EBIC")
```

SelectVARLasso*Select the Lasso Estimates from the Grid Search*

Description

Select the Lasso Estimates from the Grid Search

Usage

```
SelectVARLasso(search, crit = "ebic")
```

Arguments

search	Object. Output of the SearchVARLasso() function.
crit	Character string. Information criteria to use. Valid values include "aic", "bic", and "ebic".

Value

Returns the Lasso estimates of autoregression and cross regression coefficients.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Simulation of Autoregressive Data Functions: [BootCI\(\)](#), [BootSE\(\)](#), [SimVARExo\(\)](#), [SimVAR\(\)](#), [YXExo\(\)](#), [YX\(\)](#)

Examples

```
YStd <- StdMat(dat_p2_yx$Y)
XStd <- StdMat(dat_p2_yx$X[, -1])
lambdas <- 10^seq(-5, 5, length.out = 100)
search <- SearchVARLasso(
  YStd = YStd, XStd = XStd, lambdas = lambdas,
  max_iter = 10000, tol = 1e-5
)
SelectVARLasso(search, crit = "ebic")
```

SimVAR

*Simulate Data from a Vector Autoregressive (VAR) Model***Description**

This function generates synthetic time series data from a Vector Autoregressive (VAR) model.

Usage

```
SimVAR(time, burn_in, constant, coef, chol_cov)
```

Arguments

time	Integer. Number of time points to simulate.
burn_in	Integer. Number of burn-in observations to exclude before returning the results.
constant	Numeric vector. The constant term vector of length k, where k is the number of variables.
coef	Numeric matrix. Coefficient matrix with dimensions k by (k * p). Each k by k block corresponds to the coefficient matrix for a particular lag.
chol_cov	Numeric matrix. The Cholesky decomposition of the covariance matrix of the multivariate normal noise. It should have dimensions k by k.

Details

The `SimVAR()` function generates synthetic time series data from a Vector Autoregressive (VAR) model. The VAR model is defined by the constant term `constant`, the coefficient matrix `coef`, and the Cholesky decomposition of the covariance matrix of the multivariate normal process noise `chol_cov`. The generated time series data follows a VAR(p) process, where p is the number of lags specified by the size of `coef`. The generated data includes a burn-in period, which is excluded before returning the results.

The steps involved in generating the VAR time series data are as follows:

- Extract the number of variables k and the number of lags p from the input.
- Create a matrix data of size k by (time + burn_in) to store the generated VAR time series data.
- Set the initial values of the matrix data using the constant term `constant`.
- For each time point starting from the p-th time point to time + burn_in - 1:
 - Generate a vector of random noise from a multivariate normal distribution with mean 0 and covariance matrix `chol_cov`.
 - Generate the VAR time series values for each variable j at time t using the formula:

$$Y_{tj} = \text{constant}_j + \sum_{l=1}^p \sum_{m=1}^k (\text{coef}_{jm} * Y_{lm}) + \text{noise}_j$$

where Y_{tj} is the value of variable j at time t , constant_j is the constant term for variable j , coef_{jm} are the coefficients for variable j from lagged variables up to order p , Y_{tm} are the lagged values of variable m up to order p at time t , and noise_j is the element j from the generated vector of random process noise.

- Transpose the matrix data and return only the required time period after the burn-in period, which is from column `burn_in` to column `time + burn_in - 1`.

Value

Numeric matrix containing the simulated time series data with dimensions k by `time`, where k is the number of variables and `time` is the number of observations.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Simulation of Autoregressive Data Functions: [BootCI\(\)](#), [BootSE\(\)](#), [SelectVARLasso\(\)](#), [SimVARExo\(\)](#), [YXExo\(\)](#), [YX\(\)](#)

Examples

```
set.seed(42)
time <- 50L
burn_in <- 10L
k <- 3
p <- 2
constant <- c(1, 1, 1)
coef <- matrix(
  data = c(
    0.4, 0.0, 0.0, 0.1, 0.0, 0.0,
    0.0, 0.5, 0.0, 0.0, 0.2, 0.0,
    0.0, 0.0, 0.6, 0.0, 0.0, 0.3
  ),
  nrow = k,
  byrow = TRUE
)
chol_cov <- chol(diag(3))
y <- SimVAR(
  time = time,
  burn_in = burn_in,
  constant = constant,
  coef = coef,
  chol_cov = chol_cov
)
head(y)
```

SimVARExo	<i>Simulate Data from a Vector Autoregressive (VAR) Model with Exogenous Variables</i>
-----------	--

Description

This function generates synthetic time series data from a Vector Autoregressive (VAR) model with exogenous variables.

Usage

```
SimVARExo(time, burn_in, constant, coef, chol_cov, exo_mat, exo_coef)
```

Arguments

time	Integer. Number of time points to simulate.
burn_in	Integer. Number of burn-in observations to exclude before returning the results.
constant	Numeric vector. The constant term vector of length k , where k is the number of variables.
coef	Numeric matrix. Coefficient matrix with dimensions k by $(k * p)$. Each k by k block corresponds to the coefficient matrix for a particular lag.
chol_cov	Numeric matrix. The Cholesky decomposition of the covariance matrix of the multivariate normal noise. It should have dimensions k by k .
exo_mat	Numeric matrix. Matrix of exogenous covariates with dimensions $\text{time} + \text{burn_in}$ by x . Each column corresponds to a different exogenous variable.
exo_coef	Numeric vector. Coefficient matrix with dimensions k by x associated with the exogenous covariates.

Value

Numeric matrix containing the simulated time series data with dimensions k by time , where k is the number of variables and time is the number of observations.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Simulation of Autoregressive Data Functions: [BootCI\(\)](#), [BootSE\(\)](#), [SelectVARLasso\(\)](#), [SimVAR\(\)](#), [YXExo\(\)](#), [YX\(\)](#)

Examples

```

set.seed(42)
time <- 1000L
burn_in <- 200
k <- 3
p <- 2
constant <- c(1, 1, 1)
coef <- matrix(
  data = c(
    0.4, 0.0, 0.0, 0.1, 0.0, 0.0,
    0.0, 0.5, 0.0, 0.0, 0.2, 0.0,
    0.0, 0.0, 0.6, 0.0, 0.0, 0.3
  ),
  nrow = k,
  byrow = TRUE
)
chol_cov <- chol(diag(3))
exo_mat <- MASS::mvrnorm(
  n = time + burn_in,
  mu = c(0, 0, 0),
  Sigma = diag(3)
)
exo_coef <- matrix(
  data = c(
    0.5, 0.0, 0.0,
    0.0, 0.5, 0.0,
    0.0, 0.0, 0.5
  ),
  nrow = 3
)
y <- SimVARExo(
  time = time,
  burn_in = burn_in,
  constant = constant,
  coef = coef,
  chol_cov = chol_cov,
  exo_mat = exo_mat,
  exo_coef = exo_coef
)
str(y)

```

StdMat

Standardize Matrix

Description

This function standardizes the given matrix by centering the columns and scaling them to have unit variance.

Usage

StdMat(X)

Arguments

X Numeric matrix. The matrix to be standardized.

Value

Numeric matrix with standardized values.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Fitting Autoregressive Model Functions: [FitVARLassoSearch\(\)](#), [FitVARLasso\(\)](#), [FitVAROLS\(\)](#), [LambdaSeq\(\)](#), [OrigScale\(\)](#), [PBootVARExoLasso\(\)](#), [PBootVARExoOLS\(\)](#), [PBootVARLasso\(\)](#), [PBootVAROLS\(\)](#), [RBootVARExoLasso\(\)](#), [RBootVARExoOLS\(\)](#), [RBootVARLasso\(\)](#), [RBootVAROLS\(\)](#), [SearchVARLasso\(\)](#)

Examples

```
std <- StdMat(dat_p2)
colMeans(std)
var(std)
```

YX	<i>Create Y and X Matrices</i>
----	--------------------------------

Description

This function creates the dependent variable (Y) and predictor variable (X) matrices.

Usage

YX(data, p)

Arguments

data Numeric matrix. The time series data with dimensions t by k, where t is the number of observations and k is the number of variables.

p Integer. The order of the VAR model (number of lags).

Details

The `YX()` function creates the Y and X matrices required for fitting a Vector Autoregressive (VAR) model. Given the input data matrix with dimensions t by k , where t is the number of observations and k is the number of variables, and the order of the VAR model p (number of lags), the function constructs lagged predictor matrix X and the dependent variable matrix Y .

The steps involved in creating the Y and X matrices are as follows:

- Determine the number of observations t and the number of variables k from the input data matrix.
- Create matrices X and Y to store lagged variables and the dependent variable, respectively.
- Populate the matrices X and Y with the appropriate lagged data. The predictors matrix X contains a column of ones and the lagged values of the dependent variables, while the dependent variable matrix Y contains the original values of the dependent variables.
- The function returns a list containing the Y and X matrices, which can be used for further analysis and estimation of the VAR model parameters.

Value

List containing the dependent variable (Y) and predictor variable (X) matrices. Note that the resulting matrices will have $t - p$ rows.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

The `SimVAR()` function for simulating time series data from a VAR model.

Other Simulation of Autoregressive Data Functions: `BootCI()`, `BootSE()`, `SelectVARLasso()`, `SimVARExo()`, `SimVAR()`, `YXExo()`

Examples

```
set.seed(42)
time <- 50L
burn_in <- 10L
k <- 3
p <- 2
constant <- c(1, 1, 1)
coef <- matrix(
  data = c(
    0.4, 0.0, 0.0, 0.1, 0.0, 0.0,
    0.0, 0.5, 0.0, 0.0, 0.2, 0.0,
    0.0, 0.0, 0.6, 0.0, 0.0, 0.3
  ),
  nrow = k,
  byrow = TRUE
)
chol_cov <- chol(diag(3))
```

```

y <- SimVAR(
  time = time,
  burn_in = burn_in,
  constant = constant,
  coef = coef,
  chol_cov = chol_cov
)
yx <- YX(data = y, p = 2)
str(yx)

```

YXExo

*Create Y and X Matrices with Exogenous Variables***Description**

This function creates the dependent variable (Y) and predictor variable (X) matrices.

Usage

```
YXExo(data, p, exo_mat)
```

Arguments

data	Numeric matrix. The time series data with dimensions t by k , where t is the number of observations and k is the number of variables.
p	Integer. The order of the VAR model (number of lags).
exo_mat	Numeric matrix. Matrix of exogenous variables with dimensions t by m .

Details

The `YX()` function creates the Y and X matrices required for fitting a Vector Autoregressive (VAR) model. Given the input data matrix with dimensions t by k , where t is the number of observations and k is the number of variables, and the order of the VAR model p (number of lags), the function constructs lagged predictor matrix X and the dependent variable matrix Y.

The steps involved in creating the Y and X matrices are as follows:

- Determine the number of observations t and the number of variables k from the input data matrix.
- Create matrices X and Y to store lagged variables and the dependent variable, respectively.
- Populate the matrices X and Y with the appropriate lagged data. The predictors matrix X contains a column of ones and the lagged values of the dependent variables, while the dependent variable matrix Y contains the original values of the dependent variables.
- The function returns a list containing the Y and X matrices, which can be used for further analysis and estimation of the VAR model parameters.

Value

List containing the dependent variable (Y) and predictor variable (X) matrices. Note that the resulting matrices will have $t - p$ rows.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

The [SimVAR\(\)](#) function for simulating time series data from a VAR model.

Other Simulation of Autoregressive Data Functions: [BootCI\(\)](#), [BootSE\(\)](#), [SelectVARLasso\(\)](#), [SimVARExo\(\)](#), [SimVAR\(\)](#), [YX\(\)](#)

Examples

```
set.seed(42)
time <- 1000L
burn_in <- 200
k <- 3
p <- 2
constant <- c(1, 1, 1)
coef <- matrix(
  data = c(
    0.4, 0.0, 0.0, 0.1, 0.0, 0.0,
    0.0, 0.5, 0.0, 0.0, 0.2, 0.0,
    0.0, 0.0, 0.6, 0.0, 0.0, 0.3
  ),
  nrow = k,
  byrow = TRUE
)
chol_cov <- chol(diag(3))
exo_mat <- MASS::mvrnorm(
  n = time + burn_in,
  mu = c(0, 0, 0),
  Sigma = diag(3)
)
exo_coef <- matrix(
  data = c(
    0.5, 0.0, 0.0,
    0.0, 0.5, 0.0,
    0.0, 0.0, 0.5
  ),
  nrow = 3
)
y <- SimVARExo(
  time = time,
  burn_in = burn_in,
  constant = constant,
  coef = coef,
  chol_cov = chol_cov,
```

```
    exo_mat = exo_mat,  
    exo_coef = exo_coef  
  )  
yx <- YXExo(  
  data = y,  
  p = 2,  
  exo_mat = exo_mat[(burn_in + 1):(time + burn_in), ]  
)  
str(yx)
```

Index

* Fitting Autoregressive Model Functions

FitVARLasso, [10](#)
FitVARLassoSearch, [12](#)
FitVAROLS, [13](#)
LambdaSeq, [14](#)
OrigScale, [15](#)
PBootVARExoLasso, [16](#)
PBootVARExoOLS, [17](#)
PBootVARLasso, [18](#)
PBootVAROLS, [20](#)
RBootVARExoLasso, [21](#)
RBootVARExoOLS, [22](#)
RBootVARLasso, [23](#)
RBootVAROLS, [24](#)
SearchVARLasso, [25](#)
StdMat, [31](#)

* Simulation of Autoregressive Data

Functions

BootCI, [2](#)
BootSE, [4](#)
SelectVARLasso, [27](#)
SimVAR, [28](#)
SimVARExo, [30](#)
YX, [32](#)
YXExo, [34](#)

* data

dat_ml_p1, [5](#)
dat_ml_p2, [6](#)
dat_p1, [7](#)
dat_p1_yx, [8](#)
dat_p2, [8](#)
dat_p2_exo, [9](#)
dat_p2_exo_yx, [9](#)
dat_p2_yx, [10](#)
SimVAR, [28](#)
SimVARExo, [30](#)

* fitAutoReg

BootCI, [2](#)
BootSE, [4](#)

dat_ml_p1, [5](#)
dat_ml_p2, [6](#)
dat_p1, [7](#)
dat_p1_yx, [8](#)
dat_p2, [8](#)
dat_p2_exo, [9](#)
dat_p2_exo_yx, [9](#)
dat_p2_yx, [10](#)
FitVARLasso, [10](#)
FitVARLassoSearch, [12](#)
FitVAROLS, [13](#)
LambdaSeq, [14](#)
OrigScale, [15](#)
PBootVARExoLasso, [16](#)
PBootVARExoOLS, [17](#)
PBootVARLasso, [18](#)
PBootVAROLS, [20](#)
RBootVARExoLasso, [21](#)
RBootVARExoOLS, [22](#)
RBootVARLasso, [23](#)
RBootVAROLS, [24](#)
SearchVARLasso, [25](#)
SelectVARLasso, [27](#)
StdMat, [31](#)

* fit

FitVARLasso, [10](#)
FitVARLassoSearch, [12](#)
FitVAROLS, [13](#)
LambdaSeq, [14](#)
SearchVARLasso, [25](#)
SelectVARLasso, [27](#)

* pb

BootCI, [2](#)
BootSE, [4](#)
PBootVARExoLasso, [16](#)
PBootVARExoOLS, [17](#)
PBootVARLasso, [18](#)
PBootVAROLS, [20](#)

* rb

- BootCI, [2](#)
- BootSE, [4](#)
- RBootVARExoLasso, [21](#)
- RBootVARExoOLS, [22](#)
- RBootVARLasso, [23](#)
- RBootVAROLS, [24](#)
- * **simAutoReg**
 - SimVAR, [28](#)
 - SimVARExo, [30](#)
 - YX, [32](#)
 - YXExo, [34](#)
- * **sim**
 - SimVAR, [28](#)
 - SimVARExo, [30](#)
- * **utils**
 - OrigScale, [15](#)
 - StdMat, [31](#)
 - YX, [32](#)
 - YXExo, [34](#)
- * **var**
 - SimVAR, [28](#)
 - SimVARExo, [30](#)
- BootCI, [2](#), [4](#), [27](#), [29](#), [30](#), [33](#), [35](#)
- BootSE, [3](#), [4](#), [27](#), [29](#), [30](#), [33](#), [35](#)
- dat_ml_p1, [5](#)
- dat_ml_p2, [6](#)
- dat_p1, [7](#)
- dat_p1_yx, [8](#)
- dat_p2, [8](#)
- dat_p2_exo, [9](#)
- dat_p2_exo_yx, [9](#)
- dat_p2_yx, [10](#)
- FitVARLasso, [10](#), [12](#), [14](#), [15](#), [17–21](#), [23–26](#), [32](#)
- FitVARLasso(), [11](#)
- FitVARLassoSearch, [11](#), [12](#), [14](#), [15](#), [17–21](#), [23–26](#), [32](#)
- FitVAROLS, [11](#), [12](#), [13](#), [15](#), [17–21](#), [23–26](#), [32](#)
- FitVAROLS(), [13](#)
- LambdaSeq, [11](#), [12](#), [14](#), [14](#), [15](#), [17–21](#), [23–26](#), [32](#)
- OrigScale, [11](#), [12](#), [14](#), [15](#), [15](#), [17–21](#), [23–26](#), [32](#)
- PBootVARExoLasso, [11](#), [12](#), [14](#), [15](#), [16](#), [18–21](#), [23–26](#), [32](#)
- PBootVARExoOLS, [11](#), [12](#), [14](#), [15](#), [17](#), [17](#), [19–21](#), [23–26](#), [32](#)
- PBootVARLasso, [11](#), [12](#), [14](#), [15](#), [17](#), [18](#), [18](#), [20](#), [21](#), [23–26](#), [32](#)
- PBootVARLasso(), [2](#), [4](#)
- PBootVAROLS, [11](#), [12](#), [14](#), [15](#), [17–19](#), [20](#), [21](#), [23–26](#), [32](#)
- PBootVAROLS(), [2](#), [4](#)
- RBootVARExoLasso, [11](#), [12](#), [14](#), [15](#), [17–20](#), [21](#), [23–26](#), [32](#)
- RBootVARExoOLS, [11](#), [12](#), [14](#), [15](#), [17–21](#), [22](#), [24–26](#), [32](#)
- RBootVARLasso, [11](#), [12](#), [14](#), [15](#), [17–21](#), [23](#), [23](#), [25](#), [26](#), [32](#)
- RBootVARLasso(), [2](#), [4](#)
- RBootVAROLS, [11](#), [12](#), [14](#), [15](#), [17–21](#), [23](#), [24](#), [24](#), [26](#), [32](#)
- RBootVAROLS(), [2](#), [4](#)
- SearchVARLasso, [11](#), [12](#), [14](#), [15](#), [17–21](#), [23–25](#), [25](#), [32](#)
- SearchVARLasso(), [27](#)
- SelectVARLasso, [3](#), [4](#), [27](#), [29](#), [30](#), [33](#), [35](#)
- SimVAR, [3](#), [4](#), [27](#), [28](#), [30](#), [33](#), [35](#)
- SimVAR(), [28](#), [33](#), [35](#)
- SimVARExo, [3](#), [4](#), [27](#), [29](#), [30](#), [33](#), [35](#)
- StdMat, [11](#), [12](#), [14](#), [15](#), [17–21](#), [23–26](#), [31](#)
- YX, [3](#), [4](#), [27](#), [29](#), [30](#), [32](#), [35](#)
- YX(), [33](#), [34](#)
- YXExo, [3](#), [4](#), [27](#), [29](#), [30](#), [33](#), [34](#)