

Package ‘longMI’

December 12, 2023

Title Longitudinal Measurement Invariance

Version 1.0.0

Description Fits longitudinal measurement invariance models using the 'lavaan' package.
For a thorough exposition of testing measurement invariance,
see Millsap (2011) <[doi:10.4324/9780203821961](https://doi.org/10.4324/9780203821961)>.

URL <https://github.com/ijapesigan/longMI>,
<https://ijapesigan.github.io/longMI/>

BugReports <https://github.com/ijapesigan/longMI/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

Depends R (>= 3.5.0)

Imports lavaan

Suggests knitr, rmarkdown, testthat

RoxygenNote 7.2.3

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<<https://orcid.org/0000-0003-4818-8420>>)

Maintainer Ivan Jacob Agaloos Pesigan <r.ijapesigan@gmail.com>

R topics documented:

anova.longmi	2
Comparison	3
Configural	4
Invariance	6
osbornesudick1972	7
print.longmi	8
Strict	9

Strong	10
summary.longmi	12
Weak	13
Index	15

anova.longmi	<i>Model Comparison Method for an Object of Class longmi</i>
--------------	--

Description

Model Comparison Method for an Object of Class longmi

Usage

```
## S3 method for class 'longmi'
anova(object, ...)
```

Arguments

- object Object of class longmi.
- ... Additional arguments to pass to [lavaan::lavTestLRT\(\)](#).

Value

Returns a data frame of chi-square difference test results.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
data("osbornesudick1972", package = "longMI")
mi <- Invariance(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
anova(mi)
```

Comparison	<i>Comparison Measurement Invariance Models</i>
------------	---

Description

Comparison Measurement Invariance Models

Usage

```
Comparison(configural = NULL, weak = NULL, strong = NULL, strict = NULL, ...)
```

Arguments

<code>configural</code>	Fitted configural invariance model.
<code>weak</code>	Fitted weak invariance model.
<code>strong</code>	Fitted strong invariance model.
<code>strict</code>	Fitted strict invariance model.
<code>...</code>	Additional arguments to pass to lavaan::lavTestLRT() .

Value

Returns an object of class `longmi` which is a list with the following elements:

call Function call.
args List of function arguments.
fit Fitted models.
measures Fit measures.
fun Function used ("Comparison").

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Longitudinal Measurement Invariance Functions: [Configural\(\)](#), [Invariance\(\)](#), [Strict\(\)](#), [Strong\(\)](#), [Weak\(\)](#)

Examples

```

data("osbornesudick1972", package = "longMI")
configural_fit <- Configural(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
weak_fit <- Weak(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
strong_fit <- Strong(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
strict_fit <- Strict(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
mi <- Comparison(
  configural = configural_fit,
  weak = weak_fit,
  strong = strong_fit,
  strict = strict_fit
)
print(mi)
summary(mi)

```

Configural

Configural Invariance Model

Description

Configural Invariance Model

Usage

Configural(

```

    data,
    time_points,
    factor_loadings,
    covariances = FALSE,
    model_add = NULL,
    ...
  )

```

Arguments

<code>data</code>	Dataframe. The function assumes that the data is in the wide format and the variables are named as follows: <code>paste0("y", time_point, "_", item_number)</code> . For example, for the item 1 from the first time point, the variable name should be <code>y1_1</code> .
<code>time_points</code>	Numeric vector of discrete time points.
<code>factor_loadings</code>	List with length equal to the number of factors. Each element of the list is the item number of items for the specific factor.
<code>covariances</code>	Logical. If <code>covariance = TRUE</code> , model the covariances of the measurement error.
<code>model_add</code>	Additional specification added to the lavaan model syntax.
<code>...</code>	Additional arguments to pass to lavaan::cfa() .

Value

Returns a fitted lavaan object.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Longitudinal Measurement Invariance Functions: [Comparison\(\)](#), [Invariance\(\)](#), [Strict\(\)](#), [Strong\(\)](#), [Weak\(\)](#)

Examples

```

data("osbornesudick1972", package = "longMI")
configural_fit <- Configural(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
library(lavaan)
summary(configural_fit)

```

Invariance

*Test Longitudinal Measurement Invariance***Description**

Test Longitudinal Measurement Invariance

Usage

```
Invariance(
  data,
  time_points,
  factor_loadings,
  covariances = FALSE,
  model_add_configural = NULL,
  model_add_weak = NULL,
  model_add_strong = NULL,
  model_add_strict = NULL,
  ...
)
```

Arguments

<code>data</code>	Dataframe. The function assumes that the data is in the wide format and the variables are named as follows: <code>paste0("y", time_point, "_", item_number)</code> . For example, for the item 1 from the first time point, the variable name should be <code>y1_1</code> .
<code>time_points</code>	Numeric vector of discrete time points.
<code>factor_loadings</code>	List with length equal to the number of factors. Each element of the list is the item number of items for the specific factor.
<code>covariances</code>	Logical. If <code>covariance = TRUE</code> , model the covariances of the measurement error.
<code>model_add_configural</code>	Additional specification added to the lavaan model syntax for the configural invariance model.
<code>model_add_weak</code>	Additional specification added to the lavaan model syntax for the weak invariance model.
<code>model_add_strong</code>	Additional specification added to the lavaan model syntax for the strong invariance model.
<code>model_add_strict</code>	Additional specification added to the lavaan model syntax for the strict invariance model.
<code>...</code>	Additional arguments to pass to <code>lavaan::cfa()</code> .

Value

Returns an object of class `longmi` which is a list with the following elements:

call Function call.

args List of function arguments.

fit Fitted models.

measures Fit measures.

fun Function used ("Invariance").

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Longitudinal Measurement Invariance Functions: [Comparison\(\)](#), [Configural\(\)](#), [Strict\(\)](#), [Strong\(\)](#), [Weak\(\)](#)

Examples

```
data("osbornesudick1972", package = "longMI")
mi <- Invariance(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
print(mi)
summary(mi)
```

osbornesudick1972	<i>Wechsler Intelligence Scale for Children Data from Osborne and Sudick (1972)</i>
-------------------	---

Description

Wechsler Intelligence Scale for Children Data from Osborne and Sudick (1972)

Usage

```
osbornesudick1972
```

Format

The data set has the following variables:

- id** ID
- y1_1** Time 1 Information
- y1_2** Time 1 Comprehension
- y1_3** Time 1 Similarities
- y1_4** Time 1 Vocabulary
- y6_1** Time 6 Information
- y6_2** Time 6 Comprehension
- y6_3** Time 6 Similarities
- y6_4** Time 6 Vocabulary

References

Osborne, R. T., & Suddick, D. E. (1972). A longitudinal investigation of the intellectual differentiation hypothesis. *The Journal of Genetic Psychology: Research and Theory on Human Development*, 121(1), 83–89. doi:10.1080/00221325.1972.10533131.

print.longmi	<i>Print Method for an Object of Class longmi</i>
--------------	---

Description

Print Method for an Object of Class longmi

Usage

```
## S3 method for class 'longmi'  
print(x, digits = 4, ...)
```

Arguments

- x** Object of class longmi.
- digits** Digits to print.
- ...** additional arguments.

Value

Returns a matrix of selected fit measures.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
data("osbornesudick1972", package = "longMI")
mi <- Invariance(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
print(mi)
```

Strict

Strict Invariance Model

Description

Strict Invariance Model

Usage

```
Strict(
  data,
  time_points,
  factor_loadings,
  covariances = FALSE,
  model_add = NULL,
  ...
)
```

Arguments

<code>data</code>	Dataframe. The function assumes that the data is in the wide format and the variables are named as follows: <code>paste0("y", time_point, "_", item_number)</code> . For example, for the item 1 from the first time point, the variable name should be <code>y1_1</code> .
<code>time_points</code>	Numeric vector of discrete time points.
<code>factor_loadings</code>	List with length equal to the number of factors. Each element of the list is the item number of items for the specific factor.
<code>covariances</code>	Logical. If <code>covariance = TRUE</code> , model the covariances of the measurement error.
<code>model_add</code>	Additional specification added to the lavaan model syntax.
<code>...</code>	Additional arguments to pass to <code>lavaan::cfa()</code> .

Value

Returns a fitted lavaan object.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Longitudinal Measurement Invariance Functions: [Comparison\(\)](#), [Configural\(\)](#), [Invariance\(\)](#), [Strong\(\)](#), [Weak\(\)](#)

Examples

```
data("osbornesudick1972", package = "longMI")
strict_fit <- Strict(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
library(lavaan)
summary(strict_fit)
```

Strong

Strong Invariance Model

Description

Strong Invariance Model

Usage

```
Strong(
  data,
  time_points,
  factor_loadings,
  covariances = FALSE,
  model_add = NULL,
  ...
)
```

Arguments

<code>data</code>	Dataframe. The function assumes that the data is in the wide format and the variables are named as follows: <code>paste0("y", time_point, "_", item_number)</code> . For example, for the item 1 from the first time point, the variable name should be <code>y1_1</code> .
<code>time_points</code>	Numeric vector of discrete time points.
<code>factor_loadings</code>	List with length equal to the number of factors. Each element of the list is the item number of items for the specific factor.
<code>covariances</code>	Logical. If <code>covariance = TRUE</code> , model the covariances of the measurement error.
<code>model_add</code>	Additional specification added to the lavaan model syntax.
<code>...</code>	Additional arguments to pass to lavaan::cfa() .

Value

Returns a fitted lavaan object.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Longitudinal Measurement Invariance Functions: [Comparison\(\)](#), [Configural\(\)](#), [Invariance\(\)](#), [Strict\(\)](#), [Weak\(\)](#)

Examples

```
data("osbornesudick1972", package = "longMI")
strong_fit <- Strong(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
library(lavaan)
summary(strong_fit)
```

summary.longmi	<i>Summary Method for an Object of Class longmi</i>
----------------	---

Description

Summary Method for an Object of Class longmi

Usage

```
## S3 method for class 'longmi'  
summary(object, ...)
```

Arguments

object	Object of class longmi.
...	additional arguments to pass to the summary function in lavaan

Value

Returns a list of the summary of the fitted models.

Author(s)

Ivan Jacob Agaloos Pesigan

Examples

```
data("osbornesudick1972", package = "longMI")  
mi <- Invariance(  
  data = osbornesudick1972,  
  time_points = c(1, 6),  
  factor_loadings = list(  
    c(1, 2, 3, 4)  
  )  
)  
summary(mi)
```

Weak

*Weak Invariance Model***Description**

Weak Invariance Model

Usage

```
Weak(
  data,
  time_points,
  factor_loadings,
  covariances = FALSE,
  model_add = NULL,
  ...
)
```

Arguments

<code>data</code>	Dataframe. The function assumes that the data is in the wide format and the variables are named as follows: <code>paste0("y", time_point, "_", item_number)</code> . For example, for the item 1 from the first time point, the variable name should be <code>y1_1</code> .
<code>time_points</code>	Numeric vector of discrete time points.
<code>factor_loadings</code>	List with length equal to the number of factors. Each element of the list is the item number of items for the specific factor.
<code>covariances</code>	Logical. If <code>covariance = TRUE</code> , model the covariances of the measurement error.
<code>model_add</code>	Additional specification added to the lavaan model syntax.
<code>...</code>	Additional arguments to pass to <code>lavaan::cfa()</code> .

Value

Returns a fitted lavaan object.

Author(s)

Ivan Jacob Agaloos Pesigan

See Also

Other Longitudinal Measurement Invariance Functions: [Comparison\(\)](#), [Configural\(\)](#), [Invariance\(\)](#), [Strict\(\)](#), [Strong\(\)](#)

Examples

```
data("osbornesudick1972", package = "longMI")
weak_fit <- Weak(
  data = osbornesudick1972,
  time_points = c(1, 6),
  factor_loadings = list(
    c(1, 2, 3, 4)
  )
)
library(lavaan)
summary(weak_fit)
```

Index

* Longitudinal Measurement Invariance

Functions

Comparison, [3](#)

Configural, [4](#)

Invariance, [6](#)

Strict, [9](#)

Strong, [10](#)

Weak, [13](#)

* comparison

Comparison, [3](#)

* configural

Configural, [4](#)

* data

osbornesudick1972, [7](#)

* invariance

Invariance, [6](#)

* manSASInvariance

Comparison, [3](#)

Configural, [4](#)

Invariance, [6](#)

Strict, [9](#)

Strong, [10](#)

Weak, [13](#)

* methods

anova.longmi, [2](#)

print.longmi, [8](#)

summary.longmi, [12](#)

* strict

Strict, [9](#)

* strong

Strong, [10](#)

* weak

Weak, [13](#)

anova.longmi, [2](#)

Comparison, [3](#), [5](#), [7](#), [10](#), [11](#), [13](#)

Configural, [3](#), [4](#), [7](#), [10](#), [11](#), [13](#)

Invariance, [3](#), [5](#), [6](#), [10](#), [11](#), [13](#)

lavaan::cfa(), [5](#), [6](#), [9](#), [11](#), [13](#)

lavaan::lavTestLRT(), [2](#), [3](#)

osbornesudick1972, [7](#)

print.longmi, [8](#)

Strict, [3](#), [5](#), [7](#), [9](#), [11](#), [13](#)

Strong, [3](#), [5](#), [7](#), [10](#), [10](#), [13](#)

summary.longmi, [12](#)

Weak, [3](#), [5](#), [7](#), [10](#), [11](#), [13](#)