Package 'rProject'

December 22, 2022

Title Setup R Project

Version 0.0.0.9000
Description A collection of functions to setup R projects.
<pre>URL https://github.com/jeksterslab/rProject/,</pre>
https://jeksterslab.github.io/rProject/
<pre>BugReports https://github.com/jeksterslab/rProject/issues</pre>
License MIT + file LICENSE
Encoding UTF-8
Roxygen list(markdown = TRUE)
Depends R (>= 3.0.0)
Imports rprojroot, distro, devtools, covr, knitr, lintr, pkgdown, remotes, stats, styler, tinytex, utils
Suggests rmarkdown, testthat
RoxygenNote 7.2.3
NeedsCompilation no
Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (https://orcid.org/0000-0003-4818-8420)
Maintainer Ivan Jacob Agaloos Pesigan <r.jeksterslab@gmail.com></r.jeksterslab@gmail.com>
R topics documented:
Binary 2 Build 3 BuildIgnore 3 Clean 4 CleanPkg 4 CleanTinyTex 5 Coverage 5 DataAnalysis 6 DataProcess 6

Binary

	Dependencies
	Detritus
	Environment
	EnvironmentProject
	EnvironmentTokens
	LatexCompile
	LatexKnit
	LatexMake
	LibPaths
	Lint
	Manual
	PkgDevel
	PkgDevelGitHub
	PkgProject
	PkgProjectGitHub
	PkgProjectVersion
	PkgRepo
	Profile
	Project
	Site
	Style
	TinyTex
	VignettesPrecompile
Index	19

Binary

Setup Binaries not Included in the Package

Description

Setup Binaries not Included in the Package

Usage

Binary(path)

Arguments

path

Character string. Project path.

Author(s)

Build 3

Build Build Package

Description

Build Package

Usage

```
Build(path, vignettes = FALSE)
```

Arguments

path Character string. Project path. vignettes Logical. Build vignettes.

Author(s)

Ivan Jacob Agaloos Pesigan

BuildIgnore Build.Rbuildignore

Description

Build .Rbuildignore

Usage

```
BuildIgnore(path, project, add = NULL)
```

Arguments

path Character string. Project path.
project Character string. Project name.

add Character vector. Items to add in .Rbuildignore.

Author(s)

4 CleanPkg

Clean

Clean Files Generated on Build

Description

Delete all output files that are generated on automated build.

Usage

Clean(path)

Arguments

path

Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

CleanPkg

Clean R Packages

Description

Uninstall R packages with priority = "NA".

Usage

CleanPkg(path)

Arguments

path

Character string. Project path.

Author(s)

CleanTinyTex 5

 ${\tt CleanTinyTex}$

Clean ~/.TinyTex

Description

Uninstall TinyTex.

Usage

CleanTinyTex(path)

Arguments

path

Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Coverage

Code Coverage

Description

Code Coverage

Usage

Coverage(path)

Arguments

path

Character string. Project path.

Author(s)

6 DataProcess

DataAnalysis

Data Analysis

Description

Execute R scripts in data-analysis.

Usage

DataAnalysis(path, clean = FALSE)

Arguments

path Character string. Project path.

clean Logical. Remove all .Rds files in data-process and data-analysis before

running.

Author(s)

Ivan Jacob Agaloos Pesigan

DataProcess

Process Data

Description

Execute R scripts in data-process.

Usage

DataProcess(path, clean = FALSE)

Arguments

path Character string. Project path.

clean Logical. Remove all .Rds files in data-process before running.

Author(s)

Dependencies 7

Dependencies

Copy Dependencies to from .setup/r-dependencies to R

Description

Copy Dependencies to from .setup/r-dependencies to R

Usage

Dependencies(path)

Arguments

path

Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Detritus

Create detritus/tex/tex-fig-*

Description

Create detritus/tex/tex-fig-*

Usage

Detritus(path)

Arguments

path

Character string. Project path.

Author(s)

8 EnvironmentProject

Environment

 ${\it Setup}$. Renviron

Description

Setup . Renviron

Usage

Environment(path, project, tokens)

Arguments

path Character string. Project path.
project Character string. Project name.

tokens Named vector of tokens.

Author(s)

Ivan Jacob Agaloos Pesigan

EnvironmentProject

Set PROJECT Environment Variable

Description

Set PROJECT Environment Variable

Usage

EnvironmentProject(project)

Arguments

project

Character string. Project name.

Value

Returns project name.

Author(s)

EnvironmentTokens 9

EnvironmentTokens

Set Tokens

Description

Set Tokens

Usage

EnvironmentTokens(tokens)

Arguments

tokens

Named vector of tokens.

Value

Returns vector of secret tokens.

Author(s)

Ivan Jacob Agaloos Pesigan

LatexCompile

Compile Output of LatexKnit

Description

 $Compile\ Output\ of\ LatexKnit$

Usage

```
LatexCompile(path, clean = FALSE)
```

Arguments

path Character string. Project path.

clean Logical. Clean latexmk output except *.pdf

Author(s)

10 LatexMake

LatexKnit

Knit latexsrc/*.Rtex

Description

Knit latexsrc/*.Rtex

Usage

LatexKnit(path)

Arguments

path

Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

LatexMake

Compile Output of LatexKnit

Description

Compile Output of LatexKnit

Usage

LatexMake(path, clean = FALSE)

Arguments

path Character string. Project path.

clean Logical. Clean latexmk output except *.pdf

Author(s)

LibPaths 11

LibPaths

Add .library to Library Paths

Description

- creates a folder .library on the project path if it does not exist
- creates a .gitignore file inside .library if it does not exist
- adds .library to .libPaths()
- sets R_LIBS_USER to .library

Usage

LibPaths(path)

Arguments

path

Character string. Project path.

Value

Returns the path of .library.

Author(s)

Ivan Jacob Agaloos Pesigan

Lint

Lint Project

Description

Lint Project

Usage

Lint(path)

Arguments

path

Character string. Project path.

Author(s)

12 PkgDevel

Manual

Package Manual

Description

Package Manual

Usage

```
Manual(path, project)
```

Arguments

path Character

Character string. Project path.

project

Character string. Project name.

PkgDevel

Install Development Packages from CRAN

Description

Install Development Packages from CRAN

Usage

PkgDevel(path)

Arguments

path

Character string. Project path.

Author(s)

PkgDevelGitHub 13

PkgDevelGitHub

Install Development Packages from GitHub

Description

Install Development Packages from GitHub

Usage

PkgDevelGitHub(path)

Arguments

path

Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgProject

Install Project Packages from CRAN

Description

Install Project Packages from CRAN

Usage

```
PkgProject(path, pkg)
```

Arguments

path Character string. Project path.
pkg Character vector. R packages.

Author(s)

14 PkgProjectVersion

Description

Install Project Packages from GitHub

Usage

```
PkgProjectGitHub(path, pkg)
```

Arguments

path Character string. Project path.

pkg Character vector. GitHub packages.

Author(s)

Ivan Jacob Agaloos Pesigan

Description

Install Project Packages with Specific Version

Usage

```
PkgProjectVersion(path, pkg, ver)
```

Arguments

path Character string. Project path.

pkg Character vector. R packages.

ver Character vector. Version.

Author(s)

PkgRepo 15

PkgRepo

Setup RStudio Package Manager Repository Based on the Current Operating System

Description

Setup RStudio Package Manager Repository Based on the Current Operating System

Usage

```
PkgRepo(path)
```

Arguments

path

Character string. Project path.

Value

Returns the repository url.

Author(s)

Ivan Jacob Agaloos Pesigan

Profile

Setup . Rprofile

Description

```
Setup .Rprofile
```

Usage

```
Profile(path, project)
```

Arguments

path Character string. Project path.
project Character string. Project name.

Author(s)

Site Site

Project

Setup the project.Rproj file

Description

Setup the project.Rproj file

Usage

Project(path)

Arguments

path

Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Site

Build Website

Description

Build Website

Usage

Site(path)

Arguments

path

Character string. Project path.

Author(s)

Style 17

Style

Style Project

Description

Style Project

Usage

Style(path)

Arguments

path

Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

TinyTex

Install ~/.TinyTex

Description

Install ~/.TinyTex

Usage

TinyTex(path, force = FALSE)

Arguments

path

Character string. Project path.

force

Logical. Force install.

Author(s)

18 VignettesPrecompile

VignettesPrecompile

Precompile Vignettes

Description

Precompile Vignettes

Usage

VignettesPrecompile(path)

Arguments

path

Character string. Project path.

Author(s)

Index

```
Binary, 2
Build, 3
BuildIgnore, 3
Clean, 4
CleanPkg, 4
CleanTinyTex, 5
Coverage, 5
DataAnalysis, 6
DataProcess, 6
Dependencies, 7
Detritus, 7
Environment, 8
EnvironmentProject, 8
EnvironmentTokens, 9
LatexCompile, 9
LatexKnit, 10
LatexMake, 10
LibPaths, 11
Lint, 11
Manual, 12
PkgDevel, 12
PkgDevelGitHub, 13
PkgProject, 13
{\sf PkgProjectGitHub}, {\color{red} 14}
PkgProjectVersion, 14
PkgRepo, 15
Profile, 15
Project, 16
Site, 16
Style, 17
TinyTex, 17
VignettesPrecompile, 18
```