

Package ‘rProject’

July 26, 2023

Title Setup R Project

Version 0.0.3

Description A collection of functions to setup R projects.

URL <https://github.com/ijapesigan/rProject/>,
<https://ijapesigan.github.io/rProject/>

BugReports <https://github.com/ijapesigan/rProject/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Depends R (>= 3.5.0)

Imports cffr, covr, devtools, distro, knitr, lintr, pkgdown, quarto,
Rcpp, remotes, RefManageR, rmarkdown, roxygen2, rprojroot,
stats, styler, tinytex, utils

Suggests testthat

RoxygenNote 7.2.3

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph]
(<https://orcid.org/0000-0003-4818-8420>)

Maintainer Ivan Jacob Agaloos Pesigan <ijapesigan@gmail.com>

R topics documented:

Bib	2
Binary	3
Build	3
BuildIgnore	4
CFF	4

Clean	5
CleanPkg	5
CleanProj	6
CleanTinyTex	6
ConfigFiles	7
Coverage	7
DataAnalysis	8
DataProcess	8
Dependencies	9
Detritus	9
Environment	10
EnvironmentProject	10
EnvironmentTokens	11
InstallLocal	11
LatexCompile	12
LatexKnit	12
LatexMake	13
LibPaths	13
License	14
Lint	14
Manual	15
PkgDevel	15
PkgDevelGitHub	16
PkgProject	16
PkgProjectGitHub	17
PkgProjectVersion	17
PkgRepo	18
Profile	18
Project	19
Quarto	19
ReadMe	20
Site	20
Style	21
TinyTex	21
VignettesPrecompile	22
z	22

Index**23**

Bib

*Consolidate .bib files into a Single File***Description**

Consolidate .bib files into a Single File

Usage

Bib(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Binary

Setup Binaries not Included in the Package

Description

Setup Binaries not Included in the Package

Usage

Binary(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Build

Build Package

Description

Build Package

Usage

Build(path, vignettes = FALSE, dependencies = FALSE)

Arguments

path Character string. Project path.
vignettes Logical. Build vignettes.
dependencies Logical. Install package dependencies.

Author(s)

Ivan Jacob Agaloos Pesigan

BuildIgnore	<i>Build</i> .Rbuildignore
-------------	----------------------------

Description

Build .Rbuildignore

Usage

```
BuildIgnore(path, project, add = NULL)
```

Arguments

path	Character string. Project path.
project	Character string. Project name.
add	Character vector. Items to add to .Rbuildignore.

Author(s)

Ivan Jacob Agaloos Pesigan

CFF	<i>Build</i> CITATION.cff
-----	---------------------------

Description

Build CITATION.cff

Usage

```
CFF(path)
```

Arguments

path	Character string. Project path.
------	---------------------------------

Author(s)

Ivan Jacob Agaloos Pesigan

Clean*Clean Files Generated on Build*

Description

Delete all output files that are generated on automated build.

Usage

```
Clean(path, push = FALSE)
```

Arguments

path	Character string. Project path.
push	Logical. If push = TRUE clean in preparation for git push.

Author(s)

Ivan Jacob Agaloos Pesigan

CleanPkg*Clean R Packages*

Description

Uninstall R packages with priority = "NA".

Usage

```
CleanPkg(path)
```

Arguments

path	Character string. Project path.
------	---------------------------------

Author(s)

Ivan Jacob Agaloos Pesigan

`CleanProj`*Clean Project*

Description

Remove all files except `project.Rproj` and, optionally, `.library`.

Usage

```
CleanProj(path, lib = FALSE)
```

Arguments

<code>path</code>	Character string. Project path.
<code>lib</code>	Logical. If <code>lib = TRUE</code> , delete <code>.library</code> . If <code>lib = FALSE</code> , <code>.library</code> is not deleted.

Author(s)

Ivan Jacob Agaloos Pesigan

`CleanTinyTex`*Clean ~/.TinyTex*

Description

Uninstall TinyTex.

Usage

```
CleanTinyTex(path)
```

Arguments

<code>path</code>	Character string. Project path.
-------------------	---------------------------------

Author(s)

Ivan Jacob Agaloos Pesigan

ConfigFiles	<i>Setup Config Files</i>
-------------	---------------------------

Description

Setup Config Files

Usage

ConfigFiles(`git_user`)

Arguments

`git_user` Character string. Git user.

Details

This function requires a dotfiles GitHub repository.

Author(s)

Ivan Jacob Agaloos Pesigan

Coverage	<i>Code Coverage</i>
----------	----------------------

Description

Code Coverage

Usage

Coverage(`path`)

Arguments

`path` Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

DataAnalysis

Data Analysis

Description

Execute R scripts in data-analysis.

Usage

```
DataAnalysis(path, clean = FALSE)
```

Arguments

path	Character string. Project path.
clean	Logical. Remove all .Rds files in data-process and data-analysis before running.

Author(s)

Ivan Jacob Agaloos Pesigan

DataProcess

Process Data

Description

Execute R scripts in data-process.

Usage

```
DataProcess(path, clean = FALSE)
```

Arguments

path	Character string. Project path.
clean	Logical. Remove all .Rds files in data-process before running.

Author(s)

Ivan Jacob Agaloos Pesigan

Dependencies

Copy Dependencies to from .setup/r-dependencies to R

Description

Copy Dependencies to from .setup/r-dependencies to R

Usage

Dependencies(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Detritus

*Create detritus/tex/tex-fig-**

Description

Create detritus/tex/tex-fig-*

Usage

Detritus(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Environment	<i>Setup .Renvi</i> ron
-------------	-------------------------

Description

Setup .Renvi

Usage

Environment(path, project, tokens)

Arguments

path	Character string. Project path.
project	Character string. Project name.
tokens	Named vector of tokens.

Author(s)

Ivan Jacob Agaloos Pesigan

EnvironmentProject	<i>Set PROJECT Environment Variable</i>
--------------------	---

Description

Set PROJECT Environment Variable

Usage

EnvironmentProject(project)

Arguments

project	Character string. Project name.
---------	---------------------------------

Value

Returns project name.

Author(s)

Ivan Jacob Agaloos Pesigan

EnvironmentTokens	<i>Set Tokens</i>
-------------------	-------------------

Description

Set Tokens

Usage

```
EnvironmentTokens(tokens)
```

Arguments

tokens	Named vector of tokens.
--------	-------------------------

Value

Returns vector of secret tokens.

Author(s)

Ivan Jacob Agaloos Pesigan

InstallLocal	<i>Install Applications on Local Machine</i>
--------------	--

Description

Install Applications on Local Machine

Usage

```
InstallLocal(  
  what = c("tmux", "julia", "mpdemo", "lazygit", "pfetch", "quarto"),  
  all = FALSE,  
  force = FALSE  
)
```

Arguments

what	Character string. Vector of applications to install. Valid values include "tmux", "julia", "mpdemo", "lazygit", "pfetch", and "quarto".
all	Logical. If all = TRUE, ignore what and install all valid what values.
force	Logical. If force = TRUE, install whether or not the application is available in the system.

Author(s)

Ivan Jacob Agaloos Pesigan

LatexCompile	<i>Compile Output of LatexKnit</i>
--------------	------------------------------------

Description

Compile Output of LatexKnit

Usage

```
LatexCompile(path, clean = FALSE)
```

Arguments

path	Character string. Project path.
clean	Logical. Clean latexmk output except *.pdf

Author(s)

Ivan Jacob Agaloos Pesigan

LatexKnit	<i>Knit .setup/latex/*.Rtex</i>
-----------	---------------------------------

Description

Knit .setup/latex/*.Rtex

Usage

```
LatexKnit(path)
```

Arguments

path	Character string. Project path.
------	---------------------------------

Author(s)

Ivan Jacob Agaloos Pesigan

LatexMake	<i>Compile Output of LatexKnit</i>
-----------	------------------------------------

Description

Compile Output of LatexKnit

Usage

```
LatexMake(path, clean = FALSE)
```

Arguments

path	Character string. Project path.
clean	Logical. Clean latexmk output except *.pdf

Author(s)

Ivan Jacob Agaloos Pesigan

LibPaths	<i>Add .library to Library Paths</i>
----------	--------------------------------------

Description

- creates a folder .library on the project path if it does not exist
- creates a .gitignore file inside .library if it does not exist
- adds .library to .libPaths()
- sets R_LIBS_USER to .library

Usage

```
LibPaths(path)
```

Arguments

path	Character string. Project path.
------	---------------------------------

Value

Returns the path of .library.

Author(s)

Ivan Jacob Agaloos Pesigan

License	<i>Generate License File</i>
---------	------------------------------

Description

Generate License File

Usage

```
License(path, type = "mit")
```

Arguments

path	Character string. Project path.
type	Character string. License type. Available values include "mit" and "gpl3".

Author(s)

Ivan Jacob Agaloos Pesigan

Lint	<i>Lint Project</i>
------	---------------------

Description

Lint Project

Usage

```
Lint(path)
```

Arguments

path	Character string. Project path.
------	---------------------------------

Author(s)

Ivan Jacob Agaloos Pesigan

Manual	<i>Package Manual</i>
--------	-----------------------

Description

Package Manual

Usage

Manual(path, project)

Arguments

path	Character string. Project path.
project	Character string. Project name.

PkgDevel	<i>Install Development Packages from CRAN</i>
----------	---

Description

Install Development Packages from CRAN

Usage

PkgDevel(path)

Arguments

path	Character string. Project path.
------	---------------------------------

Author(s)

Ivan Jacob Agaloos Pesigan

PkgDevelGitHub

Install Development Packages from GitHub

Description

Install Development Packages from GitHub

Usage

PkgDevelGitHub(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgProject*Install Project Packages from CRAN*

Description

Install Project Packages from CRAN

Usage

PkgProject(path, pkg)

Arguments

path Character string. Project path.

pkg Character vector. R packages.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgProjectGitHub	<i>Install Project Packages from GitHub</i>
------------------	---

Description

Install Project Packages from GitHub

Usage

```
PkgProjectGitHub(path, pkg, ref = "HEAD")
```

Arguments

path	Character string. Project path.
pkg	Character vector. GitHub packages.
ref	Character vector. Git branch.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgProjectVersion	<i>Install Project Packages with Specific Version</i>
-------------------	---

Description

Install Project Packages with Specific Version

Usage

```
PkgProjectVersion(path, pkg, ver)
```

Arguments

path	Character string. Project path.
pkg	Character vector. R packages.
ver	Character vector. Version.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgRepo	<i>Setup RStudio Package Manager Repository Based on the Current Operating System</i>
---------	---

Description

Setup RStudio Package Manager Repository Based on the Current Operating System

Usage

PkgRepo(path)

Arguments

path Character string. Project path.

Value

Returns the repository url.

Author(s)

Ivan Jacob Agaloos Pesigan

Profile	<i>Setup .Rprofile</i>
---------	------------------------

Description

Setup .Rprofile

Usage

Profile(path, project)

Arguments

path Character string. Project path.
project Character string. Project name.

Author(s)

Ivan Jacob Agaloos Pesigan

Project	<i>Setup the project.Rproj file</i>
---------	-------------------------------------

Description

Setup the project.Rproj file

Usage

Project(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Quarto	<i>Render Quarto Project</i>
--------	------------------------------

Description

Render Quarto Project

Usage

Quarto(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

ReadMe

Build README.md

Description

Build README.md

Usage

ReadMe(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Site

Build Website

Description

Build Website

Usage

Site(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Style	<i>Style Project</i>
-------	----------------------

Description

Style Project

Usage

Style(path)

Arguments

path Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

TinyTex	<i>Install ~/.TinyTex</i>
---------	---------------------------

Description

Install ~/.TinyTex

Usage

TinyTex(path, bundle = "TinyTeX-2", force = FALSE)

Arguments

path Character string. Project path.

bundle The bundle name of TinyTeX (which determines the collection of LaTeX packages to install). See <https://github.com/rstudio/tinytex-releases#releases> for all possible bundles and their meanings.

force Logical. Force install.

Author(s)

Ivan Jacob Agaloos Pesigan

VignettesPrecompile	<i>Precompile Vignettes</i>
---------------------	-----------------------------

Description

Precompile Vignettes

Usage

```
VignettesPrecompile(path)
```

Arguments

path	Character string. Project path.
------	---------------------------------

Author(s)

Ivan Jacob Agaloos Pesigan

z	<i>Data from the Standard Normal Distribution</i>
---	---

Description

Data from the Standard Normal Distribution

Usage

```
z
```

Format

A vector of length 100.

Index

* **data**
z, [22](#)

Bib, [2](#)
Binary, [3](#)
Build, [3](#)
BuildIgnore, [4](#)

CFF, [4](#)
Clean, [5](#)
CleanPkg, [5](#)
CleanProj, [6](#)
CleanTinyTex, [6](#)
ConfigFiles, [7](#)
Coverage, [7](#)

DataAnalysis, [8](#)
DataProcess, [8](#)
Dependencies, [9](#)
Detritus, [9](#)

Environment, [10](#)
EnvironmentProject, [10](#)
EnvironmentTokens, [11](#)

InstallLocal, [11](#)

LatexCompile, [12](#)
LatexKnit, [12](#)
LatexMake, [13](#)
LibPaths, [13](#)
License, [14](#)
Lint, [14](#)

Manual, [15](#)

PkgDevel, [15](#)
PkgDevelGitHub, [16](#)
PkgProject, [16](#)
PkgProjectGitHub, [17](#)
PkgProjectVersion, [17](#)

PkgRepo, [18](#)
Profile, [18](#)
Project, [19](#)

Quarto, [19](#)

ReadMe, [20](#)

Site, [20](#)
Style, [21](#)

TinyTex, [21](#)

VignettesPrecompile, [22](#)
z, [22](#)