# Markdown Style Guide

Ivan Jacob Agaloos Pesigan

This guide covers `NEWS.md`, `README.Rmd`, vignettes (`.Rmd`, `.Rmd.orig`), Quarto (`.qmd`), `AGENTS.md`, and the files in `.setup/ai` and `.setup/logs`. It does not cover generated files (`README.md`, vignettes built from `.setup/vignettes`). Agents follow `.setup/ai/style/markdown.md`, which follows this guide and is changed together with it.

## 1 Line Breaks

Use semantic line breaks, as in LaTeX. There is no length limit. Tables and link lines stay whole. Existing files are reflowed when next edited; there are no pushes for layout alone.

## 2 Lists

Use `-` for bullets everywhere, `NEWS.md` too. Number lists `1.`, `2.`.

## 3 Headings

ATX headings (`#`) only, one `#` title per file, and no skipped levels. `NEWS.md` keeps pkgdown's `# <pkg> <version>` and `## <section>`.

## 4 Code

Fenced code blocks name a language (`r`, `bash`, `latex`, `yaml`). Use inline code for files, functions, commands, and variables.

## 5 Emphasis and Links

Use `**bold**` and `_italic_`. Links are inline with descriptive text, not "here". Bare URLs are in `<...>`.

## 6 Math

Math in `.Rmd` and `.qmd` files follows the math guide.

## 7 Tools

`make lint` reports (never fails on) bullets, headings, code fences, links, and math. `lintr` already checks the R chunks.

## References

R Core Team. (2026). *R: A language and environment for statistical computing*. R Foundation for Statistical Computing. Vienna, Austria. https://www.R-project.org/