Package 'rProject'

October 19, 2026

Title Setup R Project

Version 0.0.52

Description A collection of functions to setup R projects.

URL https://github.com/ijapesigan/rProject/, https://ijapesigan.github.io/rProject/

BugReports https://github.com/ijapesigan/rProject/issues

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Depends R (>= 3.5.0)

Imports BiocManager, cffr, covr, devtools, distro, jsonlite, knitr, lintr, pak, pkgdown, quarto, Rcpp, remotes, rmarkdown, roxygen2, rprojroot, stats, styler, tinytex, utils

Suggests testthat

Config/roxygen2/version 8.1.1.9000

NeedsCompilation no

Author Ivan Jacob Agaloos Pesigan [aut, cre, cph] (ORCID: <https://orcid.org/0000-0003-4818-8420>)

Maintainer Ivan Jacob Agaloos Pesigan <ijapesigan@gmail.com>

Contents

AI 3
AIGlobal 4
Bib 5
BibLib 5
Binary 6

Build . . . 6
BuildIgnore . . . 7
CFF . . . 7
Clean . . . 8
CleanPkg . . . 8
CleanProj . . . 9
CleanTinyTex . . . 9
ConfigFiles . . . 10
Coverage . . . 10
DataAnalysis . . . 11
DataCompress . . . 11
DataManifest . . . 12
DataPath . . . 12
DataProcess . . . 13
Dependencies . . . 14
Detritus . . . 14
Environment . . . 15
EnvironmentProject . . . 15
EnvironmentTokens . . . 16
InstallLocal . . . 16
LatexCompile . . . 17
LatexKnit . . . 17
LatexMake . . . 18
LatexTikzCompile . . . 18
LibAdd . . . 19
LibCheck . . . 20
LibFormat . . . 21
LibPaths . . . 22
License . . . 22
Lint . . . 23
Log . . . 23
Manual . . . 24
PkgDevel . . . 24
PkgDevelGitHub . . . 25
PkgProject . . . 25
PkgProjectBioconductor . . . 26
PkgProjectGitHub . . . 26
PkgProjectVersion . . . 27
PkgRepo . . . 27
Profile . . . 28
Project . . . 28
Public . . . 29
Quarto . . . 29
ReadMe . . . 30
SecretScan . . . 30
Site . . . 31
SizeCheck . . . 31
Spec . . . 32

Style 33
TinyTex 33
Verify 34
VignettesPrecompile 35
z 36

Index **37**

`AI` *Write the Project's AI Instructions*

Description

Writes the instruction files that AI tools read in this project, on top of the global instructions installed by `AIGlobal()`.

Usage

```
AI(path, type = NULL)
```

Arguments

`path`	Character string. Project path.
`type`	Character vector. Project types: any of `"package"`, `"cran"` (a package on CRAN or headed there; with `"package"`), `"manuscript"`, `"simulation"`, `"library"`, `"talk"`, and `"container"`.

Details

- `.setup/ai/project.md`: project facts that the user maintains. Created once and never overwritten.
- `.setup/todo/`: the user's to-do list, `todo.txt`, which agents read when planning and never edit, with a `.gitignore` that keeps the folder out of the public repository. Created only if the folder does not exist.
- `AGENTS.md` (Codex, Copilot CLI, Claude through `CLAUDE.md`), `CLAUDE.md` (Claude Code), and `.github/copilot-instructions.md` (Copilot in the IDE): generated, and rewritten when they change.

All of them are private (gitignored and excluded from the package build).

The project type comes from `type`, else from an `ai` list in `.setup/scripts/project.R` (e.g., `ai <- list(type = c("manuscript", "simulation"))`), else it is detected: `"simulation"` if `.sim/README.md` (which describes the simulation) exists, `"manuscript"` if a `*-manuscript*.Rtex` exists or the name starts with `man`, `"package"` and `"cran"` for a `cran-*` folder (its `project.R` names the package), `"library"` for `lib-*`, `"talk"` for `talks*`, `"container"` for `docker-*`, otherwise `"package"`.

Where the project lives (the private GitHub repository, the Overleaf project, and the public GitHub repository) comes from `.setup/repo/`, which `Project()` creates when it is missing.

The user chooses the Apptainer image and runs `apptainer exec`; the instructions tell agents not to pick an image.

Value

Returns the paths of the files that were written, invisibly.

Author(s)

Ivan Jacob Agaloos Pesigan

`AIGlobal` *Install Global AI Instructions*

Description

Copies the global AI instructions and Claude settings from `.setup/ai/global` in the project to the configuration folders of Claude Code, Codex, and GitHub Copilot in the home directory. Files are written only when their content changed. Existing files that differ are backed up with the suffix `.bak`.

Usage

```
AIGlobal(path, home = Sys.getenv("HOME"))
```

Arguments

`path`	Character string. Project path.
`home`	Character string. Home directory.

Details

Source	Installed to
`AGENTS.md`	`~/.claude/CLAUDE.md`
`AGENTS.md`	`~/.codex/AGENTS.md`
`AGENTS.md`	`~/.copilot/copilot-instructions.md`
`claude-settings.json`	`~/.claude/settings.json`

Value

Returns the paths of the files that were written.

Author(s)

Ivan Jacob Agaloos Pesigan

Bib *Consolidate .bib Files into a Single File*

Description

Joins the `.bib` files in `.setup/latex/bib` into `bib.bib`, verbatim and in file-name order, and copies it to `.setup/quarto/bib/quarto.bib` and `vignettes/vignettes.bib` when those folders exist. Without sources (a clone of the repository, which has only `bib.bib`), the existing `bib.bib` is copied. The source files are never rewritten: in `lib-*` projects they are the entries themselves (one entry per file, ASCII with LaTeX accents). `LibCheck()` validates them with biber.

Usage

```
Bib(path, bib_lib = FALSE)
```

Arguments

`path`	Character string. Project path.
`bib_lib`	Logical. If `bib_lib = TRUE`, build `bib.bib` from `lib-*` GitHub repositories.

Author(s)

Ivan Jacob Agaloos Pesigan

BibLib *Copy .bib Files from lib-* GitHUb Repositories*

Description

Copy .bib Files from lib-* GitHUb Repositories

Usage

```
BibLib(path)
```

Arguments

`path`	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Binary *Setup Binaries not Included in the Package*

Description

Setup Binaries not Included in the Package

Usage

```
Binary(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Build *Build Package*

Description

Build Package

Usage

```
Build(path, vignettes = FALSE, dependencies = FALSE)
```

Arguments

path	Character string. Project path.
vignettes	Logical. Build vignettes.
dependencies	Logical. Install package dependencies.

Author(s)

Ivan Jacob Agaloos Pesigan

BuildIgnore *Build* .Rbuildignore

Description

Build .Rbuildignore

Usage

```
BuildIgnore(path, project, add = NULL)
```

Arguments

path	Character string. Project path.
project	Character string. Project name.
add	Character vector. Items to add to .Rbuildignore.

Author(s)

Ivan Jacob Agaloos Pesigan

CFF *Build* CITATION.cff

Description

Build CITATION.cff

Usage

```
CFF(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Clean *Clean Files Generated on Build*

Description

Delete all output files that are generated on automated build.

Usage

```
Clean(path, push = FALSE)
```

Arguments

path	Character string. Project path.
push	Logical. If push = TRUE clean in preparation for git push: generated files are kept, and files matching *secrets* are deleted, except in hidden folders such as .setup.

Author(s)

Ivan Jacob Agaloos Pesigan

CleanPkg *Clean R Packages*

Description

Uninstall R packages with priority = "NA".

Usage

```
CleanPkg(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

CleanProj *Clean Project*

Description

Remove all files except `project.Rproj` and, optionally, `.library`.

Usage

```
CleanProj(path, lib = FALSE, sim = FALSE, sif = FALSE)
```

Arguments

`path`	Character string. Project path.
`lib`	Logical. If `lib = TRUE`, delete `.library`. If `lib = FALSE`, `.library` is not deleted.
`sim`	Logical. If `sim = TRUE`, delete `.sim`. If `sim = FALSE`, `.sim` is not deleted.
`sif`	Logical. If `sif = TRUE`, delete `.sif`. If `sif = FALSE`, `.sif` is not deleted.

Author(s)

Ivan Jacob Agaloos Pesigan

CleanTinyTex *Clean ~/.TinyTex*

Description

Uninstall `TinyTex`.

Usage

```
CleanTinyTex(path)
```

Arguments

`path`	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

ConfigFiles *Setup Config Files*

Description

Clones a public `dotfiles` GitHub repository and runs `make` in it. The clone ignores the global Git configuration, so URL rewrites to SSH host aliases do not apply and the repository is fetched anonymously over HTTPS. This also works inside a container without access to SSH keys.

Usage

```
ConfigFiles(repo = "ijapesigan/dotfiles")
```

Arguments

`repo`	Character string. GitHub repository in the form `owner/name`.

Author(s)

Ivan Jacob Agaloos Pesigan

Coverage *Code Coverage*

Description

Code Coverage

Usage

```
Coverage(path)
```

Arguments

`path`	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

`DataAnalysis` *Data Analysis*

Description

Execute R scripts in `data-analysis`.

Usage

```
DataAnalysis(path, clean = FALSE)
```

Arguments

`path`	Character string. Project path.
`clean`	Logical. Remove all `.Rds` files in `data-process` and `data-analysis` before running.

Author(s)

Ivan Jacob Agaloos Pesigan

`DataCompress` *Compress Data Files*

Description

Compresses data files in place with xz (e.g., `data.txt` becomes `data.txt.xz`), checks that the compressed copy reads back byte for byte, and then removes the original. Compressed files are binary, so they do not count as editable text in Overleaf (see `SizeCheck()`). Scripts that find files with `DataPath()` keep working unchanged.

Usage

```
DataCompress(path, files)
```

Arguments

`path`	Character string. Project path.
`files`	Character vector. Files to compress, relative to `path`.

Value

Returns the paths of the compressed files, invisibly.

Author(s)

Ivan Jacob Agaloos Pesigan

DataManifest *Write the Data Manifest*

Description

Writes `.setup/ai/data.md` (private), with one row for each file in the data tiers (`.setup/data-raw`, `.setup/data-private`, `.setup/data-external`): the file, its tier, size, MD5, status, the source and location (filled in by the user and kept on rewrite), and the scripts that use it.

Usage

```
DataManifest(path)
```

Arguments

`path`	Character string. Project path.

Details

External files are local only. One that is listed but missing on this machine is kept, marked "not on this machine"; one whose MD5 differs from the recorded one is marked "changed".

Value

Returns the manifest as a data frame, invisibly.

Author(s)

Ivan Jacob Agaloos Pesigan

DataPath *Find a Data File in the Data Tiers*

Description

Finds a data file by its plain name in the data tiers, in this order: `.setup/data-raw` (shareable), `.setup/data-private` (restricted; never public), and `.setup/data-external` (local only). The file can be stored as is or compressed (`.xz` or `.gz`); `utils::read.table()` and similar functions read compressed files directly.

Usage

```
DataPath(path, file, plain = FALSE)
```

Arguments

path	Character string. Project path.
file	Character string. Plain file name, e.g., "data.txt", even if it is stored as data.txt.xz.
plain	Logical. If TRUE, return a path to an uncompressed copy.

Details

With plain = TRUE, a compressed file is unpacked into .setup/data-cache (local only), for tools that need plain text, such as Mplus. The copy is refreshed when the compressed file changes.

Value

Returns the path of the file.

Author(s)

Ivan Jacob Agaloos Pesigan

DataProcess *Process Data*

Description

Execute R scripts in data-process.

Usage

```
DataProcess(path, clean = FALSE)
```

Arguments

path	Character string. Project path.
clean	Logical. Remove all .Rds files in data-process before running.

Author(s)

Ivan Jacob Agaloos Pesigan

Dependencies *Copy Dependencies to from* `.setup/r-dependencies` *to* `R`

Description

Copy Dependencies to from `.setup/r-dependencies` to `R`

Usage

```
Dependencies(path)
```

Arguments

`path`	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Detritus *Create* `detritus/tex/tex-fig-*`

Description

Create `detritus/tex/tex-fig-*`

Usage

```
Detritus(path)
```

Arguments

`path`	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Environment *Setup* .Renviron

Description

Setup .Renviron

Usage

```
Environment(path, project, tokens)
```

Arguments

path	Character string. Project path.
project	Character string. Project name.
tokens	Named vector of tokens.

Author(s)

Ivan Jacob Agaloos Pesigan

EnvironmentProject *Set* PROJECT *Environment Variable*

Description

Set PROJECT Environment Variable

Usage

```
EnvironmentProject(project)
```

Arguments

project	Character string. Project name.

Value

Returns project name.

Author(s)

Ivan Jacob Agaloos Pesigan

EnvironmentTokens *Set Tokens*

Description

Set Tokens

Usage

```
EnvironmentTokens(tokens)
```

Arguments

tokens	Named vector of tokens.

Value

Returns vector of secret tokens.

Author(s)

Ivan Jacob Agaloos Pesigan

InstallLocal *Install Applications on Local Machine*

Description

Install Applications on Local Machine

Usage

```
InstallLocal(
  what = c("tmux", "julia", "mpdemo", "lazygit", "fastfetch", "quarto"),
  all = FALSE,
  force = FALSE
)
```

Arguments

what	Character string. Vector of applications to install. Valid values include "tmux", "julia", "mpdemo", "lazygit", "fastfetch", and "quarto".
all	Logical. If all = TRUE, ignore what and install all valid what values.
force	Logical. If force = TRUE, install whether or not the application is available in the system.

Author(s)

Ivan Jacob Agaloos Pesigan

LatexCompile *Compile Output of* LatexKnit

Description

Compile Output of LatexKnit

Usage

```
LatexCompile(path, clean = FALSE)
```

Arguments

path	Character string. Project path.
clean	Logical. Clean latexmk output except *.pdf

Author(s)

Ivan Jacob Agaloos Pesigan

LatexKnit *Knit* .setup/latex/*.Rtex

Description

Knit .setup/latex/*.Rtex

Usage

```
LatexKnit(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

LatexMake *Compile Output of* LatexKnit

Description

Compile Output of LatexKnit

Usage

```
LatexMake(path, clean = FALSE)
```

Arguments

path	Character string. Project path.
clean	Logical. Clean latexmk output except *.pdf

Author(s)

Ivan Jacob Agaloos Pesigan

LatexTikzCompile *Compile Tikz*

Description

Compile Tikz

Usage

```
LatexTikzCompile(path, clean = FALSE)
```

Arguments

path	Character string. Project path.
clean	Logical. Clean latexmk output except *.pdf

Author(s)

Ivan Jacob Agaloos Pesigan

`LibAdd` *Add an Entry to the lib-* Library from a DOI*

Description

Drafts a biblatex entry from the DOI's Crossref record, in the house layout, and names the repository and file it belongs in:

Usage

```
LibAdd(doi, root, key = NULL, title = NULL, fields = NULL, write = FALSE)
```

Arguments

`doi`	Character string. The DOI.
`root`	Character string. The folder with local clones of the `lib-*` projects.
`key`	Character string or `NULL`. A key to use instead of the drafted one (e.g., with a suffix).
`title`	Character string or `NULL`. A title to use instead of the drafted one.
`fields`	Named character vector or `NULL`. Fields to set or replace (e.g., full author names or an abstract from the publisher's page).
`write`	Logical. If `TRUE`, write the file and run `LibCheck()` on its repository.

Details

- the entry type and the repository type from the Crossref type;
- `date` from the print issue (`published-print`), else the journal issue, else the first publication; the key year and the decade repository follow it;
- names and text with LaTeX accents, and `\%` and `\&` escaped;
- the key as `Family-Family-Family[-etal]-Year`, accents dropped;
- the abstract without its JATS tags;
- the ISSN and publisher reused from the library's other entries for the same journal;
- the title in a sentence-case draft.

It never invents a field: what Crossref does not have is left out. It lists what it cannot decide (initials only, an online-first date, a missing abstract, the title's proper nouns, a key already in use) as questions for the user.

Value

Returns a list with `file`, `text`, and `questions`, invisibly.

Author(s)

Ivan Jacob Agaloos Pesigan

`LibCheck` *Check the Entries of a lib-* Library*

Description

Checks every entry file in `.setup/latex/bib` of a `lib-<decade>-<type>` project against the house conventions.

Usage

```
LibCheck(path, root = NULL, error = FALSE)
```

Arguments

`path`	Character string. Project path.
`root`	Character string or `NULL`. A folder with local clones of the other `lib-*` projects, to find keys and DOIs used in more than one repository. If `NULL`, only this project is checked.
`error`	Logical. If `TRUE`, stop when there is an ERROR.

Details

- **ERROR:** the file does not parse or holds more than one entry; the file name is not `<repo>-<key>.bib`; the key does not follow `Family-Family-Family[-etal]-Year[a-z]` (three names, then `etal`, for four or more authors); the key year differs from the `date` year or lies outside the decade; a required field is missing; a non-ASCII character; an unescaped `%` in a text field; a key or DOI used twice; biber reports a missing mandatory field.
- **WARNING:** an entry type outside the repository's type; a lone suffix (`b` without `a`); other biber datamodel warnings.
- **STYLE:** not in the house layout (see `LibFormat()`); `\a'`-style accents; a page range with one hyphen; a DOI with a prefix; no final newline.

biber's warning that `publisher` is not an `@Article` field is the house convention and is not reported.

Value

Returns a data frame with the columns `file`, `key`, `severity`, `check`, and `message`, invisibly.

Author(s)

Ivan Jacob Agaloos Pesigan

`LibFormat` *Put the Entries of a lib-* Library in the House Layout*

Description

Rewrites each entry file in `.setup/latex/bib` of a `lib-*` project in the house layout, without changing what the entry says:

Usage

```
LibFormat(path, write = FALSE)
```

Arguments

`path`	Character string. Project path.
`write`	Logical. If `TRUE`, rewrite the files that change. If `FALSE`, only report them.

Details

- `@Type{Key,`, then one `field = {value},` per line, then `}`, and a final newline;
- fields in the house order: `author`, `editor`, `bookauthor`, `booktitle`, `date`, `journaltitle`, `title`, `subtitle`, the other fields alphabetically, then `abstract`, `publisher`, `keywords`, `library`, and `annotation`;
- field names in lower case and entry types in the house spelling (`Article`, `InBook`, `PhdThesis`, ...);
- `\a'`-style accents as `\'` (`{\a'e}` becomes `{\'e}`);
- page ranges with `--`;
- DOIs without a `https://doi.org/` or `doi:` prefix.

Files that do not parse, or that hold more than one entry, are left as they are (see `LibCheck()`).

Value

Returns the names of the files that change (or changed), invisibly.

Author(s)

Ivan Jacob Agaloos Pesigan

LibPaths *Add* .library *to Library Paths*

Description

- creates a folder .library on the project path if it does not exist
- creates a .gitignore file inside .library if it does not exist
- adds .library to .libPaths()
- sets R_LIBS_USER to .library

Usage

```
LibPaths(path)
```

Arguments

path	Character string. Project path.

Value

Returns the path of .library.

Author(s)

Ivan Jacob Agaloos Pesigan

License *Generate License File*

Description

Generate License File

Usage

```
License(path, type = "mit")
```

Arguments

path	Character string. Project path.
type	Character string. License type. Available values include "mit" and "gpl3".

Author(s)

Ivan Jacob Agaloos Pesigan

Lint *Lint Project*

Description

Lint Project

Usage

```
Lint(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Log *Create or Update a Change-Set Log*

Description

Creates `.setup/logs/YYYY-MM-DD-<topic>.md`, the log for one change set (one Overleaf push), and adds a pending row to `.setup/logs/index.md`. The log has the commit message skeleton, a "Pushes" table, and the list of files to update in Overleaf.

Usage

```
Log(
  path,
  topic,
  summary = topic,
  private = file.path(path, ".verify"),
  update = FALSE
)
```

Arguments

path	Character string. Project path.
topic	Character string. Short topic in kebab case (e.g., `"log-spec"`). The change-set log uses the same topic.
summary	Character string. First line of the commit message.
private	Character string. Path to a clone of the private repository at the pushed commit. By default `.verify` in the project.
update	Logical. If `TRUE`, refresh only the file lists of the newest existing log for `topic`.

Details

The file lists come from comparing the project with a clone of the private repository (by default `.verify`, kept by `.setup/scripts/verify.sh`), using the same rules as `Verify()`. Without a clone, the lists hold `TODO`.

Value

Returns the path of the log invisibly.

Author(s)

Ivan Jacob Agaloos Pesigan

`Manual` *Package Manual*

Description

Package Manual

Usage

```
Manual(path, project)
```

Arguments

`path`	Character string. Project path.
`project`	Character string. Project name.

`PkgDevel` *Install Development Packages from CRAN*

Description

Install Development Packages from CRAN

Usage

```
PkgDevel(path)
```

Arguments

`path`	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgDevelGitHub *Install Development Packages from GitHub*

Description

Install Development Packages from GitHub

Usage

```
PkgDevelGitHub(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgProject *Install Project Packages from CRAN*

Description

Install Project Packages from CRAN

Usage

```
PkgProject(path, pkg)
```

Arguments

path	Character string. Project path.
pkg	Character vector. R packages.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgProjectBioconductor *Install Project Packages from Bioconductor*

Description

Install Project Packages from Bioconductor

Usage

```
PkgProjectBioconductor(path, pkg)
```

Arguments

path	Character string. Project path.
pkg	Character vector. Bioconductor packages.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgProjectGitHub *Install Project Packages from GitHub*

Description

Install Project Packages from GitHub

Usage

```
PkgProjectGitHub(path, pkg, ref = "HEAD")
```

Arguments

path	Character string. Project path.
pkg	Character vector. GitHub packages.
ref	Character vector. Git branch.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgProjectVersion *Install Project Packages with Specific Version*

Description

Install Project Packages with Specific Version

Usage

```
PkgProjectVersion(path, pkg, ver)
```

Arguments

path	Character string. Project path.
pkg	Character vector. R packages.
ver	Character vector. Version.

Author(s)

Ivan Jacob Agaloos Pesigan

PkgRepo *Setup RStudio Package Manager Repository Based on the Current Operating System*

Description

Setup RStudio Package Manager Repository Based on the Current Operating System

Usage

```
PkgRepo(path)
```

Arguments

path	Character string. Project path.

Value

Returns the repository url.

Author(s)

Ivan Jacob Agaloos Pesigan

Profile *Setup* .Rprofile

Description

Setup .Rprofile

Usage

```
Profile(path, project)
```

Arguments

path	Character string. Project path.
project	Character string. Project name.

Author(s)

Ivan Jacob Agaloos Pesigan

Project *Setup the project.Rproj file*

Description

Setup the project.Rproj file

Usage

```
Project(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

Public *Check the Public Export*

Description

Checks the working tree that `make auto` is about to publish (after `clone.sh` swaps in the public `.git`): no private files (e.g., `.setup/ai/`, `.setup/logs/`, `AGENTS.md`), no file larger than 50 MB, and no tokens (`SecretScan()`) in the files that would be published. `make auto` calls `Public()` before `git add`, so a failed check stops the push.

Usage

```
Public(path)
```

Arguments

`path`	Character string. Project path.

Value

Returns the files that would be published, invisibly.

Author(s)

Ivan Jacob Agaloos Pesigan

Quarto *Render Quarto Project*

Description

Render Quarto Project

Usage

```
Quarto(path)
```

Arguments

`path`	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

ReadMe *Build README.md*

Description

Build README.md

Usage

```
ReadMe(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

SecretScan *Scan Project for Secrets*

Description

Searches text files in the project for strings that look like tokens (GitHub, Docker Hub, Quarto Pub, Overleaf, Codecov, OpenAI, Anthropic). Matches are reported with the value masked.

Usage

```
SecretScan(path, max_size = 5e+06, error = TRUE)
```

Arguments

path	Character string. Project path.
max_size	Numeric. Files larger than max_size bytes are skipped.
error	Logical. If TRUE, stop with an error when secrets are found.

Value

Returns a data frame of findings with the columns file, line, type, and match (masked).

Author(s)

Ivan Jacob Agaloos Pesigan

Site *Build Website*

Description

Build Website

Usage

```
Site(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

SizeCheck *Check a Project Against Overleaf's Limits*

Description

Measures what goes to Overleaf: every file in the project except local-only folders (`.git`, `.verify`, `.library`, `.Rproj.user`, `detritus`) and build output that `make` writes and Overleaf never gets (`docs`, `pkgdown`, `quarto`, `.setup/build`, `.setup/latex/pdf`, `.setup/quarto/bib`), the local-only data tiers (`.setup/data-external`, `.setup/data-cache`), and images (`.sif`).

Usage

```
SizeCheck(
  path,
  editable = 7,
  text_file = 2,
  file = 50,
  total = 100,
  files = 2000L,
  error = FALSE
)
```

Arguments

path	Character string. Project path.
editable	Numeric. Limit for all editable text, in MB.
text_file	Numeric. Limit for one editable text file, in MB.
file	Numeric. Limit for one file, in MB.
total	Numeric. Recommended limit for the whole project, in MB.
files	Integer. Limit for the number of files.
error	Logical. If TRUE, stop with an error when a check fails.

Details

- **Editable text** (fails): non-binary files in total above editable MB. Overleaf's GitHub sync stops above 7 MB.
- **Text file size** (fails): any non-binary file above text_file MB. Overleaf caps editable files at 2 MB.
- **File size** (fails): any file above file MB. Overleaf caps uploads at 50 MB.
- **Number of files** (fails): more than files files. Overleaf allows 2,000.
- **Total size** (warning): above total MB. Overleaf recommends under 100 MB with GitHub sync or git.
- **Duplicates** (warning): files of at least 1 MB with the same content.

The report also lists the largest text files and the largest files.

Value

Returns a data frame of checks with the columns check, status, and detail.

Author(s)

Ivan Jacob Agaloos Pesigan

Spec *Create a Spec*

Description

Creates .setup/ai/specs/YYYY-MM-DD-<topic>.md from a template. Every change set starts with a spec that the user approves.

Usage

```
Spec(path, topic, title = topic)
```

Arguments

path	Character string. Project path.
topic	Character string. Short topic in kebab case (e.g., "log-spec"). The change-set log uses the same topic.
title	Character string. Title of the spec.

Value

Returns the path of the spec invisibly.

Author(s)

Ivan Jacob Agaloos Pesigan

Style *Style Project*

Description

Style Project

Usage

```
Style(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

TinyTex *Install ~/.TinyTex*

Description

Install ~/.TinyTex

Usage

```
TinyTex(path, bundle = "TinyTeX-2", force = FALSE)
```

Arguments

path	Character string. Project path.
bundle	The bundle name of TinyTeX (which determines the collection of LaTeX packages to install). See https://github.com/rstudio/tinytex-releases#releases for all possible bundles and their meanings.
force	Logical. Force install.

Author(s)

Ivan Jacob Agaloos Pesigan

Verify *Verify an Overleaf Push*

Description

Checks a push from Overleaf to the private GitHub repository against the change-set log in `.setup/logs`.

Usage

```
Verify(
  path,
  private = file.path(path, ".verify"),
  log = NULL,
  record = FALSE,
  error = TRUE
)
```

Arguments

path	Character string. Project path.
private	Character string. Path to a clone of the private repository at the pushed commit. By default `.verify` in the project.
log	Character string. File name of the change-set log in `.setup/logs`. If `NULL`, the newest log with a pending push in `.setup/logs/index.md`, else the log named in the pushed commit message (`Log: .setup/logs/<log>`), as for a fix-up push.
record	Logical. If `TRUE`, write the commit and the result in the log's "Pushes" table and in `.setup/logs/index.md`, filling the pending row, or adding a row when there is none.
error	Logical. If `TRUE`, stop with an error when a check fails.

Details

The checks, and when each fails:

- **New commit:** the commit is already recorded in `index.md` (`.verify` is stale, or there was no new push). Nothing is recorded.
- **Listed files:** a file listed under "Files to update in Overleaf" is missing from or differs in the private repository. The list is the one of the pushed commit: the section of the log with a code block that starts with the commit's first line (the top-level lists for the log's own commit message; the lists inside a later push's ## section, none for a push of records only). If no block matches, every list in the log is used.
- **Deletions:** a file listed under "Delete in Overleaf" is still in the private repository.
- **Unlisted changes:** (warning only) other files differ between the project and the private repository (`.setup/notes/claude.txt`, the resume commands, and `.setup/todo/`, the user's to-do list, are not counted).
- **Commit message:** (warning only) the last commit message does not end with `Log: .setup/logs/<log>`.
- **Secrets:** `SecretScan()` finds a token in the private repository.
- **Public export:** a file that `make auto` would publish is private (e.g., `.setup/ai/`, `.setup/logs/`, `.setup/repo/`, `AGENTS.md`) or larger than 50 MB.
- **Repo info:** `.setup/repo/private-overleaf.md` is not an Overleaf project URL (for example, a share link, which grants access). Warning only: a file in `.setup/repo/` is missing, `private-github.md` differs from the `.verify` remote, or `public-github.md` differs from the repository in `clone.sh`.

Generated files (e.g., `NAMESPACE`, `man/`), local folders (e.g., `.library`), and secret files are never compared.

The private repository must be cloned on the host, because SSH keys are not available in the container. `.setup/scripts/verify.sh` clones or pulls it into `.verify` (local only; never uploaded) and then calls `Verify()`.

Value

Returns a data frame of checks with the columns `check`, `status`, and `detail`.

Author(s)

Ivan Jacob Agaloos Pesigan

`VignettesPrecompile` *Precompile Vignettes*

Description

Precompile Vignettes

Usage

```
VignettesPrecompile(path)
```

Arguments

path	Character string. Project path.

Author(s)

Ivan Jacob Agaloos Pesigan

---

z *Data from the Standard Normal Distribution*

Description

Data from the Standard Normal Distribution

Usage

```
z
```

Format

A vector of length 100.

Index

∗ **data**
    z, 36

AI, 3
AIGlobal, 4
AIGlobal(), *3*

Bib, 5
BibLib, 5
Binary, 6
Build, 6
BuildIgnore, 7

CFF, 7
Clean, 8
CleanPkg, 8
CleanProj, 9
CleanTinyTex, 9
ConfigFiles, 10
Coverage, 10

DataAnalysis, 11
DataCompress, 11
DataManifest, 12
DataPath, 12
DataPath(), *11*
DataProcess, 13
Dependencies, 14
Detritus, 14

Environment, 15
EnvironmentProject, 15
EnvironmentTokens, 16

InstallLocal, 16

LatexCompile, 17
LatexKnit, 17
LatexMake, 18
LatexTikzCompile, 18
LibAdd, 19
LibCheck, 20
LibCheck(), *5*, *19*, *21*
LibFormat, 21
LibFormat(), *20*
LibPaths, 22
License, 22
Lint, 23
Log, 23

Manual, 24

PkgDevel, 24
PkgDevelGitHub, 25
PkgProject, 25
PkgProjectBioconductor, 26
PkgProjectGitHub, 26
PkgProjectVersion, 27
PkgRepo, 27
Profile, 28
Project, 28
Project(), *3*
Public, 29

Quarto, 29

ReadMe, 30

SecretScan, 30
SecretScan(), *29*, *35*
Site, 31
SizeCheck, 31
SizeCheck(), *11*
Spec, 32
Style, 33

TinyTex, 33

utils::read.table(), *12*

Verify, 34
Verify(), *24*

VignettesPrecompile, 35

z, 36