

Coop Discounts Hyper Market

API Integration Documentation

Web & Mobile Application

Base URL	http://cooperp.freedomdns.org:8076
Database	staging-apr17
Auth Key	by_AJR=1 (required on every request)
Backend	Odoo 19 REST API
Contact	info@coop-discounts.com +971 55 594 4719
Address	Al Ghandi Complex, Showroom 03, Nadd Al Hamar, Dubai, UAE

Version 1.0 — May 2025

Overview

This document covers all API endpoints available in the Coop Discounts backend (Odoo 19). It is intended for developers integrating the website and Flutter mobile application. All APIs follow a consistent REST pattern and require the `by_AJR=1` query parameter.

Authentication Rules

Public (No Auth)	Banners/Sliders, Categories, Products
Session Required	Orders, Cart, Invoices, Loyalty, Contacts
User ID 2 Only	Web Settings / Config

NOTE: After login, the `session_id` cookie is set automatically by the browser. For mobile apps, extract `session_id` from the response and include it in subsequent request headers. Banners, categories, and products do NOT require authentication.

1 Startup / Banner Sliders

These are fixed slider IDs configured in the backend. Each returns a `data[]` object with `image_ids[]` containing slide images and linked products. No authentication required.

ID	Name	Platform	Usage
12	Company Logo	Web & Mobile	<code>banner_image</code> = company logo path. Use for header logo on web and app.
13	Splash Intro	Mobile Only	Mobile app splash/loading screen. Not needed on website.
10	Welcome Banners	Mobile Only	4 onboarding slides shown on first app launch. Not needed on website.
9	Main Home Slider	Web & Mobile	<code>image_ids[].image</code> = slide image paths. Full-width hero slider on homepage.
2	Deal of the Day	Web & Mobile	<code>image_ids[].product_id[].id</code> = product IDs. Show below main slider.
1	Best Sellers	Web & Mobile	Same structure as Deal of the Day. Show below Deal of the Day.
3	Recommended For You	Web & Mobile	Personalised product recommendations.
4	Featured Products	Web & Mobile	Curated featured product list.
5	Fresh Pick Today	Web & Mobile	Fresh grocery picks for the day.
8	Shop By Brand	Web & Mobile	<code>image_ids[].image</code> = brand logo images. Show as horizontal brand scroll.

GET	/api/deal-day-slider/{id}?by_AJR=1	Get specific slider by ID (use IDs from table above)
GET	/api/deal-day-slider?by_AJR=1	List all deal sliders

2 Web Settings (User ID 2 Only)

Restricted endpoints for website configuration. Must pass user_id=2. Call on page/app load.

GET	/api/config-settings/create?by_AJR=1&user_id=2	Create settings instance — call once on startup
GET	/api/config-settings?by_AJR=1&user_id=2	View current website settings

3 Authentication

Login — POST request, returns session cookie and user data.

```
POST /web/session/authenticate
Body: {
  "jsonrpc": "2.0",
  "method": "call",
  "params": {
    "db": "staging-apr17",
    "login": "user@email.com",
    "password": "yourpassword"
  }
}
```

Response fields to save: uid, name, partner_id, session_id (from cookie)

GET	/api/contacts/update?name=&email;=&=&deviceid;=&firebase;=&latitude;=&longitude;=&by;_AJR=1	After login — update profile with device info, location, Firebase ID
GET	/api/user/{user_id}/update?by_AJR=1&password;=newpassword	Update password
GET	/api/contacts/new_registration?name=&email;=&=&deviceid;=&firebase;=&by;_AJR=1	Register new customer account
POST	/web/session/destroy	Logout — clears session cookie

4 Categories (No Auth Required)

Use `/api/website-category` for the storefront. The `product_tmpl_ids[]` array contains the product IDs linked to each category — use these to filter products on the shop page.

GET	<code>/api/website-category?by_AJR=1</code>	All website categories for storefront display
GET	<code>/api/website-category/{id}?by_AJR=1</code>	Category detail — includes <code>product_tmpl_ids[]</code>
GET	<code>/api/product-category?by_AJR=1</code>	Internal product category tree
GET	<code>/api/product-category?by_AJR=1&domain;=[('name', 'i like', 'groceries')]</code>	Search categories by name

Field	Type	Description
<code>id</code>	<i>Integer</i>	Category ID
<code>name</code>	<i>String</i>	Category name
<code>image_1024</code>	<i>String</i>	Image path — prepend base URL to display
<code>product_tmpl_ids[]</code>	<i>Array</i>	Product template IDs belonging to this category

5 Products (No Auth Required)

GET	<code>/api/product-template?by_AJR=1&limit;=10&offset;=0</code>	Product list — page 1
GET	<code>/api/product-template?by_AJR=1&limit;=10&offset;=10</code>	Product list — page 2 (increment Offset by limit)
GET	<code>/api/product-template/{id}?by_AJR=1</code>	Product detail by template ID
GET	<code>/api/product-template?by_AJR=1&domain;=[('name', 'i like', 'milk')]</code>	Search products by name
GET	<code>/api/product-template?by_AJR=1&domain;=[('barcode', '=', '8801073143203')]</code>	Search by barcode
GET	<code>/api/product?by_AJR=1</code>	Product variants list
GET	<code>/api/product/{variant_id}?by_AJR=1</code>	Variant detail by variant ID

Field	Type	Description
<code>id</code>	<i>Integer</i>	Product template ID
<code>name</code>	<i>String</i>	Product name — strip SKU prefix [XXXXXX] before displaying
<code>image_1024</code>	<i>String</i>	Image path — prepend base URL: <code>base_url + image_1024</code>
<code>list_price</code>	<i>Float</i>	Selling price

standard_price	Float	Cost / compare-at price
barcode	String	Product barcode
product_variant_id[]	Array	Variant objects {id, name} — use id for order lines
qty_available	Float	Stock quantity — 0 means Out of Stock
website_ribbon_id	Array	Promo ribbon label e.g. "Sale", "New"
type[]	Array	"service" type should be hidden from storefront

6 Orders (Session Required)

Add to Cart flow: Step 1 — Create order to get order_id. Step 2 — Add order lines using the product variant ID.

GET	/api/order/create_order?by_AJR=1&partner;_id={partner_id}	Create order — returns rec_id (order ID)
GET	/api/order?by_AJR=1&all;_fields=1	View all orders (full details)
GET	/api/order/{order_id}?by_AJR=1	View order detail
GET	/api/order/{order_id}/update?by_AJR=1&origin;=WebOrder¬e;=instructions	Update order fields

7 Cart / Order Lines (Session Required)

NOTE: product_id in order lines must be the VARIANT ID (product_variant_id[0].id from product response), NOT the template ID.

GET	/api/order-line/create?by_AJR=1&_id={id}&product;_id={variant_id}&product;_uom_qty=1	Add item — returns rec_id (line ID)
GET	/api/order-line/{line_id}/update?by_AJR=1&product;_uom_qty=2	Update quantity
GET	/api/order/{order_id}/remove_card_item?by_AJR=1&line;_ids=[1,2]	Remove item(s) from cart
GET	/api/order-line?by_AJR=1&domain;=[('order_id','=',{order_id})]	View all lines for an order
GET	/api/order-line/{line_id}?by_AJR=1	View single order line
GET	/api/delivery-method/?by_AJR=1	Available delivery methods

8 Checkout & Payment (Session Required)		
GET	/api/payment-provider?by_AJR=1&domain;=[('state','in',['enabled'])]	Get enabled payment providers
GET	/api/payment-provider/{provider_id}?by_AJR=1	Payment provider detail
GET	/api/order/{order_id}/get_or_create_transaction?by_AJR=1&args;=[{provider_id}]	Create payment transaction — returns transaction ID
GET	/api/order/{order_id}/order_transaction_mark_done?by_AJR=1&args;=[{tx_id}]&transaction;_id={tx_id}	Mark payment done (gateway callback) — auto-creates invoice
9 Invoices (Session Required)		
GET	/api/order/{order_id}/create_invoice?by_AJR=1	Create invoice from order (also auto-triggered by mark_done)
GET	/api/invoice/?by_AJR=1	View all invoices
GET	/api/invoice/{invoice_id}?by_AJR=1	Invoice detail
GET	/api/invoice/{invoice_id}/update?by_AJR=1&ref;=your-reference	Update invoice
10 Inventory & Delivery Orders (Session Required)		
GET	/api/delivery-order?by_AJR=1	View delivery orders / stock movements
GET	/api/delivery-order/{id}?by_AJR=1	Delivery order detail
GET	/api/delivery-order/{id}/update?by_AJR=1¬e;=your+note	Update delivery order
11 Loyalty & Promotions (Session Required)		
GET	/api/loyalty-coupon?by_AJR=1&domain;=[('partner_id','=',{partner_id})]	Customer loyalty coupons
GET	/api/loyalty-program?by_AJR=1	Loyalty programs list
GET	/api/loyalty-reward/{id}?by_AJR=1&user;_id=2	Loyalty reward detail
GET	/api/order/{order_id}/apply_loyalty_point?by_AJR=1&reward;_id={id}&cart;_id={id}	Apply loyalty/coupon to order
GET	/api/loyalty-card?by_AJR=1	Customer loyalty cards

12	Customer Account (Session Required)	
GET	/api/contacts?by_AJR=1	All contacts
GET	/api/contacts/{partner_id}?by_AJR=1	Customer profile — name, email, phone, address, image, gender, etc.
GET	/api/contacts/{partner_id}/update?by_AJR=1&name;=&email;=☛=&street;=&city;=&gender;=3_1024=	Update profile fields
GET	/api/country?by_AJR=1	Countries list
GET	/api/country-state?by_AJR=1	Country states list

! Homepage Section Order (Web)			
#	Section	API Endpoint	Notes
1	Main Home Slider	/api/deal-day-slider/9	Full-width hero image carousel
2	Promo Strip	Static	Free Delivery · Returns · Secure Payment · Support
3	Category Row	/api/website-category	Horizontal scrollable category chips with images
4	Deal of the Day	/api/deal-day-slider/2	Horizontal product scroll with countdown timer
5	Best Sellers	/api/deal-day-slider/1	Horizontal product scroll
6	Recommended	/api/deal-day-slider/3	Horizontal product scroll
7	Featured Products	/api/deal-day-slider/4	Horizontal product scroll
8	Fresh Pick Today	/api/deal-day-slider/5	Horizontal product scroll
9	Shop By Brand	/api/deal-day-slider/8	Brand logo scroll using image_ids[].image
10	All Products Grid	/api/product-template?limit=10	5-column product grid with pagination

! Shop Page Layout	
LEFT SIDEBAR	RIGHT PANEL
Category list from /api/website-category with images and product count. On category click: load product_tmpl_ids[] from category detail endpoint, then filter products by those IDs.	Product grid from /api/product-template. Supports: name search, barcode search, sort by price/name, price range filter, pagination with limit & Offset.

! Critical Notes for Developers	
CORS (Web only)	Direct browser calls to the Odoo backend are blocked by CORS security. Solution: run a Node.js reverse proxy on the web server. Browser → /proxy/api/... → Node.js → Odoo. This does NOT affect the Flutter mobile app or Postman — they connect directly to Odoo.

Image Paths	All image fields (image_1024, banner_image, etc.) return relative paths. Always prepend the base URL before displaying. Wrong: /web/image/product.template/123/image_1024 Right: http://cooperp.freeddns.org:8076/web/image/product.template/123/image_1024
Product Name Cleanup	Product names may contain an internal SKU prefix like [115755]. Strip everything inside and including the square brackets before displaying to customers. E.g. "[115755] SAMYANG RAMEN" → "SAMYANG RAMEN"
Variant ID for Order Lines	The product_id parameter when creating an order line must be the VARIANT ID from product_variant_id[0].id in the product response — NOT the template ID. Using the template ID will cause errors.
Out of Stock Detection	qty_available === 0 means the product is out of stock. Disable the Add to Cart button and display an "Out of Stock" label. Values above 0 indicate available stock quantity.
Session Handling	Browser: session cookie is set automatically after login — no extra code needed. Mobile (Flutter): extract session_id from the Set-Cookie response header and include it in all subsequent authenticated request headers.
Pagination	Use limit and Offset parameters for all list endpoints. Start with Offset=0, then increment by limit for each subsequent page. Example: limit=10&Offset=0 (page 1), limit=10&Offset=10 (page 2).

Coop Discounts Hyper Market

Al Ghandi Complex, Showroom 03, Nadd Al Hamar, Dubai, UAE

info@coop-discounts.com | +971 55 594 4719 | Open Daily 8AM – 12AM

For integration support, please contact the development team with your specific endpoint questions.