



**Try command xterm & again and run ps aux command from a standard terminal. Can you find it in?**

```
:~$ xterm &
```

```
:~$ ps aux - in a new xterm
```

...

Here comes a list with active processes. xterm 5819 is in the end of that list.

**Terminal you have just started has a white background. Run a command from that xterm:**  
xterm -bg red &

**to get a red terminal window. Try to move red xterm window and check whether black xterm is located on background. Give a command ps aux and check how many lines with xterm you will find now. Each line corresponds to one xterm process.**

```
:~$ xterm -bg red &
```

```
:~$ ps aux - there are 2 xterm processes
```

**Write next command in a red xterm:**

```
xterm -bg green &
```

**You got now a green xterm window. Run ps aux from a standard terminal, that is still active. Do you see that green xterm in a list?**

```
:~$ xterm -bg green &
```

```
:~$ ps aux - there are 3 xterm processes now
```

**Start a yellow xterm now (do it from a green xterm) and run ps aux to see that yellow xterm is also presented in i list**

```
:~$ xterm -bg yellow &
```

**Run a following command from a standard terminal:**

```
ps auxf
```

```
:~$ ps auxf
```

**What do you see there? Maximize a window to see whole lines.**

**Open another xterm window with blue background from a red terminal.**

```
xterm -bg blue &
```

```
:~$ xterm -bg blue & - from a red xterm
```

**Run command ps auxf from original terminal. What do you see in output?**

```
:~$ ps auxf - screenshot shown on next page
```



### C) End process with kill command.

**Open couple terminals. Check if they are present in ps list. Stop one terminal with kill command.**

```
:~$ xterm &           - from original terminal
:~$ xterm -bg gray &   - from a new white xterm
:~$ kill -9 7298        - killing white xterm from original terminal
```

**Start a time-consuming process, like that:**

```
find / -name "*" -print -exec grep -n "clock" {} \; &
```

**Start that find process as a background process (with &-char). Process writes quite a lot of text to screen and takes some time. Check if you can find it in ps list.**

**Hint: it can be usefule to run ps command from another terminal.**

```
:~$ find / -exec ls -l {} \; &   - from original terminal (that command takes more time)
```

```
:~$ xterm ps auxf                - from grey xterm
```

....

Looks like find command is being run from dev0 (original terminal) and has process nr. 30827.

**How can you end this process while it is running? Explain.**

```
:~$ kill -9 30827              - from grey terminal
```

It works fine

Process listing out all files in long format has stopped.

When I press enter it comes a message:

```
[9]+ Killed    find / -exec ls -l {} \;
```

### D) More about parent-child processes.

**Start same find process once again and use piping now. Send output from a first command to less command. Explain a connection between two processes. How can you stop both find and less process?**

```
:~$ xterm &
:~$ find / -exec ls -l {} \; | less &   - from original terminal
:~$ ps auxf                             - from a new white xterm
:~$ kill -9 17880                        - to kill find process
:~$ kill -9 17881                        - to kill less process
```

Looks like less process runs right after find process, probably they are running together, or less process was called by already running find process.

## E) Daemon-prosesser.

**Use ps aux command again and find all daemon processes from that list. Use Google and find out what kind of processes they are.**

```
:~$ ps aux | grep daemon | wc -l
```

- there is 30 daemon processes together.  
Daemon processes are Linux programs running in background.

## F) Login from another pc.

**Find a daemon process called sshd. It can be installed via Software Center. What does this process? Check in Google. Create then a new user account on your pc. Use ssh command and try to login on that new account from your account.**

SSH – secure shell. It is used for secure connection between two hosts in unsecure network.

```
:~$ ps aux | grep sshd
```

- no result, ssh shall be installed

```
:~$ sudo apt-get update
```

```
:~$ sudo apt-get install openssh-client
```

- to install ssh on client pc (pc u will connect from)

```
:~$ sudo apt-get install openssh-server
```

- to install ssh on server pc (pc u will connect to)

```
:~$ sudo systemctl status ssh
```

- to check that ssh is running

```
:~$ sudo systemctl start ssh
```

- if not, we start it manually

```
:~$ ip a
```

- to determine your ip address, write it down

```
:~$ sudo lsof -i -P -n | grep LISTEN
```

- to check if firewall allows remote access.

Look for open ports, port 22 shall be here.

```
:~$ ssh user1@(ip address here)
```

Are you sure you want to continue connecting - yes

user1@(ip address)'s password: type it

user1@debian:~\$

That works fine, type exit to go back to your account when you are done.

## G) System Monitor

**Start a System Monitor. Find out following: what is your Linux kernel number? What is Gnome version? Give a definition to Gnome. Find info about RAM and CPU on your PC. Check what processes are running now. Which one uses most CPU time? Most memory? Check total use of CPU. If you have several CPUs find out whether all of them are used.**

~\$ uname -r  
4.19.0-12-amd64 - command to check a kernel version

~\$ gnome-shell --version  
GNOME Shell 3.30.2 - command to check GNOME version

GNOME is a free and open-source desktop environment for Unix-like operating systems.  
... GNOME 3 is the default desktop environment on many major Linux distributions including Fedora, Debian ..

Starting system monitor..

Memory  
1.0GiB(27.3%) of 3.7 GiB

4 CPU, Intel Pentium Silver prosessor.

gnome-system-monitor	- uses most cpu-time (around. 4%)
gnome-shell	- uses most memory (84.5 MiB)
CPU History	- curve goes up to 30%

CPU1 and CPU2 are used, while CPU3 and CPU4 stands still, then otherwise.