

<https://highlightjs.org/usage/>

<https://github.com/highlightjs/highlight.js/blob/master/src/languages/pgsql.js>

git clone <https://github.com/highlightjs/highlight.js.git>

<html>

<!--color style: default, dark, vs, xcode, ...--> <link rel="stylesheet"
href="https://cdnjs.cloudflare.com/ajax/libs/highlight.js/9.15.10/styles/vs.min.css">

<script src="https://cdnjs.cloudflare.com/ajax/libs/highlight.js/9.15.10/highlight.min.js"></script>

<!--language sql: --> <script
src="https://cdnjs.cloudflare.com/ajax/libs/highlight.js/9.15.10/languages/pgsql.min.js"></script>

<script>hljs.initHighlightingOnLoad();</script>

<pre style="white-space: pre-wrap;"><code class="pgsql">

```
CREATE TABLE calltraces (  
  calltrace_id serial NOT NULL,  
  start_time timestamp without time zone,  
  end_time timestamp without time zone,  
  incomplete boolean NOT NULL DEFAULT false,  
  categories integer[],  
  location character varying(50),  
  tracelogids character varying[],  
  reset_tracelogids character varying[],  
  sourceaddresses character varying[],  
  nurses boolean[],  
  cache_np timestamp,  
  cache_accepted timestamp,  
  cache_cat_changed timestamp,  
  CONSTRAINT calltraces_pkey PRIMARY KEY (calltrace_id)  
);
```

</code></pre>

</html>