

# Using Weakly Trained GANs to produce 3D Models

Kelechi M. Ikegwu<sup>1</sup>; Hsuan-Yu Chen<sup>2</sup>; Jiayi Cao<sup>3</sup>; Smit Desai<sup>4</sup>

Illinois Informatics Institute<sup>1</sup>; Department of Computer Science<sup>2,3</sup>; School of Information Sciences<sup>4</sup>

ikegwu2@illinois.edu<sup>1</sup>; hychen2@illinois.edu<sup>2</sup>; jcao7@illinois.edu<sup>3</sup>; smitad2@illinois.edu<sup>4</sup>

Ranjitha Kumar

Department of Computer Science  
ranjitha@illinois.edu

## ABSTRACT

Generative Adversarial Networks (GAN) have become the de-facto standard for generative models. However large amounts of data are required to achieve excellent performance which makes GANs challenging to apply to sparse datasets. In order to utilize GANs with sparse datasets we propose using weakly training GANs to produce generated models which we then use to augment existing data. In this paper we utilize 2 classes of a popular 3D dataset called 3DShapeNet to train on. Next data augmentation is formed on the original models, lastly we conduct a study to assess our models on Amazon Mechanical Turk.

## Author Keywords

General Adversarial Networks; 3D-Models; Data Creation; Data Augmentation

## ACM Classification Keywords

H.5.m. Information Interfaces and Presentation (e.g. HCI): Miscellaneous; I.2.m. Artificial Intelligence: Miscellaneous; I.4.m. Image Processing and Computer Vision: Miscellaneous

## INTRODUCTION

Theyre a multitude of application areas where generative models are promising method to solving certain problems. Generative Adversarial Networks (GAN) [2] is a particular model which is becoming the de-facto standard for generative models. However these models generally require a lot of data to generate sufficient results.

As an attempt to solve this problem we propose using the latent spaces from weakly trained GANs with sparse datasets to augment existing data. In the subsequent sections we frame our work with respect research that has been conducted with GANs, we discuss about our methodology for transforming

data, produced models, and perform an evaluation of our produced models.

## RELATED WORKS

The foundation of this research is based on prior work. We use a rich 3D model repository called ShapeNet [1] which contains a multitude of semantic categories organized under WordNets taxonomy [3]. In particular we utilize the table and mug categories of ShapeNet.

Hychen talk about binvox and why voxel format is used with voxnet paper

For our model we try to learn the probabilistic latent space of tables and chairs using Wu. J, Zhang. C, Xue. T, et. als work in [4]. All of the parameters are the same however, the generator  $G$  produces  $32 \times 32 \times 32$  object, our discriminator  $D$  only accepts models with the size of  $32 \times 32 \times 32$ , the learning rate is .003.

## METHODOLOGY

### GENERATED RESULTS

Your paper's title, authors and affiliations should run across the full width of the page in a single column 17.8 cm (7 in.) wide. The title should be in Helvetica 18-point bold; use Arial if Helvetica is not available. Authors' names should be in Times Roman 12-point bold, and affiliations in Times Roman 12-point. For more than three authors, you may have to place some address information in a footnote, or in a named section at the end of your paper. Please use full international addresses and telephone dialing prefixes. Leave one 10-pt line of white space below the last line of affiliations.

## EVALUATION

## CONCLUSION & FUTURE WORK

## REFERENCES

1. Chang, A. X., Funkhouser, T., Guibas, L., Hanrahan, P., Huang, Q., Li, Z., Savarese, S., Savva, M., Song, S., Su, H., Xiao, J., Yi, L., and Yu, F. ShapeNet: An Information-Rich 3D Model Repository. Tech. Rep. arXiv:1512.03012 [cs.GR], Stanford University — Princeton University — Toyota Technological Institute at Chicago, 2015.
2. Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., Courville, A., and Bengio, Y.

Paste the appropriate copyright statement here. ACM now supports three different copyright statements:

- ACM copyright: ACM holds the copyright on the work. This is the historical approach.
- License: The author(s) retain copyright, but ACM receives an exclusive publication license.
- Open Access: The author(s) wish to pay for the work to be open access. The additional fee must be paid to ACM.

This text field is large enough to hold the appropriate release statement assuming it is single spaced.

Every submission will be assigned their own unique DOI string to be included here.

- Generative adversarial nets. In *Advances in Neural Information Processing Systems 27*, Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger, Eds. Curran Associates, Inc., 2014, 2672–2680.
3. Miller, G. A. Wordnet: A lexical database for english. *Commun. ACM* 38, 11 (Nov. 1995), 39–41.
  4. Wu, J., Zhang, C., Xue, T., Freeman, W. T., and Tenenbaum, J. B. Learning a probabilistic latent space of object shapes via 3d generative-adversarial modeling. In *Advances in Neural Information Processing Systems* (2016), 82–90.