

Objective

This example demonstrates the Watchdog Timer (WDT) on PSoC® 6 MCU, using PSoC Creator™.

Requirements

Tool: PSoC Creator™ 4.2; Peripheral Driver Library (PDL) 3.0.1

Programming Language: C (Arm® GCC 5.4.1 and Arm MDK 5.22)

Associated Parts: All PSoC 6 MCU parts

Related Hardware: PSoC 6 BLE Pioneer Kit, PSoC 6 WiFi-BT Pioneer Kit

Overview

This example explains the two use cases of WDT – as a watchdog that causes a device reset in the case of a malfunction, and as a periodic interrupt source.

A macro definition determines which mode to use. Out of the box, this example demonstrates the periodic interrupt. The blue LED toggles on every interrupt at an interval of ~1 s.

For reset mode, you change the macro definition and enable an infinite loop in the `main()` function, to block execution. The device resets in ~6 s. The green LED blinks after the device comes out of reset. If you use reset mode without blocking execution, the device does not reset. The red LED toggles every 1 s in the main loop to indicate that the CPU is in action.

In addition, the red LED blinks once after power cycling or an external reset event.

Hardware Setup

This example uses the kit's default configuration. Refer to the kit guide to ensure the kit is configured correctly.

Software Setup

See the Operation section for information on how to modify the code for each demo.

Operation

1. Connect the Pioneer kit to your PC using the provided USB cable.
2. Open the PSoC Creator project
3. Modify the source code if you want to use RESET mode. By default, the example is in INTERRUPT mode.
 - a. Open `main.c` from CE220060 in the workspace.
 - b. Set `WDT_DEMO` to `WDT_RESET_DEMO` for reset demonstration
 - c. In the innermost “for” loop, uncomment the line of code `//while(1);` to cause the reset to happen.
4. When `WDT_INTERRUPT_DEMO` is selected, you can optionally put the device in Deep Sleep mode by uncommenting the function call `Cy_SysPm_DeepSleep()` in the main loop. The device wakes up from Deep Sleep mode on a WDT interrupt.
5. Build the project and program it into the PSoC 6 MCU device. Choose **Debug > Program**. For more information on device programming, see PSoC Creator Help. Flash for both CPUs is programmed in a single program operation.
6. Observe the status of LEDs based on different events summarized in [Table 1](#).

Table 1. LED Status

Project Setting	LED Status
WDT_DEMO set to WDT_INTERRUPT_DEMO	Blue LED toggles on every WDT interrupt (interval of 1 s)
WDT_DEMO set to WDT_RESET_DEMO with blocking function	After approximately 6 s, the device resets and green LED blinks to indicate WDT reset.
WDT_DEMO set to WDT_RESET_DEMO without blocking function	Red LED toggles every 1 s to indicate that the CPU is in action.


Note that red LED blinks once after power cycle or an external reset event.

Design and Implementation

The WDT in PSoC 6 MCU is a 16-bit timer and uses the Internal Low-Speed Oscillator (ILO) clock of 32 kHz. It is primarily used as a watchdog against any system malfunction, but can also be used for generating periodic interrupt.

In PSoC Creator, the Global Signal Component and Interrupt Component are used. The Global Signal Component allows access to the interrupt signal generated by the WDT; this signal is routed to the Interrupt Component for triggering the CPU.

Figure 1. Top Design Schematic



In firmware, WDT is configured in eight steps in the project as follows:

1. Unlock the WDT to enable configuration.
2. Set the ignore bits for the match resolution. In the project, it is set to 0; that means full 16-bit resolution for the match count which gives an interval of 2.048 s ($2^{16} \div 32 \text{ kHz}$) for the match event.
3. Write the match value. The WDT can generate an interrupt (if enabled) when the WDT counter reaches the match count. The project configures the match count using the macro `WDT_MATCH_COUNT`. Note that the interrupt handler modifies the match count when `WDT_INTERRUPT_DEMO` is selected to generate a periodic interrupt¹ every 1 s. The match count, however, is set to zero in `WDT_RESET_DEMO` mode to generate match events at equal intervals of time². The device resets after three WDT match events, that is, $2.048 \text{ s} \times 3 = 6.144 \text{ s}$, if the match event is not cleared. You can reduce the duration of the match event by introducing ignore bits in Step 2.
4. Clear the pending WDT interrupt.

5. Enable the ILO, which is the source for the WDT.
6. Enable the interrupt generation if WDT_INTERRUPT_DEMO mode is selected and assign the handler. Interrupt should be disabled when using the WDT_RESET_DEMO mode².
7. Enable the WDT.
8. Lock the WDT to prevent inadvertent changes.

Note:

1. The WDT generates an interrupt on match. However, the counter is not reset on match. It continues to count across the full 16-bit resolution. For this reason, the match count is updated on every WDT interrupt, when WDT_INTERRUPT_DEMO is selected.
2. Interrupt should not be enabled when reset mode of the WDT is being used. If interrupt is enabled, upon an interrupt, it needs to be cleared to avoid repeated execution of the WDT interrupt handler. This removes the actual purpose of the WDT. Thus, interrupt generation should never be enabled and the WDT match event should always be cleared in the main loop.

Components and Settings

Table 2 lists the PSoC Creator Components used in this example, how they are used in the design, and the non-default settings required so they function as intended.


Table 2. PSoC Creator Components

Component	Instance Name	Purpose	Non-default Settings
Global Signal Reference (GSRRef)	GlobalSignal_1	Used to access WDT interrupt signal	Global signal name set to SRSS combined interrupts (SRSSInt)
System Interrupt (SysInt)	WDTIsr	Used for generating CPU interrupt	None

For information on the hardware resources used by a Component, see the Component datasheet.

Figure 2 highlights the non-default settings for the GlobalSignal Component.

Figure 2. GlobalSignal Component Configuration



Reusing This Example

This example is designed for the PSoC 6 BLE pioneer kit. To port the design to a different PSoC 6 MCU device and/or kit, change the target device using the Device Selector and update the pin assignments in the Design Wide Resources Pins settings as needed. For single-core PSoC 6 MCU devices, port the code from *main_cm4.c* to *main.c*.

In some cases, a resource used by a code example (for example, an IP block) is not supported on another device. In that case, the example will not work. If you build the code targeted at such a device, you will get errors. See the device datasheet for information on what a particular device supports.

Related Documents

For a comprehensive list of PSoC 6 MCU resources, see [KBA223067](#) in the Cypress community.

For a comprehensive list of PSoC 3, PSoC 4, and PSoC 5LP resources, see [KBA86521](#) in the Cypress community.

Application Notes	
AN210781 – Getting Started with PSoC 6 MCU with Bluetooth Low Energy (BLE) Connectivity	Describes PSoC 6 MCU with BLE Connectivity devices and how to build your first PSoC Creator project
AN215656 – PSoC 6 MCU: Dual-CPU System Design	Describes the dual-CPU architecture in PSoC 6 MCU, and shows how to build a simple dual-CPU design
AN219434 – Importing PSoC Creator Code into an IDE for a PSoC 6 MCU Project	Describes how to import the code generated by PSoC Creator into your preferred IDE
PSoC Creator Component Datasheets	
Pins	Supports connection of hardware resources to physical pins
Global Signal Reference	Supports connection to device global signals
Clock	Supports local clock generation
Interrupt	Supports generating interrupts from hardware signals
Device Documentation	
PSoC 6 MCU: PSoC 63 with BLE Datasheet	PSoC 6 MCU: PSoC 63 with BLE Architecture Technical Reference Manual
PSoC 6 MCU: PSoC 62 Datasheet	PSoC 6 MCU: PSoC 62 Architecture Technical Reference Manual (TRM)
Development Kit Documentation	
CY8CKIT-062-BLE PSoC 6 BLE Pioneer Kit	
CY8CKIT-062-WiFi-BT PSoC 6 WiFi-BT Pioneer Kit	
Tool Documentation	
PSoC Creator	Look in the downloads tab for Quick Start and User Guides
WICED SDK	Installed with the SDK
Peripheral Driver Library (PDL)	Installed by PSoC Creator 4.2. Look in the <PDL install folder>/doc for the User Guide and the API Reference

Cypress Resources

Cypress provides a wealth of data at www.cypress.com to help you to select the right device, and quickly and effectively integrate the device into your design.


The following is an abbreviated list of resources related to this code example:

- **Overview:** [MCU Portfolio](#), [PSoC & MCU Roadmap](#)
- **Product Selectors:** [PSoC 1](#), [PSoC 3](#), [PSoC 4](#), [PSoC 5LP](#), or [PSoC 6](#). In addition, [PSoC Creator](#) includes a device selection tool.
- **Datasheets:** Describe and provide electrical specifications for MCU and PSoC device families.
- **Application Notes:** Cover a broad range of topics, from basic to advanced level.
- **Code Examples:** for [PSoC 3](#), [PSoC 4](#), and [PSoC 5LP](#); or for [PSoC 6](#).
- **PSoC Technical Reference Manuals (TRM):** Provide detailed descriptions of the architecture and registers for a PSoC device family.
- **Training Videos:** These videos provide guidance on getting started with various Cypress product families and tools.
- **PSoC 6 MCU Training Videos:** Provide guidance on getting started.
- **CapSense Design Guides:** Learn how to design capacitive touch-sensing applications.
- **Development Kits:** Some examples include:
 - [PSoC 6 BLE Pioneer Kit](#) is a low-cost hardware platform that enables design and debug of the PSoC 63 series. It comes with an E-Ink display shield board.
 - [PSoC 6 WiFi-BT Pioneer Kit](#) supports the PSoC 62 series MCU along with Wi-Fi and BT connectivity
 - [CY8CKIT-042](#) and [CY8CKIT-040](#), Pioneer kits, are easy-to-use and inexpensive development platforms. These kits include connectors for Arduino™ compatible shields and Digilent® Pmod™ daughter cards.
 - [CY8CKIT-049](#) is a series of very low-cost prototyping platform for sampling PSoC 4 devices.
 - [CY8CKIT-030](#) and [CY8CKIT-050](#) are designed for analog performance. They enable you to evaluate, develop, and prototype high-precision analog, low-power, and low-voltage applications powered by PSoC 3 and PSoC 5LP, respectively.
 - [CY8CKIT-001](#) is a common development platform for all PSoC family devices.
- The [MiniProg3](#) device provides an interface for flash programming and debug.

PSoC Creator

PSoC Creator is a free Windows-based Integrated Design Environment (IDE). It enables concurrent hardware and firmware design of systems based on PSoC 3, PSoC 4, PSoC 5LP, and PSoC 6 MCU. With PSoC Creator, you can:

1. Browse the collection of code examples from the **File > Code Example** menu.
2. Explore the library of 100+ Components
3. Drag and drop Components to build your hardware system design in the main design workspace
4. Review Component datasheets
5. Configure Components using configuration tools
6. Codesign your application firmware with the PSoC hardware



The screenshot illustrates the PSoC Creator IDE interface with several key components highlighted and numbered to show the design workflow:

- 1. Browse Code Examples:** The 'Find Code Example' dialog is open, showing a list of code examples under the 'Dual Core' filter.
- 2. Explore Component Catalog:** The 'Component Catalog' pane on the right shows a list of components, including 'CapSense'.
- 3. Drag and Drop Components:** The main design workspace shows a schematic diagram with components like 'CapSense' and 'PDM' being placed.
- 4. Open Datasheet:** The 'CapSense' component's datasheet is open, showing its features and configuration options.
- 5. Configure Components:** The 'Configure CapSense' dialog is open, allowing users to configure the component's settings, such as 'CSD tuning mode' and 'Sensing elements'.
- 6. Develop Firmware:** The 'Develop Firmware' pane on the left shows the C code for the application, including comments and function definitions.

Document History

Document Title: CE220060 – PSoC 6 MCU Watchdog Timer

Document Number: 002-20060

Revision	ECN	Orig. of Change	Submission Date	Description of Change
**	5788931	VJYA	06/29/2017	New code example
*A	5856603	VJYA	08/23/2017	Initial public release
*B	5918159	VJYA	11/03/2017	Updated project name
*C	6372405	RJVB	02/01/2019	Updated template Updated PSoC Creator Project

Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at [Cypress Locations](#).

Products

Arm® Cortex® Microcontrollers	cypress.com/arm
Automotive	cypress.com/automotive
Clocks & Buffers	cypress.com/clocks
Interface	cypress.com/interface
Internet of Things	cypress.com/iot
Memory	cypress.com/memory
Microcontrollers	cypress.com/mcu
PSoC	cypress.com/psoc
Power Management ICs	cypress.com/pmic
Touch Sensing	cypress.com/touch
USB Controllers	cypress.com/usb
Wireless Connectivity	cypress.com/wireless

PSoC® Solutions

[PSoC 1](#) | [PSoC 3](#) | [PSoC 4](#) | [PSoC 5LP](#) | [PSoC 6 MCU](#)

Cypress Developer Community

[Community](#) | [Projects](#) | [Videos](#) | [Blogs](#) | [Training](#) | [Components](#)

Technical Support

cypress.com/support

All other trademarks or registered trademarks referenced herein are the property of their respective owners.



Cypress Semiconductor
198 Champion Court
San Jose, CA 95134-1709

© Cypress Semiconductor Corporation, 2017-2019. This document is the property of Cypress Semiconductor Corporation and its subsidiaries ("Cypress"). This document, including any software or firmware included or referenced in this document ("Software"), is owned by Cypress under the intellectual property laws and treaties of the United States and other countries worldwide. Cypress reserves all rights under such laws and treaties and does not, except as specifically stated in this paragraph, grant any license under its patents, copyrights, trademarks, or other intellectual property rights. If the Software is not accompanied by a license agreement and you do not otherwise have a written agreement with Cypress governing the use of the Software, then Cypress hereby grants you a personal, non-exclusive, nontransferable license (without the right to sublicense) (1) under its copyright rights in the Software (a) for Software provided in source code form, to modify and reproduce the Software solely for use with Cypress hardware products, only internally within your organization, and (b) to distribute the Software in binary code form externally to end users (either directly or indirectly through resellers and distributors), solely for use on Cypress hardware product units, and (2) under those claims of Cypress's patents that are infringed by the Software (as provided by Cypress, unmodified) to make, use, distribute, and import the Software solely for use with Cypress hardware products. Any other use, reproduction, modification, translation, or compilation of the Software is prohibited.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS DOCUMENT OR ANY SOFTWARE OR ACCOMPANYING HARDWARE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. No computing device can be absolutely secure. Therefore, despite security measures implemented in Cypress hardware or software products, Cypress shall have no liability arising out of any security breach, such as unauthorized access to or use of a Cypress product. CYPRESS DOES NOT REPRESENT, WARRANT, OR GUARANTEE THAT CYPRESS PRODUCTS, OR SYSTEMS CREATED USING CYPRESS PRODUCTS, WILL BE FREE FROM CORRUPTION, ATTACK, VIRUSES, INTERFERENCE, HACKING, DATA LOSS OR THEFT, OR OTHER SECURITY INTRUSION (collectively, "Security Breach"). Cypress disclaims any liability relating to any Security Breach, and you shall and hereby do release Cypress from any claim, damage, or other liability arising from any Security Breach. In addition, the products described in these materials may contain design defects or errors known as errata which may cause the product to deviate from published specifications. To the extent permitted by applicable law, Cypress reserves the right to make changes to this document without further notice. Cypress does not assume any liability arising out of the application or use of any product or circuit described in this document. Any information provided in this document, including any sample design information or programming code, is provided only for reference purposes. It is the responsibility of the user of this document to properly design, program, and test the functionality and safety of any application made of this information and any resulting product. "High-Risk Device" means any device or system whose failure could cause personal injury, death, or property damage. Examples of High-Risk Devices are weapons, nuclear installations, surgical implants, and other medical devices. "Critical Component" means any component of a High-Risk Device whose failure to perform can be reasonably expected to cause, directly or indirectly, the failure of the High-Risk Device, or to affect its safety or effectiveness. Cypress is not liable, in whole or in part, and you shall and hereby do release Cypress from any claim, damage, or other liability arising from any use of a Cypress product as a Critical Component in a High-Risk Device. You shall indemnify and hold Cypress, its directors, officers, employees, agents, affiliates, distributors, and assigns harmless from and against all claims, costs, damages, and expenses, arising out of any claim, including claims for product liability, personal injury or death, or property damage arising from any use of a Cypress product as a Critical Component in a High-Risk Device. Cypress products are not intended or authorized for use as a Critical Component in any High-Risk Device except to the limited extent that (i) Cypress's published data sheet for the product explicitly states Cypress has qualified the product for use in a specific High-Risk Device, or (ii) Cypress has given you advance written authorization to use the product as a Critical Component in the specific High-Risk Device and you have signed a separate indemnification agreement.

Cypress, the Cypress logo, Spansion, the Spansion logo, and combinations thereof, WICED, PSoC, CapSense, EZ-USB, F-RAM, and Traveo are trademarks or registered trademarks of Cypress in the United States and other countries. For a more complete list of Cypress trademarks, visit cypress.com. Other names and brands may be claimed as property of their respective owners.