



# Switzerland — Monthly Intelligence Report

v4.2

Edition 005 — Deep-Dive Theme

Where the energy transition is outrunning the grid. edition · July 2026 · SSI v4.2 (refreshed June 2026)

CONTENTS

- A

Executive Summary
- B

Cyber & Economic Exposure Monitor
- C

Data Refresh & Changelog
- D

Deep-Dive: Monthly Theme
- E

European Context Card
- F

SSI Enhanced Neural Network
- F.5

Anti-maladaptation Gate (Radar 2 · W1–W10)
- G


Looking Ahead
- v4.2

SECTION A

## Executive Summary

### Radar 1 — v4.2: now 7-axis with the new Re composite

v4.0.2 Radar 1 had 6 axes (C/V/I/E/S/T). **v4.2 adds Re — the bounded resilience composite** capturing the new modifier family (R6c flood + R6d wildfire + R6e winter + R8 adapt + R9 compound + R10 just) in one normalised scalar ( $Re\_norm \in [0, 1]$  via  $\text{clip}((Re\_raw - 0.920) / (1.787 - 0.920), 0, 1)$ ). Two worked examples overlaid: **Unterwerk Samstager** (low-exposure reference,  $Re\_norm$  0.000) · **Poste de Chippis** (high-exposure reference,  $Re\_norm$  1.000). The Re axis is colour-highlighted in cayenne to emphasise the v4.2 architectural addition.



The Re composite (★, cayenne-highlighted axis at upper-left) captures the v4.2 resilience modifier family in one bounded scalar — formula  $Re\_raw = (R6d \times R6e \times R8 \times R9 \times R10) + (R6c - 1.00)$ , bounds  $[0.920, 1.787]$ . Per Convention #6 §2.3.6 Path B refactor (11 Jun 2026), this country's exemplars are algorithmically selected (min/max  $Re\_norm$ ) per the v4.2 methodology. The Substation in Focus radar canvas (Section A below) is rendered by shared intelligence-sections.js and now also displays the 7th Re axis (Convention #11 surface-pair coherence, V4.2-disc-24 closure 12 Jun 2026).

#### SUBSTATIONS SCORED

947

147 EHV · 163 HV · 637 distribution-tier

#### GRID LINES MAPPED

625

~6,238 km coverage

#### MC SIMULATIONS

42.9 M

10,000 per substation

#### PUBLIC DATA SOURCES

34

101 variables · zero proprietary

The SSI Index is the only operational framework that fuses substation-level engineering metrics with socio-economic consequence valuation in a single composite score — scoring 71/80 (89%) across 16 competitive dimensions, ahead of GMLC 1.1

(48/80), EPRI (40/80), and academic MCDA frameworks (41/80). Its engine processes 146,000+ source data points per run, executes 42.9 million Monte Carlo simulations through a 20×20 Gaussian copula correlation matrix, and performs 1.78 billion arithmetic operations — producing 244,701 output data points with full uncertainty quantification across 947 substations and 625 grid lines spanning ~6,238 km. v4.2 adds the Re composite (7th axis) and six resilience modifiers (R6c flood / R6d wildfire / R6e winter / R8 adapt / R9 compound / R10 just) on top of the v4.0.2 foundation.

Operated as a non-profit through a dedicated foundation, the SSI Index serves the public interest with zero dependency on proprietary data. All 101 variables are drawn from 34 verified public sources, making the methodology fully auditable and reproducible. Initially covering Switzerland's entire transmission and distribution grid, the Index is progressively being rolled out to all OECD countries — applying the same silo-breaking approach: fusing grid risk with societal exposure at asset-level resolution wherever open data permits.

Substation in Focus

BKW

Bern-Mittelland, Bern · 16 kV

0.693

High

0.146

86th

R\_FINAL

CLASSIFICATION

CI WIDTH

FLEET PERCENTILE

Re composite v4.2 7th axis

Re\_raw 1.1059 · Re\_norm 0.568

ELEVATED EXPOSURE

COMPONENTS

C

Continuity: 0.500 / 0.30 (167%)

I

Infrastructure: 0.541 / 0.25 (216%)

S

Saturation: 1.000 / 0.20 (500%) 

▲

V

Voltage: 0.593 / 0.10 (593%)

E

Economic: 0.144 / 0.10 (144%)

T

Transition: 0.925 / 0.05 (1850%)

MODIFIERS

R3

Consequence: 0.944 ↓ dampens

R4

Graph Criticality: 1.045 ↑ amplifies

R6a

Restoration: 1.004 → neutral

R6b

Seismic: 1.035 ↑ amplifies

R7

Digital Readiness: 1.000 → neutral

This month's spotlight — automatically selected for July 2026 — is **BKW** in Bern-Mittelland, Bern. With an R\_final of 0.693 (High band, 86th fleet percentile), its risk profile is dominated by the T (Transition) component at 1850% of its weight ceiling, followed by V (Voltage) at 593%. Modifiers collectively shift R\_base by 14.5%, reflecting the substation's specific geographic, socio-economic, and network context.

SECTION B — RECURRING MODULE

Cyber & Economic Exposure Monitor

**Why this section exists:** Traditional grid risk frameworks treat cybersecurity and economic vulnerability as separate domains. The SSI's R7 (Digital Readiness) modifier and E (Economic) component allow us to cross these silos — revealing substations where low digital resilience intersects with high economic consequence. This is precisely the anticipatory intelligence that infrastructure digitalisation planning requires.

CYBER HIGH EXPOSURE

0

0.0% of fleet

BLIND SPOTS

0

High/Critical + R7 < median

AVG R7 MODIFIER

1.0000

Range [0.99, 1.05]


HIGH-CONSEQUENCE SUBS

0

0.0% · R3 ≥ 1.13

### B.1 Cyber-Physical Risk Matrix

Each substation plotted by R7 digital readiness (x-axis) vs overall R\_median (y-axis). The upper-left quadrant — high risk, low digital readiness — identifies *blind spots* where grid stress is high but monitoring/response capacity is weakest.



● Low ● Medium ● High ● Critical

Dashed lines = fleet medians

The cyber-physical matrix identifies **0 blind-spot substations** — scoring High or Critical on overall risk while sitting below the fleet median for digital readiness ( $R7 < 1.0000$ ). These substations are the most vulnerable to a compound event: a grid disturbance at a location where digital monitoring, automated switching, and remote diagnostic capacity are weakest. The blind spots concentrate in —. Across the full fleet, 0 substations (0.0%) carry a HIGH cyber-exposure classification, while 0 (0.0%) are in the LOW tier.

### B.2 Economic Impact by Business Fabric

Substations segmented by economic consequence tier — derived from the R3 consequence multiplier and E component. Higher R3 indicates the substation serves a territory with greater socio-economic exposure to disruption.

### Capital-Intensive / High-Consequence

Est. VoLL: CHF15–29/kWh (≈ €15–30/kWh)

0 substations (0.0%) High/Critical: 0 (0%) Avg R: 0.000 Avg E: 0.000 / 0.10

Low 0

Med 0

High 0

Crit 0

### Industrial / Medium-Large Enterprise

Est. VoLL: CHF7.8–15/kWh (≈ €8–15/kWh)

0 substations (0.0%) High/Critical: 0 (0%) Avg R: 0.000 Avg E: 0.000 / 0.10

Low 0

Med 0

High 0

Crit 0

### Commercial / Mixed

Est. VoLL: CHF2.9–7.8/kWh (≈ €3–8/kWh)

0 substations (0.0%) High/Critical: 0 (0%) Avg R: 0.000 Avg E: 0.000 / 0.10

Low 0

Med 0

High 0

Crit 0

### Light-Rural / Agricultural

Est. VoLL: CHF1–2.9/kWh (≈ €1–3/kWh)

947 substations (100.0%) High/Critical: 783 (82.7%) Avg R: 0.600 Avg E: 0.265 / 0.10

Low 0

Med 164

High 704

Crit 79

**Value of Lost Load (VoLL) context:** ACER's 2023 estimate places average VoLL at €13.1/kWh for industrial customers and €3.2/kWh for residential. The SSI's R3 consequence multiplier allows us to identify which substations serve the most economically exposed territories. **0 substations** combine capital-intensive economic fabric ( $R3 \geq 1.14$ ) with High or Critical risk classification — representing the highest VoLL-weighted exposure in the fleet.

The capital-intensive tier concentrates in — — regions where industrial corridors depend on uninterrupted power for continuous processes. A single hour of unplanned outage at these substations carries an estimated VoLL of €15–30/kWh, compared to €1–3/kWh in rural agricultural areas. The fleet-wide average energy poverty rate is 3.2%, but this masks sharp regional variation: Southern regions combine higher energy poverty with higher grid risk, creating a double vulnerability that the E component captures. This cross-referencing of economic fabric with grid condition is unique to the SSI — no competing framework links VoLL exposure to substation-level risk scores.

## B.3 Province Digital Readiness Ranking

Provinces ranked by average R7 modifier — lower values indicate weaker digital infrastructure (DESI sub-dimensions). Cross-referenced with average R\_median to identify provinces combining digital exposure with high grid stress.



WORST DIGITAL READINESS — TOP 15 REGION REGIONS

Longer bar = higher R7 = better digital infrastructure.

|    |                                |             |        |
|----|--------------------------------|-------------|--------|
| 1  | Leventina                      | <div></div> | 1.0000 |
| 2  | Hochdorf                       | <div></div> | 1.0000 |
| 3  | Fricktal <span>▲ high R</span> | <div></div> | 1.0000 |
| 4  | Ilanz                          | <div></div> | 1.0000 |
| 5  | Brugg <span>▲ high R</span>    | <div></div> | 1.0000 |
| 6  | Renens <span>▲ high R</span>   | <div></div> | 1.0000 |
| 7  | Delemont                       | <div></div> | 1.0000 |
| 8  | Winterthur                     | <div></div> | 1.0000 |
| 9  | Pinot <span>▲ high R</span>    | <div></div> | 1.0000 |
| 10 | Bernina                        | <div></div> | 1.0000 |
| 11 | Albula                         | <div></div> | 1.0000 |
| 12 | Surselva                       | <div></div> | 1.0000 |
| 13 | Sierre                         | <div></div> | 1.0000 |
| 14 | Conthey                        | <div></div> | 1.0000 |
| 15 | Martigny                       | <div></div> | 1.0000 |

region-level analysis reveals a clear digital divide mirroring the broader DESI pattern. **Leventina** has the lowest average R7 (1.0000), while **Franches-Montagnes** leads at 1.0000 — a spread of 0.0000 across the R7 range. **O region regions** combine below-median digital readiness with above-median grid risk, making them priority targets for digitalisation investment. The R7 modifier is intentionally narrow to reflect the current limitations of open DESI data — as NIS2 compliance reporting matures, future editions will expand R7's dynamic range and incorporate operational technology (OT) security indicators.

B.4 Monthly Pulse

**Inaugural edition — Baseline Snapshot (July 2026).** This edition establishes the baseline for the Cyber & Economic Exposure Monitor. Key reference points: fleet average R7 = 1.0000, median = 1.0000; 0 substations classified HIGH cyber-exposure; 0 blind-spot substations (High/Critical risk + below-median R7); 0 Critical-band substations with below-median digital readiness. Future editions will track deltas against this baseline.

SECTION C

Data Refresh & Changelog

The SSI v4.0.2 draws on — **verified public data sources** feeding — variables across — components and — modifiers. This section provides a live registry of all sources, their update frequencies, and the current state of the fleet. Transparency in data vintage is central to the SSI's credibility.

TOTAL SOURCES

— variables

HOURLY — MONTHLY

High-frequency feeds

QUARTERLY / ANNUAL

Regular refresh cycle

STATIC / DERIVED



Standards + scenarios

Data Source Registry — July 2026

|         |                                                      |            |                   |        |
|---------|------------------------------------------------------|------------|-------------------|--------|
| OSM     | OSM Power Infrastructure                             | WEEKLY     | Node/edge         | 3 vars |
| METE0   | MeteoSwiss                                           | DAILY      | ~2 km             | 3 vars |
| SGRID   | Swissgrid (single TSO)                               | MONTHLY    | Control area      | 4 vars |
| PRONOVO | Pronovo (Guarantees of Origin Registry)              | MONTHLY    | Substation        | 3 vars |
| SED     | SED Swiss Seismological Service                      | CONTINUOUS | 200+ stations     | 3 vars |
| BABS    | BABS Civil Protection (Bundesamt)                    | CONTINUOUS | Kanton            | 1 var  |
| SECO    | SECO State Secretariat for Economic Affairs          | QUARTERLY  | Kanton            | 3 vars |
| SNB     | SNB Swiss National Bank                              | QUARTERLY  | Kanton / national | 2 vars |
| ASTRA   | ASTRA EV Registry (Bundesamt für Strassen)           | QUARTERLY  | Kanton            | 1 var  |
| INNO    | Innosuisse — Swiss Innovation Agency                 | QUARTERLY  | Kanton            | 1 var  |
| KOF     | KOF Konjunkturforschungsstelle ETH                   | QUARTERLY  | Regional          | 2 vars |
| ELCOM   | EICom (Federal Electricity Commission)               | ANNUAL     | Kanton / DSO      | 8 vars |
| BFS     | BFS / OFS (Federal Statistical Office)               | ANNUAL     | Kanton / Gemeinde | 8 vars |
| BAFU    | BAFU Federal Office for the Environment              | ANNUAL     | Kanton / station  | 4 vars |
| JRC     | JRC DSO Observatory                                  | ANNUAL     | DSO-level         | 2 vars |
| EEA     | EEA Air Quality e-Reporting                          | ANNUAL     | ~1 km + station   | 3 vars |
| ICTMIN  | ICT-Minimum Standard 2018 (NCSC)                     | ANNUAL     | CH-national       | 2 vars |
| NCSC    | NCSC National Cyber Security Centre                  | ANNUAL     | CH-national       | 2 vars |
| BFE     | BFE / OFEN Federal Energy Office                     | ANNUAL     | Kanton            | 2 vars |
| ARE     | ARE Federal Office for Spatial Development           | ANNUAL     | Kanton            | 1 var  |
| EFV     | EFV Federal Finance Administration                   | ANNUAL     | Kanton            | 1 var  |
| VSE     | VSE Verband Schweizerischer Elektrizitätsunternehmen | ANNUAL     | DSO / Kanton      | 2 vars |
| SGRID-N | Swissgrid Network Development Plan                   | ANNUAL     | TSO zone          | 2 vars |
| ELCOM-M | EICom Monitoring Report                              | ANNUAL     | DSO-level         | 2 vars |

|          |                                                 |         |                 |         |
|----------|-------------------------------------------------|---------|-----------------|---------|
| BFS-S    | BFS / OFS Spatial Typology                      | ANNUAL  | Gemeinde        | 1 var   |
| AVENIR   | Avenir Suisse — Policy Research                 | ANNUAL  | Kanton          | 1 var   |
| AEE      | AEE Suisse — Renewable Energy Agency            | ANNUAL  | Kanton          | 1 var   |
| COPER    | Copernicus CDS / ERA5                           | STATIC  | ~25 km          | 4 vars  |
| SWTOP    | swisstopo (Federal Office of Topography)        | STATIC  | 1:25,000        | 3 vars  |
| IEEE-1   | IEEE C57.91 / IEC 60076                         | STATIC  | Asset-level     | 16 vars |
| GFZ      | GFZ German Research Centre (Geosci.)            | STATIC  | ~5 km           | 2 vars  |
| BFS-GMD  | BFS Gemeindeverzeichnis (Municipality Registry) | STATIC  | 2,148 Gemeinden | 1 var   |
| ISO-9223 | ISO 9223 Corrosion                              | DERIVED | Kanton          | 1 var   |
| ENTSE    | ENTSO-E Transparency (CH observer)              | HOURLY  | CH bidding zone | 2 vars  |
| D-0M     | Open-Meteo / ERA5                               | HOURLY  | ~1 km           | 1 var   |

## C.1 Update Frequency Timeline

EXPECTED UPDATE WINDOWS

## C.2 Fleet Score Snapshot

FLEET SIZE

947

substations scored

MEDIAN R

0.601

P5=0.458 · P95=0.759

HIGH + CRITICAL

783

82.7% of fleet

HIGH CONFIDENCE

100%

947 subs · CI/R < 0.50



No primary data sources have been updated since the v4.0.2 launch baseline. All **947 substation scores remain unchanged** this edition. The fleet median R of 0.601 (mean 0.600) reflects a distribution skewed toward the lower bands, with 0.0% in Low and 17.3% in Medium. The first material score changes are expected when the national regulator publishes the annual quality-of-supply indicators and when DER registries refresh. High-frequency sources (OSM, weather) update weekly but feed only infrastructure topology (R4) and thermal proxy (I5), which have minimal impact on fleet-level score distribution.

C.3 Changelog — v3.4 → v4.0.2 → v4.2

v4.2 (June 2026) adds six resilience modifiers (R6c flood / R6d wildfire / R6e winter / R8 adapt / R9 compound / R10 just), the Re composite (7th axis, bounds [0.920, 1.787]), four new data sources ( IdroGEO PGRA, SIAB wildfire, ECMWF ERA5 Bourgouin, bulk smart meter), six new variables, and W1–W10 anti-maladaptation governance gate (5/1/1/3 4-tier mesh resolution per Convention #6 §5.6) on top of the v4.0.2 baseline.

11 changes tracked across PO, P1, and P2 releases

|        |        |                                                                                                                                                                                     |      |
|--------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| V42-1  | NEW    | R6c_flood — PGRA-style flood-vulnerability modifier (additive cliff +0.00..+0.30, P3=high/P2=medium/P1=low per national flood-hazard tier convention)                               | \$5  |
| V42-2  | NEW    | R6d_wildfire — Canadian Fire Weather Index modifier (EFFIS FWI + NASA FIRMS + national fire-registry, multiplicative [1.00, 1.20])                                                  | \$5  |
| V42-3  | NEW    | R6e_winter — Bourgouin winter-storm modifier (ECMWF ERA5 winter-precipitation signal, multiplicative [1.00, 1.02])                                                                  | \$5  |
| V42-4  | NEW    | R8_adapt — Adaptive-capacity multiplier (smart-meter penetration + DSO investment + DESI index, multiplicative [0.95, 1.05])                                                        | \$5  |
| V42-5  | NEW    | R9_compound — Compound-hazard STEP function (R6b/R6c/R6d/R6e elevated-count gates, multiplicative {1.00, 1.04, 1.08, 1.10})                                                         | \$5  |
| V42-6  | NEW    | R10_just — Energy-justice modifier (EU-SILC or national-equivalent household material-deprivation gradient, multiplicative [1.00, 1.12])                                            | \$5  |
| V42-7  | NEW    | Re composite — bounded resilience scalar $Re_{raw} = (R6d \times R6e \times R8 \times R9 \times R10) + (R6c - 1.00)$ ; $Re_{norm} = clip((Re_{raw} - 0.920)/(1.787 - 0.920), 0, 1)$ | \$7  |
| V42-8  | NEW    | R7 SFDR PAI Infrastructure axis — added to ESG Radar (Re_norm proxy under Convention #7 Data-Layer Anchoring)                                                                       | \$14 |
| V42-9  | NEW    | W1–W10 audit-state mesh — 5 Published / 1 Published-baseline ▲ / 1 Baseline-only / 3 Commercial (Convention #6 §5.6)                                                                | \$4  |
| V42-10 | CHANGE | 95 → 101 variables (+6 from v4.2 modifier inputs); 30 → 34 data sources (+4 hazard / monitoring layers)                                                                             | data |
| V42-11 | CHANGE | Substation fleet: 947 substations (per OSM canonical extract + national TSO/DSO registry cross-validation)                                                                          | data |

SECTION D — MONTHLY DEEP-DIVE

Monthly Deep-Dive Theme

**Deep-dive rotation:** Each edition features a substantive thematic analysis. The 12-month rotation: **Ed. 001** the monthly theme · **002** DER saturation hotspots · **003** Climate vulnerability under CMIP6 · **004** North–South economic impact disparity · **005** Voltage quality and industrial output · **006** Infrastructure age vs investment · **007** Stress–Resilience quadrant trends · **008** T-component forward projections · **009** Sub-national Grid Health Cards · **010** Academic validation and peer feedback · **011** European replication feasibility · **012** Year in review.

D.1 Theme Context

THEME-RELEVANT SUBSTATIONS

30

11 EHV · 19 HV

HIGH BAND

8 + 22

100.0% of corridor

CORRIDOR MEDIAN R

0.783

Fleet median: 0.601


WORST PROVINCE

Nyon

Avg R: 0.795 · 5 substations

The Vaud hosts **30 substations** across 10 region regions, making it the locus of this edition's deep-dive analysis. Its risk profile is concentrated in the upper bands: **8 substations (26.7%)** are classified High and **22** Critical, with only **0** in the Low band. 100% of corridor substations score above the national fleet median of 0.601. The corridor median R of 0.783 reflects the local risk profile. The corridor concentrates the country's industrial heartland. The SSI flags continuity-of-supply deficits, infrastructure age mismatches with modern demand patterns, and grid modernization lag under national digitalisation timelines.

D.2 Corridor Map and Scoring



| SUBSTATION                                                 | PROVINCE | R_FINAL | BAND     | C     | V     | I     | E     | S     | T     | RE<br>v4.2 | ALERT |
|------------------------------------------------------------|----------|---------|----------|-------|-------|-------|-------|-------|-------|------------|-------|
| Aigle Sub 461                                              | Aigle    | 0.799   | Critical | 0.500 | 0.783 | 0.995 | 0.071 | 0.981 | 0.794 | S          |       |
| Aigle Sub 388                                              | Aigle    | 0.798   | Critical | 0.500 | 0.783 | 0.995 | 0.071 | 0.981 | 0.794 | S          |       |
| SEIC Société<br>électrique<br>intercommunale<br>de la Côte | Nyon     | 0.797   | Critical | 0.500 | 0.324 | 0.993 | 0.629 | 0.981 | 0.794 | S          |       |
| Nyon Sub 205                                               | Nyon     | 0.795   | Critical | 0.500 | 0.324 | 0.993 | 0.629 | 0.981 | 0.794 | S          |       |

| SUBSTATION   | PROVINCE | R_FINAL | BAND     | C     | V     | I     | E     | S     | T     | RE<br>V4.2 | ALERT |
|--------------|----------|---------|----------|-------|-------|-------|-------|-------|-------|------------|-------|
| Eysins       | Nyon     | 0.795   | Critical | 0.500 | 0.324 | 0.993 | 0.629 | 0.981 | 0.794 | S          |       |
| Nyon Sub 260 | Nyon     | 0.794   | Critical | 0.500 | 0.324 | 0.993 | 0.629 | 0.981 | 0.794 | S          |       |
| Crans        | Nyon     | 0.793   | Critical | 0.500 | 0.324 | 0.993 | 0.629 | 0.981 | 0.794 | S          |       |
| Prelan       | Aigle    | 0.792   | Critical | 0.500 | 0.783 | 0.995 | 0.071 | 0.981 | 0.794 | S          |       |
| Collombey    | Aigle    | 0.791   | Critical | 0.500 | 0.783 | 0.995 | 0.071 | 0.981 | 0.794 | S          |       |
| Essert       | Aigle    | 0.790   | Critical | 0.500 | 0.783 | 0.995 | 0.071 | 0.981 | 0.794 | S          |       |

... 20 additional substations — [explore full corridor in Digital Twin →](#)

### D.3 Component Analysis

COMPONENT AVERAGES — VAUD VS FLEET

|                    |                       |
|--------------------|-----------------------|
| C — Continuity     | 0.500 vs 0.500 (0%)   |
| I — Infrastructure | 0.871 vs 0.653 (+33%) |
| S — Saturation     | 0.981 vs 0.559 (+75%) |
| V — Voltage        | 0.662 vs 0.606 (+9%)  |
| E — Economic       | 0.263 vs 0.265 (-1%)  |
| T — Transition     | 0.794 vs 0.648 (+23%) |

MODIFIER AVERAGES — VAUD VS FLEET

|                  |       |               |
|------------------|-------|---------------|
| R3 Consequence   | 0.912 | fleet 0.903 ↓ |
| R4 Graph Crit.   | 1.045 | fleet 1.043 ↑ |
| R6a Restoration  | 1.009 | fleet 1.013 → |
| R6b Seismic      | 1.043 | fleet 1.035 ↑ |
| R7 Digital Read. | 1.000 | fleet 1.000 → |

The dominant risk driver across the Vaud corridor is **T (Transition)**, averaging 0.794 against a fleet average of 0.648 — occupying 1589% of its weight ceiling (w = 0.05). The second contributor is **V (Voltage)** at 0.662 vs fleet 0.606 (662% of ceiling). Among modifiers, the R3 consequence multiplier averages 0.912 (fleet: 0.903), reflecting the socio-economic exposure of the corridor. The R6b seismic modifier averages 1.043, capturing the local seismic exposure — a dimension invisible to every competing framework.

### D.4 Province Breakdown

REGION RISK PROFILE — SORTED BY MEAN R

Longer bar = lower R = better resilience.

|         |                                        |
|---------|----------------------------------------|
| Nyon    | 5 subs · avg R = 0.795 · H:0 C:5 M:0   |
| Aigle   | 10 subs · avg R = 0.790 · H:0 C:10 M:0 |
| Morges  | 1 subs · avg R = 0.781 · H:0 C:1 M:0   |
| Moudon  | 1 subs · avg R = 0.778 · H:0 C:1 M:0   |
| Yverdon | 1 subs · avg R = 0.774 · H:0 C:1 M:0   |



The region regions–level breakdown reveals significant intra–regional variation. **Nyon** leads with a mean R of 0.795 across 5 substations, while **Renens** scores 0.657 — a spread of 0.138 within a single corridor. The SSI's substation–level granularity reveals that the Vaud is not uniformly stressed but contains distinct sub–corridors of concentrated risk — precisely the kind of spatial pattern that investment planning requires.

### D.5 Implications

**30 Vaud substations** score  $R \geq 0.650$ , placing them in the upper quartile of national risk. For NEPN / national digital plan / RRP investment prioritisation, this analysis identifies the Nyon sub–corridor as the highest–priority target — where DER deployment is accelerating against ageing infrastructure with above–average continuity deficits and significant socio–economic exposure. The SSI's silo–breaking approach reveals what no single–discipline framework can: that these substations matter not only because of their engineering condition, but because the communities they serve are disproportionately vulnerable to disruption. This is precisely the anticipatory grid planning capability that the SSI was built to provide.


SECTION E — RECURRING MODULE

## OECD Context Card

**How this works:** Each edition includes one OECD Context Card drawn from the §16 Peer Benchmarking framework. The card is selected to complement the month's deep–dive theme. This month: **SAIDI comparison** — because the Southern Coastal corridor analysis hinges on Switzerland's continuity performance relative to OECD peers. Future editions rotate through: VoLL comparison (Ed. 002), DER saturation vs Germany (003), CMIP6 climate hazard vs Nordic peers (004), etc. The underlying data updates annually with the CEER Benchmarking Report release.

### Unplanned SAIDI (min/customer/year) — Selected OECD Countries

Longer bar = lower SAIDI = better reliability. Values in min/customer/year.




Source: CEER 7th Benchmarking Report (2022); Bundesnetzagentur (2024); ARERA (2023). · See §16 Peer Benchmarking for full methodology and caveats. · Updated annually with CEER BR release. · OECD-wide expansion (USA, Japan, Canada, Australia) pending IEA/OECD reliability bulletin release.


**This month's key insight:** The Vaud corridor deep-dive shows **30 substations** (of 30) with C-component above 70% of its weight ceiling — indicating continuity-of-supply performance consistent with rural territory classification. The corridor's average C of 0.500 is **1.0× the fleet average** of 0.500. The SSI reveals what aggregate national statistics conceal: that the country's mid-tier European position is not a uniform condition but a statistical average of urban-quality performance and rural-tier performance — and the corridor concentrates the worst of the latter.

### Cantons Risk Ranking — All 26 Swiss Cantons

Where does this corridor sit within the national landscape? Regions sorted by mean R<sub>median</sub>, with band distribution and fleet comparison.

Longer bar = lower R = better resilience. Sorted worst → best.





The Vaud ranks **#1 of 26 region regions** by mean  $R_{\text{median}}$ , placing it among the upper tier of national risk. The three most stressed are Vaud, Basel-Stadt, Genève, while the three most resilient are Zug, Schwyz, Nidwalden. 8 of 26 score above the fleet average of 0.600. This ranking — possible only because the SSI scores every substation individually rather than relying on aggregate DSO or national statistics — reveals the true spatial distribution of grid stress. It is precisely this substation-level granularity that positions the SSI as a tool for investment prioritisation: not treating entire regions as monoliths, but identifying the specific corridors within each that demand attention.


## SECTION F — RECURRING MODULE

### SSI Enhanced Neural Network — Monthly Topic

**From grid intelligence to BESS valuation platform.** The SSI Index answers *"How healthy is this substation?"* The SSI Enhanced Neural Network (SSI-ENN) extends this into: *"What is a BESS worth at this substation — to the DNO and to the community?"* Each edition of this report explores one building block of the SSI-ENN's five-layer architecture, showing how the SSI Index data feeds directly into investment-grade grid analytics.

SSI-ENN value-articulation radar — 5-lens stakeholder taxonomy

The SSI-ENN's commercial-tier value articulation answers "what is a BESS worth at this substation — and to whom?" through five stakeholder lenses (architecture memo §5 Decision #12): **V<sub>Community</sub>** (welfare avoided outages, energy-poverty relief, employment) · **V<sub>Grid</sub>** (V\_DSO — avoided reinforcement, reliability, voltage, congestion, frequency, black-start, hosting capacity) · **V<sub>Owner</sub>** (NPV / IRR / payback per asset class) · **V<sub>Investor</sub>** (risk-adjusted equity return at the financing tier) · **V<sub>LP</sub>** (limited-partner cash-on-cash + DPI / TVPI portfolio metrics). The pentagon shape below is an editorial reference profile, not per-substation commercial data — per-substation evaluation requires the SSI-ENN engines (L2–21 SupplyChainDD · L4–05 Stakeholder Decomposition · L2–SYN Synergy). Foundation contact: [ssi\\_index@ikenga.eu](mailto:ssi_index@ikenga.eu).



Editorial reference shape —  $V_{Grid}$  dominates ( $V_{DSO}$  captures avoided reinforcement + reliability + voltage support + congestion relief + frequency + black-start + hosting capacity, the bulk of measurable BESS value at the substation locus per architecture memo §5).  $V_{Community}$  +  $V_{Owner}$  are co-secondary.  $V_{Investor}$  +  $V_{LP}$  reflect the financing-tier waterfall above  $V_{Owner}$  NPV. Per-substation commercial decomposition lives in the SSI-ENN — mail to [ssi\\_index@ikenga.eu](mailto:ssi_index@ikenga.eu) for analytics.

Layer 1 — Data

SSI v4.0 component taxonomy, normalisation, MC engine

Layer 2 — Valuation

DSO/TSO + Community value stacks, TCO, real options

Layer 3 — Neural Net

GBT+DNN ensemble, transfer learning, SHAP

Layer 4 — Coverage

Country prioritisation, DCI, registry, calibration

Layer 5 — Platform

Products, API, revenue model, unit economics

LAYER 3 §0.5.5 · July 2026

Uncertainty Quantification

Investment-grade predictions require calibrated confidence intervals, not just point estimates

A point estimate without uncertainty bounds is unusable for investment-grade analysis. The SSI-ENN produces calibrated P10/P50/P90 prediction intervals using two complementary approaches: quantile regression (pinball loss) and conformal prediction (distribution-free guaranteed coverage). The SSI's own Monte Carlo confidence intervals (CI\_width, P5/P95) serve as the ground truth for calibration. This calibration is verified per country, per voltage class, and per risk band.

KEY CONCEPTS

- Quantile regression (pinball loss) + conformal prediction
- Calibrated against SSI Monte Carlo ground truth
- Per-country, per-voltage, per-band calibration verification
- Investment-grade: P10/P50/P90 for all outputs

LIVE SSI DATA CONNECTION

The training set comprises 947 substations with complete feature vectors. Average CI\_width of 0.136 across the fleet provides the uncertainty ground truth that the neural network's quantile regression heads must calibrate against. The fleet's risk distribution — 0 Low, 164 Medium, 704 High, 79 Critical — ensures balanced training across all risk bands.

**Coming next month:** **LAYER 2** Total Cost of Ownership Model — *Stochastic cost modelling — because BESS economics are not deterministic*

SECTION F.5 — V4.2 ANTI-MALADAPTATION GOVERNANCE GATE

Radar 2 — W1–W10 Substation Community Value

**Wall 1 — Public W1–W10 framework.** The 10-axis Radar 2 expresses per-substation community-value baseline pre-intervention: *W1 Reliability · W2 Carbon · W3 Local Economic · W4 Climate Resilience · W5 Digital Inclusion · W6 Sovereignty · W7 Local Value Retention · W8 Communications · W9 Supply Security · W10 Compute Multiplier*. The discipline floor that the anti-maladaptation governance gate protects: *"no W axis worse off after intervention."*

5/1/1/3 4-tier audit-state classification (mesh resolution per Convention #6 §5.6)

**Published (5)** — solid fill  
W1 · W2 · W3 · W4 · W8  
*Peer-reviewed methodology operational at fleet scale.*

**Published-baseline (1) ▲** — solid fill + chevron corner marker  
W9 — Supply Security  
*Peer-reviewed academic basis (Albert/Holme topology-only baseline) with acknowledged scope limit (Buldyrev/IEEE 493 — N-1 contingency dynamics not captured at baseline).*

**Baseline-only (1)** — striped fill  
W5 — Digital Inclusion  
*Foundation methodology under development; baseline value defensible at v4.2.*

**Commercial (3)** — dashed-faded  
W6 · W7 · W10  
*Commercial deliverables — please contact the Foundation.*


Per Convention #6 §5.6.7 academic-defensibility: the 4-tier classification aligns with IPCC AR6 + JRC COIN + Reckien (2021) continuum literature. The Published-baseline tier (W9) is the principled mesh resolution that honors both peer-review status + acknowledged scope limit without forcing a false binary.

## v4.2 methodology disclosure — per-country normalisation

Across Switzerland, the substation fleet's component scores (C / V / I / E / S / T) and the Re composite have been normalised to [0, 1] via the canonical **P5/P95 percentile** method, using *per-country empirical bounds*. This is the same procedure Italy's v4.0.2 deployment applied at the scoring stage (SSI\_v4\_0 Italy/.../scoring-it/normalise.py); for v4.2 we apply it country-by-country so each fleet's within-country ranking is interpretable on its own terms. Convention #56 (visibly-honest) is preserved — no values are invented, the same canonical procedure is applied uniformly. Italy's pilot fleet keeps its native spread (0.17 – 0.64) because its empirical modifier producers (d10–d15) are already wired; per-country empirical modifier producers for the other 38 countries are queued for v4.5 and will refine the absolute risk ranking. Within-fleet relative comparisons (low-exposure vs high-exposure exemplars below) remain accurate by construction.

## Radar 2 visualization — anti-maladaptation governance gate

Two worked examples overlaid: **Unterwerk Samstagern** (low-exposure reference, Re\_norm 0.000) and **Poste de Chippis** (high-exposure reference, Re\_norm 1.000). Axis labels are colour-coded per the 5/1/1/3 mesh resolution; the ▲ chevron marks W9 as Published-baseline. Hover any axis label for the methodology tooltip.



*Altgass polygon (sage): the low-exposure reference for this country — compact footprint reflects the fleet floor on the W-axis baselines. Unterwerk Spina polygon (terracotta): the high-exposure reference — larger footprint where this country's fleet's W-axis values reach the upper percentile. Commercial-tier axes (W6 data sovereignty, W7 local value retention, W10 compute multiplier) display at zero per Convention #6 §5.6 mesh design — no public-data computation. W2 carbon uses EU-average MEF fallback (0.36) per v4.2 calibration.*

## W1–W10 axis enumeration with audit-state classification

5/1/1/3 4-TIER · V4.2 MESH RESOLUTION · LIVE VALUES VIA  
COMPUTE\_W\_BASELINES.PY

| AXIS | NAME                  | AUDIT STATE          | METHODOLOGY BASIS                                                                                                                                                       |
|------|-----------------------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| W1   | Reliability           | Published            | $C \times E2\_local \times population (SAIDI + + -POV)$                                                                                                                 |
| W2   | Carbon                | Published            | $T1 \times zonal\ MEF \times (V \cdot deg / 100) (+ EEA)$                                                                                                               |
| W3   | Local Economic        | Published            | $norm(R10\_just) - EU-SILC + OIPE\ energy-poverty$                                                                                                                      |
| W4   | Climate Resilience    | Published            | $(R6d - 1) + (R6e - 1) + (R6c - 1) + \frac{1}{2}(R9 - 1) - v4.2\ resilience\ modifier\ family$                                                                          |
| W5   | Digital Inclusion     | Baseline-only        | $norm(R8\_adapt) - bulk\ SM + + DESI$                                                                                                                                   |
| W6   | Sovereignty           | Commercial           | Foundation contact ( <a href="mailto:ssi_index@ikenga.eu">ssi_index@ikenga.eu</a> )                                                                                     |
| W7   | Local Value Retention | Commercial           | Foundation contact ( <a href="mailto:ssi_index@ikenga.eu">ssi_index@ikenga.eu</a> )                                                                                     |
| W8   | Communications        | Published            | $C \times p\_crit\_10yr \times population (Markov\ 10-yr\ critical\ probability)$                                                                                       |
| W9 ▲ | Supply Security       | Published-baseline ▲ | $0.60 \times BC\_pct + 0.30 \times bridge + 0.10 \times (1 - deg / 20) - OSM\ power-graph\ betweenness\ centrality + bridge\ identification + degree-based\ redundancy$ |
| W10  | Compute Multiplier    | Commercial           | Foundation contact ( <a href="mailto:ssi_index@ikenga.eu">ssi_index@ikenga.eu</a> )                                                                                     |

### ▲ W9 Published-baseline — mandatory transparency tooltip

W9 — Supply Security (Published-baseline). Public-tier methodology: betweenness centrality + bridge identification + degree-based redundancy, computed deterministically from OpenStreetMap power-graph data. Peer-reviewed academic basis: Albert et al. (2000) *Nature*; Holme et al. (2002); broad power-grid centrality literature. Acknowledged scope limit (per Buldyrev et al. (2010) *Nature* + IEEE 493): topology-only baseline does not capture N-1 contingency dynamics or interdependent-network cascades. Richer methodology — N-1 contingency simulation + flexibility-services valuation — lives in SSI-ENN L2-22 / L2-23 commercial deliverables. Mail to [ssi\\_index@ikenga.eu](mailto:ssi_index@ikenga.eu) for extended analysis.

**Worked examples.** The W1–W10 per-substation baseline values for two anchor cases — Altgass (low-exposure reference) and Unterwerk Spina (high-exposure reference) — are computed live by `_audit-snapshot/scripts/d3_radar2_per_country.py` against the country's `ssi-data.json`. Per Convention #6 §2.3.6 Path B refactor (11 Jun 2026), this country's exemplars are now algorithmically selected (min/max `Re_norm`) rather than named picks. See the FC v2 reference for W-axis methodology + commercial-tier rationale.

**Anti-maladaptation discipline.** The 10-axis Radar 2 baseline is the per-substation floor that any post-intervention scenario must protect. No W axis may degrade after a BESS deployment, line upgrade, or operational change. The discipline is enforced per axis (not in aggregate), and per substation (not in fleet average). This is the v4.2 governance gate that ensures grid-modernisation projects deliver net community value without hidden trade-offs.

## SECTION G

# Looking Ahead

### NEXT MONTH — EDITION 03

#### Capital Metropolitan

Deep-dive into Region 02's grid risk profile — substation map, component analysis, region regions breakdown. European Context Card: Capital-intensive tier + flood overlay.

### NEXT DATA REFRESH

#### Q4 2026 — 0 Quarterly Sources

**none** are due for refresh in Q4. Impact: DER registry (T1), business fabric indicators (E2), macro-economic data. Highest-impact annual source pending: **ElCom (Federal Electricity Commission)** (8 variables → C1–C4 (SAIDI/SAIFI), R6a restoration, quality regulation).

### FLEET SPOTLIGHT

#### 0 Bridge Substations — Single Points of Failure

**0 substations** are topological bridges — their failure disconnects part of the network. Of these, **0** are classified High or Critical. These are the fleet's single points of failure: high graph centrality (R4) combined with elevated risk makes them priority candidates for both grid reinforcement and BESS deployment.

Edition 03 will be published on the second Thursday of August 2026. Deep-dive region: **Region 02**. To ensure you receive it, confirm your subscription segment (General / Institutional / Academic) by email to [ssi\\_index@ikenga.eu](mailto:ssi_index@ikenga.eu).

**Feedback welcome.** The SSI Index is designed to evolve through stakeholder dialogue. If you represent an Swiss utility, , municipal energy company, or academic institution and would like to contribute data or methodology feedback, please contact us at [ssi\\_index@ikenga.eu](mailto:ssi_index@ikenga.eu). The SSI's credibility depends on open scrutiny.

## SSI Monthly Intelligence Report — Edition 005

Published 9 July 2026 · SSI Index **v4.2** (refreshed June 2026) · 947 substations · 625 grid lines · 6 components + **Re composite** (Radar 17th axis, bounds [0.920, 1.787]) · 20 metrics · 11 modifiers (5 baseline + 6 v4.2 resilience family)  
10,000-iteration Gaussian Copula Monte Carlo · Sobol global sensitivity analysis (196,608 evals/substation) · CMIP6 SSP2–4.5 · W1–W10 anti-maladaptation governance gate (5/1/1/3 4-tier mesh resolution per Convention #6 §5.6)

## Foundation contact

The SSI Index is a non-profit foundation project, please mail to [ssi\\_index@ikenga.eu](mailto:ssi_index@ikenga.eu) for more details.

© 2026 Altinium Invest · Corso Vittorio Emanuele 110/5, 80121 Napoli · P.IVA 10656441218

USCO Registration pending · SIAE Deposito Opere Inedite · Protected under L. 633/1941, Berne Convention, Copyright Act 1976

[View in browser](#)